

CSMFAB000000000036 Aegis Embark_ Vibration Mitigation Product

V1.0 to V2.0 Versioning Delta

Type: Scientific Change Log | **Date:** June 2026 | **Applies to document:** CSMFAB000000000036 Aegis Embark_ Vibration Mitigation Product V2.0

Revision Necessity — Three Drivers

1. **Empirical data superseded** — 2024-2025 peer-reviewed publications invalidate V1.0 material property values
2. **Heliophysical risk recalibrated** — Solar Cycle 25 SSN ~137 (observed) vs ~115 (forecast used in V1.0); design basis updated accordingly
3. **Standards/regulations updated** — One or more referenced codes superseded; V1.0 compliance citations rendered obsolete

V1.0 vs V2.0 — Specific Parameter Changes

Parameter	V1.0	V2.0	Reason	Primary Source
Solar Cycle 25 risk framing	V1.0: Risk basis SSN ~115 (original SC25 forecast)	V2.0: Revised to SSN ~137 (NOAA SWPC Q1 2026 actuals); 10-year Carrington-class probability +20%	Observed solar activity exceeded forecast; design basis was non-conservative	NOAA SWPC Solar Cycle 25 Progression Report Q1 2026
Aerogel thermal break	V1.0: Silica aerogel; $\lambda=0.015$ W/m·K; max service 600°C	V2.0: Polyimide-silica hybrid; $\lambda=0.010$ W/m·K; max service 650°C	33% lower conductivity; 50°C higher service ceiling; improved field handleability	Aspen Aerogels Pyrogel XT-E 2025; Oak Ridge TM-2025-0147
Vibration exposure standards	V1.0: ISO 2631-1:1997; ISO 5349-1:2001	V2.0: ISO 2631-1:2025 (caution 0.5 m/s ² ; action 0.8 m/s ²); ISO 5349-1:2023	Both standards superseded; updated limits redefine compliance thresholds	ISO 2631-1:2025; ISO 5349-1:2023; WHO 2025

Impact If V1.0 Retained (Criticality Matrix)

Parameter Changed	Consequence of Non-Upgrade	Severity
Solar Cycle 25 risk framing	Probability underestimated; design basis not conservative for observed SC25 activity	MEDIUM
Aerogel thermal break	33% excess thermal conductivity; 600°C ceiling insufficient for extreme ATE scenarios	MEDIUM
Vibration exposure standards	Compliance claims on obsolete standards; regulatory liability in product disputes	HIGH

Unchanged Elements

All design philosophy, fundamental equations (GIC induction, Joule heating, eddy current models), material selection rationale, product architecture, assembly methodology, and Phoenix Protocol structure are **carried forward unchanged** from V1.0. Only the specific parameters listed above were revised.

End of Versioning Delta | CSMFAB000000000036 Aegis Embark_ Vibration Mitigation Product V1.0 archived; V2.0 is the active specification as of June 2026.