

CSMFAB000000000103 V2.0

Aegis-Shielded ISO Tsunami Survival Pod: Architectural and Material Synthesis

Version 2.0 — Revised & Expanded | June 2026

Δ Change Log V1.0 □ V2.0

- Corten steel □ BFRP: Elium® thermoplastic matrix, 95% fiber recovery at EOL (added)
 - Aerogel insulation: polyimide-silica hybrid $\lambda=0.010$ W/m·K to 650°C (upgraded from silica, 600°C)
 - EMI shielding: $\text{Ti}_3\text{C}_2\text{T}_x$ MXene 92 dB SE (upgraded from carbon-doped polymer V1.0)
 - Flash Sintering for ZrO_2 corner fittings: 1200°C (–250°C vs V1.0 conventional sintering)
 - ACI 440.11-25 seismic provisions added for stacked pod tower configurations
 - Solar Cycle 25 SSN ~137: GIC load increased 20% in tsunami + Carrington concurrent scenario
 - LoRa mesh: 256-node pod network for post-event coordination without GPS/cellular
 - Open-source license: CERN OHL-S v2 adopted (stronger reciprocity than V1.0 Creative Commons)
-

1. Design Mandate: The Dual-Threat Pod

The ISO Tsunami Survival Pod addresses the compound disaster scenario: simultaneous megathrust earthquake (CSZ/Cascadia, M9.0+) generating a 15 m tsunami AND a Carrington-class GIC event. Standard steel shipping containers fail both threats:

1. **Structural failure:** Corten steel corrodes rapidly; conductive hull creates GIC heating
2. **GIC vulnerability:** Steel container with copper electrical system □ Joule heating □ fire
3. **Buoyancy:** 20-foot steel TEU weighs 2,300 kg empty — marginal positive buoyancy with occupants

V2.0 Pod positive buoyancy calculation: - Pod mass (BFRP structure): 680 kg (vs 2,300 kg Corten steel) - Aerogel buoyancy chambers: $4 \times 0.5 \text{ m}^3 = 2 \text{ m}^3$ trapped air volume - Displaced water: 2,300 kg (TEU volume submerged) □ buoyancy force: 22.6 kN - Pod + 8 occupants ($8 \times 75 \text{ kg} = 600 \text{ kg}$): total = 1,280 kg □ net buoyancy: +1,020 kg

Pod floats with 8 adults and 700 kg of emergency supplies.

2. Structural Architecture

2.1 BFRP Primary Structure (Elium® Matrix V2.0)

Replacing Corten steel with basalt fiber + Elium® thermoplastic pultrusion:

Property	Corten Steel (V1.0)	BFRP/Elum® (V2.0)
Tensile strength	480 MPa	1,100 MPa
Density	7.85 g/cm ³	1.85 g/cm ³
Specific strength	61 kN·m/kg	595 kN·m/kg
Electrical ρ	$1.3 \times 10^{-7} \Omega \cdot m$	$>10^{10} \Omega \cdot m$
Corrosion	Oxidizes in seawater	Inert
EOL recovery	Shred/downscale	95% fiber recovery
Mass (20-ft TEU equiv.)	2,300 kg	680 kg

The 1,620 kg saved enables: 700 kg emergency supplies + buoyancy reserve.

2.2 ZrO₂ Corner Fittings (Flash Sintered V2.0)

ISO 1161-standard corner fittings machined from 3Y-TZP Zirconia: - Flash sintering at 1200°C, 5 min (V2.0, vs 1500°C conventional) - Tensile strength: >1,300 MPa — exceeds ISO 1161 minimum 1,000 MPa - Zero conductivity □ piles cannot become GIC antennas when pods are stacked - Machinable: ISO thread form cut with ceramic-tipped CNC tooling

3. Acoustic and Vibration Isolation (Biodynamic Interior)

3.1 Locally Resonant Acoustic Metamaterial (LRAM) Floor

Tsunami impact delivers impulsive loads at 0.5–15 Hz and broadband structural noise 50–500 Hz. The pod floor uses LRAM panels: - Tungsten carbide sphere resonators (d=8.5 mm) in magnetite-doped PDMS - Primary attenuation: □45 dB at 3–15 Hz (impact isolation) - Secondary: □30 dB at 100–500 Hz (structural noise) - Total floor thickness: 95 mm

3.2 Cervical/Spinal Protection Seating

Occupant seats use Aegis Embark Mag-Float rail + Bio-Sync cushion principles: - 4-8 Hz spinal resonance isolation: □15 dB - MRE (Lord MRF-140CG) adjustable stiffness: crash hardening in <0.5 ms

4. EMI/GIC Shield Architecture

MXene (Ti₃C₂T_x) exterior spray, 50 μ m: - SE = 92 dB at 1 GHz - Discontinuous tile pattern: prevents DC GIC macro-loop formation - YInMn Blue ceramic enamel over MXene: SRI = 115, NIR rejection 85% — prevents solar thermal loading during tsunami waiting period (occupants may be inside pod in direct sun for 6–24 hrs)

Faraday interior for electronics: - All pod electronics (emergency beacon, water purifier control, LED lighting) in nested MXene-shielded enclosure - PEEK CF40 structural mounts — no metallic GIC path to hull

5. LoRa Mesh Pod Network

- Each pod has an embedded LoRa module (915 MHz, 2W ERP)
 - Mesh range: 5 km per hop — pods floating 1–3 km apart connect
 - Protocol: self-organizing mesh, GPS-free position using TDOA ranging
 - Use case: rescue services locate and extract pod cluster via mesh beacon without cellular/GPS
-

6. Stacking (Container City) Provisions — V2.0 ACI 440.11-25

V2.0 adds seismic analysis for multi-story pod stacking (up to 8 pods high): - BFRP column cores provide 4:1 height-to-width stability at 8 floors - ACI 440.11-25 Type S seismic provisions applied to BFRP connection design - ZrO₂ corner fitting tensile at 8-pod stack: max 320 kN □ safety factor 4.1 vs 1,300 MPa ZrO₂ strength

End CSMFAB000000000103 V2.0 | Carrington Storm Motors