

CSMHuman00000000034

Comprehensive Analysis of Electromagnetic Field Interactions with the Human Body: Frequency Dependence, Dosimetry, and Biophysical Mechanisms

1. Introduction: The Biophysical Continuum of Electromagnetic Interaction

The interaction between electromagnetic fields (EMF) and the human body represents one of the most complex frontiers in applied biophysics and engineering. It is a domain where the rigid, deterministic laws of Maxwellian electrodynamics collide with the heterogeneous, dispersive, and adaptive nature of biological tissue. As modern civilization becomes increasingly enveloped in a spectrum of artificial frequencies—ranging from the 50/60 Hz hum of power grids to the sub-terahertz pulses of 6G communication systems—the necessity for a granular, exhaustive understanding of how these fields couple with human physiology has never been more acute. This report serves as a comprehensive technical synthesis of this interaction spectrum, grounded in the foundational standards of the Institute of Electrical and Electronics Engineers (IEEE), specifically the lineage of IEEE Standard C95.1 (referenced as IEEE 827291), and expanded through contemporary research into millimeter-wave dosimetry, dielectric tissue characterization, and the contentious debate surrounding non-thermal biophysical mechanisms.¹

The central thesis of bio-electromagnetics is that the human body acts as a frequency-dependent spectral filter. The mechanism of interaction is strictly dictated by the wavelength of the incident field relative to the dimensions of the biological target—be it the whole body, a specific organ, a single cell, or a protein voltage sensor. At Extremely Low Frequencies (ELF), the body behaves as a conductive volume that perturbs the external electric field, resulting in induced surface charges and internal currents. As the frequency rises into the Radiofrequency (RF) and Microwave bands, the body transitions into a lossy dielectric resonator, capable of absorbing significant energy through dipolar rotation of water molecules, leading to volumetric heating. Finally, as we breach the frontier of Millimeter Waves (mmWave) and Terahertz (THz) frequencies, the interaction becomes quasi-optical, confined almost entirely to the cutaneous layers, where novel micro-structures such as sweat ducts

may act as helical antennas.⁴

This report navigates this continuum with rigorous technical depth. It synthesizes decades of dielectric measurement data, primarily the canonical work of Gabriel et al., with modern computational dosimetry using high-fidelity anatomical phantoms from the "Virtual Family." It critically evaluates the regulatory transition from Specific Absorption Rate (SAR) to Absorbed Power Density (APD) at 6 GHz, a pivot point that redefines safety compliance for the 5G era. Furthermore, it provides an impartial, physics-based analysis of the controversy between established thermal effects and hypothesized non-thermal mechanisms, such as Voltage-Gated Calcium Channel (VGCC) activation and the Radical Pair Mechanism, weighing the empirical biological data against the thermodynamic constraints of the Langevin limit.⁷

2. Fundamental Electrodynamics of Biological Media

To understand how electromagnetic fields affect the human body, one must first characterize the body as an electromagnetic medium. Biological tissues are not simple conductors or perfect dielectrics; they are complex, hierarchical composites of cells, interstitial fluids, and macromolecules, each contributing to the material's macroscopic response to an applied field. This response is encapsulated in the complex permittivity (ϵ^*), a parameter that is highly dispersive, varying significantly with frequency.

2.1 The Complex Permittivity and Conductivity Relation

The interaction of time-harmonic electromagnetic fields with tissue is governed by the complex permittivity equation:

$$\epsilon^*(\omega) = \epsilon'(\omega) - j\epsilon''(\omega) = \epsilon'(\omega) - j\frac{\sigma_{\text{total}}(\omega)}{\omega\epsilon_0}$$

In this formulation, the real part, $\epsilon'(\omega)$, represents the relative permittivity or dielectric constant, which measures the material's ability to store electrical potential energy through polarization. The imaginary part, $\epsilon''(\omega)$, represents the dielectric loss factor, quantifying the dissipation of energy. The term $\sigma_{\text{total}}(\omega)$ is the total effective conductivity, measured in Siemens per meter (S/m), which sums the contributions from static ionic conductivity (σ_{static}) and frequency-dependent dielectric damping.

For biological tissues, conductivity is the primary driver of energy absorption (heating), defined by the specific absorption rate (SAR). The relationship between conductivity and energy deposition is linear: as conductivity rises, the ability of the tissue to turn electromagnetic energy into heat increases, provided the field can penetrate the tissue. However, this creates a paradox: high conductivity also reduces skin depth, preventing deep

penetration at higher frequencies.¹⁰

2.2 Mechanisms of Dielectric Dispersion

The frequency dependence of tissue properties is not smooth; it is characterized by distinct "dispersion regions" where specific polarization mechanisms relax. Understanding these mechanisms is crucial for interpreting the data provided by Gabriel et al. and for modeling field interactions accurately.¹⁰

2.2.1 Alpha (α) Dispersion (Hz to kHz)

At very low frequencies, tissues exhibit enormous permittivity values, sometimes exceeding 10^6 . This phenomenon, known as α -dispersion, is primarily due to the diffusion of ions in the electrical double layer surrounding charged cellular membranes. The counter-ions in the intracellular and extracellular fluid move tangentially along the cell surface, creating massive induced dipoles. This region is critical for understanding bio-impedance and the coupling of power-line frequencies (50/60 Hz) to the body.¹⁰

2.2.2 Beta (β) Dispersion (kHz to MHz)

As the frequency increases to the radiofrequency range, the large ionic clouds can no longer follow the field oscillations. The dominant mechanism shifts to the polarization of cellular membranes themselves. This is the Maxwell-Wagner interfacial polarization effect, occurring at the boundaries between the resistive membrane and the conductive cytoplasm. Additionally, the rotation of large protein molecules contributes to this dispersion. The fading of β -dispersion marks the transition where cell membranes become capacitive shorts, allowing current to flow through the intracellular space rather than just around the cells.¹⁰

2.2.3 Gamma (γ) Dispersion (GHz Region)

In the microwave and mmWave spectrum—covering cellular telephony, Wi-Fi, and 5G—the dominant mechanism is the reorientation of free water molecules. Water is a polar molecule; under an alternating field, it rotates to align with the field vector. Friction from this rotation dissipates energy as heat. Since soft tissues (muscle, brain, organs) are roughly 70-80% water, they exhibit a strong γ -dispersion centered around 20-25 GHz (at body temperature). This mechanism is the physical basis for microwave heating and is the primary determinant of penetration depth in the 5G era.¹⁰

3. Dielectric Characterization: The Gabriel Database and Beyond

The empirical bedrock for all modern dosimetry is the comprehensive measurement of tissue properties. The most cited and extensive dataset comes from the work of C. Gabriel, S.

Gabriel, and E. Corthout (1996), who utilized automatic swept-frequency network analyzers and impedance analyzers to map the dielectric properties of over 30 tissue types from 10 Hz to 20 GHz.

3.1 Measurement Methodologies

Gabriel's team employed open-ended coaxial probe techniques for higher frequencies and impedance analysis for lower frequencies. The open-ended coaxial probe is particularly effective for in vivo and ex vivo biological measurements because it is non-destructive. The probe is pressed against the tissue, and the complex reflection coefficient (Γ) is measured. From Γ , the complex permittivity of the material terminating the probe can be calculated using a rational function model or a capacitive model. This method was crucial for establishing the baseline values used in standard safety compliance testing today.¹⁴

3.2 Tissue Classifications and Properties

The data reveals a stark bifurcation in tissue properties based on water content, a distinction that is fundamental to dosimetric modeling.

High-Water-Content Tissues:

Tissues such as muscle, brain (grey and white matter), heart, kidney, and liver exhibit high permittivity and conductivity. For example, at 900 MHz (typical mobile phone frequency), the relative permittivity of muscle is approximately 55.0, with a conductivity of roughly 0.95 S/m. These tissues are efficient absorbers of RF energy.

Low-Water-Content Tissues:

Tissues such as fat, bone (cortical and cancellous), and low-hydration skin layers (stratum corneum) act as low-loss dielectrics. Fat, at 900 MHz, has a permittivity of only ~5.5 and a conductivity of ~0.05 S/m. This contrast creates significant impedance mismatches at tissue interfaces (e.g., fat-muscle boundaries), leading to internal wave reflections and standing wave patterns that can create localized heating hotspots ("hot spots") inside the body.¹⁶

Table 1: Dielectric Properties of Key Human Tissues Across the Spectrum

Data synthesized from Gabriel et al. (1996) and extended databases for 5G/6G applications.¹³

Tissue Type	Frequency	Relative Permittivity (ϵ')	Conductivity (σ)	Penetration Depth (approx.)
Muscle	100 Hz	$> 10^6$ (Alpha dispersion)	~0.2	N/A (Quasi-static)
	900 MHz	55.0	0.95	~30 mm

	2.45 GHz	52.7	1.74	~22 mm
	28 GHz	30.0	35.0	~1 mm
Fat	900 MHz	5.5	0.05	> 150 mm
	2.45 GHz	5.3	0.10	~80 mm
	28 GHz	4.5	1.5	~5-10 mm
Skin (Dry)	900 MHz	41.0	0.87	~38 mm
	28 GHz	18-20	25.0	~1-2 mm
	60 GHz	7-10	40.0	< 0.5 mm
Cortical Bone	2.45 GHz	11.4	0.39	~40 mm
Brain (Grey)	900 MHz	50.0	1.0	~30 mm

3.3 Extending the Database: The 100 GHz Frontier

While Gabriel's data stops at 20 GHz, the advent of 5G (Frequency Range 2) and 6G necessitates data up to 100 GHz and beyond. Recent research by the IT'IS Foundation and others has extended these models using Cole-Cole extrapolations. A critical finding in the mmWave range is the behavior of the skin. As frequency increases, the "bound water" (water molecules hydrogen-bonded to proteins) plays a distinct role compared to free water, affecting the relaxation times. At 60 GHz, the penetration depth in skin drops to less than 0.5 mm, meaning the electromagnetic interaction is confined solely to the epidermis and dermis, shielding internal organs entirely but placing the cornea and skin at risk of thermal injury.¹⁸

4. Low-Frequency Interactions: Coupling and Induction (0 Hz – 100 kHz)

In the low-frequency regime, encompassing power lines (50/60 Hz) and electric vehicle drivetrains, the wavelength of the field ($\lambda \approx 5000$ km at 60 Hz) is vastly larger than the human body. Consequently, the body does not behave as an antenna; resonance is

impossible. Instead, the interaction is quasi-static, governed by induction.

4.1 Electric Field Coupling

The human body is a relatively good conductor compared to air. When placed in a low-frequency electric field, the external field lines terminate on the body surface, inducing a surface charge density. The internal electric field (E_{in}) is significantly attenuated compared to the external field (E_{ext}) by a factor of roughly 10^{-6} to 10^{-7} .

$$E_{\text{in}} \approx E_{\text{ext}} \frac{\omega \epsilon_0}{\sigma}$$

Despite this attenuation, the surface charge oscillates with the field, driving currents through the body. If a person touches a grounded object while in a strong E-field, these charges discharge to the ground, causing "micro-shocks" or "spark discharges." IEEE C95.1 standards set limits specifically to prevent these startle reactions, which, while not lethal, can lead to secondary accidents.²¹

4.2 Magnetic Field Coupling and Eddy Currents

Unlike the electric field, the low-frequency magnetic field (H) penetrates the human body with virtually no attenuation, as biological tissue permeability (μ_r) is approximately 1 (non-magnetic). According to Faraday's Law of Induction, a time-varying magnetic field induces circulating electric fields (eddy currents) within the tissue loops.

$$\oint \mathbf{E} \cdot d\mathbf{l} = -\frac{d\Phi_B}{dt}$$

The magnitude of the induced current density (J) is proportional to the loop radius (r), conductivity (σ), and frequency (f):

$$J = \pi r \sigma f B$$

This relationship indicates that larger current loops (e.g., the periphery of the torso) experience higher induced currents.

4.3 Biological Effects: Electrostimulation

The primary hazard at these frequencies is the stimulation of excitable tissues—nerves and muscles. If the induced electric field in the tissue exceeds the depolarization threshold of the nerve membrane, it can trigger action potentials.

- **Peripheral Nerve Stimulation (PNS):** Can cause tingling sensations or involuntary muscle contractions.
- **Magnetophosphenes:** In the retina, induced currents can stimulate visual receptors,

causing the perception of flickering lights even in darkness. This occurs at relatively low flux densities (around 10-20 mT) and serves as the biological basis for the "basic restrictions" in safety guidelines for the ELF range.²

5. The Resonance Region: Radiofrequency Dosimetry (100 kHz – 6 GHz)

As frequencies rise above 100 kHz and enter the MHz/GHz range, the physics of interaction shifts from induction to dielectric loss and resonance. This is the domain of FM radio, TV, cellular networks (1G to 4G), and Wi-Fi.

5.1 Whole-Body Resonance

The human body acts as a lossy dipole antenna. When the wavelength of the incident field approximates the height of the individual, resonant absorption occurs.

- **Grounded Resonance:** For a standard adult male (1.75 m) standing on a ground plane, the body functions as a quarter-wave monopole. Resonance occurs at approximately **30 MHz to 40 MHz**.
- **Free-Space Resonance:** Isolated from the ground, the body acts as a half-wave dipole, with resonance shifting to **70 MHz to 80 MHz**.
- **Child Resonance:** Because children are shorter, their resonant frequency is higher, typically falling in the **100 MHz to 150 MHz** range (the FM broadcast band).

At resonance, the absorption of RF energy is maximized. The Whole-Body Averaged SAR (WBA-SAR) can increase by a factor of 10 compared to off-resonance frequencies for the same incident field strength. This biophysical reality is the reason why exposure limits (MPEs) are strictest in the 30-300 MHz band—to account for this efficient coupling.²³

5.2 Specific Absorption Rate (SAR)

In this frequency regime, the primary established hazard is thermal: the deposition of energy faster than the body's thermoregulatory system can dissipate it. The metric for this is the Specific Absorption Rate (SAR), defined as:

$$SAR = \frac{\sigma |\mathbf{E}_{rms}|^2}{\rho} \quad$$

SAR is a mass-normalized power metric. Safety standards typically limit WBA-SAR to 0.08 W/kg for the general public and 0.4 W/kg for occupational exposure. These limits incorporate a safety factor of 10 to 50 relative to the threshold of 4 W/kg, which is the level observed to cause behavioral disruption in laboratory animals (a proxy for thermal stress).²

5.3 Computational Phantoms and FDTD

Calculating SAR inside a human body requires solving Maxwell's equations in a heterogeneous, complex geometry. This led to the evolution of "Computational Phantoms."

1. **Stylized (MIRD) Phantoms:** Early models used simple geometric shapes (cylinders for arms, spheres for heads). These were mathematically convenient but ignored anatomical detail.²⁵
2. **Voxel Phantoms:** In the 1980s and 90s, MRI and CT scans of cadavers (e.g., the "Visible Human" project) were segmented into millimeters-sized cubes (voxels). Each voxel is assigned dielectric properties (muscle, fat, bone) based on the Gabriel database. The "Norman" and "Naomi" phantoms are classic examples.
3. **The Virtual Family (IT'IS Foundation):** The current state-of-the-art involves deformable CAD-based models (boundary representation). Models like "Duke" (34-year-old male), "Ella" (26-year-old female), and "Billie" (11-year-old female) allow researchers to simulate different postures and body masses.

The **Finite-Difference Time-Domain (FDTD)** method is the standard algorithm for these simulations. It discretizes space and time, iteratively updating the E and H fields. However, FDTD faces a "curse of dimensionality" at higher frequencies: as wavelength shrinks, the voxel size must decrease to maintain accuracy ($\text{voxel} < \lambda/10$). Modeling a human at 900 MHz is manageable; modeling one at 60 GHz requires billions of voxels, necessitating hybrid ray-tracing/FDTD approaches.²³

6. The Millimeter-Wave Frontier: 6 GHz to Terahertz (5G and 6G)

The deployment of 5G New Radio (Frequency Range 2, > 24 GHz) and the research into 6G (Sub-THz) mark a fundamental discontinuity in bio-electromagnetics. At these frequencies, the body is no longer a transparent volume; it is an opaque surface.

6.1 The Skin Depth Limit and Dosimetric Shift

The penetration depth (δ) of electromagnetic waves is inversely proportional to frequency.

- At 2.4 GHz, $\delta \approx 20$ mm (penetrating into muscle/brain).
- At 60 GHz, $\delta \approx 0.5$ mm (stopping in the dermis).
- At 300 GHz (THz range), $\delta \approx 0.1$ mm (stopping in the epidermis/stratum corneum).

Because the energy is deposited in such a thin layer, mass-averaged SAR (which averages over 1g or 10g of tissue) becomes physically meaningless. A 10g cube of tissue would be

mostly "dark" (unexposed) with a thin sliver of intense heating at the surface, artificially diluting the calculated risk. Consequently, **IEEE C95.1-2019** and **ICNIRP 2020** transitioned the exposure metric above 6 GHz from SAR to **Absorbed Power Density (APD)** or **Epithelial Power Density**, measured in W/m^2 . This metric aligns with the physics of surface heating and is consistent with laser safety standards.²⁸

6.2 The Sweat Duct as a Helical Antenna

One of the most profound and specific insights in THz dosimetry is the behavior of human sweat ducts. The eccrine sweat duct is a coiled tube that traverses the epidermis.

- **Geometric Coincidence:** The dimensions of the duct (helical diameter $\sim 10\text{--}50\ \mu\text{m}$, pitch $\sim 100\ \mu\text{m}$) are remarkably close to the wavelength of sub-THz radiation.
- **Conductive filling:** When a person perspires, the duct fills with highly conductive saline sweat.
- **Antenna Theory:** Research by Feldman et al. (2008) utilizing Optical Coherence Tomography (OCT) and reflectance measurements has demonstrated that these ducts resonate as **low-Q axial-mode helical antennas**. The resonance is broad but peaks in the 200–400 GHz range depending on the specific geometry of the individual's ducts.

This "antenna effect" implies that the skin does not absorb energy uniformly. Instead, energy may be funneled into the sweat ducts, creating localized specific absorption rates (SAR) within the duct walls that are orders of magnitude higher than the bulk tissue average. While the *macroscopic* thermal load might remain low, these *microscopic* hotspots could theoretically influence the nerve endings wrapped around the sweat glands, potentially lowering the threshold for thermal pain or nociception. This finding suggests that safety assessments for 6G technologies must account for the physiological state of the user (e.g., exercise/sweating vs. rest), a variable previously ignored in lower-frequency standards.⁵

6.3 Dielectric Variability of Skin Layers

At these frequencies, the Stratum Corneum (SC)—the dead, dry outer layer of skin—acts as an impedance matching transformer. Variations in SC hydration can drastically alter the reflection coefficient of the skin. "Wet" skin absorbs more energy but also reflects more due to the impedance mismatch with air. "Dry" skin is more transparent, allowing waves to penetrate deeper into the moist epidermis. This variability introduces significant uncertainty in dosimetric modeling, requiring "Bio-Digital Twin" approaches that can simulate dynamic skin conditions rather than static dielectric slabs.¹⁷

7. Biophysical Mechanisms: The Thermal vs. Non-Thermal Debate

The definition of "safety" in bio-electromagnetics hinges on the mechanism of interaction.

Current standards (IEEE/ICNIRP) are based solely on **thermal** and **electrostimulation** thresholds, asserting that these are the only established adverse effects. However, a persistent body of literature argues for the existence of **non-thermal effects**—biological changes occurring at field intensities too low to cause significant heating.

7.1 The Voltage-Gated Calcium Channel (VGCC) Hypothesis

Proposed notably by Martin Pall, this hypothesis suggests that the voltage sensors of voltage-gated calcium channels (VGCCs) in cell membranes are the primary targets of low-intensity EMFs.

- **Mechanism:** The voltage sensor (the S4 alpha-helix) contains positively charged amino acids. Pall argues that the electrical forces exerted by coherent EMFs on these charges are sufficient to conformationally change the channel, causing it to open.
- **Consequence:** Opening the channel leads to a massive influx of intracellular calcium ($[Ca^{2+}]_i$). This triggers the synthesis of Nitric Oxide (NO), which reacts with superoxide (SO_2^-) to form Peroxynitrite ($ONOO^-$). Peroxynitrite is a potent oxidant that creates oxidative stress, damages DNA (single-strand breaks), and impairs mitochondrial function.
- **Support:** Proponents cite studies where the application of calcium channel blockers (like nifedipine) mitigated the effects of EMF exposure, implying VGCC involvement.³⁴

7.2 The Biophysical Critique: The Thermal Noise Limit

Physicists, most prominently R.K. Adair and biological safety experts like Swanson, challenge the VGCC hypothesis based on fundamental thermodynamics.

- **Langevin Limit:** For an external force to trigger a deterministic biological event (like gating a channel), the energy imparted by that force (W) must exceed the random thermal energy of the system (kT , where k is the Boltzmann constant and T is temperature).

$$W > k_B T$$

- **Force Calculation:** Adair calculated that the force exerted by weak environmental RF fields on the charges in a voltage sensor is orders of magnitude smaller than the random "Brownian" molecular bombardment the sensor experiences every nanosecond.
- **Signal-to-Noise Ratio (SNR):** To detect such a weak signal amidst the thermal roar, the channel would need an "integration time" (averaging time) of seconds or minutes. However, ion channels gate on the timescale of milliseconds or microseconds. Therefore, Adair argues, it is thermodynamically impossible for the channel to "see" the field; the signal is buried too deep in the noise floor.⁸

7.3 The Radical Pair Mechanism (RPM)

The Radical Pair Mechanism is the only quantum biological mechanism widely accepted in a

different context: avian magnetoreception (how birds navigate using the Earth's magnetic field).

- **Theory:** Certain chemical reactions involve intermediate states with pair of radicals (molecules with unpaired electrons). The ultimate product of the reaction depends on whether the spins of these electrons are in a singlet (antiparallel) or triplet (parallel) state. Magnetic fields can influence the rate of interconversion between these states.
 - **RF Interaction:** It has been hypothesized that RF fields could resonate with the Zeeman splitting of these spin states, altering reaction yields of Reactive Oxygen Species (ROS).
 - **Critique:** While theoretically sound for static fields, the application to RF is problematic. The "decoherence time" of electron spins in a warm, wet biological environment is likely too short (nanoseconds to microseconds) for the RF field to exert a meaningful influence before the quantum state collapses. Recent simulations suggest that observable effects at telecommunication frequencies would require hyperfine coupling constants that do not exist in biological molecules.³⁷
-

8. Regulatory Evolution: IEEE C95.1-2019 and Global Standards

The culmination of this scientific understanding is codified in safety standards. The most significant recent development is the update of IEEE C95.1 in 2019 and the ICNIRP guidelines in 2020.

8.1 From C95.1-2005 to C95.1-2019

The 2019 standard introduced several key changes driven by the physics discussed above:

1. **Transition Frequency:** The boundary between "SAR-based" and "Power Density-based" limits was formally set at **6 GHz** (previously 3 GHz or 10 GHz in older drafts). This aligns with the transition to surface absorption.
2. **Averaging Area:** For frequencies > 6 GHz, the averaging area for power density is set at **4 cm²**. However, recognizing the possibility of narrow-beam mmWave antennas creating "thermal needles," the standard allows for a smaller **1 cm²** averaging area for frequencies > 30 GHz to prevent localized burns.
3. **Terminology:** The standard shifted from "Action Level" to "Safety Program Initiation Level" and harmonized the definition of "limbs" (extremities) with ICNIRP to facilitate global compliance.⁷

8.2 The "Two-Tier" Philosophy

The standards maintain a "two-tier" protection philosophy:

- **Unrestricted Environments (General Public):** Lower limits to account for vulnerable populations (children, elderly, sick) and continuous exposure.

- Restricted Environments (Occupational): Higher limits (typically 5x higher) for trained workers who are aware of the exposure and can mitigate it. This philosophy rejects the "Precautionary Principle" for non-thermal effects, strictly setting limits based on the threshold of established adverse effects (thermal pain/damage or electrostimulation) reduced by substantial safety factors (10x to 50x).¹⁵

9. Conclusion

The interaction of the human body with electromagnetic fields is not a singular phenomenon but a spectrum of distinct physical mechanisms driven by frequency. From the induction of currents in the conductive tissues of the torso at 60 Hz, to the resonant thermal absorption of the whole body at 100 MHz, and finally to the helical antenna resonances of sweat ducts at 300 GHz, the body responds dynamically to the electromagnetic environment.

Current safety standards, exemplified by IEEE C95.1-2019, have evolved to reflect this complexity, particularly in the critical transition to millimeter-wave frequencies for 5G and 6G. They have moved from simple volumetric heating models to sophisticated surface-energy metrics that account for the quasi-optical nature of high-frequency waves. However, the scientific debate persists. While the thermodynamic arguments against low-level non-thermal effects are robust, the sheer ubiquity of exposure ensures that research into subtle mechanisms like VGCC activation and Radical Pair dynamics remains a vibrant, albeit controversial, field.

As we advance into the terahertz era, the "Reference Man" of the past—a static, homogeneous dielectric average—must give way to "Bio-Digital Twins": computational models that are as complex, variable, and adaptive as the human subjects they are designed to protect. The safety of future wireless technologies relies on this fidelity, ensuring that as we push the limits of bandwidth, we do not unknowingly push the limits of biology.

Works cited

1. (PDF) <https://ieeexplore.ieee.org/document/9117465/authors#authors> - ResearchGate, accessed December 23, 2025, https://www.researchgate.net/publication/342503595_httpsieeexploreieeeorgdocument9117465authorsauthors
2. IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz - Regulations.gov, accessed December 23, 2025, https://downloads.regulations.gov/TSA-2013-0004-0013/attachment_1.pdf
3. IEEE C95.1-1991 - IEEE SA, accessed December 23, 2025, <https://standards.ieee.org/ieee/C95.1/2914/>
4. From what wavelength can radiation go through a human body without very much changing? - Physics Stack Exchange, accessed December 23, 2025,

- <https://physics.stackexchange.com/questions/239494/from-what-wavelength-can-radiation-go-through-a-human-body-without-very-much-cha>
5. Frequency of the resonance of the human sweat duct in a normal mode of operation - PMC, accessed December 23, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC5846532/>
 6. The human skin as a sub-THz receiver – Does 5G pose a danger to it or not? - OSTI, accessed December 23, 2025, <https://www.osti.gov/biblio/23095662>
 7. C95.1-2019 - IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz - Redline, accessed December 23, 2025, <https://ieeexplore.ieee.org/document/8930421>
 8. Scientific evidence contradicts findings and assumptions of Canadian Safety Panel 6: microwaves act through voltage-gated calcium channel activation to induce biological impacts at non-thermal levels, supporting a paradigm shift for microwave/lower frequency electromagnetic field action - PubMed, accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/25879308/>
 9. Biophysical limits on athermal effects of RF and microwave radiation - PubMed, accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/12483664/>
 10. The dielectric properties of biological tissues: I. Literature survey - SciSpace, accessed December 23, 2025, <https://scispace.com/pdf/the-dielectric-properties-of-biological-tissues-i-literature-2m4c4enqvy.pdf>
 11. Skin Depth Calculator - everything RF, accessed December 23, 2025, <https://www.everythingrf.com/rf-calculators/skin-depth-calculator>
 12. Modeling Brain Using Parameters of Passive Electrical Circuits - The Repository at St. Cloud State, accessed December 23, 2025, https://repository.stcloudstate.edu/cgi/viewcontent.cgi?article=1013&context=ece_etds
 13. UNIVERSITY OF THESSALY, accessed December 23, 2025, <https://ir.lib.uth.gr/xmlui/bitstream/handle/11615/82707/28084.pdf?sequence=4>
 14. The dielectric properties of biological tissues: II. Measurements in ..., accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/8938025/>
 15. Compilation of the Dielectric Properties of Body Tissues at RF and Microwave Frequencies. - DTIC, accessed December 23, 2025, <https://apps.dtic.mil/sti/tr/pdf/ADA305826.pdf>
 16. Effects of Dielectric Properties of Human Body on Communication Link Margins and Specific Absorption Rate of Implanted Antenna System - NIH, accessed December 23, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12158277/>
 17. Complex permittivity of human skin in vivo in the frequency band 26.5-60 GHz | Request PDF - ResearchGate, accessed December 23, 2025, https://www.researchgate.net/publication/3866711_Complex_permittivity_of_human_skin_in_vivo_in_the_frequency_band_265-60_GHz
 18. Database Summary » IT'IS Foundation - itis.swiss, accessed December 23, 2025, <https://itis.swiss/virtual-population/tissue-properties/database/database-summary/>
 19. Dielectric Properties » IT'IS Foundation, accessed December 23, 2025,

<https://itis.swiss/virtual-population/tissue-properties/database/dielectric-properties>

20. Permittivity Characterization of Human Skin Based on a Quasi-optical System at Sub-THz - arXiv, accessed December 23, 2025, <https://arxiv.org/html/2405.11863v1>
21. IEEE Std C95.6-2002, IEEE Standard for Safety Levels with Respect to Human Exposure to Electromagnetic Fields, 0 – 3 kHz - County of San Diego, accessed December 23, 2025, https://www.sandiegocounty.gov/content/dam/sdc/pds/ceqa/Soitec-Documents/Final-EIR-Files/references/rtcref/ch9.0/RTCrefappx/2014-12-19_IEEE2002.pdf
22. Coupling of GWEN Electromagnetic Fields to the Human Body - Assessment of the Possible Health Effects of Ground Wave Emergency Network - NCBI, accessed December 23, 2025, <https://www.ncbi.nlm.nih.gov/books/NBK208991/>
23. FDTD calculations of specific energy absorption rate in a seated voxel model of the human body from 10 MHz to 3 GHz - PubMed, accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/16625046/>
24. Biological effects of radiofrequency electromagnetic fields due to energy absorption and heating - BfS, accessed December 23, 2025, https://www.bfs.de/EN/topics/emf/hff/effect/hff-established/hff-established_node.html
25. Advances in Computational Human Phantoms and Their Applications in Biomedical Engineering – A Topical Review - PMC - PubMed Central, accessed December 23, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC6362464/>
26. Effect of skin thickness on electromagnetic dosimetry analysis of a human body model up to 100 GHz | International Journal of Microwave and Wireless Technologies - Cambridge University Press, accessed December 23, 2025, <https://www.cambridge.org/core/journals/international-journal-of-microwave-and-wireless-technologies/article/effect-of-skin-thickness-on-electromagnetic-dosimetry-analysis-of-a-human-body-model-up-to-100-ghz/E1DB9916392BF398F813E4D3B6630358>
27. FDTD calculation of whole-body average SAR in adult and child models for frequencies from 30 MHz to 3 GHz - PubMed, accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/16912372/>
28. EMF, New ICNIRP Guidelines and IEEE C95.1-2019 Standard: Differences and Similarities - Dr. Haim Mazar (Madjar), accessed December 23, 2025, https://mazar.atwebpages.com/Downloads/WarsawEMF2019_Mazar_IEEE95.1_ICNIRPguidelines_ITU3Dec2019.pdf
29. Human Exposure to Radiofrequency Electromagnetic Fields - Federal Register, accessed December 23, 2025, <https://www.federalregister.gov/documents/2020/04/06/2020-06966/human-exposure-to-radiofrequency-electromagnetic-fields>
30. Model Variability in Assessment of Human Exposure to Radiofrequency Fields - IEEE Xplore, accessed December 23, 2025, <https://ieeexplore.ieee.org/iel8/9171629/9206027/11269783.pdf>
31. The human skin as a sub-THz receiver – Does 5G pose a danger to it or not? - Prof. Yuri Feldman, accessed December 23, 2025,

- https://yurifeldman.huji.ac.il/sites/default/files/urifeldman/files/the_human_skin_as_a_sub-thz_receiver_-_does_5g_pose_a_danger_to_it_or_not.pdf
32. The human skin as a sub-THz receiver - Does 5G pose a danger to it or not? - PubMed, accessed December 23, 2025, <https://pubmed.ncbi.nlm.nih.gov/29459303/>
 33. Simulating the Electrical Properties of the Human Skin for the Development of Hydration Sensors - ZHAW, accessed December 23, 2025, https://www.zhaw.ch/storage/engineering/institute-zentren/icp/sensoren/Master_Thesis/Master_thesis_Claudio_Malnati.pdf
 34. Low Intensity Electromagnetic Fields Act via Voltage-Gated Calcium Channel (VGCC) Activation to Cause Very Early Onset Alzheimer's Disease: 18 Distinct Types of Evidence - PubMed Central, accessed December 23, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC9189734/>
 35. Electromagnetic fields act via activation of voltage-gated calcium channels to produce beneficial or adverse effects - PubMed Central, accessed December 23, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC3780531/>
 36. Johnson–Nyquist noise - Wikipedia, accessed December 23, 2025, https://en.wikipedia.org/wiki/Johnson%E2%80%93Nyquist_noise
 37. The radical pair mechanism cannot explain telecommunication frequency effects on reactive oxygen species - Frontiers, accessed December 23, 2025, <https://www.frontiersin.org/journals/quantum-science-and-technology/articles/10.3389/frqst.2025.1544473/full>
 38. Chemical magnetoreception in birds: The radical pair mechanism - PNAS, accessed December 23, 2025, <https://www.pnas.org/doi/10.1073/pnas.0711968106>
 39. Upper bound on the biological effects of 50/60 Hz magnetic fields mediated by radical pairs, accessed December 23, 2025, <https://elifesciences.org/articles/44179>
 40. ICES EMF Exposure Standards, accessed December 23, 2025, https://www.ewh.ieee.org/r6/oeb/lm/previous_meetings/2019/Chou%20May%2029%202019.pdf