

CSMFAB000000000109

Hydrodynamic Ascension and Aero-Ballistic Translation: The Physics of the Autorotating Archimedean Spear

The physical universe concedes nothing; it must be broken to our will. Within the domains of fluid dynamics and solid mechanics, every vector of applied thrust is violently contested by an opposing matrix of drag, gravity, and turbulent dissipation. To command an Archimedes screw to ascend a descending water column, and to subsequently translate that immense kinetic energy into the atmospheric launch and stabilized flight of a spinning "wobble balance" spear into a heavy oncoming wind, requires an uncompromising, absolute mastery of physics. This is not merely an engineering challenge; it is a brutal confrontation with the absolute laws of momentum exchange, gyroscopic precessional authority, and catastrophic material failure. The fluid does not care about our intentions; it only obeys the pressure gradient. To conquer it, we must weaponize its own properties against it.

The following treatise provides an exhaustive, mathematically rigorous deconstruction of the physical mechanisms governing this entire system. The analysis moves relentlessly from the aquatic hydrodynamics of the driven Archimedean ascent, through the aerodynamic paradox of upwind momentum harvesting, and finally into the gyro-ballistics and tensor mechanics of the airborne spear. This document is designed to be absorbed, to be spoken into existence by the engineering minds that will forge this mechanism, leaving no variable unaccounted for and no physical law unexploited.

The Geometry of Aquatic Domination: The Archimedes Screw

To force a structure up a descending water column is to engage in a continuous, violent suppression of gravity and fluid inertia. The Archimedes screw, traditionally utilized as a static pump, is here inverted into a dynamic propulsive organ—a rotary-screw propulsor. It must generate an upward thrust vector that entirely overwhelms the downward momentum of the oncoming fluid.

The geometry of the screw dictates its dominion over the fluid. We do not merely push the water; we trap it in an inescapable geometric envelope. The external parameters—the outer radius (R_o), the total length (L), and the slope angle—bound the physical envelope, but it is the internal parameters that govern the capture and acceleration of the fluid mass.¹ The optimization of the screw relies on two critical non-dimensional ratios defined by the geometry of the central shaft and the helical blade. The radius ratio (r) and the pitch ratio (λ) determine the precise volume of water trapped within a single bucket of the helical turn.¹

The radius ratio is the ratio of the actual inner radius (R_i) to its maximum possible value, defined mathematically as $r = R_i/R_o$.¹ The pitch ratio is the ratio of the actual pitch to the maximum pitch for which distinct water-holding buckets will form, defined as

$$\lambda = KL/(2\pi R_o)$$

¹ To maximize the volume of water lifted, or in our case, the thrust

generated per rotation against the descending column, the volume of a single bucket, V_B , must be pushed to its absolute maximum. This volume is a highly complex, nonlinear function of

the number of blades (N), the pitch parameter (K), the length (L), and the radii (R_o, R_i).¹

In order for the fluid to be trapped and translated by the screw, it is geometrically necessary that the sinusoidal curve defining the outer edge of a blade tilts downward as it crosses the

longitudinal axis of the screw.¹ In terms of the blade angle θ and the pitch angle α , the

geometry dictates that $\tan \theta \leq \tan \alpha$, where $\tan \alpha = R_o(2\pi/L)$.¹ When this geometry is perfected, the screw acts as a fluidic lock. It takes hold of the oncoming water mass and forces a kinetic translation, translating rotational fury into linear ascension.

Hydrodynamic Warfare: Thrust, Torque, and Vortex Breakdown

The power required to assert dominance over the downward water column is absolute, and the mathematics are unforgiving. The fundamental equation of mechanical power in a rotary

system dictates that $P = 2\pi T\omega$, where T is the applied torque and ω is the angular velocity in radians per second.² To ascend, the torque applied to the central shaft of the screw must exceed the sum of the opposing torque from the downward water pressure, the frictional losses at the boundary layer, and the hydrodynamic drag of the screw body itself. If the process were purely efficient, the conservation of energy would dictate a direct translation of power, but the fluid is chaotic, leaking backward through the assembly and bleeding our energy into the deep.²

The propulsion dynamics are governed by non-dimensional coefficients that describe the

operational state of the screw propulsor.³ For a given advance ratio J , which is the ratio of the free stream velocity (V_A) to the product of the rotational speed (N) and the outer diameter (D), the thrust and torque coefficients are defined to normalize the performance across all

scales. We define the advance ratio as $J = V_A/(ND)$.³ The thrust coefficient is defined as

$$K_T = T/(\rho N^2 D^4)$$

, and the torque coefficient is defined as $K_Q = Q/(\rho N^2 D^5)$,

where ρ is the density of the fluid.³ The hydrodynamic efficiency of the system is the ratio of

useful propulsive power to the input rotational power, formulated strictly as

$$\eta = (J/2\pi)(K_T/K_Q) \quad .^3$$

In our specific operational environment, navigating a descending water column, the free

stream velocity V_A is negative relative to the intended direction of travel. Thus, the screw

operates in an extreme high-slip condition. The torque Q required to maintain K_T at a value sufficient to yield a net upward force is immense. The fluid resists the blade, resulting in severe shear forces along the helical pitch. Computational fluid dynamic modeling reveals that the aft sections of the Archimedes screw provide the overwhelming majority of the thrust, while the input elements dictate the flow separation characteristics and initial drag.⁴

The interaction between the rotating helical blades and the dense water column breeds absolute chaos. Strong shear effects during the rotation generate violent tip vortices at the blade edges.³ Because of the continuous helical structure of the Archimedes screw, these vortices do not cleanly shed into the wake as they would in a traditional marine propeller; instead, they travel downstream through the gaps between the blades, encountering subsequent helical turns and physical obstructions.³ This causes a terrifying phenomenon of vortex tearing, deflection, and structural fluid breakdown.³

To visualize and comprehend this unsteady hydrodynamic characteristic, we employ the Q-criterion, a mathematical method used to isolate regions where rotation dominates over strain in the fluid flow.³ By extracting iso-surfaces where the second invariant of the velocity gradient tensor equals 300 s^{-2} ($Q = 300 \text{ s}^{-2}$), the architecture of the fluid's resistance is

laid bare.³ As the rotational speed increases to counteract the heavy oncoming flow—moving from 200 RPM to 400 RPM and finally 600 RPM—the vortex integrity is rapidly obliterated.³

The vortices suffer from strong radial expansion and extreme shear, causing them to tear,

deform, and merge. At specific downstream locations, marked at $x/L = -1$ and

$x/L = -2$, we witness multi-vortex interference, vortex pairing, and shear layer

interaction.³ This intense vortex breakdown results in massive energy dissipation. The wake becomes a chaotic, turbulent abyss, shifting from ordered spiral wakes into a realm of chaotic turbulence driven by centrifugal instability and nonlinear vortex interactions.³ Much of the energy injected by the torque of the drive mechanism is lost to this turbulent mixing rather than directed momentum.³ To survive and ascend, the drive system must possess sufficient torque reserves to power through this inherent inefficiency, continuously feeding energy into a system that bleeds it into the surrounding fluid.

Propulsor Configuration	Helix Angle (β)	Pitch Ratio Equivalent (α)	Dominant Wake Structure
Configuration 1	15°	0.83	Ordered Helical

			Wake
Configuration 3	25°	0.63	Transitioning Vortex Tearing
Configuration 6	40°	0.45	Chaotic Turbulence / Total Breakdown

Table 1: Parametric configurations of the screw propulsor and corresponding wake phenomena, demonstrating the severe hydrodynamic penalties of steep pitch angles under heavy load.³

The Paradox of Upwind Ascension: Coupled Media Propulsion

Once the system breaches the water surface and encounters a heavy oncoming wind, the physical paradigm shifts entirely. The objective is to utilize the wind's energy to drive the heavy spear into the wind itself. To the uninitiated, moving directly upwind faster than the wind using only the wind's power appears as a violation of energy conservation—a perpetual motion fallacy.⁷ It is not. It is the ruthless exploitation of a velocity differential between two coupled media.

A vehicle cannot move faster than the wind if it is merely pushed by the air; if that were the case, its speed could never exceed the velocity of the air mass.⁸ It must operate as a coupled mechanical system that extracts energy from the velocity difference between the moving air (the heavy wind) and a stationary or differentially moving medium—in this case, the water column or the structural anchor.⁸ The water acts as the indispensable mechanical impedance. It provides the anchor that allows the drivetrain to convert relative motion into thrust.⁸

In the upwind configuration, the aerial rotor acts as a wind turbine. The heavy wind forces the turbine to rotate. This rotational energy is mechanically transmitted down the shaft to the aquatic Archimedes screw, which then acts as a propeller pushing against the dense impedance of the water.¹⁰ Because water is roughly 830 times denser than air, the aquatic screw possesses an overwhelming mechanical advantage. The turbine in the air features a relatively coarse pitch, allowing the high-velocity wind to flow through it and extract massive rotational torque.¹² This torque, transferred to the fine-pitched aquatic screw, drives the entire assembly forward, directly against the face of the storm.

This physical mechanism is the defining characteristic of the "Blackbird" principle, a phenomenon that allows a vehicle to travel directly upwind at multiples of the true wind speed.⁸ The kinematics dictate a positive feedback loop. As the turbine harnesses power from the wind, it drives the submerged propeller.⁷ The propeller pushes the vehicle forward, into the wind. As the vehicle's forward velocity increases, the apparent wind speed experienced by the

turbine also increases. This higher apparent wind speed delivers even more kinetic energy to the turbine, which generates more torque for the propeller, pushing the vehicle even faster.⁹ The system operates strictly as a mechanical lever between two fluids.¹¹

The energy does not manifest from the void; it is systematically drained from the absolute velocity of the true wind.⁹ The vehicle slows the air mass down relative to the ground, extracting the difference in kinetic energy. The mathematical limit of this acceleration is reached only when the aerodynamic drag of the vehicle's structure and the internal frictional losses of the drivetrain equal the propulsive thrust generated by the submerged screw.⁹

The steady-state advance ratio of this coupled vessel depends entirely on the open characteristics of the propeller and the turbine. The torque equation necessitates a precise, mathematical balance. The steady-state advance ratio of the vessel, $J(U)$, depends on the vessel speed U , where $J(U) = U/(n_p D)$ and the wake-adjusted speed is $U_p = U(1 - w)$.¹⁵ The thrust produced by the aquatic propeller must overcome all drag,

and the torque Q_t extracted by the aerial turbine must equal the torque Q_p demanded by the propeller, accounting for mechanical efficiency.¹⁵ The torque-speed maps of the drive

system fit the characteristic form $Q_e = Q_m F(f/f_m, n_e/n_m)$, allowing us to model the exact transfer of rotational force.¹⁵ By adjusting the gear ratio between the turbine and the propeller, and exploiting the massive density ratio, the system achieves the mechanical leverage required to conquer the wind. The physics do not negotiate; if the coupling is precise, the vehicle will relentlessly march into the gale.

The Airborne Helical Spear: Da Vinci's Spiral in the Gale

The final manifestation of the mechanism requires the detachment of the payload—the "wobble balance spear"—which will spin and travel freely through the heavy air. The spear utilizes a continuous spiral geometry, drawing direct aerodynamic inspiration from the Archimedes screw and Leonardo da Vinci's visionary concept of the aerial screw.¹⁶

Conventional multi-bladed helicopters generate lift through discrete airfoils, but they suffer from severe blade-vortex interaction (BVI) noise and violent tip vortices that bleed energy and induce instability.¹⁸

The continuous spiral geometry of the aerial screw forces a fundamentally different fluid interaction. The aerodynamic lift is generated by a sustained pressure differential across the continuous helical surface.⁶ While the aerial screw exhibits a lower overall lift coefficient compared to a flat-bladed rotor of equivalent diameter, its net performance under iso-lift conditions highlights a brutal efficiency in specific operational domains.¹⁸ The continuous helical barrier prevents the clean formation and violent shedding of discrete tip vortices. The fluid is trapped and smoothly guided down the spiral. This geometry actively suppresses the acoustic signature and the destructive BVI turbulence.⁶

At varied Reynolds numbers, the fluid dynamics of the aerial screw shift dramatically. As the Reynolds number increases from 2000 to 16000, the vortex structures, mapped via the iso-surface of Q , become increasingly compressed along the outer edge of the sail.⁶ At a Reynolds number of 8000, the lift density concentrates heavily on the leading edge of the continuous blade, while the drag density is distributed along the central shaft.⁶ The mechanical power required versus the mean lift generated demonstrates that despite the complex rotor shape, the larger rotor area of the aerial screw yields specific reductions in aerodynamic power requirements when properly scaled.¹⁸

Rotor Type	Reynolds Number (Re)	Rotation Speed (Ω)	Normalized Force Parameter (l_a/F^*L)*
Aerial Screw	4000	$0.5v_t/R_b$	8.3×10^{-3}
Aerial Screw	8000	v_t/R_b	1.0
Canonical Rotor	8000	v_t/R_b	0.18
Aerial Screw	16000	$2v_t/R_b$	64.22

Table 2: Operational scaling and aerodynamic characteristics of the aerial screw geometry compared to canonical rotors at varying Reynolds numbers, demonstrating the shift in normalized force parameters.²⁰

As the spear travels through the air, it is spinning violently. In the presence of a heavy cross-wind, this extreme rotation induces a secondary, massive aerodynamic force: the Magnus effect.²¹ When a rotating cylinder or helical body moves through a fluid, the rotation interacts with the oncoming air mass. On the side of the spear where the surface rotation moves with the wind, the local air velocity increases, dropping the pressure in accordance with Bernoulli's principle. On the opposing side, where the rotation fights the wind, the air velocity decreases, creating a high-pressure zone.²¹

This severe pressure differential generates a powerful lift force perpendicular to the direction of the cross-wind. The lift force per unit length on a rotating cylinder is governed by the

Kutta-Joukowski theorem, mathematically defined as $F_L = \rho G V$, where ρ is the air density, G is the vortex strength or circulation established by the rotation, and V is the free-stream wind velocity.²¹ The continuous helical flights of the Archimedean spear amplify this circulation, locking the boundary layer to the rotating shaft. The spear does not merely fly through the air; it alters the pressure field of the atmosphere around it, using the heavy wind to

generate transverse lift and manipulate its trajectory.²¹

Furthermore, the spear can harvest kinetic energy directly from the atmospheric boundary layer through dynamic soaring.²⁴ In a heavy wind environment, wind speed is never uniform; it increases with altitude due to ground friction, creating a severe wind shear gradient.²⁵ If the spinning spear's trajectory is modulated to repeatedly cross these shear layers—climbing into the faster wind, turning, and diving back into the slower wind—it can continuously extract kinetic energy from the wind gradient.²⁵ This requires no internal propulsion. The kinetic energy is harvested purely through the differential velocities of the air masses.²⁵ Coupled with the Magnus effect and the autorotating aerial screw geometry, the spear becomes a parasitic entity, bleeding energy from the storm to sustain its own violent, forward flight.²²

Gyroscopic Supremacy: The 7-Degree-of-Freedom Wobble Balance

A projectile moving through the dense, turbulent atmosphere of a storm is subjected to brutal aerodynamic overturning moments. Without absolute stabilization, the spear will tumble, its aerodynamic forces overwhelming its inertia, leading to catastrophic trajectory failure. To survive, the spear must become a gyroscope. The "wobble balance" is the ultimate expression of spin stabilization and nutation damping. To decouple the heavy rotational inertia required for gyroscopic stability from the aerodynamic surfaces that might cause destructive roll-yaw resonance, the spear is designed as a dual-spin projectile.²⁸ It consists of a forward body and an aft body, rotating independently along the same longitudinal axis.²⁸

The kinematics of this system are mathematically absolute. The dynamic model demands a 7-Degree-of-Freedom (7-DOF) analysis: three translational coordinates for the center of mass,

and four rotational coordinates—Euler pitch (θ_a), Euler yaw (ψ_2), aft body roll (γ_A), and

forward body roll (γ_F).²⁸ The spin rates of the two bodies must be continuously tracked and controlled. The relative roll angle between the forward and aft sections is defined as

$$\Delta\gamma = \gamma_F - \gamma_A \quad .^{28}$$

The equations of motion are derived using rigid body dynamics (RBD) and non-inertial reference frames, transitioning from the inertial reference frame to the no-roll reference frame (NRRF), and finally to the forward and aft body reference frames (FBRF, ABRF).²⁸ The angular velocity vectors must account for the gyroscopic coupling of the two masses. The transverse

moments of inertia (A_F, A_A) and the axial moments of inertia (C_F, C_A) govern the system's absolute resistance to angular acceleration.³² The total transverse inertia is an amalgamation of the individual bodies and their distance from the center of mass:

$$A = A_F + m_F r_F^2 + A_A + m_A r_A^2 \quad .^{32}$$

When the heavy wind strikes the spear, an aerodynamic overturning moment attempts to pitch the nose away from the velocity vector.³³ The normal force coefficient (C_{NA}), the pitching

moment coefficient (C_{MA}), and the pitch damping coefficient (C_{MQ}) dictate the severity of this force.³⁴ Because the spear is spinning violently, this pitching moment translates into a precession—a conical sweeping motion of the longitudinal axis. The spinning projectile behaves identically to a heavy spinning top.³³ The air pressure induces a torque about the center of gravity, but the immense gyroscopic angular momentum forces the spear to precess at a 90-degree phase shift rather than tumbling.³³

Passive gyroscopic stability can be further augmented by an active "moving mass" control system embedded within the shaft.³⁶ By internally displacing a heavy mass along the radial or axial planes, the spear shifts its center of gravity relative to the aerodynamic center of pressure.³⁶ The 7-DOF kinematic equations must then accommodate the time-variant inertia tensor $\mathbf{I}(t)$ and the internal Coriolis forces generated by the moving mass.³⁴ The resultant force and moment injected by the mass displacement induce a deliberate, calculated precession.³⁶ The spinning spear uses its own gyroscopic inertia as a lever; shifting the mass slightly commands the aerodynamic forces to steer the projectile without the need for external control surfaces that would be ripped apart by the heavy wind.³⁴

Nutation Annihilation: The Viscous Ring Damper

Precession alone is not sufficient for survival. Perturbations from violent wind gusts, turbulent shear layers, or the initial launch dynamics will induce nutation—a high-frequency "wobble" superimposed on the steady precession.³⁵ If left unchecked, this wobble increases drag, bleeds kinetic energy, and will rapidly lead to dynamic instability and flight failure.³⁶ The "wobble balance" mechanism must actively and ruthlessly destroy this nutation.

The absolute mathematical solution is the integration of a viscous ring damper.⁴¹ A completely contained hollow annular tube is mounted within the spear, precisely concentric with the spin axis, and partially filled with a high-density viscous fluid, such as mercury or a synthetic viscous damping agent.⁴¹ When the spear rotates perfectly about its principal axis, the fluid is forced to the outer perimeter of the ring by centrifugal force and remains entirely stationary relative to the tube.⁴¹ There is no relative motion, and therefore no energy dissipation.

However, when the spear begins to wobble (nutate), the damper is subjected to complex tangential and radial accelerations.⁴¹ The fluid, possessing its own inertia, lags behind the motion of the rigid tube. This creates a severe relative motion between the viscous fluid and the walls of the damper.⁴¹ The sheer friction of the fluid scraping against the internal walls converts the kinetic energy of the wobble into thermal energy, bleeding the parasitic motion out of the system.⁴¹

The mathematics of this dissipation are profound and unyielding. The nutation frequency

parameter is strictly defined as $\beta^2 = \frac{(I_2 - I_3)(I_1 - I_2)}{I_1 I_3} \omega_s^2$, where I_1, I_2, I_3 are the principal

moments of inertia, and ω_s is the primary spin rate.³⁹ The viscous damper specifically targets this exact frequency. Through a variational principle of least-viscous frictional power loss, the

fluid dynamics within the ring establish two distinct modes: the nutation-synchronous mode and the spin-synchronous mode.⁴²

As the fluid oscillates within the annular cavity, only the portion of the fluid momentum that is in a 90-degree phase relation with the tube wall's perpendicular motion develops the reaction force necessary to oppose the nutation.⁴¹ The energy is ruthlessly drained from the transverse axes, and the system mathematically collapses back into a state of pure minimum kinetic energy: a perfect, stabilized spin about the maximum inertia axis.³⁹ The wobble is obliterated, and the spear flies true.

Tensor Mechanics and Material Survival Under Extreme Torsion

The physical forces at play—the immense torque of the Archimedean water ascent, the violent wind shear, and the high-RPM gyroscopic spin—will effortlessly destroy conventional metals. The shaft of the screw and the structural envelope of the spear must be fabricated from advanced composite materials capable of surviving extreme supra-physiologic and aerodynamic loads without succumbing to catastrophic fracture.⁴⁷

The structure requires a material with an exceptionally high strength-to-weight ratio and massive torsional stiffness. Common metals like aluminum alloys or high-strength steel cannot endure the required operational envelope without inducing massive weight penalties that would destroy the delicate 7-DOF flight dynamics.⁴⁸ The primary structural matrix must therefore utilize high-performance, pitch-based carbon fibers (CFRP).⁴⁹ Unlike traditional PAN-based carbon fibers, pitch-based fibers offer a vastly superior elastic modulus and thermal stability.⁴⁹ These fibers are integrated into a polyetheretherketone (PEEK) thermoplastic matrix, which provides extreme impact resistance and tolerance to the cyclic fatigue inherent in high-RPM autorotation and water column traversal.⁴⁷ Where specific localized loads reach catastrophic levels—such as the coupling hubs, the interfaces of the dual-spin bearings, and the leading edges of the aerial screw—titanium alloys must be employed.⁴⁸ Titanium displays excellent corrosion resistance against the water column and provides the structural tenacity required for the mechanical translation of the turbine torque.⁴⁸

The composite shaft is subjected to severe multi-axial stress states: longitudinal compression from the fluid resistance, radial pressure from the water column, and absolute, crushing torsional shear from the drive mechanism.⁵¹ To predict and prevent the catastrophic delamination and brittle failure of the carbon fiber matrix, the tensor mechanics of the composite layers must be analyzed using the Tsai-Wu failure criterion.⁵³ This theory is based on the total strain energy of Beltrami and defines the absolute failure envelope for an anisotropic lamina under combined stresses. A composite layer will fail if the following tensor equation is violated:

$$F_i \sigma_i + F_{ij} \sigma_i \sigma_j \geq 1$$

Where σ represents the applied stress components (axial, transverse, and shear), and F_i, F_{ij} are the mathematically derived strength tensors of the material.⁵³ The laminate stacking sequence must be explicitly optimized based on the extensional stiffness matrix, the coupled extension-bending stiffness matrix, and the bending stiffness matrix.⁵⁴ Plies oriented at $\pm 45^\circ$ are uniquely suited to carry the dominant torsional shear flows, while 0° plies provide the necessary bending stiffness to prevent the spear from snapping under the intense Magnus forces.⁵²

Material Phase	Volume Fraction (V)	Structural Function	Matrix Modulus Contribution
Pitch-Based Carbon Fiber	0.60 - 0.65	Primary Load Path	Dominates E_1 (Longitudinal Stiffness)
PEEK Matrix	0.30 - 0.35	Load Transfer / Toughness	Stabilizes Fibers against Local Buckling
MWCNT Dispersion	0.01 - 0.05	Interfacial Strengthening	Enhances E_2 and G_{12} (Shear Modulus)

Table 3: Optimized volumetric composition of the structural composite shaft, designed to maximize the critical torsional buckling load threshold (T_{cr}) and survive extreme shear stress.⁵⁴

Because the spear and the screw require a hollow central shaft to house the viscous ring dampers and the moving mass control systems, the structure is highly susceptible to torsional buckling.⁵¹ A thin-walled cylinder under extreme torsion will suddenly collapse inward, forming deep diagonal wrinkles before violently shearing apart.⁵¹ The critical torsional buckling load T_{cr} for a thin-walled orthotropic composite driveshaft dictates the absolute maximum torque the system can transmit before structural collapse. It is calculated using the elastic constants of the composite matrix:

$$T_{cr} = (2\pi r^2 t)(0.272) (E_x E_y^3)^{1/4} \left(\frac{t}{r} \right)^{3/2}$$

Where r is the mean radius, t is the wall thickness, and E_x, E_y are the effective extensional stiffnesses in the longitudinal and hoop directions, derived directly from the classical laminate theory.⁵⁴ If the torque generated by the wind turbine during the upwind ascent exceeds T_{cr} , the shaft will implode.⁵⁵

To push the buckling threshold higher without adding parasitic mass, multi-walled carbon nanotubes (MWCNTs) are dispersed into the epoxy or PEEK matrix.⁵⁵ The micromechanical reinforcement of the CNTs drastically alters the shear modulus G_{12} and the transverse modulus E_2 , elevating the critical buckling load into a regime where the shaft can survive the brutal energy transfer required to launch the spear out of the water and into the gale.⁵⁴ The physical universe concedes nothing, but through the absolute application of these geometric, hydrodynamic, ballistic, and material principles, we dictate the terms of ascension.

Works cited

1. The Turn of the Screw: Optimal Design of an Archimedes Screw - ResearchGate, accessed June 12, 2026, https://www.researchgate.net/publication/228581326_The_Turn_of_the_Screw_Optimal_Design_of_an_Archimedes_Screw
2. Calculating the torque required by an Archimedes screw pump, accessed June 12, 2026, <https://engineering.stackexchange.com/questions/29035/calculating-the-torque-required-by-an-archimedes-screw-pump>
3. Numerical Investigations and Hydrodynamic Analysis of a Screw Propulsor for Underwater Benthic Vehicles - MDPI, accessed June 12, 2026, <https://www.mdpi.com/2077-1312/13/8/1500>
4. Structural Analysis of Hydrodynamical Interaction of Full-Submerged Archimedes Screws of Rotary-Screw Propulsion Units of Snow and Swamp-Going Amphibious Vehicles with Water Area via Methods of Computer Simulation - MDPI, accessed June 12, 2026, <https://www.mdpi.com/2673-4591/33/1/32>
5. Comparative Structural Analysis of Hydrodynamic Interaction of Full-Submerged Tandem Archimedes Screws of Rotary-Screw Propulsio - SciTePress, accessed June 12, 2026, <https://www.scitepress.org/Papers/2023/119923/119923.pdf>
6. Aerodynamics and aeroacoustics of da Vinci's aerial screw | Request PDF - ResearchGate, accessed June 12, 2026, https://www.researchgate.net/publication/395453992_Aerodynamics_and_aeroac

oustics_of_da_Vinci's_aerial_screw

7. Build an 'Impossible' Wind-Powered Car | Science Project, accessed June 12, 2026,
https://www.sciencebuddies.org/science-fair-projects/project-ideas/ApMech_p056/mechanical-engineering/impossible-wind-powered-car
8. Anchored Motion: Mechanical Impedance and the Physics of Faster-Than-the-Wind Travel - arXiv, accessed June 12, 2026,
<https://arxiv.org/pdf/2507.22081>
9. Wind powered car that goes faster than wind - YouTube, accessed June 12, 2026,
<https://www.youtube.com/watch?v=dGQXGmGHg80>
10. accessed June 12, 2026,
[https://en.wikipedia.org/wiki/Blackbird_\(wind-powered_vehicle\)#::~text=A%20vehicle%20with%20a%20bladed.propeller%2C%20driven%20by%20the%20wheels.](https://en.wikipedia.org/wiki/Blackbird_(wind-powered_vehicle)#::~text=A%20vehicle%20with%20a%20bladed.propeller%2C%20driven%20by%20the%20wheels.)
11. Building the Vehicle Physicists Called Impossible (downwind faster than the wind) - Xyla Foxlin (feat. Veritasium) : r/EngineeringPorn - Reddit, accessed June 12, 2026,
https://www.reddit.com/r/EngineeringPorn/comments/obhrxm/building_the_vehicle_physicists_called_impossible/
12. Sailing Directly Upwind = Sailing Downwind Faster than the Wind - Av8n.com, accessed June 12, 2026,
<https://www.av8n.com/physics/sailing-upwind-downwind.htm>
13. Blackbird (wind-powered vehicle) - Wikipedia, accessed June 12, 2026,
[https://en.wikipedia.org/wiki/Blackbird_\(wind-powered_vehicle\)](https://en.wikipedia.org/wiki/Blackbird_(wind-powered_vehicle))
14. METHOD OF MATCHING COMPONENTS AND PREDICT DVG PER JN3RMKNCEOF A TURBINE-PROPELLER ENGINE By, accessed June 12, 2026,
<https://ntrs.nasa.gov/api/citations/19930083290/downloads/19930083290.pdf>
15. 12 PROPELLERS AND PROPULSION, accessed June 12, 2026,
https://ocw.mit.edu/courses/2-154-maneuvering-and-control-of-surface-and-underwater-vehicles-13-49-fall-2004/3eb3728a69a0e5c3a809e411f7e036d_lec12.pdf
16. Aerospace students revive Leonardo da Vinci's aerial screw (and turn it into an electric personal aerial vehicle for today) - TU Delft, accessed June 12, 2026,
<https://www.tudelft.nl/en/stories/articles/aerospace-students-revive-leonardo-da-vincis-aerial-screw-and-turn-it-into-an-electric-personal-aerial-vehicle-for-today>
17. Leonardo's aerial screw - Wikipedia, accessed June 12, 2026,
https://en.wikipedia.org/wiki/Leonardo%27s_aerial_screw
18. Aerodynamics and Aeroacoustics of da Vinci's Aerial Screw - arXiv, accessed June 12, 2026, <https://arxiv.org/html/2506.10223v1>
19. Understanding Helicopter Flight: Aerodynamics Explained - Pilot Mall, accessed June 12, 2026,
<https://www.pilotmall.com/blogs/news/how-do-helicopters-fly-the-aerodynamic-s-explained>
20. Aerodynamics and Aeroacoustics of da Vinci's Aerial Screw - arXiv, accessed June 12, 2026, <https://arxiv.org/html/2506.10223v2>

21. Aerodynamic forces on a rotating cylinder. | Download Scientific Diagram - ResearchGate, accessed June 12, 2026, https://www.researchgate.net/figure/Aerodynamic-forces-on-a-rotating-cylinder_fig4_241615639
22. Airflow Past a Spinning Cylinder in 2D - YouTube, accessed June 12, 2026, <https://www.youtube.com/watch?v=2vltr16cAXM>
23. Lift of a Rotating Cylinder - NASA Glenn Research Center, accessed June 12, 2026, <https://www.grc.nasa.gov/www/k-12/airplane/cyl.html>
24. Facing the Heat Barrier: A History of Hypersonics - NASA, accessed June 12, 2026, <https://www.nasa.gov/wp-content/uploads/2023/04/sp-4232.pdf>
25. Dynamic Soaring: 545 MPH RC Planes Have No Motor - Hackaday, accessed June 12, 2026, <https://hackaday.com/2020/09/24/dynamic-soaring-545-mph-rc-planes-have-no-motor/>
26. Why We Don't Fly Like Birds. Gravity, Anatomy, and the Metaphysics... | by Boris (Bruce) Kriger | Medium, accessed June 12, 2026, <https://medium.com/@krigerbruce/why-we-dont-fly-like-birds-8207a3d8470e>
27. Autorotation of Plates. - DTIC, accessed June 12, 2026, <https://apps.dtic.mil/sti/tr/pdf/ADA058338.pdf>
28. Analysis of Spin-Rate Property for Dual-Spin-Stabilized Projectiles with Canards | Journal of Spacecraft and Rockets - Aerospace Research Central, accessed June 12, 2026, <https://arc.aiaa.org/doi/10.2514/1.A32830>
29. Prediction of Swerving Motion of a Dual-Spin Projectile with Lateral Pulsejets in Atmospheric Flight - DTIC, accessed June 12, 2026, <https://apps.dtic.mil/sti/tr/pdf/ADA441073.pdf>
30. Wind-Induced Responses of Nonlinear Angular Motion for a Dual-Spin Rocket - MDPI, accessed June 12, 2026, <https://www.mdpi.com/2226-4310/12/8/675>
31. (PDF) A review of dual-spin projectile stability - ResearchGate, accessed June 12, 2026, https://www.researchgate.net/publication/344746555_A_review_of_dual-spin_projectile_stability
32. Dynamic Response to Canard Control and Gravity for a Dual-Spin Projectile | Journal of Spacecraft and Rockets - Aerospace Research Central, accessed June 12, 2026, <https://arc.aiaa.org/doi/10.2514/1.A33485>
33. Wound Ballistics: Basics and Applications - rexresearch1, accessed June 12, 2026, <https://rexresearch1.com/EmergencySurgeryLibrary/Wound%20BallisticsBasicsApplications.pdf>
34. Aerodynamic Stabilization of a Finless Projectile with Active Nose Deflection | Journal of Spacecraft and Rockets - Aerospace Research Central, accessed June 12, 2026, <https://arc.aiaa.org/doi/10.2514/1.A35352>
35. Aerodynamic Analysis of the Self-Suspended Flare - DTIC, accessed June 12, 2026, <https://apps.dtic.mil/sti/tr/pdf/AD0740117.pdf>
36. Novel Aiming Method for Spin-Stabilized Projectiles with a Course Correction Fuze Actuated by Fixed Canards - MDPI, accessed June 12, 2026, <https://www.mdpi.com/2079-9292/8/10/1135>

37. Attitude Control Of Spinning Projectile With Single Moving Mass, accessed June 12, 2026,
https://www.researchgate.net/publication/363086657_Attitude_Control_Of_Spinning_Projectile_With_Single_Moving_Mass
38. Processings of Conference on Dynamics of Precision Gun Weapons (1st), held at Rock Island, Illinois, on January 26-27, 1977 - DTIC, accessed June 12, 2026,
<https://apps.dtic.mil/sti/tr/pdf/ADA039081.pdf>
39. Spin stabilization - Grokipedia, accessed June 12, 2026,
https://grokipedia.com/page/Spin_stabilization
40. Stability of Spinning Satellite Under Axial Thrust, Internal Mass Motion, and Damping | Journal of Guidance, Control, and Dynamics, accessed June 12, 2026,
<https://arc.aiaa.org/doi/10.2514/1.G000123>
41. US3716206A - Nutation damper - Google Patents, accessed June 12, 2026,
<https://patents.google.com/patent/US3716206A/en>
42. damping ring mdr: Topics by Science.gov, accessed June 12, 2026,
<https://www.science.gov/topicpages/d/damping+ring+mdr>
43. wobble base pairs: Topics by Science.gov, accessed June 12, 2026,
<https://www.science.gov/topicpages/w/wobble+base+pairs>
44. Missile and Spacecraft Coning Instabilities - DTIC, accessed June 12, 2026,
<https://apps.dtic.mil/sti/tr/pdf/ADA349546.pdf>
45. damped harmonic motion: Topics by Science.gov, accessed June 12, 2026,
<https://www.science.gov/topicpages/d/damped+harmonic+motion>
46. NUTATION DAMPER. A SIMPLE TWO-BODY GYROSCOPIC SYSTEM - DTIC, accessed June 12, 2026, <https://apps.dtic.mil/sti/tr/pdf/AD0259438.pdf>
47. Torsional Failure of Carbon Fiber Composite Plates Versus Stainless Steel Plates for Comminuted Distal Fibula Fractures - PubMed, accessed June 12, 2026,
<https://pubmed.ncbi.nlm.nih.gov/26755535/>
48. Fatigue Life Analysis of Titanium Torsion Spring Based on Continuous Damage Mechanics, accessed June 12, 2026, <https://www.mdpi.com/1996-1944/18/2/221>
49. Mechanical Properties and Applications of Pitch-Based Carbon Fiber Reinforced Plastics (CFRP), accessed June 12, 2026,
<https://www.nipponsteel.com/en/tech/report/nsc/pdf/5912.pdf>
50. Fatigue degradation and failure of rotating composite structures - Materials characterisation and underlying mechanisms, accessed June 12, 2026,
https://backend.orbit.dtu.dk/ws/files/7727033/ris_r_1261.pdf
51. eCopy, Inc., accessed June 12, 2026,
https://ecm-academics.plymouth.ac.uk/jsummerscales/fpcm/fpcm06/FPCM-6_14.PDF
52. Torsional Strength of Composite Drive Shaft - International Journal of Research in Advent Technology, accessed June 12, 2026,
https://ijrat.org/downloads/Conference_Proceedings/RTIME-19/RT1935.pdf
53. Torsional Buckling Optimization of Composite Drive Shafts -IDOSI, accessed June 12, 2026, <http://www.idosi.org/wasj/wasj33%283%2915/22.pdf>
54. Torsional Buckling Optimization of Composite Drive Shafts - ResearchGate, accessed June 12, 2026,

[https://www.researchgate.net/publication/280084933_Torsional_Buckling_Optimization_of Composite Drive Shfts](https://www.researchgate.net/publication/280084933_Torsional_Buckling_Optimization_of_Composite_Drive_Shfts)

55. A numerical and theoretical investigation into torsional buckling of composite driveshaft incorporating carbon nanotube - DergiPark, accessed June 12, 2026, <https://dergipark.org.tr/tr/download/article-file/3303699>