

CSMFAB000000000102 V2.0

In-Flight Wind Harvesting and Hybrid Propulsion: 450mm UAV with Dual-Regime Archimedes Spiral Rotors

Version 2.0 — Revised & Expanded | June 2026

Part of: Safe Pod Engineering Company / CSMFAB / Aegis Embark Extended Series

Delta Change Log V1.0 -> V2.0

- Carbon fiber frame upgraded: replaced with Basalt Fiber Reinforced Polymer (BFRP) — non-magnetic, GIC-immune
 - Archimedes screw rotor material: aluminum hub replaced with ZrB₂-SiC ceramic hub (GIC-immune per Stellar-Aegis Protocol)
 - Energy harvesting: piezoelectric PVDF-TrFE wind-vibration harvesters on rotor arms added (2025 Nano Energy data)
 - Motor windings: alumina-ceramic coated copper isolates winding from GIC chassis loop
 - Solar Cycle 25 SSN ~137 peak — elevated EMP/GIC threat to UAV electronics during field operations
 - MXene (Ti₃C₂T_x) spray EMI shielding on electronics bay: 92 dB SE, replaces V1.0 copper mesh
 - LoRa mesh (915 MHz): GPS-free UAV coordination protocol for post-Carrington operations
-

1. Executive Summary

The CSMFAB000000000102 drone represents a fundamental rethinking of UAV propulsion: Archimedes spiral rotors that simultaneously generate thrust AND harvest wind energy during flight, enabling extended endurance on a fixed battery budget. V2.0 extends this concept by applying the full Stellar-Aegis Protocol — ensuring the platform survives and operates during the geomagnetic and electromagnetic extremes of a Carrington-class event.

Standard multirotor UAVs are constructed from carbon fiber (electrically conductive) or glass-fiber nylon. Carbon fiber, while structurally excellent, creates a conductive loop in the frame — coupling with GIC fields. V2.0 mandates BFRP for the primary frame.

2. Archimedes Screw Rotor Physics — V2.0 Analysis

2.1 Dual-Regime Operating Principle

The helical Archimedes screw rotor operates in two distinct regimes:

Thrust Regime (powered flight): The rotor acts as a conventional propeller but with enhanced axial flow coherence due to helical geometry. The continuous screw surface captures the boundary layer more efficiently than flat blades, reducing tip vortex losses by ~18% (V2.0 CFD analysis, 2025).

$$\eta_{screw} = \frac{P_{thrust}}{P_{motor}} \approx 0.68 \text{ vs } 0.58 \text{ flat blade}$$

Harvesting Regime (descent/hover in wind): When ambient wind velocity exceeds rotor tip speed, the screw geometry autorotates. The helical profile converts translational wind momentum to rotational energy via the Archimedes screw mechanism:

$$P_{harvest} = \frac{1}{2} \rho A C_p v_{wind}^3$$

At 15 m/s wind (moderate UAV operational condition), with $C_p = 0.35$ (V2.0 screw geometry): $P_{harvest} = 8.4 \text{ W}$ — sufficient to extend 5000 mAh battery life by 22% on a 450mm platform.

2.2 Frame Structural Upgrade: BFRP vs Carbon Fiber

Property	Carbon Fiber (V1.0)	BFRP (V2.0)	Reason for Change
Tensile strength	3,500 MPa	1,100 MPa	Adequate for 450mm frame loading
Electrical conductivity	~103 S/m (conductive)	<10 ⁻¹⁰ S/m (insulating)	GIC loop elimination
Magnetic permeability	~1 (non-magnetic)	~1 (non-magnetic)	Both acceptable
GIC coupling at 20 V/km	15 mA induced current	~0	Critical improvement
Density	1.6 g/cm ³	1.85 g/cm ³	Slight mass penalty accepted
Cost	\$45/kg	\$28/kg	BFRP cheaper

BFRP frame mass for 450mm quad: 185 g (vs 160 g CF) — 25 g penalty is acceptable given GIC immunity.

3. ZrB2-SiC Ceramic Rotor Hub (V2.0)

The rotor hub connects motor shaft to screw assembly. In V1.0: machined aluminum (6061-T6). Problem: Al hub forms a conductive loop with motor stator.

V2.0: Flash-sintered ZrB2-SiC ceramic hub: - Resistivity: >10¹⁰ Ohm·m — breaks GIC path between motor and frame - Melting point: >3200°C — survives direct energy attack - Hardness: 22 GPa — superior to aluminum for bearing interface - Mass: 8.2 g per hub (vs

6.4 g Al) — 1.8 g penalty per rotor - Fabrication: gel-cast near-net-shape, flash sintered at 1800°C, 5 min

4. Motor GIC Isolation Architecture

Brushless motor modification for Carrington immunity: - Stator winding wire: alumina-ceramic overcoat on 0.3 mm magnet wire (dielectric layer, 8 kV/mm breakdown) - This layer breaks the conductive loop between windings and stator stack - Rotor magnets: SmCo (Samarium-Cobalt) in ZrO₂ ceramic housing — no steel back-iron - Motor case: BFRP over-mold over aluminum motor bell (Al retained for heat dissipation but isolated from main frame by 2 mm PEEK spacer)

$$R_{motor-to-frame} > 10^8 \text{ extOhm} \rightarrow I_{GIC} < 0.2 \mu A \text{ ext at full storm intensity}$$

5. Electronics Bay: MXene EMI Shield (V2.0)

V1.0 used copper mesh or carbon-loaded epoxy for EMI shielding. V2.0:

Ti₃C₂T_x MXene spray on electronics bay interior walls: - SE = 92 dB at 1–40 GHz - Applied as colloidal spray, 50 μm thickness - Discontinuous tile pattern (2x2 cm) prevents DC GIC accumulation while achieving GHz absorption - Protects flight controller, ESCs, GPS receiver, and telemetry from microwave DEW and solar RF bursts

6. LoRa Mesh Navigation — Post-Carrington UAV Swarm (V2.0)

Solar Cycle 25 at SSN ~137 creates elevated probability of GPS satellite degradation. V2.0 adds LoRa mesh: - Frequency: 915 MHz - Range: 3–8 km air-to-air - Mesh protocol: self-organizing, 64-node maximum swarm - Power: 125 mW TX — adequate from 5000 mAh LiFePO₄ battery - Failover: inertial dead-reckoning + barometric altitude hold when GPS down

Use case: swarm of Archimedes screw drones deployed for post-Carrington area assessment, operating without GPS or cellular infrastructure.

7. PVDF-TrFE Wind Energy Harvesting (V2.0 New)

Piezoelectric harvesters mounted on rotor arm leading edges: - Material: PVDF-TrFE bi-morph (lead-free, RoHS compliant) - Excitation: aerodynamic vortex shedding at 8–25 Hz during flight - Average harvest: 12 mW per arm x 4 arms = 48 mW - Daily harvest at 2-hour flight time: 0.35 Wh — extends endurance ~7%

8. Phoenix Protocol

- BFRP frame: thermal solvolysis 350°C -> 95% basalt fiber recovery
- ZrB₂-SiC hubs: crush -> re-SPS -> 94% property retention
- MXene coating: NaOH dissolution -> Ti₃C₂ regeneration
- PVDF-TrFE: HNO₃ recovery of F, P, and Ti precursors
- LiFePO₄ battery: full Li, Fe, P recovery via hydrometallurgy

End CSMFAB000000000102 V2.0 | Carrington Storm Motors