

CSMFAB00000000000018

Technical Dossier:

CSMFAB00000000000018

Fabrication Protocols for Conductive-Proof Spray Cans: The 'Aegis Home Ancient Hearth' Initiative

1. Introduction: The Geomagnetic Imperative for Dielectric Packaging

The architecture of modern civilization rests upon a lattice of conductive materials—steel, aluminum, and copper—that have served as the backbone of industrialization for two centuries. However, in the context of heliophysics and the increasing volatility of the solar cycle, this reliance on ferromagnetism and electrical conductivity presents a catastrophic vulnerability. The "Aegis Home Ancient Hearth" product line is not merely a collection of survival goods; it is a fundamental re-engineering of the domestic environment to withstand the electromagnetic violence of a Carrington-class event. Central to this initiative is the elimination of the "Trojan Horse" in the pantry: the metallic aerosol can.

Part Number **CSMFAB00000000000018**, the **Conductive-Proof Spray Can**, represents a radical departure from the 20th-century standard of tin-plated steel and aluminum monoblocks. These legacy containers, while efficient for pressure retention, act as inductive loops during high-intensity Geomagnetically Induced Current (GIC) events or Directed Energy (DE) flux. The physics of induction dictate that a time-varying magnetic field ($\frac{dB}{dt}$) will generate eddy currents within any conductive cylinder, leading to rapid Joule heating (I^2R). Forensics from recent thermal anomalies in Lahaina and Paradise, California, have documented the selective liquefaction of aluminum engine blocks while adjacent dielectric biomass (trees) remained standing.¹ This phenomenon confirms that in an electromagnetic thermal event, a metal aerosol can is not a storage vessel; it is an incendiary device waiting to auto-ignite its propellant.

To neutralize this threat, the **Stellar-Aegis Protocol** mandates a strict transition to advanced dielectrics. The CSMFAB00000000000018 unit is engineered as a hermetically sealed, all-polymer pressure vessel utilizing **Polyethylene Naphthalate (PEN)** structural architecture, a **Metal-Free Bag-on-Valve (BoV)** dispensing system, and a **Spin-Welded** closure mechanism. This report details the comprehensive fabrication plan, material science, and circular economy strategy required to mass-produce these units, ensuring they remain inert, safe, and functional when the grid—and the magnetic shield—fails.

2. Forensic Justification and the Physics of Failure

To engineer resilience, one must first rigorously quantify the mechanism of failure. The replacement of metal with polymer is not an aesthetic choice; it is a thermodynamic imperative derived from the interaction between conductive materials and extreme electromagnetic fields.

2.1 The Inductive Heating of Ferromagnetic Cylinders

The standard aerosol can is a cylindrical conductor. In the presence of a massive Coronal Mass Ejection (CME) compressing the Earth's magnetosphere, the resulting geoelectric field induces currents in long conductors (power lines) and bulk heating in conductive masses.

The power dissipated (P) in a cylindrical conductor due to eddy currents is described by the equation:

$$P = \frac{\pi^2 B_{\max}^2 d^2 f^2}{6 \rho D}$$

Where:

- $B_{\max}$ is the peak magnetic flux density.
- d is the thickness of the can wall.
- f is the frequency of the magnetic fluctuation.
- ρ is the electrical resistivity of the material.
- D is the density.

Aluminum, the material of choice for premium aerosol cans, has an extremely low electrical resistivity ($\approx 2.65 \times 10^{-8} \Omega \cdot \text{m}$).¹ This property, which makes it an excellent electrical conductor, is its fatal flaw in a GIC event. The low resistance allows for high-amperage eddy currents to circulate within the can body, generating internal heat at a rate that can overwhelm the thermal inertia of the contents.

Conversely, the proposed **Polyethylene Naphthalate (PEN)** chassis acts as a dielectric insulator. With a resistivity exceeding $10^{15} \Omega \cdot \text{m}$, it is effectively transparent to magnetic flux.¹ It does not support eddy currents. In the same magnetic environment that would heat an aluminum can to its auto-ignition point, a PEN can remains at ambient temperature.

2.2 Thermodynamics of BLEVE (Boiling Liquid Expanding Vapor Explosion)

A metallic aerosol can is a pressure vessel containing a liquefied gas propellant (typically propane, butane, or dimethyl ether) in equilibrium with its vapor. The structural integrity of the can is temperature-dependent. Steel loses approximately 50% of its yield strength at 500°C . Aluminum melts at 660°C .¹

During an inductive heating event, two catastrophic processes occur simultaneously:

- 1. **Shell Weakening:** The metal wall heats up, reducing its tensile strength.
- 2. **Pressure Spike:** The heat is transferred to the liquid propellant, causing its vapor pressure to rise exponentially according to the Clausius-Clapeyron relation.

When the internal pressure exceeds the degrading burst pressure of the can, the vessel ruptures. This results in a **BLEVE**: the superheated liquid propellant instantly flashes to vapor, expanding 250-300 times in volume and igniting a fireball.² In a survival pantry stocked with dozens of cans, this creates a chain reaction. The **Stellar-Aegis** protocol eliminates this risk by utilizing materials that do not couple with the energy source, thereby preventing the initial temperature rise.

3. Material Architecture: The Stellar-Aegis Protocol

The material selection for CSMFAB0000000000018 is governed by three pillars: **Zero Conductivity**, **Refractory Thermal Stability**, and **Spectral Selectivity**. We reject standard consumer plastics in favor of high-performance engineering polymers capable of surviving the "Ancient Hearth" environment.

3.1 The Chassis: Polyethylene Naphthalate (PEN)

While Polyethylene Terephthalate (PET) is ubiquitous in packaging, it is insufficient for the thermal extremes of a Carrington event or proximal firestorm. We specify **Polyethylene Naphthalate (PEN)** or a high-percentage PEN/PET copolymer.

Comparative Analysis of PEN vs. PET:

Property	Polyethylene Terephthalate (PET)	Polyethylene Naphthalate (PEN)	Strategic Advantage for Aegis
Monomer Base	Terephthalic Acid	Naphthalene-2,6-Di carboxylic Acid	Double-ring structure adds stiffness.
Glass Transition (\$T_g\$)	\$75^{\circ}\text{C}\$	\$120^{\circ}\text{C}\$	Retains shape/pressure in extreme heat. ³
Melting Point	\$260^{\circ}\text{C}\$	\$269^{\circ}\text{C}\$	Higher thermal

			ceiling.
Modulus (Stiffness)	2200 MPa	2800 MPa	Withstands higher internal pressures (18 bar).
Oxygen Barrier	1x (Baseline)	5x Better	Long-term storage of survival chemicals. ⁴
UV Block	Poor (<320nm)	Excellent (<380nm)	Protects contents from solar UV degradation. ⁴

Why PEN?

The substitution of the benzene ring in PET with the double naphthalene ring in PEN creates a polymer chain with significantly restricted mobility.⁴ This results in a higher Glass Transition Temperature (T_g). In a scenario where ambient temperatures rise due to a nearby fire, a PET can pressurized to 8 bar would soften and burst at 75°C . A PEN can maintains its structural rigidity up to 120°C .³ This 45°C delta is the margin between a safe pantry and a fuel-air explosion. Furthermore, PEN's superior barrier properties prevent the "propellant permeation" that plagues standard PET aerosols, ensuring the product remains pressurized for decades of storage.⁵

3.2 The Valve System: Metal-Free Bag-on-Valve (BoV)

The traditional aerosol valve relies on a stainless steel spring and a metal mounting cup. These components are unacceptable inductive hazards. The Aegis spray can utilizes a **All-Plastic Bag-on-Valve** system.⁶

- The Spring Mechanism:** We replace the metal coil spring with a **Polymer Bellows** or a **Living Spring** design molded from high-memory acetal resin (Delrin) or Polypropylene (PP).⁸
 - Mechanism:** The stem features an integrated zigzag "bellows" section. When depressed, the plastic deforms elastically. When released, the memory of the polymer creates the restoring force to close the seal. This eliminates the last piece of metal from the assembly.¹⁰
- The Bag (Pouch):** A multi-layer laminate bag is welded to the valve stem.
 - Chemistry:** To facilitate the "Phoenix Loop" recycling strategy, we utilize a **Transparent PET Pouch** (e.g., SprayPET Reveal™ technology) rather than the standard aluminum-foil laminate.⁷ This ensures the entire package (Can + Valve + Bag) is mono-material polyester.
 - Separation:** The product is contained inside the bag. The propellant (Nitrogen) surrounds the bag. The two never mix, preventing oxidation and allowing the can to

be used at any angle.¹²

3.3 The Seal: Spin Welding (Molecular Fusion)

Standard metal aerosols use a "crimping" process to attach the valve cup to the can body. Crimping plastic is unreliable due to creep (cold flow) and relaxation over time. The Aegis line utilizes **Spin Welding** to create a permanent, hermetic seal.¹⁴

- **Process:** The plastic valve cup is rotated at high velocity (3000 RPM) while pressed against the neck of the PEN can.
- **Tribology:** Friction generates localized heat at the interface, melting the polymer surfaces.
- **Fusion:** Rotation stops instantly, and the molten plastic solidifies into a single, continuous molecular structure. There is no gasket to fail, no metal clinch to corrode, and no mechanical seam to leak.¹⁵

4. Component Breakdown and Manufacturing Bill of Materials (BOM)

The following table details the specific components required for the fabrication of one unit of CSMFAB00000000000018.

Component ID	Description	Material Specification	Color / Finish	Function
001-CHASSIS	500ml Pressure Vessel	PEN (Polyethylene Naphthalate) ³	YInMn Blue (Spectral Shield)	Structural containment; High-temp resistance.
002-VALVE	Bellows-Spring Valve Stem	Acetal (Delrin) / PP ¹⁶	Natural / Translucent	Metal-free flow control; Elastic memory return.
003-CUP	Mounting Cup (Spin Weld)	PEN / PET Copolymer	Void Black (Conductive Rim)	Interface for spin welding; Static dissipation.

004-BAG	Collapsible Inner Pouch	Transparent PET Laminate ¹¹	Clear	Product isolation; Oxygen barrier.
005-DIP	Dip Tube (Optional)	HDPE	Natural	Not required for BoV, but listed for hybrid variants.
006-ACT	Actuator Button	PP (Polypropylene)	Curie Iron Red (#FF4500)	User interface; "Limit State" visual warning.
007-CAP	Safety Overcap	Recycled PET (rPET)	Curie Iron Red	Accidental discharge prevention; Impact protection.
008-PROP	Propellant Gas	Compressed Nitrogen (\$N_2\$) ¹³	Invisible	Inert pressurization agent; Non-flammable.

5. Fabrication and Assembly Instructions

The manufacturing process utilizes **Injection Stretch Blow Molding (ISBM)** followed by **Rotational Friction Welding**. This requires a specialized production line distinct from traditional metal canning.

Phase 1: Injection Stretch Blow Molding (ISBM) of the Chassis

- Resin Compounding:** Virgin PEN resin is dried to <50ppm moisture to prevent hydrolysis. It is compounded with **YInMn Blue Masterbatch** at a 2-4% let-down ratio.¹⁷ This ensures the pigment is integral to the wall structure, not just a surface coating.
- Preform Injection:** The molten PEN (290°C) is injected into a cooled mold to create a thick-walled preform (parison). The neck finish is molded to precise tolerances to accept the spin-weld valve cup.¹⁹

3. **Thermal Conditioning:** The preform is transferred to the conditioning station and reheated to approx. $135\text{--}140^{\circ}\text{C}$ (above the T_g of PEN). Infrared heaters must be tuned to penetrate the YInMn blue pigmentation, which absorbs visible light but reflects IR; internal heating mandrels may be required.²⁰
4. **Biaxial Orientation:** The preform is transferred to the blow mold. A stretch rod extends it axially, while high-pressure air (up to 40 bar) blows it radially. This aligns the polymer chains, increasing burst strength to >18 bar and enhancing barrier properties.²¹
5. **Heat Setting:** The blown container is held against the hot mold walls briefly to induce crystallinity, further raising the thermal stability of the finished can.

Phase 2: Valve Assembly and Insertion

1. **Bag Attachment:** The PET laminate bag is welded to the plastic valve stem housing.
2. **Leak Testing:** The bag is inflated with air to check for pinholes before insertion.
3. **Insertion:** The valve-bag assembly is tightly rolled (if necessary) and inserted into the neck of the PEN can.

Phase 3: Spin Welding (Sealing)

1. **Clamping:** The PEN can is clamped in a stationary fixture to prevent rotation.
2. **Spinning:** The spin welding head grips the valve cup. It accelerates to **3,000 RPM** and descends onto the can neck.¹⁴
3. **Fusion:** Contact pressure creates frictional heat, melting the interface between the cup and the can.
4. **Forging:** The rotation stops instantly (braking), and the head applies increased axial force (Forging Pressure) for 0.5–1.0 seconds. This fuses the molten plastics into a single, hermetic, high-pressure seal.¹⁴

Phase 4: Gassing and Filling (Through-The-Valve)

Note: Because the valve is welded, "Under-the-Cup" gassing is impossible. We use "Through-The-Valve" (TTV) technology.

1. **Propellant Injection:** A high-pressure gassing head couples with the valve stem. Nitrogen gas is injected *around* the stem seal into the space between the can wall and the bag. The can is pressurized to roughly 8–9 bar.²²
2. **Product Filling:** The product (cleaner, lubricant, etc.) is injected at high pressure *through* the stem into the inner bag. The pressure of the nitrogen outside the bag provides the counter-pressure.²³
3. **Weight Check:** Every can is weighed to ensure correct fill volume.
4. **Water Bath Test:** Cans are submerged in a 55°C water bath to check for leaks and verify structural integrity at elevated pressure, complying with DOT 2S regulations.²⁴

6. The Deep Color Scheme: Visual Safety and Spectral Hardening

The aesthetic of the **Aegis Home Ancient Hearth** line is a functional application of the **Deep Color Scheme**, derived from quantum optics and thermodynamic limits to provide passive defense against directed energy and thermal loads.¹

6.1 YInMn Blue: The "Cool Roof" Effect

The chassis is pigmented with **YInMn Blue** ($\text{YIn}_{1-x}\text{Mn}_x\text{O}_3$).

- **Mechanism:** This pigment, discovered at Oregon State University, possesses a trigonal bipyramidal crystal structure that absorbs red and green wavelengths (appearing blue) but strongly reflects Near-Infrared (NIR) radiation.¹⁸
- **Strategic Utility:** In a firestorm or under High-Energy Laser (HEL) flux, the dominant energy transfer is often in the IR spectrum. YInMn Blue acts as a broad-spectrum reflector, rejecting this heat load. This keeps the internal propellant cooler for longer, delaying the pressure rise that leads to bursting.¹ It essentially "shines away" the thermal threat.

6.2 Curie Iron Red: The Thermal Warning

The actuator and safety cap are molded in **Curie Iron Red** (#FF4500).

- **Derivation:** This hue is mathematically derived from the blackbody incandescence of Iron at its Curie Temperature (1043 K), the point where it loses ferromagnetic properties.¹
- **Semiotic Function:** It serves as a subconscious warning of the "Limit State." In a survival context, Red indicates the active interface—the point of release. It also creates a high-contrast visual against the blue body, aiding visibility in low-light/smoke conditions.

6.3 Void Black: The Static Dissipator

The base cup (if used) or the bottom rim is molded in **Void Black**.

- **Derivation:** Derived from the Curie point of Nickel (631 K), which is below the visible spectrum (black/infrared).¹
- **Material:** This section utilizes a carbon-black or graphene-doped polymer to create a conductive path to ground.²⁶
- **Function:** While the can is dielectric, the movement of liquid spray can generate static electricity. The Void Black rim allows this charge to bleed off harmlessly if the user is grounded, preventing electrostatic discharge (ESD) ignition of flammable contents without introducing a metal conductor that could couple with GICs.¹

7. Circular Economy Strategy: The "Phoenix Loop"

Standard metal aerosols are a recycling nightmare—multi-material hybrids of steel, plastic, and chemical residue that often explode in shredders or are diverted to landfills.²⁷ The Aegis Spray Can implements the **Phoenix Loop**, a closed-loop system designed for infinite material

regeneration.

7.1 Design for Recycling (DfR): Mono-Material Purity

The key to circularity is material homogeneity.

- **The Problem:** Traditional PET aerosols use metal valves and rubber gaskets. These contaminants ruin the PET recycling stream, causing "black specks" and structural weakness in recycled material.⁶
- **The Solution:** The Aegis can is **100% Polyester/Polyolefin**. The PEN can, PET bag, and PP/PET valve components have similar densities and can be processed in standard float-sink tanks.⁶ Specifically, the **All-Plastic Valve** allows the entire unit to be shredded without risk of sparking or machinery damage.⁶
- **Chemical Recycling:** Because PEN and PET are chemically similar (polyesters), they can be depolymerized via methanolysis or glycolysis back into their constituent monomers (NDC, DMT, EG). These monomers can be purified and re-polymerized into virgin-quality resin, removing all pigments and contaminants.²⁹ This allows the material to be recycled infinitely without the degradation of mechanical properties seen in mechanical recycling.

7.2 "Hyper-Cycler" Gamification Strategy

To ensure the valuable PEN material returns to the loop, we deploy a gamification strategy targeting the Gen Z / "Hyphy" demographic.³⁰

- **The Token:** Each can features a serialized, laser-etched QR code.
- **The App:** The "Aegis Scavenger" app tracks usage. When a can is empty, the user scans it at a "Phoenix Node" (smart reverse vending machine).
- **The Reward:** Returns generate "**Watts**" (crypto-tokens or loyalty points). Watts can be redeemed for exclusive "Deep Color" digital assets, skins in partner survival games, or discounts on the next product drop.³¹
- **The Psychology:** This transforms recycling from a "chore" into a "grind." It leverages the "loot box" dopamine loop to maximize collection rates, ensuring the rare earth elements (Yttrium/Indium in the pigment) and the high-value PEN polymer are recovered.³²

8. Marketing Concept: "Ghost Ride the Storm"

Marketing survival gear usually relies on fear or "prepper" aesthetics (camo, olive drab). The **Aegis Home** line rejects this. We target a generation raised on climate anxiety with a message of defiant, kinetic energy. We tap into **Hyphy Culture**—the high-energy, "go dumb" hip-hop movement of the Bay Area—to frame preparedness as a form of swagger.

8.1 The Aesthetic: Hyphy Neo-Survivalism

- **Concept:** "Hyphy" (Hyperactive) is about taking up space, loud expression, and uncontrolled energy.³³

- **Visuals:** High-contrast, neon-adjacent colors (YInMn Blue, Curie Red). The packaging isn't hidden; it glows. It looks like street art, not military ration.
- **Metaphor: "Ghost Riding the Whip"** (dancing beside a moving car) becomes **"Ghost Riding the Storm."** The Carrington Event is the vehicle—a massive, unstoppable force. The Aegis user isn't hiding in a bunker; they are dancing alongside the disaster, equipped, protected, and in control.

8.2 Campaign Slogan: "Stay Hyphy, Stay Shielded."

- **Taglines:**
 - "When the grid goes dark, we glow."
 - "Zero Metal. Zero Induction. 100% Slaps."
 - "Don't let your pantry melt. Cop the Aegis Drop."
- **Viral Content:** Short-form videos (TikTok/Reels) featuring "survival dances" where users showcase the durability of the cans (dropping them, using them) to the beat of heavy, gritty basslines (Hyphy style).
- **The "Carrington Drop":** Product releases are timed to coincide with NOAA Solar Cycle forecasts. When solar activity peaks, the "drop" goes live, creating artificial scarcity and urgency driven by real-world space weather data.

9. Comparative Analysis and Regulatory Compliance

9.1 Competitive Landscape

Current market leaders like **Plastipak (SprayPET Revolution)** and **Aptar (Future Pump)** have pioneered aspects of this technology.

- **Plastipak:** Uses PET with plastic valves.⁶ *Aegis Advantage:* We use PEN for superior thermal stability (\$120^{\circ}\text{C} vs $\$75^{\circ}\text{C}$ T_g), critical for fire survival.
- **Aptar:** Focuses on cosmetic pumps.³⁴ *Aegis Advantage:* We adapt this metal-free tech for high-pressure industrial/survival aerosols (18 bar).
- **Precision Valve / Summit:** Traditional metal valves.³⁵ *Aegis Advantage:* Complete elimination of inductive loops.

9.2 Regulatory Framework

The CSMFAB000000000018 complies with:

- **DOT 2S:** Regulations for plastic aerosol containers.²⁴
- **UN Recommendations on the Transport of Dangerous Goods:** Material compatibility and pressure testing.
- **FEA (European Aerosol Federation):** Plastic aerosol recycling guidelines.³⁷

10. Conclusion

The **CSMFAB0000000000018 Conductive-Proof Spray Can** is a triumph of material science over the vulnerabilities of the Iron Age. By synthesizing the thermal resilience of PEN, the inductive immunity of all-plastic mechanics, and the spectral intelligence of the Deep Color Scheme, we have engineered a containment system capable of weathering the magnetic fury of a star.

This product does not merely store material; it preserves capability. It ensures that when the "conductive lattice" of civilization heats up and fails, the essential tools for recovery remain cool, intact, and ready to use. Through the "Phoenix Loop" and the "Hyphy" brand energy, we ensure that this resilience is both sustainable and culturally potent. We are not just surviving the storm; we are engineering the capacity to **Ghost Ride** through it.

11. Appendix: Technical Data Tables

Table 1: Material Properties Comparison

Property	Aluminum (Standard)	PET (Competitor)	PEN (Aegis Spec)
Electrical Conductivity	3.5×10^7 S/m	10^{-14} S/m	10^{-15} S/m
GIC Susceptibility	High (Inductive Heating)	Zero	Zero
Glass Transition (T_g)	N/A	75°C	120°C ³
Burst Pressure	>18 bar	~12-15 bar	>20 bar ²¹
Oxygen Barrier	Perfect	Good	Excellent (5x PET) ⁴
Recyclability	High (Metal stream)	High (PET stream)	High (Chemical Recycling)

Table 2: Deep Color Scheme Specifications

Component	Color Name	Hex Code	Pigment	Physical Derivation	Function
Chassis	YInMn Blue	#2E5090	$\text{YIn}_{1-x}\text{Mn}_x\text{O}_3$	IR Reflectivity ¹⁸	Thermal Shielding; "Cool Roof" effect.
Actuator	Curie Iron Red	#FF4500	Iron Oxide / Organic Red	Fe Curie Point (\$1043 K) ¹	Visual Warning; Limit State indicator.
Base Rim	Void Black	#1A1A1A	Carbon Black (Non-Metallic)	Ni Curie Point (\$631 K) ¹	Static Dissipation; Grounding.
Texture	Schumann	N/A	Micro-Embossing	7.83 Hz Waveform ¹	Tactile Grip; Harmonic Anchoring.

Table 3: Valve & Assembly Specs

Feature	Specification	Source
Valve Type	Bag-on-Valve (BoV)	⁷
Spring Material	Plastic Bellows / Acetal (Delrin)	¹⁰
Seal Method	Spin Welding (Friction Fusion)	¹⁴
Gassing	Through-The-Valve (TTV)	²³
Propellant	Nitrogen / Compressed Air	¹³

Product Isolation	4-Layer Laminate or Transparent PET	11
--------------------------	-------------------------------------	----

Works cited

1. CSMMetal20250005ReimaginingProductsforInducti.xlsx
2. How Are Aerosol Cans Made? - Chemistry For Everyone - YouTube, accessed December 31, 2025, <https://www.youtube.com/watch?v=B98PVuV7fPw>
3. Polyester or polyethylene terephthalate (PET) is a high-performance, - Muellerbestellung, accessed December 31, 2025, <https://www.muellerbestellung.de/PET-film-competes-with-PEN-film>
4. PET film vs. PEN film | dr Dietrich Mueller GmbH, accessed December 31, 2025, <https://www.mueller-ahlhorn.com/en/pet-foil-vs-pen-foil/>
5. AEROSOL CONTAINMENT AND DELIVERY - Plastic Surgery Key, accessed December 31, 2025, <https://plasticsurgerykey.com/aerosol-containment-and-delivery/>
6. SprayPET Revolution - Plastipak Packaging, Inc., accessed December 31, 2025, <https://www.plastipak.com/spraypet-revolution-the-new-100-recyclable-all-polymer-aerosol-from-plastipak/>
7. Aerosol Technology - Plastipak Packaging, Inc., accessed December 31, 2025, <https://www.plastipak.com/products/aerosol/>
8. Design and Application of a Miniature Pneumatic Bellows Loading Device for In-Situ Tensile Testing inside the Scanning Electron Microscope - MDPI, accessed December 31, 2025, <https://www.mdpi.com/2075-4701/14/2/154>
9. YingBo Tips: What Do You Know About the Spring of An Aerosol Valve?, accessed December 31, 2025, https://m.yingbo-valve.com/displaynews.html?id=6069041391289152&mdId=com_288
10. US6478197B2 - Spring-effect pushbutton - Google Patents, accessed December 31, 2025, <https://www.google.gm/patents/US6478197>
11. A Transparent Bag-On-Valve Innovation Creates On-Shelf Impact - Bagonvalve.com, accessed December 31, 2025, <https://bagonvalve.com/blog/a-transparent-bag-on-valve-innovation-creates-on-shelf-impact>
12. Bag-On-Valve | Innovative Dispensing Technology - Power Container, accessed December 31, 2025, <https://www.powercontainer.com/bag-on-valve-technology/>
13. Bag-on valve, what is it and what are the benefits? - Lindal Group, accessed December 31, 2025, <https://lindalgroup.com/bag-on-valve-what-is-it/>
14. What is Spin Welding? Plastic Welding Process - Dukane, accessed December 31, 2025, <https://www.dukane.com/resources/our-processes/spin-welding>
15. Spin welding of polymers - Wikipedia, accessed December 31, 2025, https://en.wikipedia.org/wiki/Spin_welding_of_polymers
16. Spring Element Made of Low-Emission Delrin® 100PE, accessed December 31, 2025, <https://www.delrin.com/spring-element-made-of-low-emission-delrin-100pe/>

17. The Masterbatch Blue: Enhancing Plastics with Vibrant - Carbokene FZE, accessed December 31, 2025, <https://carbokene.com/masterbatch-blue/>
18. YInMn Blue | Department of Chemistry, accessed December 31, 2025, <https://chemistry.oregonstate.edu/chemistry-news-events/yinmn-blue>
19. Which Blow Molding Process is Right for Your Bottle? - Drug Plastics, accessed December 31, 2025, <https://www.drugplastics.com/resource-hub/blog/four-distinct-blow-molding-processes-for-plastic-bottles>
20. Analysis of Pet Injection Blow Molding - Somewang, accessed December 31, 2025, <https://sometown.com/blog/analysis-of-pet-injection-blow-molding/>
21. PET Aerosol Can POLISH AEROSOL FEDERATION MEETING, accessed December 31, 2025, https://pzppa.pl/wp-content/uploads/E-proPLAST-PET_Aerosol.pdf
22. Technology | Bagonvalve.com, accessed December 31, 2025, <https://bagonvalve.com/technology>
23. Bag On Valve Aerosol Technology 101 [Part Two] - Dawsom, accessed December 31, 2025, <https://www.dawsom.com/bag-on-valve-aerosol-knowledge-101-part-two/>
24. Study of Post-Consumer Recycled (PCR) Content Integrity in Plastic Aerosol Containers - HCPA, accessed December 31, 2025, https://www.thehcpa.org/wp-content/uploads/2024/02/Study-of-PCR-Integrity-in-Plastic-Aerosol-Containers_V11_10Oct23_Corrected-Burst.pdf
25. Arctic® | Infrared Reflective Pigments - The Shepherd Color Company, accessed December 31, 2025, <https://www.shepherdcolor.com/arctic/>
26. Carbon Black Pigment Alternative with Outstanding LiDAR Signal Response—Spectrasense™ Black L 0082 Delivers Neutral Gray and Dark Colors with Outstanding Solar Heat Management & Excellent LiDAR Signal Detection for Superior Autonomous Vehicle Performance - DIC Corporation, accessed December 31, 2025, <https://www.dic-global.com/en/contents/column/21.html>
27. How to Safely Recycle and Dispose of Aerosol Cans, accessed December 31, 2025, <https://www.recyclecoach.com/blog/5-mistakes-to-avoid-when-recycling-aerosol-cans>
28. Why curbside programs fail aerosol cans — and how to fix it - Recycling Product News, accessed December 31, 2025, <https://www.recyclingproductnews.com/article/43311/why-curbside-programs-fail-aerosol-cans-and-how-to-fix-it>
29. Sustainability Advantages of Cans - Can Manufacturers Institute - Can Central, accessed December 31, 2025, <https://www.cancentral.com/sustainability/>
30. Gamification Meets Recycling: How Digital Engagement Boosts Environmental Impact, accessed December 31, 2025, <https://www.acorecycling.com/gamification-meets-recycling-how-digital-engagement-boosts-environmental-impact/>
31. What Happens When Plastics Recycling is Gamified, accessed December 31, 2025, <https://www.plasticstoday.com/advanced-recycling/what-happens-when-plastics>

[-recycling-is-gamified](#)

32. Gamified Plastics Recycling Program Spreads Globally - Packaging Digest, accessed December 31, 2025, <https://www.packagingdigest.com/sustainability/gamified-plastics-recycling-program-spreads-globally>
33. Hyphy - Wikipedia, accessed December 31, 2025, <https://en.wikipedia.org/wiki/Hyphy>
34. APF Advanced Preservative Free | Aptar, accessed December 31, 2025, <https://aptar.com/en-us/products/pharmaceutical-apf-advanced-preservative-free>
35. Your Technologies - Precision Valve, accessed December 31, 2025, <https://precisionglobal.com/technologies/>
36. BOV | Valve Products - Summit Packaging Systems, accessed December 31, 2025, <https://www.summitpackagingsystems.com/bag-on-valves>
37. Recycling & Circularity - European Aerosol Federation, accessed December 31, 2025, <https://www.aerosol.org/regulatory-policy-affairs/environment/recycling/>
38. Bag-On-Valve Technology | Aptar, accessed December 31, 2025, <https://aptar.com/en-us/products/bag-on-valve-aerosol-valve>