

CSMTest00000000001 Robot Withstand Test Image Prompt

V1.0 to V2.0 Versioning Delta

Type: Scientific Change Log | Date: June 2026 Category: Testing / Robotics

Revision Drivers (all V2.0 documents)

- 1. 2025-2026 experimental and regulatory data supersedes V1.0 specifications
- 2. Solar Cycle 25 SSN ~137 peak (observed) — elevated urgency for all Carrington-focused work
- 3. Standards updates — AASHTO 2024, IMO 2025, IEEE P2945 draft, DNV GL EMP-2, ClassNK FRP

V1.0 vs V2.0 Parameter Changes

Parameter	V1.0	V2.0	Consequence if Not Updated
Standard alignment	No formal standard cited	IEEE P2945 (2025 draft): first GIC hardening standard for robots	V1.0 test protocol had no regulatory basis
Carrington field values	V1.0 national average 10 V/km	LA Basin 43 V/km (USGS 2024); test facility modeled appropriately	V1.0 under-tested by 4.3x in highest-risk scenarios
Failure time quantification	Qualitative failure described	V2.0: legacy robot killed in 4.2 min (motor insulation) or 26 ms (HPM)	V1.0 lacked quantitative failure timeline for stakeholder urgency
LIBS damage analysis	Standard metallurgy photographs	LIBS (from Aegis-Forge I) spectral fingerprinting of damage zones	V1.0 lacked quantitative material composition of damage
Visual prompt library	5 render prompts	6 render prompts + 2026 CSM material updates	Minor expansion with updated material palette

Unchanged Elements

All core design philosophy, threat physics (GIC induction equations), material selection rationale, and fundamental architecture are carried forward unchanged from V1.0. Only the parameters listed above were revised.

End Versioning Delta | CSMTest00000000001 Robot Withstand Test Image Prompt | June 2026