Exploring the saturation of the MRI via weakly nonlinear analysis

Susan E. Clark | NSF Graduate Fellow, Columbia University

Jeffrey S. Oishi | SUNY Farmingdale, AMNH

Mordecai-Mark Mac Low | AMNH

The MRI evolves in stages.



The MRI evolves in stages.



The MRI evolves in stages.



The MRI evolves in stages.



We use a thin-gap Taylor Couette setup.



We solve the non-ideal MRI equations.

momentum

$$\partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho}\nabla P - \nabla \Phi + \frac{1}{\rho}\left(\mathbf{J} \times \mathbf{B}\right) - 2\Omega \times \mathbf{u} - \Omega \times \left(\Omega \times \mathbf{r}\right) + \nu \nabla^2 \mathbf{u}$$

induction

$$\partial_t \mathbf{B} = \nabla \times \left(\mathbf{u} \times \mathbf{B}\right) + \eta \nabla^2 \mathbf{B}$$

constraints

$$\nabla \cdot \mathbf{u} = 0$$

$$\nabla \cdot \mathbf{B} = 0$$

We solve the non-ideal MRI equations.

momentum

$$\partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho} \nabla P - \nabla \Phi + \frac{1}{\rho} (\mathbf{J} \times \mathbf{B}) - 2\Omega \times \mathbf{u} - \Omega \times (\Omega \times \mathbf{r}) + \nu \nabla^2 \mathbf{u}$$

kinematic viscosity

induction

$$\partial_t \mathbf{B} = \nabla \times (\mathbf{u} \times \mathbf{B}) + \eta \nabla^2 \mathbf{B}$$

magnetic resistivity

constraints

$$\nabla \cdot \mathbf{u} = 0$$

$$\nabla \cdot \mathbf{B} = 0$$

We nondimensionalize and perturb the nonlinear MRI equations.

$$\Omega(r) \propto \Omega_0 \left(\frac{r}{r_0}\right)^{-q}$$

shear parameter

$$\mathbf{B} = B_0 \hat{\mathbf{z}}$$

background field

$$Re \equiv \frac{\Omega_0 L^2}{\nu}$$

Reynolds number

$$Rm \equiv \frac{\Omega_0 L^2}{\eta}$$

magnetic Reynolds number

$$\beta \equiv \frac{8\pi \rho_0 \Omega_0^2 L^2}{B_0^2}$$

plasma beta

We work in terms of flux and stream functions.

$$\mathbf{V} = \begin{bmatrix} \mathbf{\Psi} \\ \mathbf{u_y} \\ \mathbf{A} \\ \mathbf{B_y} \end{bmatrix}$$

We work in terms of flux and stream functions.

momentum

$$\partial_t \nabla^2 \Psi = \frac{2}{\beta} B_0 \partial_z \nabla^2 A + 2\partial_z u_y + \frac{2}{\beta} J\left(A, \nabla^2 A\right) - J\left(\Psi, \nabla^2 \Psi\right) + \frac{1}{Re} \nabla^4 \Psi$$

$$\partial_t u_y = \frac{2}{\beta} B_0 \partial_z B_y - (2-q)\Omega_0 \partial_z \Psi + \frac{2}{\beta} J\left(A, B_y\right) - J\left(\Psi, u_y\right) + \frac{1}{Re} \nabla^2 u_y$$

induction

$$\partial_t A = B_0 \partial_z \Psi + J\left(A, \Psi\right) + \frac{1}{Rm} \nabla^2 A$$

$$\partial_t B_y = B_0 \partial_z u_y - q\Omega_0 \partial_z A + J\left(A, u_y\right) - J\left(\Psi, B_y\right) + \frac{1}{Rm} \nabla^2 B_y$$

We work in terms of flux and stream functions.

momentum

viscous

$$\partial_t \nabla^2 \Psi = \frac{2}{\beta} B_0 \partial_z \nabla^2 A + 2\partial_z u_y + \frac{2}{\beta} J\left(A, \nabla^2 A\right) - J\left(\Psi, \nabla^2 \Psi\right) + \boxed{\frac{1}{Re} \nabla^4 \Psi}$$

$$\partial_t u_y = \frac{2}{\beta} B_0 \partial_z B_y - (2-q)\Omega_0 \partial_z \Psi + \frac{2}{\beta} J\left(A, B_y\right) - J\left(\Psi, u_y\right) + \boxed{\frac{1}{Re} \nabla^2 u_y}$$

induction

$$\partial_t A = B_0 \partial_z \Psi + J\left(A, \Psi\right) + \boxed{\frac{1}{Rm} \nabla^2 A}$$

resistive

$$\partial_t B_y = B_0 \partial_z u_y - q\Omega_0 \partial_z A + J\left(A, u_y\right) - J\left(\Psi, B_y\right) + \boxed{\frac{1}{Rm} \nabla^2 B_y}$$

We work in terms of flux and stream functions.

momentum

viscous

$$\partial_t \nabla^2 \Psi = \frac{2}{\beta} B_0 \partial_z \nabla^2 A + 2\partial_z u_y + \frac{2}{\beta} J\left(A, \nabla^2 A\right) - J\left(\Psi, \nabla^2 \Psi\right) + \boxed{\frac{1}{Re}\nabla^4 \Psi}$$

$$\partial_t u_y = \frac{2}{\beta} B_0 \partial_z B_y - \boxed{(2-q)\Omega_0 \partial_z \Psi} + \frac{2}{\beta} J\left(A, B_y\right) - J\left(\Psi, u_y\right) + \boxed{\frac{1}{Re}\nabla^2 u_y}$$

shear

induction

$$\partial_t A = B_0 \partial_z \Psi + J\left(A, \Psi\right) + \boxed{\frac{1}{Rm}\nabla^2 A}$$

resistive

$$\partial_t B_y = B_0 \partial_z u_y - \boxed{q\Omega_0 \partial_z A} + J\left(A, u_y\right) - J\left(\Psi, B_y\right) + \boxed{\frac{1}{Rm}\nabla^2 B_y}$$

We work in terms of flux and stream functions.

momentum

nonlinear

viscous

$$\partial_t \nabla^2 \Psi = \frac{2}{\beta} B_0 \partial_z \nabla^2 A + 2\partial_z u_y + \boxed{\frac{2}{\beta} J\left(A, \nabla^2 A\right) - J\left(\Psi, \nabla^2 \Psi\right)} + \boxed{\frac{1}{Re} \nabla^4 \Psi}$$

$$\partial_t u_y = \frac{2}{\beta} B_0 \partial_z B_y - \boxed{(2-q)\Omega_0 \partial_z \Psi} + \boxed{\frac{2}{\beta} J\left(A, B_y\right) - J\left(\Psi, u_y\right)} + \boxed{\frac{1}{Re} \nabla^2 u_y}$$

shear

induction

resistive

$$\partial_t A = B_0 \partial_z \Psi + \boxed{J\left(A, \Psi\right)} + \boxed{\frac{1}{Rm} \nabla^2 A}$$

$$\partial_t B_y = B_0 \partial_z u_y - \boxed{q\Omega_0 \partial_z A} + \boxed{J\left(A, u_y\right) - J\left(\Psi, B_y\right)} + \boxed{\frac{1}{Rm} \nabla^2 B_y}$$

Weakly nonlinear analysis explores behavior at the margin of instability.



Weakly nonlinear analysis explores behavior at the margin of instability.



Tune the most unstable mode just over the threshold of instability.



Tune the most unstable mode just over the threshold of instability.

small parameter

$$\epsilon^2 \equiv 1 - B_0$$



Multiscale analysis tracks the evolution of fast and slow variables.

$$Z \equiv \epsilon z$$



We choose an ansatz state vector form.

$$\mathbf{V} = \alpha\left(Z, T\right) \mathrm{V}\left(x\right) e^{ik_c z}$$



We choose an ansatz state vector form.

x dependence

$$\mathbf{V} = \alpha\left(Z,T\right)\mathrm{V}\left(x\right)e^{ik_c z}$$

vertical periodicity

amplitude function



The fluid quantities are expanded
in a perturbation series.

$$\mathbf{V} = \epsilon \mathbf{V_1} + \epsilon^2 \mathbf{V_2} + \epsilon^3 \mathbf{V_3} + ...$$

Dedalus is a general-purpose spectral code.



Spectrally solve the most unstable mode of the linear MRI.



We solve each term in the expanded equations at each order.



The removal of secular terms yields solvability criteria.



The removal of secular terms yields solvability criteria.



The result is an amplitude equation for the most unstable mode.

$$\partial_T \alpha = -b\partial_Z \alpha - c\alpha \left|\alpha^2\right| + h\partial_Z^2 \alpha + gik_c^3 \alpha$$

The result is an amplitude equation
for the most unstable mode.

diffusion term

$$\partial_T \alpha = -b\partial_Z \alpha - c\alpha \left|\alpha^2\right| + h\partial_Z^2 \alpha + gik_c^3 \alpha$$

nonlinear term

linear growth

The result is an amplitude equation for the most unstable mode.

diffusion term

?

$$\partial_T \alpha = -b\partial_Z \alpha - c\alpha\left|\alpha^2\right| + h\partial_Z^2 \alpha + gik_c^3 \alpha$$

linear growth

nonlinear term

First order velocity perturbations



Second order velocity perturbations



First and second order velocity perturbations



First order magnetic field perturbations



Second order magnetic field perturbations

two OOM smaller!



First and second order magnetic field perturbations



Future work:

relax thin gap approximation
helical MRI
explore parameter space
comparison to experiment