1 Basic Equations 1

## 1 Basic Equations

The so-called Stokes stream function, used in axisymmetric situations, is given by

$$\mathbf{u} = \begin{bmatrix} \frac{1}{r} \partial_z \psi \, \hat{\mathbf{r}} \\ u_{\phi} \, \hat{\phi} \\ -\frac{1}{r} \partial_r \psi \, \hat{\mathbf{z}} \end{bmatrix}; \tag{1}$$

here we define A in the same way.

Using the definitions in

$$\begin{split} \partial_t \left[ \frac{1}{r} \left( \nabla^2 \psi - \frac{2 \partial_r \psi}{r} \right) \right] + \frac{1}{r^2} J(\psi, \nabla^2 A - \frac{2 \partial_r \psi}{r}) &= \frac{\partial_z A}{r^3} \left( \nabla^2 A - \frac{2 \partial_r A}{r} \right) \\ &+ \frac{1}{r} J \left( A, \frac{1}{r} \left( \nabla^2 A - \frac{2 \partial_r A}{r} \right) \right) - \frac{2 B_\phi \partial_z B_\phi}{r} \\ &+ \nu \left\{ \nabla^2 \left[ \frac{1}{r} \left( \nabla^2 \psi - \frac{2 \partial_r \psi}{r} \right) \right] - \frac{1}{r^2} \left( \nabla^2 \psi - \frac{2 \partial_r \psi}{r} \right) \right\} \end{split}$$
(2)

$$\partial_t u_\phi + J(\psi, u_\phi) + \frac{u_\phi \partial_r \psi}{r^2} = J(B_\phi, A) - \frac{B_\phi \partial_z A}{r^2} + \nu \left( \nabla^2 u_\phi - \frac{u_\phi}{r} \right)$$
 (3)

$$\partial_t A = \frac{1}{r^2} J(\psi, A) - \eta \left[ \frac{1}{r} \left( \nabla^2 A - \frac{2\partial_r A}{r} \right) \right]$$
 (4)

Susan gets:

$$\partial_t A = \frac{1}{r} J(A, \Psi) + \frac{1}{Rm} \left[ -\frac{1}{r} \partial_r A + \partial_r^2 A + \partial_z^2 A \right]$$
 (5)

$$\partial_t B_\phi = \frac{1}{r} J(A, u_\phi) + \frac{1}{r} J(B_\phi, \psi)$$

$$+ \frac{1}{r^2} B_\phi \partial_z \psi - \frac{1}{r^2} u_\phi \partial_z A + \eta \left( \nabla^2 B_\phi - \frac{1}{r^2} B_\phi \right)$$
 (6)

## 2 Recovery of Narrow Gap Equations

## A Cylindrical derivatives

Everything here follows http://farside.ph.utexas.edu/teaching/336L/Fluidhtml/node177.html#scyl.

For a scalar field  $\psi$ ,

$$\nabla \psi = \frac{\partial \psi}{\partial r} \hat{\mathbf{r}} + \frac{1}{r} \frac{\partial \psi}{\partial \phi} \hat{\phi} + \frac{\partial \psi}{\partial z} \hat{\mathbf{z}}.$$
 (7)

However, for a vector field  $\mathbf{u}$ ,

$$\nabla \cdot \mathbf{u} = \frac{1}{r} \frac{\partial (ru_r)}{\partial r} + \frac{1}{r} \frac{\partial u_\phi}{\partial \phi} + \frac{\partial u_z}{\partial z}$$
 (8)

and

$$\nabla \times \mathbf{u} = \left(\frac{1}{r} \frac{\partial u_z}{\partial \phi} - \frac{\partial u_\phi}{\partial z}\right) \hat{\mathbf{r}} + \left(\frac{\partial u_r}{\partial z} - \frac{\partial u_z}{\partial r}\right) \hat{\phi} + \left(\frac{1}{r} \frac{\partial (ru_\phi)}{\partial r} - \frac{1}{r} \frac{\partial u_r}{\partial \phi}\right) \hat{\mathbf{z}}. \tag{9}$$

We also need the  $\phi$  component of the convective derivative  $\mathbf{u} \cdot \nabla \mathbf{u}$ ,

$$\left[\mathbf{u} \cdot \nabla \mathbf{u}\right]_{\phi} = \mathbf{u} \cdot \nabla u_{\phi} + \frac{u_r u_{\phi}}{r},\tag{10}$$

and finally, the vector Laplacian,

$$(\nabla^2 \mathbf{u})_r = \nabla^2 u_r - \frac{u_r}{r^2} - \frac{2}{r^2} \frac{\partial u_\phi}{\partial \phi}$$
 (11)

$$(\nabla^2 \mathbf{u})_{\phi} = \nabla^2 u_{\phi} + \frac{2}{r^2} \frac{\partial u_r}{\partial \phi} - \frac{u_{\phi}}{r^2}$$
 (12)

$$(\nabla^2 \mathbf{u})_z = \nabla^2 u_z,\tag{13}$$

where  $\nabla$  on the vector components is given by equation (7).