



Submittal Data Sheet

Daikin 1-Ton, Multi-Zone Multi-Position Air Handler Indoor Unit
CMXV12AVJUA

FEATURES

- 7 mm evaporator coil tube size
- Variable-speed ECM blower motor
- Compatible with Daikin One+ & Daikin One Touch Controls - No adaptors needed to wire controls
- Constant CFM over wide range of static pressure conditions independent of duct system
- All-Aluminum evaporator coil
- Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193
- Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193
- 3 kW – 10 kW electric heater kits
- Horizontal or vertical configuration capabilities
- 21" depth for easier attic access
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Screw-less sides and back helps to reduce condensation when installed in humid locations



BENEFITS

- 12-year limited parts and compressor warranty with online registration
- 5-year limited parts warranty for commercial applications
- Built in refrigeration detection system



Submittal Data Sheet

Daikin 1-Ton, Multi-Zone Multi-Position Air Handler Indoor Unit
CMXV12AVJUA

ELECTRICAL		PIPING	
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.		Gas Connection: (inch)	1/2
		Liquid Connection: (inch)	1/4
		Drain Connection: (inch)	3/4


SPECIFICATIONS			
COOLING - Airflow Rate (cfm):		COOLING - Sound Level (dBA):	
High:	400	High:	
Med:	340	Med:	
Low:	280	Low:	
SuperLow:	250	SuperLow:	
Dimensions (HxWxD) (in):		Net Weight (lb):	
45 x 17.7 x 21			

Submittal Data Sheet

Daikin 1-Ton, Multi-Zone Multi-Position Air Handler Indoor Unit

CMXV12AVJUA

DIMENSIONAL DRAWING





Submittal Data Sheet

Daikin 1-Ton, Multi-Zone Multi-Position Air Handler Indoor Unit
CMXV12AVJUA

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
No Accessories specified.		