



Submittal Data Sheet

Daikin 0.75-Ton, Floor Mount Indoor Unit
FVXV09AVJUW9





Submittal Data Sheet

Daikin 0.75-Ton, Floor Mount Indoor Unit
FVXV09AVJUW9

ELECTRICAL		PIPING	
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.		Gas Connection: (inch)	3/8
		Liquid Connection: (inch)	1/4
		Drain Connection: (inch)	3/4

SPECIFICATIONS			
COOLING - Airflow Rate (cfm):		COOLING - Sound Level (dBA):	
High:	297	High:	39
Med:	265	Med:	36
Low:	201	Low:	30
SuperLow:	173	SuperLow:	26
HEATING - Airflow Rate (cfm):		HEATING - Sound Level (dBA):	
High:	321	High:	40
Med:	261	Med:	35
Low:	219	Low:	31
SuperLow:	191	SuperLow:	26
Dimensions (HxWxD) (in):		Net Weight (lb):	
23-5/8 x 29-1/2 x 9-3/8		40	


Submittal Data Sheet

Daikin 0.75-Ton, Floor Mount Indoor Unit

FVXV09AVJUW9

DIMENSIONAL DRAWING

NOTES
1) THE → MARK SHOWS THE PIPING DIRECTION.
2) UNIT: Inch (mm)





Submittal Data Sheet

Daikin 0.75-Ton, Floor Mount Indoor Unit
FVXV09AVJUW9

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
BRC073A6	Wired Remote Controller (Requires Additional Wire Harness)	No
DCS302C71	Centralized Controller	No
DST301BA61	Schedule Timer	No
KAF970A46	Titanium apatite photocatalytic air-purifying filter WITHOUT frame	No
KER087A41	S21 conversion connector	No
KRP928BB2S	RA Interface Adaptor for DIII-Net -	No