



Preparing multiplex immunofluorescence data in QuPath for QXYCell

QuPath 0.7 workflow for platform-independent multiplex immunofluorescence data

Applies to: QuPath 0.7.0 and QXYCell 0.1 alpha

Purpose: create the measurement, annotation, segmentation, and classifier assets that QXYCell can validate and import.

QXYCell is platform-independent. It does not require COMET data or COMET-specific background subtraction. A multichannel OME-TIFF can be used when QuPath reads it correctly and the checks below are satisfied. Image correction, registration, unmixing, background removal, and marker QC remain the responsibility of the acquisition or preprocessing workflow.

What QXYCell needs

The only unconditional input is a QuPath cell measurement table. Other exports enable specific QXYCell features.

Asset	Needed for	QXYCell requirement
Cell measurements (.csv or .tsv)	Every run	Filename contains measurement, or is exactly detections.csv/detections.tsv
Annotation GeoJSON	Sample/region labels and exclusions	One file per image; filename stem must match the measurement table's Image value
Cell GeoJSON	Cell boundary geometry	Contains QuPath cell objects and their Object IDs
Single-measurement classifier JSON	Creating a threshold table	Simple classifier JSONs saved anywhere below the export folder
Filled threshold table	Applying marker positivity	Reviewed TSV/CSV with per-image threshold values

QXYCell discovers files recursively, so the assets may be arranged in subfolders. Do not put an old QXYCell output folder inside the new export folder.

1. Verify every image before analysis

Perform these checks in QuPath for every project image. Do not assume that OME-TIFF metadata is complete or correct.

- The intended image and series opens without an image-reader error.
- The image is fluorescence, not a rendered RGB snapshot.
- Width, height, channel count, bit depth, z-slices, and timepoints match the intended acquisition.

- Each channel has the expected marker/fluorophore identity and visible biological signal.
- Channels are spatially registered; obvious inter-channel displacement has been corrected upstream.
- Blank, saturated, corrupted, or unexpectedly clipped channels have been investigated.
- The **Image** tab reports pixel width and pixel height in micrometres (µm).
- Pixel width and height are plausible for the microscope and acquisition settings.
- Pixel width equals pixel height. QXYCell currently supports square pixels only.
- The pixel size selected for QXYCell is recorded with the analysis.

QuPath reads pixel calibration from the image metadata when possible, but the metadata can be absent or wrong. Pixel size is the important physical scale; nominal objective magnification is not a substitute.

Choose the QXYCell pixel size

QXYCell's default is **0.28 µm/pixel**. Use the default only when the verified QuPath pixel size is 0.28 µm in both directions.

For another square-pixel size, pass the verified value when QXYCell imports the data:

```
adata = qxy.run(
    "/path/to/qupath_export",
    pixel_size_um=0.325,
)
```

Command-line equivalent:

```
qxycell run /path/to/qupath_export --pixel-size-um 0.325
```

The value must be one positive, finite number. Do not average unequal pixel width and height values. Correct or re-export an anisotropic image before using this QXYCell workflow.

Why this matters: QuPath's exported centroid columns are already in micrometres, whereas QuPath GeoJSON geometry is expressed in full-resolution pixel coordinates. QXYCell uses `pixel_size_um` to align annotation and cell polygons with the centroids.

2. Create a QuPath project and add images

1. Create a new, empty folder dedicated to the QuPath project. Let QuPath manage this folder; do not use the QXYCell export folder as the project folder.
2. In QuPath, choose **File > Project... > Create new project** and select the empty folder.
3. Add the source images by dragging them into QuPath or choosing **File > Project... > Add images**.
4. If a file contains multiple images or series, enable the image selector and import only the intended series.
5. Set the image type to fluorescence where required.
6. Open every project entry and complete the image verification checklist above.
7. Save the project.

QuPath stores links to the source images. If images are moved, use **File > Project... > Check project URIs** to repair their locations.

3. Create analysis annotations

Annotations define regions used for segmentation and downstream grouping.

1. Select a drawing tool such as Rectangle, Ellipse, Polygon, Brush, or Wand.
2. Draw the analysis region on the image. For whole-image analysis, use **Objects > Annotations... > Create full image annotation**.

3. Assign every exported annotation a meaningful QuPath classification or name.
4. Avoid overlapping annotations that represent mutually exclusive samples.
5. Save the image data.

QXYCell annotation conventions

- A label containing Sample (case-insensitive) defines a sample boundary. Examples: Sample A, Sample_01, Tumour Sample.
- A label containing Ignore is imported as an annotation that can be removed with `qxy.remove_ignore(adata)`.
- Other labels become boolean columns named `annotation__<safe_label>` in `adata.obs`.
- Annotation labels do not create CoreID. QXYCell creates CoreID only from an exported measurement column named exactly TMA Core.
- Cells inside more than one sample annotation are reported as conflicts rather than silently assigned.

4. Segment cells with InstanSeg

InstanSeg is the recommended workflow represented here, but QXYCell does not require a particular segmentation algorithm. It requires QuPath cell objects with measurements and stable Object IDs.

Install and open InstanSeg

1. Choose **Extensions > Manage extensions**.
2. Install the Deep Java Library and InstanSeg extensions if they are not already installed.
3. Restart QuPath when requested.
4. Open **Extensions > InstanSeg**.

Test before running the complete region

1. Create or select a small representative test annotation.
2. Choose a fluorescence model appropriate for the available channels and desired output.
3. Select the correct input channels. Do not assume every channel improves segmentation.
4. Set the output to cells when cell boundaries are required.
5. Enable **Make measurements**.
6. Run the model on the test annotation.
7. Inspect nuclear/cell boundaries in dim, bright, crowded, sparse, tissue-edge, and artefact regions.
8. Adjust model, channels, tile padding, or other parameters when boundaries are systematically wrong.
9. Record the model and parameters, then run the accepted settings on the complete analysis annotation.

Use the verified physical calibration: InstanSeg models operate at a physical resolution and QuPath uses pixel calibration when rescaling image data. A successful run is not proof that segmentation is biologically accurate; visual review remains required.

5. Review measurements and optional marker classifiers

Confirm cell measurements

Open **Measure > Show detection measurements** and confirm that the cell rows contain:

- Object ID

- Centroid X μm
- Centroid Y μm
- the intended cell, cytoplasm, or nucleus marker measurements
- TMA Core when a QuPath TMA grid is used and core identity is required

QXYCell imports marker columns whose names contain mean or median (case-insensitive). Confirm that the intended marker measurements use one of those summaries.

Create optional marker thresholds

For each marker that requires a QuPath-derived starting threshold:

1. Choose **Classify > Object classification > Create single measurement classifier**.
2. Filter to cells.
3. Select one marker measurement, preferably a reviewed mean or median measurement from the appropriate compartment.
4. Set the below/above-threshold classes and enable live preview.
5. Review positive and negative cells across representative images and tissue conditions.
6. Save the classifier with a short, unique marker-based name.

QXYCell reads simple single-measurement classifier JSONs. Composite or malformed classifiers are reported but are not converted into threshold rows. Classifier thresholds are starting definitions: generate and review the QXYCell threshold table before applying positivity.

6. Export the cell measurement table

1. Save all open QuPath image data first.
2. Choose **Measure > Export measurements**.
3. Move the required project images into the selected list.
4. Set **Export type** to cells.
5. Export all columns unless you have verified a restricted column list includes every required identity, coordinate, and marker measurement.
6. Choose comma-separated (.csv) or tab-separated (.tsv) output.
7. Name the file `measurements.csv` or `measurements.tsv`.
8. Save it in a separate QXYCell export folder, not inside QuPath's managed project directory.

Required columns are exactly:

```
Image
Object ID
Centroid X  $\mu\text{m}$ 
Centroid Y  $\mu\text{m}$ 
```

One table may contain cells from multiple images. Large tables may contain millions of rows; do not resave them from spreadsheet software that may truncate rows, alter identifiers, or change headers.

7. Export annotation GeoJSON

Repeat for every image that has annotations to import.

1. Open the image and select only the annotation objects to export.

2. Choose **File > Object data... > Export as GeoJSON**. In some QuPath 0.7 installations the command may appear as **File > Export objects as GeoJSON**.
3. Export selected objects as a `GeoJSON FeatureCollection`.
4. Exclude measurements to keep the file smaller.
5. Use no compression and the `.geojson` extension.
6. Name the file from the image name exactly, removing only `.ome` and the image extension.

Examples:

Measurement Image value	Annotation filename
slide01.ome.tif	slide01.geojson
region_A.ome.tiff	region_A.geojson
sample-3.tif	sample-3.geojson

QXYCell matches annotation geometry to image rows by this stem. A file named `slide01-annotations.geojson` will not match `slide01.ome.tif`.

8. Export cell GeoJSON

Cell GeoJSON is optional but required for `cell_polygon_wkt` and cell-boundary plots.

1. Select the cell detection objects for one image, not the analysis annotations.
2. Choose the GeoJSON export command.
3. Export selected objects as a `FeatureCollection`.
4. Exclude measurements; the separate measurement table is the data source.
5. Preserve QuPath Object IDs.
6. Save as `<image-stem>-cells.geojson`, for example `slide01-cells.geojson`.

QXYCell matches cell polygons to measurement rows by QuPath Object ID. Do not refresh Object IDs between the measurement and cell-GeoJSON exports.

For very large images, cell GeoJSON can be large. Export one image at a time and verify that the feature count is plausible.

9. Assemble the QXYCell export folder

Recommended layout:

```
qupath_export/
|-- measurements.tsv
|-- annotations/
|   |-- slide01.geojson
|   |-- slide02.geojson
|-- cells/
|   |-- slide01-cells.geojson
|   |-- slide02-cells.geojson
|-- classifiers/
|-- object_classifiers/
|-- CD3.json
|-- PanCK.json
```

The source OME-TIFF files and QuPath's managed project files do not have to be copied into this export folder.

10. Run the QXYCell preflight

```
import qxy as qxy

project_dir = "/path/to/qupath_export"
report = qxy.check(project_dir, count_rows=True)

print(report.ok)
print(report.n_errors, report.n_warnings)
```

Or from a terminal:

```
qxycell check /path/to/qupath_export --count-rows
```

Review `check_report.txt`, `check_report.json`, and the tables in the generated sibling check folder. Resolve errors before import. Review warnings rather than assuming they are harmless.

The QXYCell check validates exported assets; it cannot confirm microscope calibration, channel identity, registration, biological staining quality, or segmentation accuracy. Those remain explicit QuPath pre-verification points.

11. Run QXYCell

Use the default only for verified 0.28 μm square pixels:

```
adata = qxy.run(project_dir)
```

Otherwise provide the recorded QuPath value:

```
adata = qxy.run(project_dir, pixel_size_um=0.325)
```

After import, confirm the stored audit value:

```
adata.uns["qxycell"]["pixel_size_um"]
```

Plot cell centroids and annotation or cell boundaries as a final alignment check before downstream analysis.

Final handoff checklist

- QuPath 0.7.0 project saved for every image.
- Image series, dimensions, channels, and physical units verified.
- Pixel width and height are equal and the scalar value is recorded.
- Segmentation visually reviewed across representative regions.
- `measurements.csv` or `measurements.tsv` contains all required columns.
- Annotation GeoJSON filenames match their image stems exactly.
- Cell GeoJSON retains the Object IDs used in the measurement export.
- Classifier JSONs are simple single-measurement classifiers where used.
- `qxy.check()` errors resolved and warnings reviewed.
- `qxy.run()` uses the verified `pixel_size_um` value.
- Spatial overlay alignment reviewed after import.

Troubleshooting

No measurement files found

Rename the export so its filename contains `measurement`, or use `detections.csv/detections.tsv`.

Missing required columns

Re-export cells and include Image, Object ID, Centroid X μm , and Centroid Y μm without editing the headers.

Annotations are discovered but not assigned

Check that each annotation filename stem matches the corresponding Image value after removing .ome and the image extension. Confirm that the QXYCell pixel size matches QuPath.

Cell polygons are missing

Confirm that cell objects, rather than annotations, were exported and that QuPath Object IDs match the measurement table.

Polygons are offset or scaled incorrectly

Stop downstream analysis. Recheck QuPath pixel calibration and the value passed as pixel_size_um; then rerun the import.

Pixel width and height differ

This QXYCell workflow does not support non-square pixels. Do not average the values. Correct or resample the image upstream and repeat segmentation and export.

Official references

- [QuPath 0.7.0 releases](#)
- [QuPath projects](#)
- [QuPath image concepts and pixel calibration](#)
- [QuPath InstanSeg workflow](#)
- [QuPath measurement export](#)
- [QuPath GeoJSON export](#)
- [QuPath 0.7.0 command reference](#)