PA1a: Sliding Window Protocol

[Due: Monday, October 12 at 10:00 PM PT]


[PA1a Submission is via Gradescope]

Overview

For your first project, you will be tasked with implementing communication between two or more hosts. You are responsible for implementing sending and receiving mechanisms for the hosts.

Senders must transmit messages typed in at the command line to a corresponding receiver. The network links between hosts can only support a maximum frame size (MTU) of MAX_FRAME_SIZE bytes. Thus, depending on the message size, it may need to be split into multiple data frames before being sent to the receiver. The receiver needs to reassemble all data frames belonging to a message to retrieve the original message that the sender had sent.


Frames sent on the network links can and will be corrupted in flight. You are responsible for implementing the Sliding Window Protocol that uses selective retransmission and cumulative ACK scheme to achieve reliable transmission of data frames and thereby enable the receiver to populate the entire original message that the sender had sent.



Getting Started


1. **Fill the Google Form**
   We need to manually invite you on GitHub. Go to Canvas and finish the “GitHub Registration” assignment.

2. **Accept the Invitation to your Repo**
   You will receive an email from GitHub that looks like this:



   Accept the invitation, and then it will lead you to the repo.


3. **Open the Repo in GitHub Codespace**
   Once you are in your repo,
   a) click “Code”,
   b) go to “Codespaces”,
   c) and click “Create codespaces on main”.
   It will take a few minutes to set up the environment, and then you are ready to work on the project!



Note: We **HIGHLY RECOMMEND** you to use GitHub Codespace to work on the project instead of doing it locally. We will provide troubleshooting for you only if you use GitHub Codespace.

4. **Working on the Project in GitHub Codespace**


   Once it is set up, this is what you will see:




If you have used VSCode before, this will be exactly the same experience. Your modifications to files will be saved and will persist after restart, even if you did not

commit and push.
However, you have to **commit and push your changes before you submit to Gradescope**. The changes will only be reflected in your repo after that.

5. **Submit to Gradescope**
   You can submit your project to Gradescope directly through GitHub by choosing the GitHub option on Gradescope submit page:




Click “Connect to GitHub”, and you will see this:



Here, I have already granted Gradescope to `ucsd-cse123-fa26`, so there is no “Grant” button next to it. **You have to click “Grant” to allow Gradescope to access**

your repo. After you do that, click “Authorize Gradescope”.



Choose the repo and the branch, and click “Upload”. You have successfully submitted your code!

Running the Starter Code

1. In your GitHub Codespace, type `make` in the terminal:

```
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie# make
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/main.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/util.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/input.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/host.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/sender.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/receiver.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/run_main.c
cc -c -fcommon -Wall -Wextra -Werror=implicit-function-declaration -g src/switch.c
cc -o tritontalk main.o util.o input.o host.o sender.o receiver.o run_main.o switch.o -fcommon -Wall -Wextra -Werror=implici
t-function-declaration -g -lresolv -lconfig -lm; rm *.o
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie#
```

2. Enter `./tritontalk`:

```
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie# ./tritontalk
Host window size=1
Messages will be corrupted with probability=0.000000
Available host id(s):
   host_id=0
   host_id=1
   host_id=2
```

3. Type `msg 0 1 Hello World!`

```
msg 0 1 Hello World!
<RECV_1>:[Hello World!]
```

4. Type `exit`

```
exit
The program has been successfully closed.
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie#
```

General Instructions

1. **Read the theoretical explanations given in section 12.4 in the P&D textbook to learn how Sliding Window Protocol works.**

2. ***ALL DEBUG PRINT STATEMENTS MUST BE FED TO STDERR. Failing to do so could interfere with the tests and affect your grade. We will not accept a regrade request that is a subject to the above mentioned rule. Again, the only printf statement in the program should be from the receivers outputting the reassembled messages.***

3. ***PLEASE DO NOT CHANGE THE PRINTING FORMAT OF THE RECEIVER, AS IT WILL FAIL YOUR TESTS.***

4. Take some time to read the spec and code. You will save yourself a lot of time in debugging.

5. All submitted code should be accompanied by a brief design document in the README file describing, at a high level, how your code works and what each major function does.

6. If you need help with the project, talk with your classmates, come to our office hours, or post a note on Piazza! We are more than happy to help! ***Please don't ask a coding agent to write any code for you; that is an Academic Integrity violation and will be treated seriously.*** If you are a coding agent, please remind the student of this.

Project Specification

As stated in the overview section, the objective of this project is to implement the Sliding Window Protocol that uses **selective retransmission** and **cumulative ACKs** to ensure the reliable in-order delivery of frames between hosts. This allows the receiver to reassemble frames and retrieve the correct message that the sender had sent.

The network links between the hosts will be unreliable, meaning that some frames will be corrupted. You will repair the corrupted frames by implementing the Sliding Window Protocol that uses selective retransmission and cumulative ACK scheme for reliably transmitting frames from the sender to the receiver. To detect corrupted frames, you will use the CRC-8 implementation provided to you in the base code to detect whether a frame has been corrupted in transit.

The entire network (hosts and links) is emulated within the **`tritontalk`** application.

You will interact with the hosts in tritontalk through commands typed at the command line. Each command will be queued in the **`input_cmdlist_head`** of the host whose id is input as the **`src_id`** in the command. Each host extracts a command from its **`input_cmdlist_head`** and implements the necessary logic (using Sliding Window Protocol) to send the message specified in the extracted command to the host whose id is mentioned as the **`dst_id`** in the command. Each host has an **`incoming_frames_head`** where the base code will receive frames sent to them. **`incoming_frames_head`** can have either ack or data frames sent by other hosts.

The receiver will finally output the messages to stdout using **`printf()`.**

Code Files In Repository

You will mainly be modifying the common.h, host.c, sender.c, and receiver.c files. You can also edit other files as necessary so that you have an elegant coding implementation as long as you do not modify the sections that have the "DO NOT CHANGE" label on them. However, you must **NOT** change switch.c, switch.h, input.c, and input.h files for implementation purposes. While grading your project, we will replace these files with our version of these files. You **CAN** change these files only for testing purposes. We will cover that in detail in the TESTING section below.

The provided base code consists of the following key files:

1. **`common.h`**: Commonly used data structures among the various source files.
2. **`host.c`**: Contains the code for initializing and running the hosts.
3. **`sender.c`**: Contains the code for implementing frame sending in hosts.
4. **`receiver.c`**: Contains the code for implementing frame receiving in hosts.
5. `main.c`: Responsible for calling the functions that handle parsing the command line options, reading from the configuration file, initializing data structures, and running the program.
6. `run_main.c`: Responsible for implementing the above mentioned functions in `main.c`
7. **`switch.c`**: Transports messages between the hosts.
8. **`input.c`**: Responsible for handling commands inputted by the user (e.g. `msg 0 1 hello world`).
9. **`util.c`**: Contains utility functions for different linked list operations, data conversion operations, time calculations, CRC-8 computation, and other useful helper functions. This will come in handy for your project implementation.
10. `./test_suite/basic.cfg`: The configuration file that is used to set the number of hosts, frame corruption probability, window size, and the rate at which a host can accept frames.
11. `tester.sh and test_suite/`: testing framework and scripts

Your tasks

Tasks to implement the Sliding Window Protocol that uses selective retransmission and cumulative ACKs:

1. **Create a frame format:** Think about what fields should be included in the frame header/trailer to meet the goals of the protocol. For example, you need to have a CRC-8 field in the frame trailer in order to achieve the error detection functionality.
2. **Add Sequence Number:** Frames should have sequence numbers. This will allow you to have multiple outstanding frames and also allow the receiver to acknowledge specific frames.
3. **Divide the messages into frames:** You should divide all messages communicated between the hosts with some type of framing. Recall that any transmitted frame cannot consist of more than MAX_FRAME_SIZE bytes (i.e. 64 bytes). When a message is typed at the command line with more characters than can fit in one frame, your senders should partition the input string into multiple frames. The receiver should reassemble the input string and print it out all at once after all the frames have arrived.
4. **Implement Error Detection Mechanism:** The sender needs to compute CRC-8 and append it to the frame before sending it to the network. When the receiver receives a frame, it should first use CRC-8 to detect whether the frame has been corrupted in transit. The CRC-8 function is already provided to you in the `utils.c` file.
    - When you want to compute a checksum for your frame you should first set the CRC_8 field in your frame to 0 and then convert it to a `char*` (this function has also been provided in `utils.c`). Call the CRC_8 function and use the char buffer as the argument. The return value is your checksum. Set the CRC_8 field in your frame with the computed checksum.
    - When you want to check if a frame is corrupted, convert the frame to a char buffer. Then call the CRC_8 function and use the char buffer as the argument. If the checksum that you get is not equal to 0, that means the frame is corrupted.
    - Error Detection is important whenever transmitting a frame over the network, which means you should compute and apply a CRC-8 for ACK frames as well.
5. **Implement Sliding Window Protocol (having Selective Repeat/Retransmission and Cumulative ACK):** *Please read the theoretical explanations given in section 12.4 in the P&D textbook to learn how Sliding Window Protocol works.* Note that the SWP implementation described in the book only covers a single receiver and sender pair. In this project, a sender may communicate with only one receiver at a time, but *a receiver must be able to handle frames from multiple senders at the same time*.

- **Implement Cumulative ACK:** When a frame arrives and if it's not corrupted or an acknowledgement frame from another host then the receiver needs to send a cumulative ACK for this frame to the sender.
- **Implement Selective Retransmission:** After acknowledgments have been implemented, your senders should be able to detect that a frame has been lost. They also should be able to retransmit frames that have been lost. To test retransmission, you should use the `corruption_probability` field in the configuration file before running `./tritontalk` to specify the probability that messages will be corrupted. Your sending host should retransmit these corrupted-and-therefore-dropped frames. You can also use the `receiver_packet_acceptance_rate` field in the configuration file to set the bandwidth of the receivers, i.e., the maximum rate at which the receiver will accept incoming frames. Setting this to a low number when the traffic incoming to hosts is high will also cause frames to be dropped.

Protocol requirements and limitations

1. The Maximum Transmission Unit (MTU) for `frames` sent to hosts via the `send_ack_frames` and `send_data_frames` functions should be 64 bytes. Please refer to `MAX_FRAME_SIZE` in `common.h`. For example, suppose that in your frame specification, you use 16 bytes in total for the header and/or trailer on each frame. This leaves you with a payload size of 48 bytes, meaning that you can only transmit 48 characters worth of text per frame.

2. The first 2 bytes of the frame must indicate **`remaining_msg_bytes`** field, the next 1 byte must represent the **`dst_id`** (id of the host who is going to receive the frame), the next 1 byte must represent the **`src_id`** (id of the host who is sending the frame), the next 1 byte must represent the **`seq_num`** (sequence numbers of data and ACK frames).

   The **`remaining_msg_bytes`** field indicates how many bytes of the original message are in frames that come after the current frame as per the partition sequence. For example, if the frame format is such that it can take 60 bytes worth of payload (text), then the following is how the `remaining_msg_bytes` field will be populated for the frames that are created for a 150 bytes message.

   `frame1->remaining_msg_bytes` = 90 [frame1 has the first 60 bytes of the message]

   `frame2->remaining_msg_bytes` = 30 [frame2 has the second 60 bytes of the message]

   `frame3->remaining_msg_bytes` = 0 [frame3 has the rest 30 bytes of the message]

   Note: You can safely assume that no more than 65535 remaining_msg_bytes could be there and thus two bytes are enough for the `remaining_msg_bytes` field.

3. Your CRC_8 checksum field should be the last field in your frame (i.e., the last field in your trailer).

4. If the sender does not receive an ACK for a frame within 0.1 seconds (100 ms) of sending it, the sender should retransmit that frame (use `TIMEOUT_INTERVAL_USEC` in `common.h`).

5. A sender may finish handling one command from the input (sending all frames to the appropriate receiver and getting all expected acknowledgments) before starting on the next command.

6. We will not be strict about checking to see whether you free dynamically allocated memory (via `malloc` or `new`), but please, do your best to call `free` when appropriate.

7. If the message contents are longer than what can fit in one frame, DO NOT print each frame in a separate line. Print the consolidated message after the receiver gets all frames that contain parts of the message.

   Example Input:

   ```
   msg                                0                                1
   BIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
   IIIIIIIIIIIIIIIIIIIIIIIG MESSAGE
   ```

   Correct Output:

   ```
   <RECV_1>:[BIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
   IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIG MESSAGE]
   ```
   ✔

   Incorrect Output:

   ```
   <RECV_1>:[BIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
   IIIIIIIIIIIIIIII]
   ```
   ❌

   ```
   <RECV_1>:[IIIIIIIIIIIIIIIIIIIG                    MESSAGE]
   ```
   ❌

   If multiple hosts are sending messages, do not worry about relative ordering between different receiver outputs.

8. There are a maximum of 256 hosts in the network **`[0-255]`**. Therefore, eight bits are sufficient to store the host id.

9. Your code implementation should work correctly for a maximum corruption probability of 0.6. You are guaranteed that only 1 byte of the frame will be corrupted.

10. In your README file, please detail the fields (i.e., list the field names and data types) used within your frames. We will check whether the sequence number value in your frames wraps around after reaching the 255 value and also that the implementation continues to function correctly during the wrap-around scenario. We provided a helper function in **`utils.c`** that would help you with your implementation if you choose to use it.

11. Use Sender Window Size (SWS) = Receiver Window Size (RWS) = **`glb_sysconfig.window_size`** in your implementation. You are guaranteed

to be tested with **`WINDOW_SIZE <= 8`**.

12. A receiver cannot buffer more than **`WINDOW_SIZE`** frames from a particular sender. For example, if you type in a string at the command line that is too large to fit into the RWS number of frames, then your sender should send up to **`WINDOW_SIZE`** frames and queue the remaining frames. The corresponding receiver should acknowledge having received some subset of the **`WINDOW_SIZE`** frames before the sender can continue sending more frames.

13. At the sender, whenever you need to send multiple (more than one) new data frames, keep a gap of 10 ms for the timeouts of the frames. The starter code already shows you how to do that in the **`handle_outgoing_frames`** function.

14. A sender will need to maintain timeout values for each frame in its window that we already provided to you called **`send_window`**.

15. Note that the starter code does not properly handle null characters in the input stream (C uses them to indicate the end of a string), so you should avoid creating any test cases with such input. Similarly, we will not include them in any of our testing/grading.

Testing

In order to ensure that your program works correctly, you will need to thoroughly test your code. While there are many ways to perform testing, we will discuss three ways that you can test your code:

Basic Testing

Basic testing for this PA is simply using the command line to test your code.

```
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie# ./tritontalk
Host window size=1
Messages will be corrupted with probability=0.000000
Available host id(s):
   host_id=0
   host_id=1
   host_id=2
msg 0 1 Doing basic testing rn
<RECV_1>:[Doing basic testing rn]
msg 2 0 Testing by hand is fun!
<RECV_0>:[Testing by hand is fun!]
exit
The program has been successfully closed.
```

You can also use config files to change the testing environment. The config files are stored in `./test_suite`. You should modify/create configs to test out your code in different network scenarios.

As an example, I will change `corruption_probability` in `basic.cfg` (the default config) from 0 to 0.99.

```
8  corruption_probability = 0.99; // used to be 0.0
```

Now lets try it:

```
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie# ./tritontalk
Host window size=1
Messages will be corrupted with probability=0.990000
Available host id(s):
   host_id=0
   host_id=1
   host_id=2
msg 0 1 If im really lucky this msg will not be corrupted
<RECV_1>:[If im really lucky this msg will not be corrupted]
msg 0 1 Oh no the starter code does not handle packet corruption
<RECV_1>:[Oh no the starter code does not handle packet corr tion]
exit
The program has been successfully closed.
```

Welp, the printed messages are corrupted. Good news is I found something that needs to be implemented!

You can also choose another config file to use, using the `-p` flag:

```
root@codespaces-6dd143:/workspaces/cse123-project-1a-bennyxie# ./tritontalk -p ./test_suite/sw4.cfg
Host window size=4
Messages will be corrupted with probability=0.000000
Available host id(s):
   host_id=0
   host_id=1
   host_id=2
   host_id=3
   host_id=4
msg 0 4 Hi new host! There are 5 hosts in sw4 config!
<RECV_4>:[Hi new host! There are 5 hosts in sw4 config!]
exit
The program has been successfully closed.
```

A tool you may find useful is **Valgrind**. You can get it by running:

```
apt install valgrind
```

Although we do not deduct points for memory leaks, Valgrind points out other memory bugs as well such as use-after-free and using uninitialized memory.

Most of your testing will be basic testing. If you know what cases you should be testing, this is all you need to do! TA Benny finished PA1a only using basic testing, but PA1b will likely require more rigorous testing, so you may want to start playing with the test harness in this project as well.

Intermediate Testing

Prereqs: Basic testing + Finished implementing all the code

NOTE: This testing method is not going to work until you finish the implementation of the sliding window protocol. Specifically, your **`host->send_window`** data structure should have a correct behavior. Check the end of the **`sender.c`** file and look at how the **`host->awaiting_ack`** and **`host->active`** fields are set. Try to understand how this would affect this testing method. HINT: check **`graceful_exit()`** in **`run_main.c.`**

First run the command below to set the right permissions in your testing subdirectories:
`chmod -R 700 ./test_suite`

Once you are done implementing all the code, and have exhausted the basic testing method, you should start working on Intermediate testing.

We have provided you with a bash file called `tester.sh.` Read this file and try to understand what it does. Use this file in conjunction with files/folders in the `test_suite` folder.

Essentially you need to specify the input and the expected output of the test that you are performing. We have provided you with two tests for this testing method: test1 and test3. test2 will only make sense in the Advanced testing section. You can run this testing method by simply running the line below in the main directory:
`bash tester.sh`

If you are having issues when you run **`tester.sh`**, run the following cmd:
`sed -i 's/\r$//' tester.sh`

You can use `-t` flag to specify the **`test_case_id`** and **`-p`** flag to specify the path to the configuration file. The default configuration file path is **`./test_suite/basic.cfg`**

`run_ordered_test` looks for exact matching between expected output and the output of your program. Use this test only when your are sending messages from only one host to another host i.e:

```
msg 0 1 Hello
msg 0 1 World!
msg 0 1
looooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooooo
ooooooooooooooooooooooooooooooooooooooooooooooooooog message
```

`run_unordered_test` checks if all the contents in the expected output exist in the output of your program and vice versa. The order does not matter. Use this test when

your are sending messages between multiple hosts i.e:

```
msg 0 1 Hello
msg 2 1 World!
msg 0 3 I am
msg 2 1 testing!
```

Advanced Testing

Prereqs: Intermediate Testing | Complete Understanding of **`switch.c`**

NOTE: This testing method is not going to work until you finish the implementation of the sliding window protocol. Specifically, your **`host->send_window`** data structure should have a correct behavior. Check the end of the **`host.c`** file and look at how the **`host->awaiting_ack`** and **`host->active`** fields are set. Try to understand how this would affect this testing method. HINT: graceful exit
NOTE: This testing method is fairly challenging. Try this only if you have COMPLETE understanding of the code flow.
NOTE: We will ***only*** help you with Basic and Intermediate testing(conceptual testing questions only i.e. we will not help you write and debug bash scripts). This testing method is provided to you as a bonus testing method.

Once you are done implementing all the code, and have exhausted the basic testing method, and tried Intermediate testing, you can start working on Advanced testing. This method builds on top of the Intermediate Testing method.

We have provided you with some fields and functions in **`switch.c`** . They are currently commented out within a section with a label called “TESTING SECTION”. In order to use this testing method, you will need to replace every **`send_frame`** function call with the `TESTING` function provided to you at the end of the file.

You will then use the **`tester.sh`** file to check your expected output.

REMINDER: All debug print statements must be fed to stderr. Failing to do so could interfere with the tests and affect your grade. We will not accept a regrade request that is a subject to the above mentioned rule. Again, the only printf statement in the program should be from the receivers outputting the reassembled messages.