
1: Margins

(1) Consider the following input to the XOR function in two dimensions (x_1, x_2) and the input mapped into the space (x_1, x_1x_2) .

x_1	x_2	label	x_1x_2
-1	-1	-1	1
-1	1	1	-1
1	-1	1	-1
1	1	-1	1

Table 1: Inputs to the XOR function in two dimensions and mapping.




Figure 1: The separating line producing the maximal margin in both spaces.

The XOR function in x_1, x_1x_2 space has a maximum margin of 1. This is achieved with the separating line $x_1x_2 = 0$.

Translating the line $x_1x_2 = 0$ back to the original x_1, x_2 Euclidean space will be the lines $x_1 = 0$ and $x_2 = 0$. This is because $x_1x_2 = 0$ is true when at least one of x_1 or x_2 is 0. Which is satisfied by the lines running along the x_1 -axis and the x_2 -axis.

Maximum margin of 1.




Figure 2: Geometry of the three training sets.

(2a) D_1 - Points x_1 and x_3 form the line $y - x = 0$ which has a slope of 1. A line with slope 1 that passes through point x_5 is given by $y - x + 1 = 0$. The parallel separating line between these two lines will give the maximum margin. It intersects the x-axis at $(0.5, 0)$, has a slope of 1 and is given by the formula $y - x + 0.5 = 0$. We can use the distance formula for a line and a point to determine the margin between this separating line and the nearest points.

$$\text{distance}(ax + by + c = 0, (x_0, y_0)) = \frac{|ax_0 + by_0 + c|}{\sqrt{a^2 + b^2}} \quad (1)$$

The separating line is defined by $a = -1$, $b = 1$, and $c = 0.5$.

$$\text{distance}(-x + y + 0.5 = 0, (0, 0)) = \frac{0.5}{\sqrt{2}}$$

$$\text{distance}(-x + y + 0.5 = 0, (1, 1)) = \frac{0.5}{\sqrt{2}}$$

$$\text{distance}(-x + y + 0.5 = 0, (1, 0)) = \frac{0.5}{\sqrt{2}}$$

$$\text{maximum } \gamma = \frac{1}{2\sqrt{2}}$$

D_2 - The separating line that produces the maximum margin is evident from the geometry of the training points. As seen in figure 2, the line $x = 0.25$ separates the points with the maximum margin.

The separating line is defined by $a = 1$, $b = 0$, and $c = -0.25$.

$$\text{distance}(x - 0.5 = 0, (0, 0)) = 0.25$$

$$\text{distance}(x - 0.5 = 0, (\frac{1}{2}, \frac{\sqrt{3}}{2})) = 0.25$$

$$\text{maximum } \gamma = 0.25$$

D_3 - Points x_3 and x_4 form the line $y - 2x + 1 = 0$ which has a slope of 2. A line with slope 2 that passes through point x_5 is given by $y - 2x + 2 = 0$. The parallel separating line between these two lines will give the maximum margin. It intersects the x-axis at $(\frac{3}{4}, 0)$, has a slope of 2 and is given by the formula $y - 2x + 1.5 = 0$.

The separating line is defined by $a = -2$, $b = 1$, and $c = 1.5$.

$$\text{distance}(-2x + y + 1.5 = 0, (\frac{1}{2}, 0)) = \frac{0.5}{\sqrt{5}}$$

$$\text{distance}(-2x + y + 1.5 = 0, (1, 1)) = \frac{0.5}{\sqrt{5}}$$

$$\text{distance}(-2x + y + 1.5 = 0, (1, 0)) = \frac{0.5}{\sqrt{5}}$$

$\text{maximum } \gamma = \frac{1}{2\sqrt{5}}$

(2b)

$\text{Perceptron Mistake Bound} = (\frac{R}{\gamma})^2$

(2)

D_1 - From part a we found $\gamma = \frac{1}{2\sqrt{2}}$. To find R , we find the training point furthest away from the origin as the line from the origin to this point defines the radius of the training examples. Using the Pythagorean Theorem, we determine x_7 is the furthest point from the origin with a distance of 1.5.

$$\text{PMB}(\gamma, R) = \text{PMB}(\frac{1}{2\sqrt{2}}, 1.5) = (\frac{R}{\gamma})^2 = 18$$

Mistake bound of 18

D_2 - We found $\gamma = 0.25$. The furthest point from the origin is point x_8 with a distance of $\frac{\sqrt{5}}{2}$.

$$\text{PMB}(\gamma, R) = \text{PMB}(0.25, \frac{\sqrt{5}}{2}) = (\frac{R}{\gamma})^2 = 20$$

Mistake bound of 20

D_3 - We found $\gamma = \frac{1}{2\sqrt{5}}$. The furthest point from the origin is the point x_7 with a distance of 1.5.

$$\text{PMB}(\gamma, R) = \text{PMB}(\frac{1}{2\sqrt{5}}, 1.5) = (\frac{R}{\gamma})^2 = 45$$

Mistake bound of 45

(2c)!!!!!!!!!!!!!!!!!!!!!! TODO !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!

2: Kernels

(1a)

(1b)

(2)

(3)

3: Support Vector Machines

Note: In my submitted source code there is a 'traces' directory. This contains traces of all of the experiments I ran to collect the following data.

(1) A SVM using Stochastic sub-gradient descent was trained on the **handwriting** dataset. The hyperparameters $C = 1$, $\gamma_0 = 0.01$, and $epoch = 10$ were used.

The classifier was evaluated using the *training* and *test* **handwriting** datasets with the following results:

Data Set	Mistakes	Example Count	Accuracy
handwriting training	1	1,000	0.999
handwriting testing	8	593	0.987

Table 2: Classification accuracy on the training and test set.

(2) **Splits for continuous features:** The **madelon** dataset has continuous features. I decided to make the features binary features. To determine their value, I took the mean value a feature had across all training examples. Then, depending on which side of the mean each feature value landed, the feature value was replaced by 0 for less than and 1 for greater than or equal to the mean.

Cross-validation: To determine the best hyperparameters C and γ_0 I ran 5-fold cross validation on various combinations of C and γ_0 . For all the cross validations trials an epoch of 20 was used.

C	Initial Learning Rate	Accuracy
2	0.5	0.527
2	0.01	0.539
2	0.001	0.532
0.5	0.5	0.536
0.5	0.01	0.533
0.5	0.001	0.522
0.25	0.5	0.538
0.25	0.01	0.53
0.25	0.001	0.519
0.125	0.5	0.537
0.125	0.01	0.542
0.125	0.001	0.527
0.0625	0.5	0.526
0.0625	0.01	0.514
0.0625	0.001	0.545
0.03125	0.5	0.516
0.03125	0.01	0.521
0.03125	0.001	0.548

Table 3: Results of 5-fold cross-validation.

The results of the cross-validation produced a best C of 0.03125 and a γ_0 of 0.001 using an epoch of 10. These hyperparameters were used to train the SVM classifier and it was evaluated on both the *training* and *test* set.

Data Set	Mistakes	Example Count	Accuracy
madelon training	641	2,000	0.679
madelon testing	248	600	0.587

Table 4: Classification accuracy on the training and test set.

(3) In addition to the accuracy of of the two classifiers from part *a* and part *b*, I calculated the precision, recall and F_1 score on each dataset.

Data Set	Precision	Recall	F_1 Score
handwriting training	1.0	0.998	0.999
handwriting testing	1.0	0.974	0.987
madelon training	0.679	0.68	0.679
madelon testing	0.586	0.59	0.588

Table 5: Precision, recall and F_1 score of previous classifiers.

4: Ensemble of Decision Trees

Note: In my submitted source code there is a 'traces' directory. This contains traces of all of the experiments I ran to collect the following data.

(1) Splits for continuous features: The `madelon` dataset has continuous features. I decided to make the features binary features. To determine their value, I took the mean value a feature had across all training examples. Then, depending on which side of the mean each feature value landed, the feature value was replaced by 0 for less than and 1 for greater than or equal to the mean.

Hyperparameters: I ran cross validation on the `madelon` training set to determine good hyperparameters for this experiment. The hyperparameter to determine for the ensemble of decision trees is m or the number of random samples used when training each decision tree. N and k are fixed for this experiment.

For the meta-SVM classifier, I determined the best γ_0 , C and epoch to be used on features produced by the ensemble of decision trees.

m	N	k	γ_0	C	epoch
2,000	5	8	0.1	4	15

Table 6: Hyperparameters for the ensemble and meta-SVM classifiers

Using these chosen hyperparameters, 5 decision trees were trained on k random features each. The results of these trees were used to train as the training examples for a meta-SVM classifier. This trained meta-SVM classifier was evaluated on both the *training* and *test handwriting* datasets.

Data Set	Mistakes	Examples Count	Accuracy	Precision	Recall	F_1 Score
handwriting training	257	1,000	0.743	0.844	0.651	0.735
handwriting test	127	593	0.786	0.884	0.673	0.764

Table 7: Results of meta-SVM classifier on the `handwriting` dataset.

(2a)

(2b)