

The univie-ling-expose class

Jürgen Spitzmüller*

Version 2.7, 2024/07/23

Abstract

The univie-ling-expose class provides a \LaTeX 2_{ϵ} class suitable for those research proposals (*Exposés*) that are required in the context of the public presentation of a dissertation project (*FÖP*) at the University of Vienna.¹ The class implements some standards for these proposals (such as a suitable title page). It is particularly suited for projects in the field of (Applied) Linguistics and pre-loads some packages that are considered useful in this disciplinary context. The class might also be used for General and Historical Linguistics as well as for other fields of study at Vienna University. In this case, however, some settings might have to be adjusted. This manual documents the class as well as the configuration possibilities.

Contents

1	Aims and scope	2
2	Requirements of univie-ling-expose	2
3	Fonts	3
4	Class Options	4
4.1	Font selection	4
4.2	Polyglossia	4
4.3	Package loading	4
4.4	Draft mode	5
4.5	Further options	5
5	General settings	5
5.1	Author-related data	5
5.2	Project-related data	6
6	Semantic markup	6
7	Hyperlinks	6
8	Linguistic examples and glosses	7
9	Bibliography	7
9.1	Default bibliography style (<i>Unified Style for Linguistics</i>)	7
9.2	Using APA/DGPs style	7
9.3	Using a different style or not using biblatex	8

*Please report issues via <https://github.com/jspitz/univie-ling>.

¹<http://doktorat.univie.ac.at/en/doctorate-university-of-vienna/research-proposal/>.

10 Further instructions	9
10.1 Commands and environments	9
10.2 L ^A T _E X layouts and templates	9
11 Release History	9

1 Aims and scope

The univie-ling-expose class has been written mainly with my own field in mind: Applied Linguistics. Therefore, the defaults are closely tied to the requirements in this field. This particularly concerns the preloaded bibliography style, which conforms to the standards that are proposed by the Viennese Applied Linguistics staff (see sec. 9). Furthermore, some frequently used packages (such as covington) are preloaded. As documented later, however, you can disable this (and other) default(s), use a bibliography style of your choice and load alternative packages.

The design matches as closely as necessary the standards set up within the university. This particularly concerns the title page, which takes the recommendations specified by the *StudienServiceCenter* as a model.² These specifications actually address theses, not research proposals (for which no title page specifications exist), but I think it makes sense to adapt them. Furthermore, the guidelines of the *Doktorats-Studienprogrammleitung* of the Faculty of Philological and Cultural Studies (DSPL 42) that prescribe font selection and line spacing are followed.³

2 Requirements of univie-ling-expose

The following class and packages are required and loaded by univie-ling-expose:

- scrartcl: KOMA-Script article class (base class).
- csquotes: Context sensitive quotations.
- datetime2: Date localization.
- graphicx: Graphic support.
- isodate: Format URL dates.
- l3keys: Key-value interface for class options.
- scrlayer-scrpage: Page layout settings.
- setspace: Line spacing adjustments.
- translator: Localization machinery.
- url: Support for typesetting URLs.

The following packages are required for specific features and loaded by default. However, the loading can be individually and generally omitted (see sec. 4):

²<http://ssc-philkultur.univie.ac.at/studium/masterstudien/abgabe-der-masterarbeit<25.01.2017>>.

³Published in German, see http://ssc-philkultur.univie.ac.at/fileadmin/user_upload/studentpoint/Pref_Kultur/SSC_Philologisch/Verbindliche_Richtlinien_für_Exposés.pdf

- `mathptmx`: Default serif font (*Times New Roman*).
- `urw-arial` or `helvet`: Default sans serif font (*Arial* or *Helvetica*).
- `sourcecodepro`: Default monospaced font (*Source Code Pro*).
- `biblatex`: Contemporary bibliography support.
- `caption`: Caption layout adjustments.
- `covington`: Support for linguistic examples/glosses.
- `fontenc`: Set the font encoding for PostScript fonts. Loaded with option `T1`.
- `microtype`: Micro-typographic adjustments.
- `prettyref`: Verbose cross-references.
- `varioref`: Context-sensitive cross references.

The following packages are required for optional features (not used by default):

- `biblatex-apa`: APA style for `biblatex`.
- `draftwatermark`: Create a draft mark.
- `fontspec`: Load OpenType fonts (with LuaTeX or XeTeX).
- `polyglossia`: Multi-language and script support.

3 Fonts

The class uses, by default, PostScript (a. k. a. Type 1) fonts and thus requires classic (PDF)LaTeX. Optionally, however, you can also use OpenType fonts via the `fontspec` package and the XeTeX or LuaTeX engine instead. In order to do this, use the class option `fonts=otf` (see sec. 4 for details).

In both cases, the class uses by default *Times New Roman* as a serif font, *Arial* (or, alternatively, *Helvetica*) as a sans serif font, and *Source Code Pro* as a monospaced (typewriter) font. Note that *Arial* (PostScript) font support is not included in most \TeX distributions by default, due to license reasons. You can install it easily via the `getnonfreefonts` script.⁴ If *Arial* is not installed, however, *Helvetica* (which is part of the \TeX core packages) is used as a fallback. This is usually a suitable alternative, since *Arial* and *Helvetica* only differ in subtle details. If you use `fonts=otf`, you just have to make sure that you have the fonts *Arial*, *Times New Roman* and *Source Code Pro* installed on your operating system (with exactly these names, i. e., fonts named *Arial Unicode MS* or *Times* will not be recognized!).

Note that by default, with PostScript fonts, `univie-ling-expose` also loads the `fontenc` package with `T1` font encoding, but this can be customized (see sec. 4 for details).

If you want (or need) to load all fonts and font encodings manually, you can switch off all automatic loading of fonts and font encodings by the class option `fonts=none` (see sec. 4).

⁴<https://www.tug.org/fonts/getnonfreefonts> <25.01.2017>.

4 Class Options

The `univie-ling-expose` class provides a range of key=value type options to control the font handling, package loading and some specific behavior. These are documented in this section.

4.1 Font selection

As elaborated above, the package supports PostScript fonts (via LaTeX and PDFLaTeX) as well as OpenType fonts (via XeTeX and LuaTeX). PostScript is the traditional LaTeX font format. Specific LaTeX packages and metrics files are needed to use the fonts (but all fonts needed to use this class should be included in your LaTeX distribution and thus ready to use). OpenType fonts, by contrast, are taken directly from the operating system. They usually provide a wider range of glyphs, which might be a crucial factor for a linguistic paper. However, they can only be used by newer, partly still experimental TeX engines such as XeTeX and LuaTeX.

The class provides the following option to set the font handling:

fonts=ps|otf|none: if **ps** is selected, PostScript fonts are used (this is the default and the correct choice if you use LaTeX or PDFLaTeX); if **otf** is selected, OpenType fonts are used, the class loads the `fontspec` package, sets *Times New Roman* as main font and *Arial* as sans serif font (this is the correct choice if you use XeTeX or LuaTeX; make sure you have the respective fonts installed on your system); if **none** is selected, finally, the class will not load any font package at all, and neither `fontenc` (this choice is useful if you want to control the font handling completely yourself).

With PostScript fonts, `univie-ling-expose` also loads the `fontenc` package with T1 font encoding, which is suitable for most Western European (and some Eastern European) writing systems. In order to load different, or more, encodings, the class option

fontenc=<encoding(s)> can be used (e. g., **fontenc={T1,X2}**). With **fontenc=none**, the loading of the `fontenc` package can be prevented. The package is also not loaded with **fonts=none**.

4.2 Polyglossia

If you need `polyglossia` rather than `babel` for language support, please do not use the package yourself, but rather use the package option **polyglossia=true**. This assures correct loading order. This also presets **fonts=otf**.

4.3 Package loading

Most of the extra features provided by the class can be switched off. This might be useful if you do not need the respective feature anyway, and crucial if you need an alternative package that conflicts with one of the preloaded package.

All following options are **true** by default. They can be switched off one-by-one via the value **false**, or altogether, by means of the special option **all=false**. You can also

switch selected packages on/off again after this option (e. g., `all=false,microtype=true` will switch off all packages except microtype).

apa=true|false: If `true`, the biblatex-apa style is used when biblatex is loaded. By default, the included univie-ling style is loaded, instead. See sec. 9 for details.

biblatex=true|false: If `false`, biblatex is not loaded. This is useful if you prefer Bib_T_EX over biblatex, but also if you neither want to use the preloaded univie-ling style nor the alternative biblatex-apa style (i. e., if you want to load biblatex manually with different options). See sec. 9 for details.

caption=true|false: If `false`, the caption package is not loaded. This affects the caption layout.

covington=true|false: If `false`, covington is not loaded. Covington is used for numbered examples.

microtype=true|false: If `false`, microtype is not loaded.

ref=true|false: If `false`, both prettyref and varioref are not loaded and the string (re)definitions of the class (concerning verbose cross references) are omitted.

4.4 Draft mode

The option `draftmark=true|false|firstpage` allows you to mark your document as a draft, which is indicated by a watermark (including the current date). This might be useful when sharing preliminary versions with your supervisor. With `draftmark=true`, this mark is printed on top of each page. With `draftmark=firstpage`, the draft mark appears on the title page only.

4.5 Further options

The class builds on scrartcl (KOMA article), which provides many more options to tweak the appearance of your document. You can use all these options via the `\KOMAOptions` macro. Please refer to the KOMA-Script manual [5] for details.

5 General settings

In this section, it is explained how you can enter some general settings, particular the information that must be given on the title page. The title page, following the model given in university guidelines for theses, is automatically set up by the `\maketitle` command, given that you have specified the following data in the preamble.

5.1 Author-related data

`\author{<name>}`: Name of the proposal's author.

`\studienkennzahl{<code>}`: The degree programme code (*Studienkennzahl*) as it appears on the student record sheet, e. g. *A 792 327*.

`\studienrichtung{<field of study>}`: Your degree programme (*Studienrichtung*) or field of study (*Dissertationsgebiet*) as it appears on the student record sheet, e. g. *Sprachwissenschaft*.

5.2 Project-related data

`\title{<title>}`: Title of the dissertation project.

`\subtitle{<subtitle>}`: Subtitle of the dissertation project.

`\supervisor{<name>}`: Title and name of your (main) supervisor.

`\cosupervisor{<name>}`: Title and name of your co-supervisor.

`\advisor{<name(s)>}`: Title(s) and name(s) of the advisory board members (*Doktoratsbeirat*).

6 Semantic markup

The class defines some basic semantic markup common in linguistics:

`\Expression{<text>}`: To mark expressions (object language). Typeset in *italics*.

`\Concept{<text>}`: To mark concepts. Typeset in SMALL CAPITALS.

`\Meaning{<text>}`: To mark meaning. Typeset in ‘single quotation marks’.

You can redefine each of these commands, if needed, like this:

```
\renewcommand*\Expression[1]{\textit{#1}}
\renewcommand*\Concept[1]{\textsc{#1}}
\renewcommand*\Meaning[1]{\enquote{#1}}
```

7 Hyperlinks

The stylesheet requires you to always give last access dates to web links (URLs). To make this easier, univie-ling-expose provides a number of convenience macros. To begin with, you can easily enter URLs with the last date you accessed the site with the function

```
\weblink{<URL>}[<date>]
```

This will format the date in the preferred way (“[last accessed: <date>]”), localized to English or German. The argument can be given in the form YYYY-MM-DD, DD/MM/YYYY, or DD.MM.YYYY, e.g.

```
\weblink{https://linguistics.univie.ac.at}[27/06/2024]
```

will print: <https://linguistics.univie.ac.at> [last accessed: 27/06/2024]. If you do not give the optional date argument, no date is printed unless you have specified a general last access date by means of the function

`\SetURLDate{<date>}`

which takes the same date format as argument. This function might come in handy if you have the same access date for all, or many, URLs. And it lets you update all URL access dates with a single change.

For hyperlinks without date, you can also use the legacy command `\url{<URL>}`. To output the date information only, you can use the macro `\urldate{<date>}`.

8 Linguistic examples and glosses

The class automatically loads the covington package which provides macros for examples and glosses. Please refer to the covington manual [1] for details.

9 Bibliography

9.1 Default bibliography style (*Unified Style for Linguistics*)

By default, the univie-ling-expose class loads a bibliography style which matches the conventions that are recommended by the Applied Linguistics staff of the department.⁵ These conventions draw on the *Unified Style Sheet for Linguistics* of the LSA (*Linguistic Society of America*), a style that is also quite common in General Linguistics nowadays. In order to conform to this style, the univie-ling-expose class uses the biblatex package with the univie-ling style that is included in the univie-ling-expose package.

If you are in Applied Linguistics, using the default style is highly recommended. The style recommended until 2017, namely APA/DGPs, is also still supported, but its use is no longer encouraged; see sec. 9.2 for details. If you want/need to use a different style, please refer to section 9.3 for instructions.

9.2 Using APA/DGPs style

Until 2017, rather than the Unified Style, the Applied Linguistics staff recommended conventions that drew on the citation style guide of the APA (*American Psychological Association*) and its adaptation for German by the DGPs (*Deutsche Gesellschaft für Psychologie*).

For backwards compatibility reasons, this style is still supported (though not recommended). You can enable it with the package option `apa=true`.

If you want to use APA/DGPs style, consider the following caveats.

- For full conformance with the APA/DGPs conventions (particularly with regard to the rather tricky handling of “and” vs. “&” in- and outside of parentheses), it is mandatory that you adequately use the respective biblatex(-apa) citation commands: Use `\textcite` for all inline citations and `\parencite` for all parenthesized citations (instead of manually wrapping `\cite` in parentheses). If you

⁵See <http://www.spitzmueller.org/docs/Zitierkonventionen.pdf>

cannot avoid manually set parentheses that contain citations, use `\nptextcite` (a biblatex-apa-specific command) inside them.⁶ For quotations, it is recommended to use the quotation macros/environments provided by the `csquotes` package (which is preloaded by `univie-ling-expose` anyway); the `univie-ling-expose` class assures that citations are correct if you use the optional arguments of those commands/macros in order to insert references.

- The biblatex-apa style automatically lowercases English titles. This conforms to the APA (and DGPs) conventions, which favour “sentence casing” over “title casing”. English titles, from biblatex’s point of view, are titles of bibliographic entries that are either coded as `english` via the `LangID` entry field or that have no `LangID` coding but appear in an English document (i. e., a document with main language English). Consequently, if the document’s main language is English, all non-English entries need to be linguistically coded (via `LangID`) in order to prevent erroneous lowercasing, since biblatex assumes that non-identified entries use the main language (hence, such a classification is also important for correct hyphenation of the entries).

Note that up to biblatex 3.3, the document language was not taken into account by the lowercasing automatism and all non-classified entries were treated like English entries (and thus lowercased), notwithstanding the main language; therefore, any entry needed to be coded. Even if this misbehaviour is fixed as of biblatex 3.4, it is still advisable to systematically set the proper `LangID`, since this is a prerequisite for a correct multilingual bibliography.

- The lowercasing automatism described above cannot deal properly with manual punctuation inside titles. Hence, a title such as `Maintitle. A subtitle` will come out as *Main title. a subtitle*. There are several ways to avoid that. The most proper one is to use the `title` and `subtitle` fields rather than adding everything to `title`. Alternatively, everything that is nested inside braces will not get lowercased, i. e. `Maintitle. {A} subtitle` will produce the correct result. This trick is also needed for names and other elements that should not get lowercased (*Introduction to {Germanic} linguistics*). However, please do not configure your BibTeX editor to generally embrace titles (this is a feature provided by many editors) since this will prevent biblatex-apa from lowercasing at places where it should be done.
- The biblatex-apa style requires that you use `biber` as a bibliography processor instead of `bibtex` (the program). See [4] for details.

9.3 Using a different style or not using biblatex

If you do not want or are not supposed to use neither the default Unified nor the APA/DGPs style, you can disable automatic biblatex loading via the class option `biblatex=false` (see sec. 4.3). In this case, you will need to load your own style manually, by entering the respective biblatex or BibTeX commands.

One case where you need to do that is if you prefer classic BibTeX over biblatex. If you want to follow the Applied Linguistics conventions, but prefer classic BibTeX

⁶Please refer to [6] and [3] for detailed instructions.

over biblatex, a BibTeX style file unified.bst that implements the *Unified Style Sheet for Linguistics* is available on the Internet.⁷ Note, though, that this package does not have specific support for German, so it is only really suitable if you write in English. Thus, if you want to follow the Applied Linguistics conventions, it is strongly recommended that you use biblatex with the preloaded univie-ling style.

It is also possible (though not recommended) to use the bibliography environment if, for some reason, you do not want to use biblatex nor BibTeX. Of course, in this case you are all responsible for the proper formatting of the entries. If you decide for this, you must load the natbib package and use the syntax documented in the natbib manual ([2, sec. 1]) for the proper setup of bibitems, e. g.,⁸

```
\bibitem[Jones et al.(1990)Jones, Baker, & Williams]{jon90}
      Jones, Baker, & Williams. 1990. ...
```

(Only) if natbib is loaded, univie-ling-expose will take care that the spacing with the bibliography environment is correct.

10 Further instructions

10.1 Commands and environments

Since the class draws on scrartcl, you can use all commands and environments provided by KOMA article in order to structure and typeset your document. Please refer to the comprehensive KOMA-Script manual [5] for information.

Please also refer to the template files included in the package for some further usage instructions and hints.

10.2 L^AT_EX layouts and templates

A layout for L^AT_EX⁹ can be retrieved from <https://github.com/jspitz/univie-ling/raw/master/lyx/layouts/univie-ling-expose.layout>.

Templates are provided as well:

- English template:
<https://github.com/jspitz/univie-ling/raw/master/lyx/templates/template-univie-ling-expose-english.lyx>
- German template:
<https://github.com/jspitz/univie-ling/raw/master/lyx/templates/template-univie-ling-expose-deutsch.lyx>

11 Release History

- Forthcoming (v. 2.8)

⁷<http://celxj.org/downloads/unified.bst>

⁸Note the missing space before and after the parentheses that mark the year!

⁹See <https://www.lyx.org>.

- Add basic support for bibliography environment.
- 2024/07/23 (v. 2.7)
 - Fix spacing after `\weblink`.
 - Fix empty argument check in `\weblink`.
- 2024/06/27 (v. 2.6)
 - Provide `\weblink`, `\SetURLDate` and `\urldate` macros.
- 2024/05/09 (v. 2.5)
 - No change to this class.
- 2023/03/31 (v. 2.4)
 - No change to this class.
- 2023/01/26 (v. 2.3)
 - No change to this class.
- 2022/12/06 (v. 2.2)
 - Fix boolean option parsing.
- 2022/10/21 (v. 2.1)
 - Fix **polyglossia** option.
- 2022/10/02 (v. 2.0)
 - Use `l3keys` rather than `xkeyval` for key-value option handling.
 - Fix some `varioref` definitions.
 - Use translator instead of translations for localization.
 - Various small class cleanups.
- 2022/09/08 (v. 1.20)
 - Load `varioref` AtBeginDocument.
- 2022/06/18 (v. 1.19)
 - Add option **fontenc**.
 - Fix translation of English example string.
 - Add monospaced font.
- 2022/05/11 (v. 1.18)
 - Fix error with subtitles.

- 2022/02/05 (v. 1.17)
 - Fix option **apa**.
 - Omit quotation marks when title is empty.
- 2021/11/03 (v. 1.16)
 - Add option **draftmark**. See sec. 4.4.
 - Fix grouping in **\maketitle**.
- 2021/10/19 (v. 1.15) No change to this class.
- 2021/09/01 (v. 1.14) No change to this class.
- 2020/11/11 (v. 1.13) No change to this class.
- 2020/06/25 (v. 1.12) No change to this class.
- 2020/05/05 (v. 1.11) New option **polyglossia**.
- 2020/05/01 (v. 1.10) No change to this class.
- 2019/01/21 (v. 1.9) No change to this class.
- 2019/01/15 (v. 1.8) No change to this class.
- 2018/11/07 (v. 1.7) No change to this class.
- 2018/11/04 (v. 1.6) Remove **subexamples** environment as this is now provided by covington.
- 2018/09/03 (v. 1.5) Introduce **subexamples** environment.
- 2018/04/26 (v. 1.4) Fix full date issue in biblatex bibliography style.
- 2018/03/02 (v. 1.3) No change to this class.
- 2018/02/13 (v. 1.2) No change to this class.
- 2018/02/11 (v. 1.1) No change to this class.
- 2018/02/08 (v. 1.0)
 - Switch default bibliography style (from APA to Unified).
 - Initial release to CTAN.
- 2016/05/05 (v. 0.7)
 - Fix comma after *et al.* with biblatex-apa.
- 2016/04/30 (v. 0.6)
 - Set proper citation command for csquotes' integrated environments.

- Improve templates.
- 2016/03/23 (v. 0.5)
 - Fix the output of German multi-name citations (DGPs guidelines).
 - Extend documentation of bibliographic features.
- 2016/01/29 (v. 0.4) Initial release.

References

- [1] Covington, Michael A. and Spitzmüller, Jürgen: *The covington Package. Macros for Linguistics*. September 7, 2018. <http://www.ctan.org/pkg/covington>.
- [2] Daly, Patrick W.: *Natural Sciences Citations and References*. September 13, 2010. <http://www.ctan.org/pkg/natbib>.
- [3] Kime, Philip: *APA Bib_{TEX} style. Citation and References macros for Bib_{TEX}*. March 3, 2016. <http://www.ctan.org/pkg/biblatex-apa>.
- [4] Kime, Philip and Charette, François: *Biber. A backend bibliography processor for biblatex*. March 6, 2016. <http://www.ctan.org/pkg/biber>.
- [5] Kohm, Markus (2015): KOMA-Script. The Guide. URL: <http://www.ctan.org/pkg/koma-script>.
- [6] Lehman, Philipp (with Audrey Boruvka, Philip Kime and Joseph Wright): *The biblatex Package. Programmable Bibliographies and Citations*. March 3, 2016. <http://www.ctan.org/pkg/biblatex>.