













₩ PHP

Window Object

The **window object** represents a window in browser. An object of window is created automatically by the browser.

Window is the object of browser, **it is not the object of javascript**. The javascript objects are string, array, date etc.



Note: if html document contains frame or iframe, browser creates additional window objects for each frame.

Methods of window object

The important methods of window object are as follows:

Method	Description			
alert()	displays the alert box containing message with ok button.			
confirm()	displays the confirm dialog box containing message with ok and cancel button.			
prompt()	displays a dialog box to get input from the user.			
open()	opens the new window.			
close()	closes the current window.			
setTimeout()	performs action after specified time like calling function, evaluating expressions etc.			

Example of alert() in javascript

It displays alert dialog box. It has message and ok button.

```
<script type="text/javascript">
function msg(){
  alert("Hello Alert Box");
}
</script>
<input type="button" value="click" onclick="msg()"/>
```

click

Example of confirm() in javascript

It displays the confirm dialog box. It has message with ok and cancel buttons.

```
<script type="text/javascript">
function msg(){
  var v= confirm("Are u sure?");
  if(v==true){
    alert("ok");
  }
  else{
    alert("cancel");
  }
}
</script>
<input type="button" value="delete record" onclick="msg()"/>
```

Output of the above example

delete record

Example of prompt() in javascript

It displays prompt dialog box for input. It has message and textfield.

```
<script type="text/javascript">
function msg(){
  var v= prompt("Who are you?");
  alert("I am "+v);
}
</script>
```

```
<input type="button" value="click" onclick="msg()"/>
```

Output of the above example

click

Example of open() in javascript

It displays the content in a new window.

```
<script type="text/javascript">
function msg(){
  open("http://www.javatpoint.com");
}
</script>
<input type="button" value="javatpoint" onclick="msg()"/>
```

Output of the above example

javatpoint


Example of setTimeout() in javascript

It performs its task after the given milliseconds.

```
<script type="text/javascript">
function msg(){
setTimeout(
function(){
alert("Welcome to Javatpoint after 2 seconds")
},2000);
}
</script>
<input type="button" value="click" onclick="msg()"/>
```

Output of the above example







B For Videos Join Our Youtube Channel: Join Now

Feedback

• Send your Feedback to feedback@javatpoint.com

Help Others, Please Share










Learn Latest Tutorials











React Native





Python Pillow

Python Turtle tutorial

Python Turtle

Keras tutorial

Preparation





Logical Reasoning Reasoning







Company Questions

Trending Technologies



















Git Tutorial





B.Tech / MCA

