Möglichkeiten zum Einbinden des SL3+ Brandings

1. Es ist möglich eine Schnelleingabemaske bereitzustellen. Siehe Kapitel „Stopfinder Request“.
2. Es ist möglich das SL3+ zu verlinken . Siehe Kapitel „Deeplink“.
3. Es ist möglich das Brandinglayout als IFRAME einzubinden. Siehe: https://developer.mozilla.org/de/docs/Web/HTML/Element/iframe

StopFinder-Request

Request-Example

- base URL: <host>/nwl-efa/XML_STOPFINDER_REQUEST → e.g. https://www.westfalenfahrplan.de/nwl-efa/XML_STOPFINDER_REQUEST?
- query string parameters:
  - 6 static
    - coordOutputFormat: “WGS84[dd.ddddd]”
    - outputFormat: “rapidJSON”
    - type_sf: “any”
    - locationServerActive: “1”
    - locationInfoActive: “1”
    - <customerAbbreviation>StopFinderMacro: “1” → e.g. nwlStopFinderMacro: "1"
  - 1 dynamic:
    - name_sf: <input value>

Example

User input is “ge hbf”

Corresponding stop finder request is
https://www.westfalenfahrplan.de/nwl-efa/XML_STOPFINDER_REQUEST?coordOutputFormat=WGS84%5Bdd.ddddd%5D&language=de&locationInfoActive=1&locationServerActive=1&name_sf=unna%20hbf&nwlStopFinderMacro=1&outputFormat=rapidJSON&serverInfo=1&sl3plusStopFinderMacro=1&type_sf=any&version=10.4.18.18

Response


```
▼{serverInfo: {controllerVersion: "10.4.25.29", serverID: "EFAMOBIL2_", virtDir: "vrrstd3",…},…}
  ▼locations: [{id: "de:05513:5613", isGlobalId: true, name: "Gelsenkirchen, Hbf", disassembledName: "Hbf",…}, {,…},…]
    ▼0: {id: "de:05513:5613", isGlobalId: true, name: "Gelsenkirchen, Hbf", disassembledName: "Hbf",…}
      ▶coord: [51.50493, 7.10221]
       disassembledName: "Hbf"
       id: "de:05513:5613"
       isBest: true
       isGlobalId: true
       matchQuality: 997
       name: "Gelsenkirchen, Hbf"
      ▶parent: {id: "placeID:5513000:9", name: "Gelsenkirchen", type: "locality"}
      ▶productClasses: [4, 5, 7, 10]
      ▼properties: {stopId: "20005613"}
         stopId: "20005613"
       type: "stop"
    ▶1: {,…}
    ▶2: {,…}
    ▶3: {,…}
    ▶4: {,…}
  ▶serverInfo: {controllerVersion: "10.4.25.29", serverID: "EFAMOBIL2_", virtDir: "vrrstd3",…}
  ▶systemMessages: [{type: "error", module: "BROKER", code: -8011, text: ""}]
   version: "10.4.18.18"
```


- **property “locations” is an array that consists of locations for given input (name_sf)**
- **you can use the name properties for each location to create a name string**
- **possible variations of property “type” (used for icon): stop, poi, street, singlehouse, suburb, address, platform**
- **the “id” property of a location is required for creating a deep link with the corresponding location**

DeepLink

Both mentioned cases (a and b) are tools to retrieve an ID from the user's input. These IDs can be used to load the SL3+ with preassigned values.

It is possible to preassign the journey planner page with the following form values:

- from
- to
- time
- date

The following parts are required:

- base URL: <host>/customerAbbreviation/trip?formik= → e.g. https://efademo.mentz.net/sl3+/trip?formik
- parameters for deep link:

form value		**parameter**		
form field	**example**	**parameter name**	**format**	**example**
from	GE HBF	origin		de:05513:5613
to	DO HBF	destination		de:05913:131
time	13:00	itdTime	HHmm	1300
date	10/06/2022	itdDateDayMonthYear	DDMMYYY	10062022
	Abfahrt	itdTripDateTimeDepArr		dep

- these parameters are nested within query string parameter **formik** and therefore need to be **encoded**

Examples (encoded):

https://www.westfalenfahrplan.de/nwlsl3+/trip?formik=destination%3Dde%253A05978%253A11186%26itdDateDayMonthYear%3D20082022%26itdTime%3D1024%26origin%3Dde%253A05978%253A11218&lng=de&sharedLink=true

No deep link parameter is required for the journey planner to work, you can omit any parameter you want.

Full deep link without date:

https://www.westfalenfahrplan.de/nwlsl3+/trip?formik=destination%3Dde%253A05978%253A11186%26origin%3Dde%253A05978%253A11218&lng=de&sharedLink=true