

ALL AROUND VALVE PARTNER SERIES

DELTA-T BUTTERFLY VALVES



Three butterfly designs, one Delta-T platform: resilient seated for **utility applications**, double offset for **process challenges**, triple offset for **critical control**.

Cartridge

REPLACEABLE SEAT

Field-replaceable cartridge seat enables in-line maintenance.

Anti-Blowout

GUIDED STEM

Internally guided, blowout-proof stem on every series - low operating torque with no external retainer to fail.

Class VI

BUBBLE-TIGHT

ANSI/FCI 70-2 bubble-tight shut-off and API 607 fire-safe certification on the 900 triple offset valves.

Vacuum Packing

FIRE-SAFE SEAT OPTION

Live-loaded packing seals bidirectionally with API 607 fire-safe construction available.

THE LINEUP



050 / 051 Series

RESILIENT SEATED

SIZES / CLASS

1 1/2" - 48" / 125 - 150

- Vacuum service capable
- Ductile iron body option
- NSF 61/372 certified



650 / 651 Series

RESILIENT SEATED

SIZES / CLASS

2" - 24" / 125 - 150

- Field repairable design
- Graphite-reinforced PTFE stem bushings
- Vacuum service capable



800 Series

HIGH PERFORMANCE

SIZES / CLASS

2" - 72" / 150 - 600

- WCB, CF8M, or exotic material
- Class VI bubble-tight bi-directional sealing
- Self-energized seat design



900 Series

TRIPLE OFFSET DESIGN

SIZES / CLASS

3" - 72" / 150 - 600

- Live loaded packing gland
- Field replaceable laminated seat
- Bottom stem & plated bearings for extended service life



C series

CAVITATION CONTROL

SIZES / CLASS

3" - 72" / 150 - 300

- Patented spherical disc & diffuser-plate design
- Self-energized seat design
- Field-adjustable packing standard

MILLIONS OF \$\$\$ IN REGIONAL STOCK · FAST LEAD TIMES
DIRECT ISO 5211 MOUNTING · NAMUR ACCESSORY PORTS · 3-YEAR WARRANTY

THE COMPLETE AUTOMATION PACKAGE



SOLENOID VALVES

SV / NV / SSV. NAMUR direct or inline. IP65, XP, or IS. 12-240 V AC/DC.



LIMIT SWITCHES

41 / 45 / 48 series. NEMA 4/4X to Class I Div 1. Mechanical, Magnetic, or Inductive.



POSITIONERS

PNY / PET / PES8 / PES9 smart positioners. HART partial-stroke testing. 4-20 mA / IS / XP.



ACCESSORIES

Manual operators (lockable), Lockout tagout brackets Custom fit-to-need brackets

READY TO SPEC? LET'S WALK YOUR PLANT.

Free Valve Walkdown - an MMS technician walks your facility, identifies failing or oversized actuators, and quotes Max-Air upgrades from regional stock.



SCAN TO REQUEST A VALVE WALKDOWN