

ALL AROUND VALVE PARTNER SERIES

MAX-ELECTRIC ACTUATORS

Max Electric
A Brand of Max-Air Technology.

Five Max-Electric series on one quarter turn platform - industrial duty for the plant floor, **heavy modulation** for continuous control, **hazardous-location** for corrosive zones, and **spring-return** for mechanical fail-safe.

100%

DUTY CYCLE

MF series rated for continuous duty per EN 60034 / ISO 22153 - built for full-time modulating service.

AIOC

BUILT-IN MODULATION

All-in-one controller field-selects between Open/Close/Jog and 4-20 mA without an external positioner.

LiFePO4

BATTERY BACKUP

Optional internal LiFePO4 pack drives the actuator to a fail-safe position on loss of main power.

ISO 5211

DIRECT MOUNT

F03 through F14 mounting flanges across the line bolt directly to any quarter-turn valve.

THE LINEUP



MX Series

HAZARDOUS LOCATION

TORQUE / ENCLOSURE
310 - 13,280 in-lbs
CSA-certified

- Class 1 Div 1, Groups C, D T4
- Class 2 Div 1, Groups E, F, G T130
- Refinery and petrochemical duty



ME Series

INDUSTRIAL

TORQUE / ENCLOSURE
310 - 40,000 in-lbs
NEMA 4/4X / IP67

- 8 frame sizes, full options suite
- O/C/Jog or 4-20 mA modulation
- Single-phase or 3-phase voltages



MF Series

HEAVY INDUSTRIAL

TORQUE / ENCLOSURE
310 - 13,280 in-lbs
NEMA 4/4X / IP67

- BLDC motor + LiFePO4 backup
- 100% continuous duty modulation
- Local control stations available



SX Series

HAZARDOUS LOCATION

TORQUE / ENCLOSURE
445 - 2,300 in-lbs
NEMA 4/4X/IP68

- Spring return + HazLoc in one body
- Clockwise and CCW spring return
- Mechanical fail in explosive zones



SE Series

INDUSTRIAL

TORQUE / ENCLOSURE
445 - 3,185 in-lbs
NEMA 4/4X/IP68

- Clockwise and CCW spring return
- Stored-energy spring - no battery required
- Submersible IP68 service rating

MILLIONS OF \$\$\$ IN REGIONAL STOCK · FAST LEAD TIMES
DIRECT ISO 5211 MOUNTING · NAMUR ACCESSORY PORTS · 3-YEAR WARRANTY

THE COMPLETE AUTOMATION PACKAGE



SOLENOID VALVES

SV / NV / SSV. NAMUR direct or inline. IP65, XP, or IS. 12-240 V AC/ DC.



LIMIT SWITCHES

41 / 45 / 48 series. NEMA 4/4X to Class I Div 1. Mechanical, Magnetic, or Inductive.



POSITIONERS

PNY / PET / PES8 / PES9 smart positioners. HART partial-stroke testing. 4-20 mA / IS / XP.



ACCESSORIES

Manual operators (lockable), Lockout tagout brackets Custom fit-to-need brackets

READY TO SPEC? LET'S WALK YOUR PLANT.

Free Valve Walkdown - an MMS technician walks your facility, identifies failing or oversized actuators, and quotes Max-Air upgrades from regional stock.



SCAN TO REQUEST A VALVE WALKDOWN