

ALL AROUND VALVE PARTNER SERIES

SESTO BALL VALVES



Five ball valve models on one Max-Air platform: **ISO 5211 direct mount** on every body, **API 607 fire-safe**, and a **3-year warranty**

ISO 5211

DIRECT MOUNT

Integral mounting pad on every body integrates seamlessly to Max-Air actuators without brackets or couplers.

API 607

FIRE-SAFE

Fire-tested across floating and trunnion series. API 6FA on heavy-duty pipeline trim.

ANTI-BLOWOUT

GUIDED STEM

Internally guided, blowout-proof stem on every series - low operating torque with no external retainer to fail.

B16.34

VALVE WALL THICKNESS

ASME B16.34 standards - full pressure-temperature ratings, code-compliant for B31.1 power/B31.3 process piping.

THE LINEUP



M21N Series

2-PIECE FULL BORE

SIZES / CLASS
1/4" - 4" / 1000 WOG

- Direct ISO 5211 mounting pad
- Threaded, SW, or BW ends
- Reinforced PTFE seats are standard



M31 Series

3-PIECE FULL BORE

SIZES / CLASS
1/4" - 4" / 1000 WOG

- Swing-out body, in-line maintenance
- Sanitary clamp option
- Live-loaded stem packing
- Bubble-tight shutoff



M150/M15F/M30F

FLANGED · ANSI 150/300

SIZES / CLASS
1/2" - 8" / 150 - 300

- ANSI B16.5 flange face, RF or RTJ
- Full or reduced port sizing
- Anti-static blowout-proof stem



TRUNNION | FORGED

HIGH PRESSURE · PIPELINE

SIZES / CLASS
1/2" - 36" / 150 - 2500

- Multi-port options available
- ESD/Cryogenic/Block & Bleed/Isolation
- API 607 / 6FA fire-safe



MV1F Series

SEGMENTED FLANGED

SIZES / CLASS
1" - 16" / 150

- V-notch ball: 30° / 60° / 90°
- Equal % or linear flow
- Anti-static device & live loaded packing

MILLIONS OF \$\$\$ IN REGIONAL STOCK · FAST LEAD TIMES
DIRECT ISO 5211 MOUNTING · NAMUR ACCESSORY PORTS · 3-YEAR WARRANTY

THE COMPLETE AUTOMATION PACKAGE



SOLENOID VALVES

SV / NV / SSV. NAMUR direct or inline. IP65, XP, or IS. 12-240 V AC/DC.



LIMIT SWITCHES

41 / 45 / 48 series. NEMA 4/4X to Class I Div 1. Mechanical, Magnetic, or Inductive.



POSITIONERS

PNY / PET / PES8 / PES9 smart positioners. HART partial-stroke testing. 4-20 mA / IS / XP.



ACCESSORIES

Manual operators (lockable), Lockout tagout brackets Custom fit-to-need brackets

READY TO SPEC? LET'S WALK YOUR PLANT.

Free Valve Walkdown - an MMS technician walks your facility, identifies failing or oversized actuators, and quotes Max-Air upgrades from regional stock.



SCAN TO REQUEST A VALVE WALKDOWN