

2. A person (ProxyBuyPerson) is going abroad and his friends (RealBuyPerson) need his help to buy something. We need to create a person interface (Person). The person interface has a buy function (BuyProduct). The real buy person has a product name attribute and a buy function. The proxy buy person has a real buy person attribute (realBuyPerson) and a buy function. Before purchasing, he needs to make a list of what his friends need (PreBuyProduct). After purchasing, he needs to record how much each friend should pay (PostBuyProduct).

Person

```
package experiment6_2;

interface Person {

    void BuyProduct();

}
```

ProxyBuyPerson

```
package experiment6_2;

public class ProxyBuyPerson implements Person {

    private RealBuyPerson realBuyPerson;

    private String[] productList;

    private String[] priceList;

    public ProxyBuyPerson(String[] productList, String[] priceList) {

        this.productList = productList;

    }
```

```

        this.priceList = priceList;
    }

    public void PreBuyProduct(){
        System.out.println("Before buying, record the goods
your friends need:");

        for(int i = 1; i <= productList.length; i++){
            System.out.println("Friend "+i+" needs to buy:
"+productList[i-1]);
        }
    }

    @Override
    public void BuyProduct() {
        PreBuyProduct();

        System.out.println("Proxy Man is buying products...");

        for (String product : productList) {
            realBuyPerson = new RealBuyPerson(product);
            realBuyPerson.BuyProduct();
        }

        PostBuyProduct();
    }
}

```

```

    public void PostBuyProduct(){
        System.out.println("After purchase, record the
amount paid by friends:");
        for(int i = 1;i <= priceList.length;i++){
            System.out.println("Friend "+i+" needs to pay:
"+priceList[i-1]);
        }
    }
}

```

RealBuyPerson

```

package experiment6_2;

public class RealBuyPerson implements Person{
    private String productName;

    public RealBuyPerson(String productName) {
        this.productName = productName;
    }

    @Override

```

```
    public void BuyProduct() {  
        System.out.println(productName+" is added to the  
cart");  
    }  
}
```

Test

```
package experiment6_2;  
  
public class Test {  
    public static void main(String[] args) {  
        String[] productList = {"iphone", "chocolate", "pen"};  
        String[] priceList = {"6800", "200", "30"};  
        ProxyBuyPerson proxyBuyPerson = new  
ProxyBuyPerson(productList, priceList);  
        proxyBuyPerson.BuyProduct();  
    }  
}
```

Output

```
D:\JDK\bin\java.exe "-javaagent:D:\idea\IntelliJ IDEA 2021.2.  
Before buying, record the goods your friends need:  
Friend 1 needs to buy: iphone  
Friend 2 needs to buy: chocolate  
Friend 3 needs to buy: pen  
Proxy Man is buying products...  
iphone is added to the cart  
chocolate is added to the cart  
pen is added to the cart  
After purchase, record the amount paid by friends:  
Friend 1 needs to pay: 6800  
Friend 2 needs to pay: 200  
Friend 3 needs to pay: 30  
  
Process finished with exit code 0
```