

# National Tsing Hua University

## Operating Systems

### Introduction to Nachos



**Dr. Nen-Fu Huang**

**Department of Computer Science, NTHU**

**E-mail: [nfhuang@cs.nthu.edu.tw](mailto:nfhuang@cs.nthu.edu.tw)**

© All rights reserved. No part of this publication and file may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of Professor Nen-Fu Huang (E-mail: [nfhuang@cs.nthu.edu.tw](mailto:nfhuang@cs.nthu.edu.tw)).

# Outline

---

- **Nachos**
  - **Introduction**
  - **Directory**
  - **DEBUG**
- **Basic Linux Command**

# Nachos- Introduction

---

- Not Another Completely Heuristic Operating System, or **Nachos**
- Developed at the University of California, Berkeley.
- Written in C++ for MIPS code machine simulator.
- Runs as a process on a host OS. In our case, host OS is Ubuntu 14.04 32-bit.

# Nachos- Directory

---

- **lib/**
  - some utilities used by Nachos code
  - Ex. sysdep.cc
- **machine/**
  - machine code simulation
  - Ex. mipssim.cc
- **threads/**
  - multi-threaded support code

# Nachos- Directory

---

- **network/**
  - some networking functions implementations, like post office and network communication
- **fileys/**
  - codes about file system
  - There are 2 files systems in Nachos. The **real** one use simulated disk to hold files. While the **stub** one translates those system calls of file to the host OS. You can modify Makefile to switch between the 2 modes.
  - Ex. fileys.h

# Nachos- Directory

---

- **userprog/**
  - OS codes to support address spaces, exception handling and so on
  - Ex. exception.cc
- **test/**
  - test programs to run on simulated machine
  - Ex. test1.c, start.s

# Nachos- DEBUG

- DEBUG(flag, expr)
- A special debug message implemented in Nachos.
- -flag: used to filter the type of debug message
  - All usable flags are defined in lib/debug.h.
  - You can also define your own flags!
- -expr: the message to be printed
- nachos -e <test file> -d <flag>
  - Ex. nachos -e halt -d a

```
// The pre-defined debugging flags are:
```

```
const char dbgAll = '+';           // turn on all debug messages
const char dbgThread = 't';        // threads
const char dbgSynch = 's';         // locks, semaphores, condition vars
const char dbgInt = 'i';           // interrupt emulation
const char dbgMach = 'm';          // machine emulation (USER_PROGRAM)
const char dbgDisk = 'd';          // disk emulation (FILESYS)
const char dbgFile = 'f';          // file system (FILESYS)
const char dbgAddr = 'a';          // address spaces (USER_PROGRAM)
const char dbgNet = 'n';           // network emulation (NETWORK)
```

```
case SC_Halt:
```

```
    DEBUG(dbgAddr, "Shutdown, initiated by user program.\n");
    kernel->interrupt->Halt();
    break;
```

# Basic Linux Command

---

- **> cd <path>**      #change directory
  - “..”:      parent directory
  - “~”:      home directory
  - “/”:      root directory
- **> ls**      #list files in current directory
- **> mv <source> <destination>**      #move(rename) file or directory
- **> cp [-r] <source> <destination>**      #copy file
  - recursive: copy a directory, including all its files and subdirectories
- **> rm [-r] [-f] <file name>**      #remove file
  - recursive: remove a directory, including all its files and subdirectories
  - force: force to remove



# Basic Linux Command

---

- > **mkdir** <directory name>      #make directory
- > **pwd**      #print work directory
- > **vi / vim** <file name>    #edit file with vi / vim
- > **sudo** <cmd>      #super user do

# Nachos- Directory

---

## Nachos

<https://homes.cs.washington.edu/~tom/nachos/>

[https://en.wikipedia.org/wiki/Not Another Completely Heuristic Operating System](https://en.wikipedia.org/wiki/Not_Another_Completely_Heuristic_Operating_System)

## Linux command

[http://linux.vbird.org/linux basic/0220filemanager.php](http://linux.vbird.org/linux_basic/0220filemanager.php)

**The End**

