Discrete Sliding Mode control of small UAS in tight formation flight under information constraints

J.Bolting[1] S.Fergani[1] J.-M.Biannic[2] F.Defay[1]
M.Stolle[2]

[1]Institut Supérieur de l'Aéronautique et de l'Espace (ISAE)

[2]Office National d'Études et de Recherches Aérospatiales (ONERA)

IFAC ACA'16

Outline

- $\Rightarrow$ Motivation
- $\Rightarrow$ Challenges
- $\Rightarrow$ Sliding Mode Control for relative position holding
- $\Rightarrow$ Predictive Discrete Sliding Mode Guidance laws
- $\Rightarrow$ Overview

Small UAS

=

Inexpensive

Easy to operate

Small UAS

=

Small payload

Small endurance

Benefit of tight and large formations [1]



Even lobsters do it



Why is it hard?

- dm-level relative position control under heavy perturbations in the wake
- desirable property: only **local** relative state information
- Existing linear control approaches ([3]), require leader information for mesh stability

One promising candidate:
Sliding Mode Control
performance & mesh stability

Guidance level: system dynamics



$$
\begin{aligned}
\Delta\mathbf{p}(t) &= \mathbf{p}_i(t) - \mathbf{p}_{i-1}(t) - \Delta\mathbf{p}_c(t) \\
\Delta\dot{\mathbf{p}}(t) &= \mathbf{v}_i(t) - \mathbf{v}_{i-1}(t) - \Delta\dot{\mathbf{p}}_c(t) \\
\Delta\dot{\mathbf{v}}(t) &= \mathbf{a}_i(t) - \mathbf{a}_{i-1}(t) - \Delta\ddot{\mathbf{p}}_c(t) \\
&= \mathbf{a}_{c,i}(t) + \mathbf{a}_{w,i}(t) - \mathbf{a}_{i-1}(t) - \Delta\ddot{\mathbf{p}}_c(t) \\
&= \mathbf{u}(t) + \mathbf{a}_{w,i}(t) - \mathbf{a}_{i-1}(t) - \Delta\ddot{\mathbf{p}}_c(t)
\end{aligned}
$$



Ideal Sliding Mode Control

- Insensitive to **matched** perturbations
- nonlinear
- Recently proposed for platooning [4] and formation flight [5]



Clash with reality

- actuator dynamics $\Rightarrow$ perturbations unmatched
- delays
- discrete implementation $\Rightarrow$ no infinite input switching

$\Rightarrow$ **Chattering, loss of mesh stability**

Continuous Time Sliding Mode Control applied to the UAS guidance loop

Longitudinal: TSCSMC [5] at 1000Hz



Longitudinal: TSCSMC at 100Hz



Predictive Discrete Sliding Mode Control

PDSMC

- Recent approach [7]
- Design directly in discrete time
- Preserve spirit of Sliding Mode Control: stay in boundary layer of sliding surface
- Minimizes boundary layer without tuning

Predictive Discrete Sliding Mode Control

What it looks like

$$\sigma(k) = \mathbf{G} \begin{pmatrix} \Delta \mathbf{p}(k) \\ \Delta \mathbf{v}(k) \end{pmatrix}$$

$$\sigma(k+1) = \sigma(k) + T(\mathbf{\Phi}'_k(k) + \mathbf{\Phi}'_u(k) + \mathbf{u}(k))$$

$$\underset{\mathbf{u}(k)}{\text{minimize}} \qquad |\sigma(k+1)|$$

Predictive Discrete Sliding Mode Control

Adding hard magnitude and rate constraints

$$\begin{aligned} \underset{\mathbf{u}(k)}{\text{minimize}} \quad & |\sigma(k+1)| \\ \text{subject to} \quad & \mathbf{U}_{min}(k) \leq \mathbf{u}(k) \leq \mathbf{U}_{max}(k) \end{aligned}$$

$$|\mathbf{u}(k) - \mathbf{u}(k-1)| \leq \boldsymbol{\Delta}\mathbf{U}$$

$$\mathbf{U}_{max}(k) = sat(\mathbf{u}(k-1) + \boldsymbol{\Delta}\mathbf{U}, -\mathbf{U}, \mathbf{U})$$
$$\mathbf{U}_{min}(k) = sat(\mathbf{u}(k-1) - \boldsymbol{\Delta}\mathbf{U}, -\mathbf{U}, \mathbf{U})$$

Simulation: PDSMC at 100Hz



Figures of Merit vs. sampling time



What about scalability?



Conclusion & Outlook

- PDSMC alleviates discretization issue of TSCSMC controller for TFF
- Extends existing PDSMC approaches to respect inner loop constraints

- Extend PDSMC further: inner loop dynamics, lower sampling rates, observation noise
- Better understand and quantify mesh instability

- D. Hummel, "Aerodynamic aspects of formation flight in birds," *Journal of theoretical Biology*, 1982.
- V. Jake, R. Ray, K. Ennix, and K. Walsh, "F/A-18 Performance Benefits Measured During the Autonomous Formation Flight Project," tech. rep., NASA/TM-2002-210732, Sept, 2003.
- E. Shaw and J. K. Hedrick, "Controller design for string stable heterogeneous vehicle strings," in *Decision and Control, 2007 46th IEEE Conference on*, pp. 2868–2875, IEEE, 2007.
- F. Fahimi, "Sliding-mode formation control for underactuated surface vessels," *Robotics, IEEE Transactions on*, vol. 23, no. 3, pp. 617–622, 2007.
- D. Galzi and Y. Shtessel, "UAV formations control using high order sliding modes," in *American Control Conference, 2006*, pp. 6–pp, IEEE, 2006.

A. Dogan, S. Venkataramanan, and W. Blake, “Modeling of aerodynamic coupling between aircraft in close proximity,” *Journal of Aircraft*, vol. 42, no. 4, pp. 941–955, 2005.

B. M. Houda, D. Khadija, and N. A. Said, “New discrete predictive sliding mode control for non minimum phase systems,” *International Journal of Computer Applications*, vol. 70, no. 11, 2013.