

T

Transactional truth
service-owned PostgreSQL
the record others follow
built in the lab

F

Durable fact log
JetStream, limits policy
append only, replayable
built in the lab

W

Workflow state
Temporal persistence
runs in flight, not records
built in the lab

R

Derived read model
projection plus KV cache
rebuildable, not the truth
built in the lab

E

Evidence documents
repository behind adapter
write once, never edited
proposed · no V3 ADR

one change is committed once, then told to the others

1

A database per service
own schema, own role, own migrations
ADR-052 · applied in the lab
built in the lab

2

Shared instance by default
isolation is logical, not physical
ADR-053 · accepted, not applied
proposed for V3

3

The service mints the ID
never the database, never a default
ADR-051 · a ULID, subject-safe
built in the lab

4

One writer per record
the owner writes, others are told
no second service updates it
built in the lab

a committed change becomes a published fact

A

Command accepted
the domain rule is checked first
no rule lives in a handler
built in the lab

B

Commit with an outbox
state and its fact, one transaction
a fact cannot contradict the record
proposed · no V3 ADR

C

Fact published
on the owning service's stream
one publisher per subject family
built in the lab

D

Projector writes both
the projection and the cache
one handler, so they cannot drift
built in the lab

a reader never opens another service's database

1

Cache read first
NATS KV, keyed by context
the fast answer, not the truth
built in the lab

2

A miss falls through
to the projection table beneath
a cold cache is never an error
built in the lab

3

The owner answers
over a request-reply contract
the caller names no table
built in the lab

4

Governed extraction
reporting calls and bulk exports
the only route out of the platform
proposed · no V3 ADR

X

No foreign database read
not another service, not a report, not a script

a contract or nothing; a shared table is a hidden coupling
built in the lab · enforced by a database role per service

!

Keep history only where it must replay
otherwise current state alone is a plain record

replay when a rule, an audit or a rebuild reads the order
directional position as at 2026-09-04 · no V3 ADR of record

SCOPE

One question. Which store owns what, and how does one change reach the rest? Reference data and retention are on sheet 2.

MATURITY

Mixed. Solid tiles run in the lab today. Dashed tiles are directional V3 positions as at 2026-09-04.

ROLE

A store is named by its **role**, never by product alone. The role decides the rules that follow it.

TRUTH

PostgreSQL is the **default source of truth**. The fact log records what happened; it does not replace the record.

OWNER

One service owns its data. Others are **told** through a fact or **ask** through a contract. Nobody else writes.

OUTBOX

An **outbox** writes the fact in the same transaction as the state, so a published fact can never disagree with the record.

PROJECTOR

One handler writes **both** the projection and the cache entry. Two writers would let them drift apart silently.

CACHE

The cache is an **answer**, not a record. A miss falls through to the projection and costs nothing but time.

REPLAY

Event-source only where something must **replay** the sequence. Current-state-only data stays a plain record.

OPEN

Ten open items sit in the **L3-07 register**. The outbox and the extraction interface have no V3 ADR.

Read it downward. Five stores each hold one kind of data, one service owns each one, a single commit turns into a fact and then into a read model, and a reader is served by the cache, the projection or a contract. **Built today:** every solid tile — the database, the fact log, the projector, the cache and the read path. **Not shown:** subjects and streams, which are LB-V3-L3-05 ; where a store sits, which is LB-V3-L3-08 ; tables, columns and migrations, which are L4 .

Reference Data, Distribution and Lifecycle

Where shared values come from, how one changed value reaches every reader without polling, and how long each kind of data is kept. Reference data is more than code lists: it also carries localisation, translation, App Shell theme values and platform configuration. **Maturity is marked per element**, and every retention period is deliberately shown as **not set**. **This half is directional** as at 4 September 2026 and no V3 decision of record exists for retention or lifecycle. Rendering the theme belongs to LB-V3-L3-03; what may be copied to another cell belongs to LB-V3-L3-08.

