Function	P-0 $2^{15} \_\_\_ 2^0$	P-1 $2^{15} \_\_\_ 2^0$	P-2 $2^{15} \_\_\_ 2^0$	P-3 $2^{15} \_\_\_ 2^0$	Function Description
000	ODD000	0	0	0	Clear External Master Clear (NSC)
001	ODD001	0	0	0	Clear External Input Control
002	ODD002	0	0	0	Clear External Output Control
003	ODD003	0	0	0	Clear External Input and Output Control
004	ODD004	0	0	0	Set External Master Clear (NSC)
010	ODD010	Interrupt Address $2^{15} \_\_\_ 2^0$	0	0	Enable external interrupt
020	ODD020	0	0	0	Enable disconnect
021	ODD021	0	0	0	Hold disconnect *(Disables disconnect)*
022	ODD022	0	0	0	Write disconnect *Sends Disconnect*
030	ODD030	Length $2^8 \_\_\_ 2^0$	0	0	Read Length/Status Registers
040	ODD040	Length $2^8 \_\_\_ 2^0$	0	0	Read N words from the channel *loop*
050	ODD050	Length $2^8 \_\_\_ 2^0$	0	0	Write N words to the channel
060	ODD060	Interrupt Address $2^{15} \_\_\_ 2^0$	0	Length $2^8 \_\_\_ 2^0$	Read N words from the external device
070	ODD070	Interrupt Address $2^{15} \_\_\_ 2^0$	0	Length $2^8 \_\_\_ 2^0$	Write N words to the external device
100	ODD100	Buffer Address $2^8 \_\_\_ 2^0$	0	0	Send lower 32 bits at address N to foreground
101	ODD101	Buffer Address $2^8 \_\_\_ 2^0$	0	0	Send upper 32 bits at address N to foreground
110	ODD110	Buffer Address $2^8 \_\_\_ 2^0$	Data $2^{31} \_\_\_ 2^{16}$	Data $2^{15} \_\_\_ 2^0$	Receive lower 32 bits from foreground and write to address N
111	ODD111	Buffer Address $2^8 \_\_\_ 2^0$	Data $2^{63} \_\_\_ 2^{48}$	Data $2^{47} \_\_\_ 2^{32}$	Receive upper 32 bits from foreground and write to address N
120	ODD120	0	0	0	Set low speed mode, clear NSC mode

DD = 40-43$_8$ (Device Select, Selects one DB node)

Low Speed/NSC (DB) Node Functions