




# NØMADE: Lightweight HPC Monitoring with Machine Learning-Based Failure Prediction

João Filipe Riva Tonini <sup>1</sup>✉

<sup>1</sup> Academic Research Computing, University of Richmond, VA 23173, USA ✉ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

NØMADE (NØde MAnagement DEvice) is a lightweight monitoring and predictive analytics tool for High-Performance Computing (HPC) clusters. It collects system metrics from SLURM-managed environments, stores time-series data in SQLite, and employs machine learning to predict job failures before they occur. The tool provides a real-time web dashboard and supports alerts via email, Slack, or webhooks. NØMADE requires no external databases or complex infrastructure—only Python and standard system tools.

A key innovation is the application of biogeographical network analysis concepts to HPC monitoring. Inspired by methods for identifying transition zones between bioregions ([Vilhena & Antonelli, 2015](#)), NØMADE treats HPC resource domains (compute, storage, network) as interconnected regions where failures cluster at domain boundaries—such as transitions between local scratch and network-attached storage (NAS), or between CPU and GPU workloads. This enables failure pattern recognition that emerges from the data rather than from predefined rules.

## Statement of Need

HPC administrators face a persistent challenge: detecting job failures before they impact researchers. Enterprise monitoring solutions like Prometheus, Grafana, or Nagios require significant infrastructure and target general IT systems rather than HPC-specific workloads. Existing HPC tools such as TACC Stats ([Evans et al., 2014](#)), XDMoD ([Palmer et al., 2015](#)), and LLNL's Lightweight Distributed Metric Service ([Agelastos et al., 2014](#)) provide detailed metrics but require substantial deployment effort and focus on post-hoc analysis rather than real-time prediction.

Common HPC failure patterns include:

- **NFS saturation:** Jobs writing to network storage instead of local scratch
- **Memory leaks:** Gradual consumption leading to out-of-memory kills
- **GPU thermal throttling:** Temperature-induced performance degradation
- **Queue starvation:** Resource contention causing excessive wait times


These failures often exhibit warning signs minutes to hours before critical thresholds are breached. NØMADE addresses this gap by providing:

- **Zero-infrastructure deployment:** Single SQLite database, no external services
- **Real-time prediction:** ML ensemble identifies high-risk jobs before failure
- **Predictive alerts:** Derivative analysis detects accelerating resource consumption
- **Domain-aware analysis:** Recognizes HPC-specific failure patterns at resource boundaries

The tool is suited for small-to-medium HPC centers, research groups managing clusters, or as a complement to existing monitoring infrastructure.

40 **Implementation**

41 NØMADE is implemented in Python and follows a modular architecture (Figure 1):



**Figure 1:** NØMADE architecture showing the data flow from collectors through the prediction engine to alert dispatch.




Figure 2: NØMADE dashboard showing cluster health with per-node job statistics, CPU utilization rings, and failure breakdown.




Figure 3: Network visualization showing jobs clustered by feature similarity. Failed jobs (red/orange) cluster separately from successful jobs (green), enabling pattern-based failure prediction.

- 42
- 43
- 44
- 45
- 46
- 47
- 48
- 49
- 50
- 51
- 52
- 53
- 54
- Collectors** gather metrics from system tools (`iostat`, `vmstat`, `nvidia-smi`), SLURM commands (`sacct`, `queue`, `sinfo`), and per-job I/O statistics from `/proc/[pid]/io`. A SLURM prolog hook captures job context at submission time.

**Feature Engineering** transforms raw metrics into a 17-dimensional feature vector per job, including CPU and memory efficiency from `sacct`, NFS write ratios from the job monitor, and system-level indicators (I/O wait, memory pressure, swap activity). These features enable similarity-based analysis across jobs.

**ML Prediction** uses an ensemble of three models:

  - Graph Neural Network (GNN): Captures relationships between similar jobs based on Simpson similarity of feature vectors
  - LSTM: Detects temporal patterns and early warning trajectories
  - Autoencoder: Identifies anomalous jobs that deviate from normal behavior

The ensemble outputs a continuous risk score (0–1) rather than binary classification, providing

55 nuanced assessment of job health.

56 **Alert System** supports both threshold-based alerts (disk usage, GPU temperature) and predictive  
57 alerts using derivative analysis. When the rate of change indicates a threshold will be breached,  
58 alerts fire before the actual breach occurs. Notifications route through email, Slack, or  
59 webhooks with configurable cooldowns to prevent alert fatigue.

## 60 Usage

61 NØMADE installs via pip and initializes with two commands:

```
pip install nomade-hpc
nomade init
nomade collect    # Start data collection
nomade dashboard  # Launch web interface
```

62 For HPC-wide deployment, system installation configures systemd services and SLURM prolog  
63 hooks:

```
sudo nomade init --system
sudo systemctl enable --now nomade nomade-learn
```

64 The dashboard displays real-time cluster health, job risk assessments, and historical trends.  
65 Configuration uses TOML files supporting custom thresholds, alert destinations, and collection  
66 intervals.

## 67 Acknowledgements

68 The author thanks George Flanagan for advice and inspiration on HPC system administration,  
69 and the University of Richmond Research Computing group for cluster access and testing.

## 70 References

- 71 Agelastos, A., Allan, B., Brandt, J., Cassella, P., Enos, J., Fullop, J., Gentile, A., Monk, S.,  
72 Naksinehaboon, N., Ogden, J., Rajan, M., Showerman, M., Stevenson, J., Taber, N., &  
73 Tucker, T. (2014). The lightweight distributed metric service: A scalable infrastructure  
74 for continuous monitoring of large scale computing systems and applications. *SC '14:  
75 Proceedings of the International Conference for High Performance Computing, Networking,  
76 Storage and Analysis*, 154–165. <https://doi.org/10.1109/SC.2014.18>
- 77 Evans, R. T., Barth, W. L., Browne, J. C., DeLeon, R. L., Furlani, T. R., Gallo, S. M., Jones,  
78 M. D., & Patra, A. K. (2014). TACC Stats: Analysis of HPC system resource usage.  
79 *Proceedings of the 2014 Annual Conference on Extreme Science and Engineering Discovery  
80 Environment*, 1–8. <https://doi.org/10.1145/2616498.2616533>
- 81 Palmer, J. T., Gallo, S. M., Furlani, T. R., Jones, M. D., DeLeon, R. L., White, J. P.,  
82 Simakov, N., Patra, A. K., Sperhac, J., Yearke, T., Rathsam, R., Inber, M., Cornelius,  
83 C. D., & Browne, J. C. (2015). XDMoD: A tool for the comprehensive management  
84 of high-performance computing resources. *Computing in Science & Engineering*, 17(2),  
85 52–62. <https://doi.org/10.1109/MCSE.2015.32>
- 86 Vilhena, D. A., & Antonelli, A. (2015). A network approach for identifying and delimiting  
87 biogeographical regions. *Nature Communications*, 6(1), 6848. [https://doi.org/10.1038/  
88 ncomms7848](https://doi.org/10.1038/ncomms7848)