Example Corp

# Container Image Vulnerability Scan Report

| | |
|---|---|
| Scope | demo |
| Scan Source | Trivy (files) |
| Images | 4 |
| Scan Period | 2026-11-07T14:32:23Z – 2026-11-07T14:33:40Z |
| Generated | 2026-11-09 |

# Contents

Summary ..... 3
Remediation ..... 5
Vulnerability Inventory ..... 16
Image Details ..... 45
  `nginx:1.21.0` ..... 45
  `ghcr.io/christophetd/log4shell-vulnerable-app:latest` ..... 73
  `alpine:3.22` ..... 97
  `busybox:1.37` ..... 97
Appendix ..... 98

# Summary

This report covers 4 images and 461 unique vulnerabilities.

**44** Critical

**227** High

**365** Medium

**183** Low

Unrated 9



Critical 44 High 227 Medium 365 Low 183 Unrated 9

**742**

(90%) have fixes available

**2**

of 4 images contain Critical or High vulnerabilities

## Priority Images

| Image | Critical | High | Medium | Low |
|---|---|---|---|---|
| nginx:1.21.0 | 27 | 142 | 193 | 23 |
| ghcr.io/christophetd/log4shell-vulnerable-app:latest | 17 | 85 | 171 | 160 |
| alpine:3.22 | 0 | 0 | 1 | 0 |
| busybox:1.37 | 0 | 0 | 0 | 0 |

## Priority Vulnerabilities

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2021-44228 | Critical | 10.0 | org.apache.logging.log4j:log4j-core | 2.15.0, 2.3.1, 2.12.2 | 1 |
| CVE-2016-1000027 | Critical | 9.8 | org.springframework:spring-web | 6.0.0 | 1 |
| CVE-2019-12900 | Critical | 9.8 | libbz2 | 1.0.6-r7 | 1 |
| CVE-2019-14697 | Critical | 9.8 | musl, musl-utils | 1.1.19-r11 | 1 |
| CVE-2019-8457 | Critical | 9.8 | libdb5.3, sqlite-libs | 3.25.3-r1 | 2 |
| CVE-2021-33574 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| CVE-2021-3711 | Critical | 9.8 | libssl1.1, openssl | 1.1.1d-0+deb10u7 | 1 |
| CVE-2022-1471 | Critical | 9.8 | org.yaml:snakeyaml | 2.0 | 1 |
| CVE-2022-1664 | Critical | 9.8 | dpkg | 1.19.8 | 1 |
| CVE-2022-22822 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| CVE-2022-22823 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| CVE-2022-22824 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| CVE-2022-22965 | Critical | 9.8 | org.springframework:spring-beans, org.springframework:spring-webmvc | 5.2.20.RELEASE, 5.3.18 | 1 |
| CVE-2022-23218 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2022-23219 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |

# Remediation

Prioritize updating the following packages to fixed versions to reduce vulnerability risk.

### libexpat1 → 2.2.6-2+deb10u2

Resolves 4 Critical, 6 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

### libc-bin → 2.28-10+deb10u2

Resolves 4 Critical, 4 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

### libc6 → 2.28-10+deb10u2

Resolves 4 Critical, 4 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

### libexpat1 → 2.2.6-2+deb10u3

Resolves 3 Critical, 1 High, 1 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

### openjdk8 → 8.191.12-r0

Resolves 1 Critical, 2 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

### openjdk8-jre → 8.191.12-r0

Resolves 1 Critical, 2 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

### openjdk8-jre-base → 8.191.12-r0

Resolves 1 Critical, 2 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

### openjdk8-jre-lib → 8.191.12-r0

Resolves 1 Critical, 2 High, 4 Medium, and 2 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

### libfreetype6 → 2.9.1-3+deb10u3

Resolves 1 Critical, 2 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**libssl1.1 → 1.1.1d-0+deb10u7**

Resolves 1 Critical, 1 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**openssl → 1.1.1d-0+deb10u7**

Resolves 1 Critical, 1 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**curl → 7.64.0-4+deb10u4**

Resolves 1 Critical, 0 High, 2 Medium, and 1 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**libcurl4 → 7.64.0-4+deb10u4**

Resolves 1 Critical, 0 High, 2 Medium, and 1 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**dpkg → 1.19.8**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**libbz2 → 1.0.6-r7**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**libldap-2.4-2 → 2.4.47+dfsg-3+deb10u7**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**libldap-common → 2.4.47+dfsg-3+deb10u7**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**libtasn1-6 → 4.13-3+deb10u1**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`nginx:1.21.0`

**musl → 1.1.19-r11**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**musl-utils → 1.1.19-r11**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.apache.logging.log4j:log4j-core → 2.15.0, 2.3.1, 2.12.2**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.apache.logging.log4j:log4j-core → 2.16.0, 2.12.2, 2.3.1**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.apache.tomcat.embed:tomcat-embed-core → 11.0.15, 10.1.50, 9.0.113**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.apache.tomcat.embed:tomcat-embed-core → 11.0.3, 10.1.35, 9.0.99**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.springframework:spring-beans → 5.2.20.RELEASE, 5.3.18**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.springframework:spring-web → 6.0.0**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.springframework:spring-webmvc → 5.2.20.RELEASE, 5.3.18**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.springframework:spring-webmvc → 7.0.9**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**org.yaml:snakeyaml → 2.0**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

**sqlite-libs → 3.25.3-r1**

Resolves 1 Critical, 0 High, 0 Medium, and 0 Low vulnerabilities. Affects 1 images.

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

## Further fixes

239 further fixes are listed below.

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| zlib1g | 1:1.2.11.dfsg-1+deb10u2 | 1 | 0 | 0 | 0 | 1 |
| curl | 7.64.0-4+deb10u3 | 0 | 4 | 4 | 2 | 1 |
| libcurl4 | 7.64.0-4+deb10u3 | 0 | 4 | 4 | 2 | 1 |
| libssl1.1 | 1.1.1n-0+deb10u4 | 0 | 3 | 2 | 0 | 1 |
| openssl | 1.1.1n-0+deb10u4 | 0 | 3 | 2 | 0 | 1 |
| libssh2-1 | 1.8.0-2.1+deb10u1 | 0 | 3 | 0 | 0 | 1 |
| libxpm4 | 1:3.5.12-1+deb10u1 | 0 | 3 | 0 | 0 | 1 |
| openjdk8 | 8.272.10-r0 | 0 | 2 | 4 | 10 | 1 |
| openjdk8-jre | 8.272.10-r0 | 0 | 2 | 4 | 10 | 1 |
| openjdk8-jre-base | 8.272.10-r0 | 0 | 2 | 4 | 10 | 1 |
| openjdk8-jre-lib | 8.272.10-r0 | 0 | 2 | 4 | 10 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 0 | 2 | 4 | 1 | 1 |
| openjdk8 | 8.252.09-r0 | 0 | 2 | 3 | 5 | 1 |
| openjdk8-jre | 8.252.09-r0 | 0 | 2 | 3 | 5 | 1 |
| openjdk8-jre-base | 8.252.09-r0 | 0 | 2 | 3 | 5 | 1 |
| openjdk8-jre-lib | 8.252.09-r0 | 0 | 2 | 3 | 5 | 1 |
| openjdk8 | 8.212.04-r0 | 0 | 2 | 1 | 0 | 1 |
| openjdk8-jre | 8.212.04-r0 | 0 | 2 | 1 | 0 | 1 |
| openjdk8-jre-base | 8.212.04-r0 | 0 | 2 | 1 | 0 | 1 |
| openjdk8-jre-lib | 8.212.04-r0 | 0 | 2 | 1 | 0 | 1 |
| org.apache.logging.log4j:log4j-core | 2.25.4 | 0 | 2 | 1 | 0 | 1 |
| libncursesw6 | 6.1+20181013-2+deb10u5 | 0 | 2 | 0 | 0 | 1 |
| libnghttp2-14 | 1.36.0-2+deb10u2 | 0 | 2 | 0 | 0 | 1 |
| libtinfo6 | 6.1+20181013-2+deb10u5 | 0 | 2 | 0 | 0 | 1 |
| libxml2 | 2.9.4+dfsg1-7+deb10u5 | 0 | 2 | 0 | 0 | 1 |
| libxslt1.1 | 1.1.32-2.2~deb10u2 | 0 | 2 | 0 | 0 | 1 |
| ncurses-base | 6.1+20181013-2+deb10u5 | 0 | 2 | 0 | 0 | 1 |
| ncurses-bin | 6.1+20181013-2+deb10u5 | 0 | 2 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M21, 10.1.25, 9.0.90 | 0 | 2 | 0 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.2, 10.1.34, 9.0.98 | 0 | 2 | 0 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u5 | 0 | 1 | 18 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u7 | 0 | 1 | 11 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u4 | 0 | 1 | 8 | 0 | 1 |
| curl | 7.64.0-4+deb10u6 | 0 | 1 | 3 | 0 | 1 |
| libc-bin | 2.28-10+deb10u4 | 0 | 1 | 3 | 0 | 1 |
| libc6 | 2.28-10+deb10u4 | 0 | 1 | 3 | 0 | 1 |
| libcurl4 | 7.64.0-4+deb10u6 | 0 | 1 | 3 | 0 | 1 |
| libssl1.1 | 1.1.1n-0+deb10u5 | 0 | 1 | 3 | 0 | 1 |
| openssl | 1.1.1n-0+deb10u5 | 0 | 1 | 3 | 0 | 1 |
| org.yaml:snakeyaml | 1.31 | 0 | 1 | 3 | 0 | 1 |
| openjdk8 | 8.242.08-r0 | 0 | 1 | 2 | 4 | 1 |
| openjdk8-jre | 8.242.08-r0 | 0 | 1 | 2 | 4 | 1 |
| openjdk8-jre-base | 8.242.08-r0 | 0 | 1 | 2 | 4 | 1 |
| openjdk8-jre-lib | 8.242.08-r0 | 0 | 1 | 2 | 4 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.8, 10.1.42, 9.0.106 | 0 | 1 | 2 | 1 | 1 |
| libgd3 | 2.2.5-5.2+deb10u1 | 0 | 1 | 2 | 0 | 1 |
| libpng | 1.6.37-r0 | 0 | 1 | 2 | 0 | 1 |
| libx11-6 | 2:1.6.7-1+deb10u4 | 0 | 1 | 2 | 0 | 1 |
| libx11-data | 2:1.6.7-1+deb10u4 | 0 | 1 | 2 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.25, 10.1.58, 9.0.121 | 0 | 1 | 2 | 0 | 1 |
| org.springframework:spring-expression | 7.0.8, 6.2.19 | 0 | 1 | 2 | 0 | 1 |
| com.fasterxml.jackson.core:jackson-databind | 2.18.8, 2.21.4, 3.1.4 | 0 | 1 | 1 | 0 | 1 |
| libgnutls30 | 3.6.7-4+deb10u9 | 0 | 1 | 1 | 0 | 1 |
| libssl1.1 | 1.1.1d-0+deb10u8 | 0 | 1 | 1 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u9 | 0 | 1 | 1 | 0 | 1 |
| openssl | 1.1.1d-0+deb10u8 | 0 | 1 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94 | 0 | 1 | 1 | 0 | 1 |
| sqlite-libs | 3.25.3-r3 | 0 | 1 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.11, 10.1.45, 9.0.109 | 0 | 1 | 0 | 1 | 1 |
| com.fasterxml.jackson.core:jackson-core | 2.15.0 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core:jackson-core | 2.18.8, 2.21.4 | 0 | 1 | 0 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| com.fasterxml.jackson.core: jackson-core | 2.21.7, 2.22.3, 2.18.11 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.12.6, 2.13.1 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.12.7.1, 2.13.4 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.12.7.1, 2.13.4.2 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.13.2.1, 2.12.6.1 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.14.0 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.18.11, 2.21.7, 2.22.3 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.18.8, 3.1.4, 2.21.4 | 0 | 1 | 0 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.21.7, 2.18.11, 2.22.3 | 0 | 1 | 0 | 0 | 1 |
| curl | 7.64.0-4+deb10u9 | 0 | 1 | 0 | 0 | 1 |
| gzip | 1.9-3+deb10u1 | 0 | 1 | 0 | 0 | 1 |
| libc-bin | 2.28-10+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libc6 | 2.28-10+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libcurl4 | 7.64.0-4+deb10u9 | 0 | 1 | 0 | 0 | 1 |
| libexpat1 | 2.2.6-2+deb10u5 | 0 | 1 | 0 | 0 | 1 |
| libexpat1 | 2.2.6-2+deb10u6 | 0 | 1 | 0 | 0 | 1 |
| libexpat1 | 2.2.6-2+deb10u7 | 0 | 1 | 0 | 0 | 1 |
| libgmp10 | 2:6.1.2+dfsg-4+deb10u1 | 0 | 1 | 0 | 0 | 1 |
| libgnutls30 | 3.6.7-4+deb10u10 | 0 | 1 | 0 | 0 | 1 |
| libgnutls30 | 3.6.7-4+deb10u12 | 0 | 1 | 0 | 0 | 1 |
| libgssapi-krb5-2 | 1.17-3+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libgssapi-krb5-2 | 1.17-3+deb10u5 | 0 | 1 | 0 | 0 | 1 |
| libjpeg-turbo | 1.5.3-r6 | 0 | 1 | 0 | 0 | 1 |
| libk5crypto3 | 1.17-3+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libk5crypto3 | 1.17-3+deb10u5 | 0 | 1 | 0 | 0 | 1 |
| libkrb5-3 | 1.17-3+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libkrb5-3 | 1.17-3+deb10u5 | 0 | 1 | 0 | 0 | 1 |
| libkrb5support0 | 1.17-3+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libkrb5support0 | 1.17-3+deb10u5 | 0 | 1 | 0 | 0 | 1 |
| liblzma5 | 5.2.4-1+deb10u1 | 0 | 1 | 0 | 0 | 1 |
| libncursesw6 | 6.1+20181013-2+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libsasl2-2 | 2.1.27+dfsg-1+deb10u2 | 0 | 1 | 0 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| libsasl2-modules-db | 2.1.27+dfsg-1+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libssl1.1 | 1.1.1n-0+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libssl1.1 | 1.1.1n-0+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libsystemd0 | 241-7~deb10u9 | 0 | 1 | 0 | 0 | 1 |
| libtinfo6 | 6.1+20181013-2+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libudev1 | 241-7~deb10u9 | 0 | 1 | 0 | 0 | 1 |
| libwebp6 | 0.6.1-2+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| libwebp6 | 0.6.1-2+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libx11-6 | 2:1.6.7-1+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libx11-data | 2:1.6.7-1+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| libxml2 | 2.9.4+dfsg1-7+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| ncurses-base | 6.1+20181013-2+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| ncurses-bin | 6.1+20181013-2+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| openssl | 1.1.1n-0+deb10u2 | 0 | 1 | 0 | 0 | 1 |
| openssl | 1.1.1n-0+deb10u3 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 10.1.5, 11.0.0-M5, 8.5.88, 9.0.71 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M11, 10.1.16, 9.0.83, 8.5.96 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.10, 10.1.44, 9.0.108 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.5, 10.1.37, 9.0.101 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 8.5.83, 9.0.68, 10.0.27, 10.1.1 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 8.5.84, 9.0.69, 10.1.2 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 8.5.99, 9.0.86, 10.1.19, 11.0.0-M17 | 0 | 1 | 0 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-websocket | 11.0.0-M17, 10.1.19, 9.0.86, 8.5.99 | 0 | 1 | 0 | 0 | 1 |
| org.springframework.boot:spring-boot | 3.3.11, 3.4.5 | 0 | 1 | 0 | 0 | 1 |
| org.springframework.boot:spring-boot | 4.0.6, 3.5.14 | 0 | 1 | 0 | 0 | 1 |
| org.springframework.boot:spring-boot-autoconfigure | 3.0.7, 2.7.12, 2.6.15, 2.5.15 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-core | 6.2.11 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-core | 7.0.8, 6.2.19 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-web | 5.3.34, 6.0.19, 6.1.6 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-web | 6.1.5, 6.0.18, 5.3.33 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-webmvc | 6.0.7, 5.3.26 | 0 | 1 | 0 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| org.springframework:spring-webmvc | 6.1.13 | 0 | 1 | 0 | 0 | 1 |
| org.springframework:spring-webmvc | 6.1.14 | 0 | 1 | 0 | 0 | 1 |
| sqlite-libs | 3.25.0-r4 | 0 | 1 | 0 | 0 | 1 |
| sqlite-libs | 3.25.3-r0 | 0 | 1 | 0 | 0 | 1 |
| zlib1g | 1:1.2.11.dfsg-1+deb10u1 | 0 | 1 | 0 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u8 | 0 | 0 | 8 | 0 | 1 |
| org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 0 | 0 | 7 | 0 | 1 |
| openjdk8 | 8.232.09-r0 | 0 | 0 | 5 | 12 | 1 |
| openjdk8-jre | 8.232.09-r0 | 0 | 0 | 5 | 12 | 1 |
| openjdk8-jre-base | 8.232.09-r0 | 0 | 0 | 5 | 12 | 1 |
| openjdk8-jre-lib | 8.232.09-r0 | 0 | 0 | 5 | 12 | 1 |
| openjdk8 | 8.222.10-r0 | 0 | 0 | 5 | 3 | 1 |
| openjdk8-jre | 8.222.10-r0 | 0 | 0 | 5 | 3 | 1 |
| openjdk8-jre-base | 8.222.10-r0 | 0 | 0 | 5 | 3 | 1 |
| openjdk8-jre-lib | 8.222.10-r0 | 0 | 0 | 5 | 3 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.23, 10.1.56, 9.0.119 | 0 | 0 | 2 | 1 | 1 |
| bsdutils | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| com.fasterxml.jackson.core:jackson-databind | 2.18.10, 2.21.6, 2.22.2 | 0 | 0 | 2 | 0 | 1 |
| fdisk | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libblkid1 | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libfdisk1 | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libmount1 | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libsmartcols1 | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libssl1.1 | 1.1.1n-0+deb10u6 | 0 | 0 | 2 | 0 | 1 |
| libuuid1 | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| libxml2 | 2.9.4+dfsg1-7+deb10u6 | 0 | 0 | 2 | 0 | 1 |
| libxpm4 | 1:3.5.12-1+deb10u2 | 0 | 0 | 2 | 0 | 1 |
| mount | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| openssl | 1.1.1n-0+deb10u6 | 0 | 0 | 2 | 0 | 1 |
| org.springframework:spring-webmvc | 7.0.7, 6.2.18 | 0 | 0 | 2 | 0 | 1 |
| org.yaml:snakeyaml | 1.32 | 0 | 0 | 2 | 0 | 1 |
| util-linux | 2.33.1-0.1+deb10u1 | 0 | 0 | 2 | 0 | 1 |
| openjdk8 | 8.201.08-r0 | 0 | 0 | 1 | 2 | 1 |
| openjdk8-jre | 8.201.08-r0 | 0 | 0 | 1 | 2 | 1 |
| openjdk8-jre-base | 8.201.08-r0 | 0 | 0 | 1 | 2 | 1 |
| openjdk8-jre-lib | 8.201.08-r0 | 0 | 0 | 1 | 2 | 1 |
| curl | 7.64.0-4+deb10u7 | 0 | 0 | 1 | 1 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| curl | 7.64.0-4+deb10u8 | 0 | 0 | 1 | 1 | 1 |
| libcurl4 | 7.64.0-4+deb10u7 | 0 | 0 | 1 | 1 | 1 |
| libcurl4 | 7.64.0-4+deb10u8 | 0 | 0 | 1 | 1 | 1 |
| org.springframework:spring-webmvc | 7.0.6, 6.2.17 | 0 | 0 | 1 | 1 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.18.9, 2.21.5, 2.22.1 | 0 | 0 | 1 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 2.21.5, 2.18.9, 2.22.1 | 0 | 0 | 1 | 0 | 1 |
| com.fasterxml.jackson.core: jackson-databind | 3.1.4, 2.18.9, 2.21.5, 2.22.1 | 0 | 0 | 1 | 0 | 1 |
| curl | 7.64.0-4+deb10u5 | 0 | 0 | 1 | 0 | 1 |
| gpgv | 2.2.12-1+deb10u2 | 0 | 0 | 1 | 0 | 1 |
| krb5-libs | 1.15.4-r0 | 0 | 0 | 1 | 0 | 1 |
| libcom_err | 1.44.2-r1 | 0 | 0 | 1 | 0 | 1 |
| libcom_err | 1.44.2-r2 | 0 | 0 | 1 | 0 | 1 |
| libcurl4 | 7.64.0-4+deb10u5 | 0 | 0 | 1 | 0 | 1 |
| libgnutls30 | 3.6.7-4+deb10u11 | 0 | 0 | 1 | 0 | 1 |
| libgssapi-krb5-2 | 1.17-3+deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libgssapi-krb5-2 | 1.17-3+deb10u6 | 0 | 0 | 1 | 0 | 1 |
| libicu63 | 63.1-6+deb10u2 | 0 | 0 | 1 | 0 | 1 |
| libjpeg-turbo | 1.5.3-r5 | 0 | 0 | 1 | 0 | 1 |
| libk5crypto3 | 1.17-3+deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libk5crypto3 | 1.17-3+deb10u6 | 0 | 0 | 1 | 0 | 1 |
| libkrb5-3 | 1.17-3+deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libkrb5-3 | 1.17-3+deb10u6 | 0 | 0 | 1 | 0 | 1 |
| libkrb5support0 | 1.17-3+deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libkrb5support0 | 1.17-3+deb10u6 | 0 | 0 | 1 | 0 | 1 |
| libncursesw6 | 6.1+20181013-2+deb10u4 | 0 | 0 | 1 | 0 | 1 |
| libnghttp2-14 | 1.36.0-2+deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libsystemd0 | 241-7~deb10u10 | 0 | 0 | 1 | 0 | 1 |
| libsystemd0 | 241-7~deb10u8 | 0 | 0 | 1 | 0 | 1 |
| libtasn1 | 4.14-r0 | 0 | 0 | 1 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u3 | 0 | 0 | 1 | 0 | 1 |
| libtiff5 | 4.1.0+git191117-2~deb10u6 | 0 | 0 | 1 | 0 | 1 |
| libtinfo6 | 6.1+20181013-2+deb10u4 | 0 | 0 | 1 | 0 | 1 |
| libudev1 | 241-7~deb10u10 | 0 | 0 | 1 | 0 | 1 |
| libudev1 | 241-7~deb10u8 | 0 | 0 | 1 | 0 | 1 |
| libxml2 | 2.9.4+dfsg1-7+deb10u4 | 0 | 0 | 1 | 0 | 1 |
| ncurses-base | 6.1+20181013-2+deb10u4 | 0 | 0 | 1 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| ncurses-bin | 6.1+20181013-2+deb10u4 | 0 | 0 | 1 | 0 | 1 |
| org.apache.logging.log4j:log4j-api | 2.25.5, 2.26.1 | 0 | 0 | 1 | 0 | 1 |
| org.apache.logging.log4j:log4j-core | 2.12.3, 2.17.0, 2.3.1 | 0 | 0 | 1 | 0 | 1 |
| org.apache.logging.log4j:log4j-core | 2.25.3 | 0 | 0 | 1 | 0 | 1 |
| org.apache.logging.log4j:log4j-core | 2.3.2, 2.12.4, 2.17.1 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 10.1.14, 9.0.81, 8.5.94, 11.0.0-M12 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.12, 10.1.47, 9.0.110 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 8.5.93, 9.0.80, 10.1.13, 11.0.0-M11 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.105, 10.1.41, 11.0.7 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.107 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.107, 10.1.43, 11.0.9 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.52, 11.0.20 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.53, 11.0.20 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.54, 11.0.21 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 9.0.117, 10.1.54, 11.0.21 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-beans | 5.2.22.RELEASE, 5.3.20 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-context | 5.3.19, 5.2.21.RELEASE | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-context | 6.1.14 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-core | 5.3.14, 5.2.19 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-expression | 5.3.17, 5.2.20.RELEASE | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-expression | 5.3.39 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-expression | 6.0.7, 5.3.26, 5.2.23.RELEASE | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-expression | 6.0.8, 5.3.27, 5.2.24.RELEASE | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-web | 5.3.38, 6.0.23, 6.1.12 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-web | 6.1.14 | 0 | 0 | 1 | 0 | 1 |

| Package | Fixed Version | Critical | High | Medium | Low | Images |
|---|---|---|---|---|---|---|
| org.springframework:spring-webmvc | 5.3.42 | 0 | 0 | 1 | 0 | 1 |
| org.springframework:spring-webmvc | 6.2.10 | 0 | 0 | 1 | 0 | 1 |
| sqlite-libs | 3.25.3-r2 | 0 | 0 | 1 | 0 | 1 |
| zlib | 1.4-r0 | 0 | 0 | 1 | 0 | 1 |
| org.apache.tomcat.embed:tomcat-embed-core | 11.0.9, 10.1.43, 9.0.107 | 0 | 0 | 0 | 1 | 1 |
| org.springframework:spring-context | 6.2.7, 6.1.20 | 0 | 0 | 0 | 1 | 1 |
| org.springframework:spring-web | 6.1.4, 6.0.17, 5.3.32 | 0 | 0 | 0 | 1 | 1 |
| tar | 1.30+dfsg-6+deb10u1 | 0 | 0 | 0 | 1 | 1 |
| debian-archive-keyring | 2019.1+deb10u2 | 0 | 0 | 0 | 0 | 1 |
| libbz2-1.0 | 1.0.6-9.2~deb10u2 | 0 | 0 | 0 | 0 | 1 |
| libexpat1 | 2.2.6-2+deb10u4 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2021a-0+deb10u10 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2021a-0+deb10u11 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2021a-0+deb10u12 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2021a-0+deb10u7 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2021a-0+deb10u8 | 0 | 0 | 0 | 0 | 1 |
| tzdata | 2024a-0+deb10u1 | 0 | 0 | 0 | 0 | 1 |

## Vulnerabilities Without Fixes

86 vulnerabilities have no fix available. Assess mitigation options.

| Status | Count |
|---|---|
| Affected | 45 |
| Will Not Fix | 30 |
| Fix Deferred | 11 |

# Vulnerability Inventory

461 unique vulnerabilities.

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2021-44228 | Critical | 10.0 | org.apache.logging.log4j:log4j-core | 2.15.0, 2.3.1, 2.12.2 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2016-1000027 | Critical | 9.8 | org.springframework:spring-web | 6.0.0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-12900 | Critical | 9.8 | libbz2 | 1.0.6-r7 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-14697 | Critical | 9.8 | musl, musl-utils | 1.1.19-r11 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-8457 | Critical | 9.8 | libdb5.3, sqlite-libs | 3.25.3-r1 | 2 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest · nginx:1.21.0 | | | | | |
| CVE-2021-33574 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-3711 | Critical | 9.8 | libssl1.1, openssl | 1.1.1d-0+deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-1471 | Critical | 9.8 | org.yaml:snakeyaml | 2.0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-1664 | Critical | 9.8 | dpkg | 1.19.8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22822 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22823 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22824 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22965 | Critical | 9.8 | org.springframework:spring-beans, org.springframework:spring-webmvc | 5.2.20.RELEASE, 5.3.18 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-23218 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-23219 | Critical | 9.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-23852 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-25235 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u3 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-25236 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-25315 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-27404 | Critical | 9.8 | libfreetype6 | 2.9.1-3+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-29155 | Critical | 9.8 | libldap-2.4-2, libldap-common | 2.4.47+dfsg-3+deb10u7 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-32221 | Critical | 9.8 | curl, libcurl4 | 7.64.0-4+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-37434 | Critical | 9.8 | zlib1g | 1:1.2.11.dfsg-1+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-45853 | Critical | 9.8 | zlib1g | — | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2025-24813 | Critical | 9.8 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.3, 10.1.35, 9.0.99 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-47884 | Critical | 9.8 | org.springframework:spring-webmvc | 7.0.9 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-35942 | Critical | 9.1 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-46848 | Critical | 9.1 | libtasn1-6 | 4.13-3+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2025-66614 | Critical | 9.1 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.15, 10.1.50, 9.0.113 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2018-3183 | Critical | 9.0 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-45046 | Critical | 9.0 | org.apache.logging.log4j:log4j-core | 2.16.0, 2.12.2, 2.3.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2018-14550 | High | 8.8 | libpng | 1.6.37-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-30560 | High | 8.8 | libxslt1.1 | 1.1.32-2.2~deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2021-39537 | High | 8.8 | libncursesw6, libtinfo6, ncurses-base, ncurses-bin | 6.1+20181013-2+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-45960 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-1271 | High | 8.8 | gzip, liblzma5 | 1.9-3+deb10u1, 5.2.4-1+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22825 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22826 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22827 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-24407 | High | 8.8 | libsasl2-2, libsasl2-modules-db | 2.1.27+dfsg-1+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3970 | High | 8.8 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-42898 | High | 8.8 | libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0 | 1.17-3+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-4883 | High | 8.8 | libxpm4 | 1:3.5.12-1+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-25434 | High | 8.8 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-27533 | High | 8.8 | curl, libcurl4 | 7.64.0-4+deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-27534 | High | 8.8 | curl, libcurl4 | 7.64.0-4+deb10u9 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-4863 | High | 8.8 | libwebp6 | 0.6.1-2+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-2961 | High | 8.8 | libc-bin, libc6 | 2.28-10+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2025-49124 | High | 8.4 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.8, 10.1.42, 9.0.106 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-3149 | High | 8.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2018-3169 | High | 8.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-14583 | High | 8.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-2803 | High | 8.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-2805 | High | 8.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-65182 | High | 8.2 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.25, 10.1.58, 9.0.121 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2017-6363 | High | 8.1 | libgd3 | — | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-12886 | High | 8.1 | gcc-8-base, libgcc1, libstdc++6 | — | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-20346 | High | 8.1 | sqlite-libs | 3.25.3-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-13115 | High | 8.1 | libssh2-1 | 1.8.0-2.1+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-17498 | High | 8.1 | libssh2-1 | 1.8.0-2.1+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-17543 | High | 8.1 | liblz4-1 | — | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-2698 | High | 8.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.212.04-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-2604 | High | 8.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-6096 | High | 8.1 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-22576 | High | 8.1 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-40674 | High | 8.1 | libexpat1 | 2.2.6-2+deb10u5 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2023-31484 | High | 8.1 | perl-base | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-22259 | High | 8.1 | org.springframework:spring-web | 6.1.5, 6.0.18, 5.3.33 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-22262 | High | 8.1 | org.springframework:spring-web | 5.3.34, 6.0.19, 6.1.6 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-50379 | High | 8.1 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.2, 10.1.34, 9.0.98 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-56337 | High | 8.1 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.2, 10.1.34, 9.0.98 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-54512 | High | 8.1 | com.fasterxml.jackson.core:jackson-databind | 2.18.8, 3.1.4, 2.21.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-54513 | High | 8.1 | com.fasterxml.jackson.core:jackson-databind | 2.18.8, 2.21.4, 3.1.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2201 | High | 7.8 | libjpeg-turbo | 1.5.3-r6 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-3843 | High | 7.8 | libsystemd0, libudev1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2019-3844 | High | 7.8 | libsystemd0, libudev1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2020-16156 | High | 7.8 | perl-base | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-3999 | High | 7.8 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-46143 | High | 7.8 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-1304 | High | 7.8 | e2fsprogs, libcom-err2, libext2fs2, libss2 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-40304 | High | 7.8 | libxml2 | 2.9.4+dfsg1-7+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-26604 | High | 7.8 | libsystemd0, libudev1 | 241-7~deb10u9 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-29491 | High | 7.8 | libncursesw6, libtinfo6, ncurses-base, ncurses-bin | 6.1+20181013-2+deb10u5 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-43787 | High | 7.8 | libx11-6, libx11-data | 2:1.6.7-1+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-33599 | High | 7.6 | libc-bin, libc6 | 2.28-10+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2017-16932 | High | 7.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-14553 | High | 7.5 | libgd3 | 2.2.5-5.2+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-25032 | High | 7.5 | zlib1g | 1:1.2.11.dfsg-1+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-12290 | High | 7.5 | libidn2-0 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-14855 | High | 7.5 | gpgv | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-15847 | High | 7.5 | gcc-8-base, libgcc1, libstdc++6 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-19244 | High | 7.5 | sqlite-libs | 3.25.3-r3 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2602 | High | 7.5 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.212.04-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-5815 | High | 7.5 | libxslt1.1 | 1.1.32-2.2~deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-11080 | High | 7.5 | libnghttp2-14 | 1.36.0-2+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-11655 | High | 7.5 | sqlite-libs | 3.25.0-r4 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-22218 | High | 7.5 | libssh2-1 | 1.8.0-2.1+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-36518 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.2.1, 2.12.6.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-22946 | High | 7.5 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-3326 | High | 7.5 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-33560 | High | 7.5 | libgcrypt20 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-36222 | High | 7.5 | libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0 | 1.17-3+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-43618 | High | 7.5 | libgmp10 | 2:6.1.2+dfsg-4+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-46877 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.12.6, 2.13.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2022-0778 | High | 7.5 | libssl1.1, openssl | 1.1.1d-0+deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-2309 | High | 7.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-23308 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-23990 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-2509 | High | 7.5 | libgnutls30 | 3.6.7-4+deb10u9 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-25314 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-25857 | High | 7.5 | org.yaml:snakeyaml | 1.31 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2022-27405 | High | 7.5 | libfreetype6 | 2.9.1-3+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-27406 | High | 7.5 | libfreetype6 | 2.9.1-3+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-27781 | High | 7.5 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-27782 | High | 7.5 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-40303 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u5 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-42003 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.12.7.1, 2.13.4.2 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2022-42004 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.12.7.1, 2.13.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-42252 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 8.5.83, 9.0.68, 10.0.27, 10.1.1 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-43680 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-4450 | High | 7.5 | libssl1.1, openssl | 1.1.1n-0+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-44617 | High | 7.5 | libxpm4 | 1:3.5.12-1+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-45143 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 8.5.84, 9.0.69, 10.1.2 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-46285 | High | 7.5 | libxpm4 | 1:3.5.12-1+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0215 | High | 7.5 | libssl1.1, openssl | 1.1.1n-0+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0464 | High | 7.5 | libssl1.1, openssl | 1.1.1n-0+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-1999 | High | 7.5 | libwebp6 | 0.6.1-2+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-20860 | High | 7.5 | org.springframework:spring-webmvc | 6.0.7, 5.3.26 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-20883 | High | 7.5 | org.springframework.boot:spring-boot-autoconfigure | 3.0.7, 2.7.12, 2.6.15, 2.5.15 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-24998 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 10.1.5, 11.0.0-M5, 8.5.88, 9.0.71 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-2953 | High | 7.5 | libldap-2.4-2, libldap-common | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-3138 | High | 7.5 | libx11-6, libx11-data | 2:1.6.7-1+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-44487 | High | 7.5 | libnghttp2-14, org.apache.tomcat.embed:tomcat-embed-core | 1.36.0-2+deb10u2, 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94 | 2 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` · `nginx:1.21.0` | | | | | |
| CVE-2023-46589 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M11, 10.1.16, 9.0.83, 8.5.96 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2023-50387 | High | 7.5 | libsystemd0, libudev1 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-50868 | High | 7.5 | libsystemd0, libudev1 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-52355 | High | 7.5 | libtiff5 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-52356 | High | 7.5 | libtiff5 | 4.1.0+git191117-2~deb10u9 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-52425 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u7 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-0553 | High | 7.5 | libgnutls30 | 3.6.7-4+deb10u12 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-23672 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-websocket | 11.0.0-M17, 10.1.19, 9.0.86, 8.5.99 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-2398 | High | 7.5 | curl, libcurl4 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-24549 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 8.5.99, 9.0.86, 10.1.19, 11.0.0-M17 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-25062 | High | 7.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-34750 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M21, 10.1.25, 9.0.90 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-38286 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M21, 10.1.25, 9.0.90 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-38816 | High | 7.5 | org.springframework:spring-webmvc | 6.1.13 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-38819 | High | 7.5 | org.springframework:spring-webmvc | 6.1.14 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2025-41249 | High | 7.5 | org.springframework:spring-core | 6.2.11 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-48989 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.10, 10.1.44, 9.0.108 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-52999 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.15.0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-55752 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.11, 10.1.45, 9.0.109 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-34479 | High | 7.5 | org.apache.logging.log4j:log4j-core | 2.25.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-34480 | High | 7.5 | org.apache.logging.log4j:log4j-core | 2.25.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41284 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41848 | High | 7.5 | org.springframework:spring-core | 7.0.8, 6.2.19 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41851 | High | 7.5 | org.springframework:spring-expression | 7.0.8, 6.2.19 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-50193 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.14.0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-68494 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.18.8, 2.21.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-89425 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.21.7, 2.22.3, 2.18.11 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-91776 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.18.11, 2.21.7, 2.22.3 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-91777 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.21.7, 2.18.11, 2.22.3 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14593 | High | 7.4 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2021-3712 | High | 7.4 | libssl1.1, openssl | 1.1.1d-0+deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0286 | High | 7.4 | libssl1.1, openssl | 1.1.1n-0+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0361 | High | 7.4 | libgnutls30 | 3.6.7-4+deb10u10 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-1292 | High | 7.3 | libssl1.1, openssl | 1.1.1n-0+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-2068 | High | 7.3 | libssl1.1, openssl | 1.1.1n-0+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2025-22235 | High | 7.3 | org.springframework.boot:spring-boot | 3.3.11, 3.4.5 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41293 | High | 7.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-55957 | High | 7.3 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.5, 10.1.37, 9.0.101 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2022-0891 | High | 7.1 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-29458 | High | 7.1 | libncursesw6, libtinfo6, ncurses-base, ncurses-bin | 6.1+20181013-2+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-1751 | High | 7.0 | libc-bin, libc6 | — | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-1752 | High | 7.0 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2026-40973 | High | 7.0 | org.springframework.boot:spring-boot | 4.0.6, 3.5.14 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2949 | Medium | 6.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2989 | Medium | 6.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-2601 | Medium | 6.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-5094 | Medium | 6.7 | libcom_err | 1.44.2-r1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-5188 | Medium | 6.7 | libcom_err | 1.44.2-r2 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-44832 | Medium | 6.6 | org.apache.logging.log4j:log4j-core | 2.3.2, 2.12.4, 2.17.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2016-2781 | Medium | 6.5 | coreutils | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2018-11212 | Medium | 6.5 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.201.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-13785 | Medium | 6.5 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-14048 | Medium | 6.5 | libpng | 1.6.37-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-14498 | Medium | 6.5 | libjpeg-turbo | 1.5.3-r5 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-16168 | Medium | 6.5 | sqlite-libs | 3.25.3-r2 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-19143 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2020-19189 | Medium | 6.5 | libncursesw6, libtinfo6, ncurses-base, ncurses-bin | 6.1+20181013-2+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-37750 | Medium | 6.5 | libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0 | 1.17-3+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-38115 | Medium | 6.5 | libgd3 | 2.2.5-5.2+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-40812 | Medium | 6.5 | libgd3 | 2.2.5-5.2+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-4209 | Medium | 6.5 | libgnutls30 | 3.6.7-4+deb10u9 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-0865 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-1210 | Medium | 6.5 | libtiff5 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-2056 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-2057 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2022-2058 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22950 | Medium | 6.5 | org.springframework:spring-expression | 5.3.17, 5.2.20.RELEASE | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-25313 | Medium | 6.5 | libexpat1 | 2.2.6-2+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-27776 | Medium | 6.5 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-29824 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-32206 | Medium | 6.5 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-34526 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-34903 | Medium | 6.5 | gpgv | 2.2.12-1+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3597 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3598 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3599 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3626 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3627 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-38749 | Medium | 6.5 | org.yaml:snakeyaml | 1.31 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-38751 | Medium | 6.5 | org.yaml:snakeyaml | 1.31 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-38752 | Medium | 6.5 | org.yaml:snakeyaml | 1.32 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-40090 | Medium | 6.5 | libtiff5 | – | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-41854 | Medium | 6.5 | org.yaml:snakeyaml | 1.32 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2023-20861 | Medium | 6.5 | org.springframework:spring-expression | 6.0.7, 5.3.26, 5.2.23.RELEASE | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2023-20863 | Medium | 6.5 | org.springframework:spring-expression | 6.0.8, 5.3.27, 5.2.24.RELEASE | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2023-23916 | Medium | 6.5 | curl, libcurl4 | 7.64.0-4+deb10u5 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-2650 | Medium | 6.5 | libssl1.1, openssl | 1.1.1n-0+deb10u5 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-28484 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u6 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-29469 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u6 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-3316 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-36054 | Medium | 6.5 | libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0 | 1.17-3+deb10u6 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-3618 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-39615 | Medium | 6.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-40745 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-41175 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-45322 | Medium | 6.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-46218 | Medium | 6.5 | curl, libcurl4 | 7.64.0-4+deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-50495 | Medium | 6.5 | libncursesw6, libtinfo6, ncurses-base, ncurses-bin | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2023-6277 | Medium | 6.5 | libtiff5 | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2025-46701 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.105, 10.1.41, 11.0.7 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-55668 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.8, 10.1.42, 9.0.106 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-22737 | Medium | 6.5 | org.springframework:spring-webmvc | 7.0.6, 6.2.17 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-34487 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.117, 10.1.54, 11.0.21 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-42498 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-43512 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-53404 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.23, 10.1.56, 9.0.119 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-55956 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.23, 10.1.56, 9.0.119 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-59889 | Medium | 6.5 | com.fasterxml.jackson.core:jackson-databind | 2.21.5, 2.18.9, 2.22.1 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-68525 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.25, 10.1.58, 9.0.121 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-13627 | Medium | 6.3 | libgcrypt20 | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2016-3709 | Medium | 6.1 | libxml2 | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-1355 | Medium | 6.1 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-41080 | Medium | 6.1 | org.apache.tomcat.embed:tomcat-embed-core | 8.5.93, 9.0.80, 10.1.13, 11.0.0-M11 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41844 | Medium | 6.1 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41845 | Medium | 6.1 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41846 | Medium | 6.1 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2016-10228 | Medium | 5.9 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-19242 | Medium | 5.9 | sqlite-libs | 3.25.3-r3 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-25013 | Medium | 5.9 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2019-2684 | Medium | 5.9 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.212.04-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2958 | Medium | 5.9 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-22947 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-4160 | Medium | 5.9 | libssl1.1, openssl | 1.1.1d-0+deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-45105 | Medium | 5.9 | org.apache.logging.log4j:log4j-core | 2.12.3, 2.17.0, 2.3.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2022-32208 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-4304 | Medium | 5.9 | libssl1.1, openssl | 1.1.1n-0+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-43552 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-27535 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u6 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-27536 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u6 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-28321 | Medium | 5.9 | curl, libcurl4 | 7.64.0-4+deb10u7 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-4806 | Medium | 5.9 | libc-bin, libc6 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-4813 | Medium | 5.9 | libc-bin, libc6 | – | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-5981 | Medium | 5.9 | libgnutls30 | 3.6.7-4+deb10u11 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2023-7008 | Medium | 5.9 | libsystemd0, libudev1 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2024-38808 | Medium | 5.9 | org.springframework:spring-expression | 5.3.39 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2025-41242 | Medium | 5.9 | org.springframework:spring-webmvc | 6.2.10 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-22741 | Medium | 5.9 | org.springframework:spring-webmvc | 7.0.7, 6.2.18 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-34477 | Medium | 5.9 | org.apache.logging.log4j:log4j-core | 2.25.4 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41841 | Medium | 5.9 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41842 | Medium | 5.9 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41843 | Medium | 5.9 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41849 | Medium | 5.9 | org.springframework:spring-expression | – | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-41850 | Medium | 5.9 | org.springframework:spring-expression | 7.0.8, 6.2.19 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-49844 | Medium | 5.9 | org.apache.logging.log4j:log4j-api | 2.25.5, 2.26.1 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2022-27774 | Medium | 5.7 | curl, libcurl4 | 7.64.0-4+deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-3180 | Medium | 5.6 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2024-4741 | Medium | 5.6 | libssl1.1, openssl | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2026-83557 | Medium | 5.6 | com.fasterxml.jackson.core:jackson-databind | 2.18.10, 2.21.6, 2.22.2 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2016-9318 | Medium | 5.5 | libxml2 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-1000654 | Medium | 5.5 | libtasn1 | 4.14-r0 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2018-16435 | Medium | 5.5 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-10029 | Medium | 5.5 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-21913 | Medium | 5.5 | libicu63 | 63.1-6+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-27618 | Medium | 5.5 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2020-35538 | Medium | 5.5 | libjpeg62-turbo | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-33910 | Medium | 5.5 | libsystemd0, libudev1 | 241-7~deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-37600 | Medium | 5.5 | bsdutils, fdisk, libblkid1, libfdisk1, libmount1, libsmartcols1, libuuid1, mount, util-linux | 2.33.1-0.1+deb10u1 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-3997 | Medium | 5.5 | libsystemd0, libudev1 | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2021-46822 | Medium | 5.5 | libjpeg62-turbo | – | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0561 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0562 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0907 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0908 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0909 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-0924 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2022-1354 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2022-22844 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-2867 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-2868 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-2869 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3570 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-3821 | Medium | 5.5 | libsystemd0, libudev1 | 241-7~deb10u10 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-38750 | Medium | 5.5 | org.yaml:snakeyaml | 1.31 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-4415 | Medium | 5.5 | libsystemd0, libudev1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-4645 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-48281 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0795 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0796 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0797 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0798 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0799 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2023-0800 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0801 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0802 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0803 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0804 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-25433 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-25435 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-26965 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-26966 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-27538 | Medium | 5.5 | curl, libcurl4 | 7.64.0-4+deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-2908 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-30086 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-30774 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-3576 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u9 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-43785 | Medium | 5.5 | libx11-6, libx11-data | 2:1.6.7-1+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2023-43786 | Medium | 5.5 | libx11-6, libx11-data | 2:1.6.7-1+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-43788 | Medium | 5.5 | libxpm4 | 1:3.5.12-1+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-43789 | Medium | 5.5 | libxpm4 | 1:3.5.12-1+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-4641 | Medium | 5.5 | login, passwd | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-0727 | Medium | 5.5 | libssl1.1, openssl | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-22365 | Medium | 5.5 | libpam-modules, libpam-modules-bin, libpam-runtime, libpam0g | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2026-34483 | Medium | 5.4 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.54, 11.0.21 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-43515 | Medium | 5.4 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-20217 | Medium | 5.3 | krb5-libs | 1.15.4-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-3214 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-7169 | Medium | 5.3 | login, passwd | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2019-2762 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2769 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-7317 | Medium | 5.3 | libpng, openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 1.6.37-r0, 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14155 | Medium | 5.3 | libpcre3 | — | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2020-14621 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2020-14803 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2781 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2830 | Medium | 5.3 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-2097 | Medium | 5.3 | libssl1.1, openssl | 1.1.1n-0+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-22968 | Medium | 5.3 | org.springframework:spring-context | 5.3.19, 5.2.21.RELEASE | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2022-22970 | Medium | 5.3 | org.springframework:spring-beans | 5.2.22.RELEASE, 5.3.20 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-0465 | Medium | 5.3 | libssl1.1, openssl | 1.1.1n-0+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-0466 | Medium | 5.3 | libssl1.1, openssl | 1.1.1n-0+deb10u5 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-3446 | Medium | 5.3 | libssl1.1, openssl | 1.1.1n-0+deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-3817 | Medium | 5.3 | libssl1.1, openssl | 1.1.1n-0+deb10u6 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-42795 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 10.1.14, 9.0.81, 8.5.94, 11.0.0-M12 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-45648 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2023-5678 | Medium | 5.3 | libssl1.1, openssl | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-28182 | Medium | 5.3 | libnghttp2-14 | 1.36.0-2+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-33600 | Medium | 5.3 | libc-bin, libc6 | 2.28-10+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-38809 | Medium | 5.3 | org.springframework:spring-web | 5.3.38, 6.0.23, 6.1.12 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2024-38820 | Medium | 5.3 | org.springframework:spring-context, org.springframework:spring-web | 6.1.14 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-38828 | Medium | 5.3 | org.springframework:spring-webmvc | 5.3.42 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-48988 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.8, 10.1.42, 9.0.106 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-52434 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.107 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-53506 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.107, 10.1.43, 11.0.9 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-61795 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.12, 10.1.47, 9.0.110 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-19032 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.18.10, 2.21.6, 2.22.2 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-22745 | Medium | 5.3 | org.springframework:spring-webmvc | 7.0.7, 6.2.18 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41852 | Medium | 5.3 | org.springframework:spring-expression | 7.0.8, 6.2.19 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-41853 | Medium | 5.3 | org.springframework:spring-webmvc | 7.0.8, 6.2.19 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-43513 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-54514 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.18.8, 2.21.4, 3.1.4 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-54515 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 3.1.4, 2.18.9, 2.21.5, 2.22.1 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-77310 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.18.9, 2.21.5, 2.22.1 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2745 | Medium | 5.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2816 | Medium | 4.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2019-2975 | Medium | 4.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14556 | Medium | 4.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2593 | Medium | 4.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2800 | Medium | 4.8 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-68161 | Medium | 4.8 | org.apache.logging.log4j:log4j-core | 2.25.3 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-65905 | Medium | 4.8 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.25, 10.1.58, 9.0.121 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2999 | Medium | 4.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-28085 | Medium | 4.4 | bsdutils, fdisk, libblkid1, libfdisk1, libmount1, libsmartcols1, libuuid1, mount, util-linux | 2.33.1-0.1+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-22060 | Medium | 4.3 | org.springframework:spring-core | 5.3.14, 5.2.19 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-24880 | Medium | 4.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.52, 11.0.20 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-25854 | Medium | 4.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.116, 10.1.53, 11.0.20 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14792 | Medium | 4.2 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-33601 | Medium | 4.0 | libc-bin, libc6 | 2.28-10+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-33602 | Medium | 4.0 | libc-bin, libc6 | 2.28-10+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2026-4738 | Medium | — | zlib | 1.4-r0 | 1 |
| Affected Images alpine:3.22 | | | | | |
| CVE-2019-2426 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.201.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2019-2842 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2894 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2962 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2964 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2973 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2978 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2981 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2983 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2987 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2988 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2992 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14577 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14578 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14579 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14581 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2020-14779 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14781 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14782 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-14797 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2583 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2590 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2654 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2659 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.242.08-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2754 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2755 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2756 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2757 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2020-2773 | Low | 3.7 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.252.09-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2021-22924 | Low | 3.7 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2022-35252 | Low | 3.7 | curl, libcurl4 | 7.64.0-4+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| CVE-2023-28322 | Low | 3.7 | curl, libcurl4 | 7.64.0-4+deb10u8 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-38546 | Low | 3.7 | curl, libcurl4 | 7.64.0-4+deb10u7 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2024-2511 | Low | 3.7 | libssl1.1, openssl | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2025-49125 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.8, 10.1.42, 9.0.106 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-52520 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.9, 10.1.43, 9.0.107 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2026-43514 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.118, 10.1.55, 11.0.22 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2025-55754 | Low | 3.5 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.11, 10.1.45, 9.0.109 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2018-3136 | Low | 3.4 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-2786 | Low | 3.4 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2024-22243 | Low | 3.4 | org.springframework:spring-web | 6.1.4, 6.0.17, 5.3.32 | 1 |
| Affected Images ghcr.io/christophetd/log4shell-vulnerable-app:latest | | | | | |
| CVE-2019-19126 | Low | 3.3 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-36084 | Low | 3.3 | libsepol1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-36085 | Low | 3.3 | libsepol1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-36086 | Low | 3.3 | libsepol1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2021-36087 | Low | 3.3 | libsepol1 | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-29383 | Low | 3.3 | login, passwd | – | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| CVE-2023-39804 | Low | 3.3 | tar | 1.30+dfsg-6+deb10u1 | 1 |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2018-3139 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.191.12-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2422 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.201.08-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2766 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.222.10-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2933 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2019-2945 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.232.09-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-14796 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2020-14798 | Low | 3.1 | openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib | 8.272.10-r0 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-22898 | Low | 3.1 | curl, libcurl4 | 7.64.0-4+deb10u3 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2025-22233 | Low | 3.1 | org.springframework:spring-context | 6.2.7, 6.1.20 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2026-22735 | Low | 2.6 | org.springframework:spring-webmvc | 7.0.6, 6.2.17 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| CVE-2021-27645 | Low | 2.5 | libc-bin, libc6 | 2.28-10+deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| CVE-2026-55276 | Low | 2.3 | org.apache.tomcat.embed:tomcat-embed-core | 11.0.23, 10.1.56, 9.0.119 | 1 |
| Affected Images `ghcr.io/christophetd/log4shell-vulnerable-app:latest` | | | | | |
| DLA-3112-1 | Unrated | — | libbz2-1.0 | 1.0.6-9.2~deb10u2 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| DLA-3134-1 | Unrated | — | tzdata | 2021a-0+deb10u7 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| DLA-3161-1 | Unrated | — | tzdata | 2021a-0+deb10u8 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |
| DLA-3366-1 | Unrated | — | tzdata | 2021a-0+deb10u10 | 1 |
| Affected Images `nginx:1.21.0` | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Fixed Version | Images |
|---|---|---|---|---|---|
| DLA-3412-1 | Unrated | — | tzdata | 2021a-0+deb10u11 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| DLA-3482-1 | Unrated | — | debian-archive-keyring | 2019.1+deb10u2 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| DLA-3684-1 | Unrated | — | tzdata | 2021a-0+deb10u12 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| DLA-3788-1 | Unrated | — | tzdata | 2024a-0+deb10u1 | 1 |
| Affected Images nginx:1.21.0 | | | | | |
| DSA-5085-2 | Unrated | — | libexpat1 | 2.2.6-2+deb10u4 | 1 |
| Affected Images nginx:1.21.0 | | | | | |

# Image Details

## nginx:1.21.0

| | |
|---|---|
| Digest | sha256:47ae43cdfc7064d28800bc42e79a429540c7c80168e8c8952778c0d5af1c09db |
| Platform | linux/amd64 |
| Operating System | debian 10.10 |
| Size | — |
| Created | 2021-06-23T07:16:26Z |
| Scanned | 2026-11-07T14:32:23Z |
| Vulnerabilities by Severity | Critical 27 · High 142 · Medium 193 · Low 23 · Unrated 9 |

### Vulnerability Details

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2019-8457 | Critical | 9.8 | libdb5.3 | 5.3.28+dfsg1-0.5 | — |
| SQLite3 from 3.6.0 to and including 3.27.2 is vulnerable to heap out-of-bound read in the rtreenode() function when handling invalid rtree tables. | | | | | |
| CVE-2021-33574 | Critical | 9.8 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| The mq_notify function in the GNU C Library (aka glibc) versions 2.32 and 2.33 has a use-after-free. It may use the notification thread attributes object (passed through its struct sigevent parameter) after it has been freed by the caller, leading to a denial of service (application crash) or possibly unspecified other impact. | | | | | |
| CVE-2021-33574 | Critical | 9.8 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| The mq_notify function in the GNU C Library (aka glibc) versions 2.32 and 2.33 has a use-after-free. It may use the notification thread attributes object (passed through its struct sigevent parameter) after it has been freed by the caller, leading to a denial of service (application crash) or possibly unspecified other impact. | | | | | |
| CVE-2021-3711 | Critical | 9.8 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u7 |
| In order to decrypt SM2 encrypted data an application is expected to call the API function EVP_PKEY_decrypt(). Typically an application will call this function twice. The first time, on entry, the "out" parameter can be NULL and, on exit, the "outlen" parameter is populated with the buffer size required to hold the decrypted plaintext. The application can then allocate a sufficiently sized buffer and call EVP_PKEY_decrypt() again, but this time passing a non-NULL value for the "out" parameter. A bug in the implementation of the SM2 decryption code means that the calculation of the buffer size ... | | | | | |
| CVE-2021-3711 | Critical | 9.8 | openssl | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u7 |
| In order to decrypt SM2 encrypted data an application is expected to call the API function EVP_PKEY_decrypt(). Typically an application will call this function twice. The first time, on entry, the "out" parameter can be NULL and, on exit, the "outlen" parameter is populated with the buffer size required to hold the decrypted plaintext. The application can then allocate a sufficiently sized buffer and call EVP_PKEY_decrypt() again, but this time passing a non-NULL value for the "out" parameter. A bug in the implementation of the SM2 decryption code means that the calculation of the buffer size ... | | | | | |
| CVE-2022-1664 | Critical | 9.8 | dpkg | 1.19.7 | 1.19.8 |
| Dpkg::Source::Archive in dpkg, the Debian package management system, before version 1.21.8, 1.20.10, 1.19.8, 1.18.26 is prone to a directory traversal vulnerability. When extracting untrusted source packages in v2 and v3 source package formats that include a debian.tar, the in-place extraction can lead to directory traversal situations on specially crafted orig.tar and debian.tar tarballs. | | | | | |
| CVE-2022-22822 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| addBinding in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-22823 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| build_model in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-22824 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| defineAttribute in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-23218 | Critical | 9.8 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| The deprecated compatibility function svcunix_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its path argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution. | | | | | |
| CVE-2022-23218 | Critical | 9.8 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| The deprecated compatibility function svcunix_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its path argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution. | | | | | |
| CVE-2022-23219 | Critical | 9.8 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| The deprecated compatibility function clnt_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its hostname argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution. | | | | | |
| CVE-2022-23219 | Critical | 9.8 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| The deprecated compatibility function clnt_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its hostname argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution. | | | | | |
| CVE-2022-23852 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| Expat (aka libexpat) before 2.4.4 has a signed integer overflow in XML_GetBuffer, for configurations with a nonzero XML_CONTEXT_BYTES. | | | | | |
| CVE-2022-25235 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u3 |
| xmltok_impl.c in Expat (aka libexpat) before 2.4.5 lacks certain validation of encoding, such as checks for whether a UTF-8 character is valid in a certain context. | | | | | |
| CVE-2022-25236 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u3 |
| xmlparse.c in Expat (aka libexpat) before 2.4.5 allows attackers to insert namespace-separator characters into namespace URIs. | | | | | |
| CVE-2022-25315 | Critical | 9.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u3 |
| In Expat (aka libexpat) before 2.4.5, there is an integer overflow in storeRawNames. | | | | | |
| CVE-2022-27404 | Critical | 9.8 | libfreetype6 | 2.9.1-3+deb10u2 | 2.9.1-3+deb10u3 |
| FreeType commit 1e2eb65048f75c64b68708efed6ce904c31f3b2f was discovered to contain a heap buffer overflow via the function sfnt_init_face. | | | | | |
| CVE-2022-29155 | Critical | 9.8 | libldap-2.4-2 | 2.4.47+dfsg-3+deb10u6 | 2.4.47+dfsg-3+deb10u7 |
| In OpenLDAP 2.x before 2.5.12 and 2.6.x before 2.6.2, a SQL injection vulnerability exists in the experimental back-sql backend to slapd, via a SQL statement within an LDAP query. This can occur during an LDAP search operation when the search filter is processed, due to a lack of proper escaping. | | | | | |
| CVE-2022-29155 | Critical | 9.8 | libldap-common | 2.4.47+dfsg-3+deb10u6 | 2.4.47+dfsg-3+deb10u7 |
| In OpenLDAP 2.x before 2.5.12 and 2.6.x before 2.6.2, a SQL injection vulnerability exists in the experimental back-sql backend to slapd, via a SQL statement within an LDAP query. This can occur during an LDAP search operation when the search filter is processed, due to a lack of proper escaping. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-32221 | Critical | 9.8 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| When doing HTTP(S) transfers, libcurl might erroneously use the read callback (`CURLOPT_READFUNCTION`) to ask for data to send, even when the `CURLOPT_POSTFIELDS` option has been set, if the same handle previously was used to issue a `PUT` request which used that callback. This flaw may surprise the application and cause it to misbehave and either send off the wrong data or use memory after free or similar in the subsequent `POST` request. The problem exists in the logic for a reused handle when it is changed from a PUT to a POST. | | | | | |
| CVE-2022-32221 | Critical | 9.8 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| When doing HTTP(S) transfers, libcurl might erroneously use the read callback (`CURLOPT_READFUNCTION`) to ask for data to send, even when the `CURLOPT_POSTFIELDS` option has been set, if the same handle previously was used to issue a `PUT` request which used that callback. This flaw may surprise the application and cause it to misbehave and either send off the wrong data or use memory after free or similar in the subsequent `POST` request. The problem exists in the logic for a reused handle when it is changed from a PUT to a POST. | | | | | |
| CVE-2022-37434 | Critical | 9.8 | zlib1g | 1:1.2.11.dfsg-1 | 1:1.2.11.dfsg-1+deb10u2 |
| zlib through 1.2.12 has a heap-based buffer over-read or buffer overflow in inflate in inflate.c via a large gzip header extra field. NOTE: only applications that call inflateGetHeader are affected. Some common applications bundle the affected zlib source code but may be unable to call inflateGetHeader (e.g., see the nodejs/node reference). | | | | | |
| CVE-2023-45853 | Critical | 9.8 | zlib1g | 1:1.2.11.dfsg-1 | — |
| MiniZip in zlib through 1.3 has an integer overflow and resultant heap-based buffer overflow in zipOpenNewFileInZip4_64 via a long filename, comment, or extra field. NOTE: MiniZip is not a supported part of the zlib product. NOTE: pyminizip through 0.2.6 is also vulnerable because it bundles an affected zlib version, and exposes the applicable MiniZip code through its compress API. | | | | | |
| CVE-2021-35942 | Critical | 9.1 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| The wordexp function in the GNU C Library (aka glibc) through 2.33 may crash or read arbitrary memory in parse_param (in posix/wordexp.c) when called with an untrusted, crafted pattern, potentially resulting in a denial of service or disclosure of information. This occurs because atoi was used but strtoul should have been used to ensure correct calculations. | | | | | |
| CVE-2021-35942 | Critical | 9.1 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| The wordexp function in the GNU C Library (aka glibc) through 2.33 may crash or read arbitrary memory in parse_param (in posix/wordexp.c) when called with an untrusted, crafted pattern, potentially resulting in a denial of service or disclosure of information. This occurs because atoi was used but strtoul should have been used to ensure correct calculations. | | | | | |
| CVE-2021-46848 | Critical | 9.1 | libtasn1-6 | 4.13-3 | 4.13-3+deb10u1 |
| GNU Libtasn1 before 4.19.0 has an ETYPE_OK off-by-one array size check that affects asn1_encode_simple_der. | | | | | |
| CVE-2021-30560 | High | 8.8 | libxslt1.1 | 1.1.32-2.2~deb10u1 | 1.1.32-2.2~deb10u2 |
| Use after free in Blink XSLT in Google Chrome prior to 91.0.4472.164 allowed a remote attacker to potentially exploit heap corruption via a crafted HTML page. | | | | | |
| CVE-2021-39537 | High | 8.8 | libncursesw6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow. | | | | | |
| CVE-2021-39537 | High | 8.8 | libtinfo6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2021-39537 | High | 8.8 | ncurses-base | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow. | | | | | |
| CVE-2021-39537 | High | 8.8 | ncurses-bin | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow. | | | | | |
| CVE-2021-45960 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| In Expat (aka libexpat) before 2.4.3, a left shift by 29 (or more) places in the storeAtts function in xmlparse.c can lead to realloc misbehavior (e.g., allocating too few bytes, or only freeing memory). | | | | | |
| CVE-2022-1271 | High | 8.8 | gzip | 1.9-3 | 1.9-3+deb10u1 |
| An arbitrary file write vulnerability was found in GNU gzip's zgrep utility. When zgrep is applied on the attacker's chosen file name (for example, a crafted file name), this can overwrite an attacker's content to an arbitrary attacker-selected file. This flaw occurs due to insufficient validation when processing filenames with two or more newlines where selected content and the target file names are embedded in crafted multi-line file names. This flaw allows a remote, low privileged attacker to force zgrep to write arbitrary files on the system. | | | | | |
| CVE-2022-1271 | High | 8.8 | liblzma5 | 5.2.4-1 | 5.2.4-1+deb10u1 |
| An arbitrary file write vulnerability was found in GNU gzip's zgrep utility. When zgrep is applied on the attacker's chosen file name (for example, a crafted file name), this can overwrite an attacker's content to an arbitrary attacker-selected file. This flaw occurs due to insufficient validation when processing filenames with two or more newlines where selected content and the target file names are embedded in crafted multi-line file names. This flaw allows a remote, low privileged attacker to force zgrep to write arbitrary files on the system. | | | | | |
| CVE-2022-22825 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| lookup in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-22826 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| nextScaffoldPart in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-22827 | High | 8.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| storeAtts in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow. | | | | | |
| CVE-2022-24407 | High | 8.8 | libsasl2-2 | 2.1.27+dfsg-1+deb10u1 | 2.1.27+dfsg-1+deb10u2 |
| In Cyrus SASL 2.1.17 through 2.1.27 before 2.1.28, plugins/sql.c does not escape the password for a SQL INSERT or UPDATE statement. | | | | | |
| CVE-2022-24407 | High | 8.8 | libsasl2-modules-db | 2.1.27+dfsg-1+deb10u1 | 2.1.27+dfsg-1+deb10u2 |
| In Cyrus SASL 2.1.17 through 2.1.27 before 2.1.28, plugins/sql.c does not escape the password for a SQL INSERT or UPDATE statement. | | | | | |
| CVE-2022-3970 | High | 8.8 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| A vulnerability was found in LibTIFF. It has been classified as critical. This affects the function TIFFReadRGBATileExt of the file libtiff/tif_getimage.c. The manipulation leads to integer overflow. It is possible to initiate the attack remotely. The exploit has been disclosed to the public and may be used. The name of the patch is 227500897dfb07fb7d27f7aa570050e62617e3be. It is recommended to apply a patch to fix this issue. The identifier VDB-213549 was assigned to this vulnerability. | | | | | |
| CVE-2022-42898 | High | 8.8 | libgssapi-krb5-2 | 1.17-3+deb10u1 | 1.17-3+deb10u5 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug." | | | | | |
| CVE-2022-42898 | High | 8.8 | libk5crypto3 | 1.17-3+deb10u1 | 1.17-3+deb10u5 |
| PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug." | | | | | |
| CVE-2022-42898 | High | 8.8 | libkrb5-3 | 1.17-3+deb10u1 | 1.17-3+deb10u5 |
| PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug." | | | | | |
| CVE-2022-42898 | High | 8.8 | libkrb5support0 | 1.17-3+deb10u1 | 1.17-3+deb10u5 |
| PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug." | | | | | |
| CVE-2022-4883 | High | 8.8 | libxpm4 | 1:3.5.12-1 | 1:3.5.12-1+deb10u1 |
| A flaw was found in libXpm. When processing files with .Z or .gz extensions, the library calls external programs to compress and uncompress files, relying on the PATH environment variable to find these programs, which could allow a malicious user to execute other programs by manipulating the PATH environment variable. | | | | | |
| CVE-2023-25434 | High | 8.8 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| libtiff 4.5.0 is vulnerable to Buffer Overflow via extractContigSamplesBytes() at /libtiff/tools/tiffcrop.c:3215. | | | | | |
| CVE-2023-27533 | High | 8.8 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| A vulnerability in input validation exists in curl <8.0 during communication using the TELNET protocol may allow an attacker to pass on maliciously crafted user name and "telnet options" during server negotiation. The lack of proper input scrubbing allows an attacker to send content or perform option negotiation without the application's intent. This vulnerability could be exploited if an application allows user input, thereby enabling attackers to execute arbitrary code on the system. | | | | | |
| CVE-2023-27533 | High | 8.8 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| A vulnerability in input validation exists in curl <8.0 during communication using the TELNET protocol may allow an attacker to pass on maliciously crafted user name and "telnet options" during server negotiation. The lack of proper input scrubbing allows an attacker to send content or perform option negotiation without the application's intent. This vulnerability could be exploited if an application allows user input, thereby enabling attackers to execute arbitrary code on the system. | | | | | |
| CVE-2023-27534 | High | 8.8 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u9 |
| A path traversal vulnerability exists in curl <8.0.0 SFTP implementation causes the tilde (~) character to be wrongly replaced when used as a prefix in the first path element, in addition to its intended use as the first element to indicate a path relative to the user's home directory. Attackers can exploit this flaw to bypass filtering or execute arbitrary code by crafting a path like /~2/foo while accessing a server with a specific user. | | | | | |
| CVE-2023-27534 | High | 8.8 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u9 |
| A path traversal vulnerability exists in curl <8.0.0 SFTP implementation causes the tilde (~) character to be wrongly replaced when used as a prefix in the first path element, in addition to its intended use as the first element to indicate a path relative to the user's home directory. At- | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| tackers can exploit this flaw to bypass filtering or execute arbitrary code by crafting a path like /~2/foo while accessing a server with a specific user. | | | | | |
| CVE-2023-4863 | High | 8.8 | libwebp6 | 0.6.1-2+deb10u1 | 0.6.1-2+deb10u3 |
| Heap buffer overflow in libwebp in Google Chrome prior to 116.0.5845.187 and libwebp 1.3.2 allowed a remote attacker to perform an out of bounds memory write via a crafted HTML page. (Chromium security severity: Critical) | | | | | |
| CVE-2024-2961 | High | 8.8 | libc-bin | 2.28-10 | 2.28-10+deb10u3 |
| The iconv() function in the GNU C Library versions 2.39 and older may overflow the output buffer passed to it by up to 4 bytes when converting strings to the ISO-2022-CN-EXT character set, which may be used to crash an application or overwrite a neighbouring variable. | | | | | |
| CVE-2024-2961 | High | 8.8 | libc6 | 2.28-10 | 2.28-10+deb10u3 |
| The iconv() function in the GNU C Library versions 2.39 and older may overflow the output buffer passed to it by up to 4 bytes when converting strings to the ISO-2022-CN-EXT character set, which may be used to crash an application or overwrite a neighbouring variable. | | | | | |
| CVE-2017-6363 | High | 8.1 | libgd3 | 2.2.5-5.2 | — |
| In the GD Graphics Library (aka LibGD) through 2.2.5, there is a heap-based buffer over-read in tiffWriter in gd_tiff.c. NOTE: the vendor says "In my opinion this issue should not have a CVE, since the GD and GD2 formats are documented to be 'obsolete, and should only be used for development and testing purposes.' | | | | | |
| CVE-2018-12886 | High | 8.1 | gcc-8-base | 8.3.0-6 | — |
| stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against. | | | | | |
| CVE-2018-12886 | High | 8.1 | libgcc1 | 1:8.3.0-6 | — |
| stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against. | | | | | |
| CVE-2018-12886 | High | 8.1 | libstdc++6 | 8.3.0-6 | — |
| stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against. | | | | | |
| CVE-2019-13115 | High | 8.1 | libssh2-1 | 1.8.0-2.1 | 1.8.0-2.1+deb10u1 |
| In libssh2 before 1.9.0, kex_method_diffie_hellman_group_exchange_sha256_key_exchange in kex.c has an integer overflow that could lead to an out-of-bounds read in the way packets are read from the server. A remote attacker who compromises a SSH server may be able to disclose sensitive information or cause a denial of service condition on the client system when a user connects to the server. This is related to an _libssh2_check_length mistake, and is different from the various issues fixed in 1.8.1, such as CVE-2019-3855. | | | | | |
| CVE-2019-17498 | High | 8.1 | libssh2-1 | 1.8.0-2.1 | 1.8.0-2.1+deb10u1 |
| In libssh2 v1.9.0 and earlier versions, the SSH_MSG_DISCONNECT logic in packet.c has an integer overflow in a bounds check, enabling an attacker to specify an arbitrary (out-of-bounds) offset for a subsequent memory read. A crafted SSH server may be able to disclose sensitive information or cause a denial of service condition on the client system when a user connects to the server. | | | | | |
| CVE-2019-17543 | High | 8.1 | liblz4-1 | 1.8.3-1+deb10u1 | — |
| LZ4 before 1.9.2 has a heap-based buffer overflow in LZ4_write32 (related to LZ4_compress_destSize), affecting applications that call LZ4_compress_fast with a large input. (This issue can also lead to data corruption.) NOTE: the vendor states "only a few specific / uncommon usages of the API are at risk." | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-6096 | High | 8.1 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| An exploitable signed comparison vulnerability exists in the ARMv7 memcpy() implementation of GNU glibc 2.30.9000. Calling memcpy() (on ARMv7 targets that utilize the GNU glibc implementation) with a negative value for the 'num' parameter results in a signed comparison vulnerability. If an attacker underflows the 'num' parameter to memcpy(), this vulnerability could lead to undefined behavior such as writing to out-of-bounds memory and potentially remote code execution. Furthermore, this memcpy() implementation allows for program execution to continue in scenarios where a segmentation fault or... | | | | | |
| CVE-2020-6096 | High | 8.1 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| An exploitable signed comparison vulnerability exists in the ARMv7 memcpy() implementation of GNU glibc 2.30.9000. Calling memcpy() (on ARMv7 targets that utilize the GNU glibc implementation) with a negative value for the 'num' parameter results in a signed comparison vulnerability. If an attacker underflows the 'num' parameter to memcpy(), this vulnerability could lead to undefined behavior such as writing to out-of-bounds memory and potentially remote code execution. Furthermore, this memcpy() implementation allows for program execution to continue in scenarios where a segmentation fault or... | | | | | |
| CVE-2022-22576 | High | 8.1 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| An improper authentication vulnerability exists in curl 7.33.0 to and including 7.82.0 which might allow reuse OAUTH2-authenticated connections without properly making sure that the connection was authenticated with the same credentials as set for this transfer. This affects SASL-enabled protocols: SMPTP(S), IMAP(S), POP3(S) and LDAP(S) (openldap only). | | | | | |
| CVE-2022-22576 | High | 8.1 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| An improper authentication vulnerability exists in curl 7.33.0 to and including 7.82.0 which might allow reuse OAUTH2-authenticated connections without properly making sure that the connection was authenticated with the same credentials as set for this transfer. This affects SASL-enabled protocols: SMPTP(S), IMAP(S), POP3(S) and LDAP(S) (openldap only). | | | | | |
| CVE-2022-40674 | High | 8.1 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u5 |
| libexpat before 2.4.9 has a use-after-free in the doContent function in xmlparse.c. | | | | | |
| CVE-2023-31484 | High | 8.1 | perl-base | 5.28.1-6+deb10u1 | — |
| CPAN.pm before 2.35 does not verify TLS certificates when downloading distributions over HTTPS. | | | | | |
| CVE-2019-3843 | High | 7.8 | libsystemd0 | 241-7~deb10u7 | — |
| It was discovered that a systemd service that uses DynamicUser property can create a SUID/SGID binary that would be allowed to run as the transient service UID/GID even after the service is terminated. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the UID/GID will be recycled. | | | | | |
| CVE-2019-3843 | High | 7.8 | libudev1 | 241-7~deb10u7 | — |
| It was discovered that a systemd service that uses DynamicUser property can create a SUID/SGID binary that would be allowed to run as the transient service UID/GID even after the service is terminated. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the UID/GID will be recycled. | | | | | |
| CVE-2019-3844 | High | 7.8 | libsystemd0 | 241-7~deb10u7 | — |
| It was discovered that a systemd service that uses DynamicUser property can get new privileges through the execution of SUID binaries, which would allow to create binaries owned by the service transient group with the setgid bit set. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the GID will be recycled. | | | | | |
| CVE-2019-3844 | High | 7.8 | libudev1 | 241-7~deb10u7 | — |
| It was discovered that a systemd service that uses DynamicUser property can get new privileges through the execution of SUID binaries, which would allow to create binaries owned by the service transient group with the setgid bit set. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the GID will be recycled. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-16156 | High | 7.8 | perl-base | 5.28.1-6+deb10u1 | — |
| CPAN 2.28 allows Signature Verification Bypass. | | | | | |
| CVE-2021-3999 | High | 7.8 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| A flaw was found in glibc. An off-by-one buffer overflow and underflow in getcwd() may lead to memory corruption when the size of the buffer is exactly 1. A local attacker who can control the input buffer and size passed to getcwd() in a setuid program could use this flaw to potentially execute arbitrary code and escalate their privileges on the system. | | | | | |
| CVE-2021-3999 | High | 7.8 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| A flaw was found in glibc. An off-by-one buffer overflow and underflow in getcwd() may lead to memory corruption when the size of the buffer is exactly 1. A local attacker who can control the input buffer and size passed to getcwd() in a setuid program could use this flaw to potentially execute arbitrary code and escalate their privileges on the system. | | | | | |
| CVE-2021-46143 | High | 7.8 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| In doProlog in xmlparse.c in Expat (aka libexpat) before 2.4.3, an integer overflow exists for m_groupSize. | | | | | |
| CVE-2022-1304 | High | 7.8 | e2fsprogs | 1.44.5-1+deb10u3 | — |
| An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem. | | | | | |
| CVE-2022-1304 | High | 7.8 | libcom-err2 | 1.44.5-1+deb10u3 | — |
| An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem. | | | | | |
| CVE-2022-1304 | High | 7.8 | libext2fs2 | 1.44.5-1+deb10u3 | — |
| An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem. | | | | | |
| CVE-2022-1304 | High | 7.8 | libss2 | 1.44.5-1+deb10u3 | — |
| An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem. | | | | | |
| CVE-2022-40304 | High | 7.8 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u5 |
| An issue was discovered in libxml2 before 2.10.3. Certain invalid XML entity definitions can corrupt a hash table key, potentially leading to subsequent logic errors. In one case, a double-free can be provoked. | | | | | |
| CVE-2023-26604 | High | 7.8 | libsystemd0 | 241-7~deb10u7 | 241-7~deb10u9 |
| systemd before 247 does not adequately block local privilege escalation for some Sudo configurations, e.g., plausible sudoers files in which the "systemctl status" command may be executed. Specifically, systemd does not set LESSSECURE to 1, and thus other programs may be launched from the less program. This presents a substantial security risk when running systemctl from Sudo, because less executes as root when the terminal size is too small to show the complete systemctl output. | | | | | |
| CVE-2023-26604 | High | 7.8 | libudev1 | 241-7~deb10u7 | 241-7~deb10u9 |
| systemd before 247 does not adequately block local privilege escalation for some Sudo configurations, e.g., plausible sudoers files in which the "systemctl status" command may be executed. Specifically, systemd does not set LESSSECURE to 1, and thus other programs may be launched from the less program. This presents a substantial security risk when running systemctl from Sudo, because less executes as root when the terminal size is too small to show the complete systemctl output. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-29491 | High | 7.8 | libncursesw6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable. | | | | | |
| CVE-2023-29491 | High | 7.8 | libtinfo6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable. | | | | | |
| CVE-2023-29491 | High | 7.8 | ncurses-base | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable. | | | | | |
| CVE-2023-29491 | High | 7.8 | ncurses-bin | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u5 |
| ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable. | | | | | |
| CVE-2023-43787 | High | 7.8 | libx11-6 | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |
| A vulnerability was found in libX11 due to an integer overflow within the XCreateImage() function. This flaw allows a local user to trigger an integer overflow and execute arbitrary code with elevated privileges. | | | | | |
| CVE-2023-43787 | High | 7.8 | libx11-data | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |
| A vulnerability was found in libX11 due to an integer overflow within the XCreateImage() function. This flaw allows a local user to trigger an integer overflow and execute arbitrary code with elevated privileges. | | | | | |
| CVE-2024-33599 | High | 7.6 | libc-bin | 2.28-10 | 2.28-10+deb10u4 |
| nscd: Stack-based buffer overflow in netgroup cache<br><br>If the Name Service Cache Daemon's (nscd) fixed size cache is exhausted by client requests then a subsequent client request for netgroup data may result in a stack-based buffer overflow. This flaw was introduced in glibc 2.15 when the cache was added to nscd.<br><br>This vulnerability is only present in the nscd binary. | | | | | |
| CVE-2024-33599 | High | 7.6 | libc6 | 2.28-10 | 2.28-10+deb10u4 |
| nscd: Stack-based buffer overflow in netgroup cache<br><br>If the Name Service Cache Daemon's (nscd) fixed size cache is exhausted by client requests then a subsequent client request for netgroup data may result in a stack-based buffer overflow. This flaw was introduced in glibc 2.15 when the cache was added to nscd.<br><br>This vulnerability is only present in the nscd binary. | | | | | |
| CVE-2017-16932 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |
| parser.c in libxml2 before 2.9.5 does not prevent infinite recursion in parameter entities. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-14553 | High | 7.5 | libgd3 | 2.2.5-5.2 | 2.2.5-5.2+deb10u1 |
| gdImageClone in gd.c in libgd 2.1.0-rc2 through 2.2.5 has a NULL pointer dereference allowing attackers to crash an application via a specific function call sequence. Only affects PHP when linked with an external libgd (not bundled). | | | | | |
| CVE-2018-25032 | High | 7.5 | zlib1g | 1:1.2.11.dfsg-1 | 1:1.2.11.dfsg-1+deb10u1 |
| zlib before 1.2.12 allows memory corruption when deflating (i.e., when compressing) if the input has many distant matches. | | | | | |
| CVE-2019-12290 | High | 7.5 | libidn2-0 | 2.0.5-1+deb10u1 | — |
| GNU libidn2 before 2.2.0 fails to perform the roundtrip checks specified in RFC3490 Section 4.2 when converting A-labels to U-labels. This makes it possible in some circumstances for one domain to impersonate another. By creating a malicious domain that matches a target domain except for the inclusion of certain punycoded Unicode characters (that would be discarded when converted first to a Unicode label and then back to an ASCII label), arbitrary domains can be impersonated. | | | | | |
| CVE-2019-14855 | High | 7.5 | gpgv | 2.2.12-1+deb10u1 | — |
| A flaw was found in the way certificate signatures could be forged using collisions found in the SHA-1 algorithm. An attacker could use this weakness to create forged certificate signatures. This issue affects GnuPG versions before 2.2.18. | | | | | |
| CVE-2019-15847 | High | 7.5 | gcc-8-base | 8.3.0-6 | — |
| The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same. | | | | | |
| CVE-2019-15847 | High | 7.5 | libgcc1 | 1:8.3.0-6 | — |
| The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same. | | | | | |
| CVE-2019-15847 | High | 7.5 | libstdc++6 | 8.3.0-6 | — |
| The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same. | | | | | |
| CVE-2019-5815 | High | 7.5 | libxslt1.1 | 1.1.32-2.2~deb10u1 | 1.1.32-2.2~deb10u2 |
| Type confusion in xsltNumberFormatGetMultipleLevel prior to libxslt 1.1.33 could allow attackers to potentially exploit heap corruption via crafted XML data. | | | | | |
| CVE-2020-11080 | High | 7.5 | libnghttp2-14 | 1.36.0-2+deb10u1 | 1.36.0-2+deb10u2 |
| In nghttp2 before version 1.41.0, the overly large HTTP/2 SETTINGS frame payload causes denial of service. The proof of concept attack involves a malicious client constructing a SETTINGS frame with a length of 14,400 bytes (2400 individual settings entries) over and over again. The attack causes the CPU to spike at 100%. nghttp2 v1.41.0 fixes this vulnerability. There is a workaround to this vulnerability. Implement nghttp2_on_frame_recv_callback callback, and if received frame is SETTINGS frame and the number of settings entries are large (e.g., > 32), then drop the connection. | | | | | |
| CVE-2020-22218 | High | 7.5 | libssh2-1 | 1.8.0-2.1 | 1.8.0-2.1+deb10u1 |
| An issue was discovered in function _libssh2_packet_add in libssh2 1.10.0 allows attackers to access out of bounds memory. | | | | | |
| CVE-2021-22946 | High | 7.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| A user can tell curl >= 7.20.0 and <= 7.78.0 to require a successful upgrade to TLS when speaking to an IMAP, POP3 or FTP server (`--ssl-reqd` on the command line or`CURLOPT_USE_SSL` set to `CURLUSESSL_CONTROL` or `CURLUSESSL_ALL` withlibcurl). This requirement could be bypassed if the server would return a properly crafted but perfectly legitimate response.This flaw would then make curl silently | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| continue its operations **withoutTLS** contrary to the instructions and expectations, exposing possibly sensitive data in clear text over the network. | | | | | |
| CVE-2021-22946 | High | 7.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| A user can tell curl >= 7.20.0 and <= 7.78.0 to require a successful upgrade to TLS when speaking to an IMAP, POP3 or FTP server (`--ssl-reqd` on the command line or`CURLOPT_USE_SSL` set to `CURLUSESSL_CONTROL` or `CURLUSESSL_ALL` withlibcurl). This requirement could be bypassed if the server would return a properly crafted but perfectly legitimate response.This flaw would then make curl silently continue its operations **withoutTLS** contrary to the instructions and expectations, exposing possibly sensitive data in clear text over the network. | | | | | |
| CVE-2021-3326 | High | 7.5 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| The iconv function in the GNU C Library (aka glibc or libc6) 2.32 and earlier, when processing invalid input sequences in the ISO-2022-JP-3 encoding, fails an assertion in the code path and aborts the program, potentially resulting in a denial of service. | | | | | |
| CVE-2021-3326 | High | 7.5 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| The iconv function in the GNU C Library (aka glibc or libc6) 2.32 and earlier, when processing invalid input sequences in the ISO-2022-JP-3 encoding, fails an assertion in the code path and aborts the program, potentially resulting in a denial of service. | | | | | |
| CVE-2021-33560 | High | 7.5 | libgcrypt20 | 1.8.4-5+deb10u1 | — |
| Libgcrypt before 1.8.8 and 1.9.x before 1.9.3 mishandles ElGamal encryption because it lacks exponent blinding to address a side-channel attack against mpi_powm, and the window size is not chosen appropriately. This, for example, affects use of ElGamal in OpenPGP. | | | | | |
| CVE-2021-36222 | High | 7.5 | libgssapi-krb5-2 | 1.17-3+deb10u1 | 1.17-3+deb10u2 |
| ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation. | | | | | |
| CVE-2021-36222 | High | 7.5 | libk5crypto3 | 1.17-3+deb10u1 | 1.17-3+deb10u2 |
| ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation. | | | | | |
| CVE-2021-36222 | High | 7.5 | libkrb5-3 | 1.17-3+deb10u1 | 1.17-3+deb10u2 |
| ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation. | | | | | |
| CVE-2021-36222 | High | 7.5 | libkrb5support0 | 1.17-3+deb10u1 | 1.17-3+deb10u2 |
| ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation. | | | | | |
| CVE-2021-43618 | High | 7.5 | libgmp10 | 2:6.1.2+dfsg-4 | 2:6.1.2+dfsg-4+deb10u1 |
| GNU Multiple Precision Arithmetic Library (GMP) through 6.2.1 has an mpz/inp_raw.c integer overflow and resultant buffer overflow via crafted input, leading to a segmentation fault on 32-bit platforms. | | | | | |
| CVE-2022-0778 | High | 7.5 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u8 |
| The BN_mod_sqrt() function, which computes a modular square root, contains a bug that can cause it to loop forever for non-prime moduli. Internally this function is used when parsing certificates that contain elliptic curve public keys in compressed form or explicit elliptic curve parameters with a base point encoded in compressed form. It is possible to trigger the infinite loop by crafting a certificate that has invalid | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| explicit curve parameters. Since certificate parsing happens prior to verification of the certificate signature, any process that parses an externally supplied certificate ma... | | | | | |
| CVE-2022-0778 | High | 7.5 | openssl | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u8 |
| The BN_mod_sqrt() function, which computes a modular square root, contains a bug that can cause it to loop forever for non-prime moduli. Internally this function is used when parsing certificates that contain elliptic curve public keys in compressed form or explicit elliptic curve parameters with a base point encoded in compressed form. It is possible to trigger the infinite loop by crafting a certificate that has invalid explicit curve parameters. Since certificate parsing happens prior to verification of the certificate signature, any process that parses an externally supplied certificate ma... | | | | | |
| CVE-2022-2309 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |
| NULL Pointer Dereference allows attackers to cause a denial of service (or application crash). This only applies when lxml is used together with libxml2 2.9.10 through 2.9.14. libxml2 2.9.9 and earlier are not affected. It allows triggering crashes through forged input data, given a vulnerable code sequence in the application. The vulnerability is caused by the iterwalk function (also used by the canonicalize function). Such code shouldn't be in wide-spread use, given that parsing + iterwalk would usually be replaced with the more efficient iterparse function. However, an XML converter that se... | | | | | |
| CVE-2022-23308 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u3 |
| valid.c in libxml2 before 2.9.13 has a use-after-free of ID and IDREF attributes. | | | | | |
| CVE-2022-23990 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u2 |
| Expat (aka libexpat) before 2.4.4 has an integer overflow in the doProlog function. | | | | | |
| CVE-2022-2509 | High | 7.5 | libgnutls30 | 3.6.7-4+deb10u7 | 3.6.7-4+deb10u9 |
| A vulnerability found in gnutls. This security flaw happens because of a double free error occurs during verification of pkcs7 signatures in gnutls_pkcs7_verify function. | | | | | |
| CVE-2022-25314 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u3 |
| In Expat (aka libexpat) before 2.4.5, there is an integer overflow in copyString. | | | | | |
| CVE-2022-27405 | High | 7.5 | libfreetype6 | 2.9.1-3+deb10u2 | 2.9.1-3+deb10u3 |
| FreeType commit 53dfdcd8198d2b3201a23c4bad9190519ba918db was discovered to contain a segmentation violation via the function FNT_Size_Request. | | | | | |
| CVE-2022-27406 | High | 7.5 | libfreetype6 | 2.9.1-3+deb10u2 | 2.9.1-3+deb10u3 |
| FreeType commit 22a0cccb4d9d002f33c1ba7a4b36812c7d4f46b5 was discovered to contain a segmentation violation via the function FT_Request_Size. | | | | | |
| CVE-2022-27781 | High | 7.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| libcurl provides the `CURLOPT_CERTINFO` option to allow applications torequest details to be returned about a server's certificate chain.Due to an erroneous function, a malicious server could make libcurl built withNSS get stuck in a never-ending busy-loop when trying to retrieve thatinformation. | | | | | |
| CVE-2022-27781 | High | 7.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| libcurl provides the `CURLOPT_CERTINFO` option to allow applications torequest details to be returned about a server's certificate chain.Due to an erroneous function, a malicious server could make libcurl built withNSS get stuck in a never-ending busy-loop when trying to retrieve thatinformation. | | | | | |
| CVE-2022-27782 | High | 7.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| libcurl would reuse a previously created connection even when a TLS or SSHrelated option had been changed that should have prohibited reuse.libcurl keeps previously used connections in a connection pool for subsequenttransfers to reuse if one of them matches the setup. However, several TLS andSSH settings were left out from the configuration match checks, making themmatch too easily. | | | | | |
| CVE-2022-27782 | High | 7.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| libcurl would reuse a previously created connection even when a TLS or SSHrelated option had been changed that should have prohibited reuse.libcurl keeps previously used connections in a connection pool for subsequenttransfers to reuse if one of them matches the setup. However, several TLS andSSH settings were left out from the configuration match checks, making themmatch too easily. | | | | | |
| CVE-2022-40303 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u5 |
| An issue was discovered in libxml2 before 2.10.3. When parsing a multi-gigabyte XML document with the XML_PARSE_HUGE parser option enabled, several integer counters can overflow. This results in an attempt to access an array at a negative 2GB offset, typically leading to a segmentation fault. | | | | | |
| CVE-2022-43680 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u6 |
| In libexpat through 2.4.9, there is a use-after free caused by overeager destruction of a shared DTD in XML_ExternalEntityParserCreate in out-of-memory situations. | | | | | |
| CVE-2022-4450 | High | 7.5 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| The function PEM_read_bio_ex() reads a PEM file from a BIO and parses and decodes the "name" (e.g. "CERTIFICATE"), any header data and the payload data. If the function succeeds then the "name_out", "header" and "data" arguments are populated with pointers to buffers containing the relevant decoded data. The caller is responsible for freeing those buffers. It is possible to construct a PEM file that results in 0 bytes of payload data. In this case PEM_read_bio_ex() will return a failure code but will populate the header argument with a pointer to a buffer that has already been freed. If the ca... | | | | | |
| CVE-2022-4450 | High | 7.5 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| The function PEM_read_bio_ex() reads a PEM file from a BIO and parses and decodes the "name" (e.g. "CERTIFICATE"), any header data and the payload data. If the function succeeds then the "name_out", "header" and "data" arguments are populated with pointers to buffers containing the relevant decoded data. The caller is responsible for freeing those buffers. It is possible to construct a PEM file that results in 0 bytes of payload data. In this case PEM_read_bio_ex() will return a failure code but will populate the header argument with a pointer to a buffer that has already been freed. If the ca... | | | | | |
| CVE-2022-44617 | High | 7.5 | libxpm4 | 1:3.5.12-1 | 1:3.5.12-1+deb10u1 |
| A flaw was found in libXpm. When processing a file with width of 0 and a very large height, some parser functions will be called repeatedly and can lead to an infinite loop, resulting in a Denial of Service in the application linked to the library. | | | | | |
| CVE-2022-46285 | High | 7.5 | libxpm4 | 1:3.5.12-1 | 1:3.5.12-1+deb10u1 |
| A flaw was found in libXpm. This issue occurs when parsing a file with a comment not closed; the end-of-file condition will not be detected, leading to an infinite loop and resulting in a Denial of Service in the application linked to the library. | | | | | |
| CVE-2023-0215 | High | 7.5 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| The public API function BIO_new_NDEF is a helper function used for streaming ASN.1 data via a BIO. It is primarily used internally to OpenSSL to support the SMIME, CMS and PKCS7 streaming capabilities, but may also be called directly by end user applications.<br><br>The function receives a BIO from the caller, prepends a new BIO_f_asn1 filter BIO onto the front of it to form a BIO chain, and then returns the new head of | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| | | | the BIO chain to the caller. Under certain conditions, for example if a CMS recipient public key is invalid, the new filter BIO is freed and the function returns a NULL result indica... | | |
| CVE-2023-0215 | High | 7.5 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| | | | The public API function BIO_new_NDEF is a helper function used for streaming ASN.1 data via a BIO. It is primarily used internally to OpenSSL to support the SMIME, CMS and PKCS7 streaming capabilities, but may also be called directly by end user applications.<br><br>The function receives a BIO from the caller, prepends a new BIO_f_asn1 filter BIO onto the front of it to form a BIO chain, and then returns the new head of the BIO chain to the caller. Under certain conditions, for example if a CMS recipient public key is invalid, the new filter BIO is freed and the function returns a NULL result indica... | | |
| CVE-2023-0464 | High | 7.5 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| | | | A security vulnerability has been identified in all supported versions<br><br>of OpenSSL related to the verification of X.509 certificate chains that include policy constraints. Attackers may be able to exploit this vulnerability by creating a malicious certificate chain that triggers exponential use of computational resources, leading to a denial-of-service (DoS) attack on affected systems.<br><br>Policy processing is disabled by default but can be enabled by passing the `-policy' argument to the command line utilities or by calling the `X509_VERIFY_PARAM_set1_policies()' function. | | |
| CVE-2023-0464 | High | 7.5 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| | | | A security vulnerability has been identified in all supported versions<br><br>of OpenSSL related to the verification of X.509 certificate chains that include policy constraints. Attackers may be able to exploit this vulnerability by creating a malicious certificate chain that triggers exponential use of computational resources, leading to a denial-of-service (DoS) attack on affected systems.<br><br>Policy processing is disabled by default but can be enabled by passing the `-policy' argument to the command line utilities or by calling the `X509_VERIFY_PARAM_set1_policies()' function. | | |
| CVE-2023-1999 | High | 7.5 | libwebp6 | 0.6.1-2+deb10u1 | 0.6.1-2+deb10u2 |
| | | | There exists a use after free/double free in libwebp. An attacker can use the ApplyFiltersAndEncode() function and loop through to free best.bw and assign best = trial pointer. The second loop will then return 0 because of an Out of memory error in VP8 encoder, the pointer is still assigned to trial and the AddressSanitizer will attempt a double free. | | |
| CVE-2023-2953 | High | 7.5 | libldap-2.4-2 | 2.4.47+dfsg-3+deb10u6 | — |
| | | | A vulnerability was found in openldap. This security flaw causes a null pointer dereference in ber_memalloc_x() function. | | |
| CVE-2023-2953 | High | 7.5 | libldap-common | 2.4.47+dfsg-3+deb10u6 | — |
| | | | A vulnerability was found in openldap. This security flaw causes a null pointer dereference in ber_memalloc_x() function. | | |
| CVE-2023-3138 | High | 7.5 | libx11-6 | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u3 |
| | | | A vulnerability was found in libX11. The security flaw occurs because the functions in src/InitExt.c in libX11 do not check that the values provided for the Request, Event, or Error IDs are within the bounds of the arrays that those functions write to, using those IDs as array in- | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| dexes. They trust that they were called with values provided by an Xserver adhering to the bounds specified in the X11 protocol, as all X servers provided by X.Org do. As the protocol only specifies a single byte for these values, an out-of-bounds value provided by a malicious server (or a malicious proxy-in-the-middle... | | | | | |
| CVE-2023-3138 | High | 7.5 | libx11-data | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u3 |
| A vulnerability was found in libX11. The security flaw occurs because the functions in src/InitExt.c in libX11 do not check that the values provided for the Request, Event, or Error IDs are within the bounds of the arrays that those functions write to, using those IDs as array indexes. They trust that they were called with values provided by an Xserver adhering to the bounds specified in the X11 protocol, as all X servers provided by X.Org do. As the protocol only specifies a single byte for these values, an out-of-bounds value provided by a malicious server (or a malicious proxy-in-the-middle... | | | | | |
| CVE-2023-44487 | High | 7.5 | libnghttp2-14 | 1.36.0-2+deb10u1 | 1.36.0-2+deb10u2 |
| The HTTP/2 protocol allows a denial of service (server resource consumption) because request cancellation can reset many streams quickly, as exploited in the wild in August through October 2023. | | | | | |
| CVE-2023-50387 | High | 7.5 | libsystemd0 | 241-7~deb10u7 | – |
| Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the "KeyTrap" issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records. | | | | | |
| CVE-2023-50387 | High | 7.5 | libudev1 | 241-7~deb10u7 | – |
| Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the "KeyTrap" issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records. | | | | | |
| CVE-2023-50868 | High | 7.5 | libsystemd0 | 241-7~deb10u7 | – |
| The Closest Encloser Proof aspect of the DNS protocol (in RFC 5155 when RFC 9276 guidance is skipped) allows remote attackers to cause a denial of service (CPU consumption for SHA-1 computations) via DNSSEC responses in a random subdomain attack, aka the "NSEC3" issue. The RFC 5155 specification implies that an algorithm must perform thousands of iterations of a hash function in certain situations. | | | | | |
| CVE-2023-50868 | High | 7.5 | libudev1 | 241-7~deb10u7 | – |
| The Closest Encloser Proof aspect of the DNS protocol (in RFC 5155 when RFC 9276 guidance is skipped) allows remote attackers to cause a denial of service (CPU consumption for SHA-1 computations) via DNSSEC responses in a random subdomain attack, aka the "NSEC3" issue. The RFC 5155 specification implies that an algorithm must perform thousands of iterations of a hash function in certain situations. | | | | | |
| CVE-2023-52355 | High | 7.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | – |
| An out-of-memory flaw was found in libtiff that could be triggered by passing a crafted tiff file to the TIFFRasterScanlineSize64() API. This flaw allows a remote attacker to cause a denial of service via a crafted input with a size smaller than 379 KB. | | | | | |
| CVE-2023-52356 | High | 7.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u9 |
| A segment fault (SEGV) flaw was found in libtiff that could be triggered by passing a crafted tiff file to the TIFFReadRGBATileExt() API. This flaw allows a remote attacker to cause a heap-buffer overflow, leading to a denial of service. | | | | | |
| CVE-2023-52425 | High | 7.5 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u7 |
| libexpat through 2.5.0 allows a denial of service (resource consumption) because many full reparsings are required in the case of a large token for which multiple buffer fills are needed. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2024-0553 | High | 7.5 | libgnutls30 | 3.6.7-4+deb10u7 | 3.6.7-4+deb10u12 |

A vulnerability was found in GnuTLS. The response times to malformed ciphertexts in RSA-PSK ClientKeyExchange differ from the response times of ciphertexts with correct PKCS#1 v1.5 padding. This issue may allow a remote attacker to perform a timing side-channel attack in the RSA-PSK key exchange, potentially leading to the leakage of sensitive data. CVE-2024-0553 is designated as an incomplete resolution for CVE-2023-5981.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-2398 | High | 7.5 | curl | 7.64.0-4+deb10u2 | — |

When an application tells libcurl it wants to allow HTTP/2 server push, and the amount of received headers for the push surpasses the maximum allowed limit (1000), libcurl aborts the server push. When aborting, libcurl inadvertently does not free all the previously allocated headers and instead leaks the memory. Further, this error condition fails silently and is therefore not easily detected by an application.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-2398 | High | 7.5 | libcurl4 | 7.64.0-4+deb10u2 | — |

When an application tells libcurl it wants to allow HTTP/2 server push, and the amount of received headers for the push surpasses the maximum allowed limit (1000), libcurl aborts the server push. When aborting, libcurl inadvertently does not free all the previously allocated headers and instead leaks the memory. Further, this error condition fails silently and is therefore not easily detected by an application.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-25062 | High | 7.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |

An issue was discovered in libxml2 before 2.11.7 and 2.12.x before 2.12.5. When using the XML Reader interface with DTD validation and XInclude expansion enabled, processing crafted XML documents can lead to an xmlValidatePopElement use-after-free.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2021-3712 | High | 7.4 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u7 |

ASN.1 strings are represented internally within OpenSSL as an ASN1_STRING structure which contains a buffer holding the string data and a field holding the buffer length. This contrasts with normal C strings which are repesented as a buffer for the string data which is terminated with a NUL (0) byte. Although not a strict requirement, ASN.1 strings that are parsed using OpenSSL's own "d2i" functions (and other similar parsing functions) as well as any string whose value has been set with the ASN1_STRING_set() function will additionally NUL terminate the byte array in the ASN1_STRING structure....

| | | | | | |
|---|---|---|---|---|---|
| CVE-2021-3712 | High | 7.4 | openssl | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u7 |

ASN.1 strings are represented internally within OpenSSL as an ASN1_STRING structure which contains a buffer holding the string data and a field holding the buffer length. This contrasts with normal C strings which are repesented as a buffer for the string data which is terminated with a NUL (0) byte. Although not a strict requirement, ASN.1 strings that are parsed using OpenSSL's own "d2i" functions (and other similar parsing functions) as well as any string whose value has been set with the ASN1_STRING_set() function will additionally NUL terminate the byte array in the ASN1_STRING structure....

| | | | | | |
|---|---|---|---|---|---|
| CVE-2023-0286 | High | 7.4 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |

There is a type confusion vulnerability relating to X.400 address processing inside an X.509 GeneralName. X.400 addresses were parsed as an ASN1_STRING but the public structure definition for GENERAL_NAME incorrectly specified the type of the x400Address field as ASN1_TYPE. This field is subsequently interpreted by the OpenSSL function GENERAL_NAME_cmp as an ASN1_TYPE rather than an ASN1_STRING.

When CRL checking is enabled (i.e. the application sets the X509_V_FLAG_CRL_CHECK flag), this vulnerability may allow an attacker to pass arbitrary pointers to a memcmp call, enabling them to read mem...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2023-0286 | High | 7.4 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |

There is a type confusion vulnerability relating to X.400 address processing inside an X.509 GeneralName. X.400 addresses were parsed as an ASN1_STRING but the public structure definition for GENERAL_NAME incorrectly specified the type of the x400Address field as ASN1_TYPE. This field is subsequently interpreted by the OpenSSL function GENERAL_NAME_cmp as an ASN1_TYPE rather than an ASN1_STRING.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| When CRL checking is enabled (i.e. the application sets the X509_V_FLAG_CRL_CHECK flag), this vulnerability may allow an attacker to pass arbitrary pointers to a memcmp call, enabling them to read mem... | | | | | |
| CVE-2023-0361 | High | 7.4 | libgnutls30 | 3.6.7-4+deb10u7 | 3.6.7-4+deb10u10 |
| A timing side-channel in the handling of RSA ClientKeyExchange messages was discovered in GnuTLS. This side-channel can be sufficient to recover the key encrypted in the RSA ciphertext across a network in a Bleichenbacher style attack. To achieve a successful decryption the attacker would need to send a large amount of specially crafted messages to the vulnerable server. By recovering the secret from the ClientKeyExchange message, the attacker would be able to decrypt the application data exchanged over that connection. | | | | | |
| CVE-2022-1292 | High | 7.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u2 |
| The c_rehash script does not properly sanitise shell metacharacters to prevent command injection. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbitrary commands with the privileges of the script. Use of the c_rehash script is considered obsolete and should be replaced by the OpenSSL rehash command line tool. Fixed in OpenSSL 3.0.3 (Affected 3.0.0,3.0.1,3.0.2). Fixed in OpenSSL 1.1.1o (Affected 1.1.1-1.1.1n). Fixed in OpenSSL 1.0.2ze (Affected 1.0.2-1.0.2zd). | | | | | |
| CVE-2022-1292 | High | 7.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u2 |
| The c_rehash script does not properly sanitise shell metacharacters to prevent command injection. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbitrary commands with the privileges of the script. Use of the c_rehash script is considered obsolete and should be replaced by the OpenSSL rehash command line tool. Fixed in OpenSSL 3.0.3 (Affected 3.0.0,3.0.1,3.0.2). Fixed in OpenSSL 1.1.1o (Affected 1.1.1-1.1.1n). Fixed in OpenSSL 1.0.2ze (Affected 1.0.2-1.0.2zd). | | | | | |
| CVE-2022-2068 | High | 7.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u3 |
| In addition to the c_rehash shell command injection identified in CVE-2022-1292, further circumstances where the c_rehash script does not properly sanitise shell metacharacters to prevent command injection were found by code review. When the CVE-2022-1292 was fixed it was not discovered that there are other places in the script where the file names of certificates being hashed were possibly passed to a command executed through the shell. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbi... | | | | | |
| CVE-2022-2068 | High | 7.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u3 |
| In addition to the c_rehash shell command injection identified in CVE-2022-1292, further circumstances where the c_rehash script does not properly sanitise shell metacharacters to prevent command injection were found by code review. When the CVE-2022-1292 was fixed it was not discovered that there are other places in the script where the file names of certificates being hashed were possibly passed to a command executed through the shell. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbi... | | | | | |
| CVE-2022-0891 | High | 7.1 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| A heap buffer overflow in ExtractImageSection function in tiffcrop.c in libtiff library Version 4.3.0 allows attacker to trigger unsafe or out of bounds memory access via crafted TIFF image file which could result into application crash, potential information disclosure or any other context-dependent impact | | | | | |
| CVE-2022-29458 | High | 7.1 | libncursesw6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u3 |
| ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library. | | | | | |
| CVE-2022-29458 | High | 7.1 | libtinfo6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u3 |
| ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-29458 | High | 7.1 | ncurses-base | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u3 |
| ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library. | | | | | |
| CVE-2022-29458 | High | 7.1 | ncurses-bin | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u3 |
| ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library. | | | | | |
| CVE-2020-1751 | High | 7.0 | libc-bin | 2.28-10 | — |
| An out-of-bounds write vulnerability was found in glibc before 2.31 when handling signal trampolines on PowerPC. Specifically, the backtrace function did not properly check the array bounds when storing the frame address, resulting in a denial of service or potential code execution. The highest threat from this vulnerability is to system availability. | | | | | |
| CVE-2020-1751 | High | 7.0 | libc6 | 2.28-10 | — |
| An out-of-bounds write vulnerability was found in glibc before 2.31 when handling signal trampolines on PowerPC. Specifically, the backtrace function did not properly check the array bounds when storing the frame address, resulting in a denial of service or potential code execution. The highest threat from this vulnerability is to system availability. | | | | | |
| CVE-2020-1752 | High | 7.0 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| A use-after-free vulnerability introduced in glibc upstream version 2.14 was found in the way the tilde expansion was carried out. Directory paths containing an initial tilde followed by a valid username were affected by this issue. A local attacker could exploit this flaw by creating a specially crafted path that, when processed by the glob function, would potentially lead to arbitrary code execution. This was fixed in version 2.32. | | | | | |
| CVE-2020-1752 | High | 7.0 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| A use-after-free vulnerability introduced in glibc upstream version 2.14 was found in the way the tilde expansion was carried out. Directory paths containing an initial tilde followed by a valid username were affected by this issue. A local attacker could exploit this flaw by creating a specially crafted path that, when processed by the glob function, would potentially lead to arbitrary code execution. This was fixed in version 2.32. | | | | | |
| CVE-2016-2781 | Medium | 6.5 | coreutils | 8.30-3 | — |
| CVE-2020-19143 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u3 |
| CVE-2020-19189 | Medium | 6.5 | libncursesw6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u4 |
| CVE-2020-19189 | Medium | 6.5 | libtinfo6 | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u4 |
| CVE-2020-19189 | Medium | 6.5 | ncurses-base | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u4 |
| CVE-2020-19189 | Medium | 6.5 | ncurses-bin | 6.1+20181013-2+deb10u2 | 6.1+20181013-2+deb10u4 |
| CVE-2021-37750 | Medium | 6.5 | libgssapi-krb5-2 | 1.17-3+deb10u1 | 1.17-3+deb10u3 |
| CVE-2021-37750 | Medium | 6.5 | libk5crypto3 | 1.17-3+deb10u1 | 1.17-3+deb10u3 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2021-37750 | Medium | 6.5 | libkrb5-3 | 1.17-3+deb10u1 | 1.17-3+deb10u3 |
| CVE-2021-37750 | Medium | 6.5 | libkrb5support0 | 1.17-3+deb10u1 | 1.17-3+deb10u3 |
| CVE-2021-38115 | Medium | 6.5 | libgd3 | 2.2.5-5.2 | 2.2.5-5.2+deb10u1 |
| CVE-2021-40812 | Medium | 6.5 | libgd3 | 2.2.5-5.2 | 2.2.5-5.2+deb10u1 |
| CVE-2021-4209 | Medium | 6.5 | libgnutls30 | 3.6.7-4+deb10u7 | 3.6.7-4+deb10u9 |
| CVE-2022-0865 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-1210 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | — |
| CVE-2022-2056 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-2057 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-2058 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-25313 | Medium | 6.5 | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u3 |
| CVE-2022-27776 | Medium | 6.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-27776 | Medium | 6.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-29824 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u4 |
| CVE-2022-32206 | Medium | 6.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-32206 | Medium | 6.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-34526 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-34903 | Medium | 6.5 | gpgv | 2.2.12-1+deb10u1 | 2.2.12-1+deb10u2 |
| CVE-2022-3597 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-3598 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-3599 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-3626 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-3627 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-40090 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | — |
| CVE-2023-23916 | Medium | 6.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u5 |
| CVE-2023-23916 | Medium | 6.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u5 |
| CVE-2023-2650 | Medium | 6.5 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-2650 | Medium | 6.5 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-28484 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u6 |
| CVE-2023-29469 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | 2.9.4+dfsg1-7+deb10u6 |
| CVE-2023-3316 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-36054 | Medium | 6.5 | libgssapi-krb5-2 | 1.17-3+deb10u1 | 1.17-3+deb10u6 |
| CVE-2023-36054 | Medium | 6.5 | libk5crypto3 | 1.17-3+deb10u1 | 1.17-3+deb10u6 |
| CVE-2023-36054 | Medium | 6.5 | libkrb5-3 | 1.17-3+deb10u1 | 1.17-3+deb10u6 |
| CVE-2023-36054 | Medium | 6.5 | libkrb5support0 | 1.17-3+deb10u1 | 1.17-3+deb10u6 |
| CVE-2023-3618 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-39615 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |
| CVE-2023-40745 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-41175 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-45322 | Medium | 6.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-46218 | Medium | 6.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u8 |
| CVE-2023-46218 | Medium | 6.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u8 |
| CVE-2023-50495 | Medium | 6.5 | libncursesw6 | 6.1+20181013-2+deb10u2 | — |
| CVE-2023-50495 | Medium | 6.5 | libtinfo6 | 6.1+20181013-2+deb10u2 | — |
| CVE-2023-50495 | Medium | 6.5 | ncurses-base | 6.1+20181013-2+deb10u2 | — |
| CVE-2023-50495 | Medium | 6.5 | ncurses-bin | 6.1+20181013-2+deb10u2 | — |
| CVE-2023-6277 | Medium | 6.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | — |
| CVE-2019-13627 | Medium | 6.3 | libgcrypt20 | 1.8.4-5+deb10u1 | — |
| CVE-2016-3709 | Medium | 6.1 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |
| CVE-2022-1355 | Medium | 6.1 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2016-10228 | Medium | 5.9 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2016-10228 | Medium | 5.9 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2019-25013 | Medium | 5.9 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2019-25013 | Medium | 5.9 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2021-22947 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2021-22947 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2021-4160 | Medium | 5.9 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u8 |
| CVE-2021-4160 | Medium | 5.9 | openssl | 1.1.1d-0+deb10u6 | 1.1.1d-0+deb10u8 |
| CVE-2022-32208 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-32208 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-4304 | Medium | 5.9 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-4304 | Medium | 5.9 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| CVE-2022-43552 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2022-43552 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2023-27535 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-27535 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-27536 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-27536 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-28321 | Medium | 5.9 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u7 |
| CVE-2023-28321 | Medium | 5.9 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u7 |
| CVE-2023-4806 | Medium | 5.9 | libc-bin | 2.28-10 | — |
| CVE-2023-4806 | Medium | 5.9 | libc6 | 2.28-10 | — |
| CVE-2023-4813 | Medium | 5.9 | libc-bin | 2.28-10 | — |
| CVE-2023-4813 | Medium | 5.9 | libc6 | 2.28-10 | — |
| CVE-2023-5981 | Medium | 5.9 | libgnutls30 | 3.6.7-4+deb10u7 | 3.6.7-4+deb10u11 |
| CVE-2023-7008 | Medium | 5.9 | libsystemd0 | 241-7~deb10u7 | — |
| CVE-2023-7008 | Medium | 5.9 | libudev1 | 241-7~deb10u7 | — |
| CVE-2022-27774 | Medium | 5.7 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2022-27774 | Medium | 5.7 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2024-4741 | Medium | 5.6 | libssl1.1 | 1.1.1d-0+deb10u6 | — |
| CVE-2024-4741 | Medium | 5.6 | openssl | 1.1.1d-0+deb10u6 | — |
| CVE-2016-9318 | Medium | 5.5 | libxml2 | 2.9.4+dfsg1-7+deb10u2 | — |
| CVE-2020-10029 | Medium | 5.5 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2020-10029 | Medium | 5.5 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2020-21913 | Medium | 5.5 | libicu63 | 63.1-6+deb10u1 | 63.1-6+deb10u2 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-27618 | Medium | 5.5 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2020-27618 | Medium | 5.5 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2020-35538 | Medium | 5.5 | libjpeg62-turbo | 1:1.5.2-2+deb10u1 | — |
| CVE-2021-33910 | Medium | 5.5 | libsystemd0 | 241-7~deb10u7 | 241-7~deb10u8 |
| CVE-2021-33910 | Medium | 5.5 | libudev1 | 241-7~deb10u7 | 241-7~deb10u8 |
| CVE-2021-37600 | Medium | 5.5 | bsdutils | 1:2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | fdisk | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | libblkid1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | libfdisk1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | libmount1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | libsmartcols1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | libuuid1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | mount | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-37600 | Medium | 5.5 | util-linux | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2021-3997 | Medium | 5.5 | libsystemd0 | 241-7~deb10u7 | — |
| CVE-2021-3997 | Medium | 5.5 | libudev1 | 241-7~deb10u7 | — |
| CVE-2021-46822 | Medium | 5.5 | libjpeg62-turbo | 1:1.5.2-2+deb10u1 | — |
| CVE-2022-0561 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-0562 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-0907 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-0908 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-0909 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-0924 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-1354 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-22844 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u4 |
| CVE-2022-2867 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-2868 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-2869 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-3570 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-3821 | Medium | 5.5 | libsystemd0 | 241-7~deb10u7 | 241-7~deb10u10 |
| CVE-2022-3821 | Medium | 5.5 | libudev1 | 241-7~deb10u7 | 241-7~deb10u10 |
| CVE-2022-4415 | Medium | 5.5 | libsystemd0 | 241-7~deb10u7 | — |
| CVE-2022-4415 | Medium | 5.5 | libudev1 | 241-7~deb10u7 | — |
| CVE-2022-4645 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2022-48281 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u6 |
| CVE-2023-0795 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0796 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0797 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0798 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-0799 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0800 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0801 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0802 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0803 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-0804 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-25433 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-25435 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u7 |
| CVE-2023-26965 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-26966 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-27538 | Medium | 5.5 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-27538 | Medium | 5.5 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u6 |
| CVE-2023-2908 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u8 |
| CVE-2023-30086 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2023-30774 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u5 |
| CVE-2023-3576 | Medium | 5.5 | libtiff5 | 4.1.0+git191117-2~deb10u2 | 4.1.0+git191117-2~deb10u9 |
| CVE-2023-43785 | Medium | 5.5 | libx11-6 | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |
| CVE-2023-43785 | Medium | 5.5 | libx11-data | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-43786 | Medium | 5.5 | libx11-6 | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |
| CVE-2023-43786 | Medium | 5.5 | libx11-data | 2:1.6.7-1+deb10u2 | 2:1.6.7-1+deb10u4 |
| CVE-2023-43788 | Medium | 5.5 | libxpm4 | 1:3.5.12-1 | 1:3.5.12-1+deb10u2 |
| CVE-2023-43789 | Medium | 5.5 | libxpm4 | 1:3.5.12-1 | 1:3.5.12-1+deb10u2 |
| CVE-2023-4641 | Medium | 5.5 | login | 1:4.5-1.1 | — |
| CVE-2023-4641 | Medium | 5.5 | passwd | 1:4.5-1.1 | — |
| CVE-2024-0727 | Medium | 5.5 | libssl1.1 | 1.1.1d-0+deb10u6 | — |
| CVE-2024-0727 | Medium | 5.5 | openssl | 1.1.1d-0+deb10u6 | — |
| CVE-2024-22365 | Medium | 5.5 | libpam-modules | 1.3.1-5 | — |
| CVE-2024-22365 | Medium | 5.5 | libpam-modules-bin | 1.3.1-5 | — |
| CVE-2024-22365 | Medium | 5.5 | libpam-runtime | 1.3.1-5 | — |
| CVE-2024-22365 | Medium | 5.5 | libpam0g | 1.3.1-5 | — |
| CVE-2018-7169 | Medium | 5.3 | login | 1:4.5-1.1 | — |
| CVE-2018-7169 | Medium | 5.3 | passwd | 1:4.5-1.1 | — |
| CVE-2020-14155 | Medium | 5.3 | libpcre3 | 2:8.39-12 | — |
| CVE-2022-2097 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| CVE-2022-2097 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u4 |
| CVE-2023-0465 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-0465 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-0466 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-0466 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u5 |
| CVE-2023-3446 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u6 |
| CVE-2023-3446 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u6 |
| CVE-2023-3817 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u6 |
| CVE-2023-3817 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | 1.1.1n-0+deb10u6 |
| CVE-2023-5678 | Medium | 5.3 | libssl1.1 | 1.1.1d-0+deb10u6 | — |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-5678 | Medium | 5.3 | openssl | 1.1.1d-0+deb10u6 | — |
| CVE-2024-28182 | Medium | 5.3 | libnghttp2-14 | 1.36.0-2+deb10u1 | 1.36.0-2+deb10u3 |
| CVE-2024-33600 | Medium | 5.3 | libc-bin | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2024-33600 | Medium | 5.3 | libc6 | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2024-28085 | Medium | 4.4 | bsdutils | 1:2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | fdisk | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | libblkid1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | libfdisk1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | libmount1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | libsmartcols1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | libuuid1 | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | mount | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-28085 | Medium | 4.4 | util-linux | 2.33.1-0.1 | 2.33.1-0.1+deb10u1 |
| CVE-2024-33601 | Medium | 4.0 | libc-bin | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2024-33601 | Medium | 4.0 | libc6 | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2024-33602 | Medium | 4.0 | libc-bin | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2024-33602 | Medium | 4.0 | libc6 | 2.28-10 | 2.28-10+deb10u4 |
| CVE-2021-22924 | Low | 3.7 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2021-22924 | Low | 3.7 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2022-35252 | Low | 3.7 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2022-35252 | Low | 3.7 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u4 |
| CVE-2023-28322 | Low | 3.7 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u8 |
| CVE-2023-28322 | Low | 3.7 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u8 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2023-38546 | Low | 3.7 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u7 |
| CVE-2023-38546 | Low | 3.7 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u7 |
| CVE-2024-2511 | Low | 3.7 | libssl1.1 | 1.1.1d-0+deb10u6 | — |
| CVE-2024-2511 | Low | 3.7 | openssl | 1.1.1d-0+deb10u6 | — |
| CVE-2019-19126 | Low | 3.3 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2019-19126 | Low | 3.3 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2021-36084 | Low | 3.3 | libsepol1 | 2.8-1 | — |
| CVE-2021-36085 | Low | 3.3 | libsepol1 | 2.8-1 | — |
| CVE-2021-36086 | Low | 3.3 | libsepol1 | 2.8-1 | — |
| CVE-2021-36087 | Low | 3.3 | libsepol1 | 2.8-1 | — |
| CVE-2023-29383 | Low | 3.3 | login | 1:4.5-1.1 | — |
| CVE-2023-29383 | Low | 3.3 | passwd | 1:4.5-1.1 | — |
| CVE-2023-39804 | Low | 3.3 | tar | 1.30+dfsg-6 | 1.30+dfsg-6+deb10u1 |
| CVE-2021-22898 | Low | 3.1 | curl | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2021-22898 | Low | 3.1 | libcurl4 | 7.64.0-4+deb10u2 | 7.64.0-4+deb10u3 |
| CVE-2021-27645 | Low | 2.5 | libc-bin | 2.28-10 | 2.28-10+deb10u2 |
| CVE-2021-27645 | Low | 2.5 | libc6 | 2.28-10 | 2.28-10+deb10u2 |
| DLA-3112-1 | Unrated | — | libbz2-1.0 | 1.0.6-9.2~deb10u1 | 1.0.6-9.2~deb10u2 |
| DLA-3134-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2021a-0+deb10u7 |
| DLA-3161-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2021a-0+deb10u8 |
| DLA-3366-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2021a-0+deb10u10 |
| DLA-3412-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2021a-0+deb10u11 |
| DLA-3482-1 | Unrated | — | debian-archive-keyring | 2019.1+deb10u1 | 2019.1+deb10u2 |
| DLA-3684-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2021a-0+deb10u12 |
| DLA-3788-1 | Unrated | — | tzdata | 2021a-0+deb10u1 | 2024a-0+deb10u1 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| DSA-5085-2 | Unrated | — | libexpat1 | 2.2.6-2+deb10u1 | 2.2.6-2+deb10u4 |

# ghcr.io/christophetd/log4shell-vulnerable-app:latest

Digest sha256:6f88430688108e512f7405ac3c73d47f5c370780b94182854ea2cddc6bd59929
Platform linux/amd64
Operating System alpine 3.8.2
Size —
Created 2022-02-24T11:34:04Z
Scanned 2026-11-07T14:33:40Z
Vulnerabilities by Severity Critical 17 High 85 Medium 171 Low 160 Unrated 0

## Vulnerability Details

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2021-44228 | Critical | 10.0 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.15.0, 2.3.1, 2.12.2 |
| | | | Apache Log4j2 2.0-beta9 through 2.15.0 (excluding security releases 2.12.2, 2.12.3, and 2.3.1) JNDI features used in configuration, log messages, and parameters do not protect against attacker controlled LDAP and other JNDI related endpoints. An attacker who can control log messages or log message parameters can execute arbitrary code loaded from LDAP servers when message lookup substitution is enabled. From log4j 2.15.0, this behavior has been disabled by default. From version 2.16.0 (along with 2.12.2, 2.12.3, and 2.3.1), this functionality has been completely removed. Note that this vulnera... | | |
| CVE-2016-1000027 | Critical | 9.8 | org.springframework:spring-web | 5.3.13 | 6.0.0 |
| | | | Pivotal Spring Framework through 5.3.16 suffers from a potential remote code execution (RCE) issue if used for Java deserialization of untrusted data. Depending on how the library is implemented within a product, this issue may or not occur, and authentication may be required. NOTE: the vendor's position is that untrusted data is not an intended use case. The product's behavior will not be changed because some users rely on deserialization of trusted data. | | |
| CVE-2019-12900 | Critical | 9.8 | libbz2 | 1.0.6-r6 | 1.0.6-r7 |
| | | | BZ2_decompress in decompress.c in bzip2 through 1.0.6 has an out-of-bounds write when there are many selectors. | | |
| CVE-2019-14697 | Critical | 9.8 | musl | 1.1.19-r10 | 1.1.19-r11 |
| | | | musl libc through 1.1.23 has an x87 floating-point stack adjustment imbalance, related to the math/i386/ directory. In some cases, use of this library could introduce out-of-bounds writes that are not present in an application's source code. | | |
| CVE-2019-14697 | Critical | 9.8 | musl-utils | 1.1.19-r10 | 1.1.19-r11 |
| | | | musl libc through 1.1.23 has an x87 floating-point stack adjustment imbalance, related to the math/i386/ directory. In some cases, use of this library could introduce out-of-bounds writes that are not present in an application's source code. | | |
| CVE-2019-8457 | Critical | 9.8 | sqlite-libs | 3.24.0-r0 | 3.25.3-r1 |
| | | | SQLite3 from 3.6.0 to and including 3.27.2 is vulnerable to heap out-of-bound read in the rtreenode() function when handling invalid rtree tables. | | |
| CVE-2022-1471 | Critical | 9.8 | org.yaml:snakeyaml | 1.29 | 2.0 |
| | | | SnakeYaml's Constructor() class does not restrict types which can be instantiated during deserialization. Deserializing yaml content provided by an attacker can lead to remote code execution. We recommend using SnakeYaml's SafeConsturctor when parsing untrusted content to restrict deserialization. We recommend upgrading to version 2.0 and beyond. | | |
| CVE-2022-22965 | Critical | 9.8 | org.springframework:spring-beans | 5.3.13 | 5.2.20.RELEASE, 5.3.18 |
| | | | A Spring MVC or Spring WebFlux application running on JDK 9+ may be vulnerable to remote code execution (RCE) via data binding. The specific exploit requires the application to run on Tomcat as a WAR deployment. If the application is deployed as a Spring Boot executable jar, i.e. the default, it is not vulnerable to the exploit. However, the nature of the vulnerability is more general, and there may be other ways to exploit it. | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2022-22965 | Critical | 9.8 | org.springframework:spring-webmvc | 5.3.13 | 5.2.20.RELEASE, 5.3.18 |

A Spring MVC or Spring WebFlux application running on JDK 9+ may be vulnerable to remote code execution (RCE) via data binding. The specific exploit requires the application to run on Tomcat as a WAR deployment. If the application is deployed as a Spring Boot executable jar, i.e. the default, it is not vulnerable to the exploit. However, the nature of the vulnerability is more general, and there may be other ways to exploit it.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2025-24813 | Critical | 9.8 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.3, 10.1.35, 9.0.99 |

Path Equivalence: 'file.Name' (Internal Dot) leading to Remote Code Execution and/or Information disclosure and/or malicious content added to uploaded files via write enabled Default Servlet in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.2, from 10.1.0-M1 through 10.1.34, from 9.0.0.M1 through 9.0.98.
The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions
may also be affected.

If all of the following were true, a malicious user was able to view security sensitive ...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-47884 | Critical | 9.8 | org.springframework:spring-webmvc | 5.3.13 | 7.0.9 |

Use of XsltView in a Spring MVC application can result in SSRF and RCE attack if the application has an "/**" mapping that results in view rendering, and where the view name is not explicitly specified.
Spring Framework 7.0.0 - 7.0.8
Spring Framework 6.2.0 - 6.2.19
Spring Framework 6.1.0 - 6.1.28
Spring Framework 6.0.0 - 6.0.30
Spring Framework 5.3.0 - 5.3.49
Spring Framework 5.2.25.RELEASE and earlier

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2025-66614 | Critical | 9.1 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.15, 10.1.50, 9.0.113 |

Improper Input Validation vulnerability.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.14, from 10.1.0-M1 through 10.1.49, from 9.0.0-M1 through 9.0.112.

The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 through 8.5.100. Older EOL versions are not affected.
Tomcat did not validate that the host name provided via the SNI
extension was the same as the host name provided in the HTTP host header
field. If Tomcat was configured with more than one virtual host and the
TLS configuration for one of those hosts did not require clie...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-3183 | Critical | 9.0 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-3183 | Critical | 9.0 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-3183 | Critical | 9.0 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenti-

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| cated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit... | | | | | |
| CVE-2018-3183 | Critical | 9.0 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit... | | | | | |
| CVE-2021-45046 | Critical | 9.0 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.16.0, 2.12.2, 2.3.1 |
| It was found that the fix to address CVE-2021-44228 in Apache Log4j 2.15.0 was incomplete in certain non-default configurations. This could allows attackers with control over Thread Context Map (MDC) input data when the logging configuration uses a non-default Pattern Layout with either a Context Lookup (for example, $${ctx:loginId}) or a Thread Context Map pattern (%X, %mdc, or %MDC) to craft malicious input data using a JNDI Lookup pattern resulting in an information leak and remote code execution in some environments and local code execution in all environments. Log4j 2.16.0 (Java 8) and 2.... | | | | | |
| CVE-2018-14550 | High | 8.8 | libpng | 1.6.34-r1 | 1.6.37-r0 |
| An issue has been found in third-party PNM decoding associated with libpng 1.6.35. It is a stack-based buffer overflow in the function get_token in pnm2png.c in pnm2png. | | | | | |
| CVE-2025-49124 | High | 8.4 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.8, 10.1.42, 9.0.106 |
| Untrusted Search Path vulnerability in Apache Tomcat installer for Windows. During installation, the Tomcat installer for Windows used icacls.exe without specifying a full path.<br><br>This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.7, from 10.1.0 through 10.1.41, from 9.0.23 through 9.0.105.<br>The following versions were EOL at the time the CVE was created but are<br>known to be affected: 8.5.0 through 8.5.100 and 7.0.95 through 7.0.109. Other EOL versions may also be affected.<br><br>Users are recommended to upgrade to version 11.0.8, 10.1.42 or 9.0.106, which fix the issue. | | | | | |
| CVE-2018-3149 | High | 8.3 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe... | | | | | |
| CVE-2018-3149 | High | 8.3 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe... | | | | | |
| CVE-2018-3149 | High | 8.3 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe... | | | | | |
| CVE-2018-3149 | High | 8.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful at- | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| tacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe... | | | | | |
| CVE-2018-3169 | High | 8.3 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ... | | | | | |
| CVE-2018-3169 | High | 8.3 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ... | | | | | |
| CVE-2018-3169 | High | 8.3 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ... | | | | | |
| CVE-2018-3169 | High | 8.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ... | | | | | |
| CVE-2020-14583 | High | 8.3 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r... | | | | | |
| CVE-2020-14583 | High | 8.3 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r... | | | | | |
| CVE-2020-14583 | High | 8.3 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r... | | | | | |
| CVE-2020-14583 | High | 8.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r... | | | | | |
| CVE-2020-2803 | High | 8.3 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2803 | High | 8.3 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2803 | High | 8.3 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2803 | High | 8.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2805 | High | 8.3 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2805 | High | 8.3 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2805 | High | 8.3 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2020-2805 | High | 8.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul... | | | | | |
| CVE-2026-65182 | High | 8.2 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.25, 10.1.58, 9.0.121 |
| Improper Access Control, Incorrect Authorization vulnerability in Apache Tomcat leads to security constraint bypass if a constraint for a longer path is specified before a more restrictive constraint for a shorter sub-path. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.24, from 10.1.0-M1 through 10.1.57, from 9.0.0.M1 through 9.0.120, from 8.5.0 through 8.5.100, from 7.0.0 through 7.0.109.

Users are recommended to upgrade to version 11.0.25, 10.1.58, 9.0.121, which fixes the issue.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2018-20346 | High | 8.1 | sqlite-libs | 3.24.0-r0 | 3.25.3-r0 |

SQLite before 3.25.3, when the FTS3 extension is enabled, encounters an integer overflow (and resultant buffer overflow) for FTS3 queries that occur after crafted changes to FTS3 shadow tables, allowing remote attackers to execute arbitrary code by leveraging the ability to run arbitrary SQL statements (such as in certain WebSQL use cases), aka Magellan.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2019-2698 | High | 8.1 | openjdk8 | 8.181.13-r0 | 8.212.04-r0 |

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2019-2698 | High | 8.1 | openjdk8-jre | 8.181.13-r0 | 8.212.04-r0 |

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2019-2698 | High | 8.1 | openjdk8-jre-base | 8.181.13-r0 | 8.212.04-r0 |

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2019-2698 | High | 8.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.212.04-r0 |

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-2604 | High | 8.1 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-2604 | High | 8.1 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-2604 | High | 8.1 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-2604 | High | 8.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-22259 | High | 8.1 | org.springframework:spring-web | 5.3.13 | 6.1.5, 6.0.18, 5.3.33 |

Applications that use UriComponentsBuilder in Spring Framework to parse an externally provided URL (e.g. through a query parameter) AND perform validation checks on the host of the parsed URL may be vulnerable to a  open redirect https://cwe.mitre.org/data/definitions/601.html  attack or to a SSRF attack if the URL is used after passing validation checks.

This is the same as  CVE-2024-22243 https://spring.io/security/cve-2024-22243 , but with different input.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-22262 | High | 8.1 | org.springframework:spring-web | 5.3.13 | 5.3.34, 6.0.19, 6.1.6 |

Applications that use UriComponentsBuilder to parse an externally provided URL (e.g. through a query parameter) AND perform validation checks on the host of the parsed URL may be vulnerable to a  open redirect https://cwe.mitre.org/data/definitions/601.html  attack or to a SSRF attack if the URL is used after passing validation checks.

This is the same as  CVE-2024-22259 https://spring.io/security/cve-2024-22259  and  CVE-2024-22243 https://spring.io/security/cve-2024-22243 , but with different input.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-50379 | High | 8.1 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.2, 10.1.34, 9.0.98 |

Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability during JSP compilation in Apache Tomcat permits an RCE on case insensitive file systems when the default servlet is enabled for write (non-default configuration).

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.1, from 10.1.0-M1 through 10.1.33, from 9.0.0.M1 through 9.0.97.

The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.2, 10.1.34 or 9.0.98, which ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2024-56337 | High | 8.1 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.2, 10.1.34, 9.0.98 |

Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.1, from 10.1.0-M1 through 10.1.33, from 9.0.0.M1 through 9.0.97.
The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions
may also be affected.

The mitigation for CVE-2024-50379 was incomplete.

Users running Tomcat on a case insensitive file system with the default servlet write enabled (readonly initialisation
parameter set to the non-default value of false) m...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2026-54512 | High | 8.1 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.8, 3.1.4, 2.21.4 |

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.10.0 until 2.18.8, 2.21.4, and 3.1.4, jackson-databind's PolymorphicTypeValidator (PTV) is the primary safety mechanism guarding polymorphic deserialization. When polymorphic typing is enabled and a type identifier contains generic parameters (i.e. the type ID string contains <), DatabindContext._resolveAndValidateGeneric() validates only the raw container class name (the substring before <) against the configured PTV. If the container type is approved, the method parses t...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2026-54513 | High | 8.1 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.8, 2.21.4, 3.1.4 |

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.10.0 until 2.18.8, 2.21.4, and 3.1.4, BasicPolymorphicTypeValidator.Builder.allowIfSubTypeIsArray() allowlists any array type based only on

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| clazz.isArray(), without validating the array's component (element) type against the configured allowlist. A PTV built with allowIfSubTypeIsArray() plus an explicit concrete-type allowlist therefore still permits EvilType[] even though EvilType is not allowlisted. When Jackson deserializes the elements and no per-element type IDs are p... | | | | | |
| CVE-2019-2201 | High | 7.8 | libjpeg-turbo | 1.5.3-r3 | 1.5.3-r6 |
| In generate_jsimd_ycc_rgb_convert_neon of jsimd_arm64_neon.S, there is a possible out of bounds write due to a missing bounds check. This could lead to remote code execution in an unprivileged process with no additional execution privileges needed. User interaction is needed for exploitation.Product: AndroidVersions: Android-8.0 Android-8.1 Android-9 Android-10Android ID: A-120551338 | | | | | |
| CVE-2019-19244 | High | 7.5 | sqlite-libs | 3.24.0-r0 | 3.25.3-r3 |
| sqlite3Select in select.c in SQLite 3.30.1 allows a crash if a sub-select uses both DISTINCT and window functions, and also has certain ORDER BY usage. | | | | | |
| CVE-2019-2602 | High | 7.5 | openjdk8 | 8.181.13-r0 | 8.212.04-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t... | | | | | |
| CVE-2019-2602 | High | 7.5 | openjdk8-jre | 8.181.13-r0 | 8.212.04-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t... | | | | | |
| CVE-2019-2602 | High | 7.5 | openjdk8-jre-base | 8.181.13-r0 | 8.212.04-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t... | | | | | |
| CVE-2019-2602 | High | 7.5 | openjdk8-jre-lib | 8.181.13-r0 | 8.212.04-r0 |
| Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t... | | | | | |
| CVE-2020-11655 | High | 7.5 | sqlite-libs | 3.24.0-r0 | 3.25.0-r4 |
| SQLite through 3.31.1 allows attackers to cause a denial of service (segmentation fault) via a malformed window-function query because the AggInfo object's initialization is mishandled. | | | | | |
| CVE-2020-36518 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.13.2.1, 2.12.6.1 |
| jackson-databind before 2.13.0 allows a Java StackOverflow exception and denial of service via a large depth of nested objects. | | | | | |
| CVE-2021-46877 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.12.6, 2.13.1 |
| jackson-databind 2.10.x through 2.12.x before 2.12.6 and 2.13.x before 2.13.1 allows attackers to cause a denial of service (2 GB transient heap usage per read) in uncommon situations involving JsonNode JDK serialization. | | | | | |
| CVE-2022-25857 | High | 7.5 | org.yaml:snakeyaml | 1.29 | 1.31 |
| The package org.yaml:snakeyaml from 0 and before 1.31 are vulnerable to Denial of Service (DoS) due missing to nested depth limitation for collections. | | | | | |
| CVE-2022-42003 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.12.7.1, 2.13.4.2 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| In FasterXML jackson-databind before versions 2.13.4.1 and 2.12.17.1, resource exhaustion can occur because of a lack of a check in primitive value deserializers to avoid deep wrapper array nesting, when the UNWRAP_SINGLE_VALUE_ARRAYS feature is enabled. | | | | | |
| CVE-2022-42004 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.12.7.1, 2.13.4 |
| In FasterXML jackson-databind before 2.13.4, resource exhaustion can occur because of a lack of a check in BeanDeserializer._deserializeFromArray to prevent use of deeply nested arrays. An application is vulnerable only with certain customized choices for deserialization. | | | | | |
| CVE-2022-42252 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 8.5.83, 9.0.68, 10.0.27, 10.1.1 |
| If Apache Tomcat 8.5.0 to 8.5.82, 9.0.0-M1 to 9.0.67, 10.0.0-M1 to 10.0.26 or 10.1.0-M1 to 10.1.0 was configured to ignore invalid HTTP headers via setting rejectIllegalHeader to false (the default for 8.5.x only), Tomcat did not reject a request containing an invalid Content-Length header making a request smuggling attack possible if Tomcat was located behind a reverse proxy that also failed to reject the request with the invalid header. | | | | | |
| CVE-2022-45143 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 8.5.84, 9.0.69, 10.1.2 |
| The JsonErrorReportValve in Apache Tomcat 8.5.83, 9.0.40 to 9.0.68 and 10.1.0-M1 to 10.1.1 did not escape the type, message or description values. In some circumstances these are constructed from user provided data and it was therefore possible for users to supply values that invalidated or manipulated the JSON output. | | | | | |
| CVE-2023-20860 | High | 7.5 | org.springframework:spring-webmvc | 5.3.13 | 6.0.7, 5.3.26 |
| Spring Framework running version 6.0.0 - 6.0.6 or 5.3.0 - 5.3.25 using "**" as a pattern in Spring Security configuration with the mvcRequestMatcher creates a mismatch in pattern matching between Spring Security and Spring MVC, and the potential for a security bypass. | | | | | |
| CVE-2023-20883 | High | 7.5 | org.springframework.boot:spring-boot-autoconfigure | 2.6.1 | 3.0.7, 2.7.12, 2.6.15, 2.5.15 |
| In Spring Boot versions 3.0.0 - 3.0.6, 2.7.0 - 2.7.11, 2.6.0 - 2.6.14, 2.5.0 - 2.5.14 and older unsupported versions, there is potential for a denial-of-service (DoS) attack if Spring MVC is used together with a reverse proxy cache. | | | | | |
| CVE-2023-24998 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 10.1.5, 11.0.0-M5, 8.5.88, 9.0.71 |
| Apache Commons FileUpload before 1.5 does not limit the number of request parts to be processed resulting in the possibility of an attacker triggering a DoS with a malicious upload or series of uploads.<br><br>Note that, like all of the file upload limits, the new configuration option (FileUploadBase#setFileCountMax) is not enabled by default and must be explicitly configured. | | | | | |
| CVE-2023-44487 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94 |
| The HTTP/2 protocol allows a denial of service (server resource consumption) because request cancellation can reset many streams quickly, as exploited in the wild in August through October 2023. | | | | | |
| CVE-2023-46589 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.0-M11, 10.1.16, 9.0.83, 8.5.96 |
| Improper Input Validation vulnerability in Apache Tomcat.Tomcat from 11.0.0-M1 through 11.0.0-M10, from 10.1.0-M1 through 10.1.15, from 9.0.0-M1 through 9.0.82 and from 8.5.0 through 8.5.95 did not correctly parse HTTP trailer headers. A trailer header that exceeded the header size limit could cause Tomcat to treat a single request as multiple requests leading to the possibility of request smuggling when behind a reverse proxy. | | | | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| | | | Older, EOL versions may also be affected.<br><br>Users are recommended to upgrade to version 11.0.0-M11 onwards, 10.1.16 onwards, 9.0.83 onwards or 8.5.96 onwards, which... | | |
| CVE-2024-23672 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-websocket | 9.0.55 | 11.0.0-M17, 10.1.19, 9.0.86, 8.5.99 |
| | | | Denial of Service via incomplete cleanup vulnerability in Apache Tomcat. It was possible for WebSocket clients to keep WebSocket connections open leading to increased resource consumption.This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M16, from 10.1.0-M1 through 10.1.18, from 9.0.0-M1 through 9.0.85, from 8.5.0 through 8.5.98.<br><br>Older, EOL versions may also be affected.<br><br>Users are recommended to upgrade to version 11.0.0-M17, 10.1.19, 9.0.86 or 8.5.99 which fix the issue. | | |
| CVE-2024-24549 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 8.5.99, 9.0.86, 10.1.19, 11.0.0-M17 |
| | | | Denial of Service due to improper input validation vulnerability for HTTP/2 requests in Apache Tomcat. When processing an HTTP/2 request, if the request exceeded any of the configured limits for headers, the associated HTTP/2 stream was not reset until after all of the headers had been processed.This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M16, from 10.1.0-M1 through 10.1.18, from 9.0.0-M1 through 9.0.85, from 8.5.0 through 8.5.98. Other, older, EOL versions may also be affected.<br><br>Users are recommended to upgrade to version 11.0.0-M17, 10.1.19, 9.0.86 or 8.5.99 which fix the... | | |
| CVE-2024-34750 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.0-M21, 10.1.25, 9.0.90 |
| | | | Improper Handling of Exceptional Conditions, Uncontrolled Resource Consumption vulnerability in Apache Tomcat. When processing an HTTP/2 stream, Tomcat did not handle some cases of excessive HTTP headers correctly. This led to a miscounting of active HTTP/2 streams which in turn led to the use of an incorrect infinite timeout which allowed connections to remain open which should have been closed.<br><br>This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M20, from 10.1.0-M1 through 10.1.24, from 9.0.0-M1 through 9.0.89.<br><br>The following versions were EOL at the time the CVE was created but... | | |
| CVE-2024-38286 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.0-M21, 10.1.25, 9.0.90 |
| | | | Allocation of Resources Without Limits or Throttling vulnerability in Apache Tomcat.<br><br>This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M20, from 10.1.0-M1 through 10.1.24, from 9.0.13 through 9.0.89.<br><br>The following versions were EOL at the time the CVE was created but are<br>known to be affected: 8.5.35 through 8.5.100 and 7.0.92 through 7.0.109. Other EOL versions may also be affected.<br><br>Users are recommended to upgrade to version 11.0.0-M21, 10.1.25, or 9.0.90, which fixes the issue. | | |
| | | | Apache Tomcat, under certain configurations on any platform, allows an attacker to cause an ... | | |
| CVE-2024-38816 | High | 7.5 | org.springframework:spring-webmvc | 5.3.13 | 6.1.13 |
| | | | Applications serving static resources through the functional web frameworks WebMvc.fn or WebFlux.fn are vulnerable to path traversal attacks. An attacker can craft malicious HTTP requests and obtain any file on the file system that is also accessible to the process in which the Spring application is running.<br><br>Specifically, an application is vulnerable when both of the following are true: | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| | | | * the web application uses RouterFunctions to serve static resources<br>* resource handling is explicitly configured with a FileSystemResource location<br><br>However, malicious requests are blocked and rejecte... | | |
| CVE-2024-38819 | High | 7.5 | org.springframework:spring-webmvc | 5.3.13 | 6.1.14 |
| | | | Applications serving static resources through the functional web frameworks WebMvc.fn or WebFlux.fn are vulnerable to path traversal attacks. An attacker can craft malicious HTTP requests and obtain any file on the file system that is also accessible to the process in which the Spring application is running. | | |
| CVE-2025-41249 | High | 7.5 | org.springframework:spring-core | 5.3.13 | 6.2.11 |
| | | | The Spring Framework annotation detection mechanism may not correctly resolve annotations on methods within type hierarchies with a parameterized super type with unbounded generics. This can be an issue if such annotations are used for authorization decisions.<br><br>Your application may be affected by this if you are using Spring Security's @EnableMethodSecurity feature.<br><br>You are not affected by this if you are not using @EnableMethodSecurity or if you do not use security annotations on methods in generic superclasses or generic interfaces.<br><br>This CVE is published in conjunction with CVE-2025-41248... | | |
| CVE-2025-48989 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.10, 10.1.44, 9.0.108 |
| | | | Improper Resource Shutdown or Release vulnerability in Apache Tomcat made Tomcat vulnerable to the made you reset attack.<br><br>This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.9, from 10.1.0-M1 through 10.1.43 and from 9.0.0.M1 through 9.0.107. Older, EOL versions may also be affected.<br><br>Users are recommended to upgrade to one of versions 11.0.10, 10.1.44 or 9.0.108 which fix the issue. | | |
| CVE-2025-52999 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.13.0 | 2.15.0 |
| | | | jackson-core contains core low-level incremental ("streaming") parser and generator abstractions used by Jackson Data Processor. In versions prior to 2.15.0, if a user parses an input file and it has deeply nested data, Jackson could end up throwing a StackoverflowError if the depth is particularly large. jackson-core 2.15.0 contains a configurable limit for how deep Jackson will traverse in an input document, defaulting to an allowable depth of 1000. jackson-core will throw a StreamConstraintsException if the limit is reached. jackson-databind also benefits from this change because it uses ja... | | |
| CVE-2025-55752 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.11, 10.1.45, 9.0.109 |
| | | | Relative Path Traversal vulnerability in Apache Tomcat.<br><br>The fix for bug 60013 introduced a regression where the rewritten URL was normalized before it was decoded. This introduced the possibility that, for rewrite rules that rewrite query parameters to the URL, an attacker could manipulate the request URI to bypass security constraints including the protection for /WEB-INF/ and /META-INF/. If PUT requests were also enabled then malicious files could be uploaded leading to remote code execution. PUT requests are normally limited to trusted users and it is considered unl... | | |
| CVE-2026-34479 | High | 7.5 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.25.4 |
| | | | The Log4j1XmlLayout from the Apache Log4j 1-to-Log4j 2 bridge fails to escape characters forbidden by the XML 1.0 standard, producing malformed XML output. Conforming XML parsers are required to reject documents containing such characters with a fatal error, which may cause downstream log processing systems to drop or fail to index affected records.<br><br>Two groups of users are affected:<br><br>* Those using Log4j1XmlLayout directly in a Log4j Core 2 configuration file.<br>* Those using the Log4j 1 configuration compatibility layer with org.apache.log4j.xml.XMLLayout specified as the layout class.<br><br>... | | |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-34480 | High | 7.5 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.25.4 |

Apache Log4j Core's XmlLayout https://logging.apache.org/log4j/2.x/manual/layouts.html#XmlLayout , in versions up to and including 2.25.3, fails to sanitize characters forbidden by the XML 1.0 specification https://www.w3.org/TR/xml/#charsets producing invalid XML output whenever a log message or MDC value contains such characters.

The impact depends on the StAX implementation in use:

* JRE built-in StAX: Forbidden characters are silently written to the output, producing malformed XML. Conforming parsers must reject such documents with a fatal error, which may cause downstream log-proc...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-41284 | High | 7.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |

Allocation of Resources Without Limits or Throttling vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.21, from 10.1.0-M1 through 10.1.54, from 9.0.0.M1 through 9.0.117. Older, unsupported versions may also be affected.

Users are recommended to upgrade to version [FIXED_VERSION], which fixes the issue.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-41848 | High | 7.5 | org.springframework:spring-core | 5.3.13 | 7.0.8, 6.2.19 |

Applications may be vulnerable to a Regular Expression Denial of Service (ReDoS) attack if an attacker is able to provide a pattern which is then directly or indirectly supplied to one of the following methods in AntPathMatcher: match(String pattern, String path), matchStart(String pattern, String path), extractUriTemplateVariables(String pattern, String path).

Affected versions:
Spring Framework 7.0.0 through 7.0.7; 6.2.0 through 6.2.18; 6.1.0 through 6.1.27; 5.3.0 through 5.3.48.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-41851 | High | 7.5 | org.springframework:spring-expression | 5.3.13 | 7.0.8, 6.2.19 |

Applications which accept user-supplied Spring Expression Language (SpEL) expressions may be vulnerable to a Denial of Service (DoS) attack if the evaluation of a SpEL expression triggers unbounded cache growth.

Affected versions:
Spring Framework 7.0.0 through 7.0.7; 6.2.0 through 6.2.18; 6.1.0 through 6.1.27; 5.3.0 through 5.3.48.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-50193 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.14.0 |

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.13.0 until 2.14.0, a potential Denial-of-Service exists when attacker sends deeply nested JSON if (and only if) the service reads deeply nested (1000s of levels) JSON as JsonNode (ObjectMapper.readTree()) and writes out same (or modifided) node using JsonNode.toString(). This can consume significant amount of resources with concurrent relatively small requests (1000 nested arrays is 2kB). This vulnerability is fixed in 2.14.0.

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-68494 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.13.0 | 2.18.8, 2.21.4 |

The fix released in jackson-core 2.18.6 and 2.21.1 for CVE-2026-18401 (GHSA-72hv-8253-57qq, number length constraint bypass in the non-blocking parser) is incomplete. This record covers the remaining bypass.

The earlier fix wired validateIntegerLength() into a new _setIntLength() helper and invoked it wherever the integer portion of a number is decided: a terminator byte arrives, a '.' or 'e'/'E' is seen, or input ends inside a fully buffered value. It was not invoked on the attacker-relevant path where the parser runs out of input while still inside the MINOR_NUMBER_INTEGER_DIGITS minor stat...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-89425 | High | 7.5 | com.fasterxml.jackson.core:jackson-core | 2.13.0 | 2.21.7, 2.22.3, 2.18.11 |

UTF8DataInputJsonParser._reportInvalidToken() in FasterXML jackson-core builds the offending-token text for its error message by appending Java identifier characters to a StringBuilder in a loop that has no upper bound. Unlike the three sibling parser implementations, including UTF8StreamJsonParser, it never consults ErrorReportConfiguration.getMaxErrorTokenLength() (default 256). A malformed token supplied to a parser created through JsonFactory.createParser(DataInput) is therefore accumulated in full. No StreamReadConstraints setting mitigates this: maxDocumentLength cannot be applied to Dat...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-91776 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.11, 2.21.7, 2.22.3 |

TypeDeserializerBase._findDeserializer() in FasterXML jackson-databind caches the resolved deserializer under the raw, attacker-supplied type ID. When name-based polymorphism is configured with a fallback, for example @JsonTypeInfo(use = Id.NAME, defaultImpl = ...), every distinct unrecognized type ID resolves to the same fallback deserializer but is retained as its own key in the _deserializers map. That map has no configurable bound and lives for the lifetime of the type deserializer, so an attacker who can repeatedly supply fresh unknown type IDs causes monotonic memory retention across req...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2026-91777 | High | 7.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.21.7, 2.18.11, 2.22.3 |

Forward-reference completion for @JsonIdentityInfo object IDs in FasterXML jackson-databind performs a linear scan of the pending-reference accumulator for every resolved ID. The affected paths are CollectionDeserializer.CollectionReferringAccumulator.resolveForwardReference() and the equivalent implementation in MapDeserializer. When a document first creates N unresolved object-ID references in an identity-enabled collection or map and then defines those same IDs in reverse order, completion performs on the order of N * (N + 1) / 2 identity comparisons, so a shallow document whose size grows ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-14593 | High | 7.4 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-14593 | High | 7.4 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-14593 | High | 7.4 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2020-14593 | High | 7.4 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2025-22235 | High | 7.3 | org.springframework.boot:spring-boot | 2.6.1 | 3.3.11, 3.4.5 |

EndpointRequest.to() creates a matcher for null/** if the actuator endpoint, for which the EndpointRequest has been created, is disabled or not exposed.

Your application may be affected by this if all the following conditions are met:

* You use Spring Security
* EndpointRequest.to() has been used in a Spring Security chain configuration
* The endpoint which EndpointRequest references is disabled or not exposed via web
* Your application handles requests to /null and this path needs protection

You are not affected if any of the following is true:

* You don't use Spring Secur...

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-41293 | High | 7.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |

Improper Input Validation vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.21, from 10.1.0-M1 through 10.1.54, from 9.0.0.M1 through 9.0.117, from 10.0.0-M1 through 10.0.27.
Older, end of support versions may also be affected.

Users are recommended to upgrade to version [FIXED_VERSION], which fixes the issue.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2026-55957 | High | 7.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.5, 10.1.37, 9.0.101 |

Missing Critical Step in Authentication vulnerability in Apache Tomcat when the JNDIRealm was configured to authenticate binds using GSS-API allowed attackers to authenticate without provided the correct password.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.4, from 10.1.0-M1 through 10.1.36, from 9.0.0.M1 through 9.0.100, from 8.5.0 through 8.5.100, from 7.0.0 through 7.0.109.

Users are recommended to upgrade to version 11.0.5, 10.1.37 or 9.0.101, which fixes the issue.

| | | | | | |
|---|---|---|---|---|---|
| CVE-2026-40973 | High | 7.0 | org.springframework.boot:spring-boot | 2.6.1 | 4.0.6, 3.5.14 |

A local attacker on the same host as the application may be able to take control of the directory used by `ApplicationTemp`. When `server.servlet.session.persistent` is set to `true` and the attack persists across application restarts, this may allow the attacker to read session information and hijack authenticated users or deploy a gadget chain and execute code as the application's user.

Affected: Spring Boot 4.0.0–4.0.5 (fix 4.0.6), 3.5.0–3.5.13 (fix 3.5.14), 3.4.0–3.4.15 (fix 3.4.16), 3.3.0–3.3.18 (fix 3.3.19), 2.7.0–2.7.32 (fix 2.7.33); predictable temp directory / `ApplicationTemp` owner...

| | | | | | |
|---|---|---|---|---|---|
| CVE-2019-2949 | Medium | 6.8 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2949 | Medium | 6.8 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2949 | Medium | 6.8 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2949 | Medium | 6.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2989 | Medium | 6.8 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2989 | Medium | 6.8 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2989 | Medium | 6.8 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2989 | Medium | 6.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2020-2601 | Medium | 6.8 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2601 | Medium | 6.8 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2601 | Medium | 6.8 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2601 | Medium | 6.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2019-5094 | Medium | 6.7 | libcom_err | 1.44.2-r0 | 1.44.2-r1 |
| CVE-2019-5188 | Medium | 6.7 | libcom_err | 1.44.2-r0 | 1.44.2-r2 |
| CVE-2021-44832 | Medium | 6.6 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.3.2, 2.12.4, 2.17.1 |
| CVE-2018-11212 | Medium | 6.5 | openjdk8 | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2018-11212 | Medium | 6.5 | openjdk8-jre | 8.181.13-r0 | 8.201.08-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-11212 | Medium | 6.5 | openjdk8-jre-base | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2018-11212 | Medium | 6.5 | openjdk8-jre-lib | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2018-13785 | Medium | 6.5 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-13785 | Medium | 6.5 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-13785 | Medium | 6.5 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-13785 | Medium | 6.5 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-14048 | Medium | 6.5 | libpng | 1.6.34-r1 | 1.6.37-r0 |
| CVE-2018-14498 | Medium | 6.5 | libjpeg-turbo | 1.5.3-r3 | 1.5.3-r5 |
| CVE-2019-16168 | Medium | 6.5 | sqlite-libs | 3.24.0-r0 | 3.25.3-r2 |
| CVE-2022-22950 | Medium | 6.5 | org.springframework:spring-expression | 5.3.13 | 5.3.17, 5.2.20.RELEASE |
| CVE-2022-38749 | Medium | 6.5 | org.yaml:snakeyaml | 1.29 | 1.31 |
| CVE-2022-38751 | Medium | 6.5 | org.yaml:snakeyaml | 1.29 | 1.31 |
| CVE-2022-38752 | Medium | 6.5 | org.yaml:snakeyaml | 1.29 | 1.32 |
| CVE-2022-41854 | Medium | 6.5 | org.yaml:snakeyaml | 1.29 | 1.32 |
| CVE-2023-20861 | Medium | 6.5 | org.springframework:spring-expression | 5.3.13 | 6.0.7, 5.3.26, 5.2.23.RELEASE |
| CVE-2023-20863 | Medium | 6.5 | org.springframework:spring-expression | 5.3.13 | 6.0.8, 5.3.27, 5.2.24.RELEASE |
| CVE-2025-46701 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.105, 10.1.41, 11.0.7 |
| CVE-2025-55668 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.8, 10.1.42, 9.0.106 |
| CVE-2026-22737 | Medium | 6.5 | org.springframework:spring-webmvc | 5.3.13 | 7.0.6, 6.2.17 |
| CVE-2026-34487 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.117, 10.1.54, 11.0.21 |
| CVE-2026-42498 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |
| CVE-2026-43512 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |
| CVE-2026-53404 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.23, 10.1.56, 9.0.119 |
| CVE-2026-55956 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.23, 10.1.56, 9.0.119 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-59889 | Medium | 6.5 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.21.5, 2.18.9, 2.22.1 |
| CVE-2026-68525 | Medium | 6.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.25, 10.1.58, 9.0.121 |
| CVE-2023-41080 | Medium | 6.1 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 8.5.93, 9.0.80, 10.1.13, 11.0.0-M11 |
| CVE-2026-41844 | Medium | 6.1 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41845 | Medium | 6.1 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41846 | Medium | 6.1 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2019-19242 | Medium | 5.9 | sqlite-libs | 3.24.0-r0 | 3.25.3-r3 |
| CVE-2019-2684 | Medium | 5.9 | openjdk8 | 8.181.13-r0 | 8.212.04-r0 |
| CVE-2019-2684 | Medium | 5.9 | openjdk8-jre | 8.181.13-r0 | 8.212.04-r0 |
| CVE-2019-2684 | Medium | 5.9 | openjdk8-jre-base | 8.181.13-r0 | 8.212.04-r0 |
| CVE-2019-2684 | Medium | 5.9 | openjdk8-jre-lib | 8.181.13-r0 | 8.212.04-r0 |
| CVE-2019-2958 | Medium | 5.9 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2958 | Medium | 5.9 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2958 | Medium | 5.9 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2958 | Medium | 5.9 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2021-45105 | Medium | 5.9 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.12.3, 2.17.0, 2.3.1 |
| CVE-2024-38808 | Medium | 5.9 | org.springframework:spring-expression | 5.3.13 | 5.3.39 |
| CVE-2025-41242 | Medium | 5.9 | org.springframework:spring-webmvc | 5.3.13 | 6.2.10 |
| CVE-2026-22741 | Medium | 5.9 | org.springframework:spring-webmvc | 5.3.13 | 7.0.7, 6.2.18 |
| CVE-2026-34477 | Medium | 5.9 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.25.4 |
| CVE-2026-41841 | Medium | 5.9 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41842 | Medium | 5.9 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41843 | Medium | 5.9 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41849 | Medium | 5.9 | org.springframework:spring-expression | 5.3.13 | — |
| CVE-2026-41850 | Medium | 5.9 | org.springframework:spring-expression | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-49844 | Medium | 5.9 | org.apache.logging.log4j:log4j-api | 2.14.1 | 2.25.5, 2.26.1 |
| CVE-2018-3180 | Medium | 5.6 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2018-3180 | Medium | 5.6 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3180 | Medium | 5.6 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3180 | Medium | 5.6 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2026-83557 | Medium | 5.6 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.10, 2.21.6, 2.22.2 |
| CVE-2018-1000654 | Medium | 5.5 | libtasn1 | 4.13-r0 | 4.14-r0 |
| CVE-2018-16435 | Medium | 5.5 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-16435 | Medium | 5.5 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-16435 | Medium | 5.5 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-16435 | Medium | 5.5 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2022-38750 | Medium | 5.5 | org.yaml:snakeyaml | 1.29 | 1.31 |
| CVE-2026-34483 | Medium | 5.4 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.116, 10.1.54, 11.0.21 |
| CVE-2026-43515 | Medium | 5.4 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |
| CVE-2018-20217 | Medium | 5.3 | krb5-libs | 1.15.3-r0 | 1.15.4-r0 |
| CVE-2018-3214 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3214 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3214 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3214 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2019-2762 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2762 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2762 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2762 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2769 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2769 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2769 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2769 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-7317 | Medium | 5.3 | libpng | 1.6.34-r1 | 1.6.37-r0 |
| CVE-2019-7317 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-7317 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-7317 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-7317 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2020-14621 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-14621 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14621 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14621 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14803 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14803 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14803 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14803 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-2781 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2781 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2781 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2781 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2830 | Medium | 5.3 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2830 | Medium | 5.3 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2830 | Medium | 5.3 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2830 | Medium | 5.3 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2022-22968 | Medium | 5.3 | org.springframework:spring-context | 5.3.13 | 5.3.19, 5.2.21.RELEASE |
| CVE-2022-22970 | Medium | 5.3 | org.springframework:spring-beans | 5.3.13 | 5.2.22.RELEASE, 5.3.20 |
| CVE-2023-42795 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 10.1.14, 9.0.81, 8.5.94, 11.0.0-M12 |
| CVE-2023-45648 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94 |
| CVE-2024-38809 | Medium | 5.3 | org.springframework:spring-web | 5.3.13 | 5.3.38, 6.0.23, 6.1.12 |
| CVE-2024-38820 | Medium | 5.3 | org.springframework:spring-context | 5.3.13 | 6.1.14 |
| CVE-2024-38820 | Medium | 5.3 | org.springframework:spring-web | 5.3.13 | 6.1.14 |
| CVE-2024-38828 | Medium | 5.3 | org.springframework:spring-webmvc | 5.3.13 | 5.3.42 |
| CVE-2025-48988 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.8, 10.1.42, 9.0.106 |
| CVE-2025-52434 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.107 |
| CVE-2025-53506 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.107, 10.1.43, 11.0.9 |
| CVE-2025-61795 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.12, 10.1.47, 9.0.110 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-19032 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.10, 2.21.6, 2.22.2 |
| CVE-2026-22745 | Medium | 5.3 | org.springframework:spring-webmvc | 5.3.13 | 7.0.7, 6.2.18 |
| CVE-2026-41852 | Medium | 5.3 | org.springframework:spring-expression | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-41853 | Medium | 5.3 | org.springframework:spring-webmvc | 5.3.13 | 7.0.8, 6.2.19 |
| CVE-2026-43513 | Medium | 5.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |
| CVE-2026-54514 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.8, 2.21.4, 3.1.4 |
| CVE-2026-54515 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 3.1.4, 2.18.9, 2.21.5, 2.22.1 |
| CVE-2026-77310 | Medium | 5.3 | com.fasterxml.jackson.core:jackson-databind | 2.13.0 | 2.18.9, 2.21.5, 2.22.1 |
| CVE-2019-2745 | Medium | 5.1 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2745 | Medium | 5.1 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2745 | Medium | 5.1 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2745 | Medium | 5.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2816 | Medium | 4.8 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2816 | Medium | 4.8 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2816 | Medium | 4.8 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2816 | Medium | 4.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2975 | Medium | 4.8 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2975 | Medium | 4.8 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2975 | Medium | 4.8 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2975 | Medium | 4.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2020-14556 | Medium | 4.8 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14556 | Medium | 4.8 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14556 | Medium | 4.8 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14556 | Medium | 4.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-2593 | Medium | 4.8 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2593 | Medium | 4.8 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2593 | Medium | 4.8 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2593 | Medium | 4.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2800 | Medium | 4.8 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2800 | Medium | 4.8 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-2800 | Medium | 4.8 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2800 | Medium | 4.8 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2025-68161 | Medium | 4.8 | org.apache.logging.log4j:log4j-core | 2.14.1 | 2.25.3 |
| CVE-2026-65905 | Medium | 4.8 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.25, 10.1.58, 9.0.121 |
| CVE-2019-2999 | Medium | 4.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2999 | Medium | 4.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2999 | Medium | 4.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2999 | Medium | 4.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2021-22060 | Medium | 4.3 | org.springframework:spring-core | 5.3.13 | 5.3.14, 5.2.19 |
| CVE-2026-24880 | Medium | 4.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.116, 10.1.52, 11.0.20 |
| CVE-2026-25854 | Medium | 4.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.116, 10.1.53, 11.0.20 |
| CVE-2020-14792 | Medium | 4.2 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14792 | Medium | 4.2 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14792 | Medium | 4.2 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14792 | Medium | 4.2 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2019-2426 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2426 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2426 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2426 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2842 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2842 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2842 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2842 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2894 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2894 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2894 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2894 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2962 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2962 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2962 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2962 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2019-2964 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2964 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2964 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2964 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2973 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2973 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2973 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2973 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2978 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2978 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2978 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2978 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2981 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2981 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2981 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2981 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2983 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2983 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2983 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2983 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2987 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2987 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2987 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2987 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2988 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2988 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2988 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2988 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2992 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2992 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2992 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2992 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2020-14577 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14577 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14577 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-14577 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14578 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14578 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14578 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14578 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14579 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14579 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14579 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14579 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14581 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14581 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14581 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14581 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14779 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14779 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14779 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14779 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14781 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14781 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14781 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14781 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14782 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14782 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14782 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14782 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14797 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14797 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14797 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14797 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-2583 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2583 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2583 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2583 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2590 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2590 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-2590 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2590 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2654 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2654 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2654 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2654 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2659 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2659 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2659 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2659 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.242.08-r0 |
| CVE-2020-2754 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2754 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2754 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2754 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2755 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2755 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2755 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2755 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2756 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2756 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2756 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2756 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2757 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2757 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2757 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2757 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2773 | Low | 3.7 | openjdk8 | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2773 | Low | 3.7 | openjdk8-jre | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2773 | Low | 3.7 | openjdk8-jre-base | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2020-2773 | Low | 3.7 | openjdk8-jre-lib | 8.181.13-r0 | 8.252.09-r0 |
| CVE-2025-49125 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.8, 10.1.42, 9.0.106 |
| CVE-2025-52520 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.9, 10.1.43, 9.0.107 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-43514 | Low | 3.7 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 9.0.118, 10.1.55, 11.0.22 |
| CVE-2025-55754 | Low | 3.5 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.11, 10.1.45, 9.0.109 |
| CVE-2018-3136 | Low | 3.4 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3136 | Low | 3.4 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3136 | Low | 3.4 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3136 | Low | 3.4 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2019-2786 | Low | 3.4 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2786 | Low | 3.4 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2786 | Low | 3.4 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2786 | Low | 3.4 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2024-22243 | Low | 3.4 | org.springframework:spring-web | 5.3.13 | 6.1.4, 6.0.17, 5.3.32 |
| CVE-2018-3139 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3139 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3139 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2018-3139 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.191.12-r0 |
| CVE-2019-2422 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2422 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2422 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2422 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.201.08-r0 |
| CVE-2019-2766 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2766 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2766 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2766 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.222.10-r0 |
| CVE-2019-2933 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2933 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2933 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2933 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2945 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2945 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2945 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2019-2945 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.232.09-r0 |
| CVE-2020-14796 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2020-14796 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14796 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14796 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14798 | Low | 3.1 | openjdk8 | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14798 | Low | 3.1 | openjdk8-jre | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14798 | Low | 3.1 | openjdk8-jre-base | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2020-14798 | Low | 3.1 | openjdk8-jre-lib | 8.181.13-r0 | 8.272.10-r0 |
| CVE-2025-22233 | Low | 3.1 | org.springframework:spring-context | 5.3.13 | 6.2.7, 6.1.20 |
| CVE-2026-22735 | Low | 2.6 | org.springframework:spring-webmvc | 5.3.13 | 7.0.6, 6.2.17 |
| CVE-2026-55276 | Low | 2.3 | org.apache.tomcat.embed:tomcat-embed-core | 9.0.55 | 11.0.23, 10.1.56, 9.0.119 |

## alpine:3.22

Digest sha256:bfe7ceb9f09ec0566c48fb93356e45a47a00be5a1dd14fa5b909e7709c66b034
Platform linux/amd64
Operating System alpine 3.22.8
Size —
Created 2026-11-05T18:01:05Z
Scanned 2026-11-07T14:32:29Z
Vulnerabilities by Severity Critical 0 High 0 Medium 1 Low 0 Unrated 0

### Vulnerability Details

| Vulnerability ID | Severity | CVSS | Package | Installed Version | Fixed Version |
|---|---|---|---|---|---|
| CVE-2026-4738 | Medium | — | zlib | 1.3.2-r1 | 1.4-r0 |

label: MEDIUM

## busybox:1.37

Digest sha256:a7dbc319b1438115a207e11930dc4bb3e643dcb3ec0bdd694bb36cd8fad289ec
Platform linux/amd64
Operating System —
Size —
Created 2024-09-26T21:31:42Z
Scanned 2026-11-07T14:33:25Z
Vulnerabilities by Severity Critical 0 High 0 Medium 0 Low 0 Unrated 0

### Vulnerability Details

No vulnerabilities found.

# Appendix

## Methodology

| | |
|---|---|
| Scanner | Trivy (files) · Trivy |
| Vulnerability Database | — |
| Report Tool | judex 0.1.0 |

## Severity Rules

This tool determines severity from CVSS v3 scores rather than scanner labels. When v3 scores are unavailable, it falls back to v2, then to scanner labels with an annotation.

| | |
|---|---|
| Critical | ≥ 9.0 |
| High | 7.0 – 8.9 |
| Medium | 4.0 – 6.9 |
| Low | 0.1 – 3.9 |
| Unrated | – |

## CVSS Score Sources

| Source | Count |
|---|---|
| nvd | 687 |
| redhat | 129 |
| – | 10 |
| bitnami | 1 |
| ghsa | 1 |

This report covers images stored in registries and does not represent workloads running in clusters.

## Images Not Scanned or Failed

—

## Images Not Scanned in Over 30 Days

—

## Limitations

1. Recomputed severity may differ from the scanner's interface.
2. Scores for the same vulnerability may differ between scanners due to different data sources.
3. NeuVector fills in scores for some older vulnerabilities, which may affect severity classification.
4. Vulnerability coverage depends on the scanner and its database.
5. Scan scope covers registry images and does not represent running workloads.
6. Reports are generated independently and do not track changes between runs.

Generated by judex 0.1.0