範例科技股份有限公司

容器映像檔弱點掃描報告

範圍	demo
掃描來源	Trivy (files)
映像檔數量	4
掃描期間	2026-11-07T14:32:23Z – 2026-11-07T14:33:40Z
產生時間	2026-11-09

目錄

總覽 3
修補建議 5
弱點盤點 16
各映像檔明細 45
  nginx:1.21.0 45
  ghcr.io/christophetd/log4shell-vulnerable-app:latest 73
  alpine:3.22 97
  busybox:1.37 97
附錄 98

總覽

本報告涵蓋 4 個映像檔，共 461 個不重複弱點。

44	227	365	183
Critical	High	Medium	Low

Unrated 9



Critical 44 High 227 Medium 365 Low 183 Unrated 9

742

個弱點（90%）已有修補版本

2

個映像檔（共 4 個）含 Critical 或 High 等級弱點

優先處理的映像檔

映像檔	Critical	High	Medium	Low
nginx:1.21.0	27	142	193	23
ghcr.io/christophetd/log4shell-vulnerable-app:latest	17	85	171	160
alpine:3.22	0	0	1	0
busybox:1.37	0	0	0	0

優先處理的弱點

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2021-44228	Critical	10.0	org.apache.logging.log4j:log4j-core	2.15.0, 2.3.1, 2.12.2	1
CVE-2016-1000027	Critical	9.8	org.springframework:spring-web	6.0.0	1
CVE-2019-12900	Critical	9.8	libbz2	1.0.6-r7	1
CVE-2019-14697	Critical	9.8	musl, musl-utils	1.1.19-r11	1
CVE-2019-8457	Critical	9.8	libdb5.3, sqlite-libs	3.25.3-r1	2
CVE-2021-33574	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1
CVE-2021-3711	Critical	9.8	libssl1.1, openssl	1.1.1d-0+deb10u7	1
CVE-2022-1471	Critical	9.8	org.yaml:snakeyaml	2.0	1
CVE-2022-1664	Critical	9.8	dpkg	1.19.8	1
CVE-2022-22822	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
CVE-2022-22823	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
CVE-2022-22824	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
CVE-2022-22965	Critical	9.8	org.springframework:spring-beans, org.springframework:spring-webmvc	5.2.20.RELEASE, 5.3.18	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2022-23218	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1
CVE-2022-23219	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1

修補建議

優先更新下列套件至修補版本，以降低弱點風險。

libexpat1 → 2.2.6-2+deb10u2

可修補 Critical 4、High 6、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libc-bin → 2.28-10+deb10u2

可修補 Critical 4、High 4、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libc6 → 2.28-10+deb10u2

可修補 Critical 4、High 4、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libexpat1 → 2.2.6-2+deb10u3

可修補 Critical 3、High 1、Medium 1、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

openjdk8 → 8.191.12-r0

可修補 Critical 1、High 2、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

openjdk8-jre → 8.191.12-r0

可修補 Critical 1、High 2、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

openjdk8-jre-base → 8.191.12-r0

可修補 Critical 1、High 2、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

openjdk8-jre-lib → 8.191.12-r0

可修補 Critical 1、High 2、Medium 4、Low 2 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

libfreetype6 → 2.9.1-3+deb10u3

可修補 Critical 1、High 2、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libssl1.1 → 1.1.1d-0+deb10u7

可修補 Critical 1、High 1、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

openssl → 1.1.1d-0+deb10u7

可修補 Critical 1、High 1、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

curl → 7.64.0-4+deb10u4

可修補 Critical 1、High 0、Medium 2、Low 1 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libcurl4 → 7.64.0-4+deb10u4

可修補 Critical 1、High 0、Medium 2、Low 1 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

dpkg → 1.19.8

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libbz2 → 1.0.6-r7

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

libldap-2.4-2 → 2.4.47+dfsg-3+deb10u7

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libldap-common → 2.4.47+dfsg-3+deb10u7

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

libtasn1-6 → 4.13-3+deb10u1

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`nginx:1.21.0`

musl → 1.1.19-r11

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

musl-utils → 1.1.19-r11

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.apache.logging.log4j:log4j-core → 2.15.0, 2.3.1, 2.12.2

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.apache.logging.log4j:log4j-core → 2.16.0, 2.12.2, 2.3.1

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.apache.tomcat.embed:tomcat-embed-core → 11.0.15, 10.1.50, 9.0.113

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.apache.tomcat.embed:tomcat-embed-core → 11.0.3, 10.1.35, 9.0.99

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.springframework:spring-beans → 5.2.20.RELEASE, 5.3.18

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.springframework:spring-web → 6.0.0

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.springframework:spring-webmvc → 5.2.20.RELEASE, 5.3.18

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.springframework:spring-webmvc → 7.0.9

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

org.yaml:snakeyaml → 2.0

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

sqlite-libs → 3.25.3-r1

可修補 Critical 1、High 0、Medium 0、Low 0 個弱點。 影響 1 個映像檔。

`ghcr.io/christophetd/log4shell-vulnerable-app:latest`

其餘修補項目

另有 239 個修補項目列於下表。

套件	修補版本	Critical	High	Medium	Low	映像檔
zlib1g	1:1.2.11.dfsg-1+deb10u2	1	0	0	0	1
curl	7.64.0-4+deb10u3	0	4	4	2	1
libcurl4	7.64.0-4+deb10u3	0	4	4	2	1
libssl1.1	1.1.1n-0+deb10u4	0	3	2	0	1
openssl	1.1.1n-0+deb10u4	0	3	2	0	1
libssh2-1	1.8.0-2.1+deb10u1	0	3	0	0	1
libxpm4	1:3.5.12-1+deb10u1	0	3	0	0	1
openjdk8	8.272.10-r0	0	2	4	10	1
openjdk8-jre	8.272.10-r0	0	2	4	10	1
openjdk8-jre-base	8.272.10-r0	0	2	4	10	1
openjdk8-jre-lib	8.272.10-r0	0	2	4	10	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	0	2	4	1	1
openjdk8	8.252.09-r0	0	2	3	5	1
openjdk8-jre	8.252.09-r0	0	2	3	5	1
openjdk8-jre-base	8.252.09-r0	0	2	3	5	1
openjdk8-jre-lib	8.252.09-r0	0	2	3	5	1
openjdk8	8.212.04-r0	0	2	1	0	1
openjdk8-jre	8.212.04-r0	0	2	1	0	1
openjdk8-jre-base	8.212.04-r0	0	2	1	0	1
openjdk8-jre-lib	8.212.04-r0	0	2	1	0	1
org.apache.logging.log4j:log4j-core	2.25.4	0	2	1	0	1
libncursesw6	6.1+20181013-2+deb10u5	0	2	0	0	1
libnghttp2-14	1.36.0-2+deb10u2	0	2	0	0	1
libtinfo6	6.1+20181013-2+deb10u5	0	2	0	0	1
libxml2	2.9.4+dfsg1-7+deb10u5	0	2	0	0	1
libxslt1.1	1.1.32-2.2~deb10u2	0	2	0	0	1
ncurses-base	6.1+20181013-2+deb10u5	0	2	0	0	1
ncurses-bin	6.1+20181013-2+deb10u5	0	2	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M21, 10.1.25, 9.0.90	0	2	0	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
org.apache.tomcat.embed:tomcat-embed-core	11.0.2, 10.1.34, 9.0.98	0	2	0	0	1
libtiff5	4.1.0+git191117-2~deb10u5	0	1	18	0	1
libtiff5	4.1.0+git191117-2~deb10u7	0	1	11	0	1
libtiff5	4.1.0+git191117-2~deb10u4	0	1	8	0	1
curl	7.64.0-4+deb10u6	0	1	3	0	1
libc-bin	2.28-10+deb10u4	0	1	3	0	1
libc6	2.28-10+deb10u4	0	1	3	0	1
libcurl4	7.64.0-4+deb10u6	0	1	3	0	1
libssl1.1	1.1.1n-0+deb10u5	0	1	3	0	1
openssl	1.1.1n-0+deb10u5	0	1	3	0	1
org.yaml:snakeyaml	1.31	0	1	3	0	1
openjdk8	8.242.08-r0	0	1	2	4	1
openjdk8-jre	8.242.08-r0	0	1	2	4	1
openjdk8-jre-base	8.242.08-r0	0	1	2	4	1
openjdk8-jre-lib	8.242.08-r0	0	1	2	4	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.8, 10.1.42, 9.0.106	0	1	2	1	1
libgd3	2.2.5-5.2+deb10u1	0	1	2	0	1
libpng	1.6.37-r0	0	1	2	0	1
libx11-6	2:1.6.7-1+deb10u4	0	1	2	0	1
libx11-data	2:1.6.7-1+deb10u4	0	1	2	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.25, 10.1.58, 9.0.121	0	1	2	0	1
org.springframework:spring-expression	7.0.8, 6.2.19	0	1	2	0	1
com.fasterxml.jackson.core:jackson-databind	2.18.8, 2.21.4, 3.1.4	0	1	1	0	1
libgnutls30	3.6.7-4+deb10u9	0	1	1	0	1
libssl1.1	1.1.1d-0+deb10u8	0	1	1	0	1
libtiff5	4.1.0+git191117-2~deb10u9	0	1	1	0	1
openssl	1.1.1d-0+deb10u8	0	1	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M12, 10.1.14, 9.0.81, 8.5.94	0	1	1	0	1
sqlite-libs	3.25.3-r3	0	1	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.11, 10.1.45, 9.0.109	0	1	0	1	1
com.fasterxml.jackson.core:jackson-core	2.15.0	0	1	0	0	1
com.fasterxml.jackson.core:jackson-core	2.18.8, 2.21.4	0	1	0	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
com.fasterxml.jackson.core: jackson-core	2.21.7, 2.22.3, 2.18.11	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.12.6, 2.13.1	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.12.7.1, 2.13.4	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.12.7.1, 2.13.4.2	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.13.2.1, 2.12.6.1	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.14.0	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.18.11, 2.21.7, 2.22.3	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.18.8, 3.1.4, 2.21.4	0	1	0	0	1
com.fasterxml.jackson.core: jackson-databind	2.21.7, 2.18.11, 2.22.3	0	1	0	0	1
curl	7.64.0-4+deb10u9	0	1	0	0	1
gzip	1.9-3+deb10u1	0	1	0	0	1
libc-bin	2.28-10+deb10u3	0	1	0	0	1
libc6	2.28-10+deb10u3	0	1	0	0	1
libcurl4	7.64.0-4+deb10u9	0	1	0	0	1
libexpat1	2.2.6-2+deb10u5	0	1	0	0	1
libexpat1	2.2.6-2+deb10u6	0	1	0	0	1
libexpat1	2.2.6-2+deb10u7	0	1	0	0	1
libgmp10	2:6.1.2+dfsg-4+deb10u1	0	1	0	0	1
libgnutls30	3.6.7-4+deb10u10	0	1	0	0	1
libgnutls30	3.6.7-4+deb10u12	0	1	0	0	1
libgssapi-krb5-2	1.17-3+deb10u2	0	1	0	0	1
libgssapi-krb5-2	1.17-3+deb10u5	0	1	0	0	1
libjpeg-turbo	1.5.3-r6	0	1	0	0	1
libk5crypto3	1.17-3+deb10u2	0	1	0	0	1
libk5crypto3	1.17-3+deb10u5	0	1	0	0	1
libkrb5-3	1.17-3+deb10u2	0	1	0	0	1
libkrb5-3	1.17-3+deb10u5	0	1	0	0	1
libkrb5support0	1.17-3+deb10u2	0	1	0	0	1
libkrb5support0	1.17-3+deb10u5	0	1	0	0	1
liblzma5	5.2.4-1+deb10u1	0	1	0	0	1
libncursesw6	6.1+20181013-2+deb10u3	0	1	0	0	1
libsasl2-2	2.1.27+dfsg-1+deb10u2	0	1	0	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
libsasl2-modules-db	2.1.27+dfsg-1+deb10u2	0	1	0	0	1
libssl1.1	1.1.1n-0+deb10u2	0	1	0	0	1
libssl1.1	1.1.1n-0+deb10u3	0	1	0	0	1
libsystemd0	241-7~deb10u9	0	1	0	0	1
libtinfo6	6.1+20181013-2+deb10u3	0	1	0	0	1
libudev1	241-7~deb10u9	0	1	0	0	1
libwebp6	0.6.1-2+deb10u2	0	1	0	0	1
libwebp6	0.6.1-2+deb10u3	0	1	0	0	1
libx11-6	2:1.6.7-1+deb10u3	0	1	0	0	1
libx11-data	2:1.6.7-1+deb10u3	0	1	0	0	1
libxml2	2.9.4+dfsg1-7+deb10u3	0	1	0	0	1
ncurses-base	6.1+20181013-2+deb10u3	0	1	0	0	1
ncurses-bin	6.1+20181013-2+deb10u3	0	1	0	0	1
openssl	1.1.1n-0+deb10u2	0	1	0	0	1
openssl	1.1.1n-0+deb10u3	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	10.1.5, 11.0.0-M5, 8.5.88, 9.0.71	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M11, 10.1.16, 9.0.83, 8.5.96	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.10, 10.1.44, 9.0.108	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.5, 10.1.37, 9.0.101	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	8.5.83, 9.0.68, 10.0.27, 10.1.1	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	8.5.84, 9.0.69, 10.1.2	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-core	8.5.99, 9.0.86, 10.1.19, 11.0.0-M17	0	1	0	0	1
org.apache.tomcat.embed:tomcat-embed-websocket	11.0.0-M17, 10.1.19, 9.0.86, 8.5.99	0	1	0	0	1
org.springframework.boot:spring-boot	3.3.11, 3.4.5	0	1	0	0	1
org.springframework.boot:spring-boot	4.0.6, 3.5.14	0	1	0	0	1
org.springframework.boot:spring-boot-autoconfigure	3.0.7, 2.7.12, 2.6.15, 2.5.15	0	1	0	0	1
org.springframework:spring-core	6.2.11	0	1	0	0	1
org.springframework:spring-core	7.0.8, 6.2.19	0	1	0	0	1
org.springframework:spring-web	5.3.34, 6.0.19, 6.1.6	0	1	0	0	1
org.springframework:spring-web	6.1.5, 6.0.18, 5.3.33	0	1	0	0	1
org.springframework:spring-webmvc	6.0.7, 5.3.26	0	1	0	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
org.springframework:spring-webmvc	6.1.13	0	1	0	0	1
org.springframework:spring-webmvc	6.1.14	0	1	0	0	1
sqlite-libs	3.25.0-r4	0	1	0	0	1
sqlite-libs	3.25.3-r0	0	1	0	0	1
zlib1g	1:1.2.11.dfsg-1+deb10u1	0	1	0	0	1
libtiff5	4.1.0+git191117-2~deb10u8	0	0	8	0	1
org.springframework:spring-webmvc	7.0.8, 6.2.19	0	0	7	0	1
openjdk8	8.232.09-r0	0	0	5	12	1
openjdk8-jre	8.232.09-r0	0	0	5	12	1
openjdk8-jre-base	8.232.09-r0	0	0	5	12	1
openjdk8-jre-lib	8.232.09-r0	0	0	5	12	1
openjdk8	8.222.10-r0	0	0	5	3	1
openjdk8-jre	8.222.10-r0	0	0	5	3	1
openjdk8-jre-base	8.222.10-r0	0	0	5	3	1
openjdk8-jre-lib	8.222.10-r0	0	0	5	3	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.23, 10.1.56, 9.0.119	0	0	2	1	1
bsdutils	2.33.1-0.1+deb10u1	0	0	2	0	1
com.fasterxml.jackson.core:jackson-databind	2.18.10, 2.21.6, 2.22.2	0	0	2	0	1
fdisk	2.33.1-0.1+deb10u1	0	0	2	0	1
libblkid1	2.33.1-0.1+deb10u1	0	0	2	0	1
libfdisk1	2.33.1-0.1+deb10u1	0	0	2	0	1
libmount1	2.33.1-0.1+deb10u1	0	0	2	0	1
libsmartcols1	2.33.1-0.1+deb10u1	0	0	2	0	1
libssl1.1	1.1.1n-0+deb10u6	0	0	2	0	1
libuuid1	2.33.1-0.1+deb10u1	0	0	2	0	1
libxml2	2.9.4+dfsg1-7+deb10u6	0	0	2	0	1
libxpm4	1:3.5.12-1+deb10u2	0	0	2	0	1
mount	2.33.1-0.1+deb10u1	0	0	2	0	1
openssl	1.1.1n-0+deb10u6	0	0	2	0	1
org.springframework:spring-webmvc	7.0.7, 6.2.18	0	0	2	0	1
org.yaml:snakeyaml	1.32	0	0	2	0	1
util-linux	2.33.1-0.1+deb10u1	0	0	2	0	1
openjdk8	8.201.08-r0	0	0	1	2	1
openjdk8-jre	8.201.08-r0	0	0	1	2	1
openjdk8-jre-base	8.201.08-r0	0	0	1	2	1
openjdk8-jre-lib	8.201.08-r0	0	0	1	2	1
curl	7.64.0-4+deb10u7	0	0	1	1	1

套件	修補版本	Critical	High	Medium	Low	映像檔
curl	7.64.0-4+deb10u8	0	0	1	1	1
libcurl4	7.64.0-4+deb10u7	0	0	1	1	1
libcurl4	7.64.0-4+deb10u8	0	0	1	1	1
org.springframework:spring-webmvc	7.0.6, 6.2.17	0	0	1	1	1
com.fasterxml.jackson.core: jackson-databind	2.18.9, 2.21.5, 2.22.1	0	0	1	0	1
com.fasterxml.jackson.core: jackson-databind	2.21.5, 2.18.9, 2.22.1	0	0	1	0	1
com.fasterxml.jackson.core: jackson-databind	3.1.4, 2.18.9, 2.21.5, 2.22.1	0	0	1	0	1
curl	7.64.0-4+deb10u5	0	0	1	0	1
gpgv	2.2.12-1+deb10u2	0	0	1	0	1
krb5-libs	1.15.4-r0	0	0	1	0	1
libcom_err	1.44.2-r1	0	0	1	0	1
libcom_err	1.44.2-r2	0	0	1	0	1
libcurl4	7.64.0-4+deb10u5	0	0	1	0	1
libgnutls30	3.6.7-4+deb10u11	0	0	1	0	1
libgssapi-krb5-2	1.17-3+deb10u3	0	0	1	0	1
libgssapi-krb5-2	1.17-3+deb10u6	0	0	1	0	1
libicu63	63.1-6+deb10u2	0	0	1	0	1
libjpeg-turbo	1.5.3-r5	0	0	1	0	1
libk5crypto3	1.17-3+deb10u3	0	0	1	0	1
libk5crypto3	1.17-3+deb10u6	0	0	1	0	1
libkrb5-3	1.17-3+deb10u3	0	0	1	0	1
libkrb5-3	1.17-3+deb10u6	0	0	1	0	1
libkrb5support0	1.17-3+deb10u3	0	0	1	0	1
libkrb5support0	1.17-3+deb10u6	0	0	1	0	1
libncursesw6	6.1+20181013-2+deb10u4	0	0	1	0	1
libnghttp2-14	1.36.0-2+deb10u3	0	0	1	0	1
libsystemd0	241-7~deb10u10	0	0	1	0	1
libsystemd0	241-7~deb10u8	0	0	1	0	1
libtasn1	4.14-r0	0	0	1	0	1
libtiff5	4.1.0+git191117-2~deb10u3	0	0	1	0	1
libtiff5	4.1.0+git191117-2~deb10u6	0	0	1	0	1
libtinfo6	6.1+20181013-2+deb10u4	0	0	1	0	1
libudev1	241-7~deb10u10	0	0	1	0	1
libudev1	241-7~deb10u8	0	0	1	0	1
libxml2	2.9.4+dfsg1-7+deb10u4	0	0	1	0	1
ncurses-base	6.1+20181013-2+deb10u4	0	0	1	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
ncurses-bin	6.1+20181013-2+deb10u4	0	0	1	0	1
org.apache.logging.log4j:log4j-api	2.25.5, 2.26.1	0	0	1	0	1
org.apache.logging.log4j:log4j-core	2.12.3, 2.17.0, 2.3.1	0	0	1	0	1
org.apache.logging.log4j:log4j-core	2.25.3	0	0	1	0	1
org.apache.logging.log4j:log4j-core	2.3.2, 2.12.4, 2.17.1	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	10.1.14, 9.0.81, 8.5.94, 11.0.0-M12	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.12, 10.1.47, 9.0.110	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	8.5.93, 9.0.80, 10.1.13, 11.0.0-M11	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.105, 10.1.41, 11.0.7	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.107	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.107, 10.1.43, 11.0.9	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.52, 11.0.20	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.53, 11.0.20	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.54, 11.0.21	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	9.0.117, 10.1.54, 11.0.21	0	0	1	0	1
org.springframework:spring-beans	5.2.22.RELEASE, 5.3.20	0	0	1	0	1
org.springframework:spring-context	5.3.19, 5.2.21.RELEASE	0	0	1	0	1
org.springframework:spring-context	6.1.14	0	0	1	0	1
org.springframework:spring-core	5.3.14, 5.2.19	0	0	1	0	1
org.springframework:spring-expression	5.3.17, 5.2.20.RELEASE	0	0	1	0	1
org.springframework:spring-expression	5.3.39	0	0	1	0	1
org.springframework:spring-expression	6.0.7, 5.3.26, 5.2.23.RELEASE	0	0	1	0	1
org.springframework:spring-expression	6.0.8, 5.3.27, 5.2.24.RELEASE	0	0	1	0	1
org.springframework:spring-web	5.3.38, 6.0.23, 6.1.12	0	0	1	0	1
org.springframework:spring-web	6.1.14	0	0	1	0	1

套件	修補版本	Critical	High	Medium	Low	映像檔
org.springframework:spring-webmvc	5.3.42	0	0	1	0	1
org.springframework:spring-webmvc	6.2.10	0	0	1	0	1
sqlite-libs	3.25.3-r2	0	0	1	0	1
zlib	1.4-r0	0	0	1	0	1
org.apache.tomcat.embed:tomcat-embed-core	11.0.9, 10.1.43, 9.0.107	0	0	0	1	1
org.springframework:spring-context	6.2.7, 6.1.20	0	0	0	1	1
org.springframework:spring-web	6.1.4, 6.0.17, 5.3.32	0	0	0	1	1
tar	1.30+dfsg-6+deb10u1	0	0	0	1	1
debian-archive-keyring	2019.1+deb10u2	0	0	0	0	1
libbz2-1.0	1.0.6-9.2~deb10u2	0	0	0	0	1
libexpat1	2.2.6-2+deb10u4	0	0	0	0	1
tzdata	2021a-0+deb10u10	0	0	0	0	1
tzdata	2021a-0+deb10u11	0	0	0	0	1
tzdata	2021a-0+deb10u12	0	0	0	0	1
tzdata	2021a-0+deb10u7	0	0	0	0	1
tzdata	2021a-0+deb10u8	0	0	0	0	1
tzdata	2024a-0+deb10u1	0	0	0	0	1

尚無修補版本的弱點

共 86 個弱點尚無修補版本，請評估緩解措施。

狀態	數量
受影響	45
不予修補	30
延後修補	11

弱點盤點

共 461 個不重複弱點。

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2021-44228	Critical	10.0	org.apache.logging.log4j:log4j-core	2.15.0, 2.3.1, 2.12.2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2016-1000027	Critical	9.8	org.springframework:spring-web	6.0.0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-12900	Critical	9.8	libbz2	1.0.6-r7	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-14697	Critical	9.8	musl, musl-utils	1.1.19-r11	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-8457	Critical	9.8	libdb5.3, sqlite-libs	3.25.3-r1	2
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest · nginx:1.21.0					
CVE-2021-33574	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-3711	Critical	9.8	libssl1.1, openssl	1.1.1d-0+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1471	Critical	9.8	org.yaml:snakeyaml	2.0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-1664	Critical	9.8	dpkg	1.19.8	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22822	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22823	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22824	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22965	Critical	9.8	org.springframework:spring-beans, org.springframework:spring-webmvc	5.2.20.RELEASE, 5.3.18	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-23218	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-23219	Critical	9.8	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-23852	Critical	9.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-25235	Critical	9.8	libexpat1	2.2.6-2+deb10u3	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2022-25236	Critical	9.8	libexpat1	2.2.6-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-25315	Critical	9.8	libexpat1	2.2.6-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-27404	Critical	9.8	libfreetype6	2.9.1-3+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-29155	Critical	9.8	libldap-2.4-2, libldap-common	2.4.47+dfsg-3+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-32221	Critical	9.8	curl, libcurl4	7.64.0-4+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-37434	Critical	9.8	zlib1g	1:1.2.11.dfsg-1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-45853	Critical	9.8	zlib1g	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-24813	Critical	9.8	org.apache.tomcat.embed:tomcat-embed-core	11.0.3, 10.1.35, 9.0.99	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-47884	Critical	9.8	org.springframework:spring-webmvc	7.0.9	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-35942	Critical	9.1	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-46848	Critical	9.1	libtasn1-6	4.13-3+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-66614	Critical	9.1	org.apache.tomcat.embed:tomcat-embed-core	11.0.15, 10.1.50, 9.0.113	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-3183	Critical	9.0	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-45046	Critical	9.0	org.apache.logging.log4j:log4j-core	2.16.0, 2.12.2, 2.3.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-14550	High	8.8	libpng	1.6.37-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-30560	High	8.8	libxslt1.1	1.1.32-2.2~deb10u2	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2021-39537	High	8.8	libncursesw6, libtinfo6, ncurses-base, ncurses-bin	6.1+20181013-2+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-45960	High	8.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1271	High	8.8	gzip, liblzma5	1.9-3+deb10u1, 5.2.4-1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22825	High	8.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22826	High	8.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22827	High	8.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-24407	High	8.8	libsasl2-2, libsasl2-modules-db	2.1.27+dfsg-1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3970	High	8.8	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-42898	High	8.8	libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0	1.17-3+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-4883	High	8.8	libxpm4	1:3.5.12-1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-25434	High	8.8	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-27533	High	8.8	curl, libcurl4	7.64.0-4+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-27534	High	8.8	curl, libcurl4	7.64.0-4+deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-4863	High	8.8	libwebp6	0.6.1-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-2961	High	8.8	libc-bin, libc6	2.28-10+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-49124	High	8.4	org.apache.tomcat.embed:tomcat-embed-core	11.0.8, 10.1.42, 9.0.106	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-3149	High	8.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-3169	High	8.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14583	High	8.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2803	High	8.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2805	High	8.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-65182	High	8.2	org.apache.tomcat.embed:tomcat-embed-core	11.0.25, 10.1.58, 9.0.121	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2017-6363	High	8.1	libgd3	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-12886	High	8.1	gcc-8-base, libgcc1, libstdc++6	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-20346	High	8.1	sqlite-libs	3.25.3-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-13115	High	8.1	libssh2-1	1.8.0-2.1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-17498	High	8.1	libssh2-1	1.8.0-2.1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-17543	High	8.1	liblz4-1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-2698	High	8.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.212.04-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2604	High	8.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-6096	High	8.1	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22576	High	8.1	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-40674	High	8.1	libexpat1	2.2.6-2+deb10u5	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2023-31484	High	8.1	perl-base	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-22259	High	8.1	org.springframework:spring-web	6.1.5, 6.0.18, 5.3.33	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-22262	High	8.1	org.springframework:spring-web	5.3.34, 6.0.19, 6.1.6	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-50379	High	8.1	org.apache.tomcat.embed:tomcat-embed-core	11.0.2, 10.1.34, 9.0.98	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-56337	High	8.1	org.apache.tomcat.embed:tomcat-embed-core	11.0.2, 10.1.34, 9.0.98	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-54512	High	8.1	com.fasterxml.jackson.core:jackson-databind	2.18.8, 3.1.4, 2.21.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-54513	High	8.1	com.fasterxml.jackson.core:jackson-databind	2.18.8, 2.21.4, 3.1.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2201	High	7.8	libjpeg-turbo	1.5.3-r6	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-3843	High	7.8	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-3844	High	7.8	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-16156	High	7.8	perl-base	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-3999	High	7.8	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-46143	High	7.8	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1304	High	7.8	e2fsprogs, libcom-err2, libext2fs2, libss2	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-40304	High	7.8	libxml2	2.9.4+dfsg1-7+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-26604	High	7.8	libsystemd0, libudev1	241-7~deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-29491	High	7.8	libncursesw6, libtinfo6, ncurses-base, ncurses-bin	6.1+20181013-2+deb10u5	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2023-43787	High	7.8	libx11-6, libx11-data	2:1.6.7-1+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-33599	High	7.6	libc-bin, libc6	2.28-10+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2017-16932	High	7.5	libxml2	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-14553	High	7.5	libgd3	2.2.5-5.2+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-25032	High	7.5	zlib1g	1:1.2.11.dfsg-1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-12290	High	7.5	libidn2-0	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-14855	High	7.5	gpgv	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-15847	High	7.5	gcc-8-base, libgcc1, libstdc++6	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-19244	High	7.5	sqlite-libs	3.25.3-r3	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2602	High	7.5	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.212.04-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-5815	High	7.5	libxslt1.1	1.1.32-2.2~deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-11080	High	7.5	libnghttp2-14	1.36.0-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-11655	High	7.5	sqlite-libs	3.25.0-r4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-22218	High	7.5	libssh2-1	1.8.0-2.1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-36518	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.2.1, 2.12.6.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-22946	High	7.5	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-3326	High	7.5	libc-bin, libc6	2.28-10+deb10u2	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2021-33560	High	7.5	libgcrypt20	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-36222	High	7.5	libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0	1.17-3+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-43618	High	7.5	libgmp10	2:6.1.2+dfsg-4+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-46877	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.12.6, 2.13.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-0778	High	7.5	libssl1.1, openssl	1.1.1d-0+deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2309	High	7.5	libxml2	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-23308	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-23990	High	7.5	libexpat1	2.2.6-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2509	High	7.5	libgnutls30	3.6.7-4+deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-25314	High	7.5	libexpat1	2.2.6-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-25857	High	7.5	org.yaml:snakeyaml	1.31	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-27405	High	7.5	libfreetype6	2.9.1-3+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-27406	High	7.5	libfreetype6	2.9.1-3+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-27781	High	7.5	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-27782	High	7.5	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-40303	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-42003	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.12.7.1, 2.13.4.2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2022-42004	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.12.7.1, 2.13.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-42252	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	8.5.83, 9.0.68, 10.0.27, 10.1.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-43680	High	7.5	libexpat1	2.2.6-2+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-4450	High	7.5	libssl1.1, openssl	1.1.1n-0+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-44617	High	7.5	libxpm4	1:3.5.12-1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-45143	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	8.5.84, 9.0.69, 10.1.2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-46285	High	7.5	libxpm4	1:3.5.12-1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0215	High	7.5	libssl1.1, openssl	1.1.1n-0+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0464	High	7.5	libssl1.1, openssl	1.1.1n-0+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-1999	High	7.5	libwebp6	0.6.1-2+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-20860	High	7.5	org.springframework:spring-webmvc	6.0.7, 5.3.26	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-20883	High	7.5	org.springframework.boot:spring-boot-autoconfigure	3.0.7, 2.7.12, 2.6.15, 2.5.15	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-24998	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	10.1.5, 11.0.0-M5, 8.5.88, 9.0.71	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-2953	High	7.5	libldap-2.4-2, libldap-common	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3138	High	7.5	libx11-6, libx11-data	2:1.6.7-1+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-44487	High	7.5	libnghttp2-14, org.apache.tomcat.embed:tomcat-embed-core	1.36.0-2+deb10u2, 11.0.0-M12, 10.1.14, 9.0.81, 8.5.94	2

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest · nginx:1.21.0					
CVE-2023-46589	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M11, 10.1.16, 9.0.83, 8.5.96	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-50387	High	7.5	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-50868	High	7.5	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-52355	High	7.5	libtiff5	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-52356	High	7.5	libtiff5	4.1.0+git191117-2~deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-52425	High	7.5	libexpat1	2.2.6-2+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-0553	High	7.5	libgnutls30	3.6.7-4+deb10u12	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-23672	High	7.5	org.apache.tomcat.embed:tomcat-embed-websocket	11.0.0-M17, 10.1.19, 9.0.86, 8.5.99	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-2398	High	7.5	curl, libcurl4	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-24549	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	8.5.99, 9.0.86, 10.1.19, 11.0.0-M17	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-25062	High	7.5	libxml2	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-34750	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M21, 10.1.25, 9.0.90	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-38286	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M21, 10.1.25, 9.0.90	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-38816	High	7.5	org.springframework:spring-webmvc	6.1.13	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-38819	High	7.5	org.springframework:spring-webmvc	6.1.14	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-41249	High	7.5	org.springframework:spring-core	6.2.11	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-48989	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.10, 10.1.44, 9.0.108	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-52999	High	7.5	com.fasterxml.jackson.core:jackson-core	2.15.0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-55752	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.11, 10.1.45, 9.0.109	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-34479	High	7.5	org.apache.logging.log4j:log4j-core	2.25.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-34480	High	7.5	org.apache.logging.log4j:log4j-core	2.25.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41284	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41848	High	7.5	org.springframework:spring-core	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41851	High	7.5	org.springframework:spring-expression	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-50193	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.14.0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-68494	High	7.5	com.fasterxml.jackson.core:jackson-core	2.18.8, 2.21.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-89425	High	7.5	com.fasterxml.jackson.core:jackson-core	2.21.7, 2.22.3, 2.18.11	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-91776	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.18.11, 2.21.7, 2.22.3	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-91777	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.21.7, 2.18.11, 2.22.3	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14593	High	7.4	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-3712	High	7.4	libssl1.1, openssl	1.1.1d-0+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0286	High	7.4	libssl1.1, openssl	1.1.1n-0+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0361	High	7.4	libgnutls30	3.6.7-4+deb10u10	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2022-1292	High	7.3	libssl1.1, openssl	1.1.1n-0+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2068	High	7.3	libssl1.1, openssl	1.1.1n-0+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-22235	High	7.3	org.springframework.boot:spring-boot	3.3.11, 3.4.5	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41293	High	7.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-55957	High	7.3	org.apache.tomcat.embed:tomcat-embed-core	11.0.5, 10.1.37, 9.0.101	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-0891	High	7.1	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-29458	High	7.1	libncursesw6, libtinfo6, ncurses-base, ncurses-bin	6.1+20181013-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-1751	High	7.0	libc-bin, libc6	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-1752	High	7.0	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2026-40973	High	7.0	org.springframework.boot:spring-boot	4.0.6, 3.5.14	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2949	Medium	6.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2989	Medium	6.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2601	Medium	6.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-5094	Medium	6.7	libcom_err	1.44.2-r1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-5188	Medium	6.7	libcom_err	1.44.2-r2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-44832	Medium	6.6	org.apache.logging.log4j:log4j-core	2.3.2, 2.12.4, 2.17.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2016-2781	Medium	6.5	coreutils	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-11212	Medium	6.5	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.201.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-13785	Medium	6.5	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-14048	Medium	6.5	libpng	1.6.37-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-14498	Medium	6.5	libjpeg-turbo	1.5.3-r5	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-16168	Medium	6.5	sqlite-libs	3.25.3-r2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-19143	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-19189	Medium	6.5	libncursesw6, libtinfo6, ncurses-base, ncurses-bin	6.1+20181013-2+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-37750	Medium	6.5	libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0	1.17-3+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-38115	Medium	6.5	libgd3	2.2.5-5.2+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-40812	Medium	6.5	libgd3	2.2.5-5.2+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-4209	Medium	6.5	libgnutls30	3.6.7-4+deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0865	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1210	Medium	6.5	libtiff5	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2056	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2057	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2022-2058	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22950	Medium	6.5	org.springframework:spring-expression	5.3.17, 5.2.20.RELEASE	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-25313	Medium	6.5	libexpat1	2.2.6-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-27776	Medium	6.5	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-29824	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-32206	Medium	6.5	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-34526	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-34903	Medium	6.5	gpgv	2.2.12-1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3597	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3598	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3599	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3626	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3627	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-38749	Medium	6.5	org.yaml:snakeyaml	1.31	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-38751	Medium	6.5	org.yaml:snakeyaml	1.31	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-38752	Medium	6.5	org.yaml:snakeyaml	1.32	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-40090	Medium	6.5	libtiff5	–	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2022-41854	Medium	6.5	org.yaml:snakeyaml	1.32	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-20861	Medium	6.5	org.springframework:spring-expression	6.0.7, 5.3.26, 5.2.23.RELEASE	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-20863	Medium	6.5	org.springframework:spring-expression	6.0.8, 5.3.27, 5.2.24.RELEASE	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-23916	Medium	6.5	curl, libcurl4	7.64.0-4+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-2650	Medium	6.5	libssl1.1, openssl	1.1.1n-0+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-28484	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-29469	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3316	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-36054	Medium	6.5	libgssapi-krb5-2, libk5crypto3, libkrb5-3, libkrb5support0	1.17-3+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3618	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-39615	Medium	6.5	libxml2	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-40745	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-41175	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-45322	Medium	6.5	libxml2	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-46218	Medium	6.5	curl, libcurl4	7.64.0-4+deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-50495	Medium	6.5	libncursesw6, libtinfo6, ncurses-base, ncurses-bin	–	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2023-6277	Medium	6.5	libtiff5	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-46701	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.105, 10.1.41, 11.0.7	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-55668	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.8, 10.1.42, 9.0.106	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-22737	Medium	6.5	org.springframework:spring-webmvc	7.0.6, 6.2.17	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-34487	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.117, 10.1.54, 11.0.21	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-42498	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-43512	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-53404	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.23, 10.1.56, 9.0.119	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-55956	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.23, 10.1.56, 9.0.119	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-59889	Medium	6.5	com.fasterxml.jackson.core:jackson-databind	2.21.5, 2.18.9, 2.22.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-68525	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.25, 10.1.58, 9.0.121	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-13627	Medium	6.3	libgcrypt20	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2016-3709	Medium	6.1	libxml2	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1355	Medium	6.1	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-41080	Medium	6.1	org.apache.tomcat.embed:tomcat-embed-core	8.5.93, 9.0.80, 10.1.13, 11.0.0-M11	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41844	Medium	6.1	org.springframework:spring-webmvc	7.0.8, 6.2.19	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41845	Medium	6.1	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41846	Medium	6.1	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2016-10228	Medium	5.9	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-19242	Medium	5.9	sqlite-libs	3.25.3-r3	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-25013	Medium	5.9	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-2684	Medium	5.9	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.212.04-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2958	Medium	5.9	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-22947	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-4160	Medium	5.9	libssl1.1, openssl	1.1.1d-0+deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-45105	Medium	5.9	org.apache.logging.log4j:log4j-core	2.12.3, 2.17.0, 2.3.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-32208	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-4304	Medium	5.9	libssl1.1, openssl	1.1.1n-0+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-43552	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-27535	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-27536	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-28321	Medium	5.9	curl, libcurl4	7.64.0-4+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-4806	Medium	5.9	libc-bin, libc6	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-4813	Medium	5.9	libc-bin, libc6	—	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2023-5981	Medium	5.9	libgnutls30	3.6.7-4+deb10u11	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-7008	Medium	5.9	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-38808	Medium	5.9	org.springframework:spring-expression	5.3.39	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-41242	Medium	5.9	org.springframework:spring-webmvc	6.2.10	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-22741	Medium	5.9	org.springframework:spring-webmvc	7.0.7, 6.2.18	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-34477	Medium	5.9	org.apache.logging.log4j:log4j-core	2.25.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41841	Medium	5.9	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41842	Medium	5.9	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41843	Medium	5.9	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41849	Medium	5.9	org.springframework:spring-expression	—	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41850	Medium	5.9	org.springframework:spring-expression	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-49844	Medium	5.9	org.apache.logging.log4j:log4j-api	2.25.5, 2.26.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-27774	Medium	5.7	curl, libcurl4	7.64.0-4+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-3180	Medium	5.6	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-4741	Medium	5.6	libssl1.1, openssl	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2026-83557	Medium	5.6	com.fasterxml.jackson.core:jackson-databind	2.18.10, 2.21.6, 2.22.2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2016-9318	Medium	5.5	libxml2	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2018-1000654	Medium	5.5	libtasn1	4.14-r0	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-16435	Medium	5.5	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-10029	Medium	5.5	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-21913	Medium	5.5	libicu63	63.1-6+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-27618	Medium	5.5	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-35538	Medium	5.5	libjpeg62-turbo	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-33910	Medium	5.5	libsystemd0, libudev1	241-7~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-37600	Medium	5.5	bsdutils, fdisk, libblkid1, libfdisk1, libmount1, libsmartcols1, libuuid1, mount, util-linux	2.33.1-0.1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-3997	Medium	5.5	libsystemd0, libudev1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-46822	Medium	5.5	libjpeg62-turbo	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0561	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0562	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0907	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0908	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0909	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-0924	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-1354	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2022-22844	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2867	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2868	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-2869	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3570	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-3821	Medium	5.5	libsystemd0, libudev1	241-7~deb10u10	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-38750	Medium	5.5	org.yaml:snakeyaml	1.31	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-4415	Medium	5.5	libsystemd0, libudev1	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-4645	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-48281	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0795	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0796	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0797	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0798	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0799	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2023-0800	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0801	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0802	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0803	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0804	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-25433	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-25435	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-26965	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-26966	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-27538	Medium	5.5	curl, libcurl4	7.64.0-4+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-2908	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-30086	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-30774	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3576	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u9	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-43785	Medium	5.5	libx11-6, libx11-data	2:1.6.7-1+deb10u4	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2023-43786	Medium	5.5	libx11-6, libx11-data	2:1.6.7-1+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-43788	Medium	5.5	libxpm4	1:3.5.12-1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-43789	Medium	5.5	libxpm4	1:3.5.12-1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-4641	Medium	5.5	login, passwd	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-0727	Medium	5.5	libssl1.1, openssl	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-22365	Medium	5.5	libpam-modules, libpam-modules-bin, libpam-runtime, libpam0g	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2026-34483	Medium	5.4	org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.54, 11.0.21	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-43515	Medium	5.4	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-20217	Medium	5.3	krb5-libs	1.15.4-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-3214	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-7169	Medium	5.3	login, passwd	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2019-2762	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2769	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-7317	Medium	5.3	libpng, openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	1.6.37-r0, 8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14155	Medium	5.3	libpcre3	—	1
受影響的映像檔 nginx:1.21.0					
CVE-2020-14621	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2020-14803	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2781	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2830	Medium	5.3	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-2097	Medium	5.3	libssl1.1, openssl	1.1.1n-0+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-22968	Medium	5.3	org.springframework:spring-context	5.3.19, 5.2.21.RELEASE	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2022-22970	Medium	5.3	org.springframework:spring-beans	5.2.22.RELEASE, 5.3.20	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-0465	Medium	5.3	libssl1.1, openssl	1.1.1n-0+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-0466	Medium	5.3	libssl1.1, openssl	1.1.1n-0+deb10u5	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3446	Medium	5.3	libssl1.1, openssl	1.1.1n-0+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-3817	Medium	5.3	libssl1.1, openssl	1.1.1n-0+deb10u6	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-42795	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	10.1.14, 9.0.81, 8.5.94, 11.0.0-M12	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-45648	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	11.0.0-M12, 10.1.14, 9.0.81, 8.5.94	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2023-5678	Medium	5.3	libssl1.1, openssl	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-28182	Medium	5.3	libnghttp2-14	1.36.0-2+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-33600	Medium	5.3	libc-bin, libc6	2.28-10+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-38809	Medium	5.3	org.springframework:spring-web	5.3.38, 6.0.23, 6.1.12	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2024-38820	Medium	5.3	org.springframework:spring-context, org.springframework:spring-web	6.1.14	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-38828	Medium	5.3	org.springframework:spring-webmvc	5.3.42	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-48988	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	11.0.8, 10.1.42, 9.0.106	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-52434	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.107	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-53506	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.107, 10.1.43, 11.0.9	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-61795	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	11.0.12, 10.1.47, 9.0.110	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-19032	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.18.10, 2.21.6, 2.22.2	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-22745	Medium	5.3	org.springframework:spring-webmvc	7.0.7, 6.2.18	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41852	Medium	5.3	org.springframework:spring-expression	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-41853	Medium	5.3	org.springframework:spring-webmvc	7.0.8, 6.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-43513	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-54514	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.18.8, 2.21.4, 3.1.4	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-54515	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	3.1.4, 2.18.9, 2.21.5, 2.22.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-77310	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.18.9, 2.21.5, 2.22.1	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2745	Medium	5.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2816	Medium	4.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2019-2975	Medium	4.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14556	Medium	4.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2593	Medium	4.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2800	Medium	4.8	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-68161	Medium	4.8	org.apache.logging.log4j:log4j-core	2.25.3	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-65905	Medium	4.8	org.apache.tomcat.embed:tomcat-embed-core	11.0.25, 10.1.58, 9.0.121	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2999	Medium	4.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-28085	Medium	4.4	bsdutils, fdisk, libblkid1, libfdisk1, libmount1, libsmartcols1, libuuid1, mount, util-linux	2.33.1-0.1+deb10u1	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-22060	Medium	4.3	org.springframework:spring-core	5.3.14, 5.2.19	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-24880	Medium	4.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.52, 11.0.20	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-25854	Medium	4.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.116, 10.1.53, 11.0.20	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14792	Medium	4.2	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-33601	Medium	4.0	libc-bin, libc6	2.28-10+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-33602	Medium	4.0	libc-bin, libc6	2.28-10+deb10u4	1
受影響的映像檔 nginx:1.21.0					
CVE-2026-4738	Medium	—	zlib	1.4-r0	1
受影響的映像檔 alpine:3.22					
CVE-2019-2426	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.201.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2019-2842	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2894	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2962	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2964	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2973	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2978	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2981	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2983	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2987	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2988	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2992	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14577	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14578	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14579	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14581	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14779	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14781	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14782	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14797	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2583	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2590	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2654	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2659	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.242.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2754	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2755	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2756	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2757	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-2773	Low	3.7	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.252.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-22924	Low	3.7	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2022-35252	Low	3.7	curl, libcurl4	7.64.0-4+deb10u4	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
CVE-2023-28322	Low	3.7	curl, libcurl4	7.64.0-4+deb10u8	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-38546	Low	3.7	curl, libcurl4	7.64.0-4+deb10u7	1
受影響的映像檔 nginx:1.21.0					
CVE-2024-2511	Low	3.7	libssl1.1, openssl	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-49125	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	11.0.8, 10.1.42, 9.0.106	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-52520	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	11.0.9, 10.1.43, 9.0.107	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-43514	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	9.0.118, 10.1.55, 11.0.22	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2025-55754	Low	3.5	org.apache.tomcat.embed:tomcat-embed-core	11.0.11, 10.1.45, 9.0.109	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2018-3136	Low	3.4	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2786	Low	3.4	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2024-22243	Low	3.4	org.springframework:spring-web	6.1.4, 6.0.17, 5.3.32	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-19126	Low	3.3	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-36084	Low	3.3	libsepol1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-36085	Low	3.3	libsepol1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-36086	Low	3.3	libsepol1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2021-36087	Low	3.3	libsepol1	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-29383	Low	3.3	login, passwd	–	1
受影響的映像檔 nginx:1.21.0					
CVE-2023-39804	Low	3.3	tar	1.30+dfsg-6+deb10u1	1

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
受影響的映像檔 nginx:1.21.0					
CVE-2018-3139	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.191.12-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2422	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.201.08-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2766	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.222.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2933	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2019-2945	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.232.09-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14796	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2020-14798	Low	3.1	openjdk8, openjdk8-jre, openjdk8-jre-base, openjdk8-jre-lib	8.272.10-r0	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-22898	Low	3.1	curl, libcurl4	7.64.0-4+deb10u3	1
受影響的映像檔 nginx:1.21.0					
CVE-2025-22233	Low	3.1	org.springframework:spring-context	6.2.7, 6.1.20	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2026-22735	Low	2.6	org.springframework:spring-webmvc	7.0.6, 6.2.17	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
CVE-2021-27645	Low	2.5	libc-bin, libc6	2.28-10+deb10u2	1
受影響的映像檔 nginx:1.21.0					
CVE-2026-55276	Low	2.3	org.apache.tomcat.embed:tomcat-embed-core	11.0.23, 10.1.56, 9.0.119	1
受影響的映像檔 ghcr.io/christophetd/log4shell-vulnerable-app:latest					
DLA-3112-1	Unrated	—	libbz2-1.0	1.0.6-9.2~deb10u2	1
受影響的映像檔 nginx:1.21.0					
DLA-3134-1	Unrated	—	tzdata	2021a-0+deb10u7	1
受影響的映像檔 nginx:1.21.0					
DLA-3161-1	Unrated	—	tzdata	2021a-0+deb10u8	1
受影響的映像檔 nginx:1.21.0					
DLA-3366-1	Unrated	—	tzdata	2021a-0+deb10u10	1
受影響的映像檔 nginx:1.21.0					

弱點編號	嚴重等級	CVSS	套件	修補版本	映像檔
DLA-3412-1	Unrated	—	tzdata	2021a-0+deb10u11	1
受影響的映像檔 nginx:1.21.0					
DLA-3482-1	Unrated	—	debian-archive-keyring	2019.1+deb10u2	1
受影響的映像檔 nginx:1.21.0					
DLA-3684-1	Unrated	—	tzdata	2021a-0+deb10u12	1
受影響的映像檔 nginx:1.21.0					
DLA-3788-1	Unrated	—	tzdata	2024a-0+deb10u1	1
受影響的映像檔 nginx:1.21.0					
DSA-5085-2	Unrated	—	libexpat1	2.2.6-2+deb10u4	1
受影響的映像檔 nginx:1.21.0					

各映像檔明細

nginx:1.21.0

Digest	sha256:47ae43cdfc7064d28800bc42e79a429540c7c80168e8c8952778c0d5af1c09db
平台	linux/amd64
作業系統	debian 10.10
大小	—
建立時間	2021-06-23T07:16:26Z
掃描時間	2026-11-07T14:32:23Z
各嚴重等級弱點數	Critical 27 High 142 Medium 193 Low 23 Unrated 9

弱點明細

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2019-8457	Critical	9.8	libdb5.3	5.3.28+dfsg1-0.5	—
SQLite3 from 3.6.0 to and including 3.27.2 is vulnerable to heap out-of-bound read in the rtreenode() function when handling invalid rtree tables.					
CVE-2021-33574	Critical	9.8	libc-bin	2.28-10	2.28-10+deb10u2
The mq_notify function in the GNU C Library (aka glibc) versions 2.32 and 2.33 has a use-after-free. It may use the notification thread attributes object (passed through its struct sigevent parameter) after it has been freed by the caller, leading to a denial of service (application crash) or possibly unspecified other impact.					
CVE-2021-33574	Critical	9.8	libc6	2.28-10	2.28-10+deb10u2
The mq_notify function in the GNU C Library (aka glibc) versions 2.32 and 2.33 has a use-after-free. It may use the notification thread attributes object (passed through its struct sigevent parameter) after it has been freed by the caller, leading to a denial of service (application crash) or possibly unspecified other impact.					
CVE-2021-3711	Critical	9.8	libssl1.1	1.1.1d-0+deb10u6	1.1.1d-0+deb10u7
In order to decrypt SM2 encrypted data an application is expected to call the API function EVP_PKEY_decrypt(). Typically an application will call this function twice. The first time, on entry, the "out" parameter can be NULL and, on exit, the "outlen" parameter is populated with the buffer size required to hold the decrypted plaintext. The application can then allocate a sufficiently sized buffer and call EVP_PKEY_decrypt() again, but this time passing a non-NULL value for the "out" parameter. A bug in the implementation of the SM2 decryption code means that the calculation of the buffer size ...					
CVE-2021-3711	Critical	9.8	openssl	1.1.1d-0+deb10u6	1.1.1d-0+deb10u7
In order to decrypt SM2 encrypted data an application is expected to call the API function EVP_PKEY_decrypt(). Typically an application will call this function twice. The first time, on entry, the "out" parameter can be NULL and, on exit, the "outlen" parameter is populated with the buffer size required to hold the decrypted plaintext. The application can then allocate a sufficiently sized buffer and call EVP_PKEY_decrypt() again, but this time passing a non-NULL value for the "out" parameter. A bug in the implementation of the SM2 decryption code means that the calculation of the buffer size ...					
CVE-2022-1664	Critical	9.8	dpkg	1.19.7	1.19.8
Dpkg::Source::Archive in dpkg, the Debian package management system, before version 1.21.8, 1.20.10, 1.19.8, 1.18.26 is prone to a directory traversal vulnerability. When extracting untrusted source packages in v2 and v3 source package formats that include a debian.tar, the in-place extraction can lead to directory traversal situations on specially crafted orig.tar and debian.tar tarballs.					
CVE-2022-22822	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
addBinding in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-22823	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
build_model in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-22824	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
defineAttribute in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-23218	Critical	9.8	libc-bin	2.28-10	2.28-10+deb10u2
The deprecated compatibility function svcunix_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its path argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution.					
CVE-2022-23218	Critical	9.8	libc6	2.28-10	2.28-10+deb10u2
The deprecated compatibility function svcunix_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its path argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution.					
CVE-2022-23219	Critical	9.8	libc-bin	2.28-10	2.28-10+deb10u2
The deprecated compatibility function clnt_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its hostname argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution.					
CVE-2022-23219	Critical	9.8	libc6	2.28-10	2.28-10+deb10u2
The deprecated compatibility function clnt_create in the sunrpc module of the GNU C Library (aka glibc) through 2.34 copies its hostname argument on the stack without validating its length, which may result in a buffer overflow, potentially resulting in a denial of service or (if an application is not built with a stack protector enabled) arbitrary code execution.					
CVE-2022-23852	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
Expat (aka libexpat) before 2.4.4 has a signed integer overflow in XML_GetBuffer, for configurations with a nonzero XML_CONTEXT_BYTES.					
CVE-2022-25235	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u3
xmltok_impl.c in Expat (aka libexpat) before 2.4.5 lacks certain validation of encoding, such as checks for whether a UTF-8 character is valid in a certain context.					
CVE-2022-25236	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u3
xmlparse.c in Expat (aka libexpat) before 2.4.5 allows attackers to insert namespace-separator characters into namespace URIs.					
CVE-2022-25315	Critical	9.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u3
In Expat (aka libexpat) before 2.4.5, there is an integer overflow in storeRawNames.					
CVE-2022-27404	Critical	9.8	libfreetype6	2.9.1-3+deb10u2	2.9.1-3+deb10u3
FreeType commit 1e2eb65048f75c64b68708efed6ce904c31f3b2f was discovered to contain a heap buffer overflow via the function sfnt_init_face.					
CVE-2022-29155	Critical	9.8	libldap-2.4-2	2.4.47+dfsg-3+deb10u6	2.4.47+dfsg-3+deb10u7
In OpenLDAP 2.x before 2.5.12 and 2.6.x before 2.6.2, a SQL injection vulnerability exists in the experimental back-sql backend to slapd, via a SQL statement within an LDAP query. This can occur during an LDAP search operation when the search filter is processed, due to a lack of proper escaping.					
CVE-2022-29155	Critical	9.8	libldap-common	2.4.47+dfsg-3+deb10u6	2.4.47+dfsg-3+deb10u7
In OpenLDAP 2.x before 2.5.12 and 2.6.x before 2.6.2, a SQL injection vulnerability exists in the experimental back-sql backend to slapd, via a SQL statement within an LDAP query. This can occur during an LDAP search operation when the search filter is processed, due to a lack of proper escaping.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-32221	Critical	9.8	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u4
When doing HTTP(S) transfers, libcurl might erroneously use the read callback (`CURLOPT_READFUNCTION`) to ask for data to send, even when the `CURLOPT_POSTFIELDS` option has been set, if the same handle previously was used to issue a `PUT` request which used that callback. This flaw may surprise the application and cause it to misbehave and either send off the wrong data or use memory after free or similar in the subsequent `POST` request. The problem exists in the logic for a reused handle when it is changed from a PUT to a POST.					
CVE-2022-32221	Critical	9.8	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u4
When doing HTTP(S) transfers, libcurl might erroneously use the read callback (`CURLOPT_READFUNCTION`) to ask for data to send, even when the `CURLOPT_POSTFIELDS` option has been set, if the same handle previously was used to issue a `PUT` request which used that callback. This flaw may surprise the application and cause it to misbehave and either send off the wrong data or use memory after free or similar in the subsequent `POST` request. The problem exists in the logic for a reused handle when it is changed from a PUT to a POST.					
CVE-2022-37434	Critical	9.8	zlib1g	1:1.2.11.dfsg-1	1:1.2.11.dfsg-1+deb10u2
zlib through 1.2.12 has a heap-based buffer over-read or buffer overflow in inflate in inflate.c via a large gzip header extra field. NOTE: only applications that call inflateGetHeader are affected. Some common applications bundle the affected zlib source code but may be unable to call inflateGetHeader (e.g., see the nodejs/node reference).					
CVE-2023-45853	Critical	9.8	zlib1g	1:1.2.11.dfsg-1	—
MiniZip in zlib through 1.3 has an integer overflow and resultant heap-based buffer overflow in zipOpenNewFileInZip4_64 via a long filename, comment, or extra field. NOTE: MiniZip is not a supported part of the zlib product. NOTE: pyminizip through 0.2.6 is also vulnerable because it bundles an affected zlib version, and exposes the applicable MiniZip code through its compress API.					
CVE-2021-35942	Critical	9.1	libc-bin	2.28-10	2.28-10+deb10u2
The wordexp function in the GNU C Library (aka glibc) through 2.33 may crash or read arbitrary memory in parse_param (in posix/wordexp.c) when called with an untrusted, crafted pattern, potentially resulting in a denial of service or disclosure of information. This occurs because atoi was used but strtoul should have been used to ensure correct calculations.					
CVE-2021-35942	Critical	9.1	libc6	2.28-10	2.28-10+deb10u2
The wordexp function in the GNU C Library (aka glibc) through 2.33 may crash or read arbitrary memory in parse_param (in posix/wordexp.c) when called with an untrusted, crafted pattern, potentially resulting in a denial of service or disclosure of information. This occurs because atoi was used but strtoul should have been used to ensure correct calculations.					
CVE-2021-46848	Critical	9.1	libtasn1-6	4.13-3	4.13-3+deb10u1
GNU Libtasn1 before 4.19.0 has an ETYPE_OK off-by-one array size check that affects asn1_encode_simple_der.					
CVE-2021-30560	High	8.8	libxslt1.1	1.1.32-2.2~deb10u1	1.1.32-2.2~deb10u2
Use after free in Blink XSLT in Google Chrome prior to 91.0.4472.164 allowed a remote attacker to potentially exploit heap corruption via a crafted HTML page.					
CVE-2021-39537	High	8.8	libncursesw6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow.					
CVE-2021-39537	High	8.8	libtinfo6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2021-39537	High	8.8	ncurses-base	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow.					
CVE-2021-39537	High	8.8	ncurses-bin	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
An issue was discovered in ncurses through v6.2-1. _nc_captoinfo in captoinfo.c has a heap-based buffer overflow.					
CVE-2021-45960	High	8.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
In Expat (aka libexpat) before 2.4.3, a left shift by 29 (or more) places in the storeAtts function in xmlparse.c can lead to realloc misbehavior (e.g., allocating too few bytes, or only freeing memory).					
CVE-2022-1271	High	8.8	gzip	1.9-3	1.9-3+deb10u1
An arbitrary file write vulnerability was found in GNU gzip's zgrep utility. When zgrep is applied on the attacker's chosen file name (for example, a crafted file name), this can overwrite an attacker's content to an arbitrary attacker-selected file. This flaw occurs due to insufficient validation when processing filenames with two or more newlines where selected content and the target file names are embedded in crafted multi-line file names. This flaw allows a remote, low privileged attacker to force zgrep to write arbitrary files on the system.					
CVE-2022-1271	High	8.8	liblzma5	5.2.4-1	5.2.4-1+deb10u1
An arbitrary file write vulnerability was found in GNU gzip's zgrep utility. When zgrep is applied on the attacker's chosen file name (for example, a crafted file name), this can overwrite an attacker's content to an arbitrary attacker-selected file. This flaw occurs due to insufficient validation when processing filenames with two or more newlines where selected content and the target file names are embedded in crafted multi-line file names. This flaw allows a remote, low privileged attacker to force zgrep to write arbitrary files on the system.					
CVE-2022-22825	High	8.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
lookup in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-22826	High	8.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
nextScaffoldPart in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-22827	High	8.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
storeAtts in xmlparse.c in Expat (aka libexpat) before 2.4.3 has an integer overflow.					
CVE-2022-24407	High	8.8	libsasl2-2	2.1.27+dfsg-1+deb10u1	2.1.27+dfsg-1+deb10u2
In Cyrus SASL 2.1.17 through 2.1.27 before 2.1.28, plugins/sql.c does not escape the password for a SQL INSERT or UPDATE statement.					
CVE-2022-24407	High	8.8	libsasl2-modules-db	2.1.27+dfsg-1+deb10u1	2.1.27+dfsg-1+deb10u2
In Cyrus SASL 2.1.17 through 2.1.27 before 2.1.28, plugins/sql.c does not escape the password for a SQL INSERT or UPDATE statement.					
CVE-2022-3970	High	8.8	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
A vulnerability was found in LibTIFF. It has been classified as critical. This affects the function TIFFReadRGBATileExt of the file libtiff/tif_getimage.c. The manipulation leads to integer overflow. It is possible to initiate the attack remotely. The exploit has been disclosed to the public and may be used. The name of the patch is 227500897dfb07fb7d27f7aa570050e62617e3be. It is recommended to apply a patch to fix this issue. The identifier VDB-213549 was assigned to this vulnerability.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-42898	High	8.8	libgssapi-krb5-2	1.17-3+deb10u1	1.17-3+deb10u5
PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug."					
CVE-2022-42898	High	8.8	libk5crypto3	1.17-3+deb10u1	1.17-3+deb10u5
PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug."					
CVE-2022-42898	High	8.8	libkrb5-3	1.17-3+deb10u1	1.17-3+deb10u5
PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug."					
CVE-2022-42898	High	8.8	libkrb5support0	1.17-3+deb10u1	1.17-3+deb10u5
PAC parsing in MIT Kerberos 5 (aka krb5) before 1.19.4 and 1.20.x before 1.20.1 has integer overflows that may lead to remote code execution (in KDC, kadmind, or a GSS or Kerberos application server) on 32-bit platforms (which have a resultant heap-based buffer overflow), and cause a denial of service on other platforms. This occurs in krb5_pac_parse in lib/krb5/krb/pac.c. Heimdal before 7.7.1 has "a similar bug."					
CVE-2022-4883	High	8.8	libxpm4	1:3.5.12-1	1:3.5.12-1+deb10u1
A flaw was found in libXpm. When processing files with .Z or .gz extensions, the library calls external programs to compress and uncompress files, relying on the PATH environment variable to find these programs, which could allow a malicious user to execute other programs by manipulating the PATH environment variable.					
CVE-2023-25434	High	8.8	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
libtiff 4.5.0 is vulnerable to Buffer Overflow via extractContigSamplesBytes() at /libtiff/tools/tiffcrop.c:3215.					
CVE-2023-27533	High	8.8	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u6
A vulnerability in input validation exists in curl <8.0 during communication using the TELNET protocol may allow an attacker to pass on maliciously crafted user name and "telnet options" during server negotiation. The lack of proper input scrubbing allows an attacker to send content or perform option negotiation without the application's intent. This vulnerability could be exploited if an application allows user input, thereby enabling attackers to execute arbitrary code on the system.					
CVE-2023-27533	High	8.8	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u6
A vulnerability in input validation exists in curl <8.0 during communication using the TELNET protocol may allow an attacker to pass on maliciously crafted user name and "telnet options" during server negotiation. The lack of proper input scrubbing allows an attacker to send content or perform option negotiation without the application's intent. This vulnerability could be exploited if an application allows user input, thereby enabling attackers to execute arbitrary code on the system.					
CVE-2023-27534	High	8.8	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u9
A path traversal vulnerability exists in curl <8.0.0 SFTP implementation causes the tilde (~) character to be wrongly replaced when used as a prefix in the first path element, in addition to its intended use as the first element to indicate a path relative to the user's home directory. Attackers can exploit this flaw to bypass filtering or execute arbitrary code by crafting a path like /~2/foo while accessing a server with a specific user.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-27534	High	8.8	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u9
A path traversal vulnerability exists in curl <8.0.0 SFTP implementation causes the tilde (~) character to be wrongly replaced when used as a prefix in the first path element, in addition to its intended use as the first element to indicate a path relative to the user's home directory. Attackers can exploit this flaw to bypass filtering or execute arbitrary code by crafting a path like /~2/foo while accessing a server with a specific user.					
CVE-2023-4863	High	8.8	libwebp6	0.6.1-2+deb10u1	0.6.1-2+deb10u3
Heap buffer overflow in libwebp in Google Chrome prior to 116.0.5845.187 and libwebp 1.3.2 allowed a remote attacker to perform an out of bounds memory write via a crafted HTML page. (Chromium security severity: Critical)					
CVE-2024-2961	High	8.8	libc-bin	2.28-10	2.28-10+deb10u3
The iconv() function in the GNU C Library versions 2.39 and older may overflow the output buffer passed to it by up to 4 bytes when converting strings to the ISO-2022-CN-EXT character set, which may be used to crash an application or overwrite a neighbouring variable.					
CVE-2024-2961	High	8.8	libc6	2.28-10	2.28-10+deb10u3
The iconv() function in the GNU C Library versions 2.39 and older may overflow the output buffer passed to it by up to 4 bytes when converting strings to the ISO-2022-CN-EXT character set, which may be used to crash an application or overwrite a neighbouring variable.					
CVE-2017-6363	High	8.1	libgd3	2.2.5-5.2	–
In the GD Graphics Library (aka LibGD) through 2.2.5, there is a heap-based buffer over-read in tiffWriter in gd_tiff.c. NOTE: the vendor says "In my opinion this issue should not have a CVE, since the GD and GD2 formats are documented to be 'obsolete, and should only be used for development and testing purposes.'					
CVE-2018-12886	High	8.1	gcc-8-base	8.3.0-6	–
stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against.					
CVE-2018-12886	High	8.1	libgcc1	1:8.3.0-6	–
stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against.					
CVE-2018-12886	High	8.1	libstdc++6	8.3.0-6	–
stack_protect_prologue in cfgexpand.c and stack_protect_epilogue in function.c in GNU Compiler Collection (GCC) 4.1 through 8 (under certain circumstances) generate instruction sequences when targeting ARM targets that spill the address of the stack protector guard, which allows an attacker to bypass the protection of -fstack-protector, -fstack-protector-all, -fstack-protector-strong, and -fstack-protector-explicit against stack overflow by controlling what the stack canary is compared against.					
CVE-2019-13115	High	8.1	libssh2-1	1.8.0-2.1	1.8.0-2.1+deb10u1
In libssh2 before 1.9.0, kex_method_diffie_hellman_group_exchange_sha256_key_exchange in kex.c has an integer overflow that could lead to an out-of-bounds read in the way packets are read from the server. A remote attacker who compromises a SSH server may be able to disclose sensitive information or cause a denial of service condition on the client system when a user connects to the server. This is related to an _libssh2_check_length mistake, and is different from the various issues fixed in 1.8.1, such as CVE-2019-3855.					
CVE-2019-17498	High	8.1	libssh2-1	1.8.0-2.1	1.8.0-2.1+deb10u1
In libssh2 v1.9.0 and earlier versions, the SSH_MSG_DISCONNECT logic in packet.c has an integer overflow in a bounds check, enabling an attacker to specify an arbitrary (out-of-bounds) offset for a subsequent memory read. A crafted SSH server may be able to disclose sensitive information or cause a denial of service condition on the client system when a user connects to the server.					
CVE-2019-17543	High	8.1	liblz4-1	1.8.3-1+deb10u1	–

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
LZ4 before 1.9.2 has a heap-based buffer overflow in LZ4_write32 (related to LZ4_compress_destSize), affecting applications that call LZ4_compress_fast with a large input. (This issue can also lead to data corruption.) NOTE: the vendor states "only a few specific / uncommon usages of the API are at risk."					
CVE-2020-6096	High	8.1	libc-bin	2.28-10	2.28-10+deb10u2
An exploitable signed comparison vulnerability exists in the ARMv7 memcpy() implementation of GNU glibc 2.30.9000. Calling memcpy() (on ARMv7 targets that utilize the GNU glibc implementation) with a negative value for the 'num' parameter results in a signed comparison vulnerability. If an attacker underflows the 'num' parameter to memcpy(), this vulnerability could lead to undefined behavior such as writing to out-of-bounds memory and potentially remote code execution. Furthermore, this memcpy() implementation allows for program execution to continue in scenarios where a segmentation fault or...					
CVE-2020-6096	High	8.1	libc6	2.28-10	2.28-10+deb10u2
An exploitable signed comparison vulnerability exists in the ARMv7 memcpy() implementation of GNU glibc 2.30.9000. Calling memcpy() (on ARMv7 targets that utilize the GNU glibc implementation) with a negative value for the 'num' parameter results in a signed comparison vulnerability. If an attacker underflows the 'num' parameter to memcpy(), this vulnerability could lead to undefined behavior such as writing to out-of-bounds memory and potentially remote code execution. Furthermore, this memcpy() implementation allows for program execution to continue in scenarios where a segmentation fault or...					
CVE-2022-22576	High	8.1	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
An improper authentication vulnerability exists in curl 7.33.0 to and including 7.82.0 which might allow reuse OAUTH2-authenticated connections without properly making sure that the connection was authenticated with the same credentials as set for this transfer. This affects SASL-enabled protocols: SMPTP(S), IMAP(S), POP3(S) and LDAP(S) (openldap only).					
CVE-2022-22576	High	8.1	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
An improper authentication vulnerability exists in curl 7.33.0 to and including 7.82.0 which might allow reuse OAUTH2-authenticated connections without properly making sure that the connection was authenticated with the same credentials as set for this transfer. This affects SASL-enabled protocols: SMPTP(S), IMAP(S), POP3(S) and LDAP(S) (openldap only).					
CVE-2022-40674	High	8.1	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u5
libexpat before 2.4.9 has a use-after-free in the doContent function in xmlparse.c.					
CVE-2023-31484	High	8.1	perl-base	5.28.1-6+deb10u1	—
CPAN.pm before 2.35 does not verify TLS certificates when downloading distributions over HTTPS.					
CVE-2019-3843	High	7.8	libsystemd0	241-7~deb10u7	—
It was discovered that a systemd service that uses DynamicUser property can create a SUID/SGID binary that would be allowed to run as the transient service UID/GID even after the service is terminated. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the UID/GID will be recycled.					
CVE-2019-3843	High	7.8	libudev1	241-7~deb10u7	—
It was discovered that a systemd service that uses DynamicUser property can create a SUID/SGID binary that would be allowed to run as the transient service UID/GID even after the service is terminated. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the UID/GID will be recycled.					
CVE-2019-3844	High	7.8	libsystemd0	241-7~deb10u7	—
It was discovered that a systemd service that uses DynamicUser property can get new privileges through the execution of SUID binaries, which would allow to create binaries owned by the service transient group with the setgid bit set. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the GID will be recycled.					
CVE-2019-3844	High	7.8	libudev1	241-7~deb10u7	—

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
It was discovered that a systemd service that uses DynamicUser property can get new privileges through the execution of SUID binaries, which would allow to create binaries owned by the service transient group with the setgid bit set. A local attacker may use this flaw to access resources that will be owned by a potentially different service in the future, when the GID will be recycled.					
CVE-2020-16156	● High	7.8	perl-base	5.28.1-6+deb10u1	—
CPAN 2.28 allows Signature Verification Bypass.					
CVE-2021-3999	● High	7.8	libc-bin	2.28-10	2.28-10+deb10u2
A flaw was found in glibc. An off-by-one buffer overflow and underflow in getcwd() may lead to memory corruption when the size of the buffer is exactly 1. A local attacker who can control the input buffer and size passed to getcwd() in a setuid program could use this flaw to potentially execute arbitrary code and escalate their privileges on the system.					
CVE-2021-3999	● High	7.8	libc6	2.28-10	2.28-10+deb10u2
A flaw was found in glibc. An off-by-one buffer overflow and underflow in getcwd() may lead to memory corruption when the size of the buffer is exactly 1. A local attacker who can control the input buffer and size passed to getcwd() in a setuid program could use this flaw to potentially execute arbitrary code and escalate their privileges on the system.					
CVE-2021-46143	● High	7.8	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
In doProlog in xmlparse.c in Expat (aka libexpat) before 2.4.3, an integer overflow exists for m_groupSize.					
CVE-2022-1304	● High	7.8	e2fsprogs	1.44.5-1+deb10u3	—
An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem.					
CVE-2022-1304	● High	7.8	libcom-err2	1.44.5-1+deb10u3	—
An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem.					
CVE-2022-1304	● High	7.8	libext2fs2	1.44.5-1+deb10u3	—
An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem.					
CVE-2022-1304	● High	7.8	libss2	1.44.5-1+deb10u3	—
An out-of-bounds read/write vulnerability was found in e2fsprogs 1.46.5. This issue leads to a segmentation fault and possibly arbitrary code execution via a specially crafted filesystem.					
CVE-2022-40304	● High	7.8	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u5
An issue was discovered in libxml2 before 2.10.3. Certain invalid XML entity definitions can corrupt a hash table key, potentially leading to subsequent logic errors. In one case, a double-free can be provoked.					
CVE-2023-26604	● High	7.8	libsystemd0	241-7~deb10u7	241-7~deb10u9
systemd before 247 does not adequately block local privilege escalation for some Sudo configurations, e.g., plausible sudoers files in which the "systemctl status" command may be executed. Specifically, systemd does not set LESSSECURE to 1, and thus other programs may be launched from the less program. This presents a substantial security risk when running systemctl from Sudo, because less executes as root when the terminal size is too small to show the complete systemctl output.					
CVE-2023-26604	● High	7.8	libudev1	241-7~deb10u7	241-7~deb10u9
systemd before 247 does not adequately block local privilege escalation for some Sudo configurations, e.g., plausible sudoers files in which the "systemctl status" command may be executed. Specifically, systemd does not set LESSSECURE to 1, and thus other programs may be					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
launched from the less program. This presents a substantial security risk when running systemctl from Sudo, because less executes as root when the terminal size is too small to show the complete systemctl output.					
CVE-2023-29491	High	7.8	libncursesw6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable.					
CVE-2023-29491	High	7.8	libtinfo6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable.					
CVE-2023-29491	High	7.8	ncurses-base	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable.					
CVE-2023-29491	High	7.8	ncurses-bin	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u5
ncurses before 6.4 20230408, when used by a setuid application, allows local users to trigger security-relevant memory corruption via malformed data in a terminfo database file that is found in $HOME/.terminfo or reached via the TERMINFO or TERM environment variable.					
CVE-2023-43787	High	7.8	libx11-6	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4
A vulnerability was found in libX11 due to an integer overflow within the XCreateImage() function. This flaw allows a local user to trigger an integer overflow and execute arbitrary code with elevated privileges.					
CVE-2023-43787	High	7.8	libx11-data	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4
A vulnerability was found in libX11 due to an integer overflow within the XCreateImage() function. This flaw allows a local user to trigger an integer overflow and execute arbitrary code with elevated privileges.					
CVE-2024-33599	High	7.6	libc-bin	2.28-10	2.28-10+deb10u4
nscd: Stack-based buffer overflow in netgroup cache If the Name Service Cache Daemon's (nscd) fixed size cache is exhausted by client requests then a subsequent client request for netgroup data may result in a stack-based buffer overflow. This flaw was introduced in glibc 2.15 when the cache was added to nscd. This vulnerability is only present in the nscd binary.					
CVE-2024-33599	High	7.6	libc6	2.28-10	2.28-10+deb10u4
nscd: Stack-based buffer overflow in netgroup cache If the Name Service Cache Daemon's (nscd) fixed size cache is exhausted by client requests then a subsequent client request for netgroup data may result in a stack-based buffer overflow. This flaw was introduced in glibc 2.15 when the cache was added to nscd. This vulnerability is only present in the nscd binary.					
CVE-2017-16932	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u2	—

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
parser.c in libxml2 before 2.9.5 does not prevent infinite recursion in parameter entities.					
CVE-2018-14553	High	7.5	libgd3	2.2.5-5.2	2.2.5-5.2+deb10u1
gdImageClone in gd.c in libgd 2.1.0-rc2 through 2.2.5 has a NULL pointer dereference allowing attackers to crash an application via a specific function call sequence. Only affects PHP when linked with an external libgd (not bundled).					
CVE-2018-25032	High	7.5	zlib1g	1:1.2.11.dfsg-1	1:1.2.11.dfsg-1+deb10u1
zlib before 1.2.12 allows memory corruption when deflating (i.e., when compressing) if the input has many distant matches.					
CVE-2019-12290	High	7.5	libidn2-0	2.0.5-1+deb10u1	—
GNU libidn2 before 2.2.0 fails to perform the roundtrip checks specified in RFC3490 Section 4.2 when converting A-labels to U-labels. This makes it possible in some circumstances for one domain to impersonate another. By creating a malicious domain that matches a target domain except for the inclusion of certain punycoded Unicode characters (that would be discarded when converted first to a Unicode label and then back to an ASCII label), arbitrary domains can be impersonated.					
CVE-2019-14855	High	7.5	gpgv	2.2.12-1+deb10u1	—
A flaw was found in the way certificate signatures could be forged using collisions found in the SHA-1 algorithm. An attacker could use this weakness to create forged certificate signatures. This issue affects GnuPG versions before 2.2.18.					
CVE-2019-15847	High	7.5	gcc-8-base	8.3.0-6	—
The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same.					
CVE-2019-15847	High	7.5	libgcc1	1:8.3.0-6	—
The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same.					
CVE-2019-15847	High	7.5	libstdc++6	8.3.0-6	—
The POWER9 backend in GNU Compiler Collection (GCC) before version 10 could optimize multiple calls of the __builtin_darn intrinsic into a single call, thus reducing the entropy of the random number generator. This occurred because a volatile operation was not specified. For example, within a single execution of a program, the output of every __builtin_darn() call may be the same.					
CVE-2019-5815	High	7.5	libxslt1.1	1.1.32-2.2~deb10u1	1.1.32-2.2~deb10u2
Type confusion in xsltNumberFormatGetMultipleLevel prior to libxslt 1.1.33 could allow attackers to potentially exploit heap corruption via crafted XML data.					
CVE-2020-11080	High	7.5	libnghttp2-14	1.36.0-2+deb10u1	1.36.0-2+deb10u2
In nghttp2 before version 1.41.0, the overly large HTTP/2 SETTINGS frame payload causes denial of service. The proof of concept attack involves a malicious client constructing a SETTINGS frame with a length of 14,400 bytes (2400 individual settings entries) over and over again. The attack causes the CPU to spike at 100%. nghttp2 v1.41.0 fixes this vulnerability. There is a workaround to this vulnerability. Implement nghttp2_on_frame_recv_callback callback, and if received frame is SETTINGS frame and the number of settings entries are large (e.g., > 32), then drop the connection.					
CVE-2020-22218	High	7.5	libssh2-1	1.8.0-2.1	1.8.0-2.1+deb10u1
An issue was discovered in function _libssh2_packet_add in libssh2 1.10.0 allows attackers to access out of bounds memory.					
CVE-2021-22946	High	7.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
A user can tell curl >= 7.20.0 and <= 7.78.0 to require a successful upgrade to TLS when speaking to an IMAP, POP3 or FTP server (`--ssl-reqd` on the command line or`CURLOPT_USE_SSL` set to `CURLUSESSL_CONTROL` or `CURLUSESSL_ALL` withlibcurl). This requirement					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
could be bypassed if the server would return a properly crafted but perfectly legitimate response.This flaw would then make curl silently continue its operations **withoutTLS** contrary to the instructions and expectations, exposing possibly sensitive data in clear text over the network.					
CVE-2021-22946	High	7.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
A user can tell curl >= 7.20.0 and <= 7.78.0 to require a successful upgrade to TLS when speaking to an IMAP, POP3 or FTP server (`--ssl-reqd` on the command line or`CURLOPT_USE_SSL` set to `CURLUSESSL_CONTROL` or `CURLUSESSL_ALL` withlibcurl). This requirement could be bypassed if the server would return a properly crafted but perfectly legitimate response.This flaw would then make curl silently continue its operations **withoutTLS** contrary to the instructions and expectations, exposing possibly sensitive data in clear text over the network.					
CVE-2021-3326	High	7.5	libc-bin	2.28-10	2.28-10+deb10u2
The iconv function in the GNU C Library (aka glibc or libc6) 2.32 and earlier, when processing invalid input sequences in the ISO-2022-JP-3 encoding, fails an assertion in the code path and aborts the program, potentially resulting in a denial of service.					
CVE-2021-3326	High	7.5	libc6	2.28-10	2.28-10+deb10u2
The iconv function in the GNU C Library (aka glibc or libc6) 2.32 and earlier, when processing invalid input sequences in the ISO-2022-JP-3 encoding, fails an assertion in the code path and aborts the program, potentially resulting in a denial of service.					
CVE-2021-33560	High	7.5	libgcrypt20	1.8.4-5+deb10u1	—
Libgcrypt before 1.8.8 and 1.9.x before 1.9.3 mishandles ElGamal encryption because it lacks exponent blinding to address a side-channel attack against mpi_powm, and the window size is not chosen appropriately. This, for example, affects use of ElGamal in OpenPGP.					
CVE-2021-36222	High	7.5	libgssapi-krb5-2	1.17-3+deb10u1	1.17-3+deb10u2
ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation.					
CVE-2021-36222	High	7.5	libk5crypto3	1.17-3+deb10u1	1.17-3+deb10u2
ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation.					
CVE-2021-36222	High	7.5	libkrb5-3	1.17-3+deb10u1	1.17-3+deb10u2
ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation.					
CVE-2021-36222	High	7.5	libkrb5support0	1.17-3+deb10u1	1.17-3+deb10u2
ec_verify in kdc/kdc_preauth_ec.c in the Key Distribution Center (KDC) in MIT Kerberos 5 (aka krb5) before 1.18.4 and 1.19.x before 1.19.2 allows remote attackers to cause a NULL pointer dereference and daemon crash. This occurs because a return value is not properly managed in a certain situation.					
CVE-2021-43618	High	7.5	libgmp10	2:6.1.2+dfsg-4	2:6.1.2+dfsg-4+deb10u1
GNU Multiple Precision Arithmetic Library (GMP) through 6.2.1 has an mpz/inp_raw.c integer overflow and resultant buffer overflow via crafted input, leading to a segmentation fault on 32-bit platforms.					
CVE-2022-0778	High	7.5	libssl1.1	1.1.1d-0+deb10u6	1.1.1d-0+deb10u8
The BN_mod_sqrt() function, which computes a modular square root, contains a bug that can cause it to loop forever for non-prime moduli. Internally this function is used when parsing certificates that contain elliptic curve public keys in compressed form or explicit elliptic curve					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
parameters with a base point encoded in compressed form. It is possible to trigger the infinite loop by crafting a certificate that has invalid explicit curve parameters. Since certificate parsing happens prior to verification of the certificate signature, any process that parses an externally supplied certificate ma...					
CVE-2022-0778	High	7.5	openssl	1.1.1d-0+deb10u6	1.1.1d-0+deb10u8
The BN_mod_sqrt() function, which computes a modular square root, contains a bug that can cause it to loop forever for non-prime moduli. Internally this function is used when parsing certificates that contain elliptic curve public keys in compressed form or explicit elliptic curve parameters with a base point encoded in compressed form. It is possible to trigger the infinite loop by crafting a certificate that has invalid explicit curve parameters. Since certificate parsing happens prior to verification of the certificate signature, any process that parses an externally supplied certificate ma...					
CVE-2022-2309	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u2	—
NULL Pointer Dereference allows attackers to cause a denial of service (or application crash). This only applies when lxml is used together with libxml2 2.9.10 through 2.9.14. libxml2 2.9.9 and earlier are not affected. It allows triggering crashes through forged input data, given a vulnerable code sequence in the application. The vulnerability is caused by the iterwalk function (also used by the canonicalize function). Such code shouldn't be in wide-spread use, given that parsing + iterwalk would usually be replaced with the more efficient iterparse function. However, an XML converter that se...					
CVE-2022-23308	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u3
valid.c in libxml2 before 2.9.13 has a use-after-free of ID and IDREF attributes.					
CVE-2022-23990	High	7.5	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u2
Expat (aka libexpat) before 2.4.4 has an integer overflow in the doProlog function.					
CVE-2022-2509	High	7.5	libgnutls30	3.6.7-4+deb10u7	3.6.7-4+deb10u9
A vulnerability found in gnutls. This security flaw happens because of a double free error occurs during verification of pkcs7 signatures in gnutls_pkcs7_verify function.					
CVE-2022-25314	High	7.5	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u3
In Expat (aka libexpat) before 2.4.5, there is an integer overflow in copyString.					
CVE-2022-27405	High	7.5	libfreetype6	2.9.1-3+deb10u2	2.9.1-3+deb10u3
FreeType commit 53dfdcd8198d2b3201a23c4bad9190519ba918db was discovered to contain a segmentation violation via the function FNT_Size_Request.					
CVE-2022-27406	High	7.5	libfreetype6	2.9.1-3+deb10u2	2.9.1-3+deb10u3
FreeType commit 22a0cccb4d9d002f33c1ba7a4b36812c7d4f46b5 was discovered to contain a segmentation violation via the function FT_Request_Size.					
CVE-2022-27781	High	7.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
libcurl provides the `CURLOPT_CERTINFO` option to allow applications torequest details to be returned about a server's certificate chain.Due to an erroneous function, a malicious server could make libcurl built withNSS get stuck in a never-ending busy-loop when trying to retrieve thatinformation.					
CVE-2022-27781	High	7.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
libcurl provides the `CURLOPT_CERTINFO` option to allow applications torequest details to be returned about a server's certificate chain.Due to an erroneous function, a malicious server could make libcurl built withNSS get stuck in a never-ending busy-loop when trying to retrieve thatinformation.					
CVE-2022-27782	High	7.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
libcurl would reuse a previously created connection even when a TLS or SSHrelated option had been changed that should have prohibited reuse.libcurl keeps previously used connections in a connection pool for subsequenttransfers to reuse if one of them matches the setup. However, several TLS andSSH settings were left out from the configuration match checks, making themmatch too easily.					
CVE-2022-27782	High	7.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
libcurl would reuse a previously created connection even when a TLS or SSHrelated option had been changed that should have prohibited reuse.libcurl keeps previously used connections in a connection pool for subsequenttransfers to reuse if one of them matches the setup. However, several TLS andSSH settings were left out from the configuration match checks, making themmatch too easily.					
CVE-2022-40303	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u5
An issue was discovered in libxml2 before 2.10.3. When parsing a multi-gigabyte XML document with the XML_PARSE_HUGE parser option enabled, several integer counters can overflow. This results in an attempt to access an array at a negative 2GB offset, typically leading to a segmentation fault.					
CVE-2022-43680	High	7.5	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u6
In libexpat through 2.4.9, there is a use-after free caused by overeager destruction of a shared DTD in XML_ExternalEntityParserCreate in out-of-memory situations.					
CVE-2022-4450	High	7.5	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
The function PEM_read_bio_ex() reads a PEM file from a BIO and parses and decodes the "name" (e.g. "CERTIFICATE"), any header data and the payload data. If the function succeeds then the "name_out", "header" and "data" arguments are populated with pointers to buffers containing the relevant decoded data. The caller is responsible for freeing those buffers. It is possible to construct a PEM file that results in 0 bytes of payload data. In this case PEM_read_bio_ex() will return a failure code but will populate the header argument with a pointer to a buffer that has already been freed. If the ca...					
CVE-2022-4450	High	7.5	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
The function PEM_read_bio_ex() reads a PEM file from a BIO and parses and decodes the "name" (e.g. "CERTIFICATE"), any header data and the payload data. If the function succeeds then the "name_out", "header" and "data" arguments are populated with pointers to buffers containing the relevant decoded data. The caller is responsible for freeing those buffers. It is possible to construct a PEM file that results in 0 bytes of payload data. In this case PEM_read_bio_ex() will return a failure code but will populate the header argument with a pointer to a buffer that has already been freed. If the ca...					
CVE-2022-44617	High	7.5	libxpm4	1:3.5.12-1	1:3.5.12-1+deb10u1
A flaw was found in libXpm. When processing a file with width of 0 and a very large height, some parser functions will be called repeatedly and can lead to an infinite loop, resulting in a Denial of Service in the application linked to the library.					
CVE-2022-46285	High	7.5	libxpm4	1:3.5.12-1	1:3.5.12-1+deb10u1
A flaw was found in libXpm. This issue occurs when parsing a file with a comment not closed; the end-of-file condition will not be detected, leading to an infinite loop and resulting in a Denial of Service in the application linked to the library.					
CVE-2023-0215	High	7.5	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
The public API function BIO_new_NDEF is a helper function used for streaming ASN.1 data via a BIO. It is primarily used internally to OpenSSL to support the SMIME, CMS and PKCS7 streaming capabilities, but may also be called directly by end user applications. The function receives a BIO from the caller, prepends a new BIO_f_asn1 filter BIO onto the front of it to form a BIO chain, and then returns the new head of					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
the BIO chain to the caller. Under certain conditions, for example if a CMS recipient public key is invalid, the new filter BIO is freed and the function returns a NULL result indica...					
CVE-2023-0215	High	7.5	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
The public API function BIO_new_NDEF is a helper function used for streaming ASN.1 data via a BIO. It is primarily used internally to OpenSSL to support the SMIME, CMS and PKCS7 streaming capabilities, but may also be called directly by end user applications. The function receives a BIO from the caller, prepends a new BIO_f_asn1 filter BIO onto the front of it to form a BIO chain, and then returns the new head of the BIO chain to the caller. Under certain conditions, for example if a CMS recipient public key is invalid, the new filter BIO is freed and the function returns a NULL result indica...					
CVE-2023-0464	High	7.5	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
A security vulnerability has been identified in all supported versions of OpenSSL related to the verification of X.509 certificate chains that include policy constraints. Attackers may be able to exploit this vulnerability by creating a malicious certificate chain that triggers exponential use of computational resources, leading to a denial-of-service (DoS) attack on affected systems. Policy processing is disabled by default but can be enabled by passing the `-policy' argument to the command line utilities or by calling the `X509_VERIFY_PARAM_set1_policies()' function.					
CVE-2023-0464	High	7.5	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
A security vulnerability has been identified in all supported versions of OpenSSL related to the verification of X.509 certificate chains that include policy constraints. Attackers may be able to exploit this vulnerability by creating a malicious certificate chain that triggers exponential use of computational resources, leading to a denial-of-service (DoS) attack on affected systems. Policy processing is disabled by default but can be enabled by passing the `-policy' argument to the command line utilities or by calling the `X509_VERIFY_PARAM_set1_policies()' function.					
CVE-2023-1999	High	7.5	libwebp6	0.6.1-2+deb10u1	0.6.1-2+deb10u2
There exists a use after free/double free in libwebp. An attacker can use the ApplyFiltersAndEncode() function and loop through to free best.bw and assign best = trial pointer. The second loop will then return 0 because of an Out of memory error in VP8 encoder, the pointer is still assigned to trial and the AddressSanitizer will attempt a double free.					
CVE-2023-2953	High	7.5	libldap-2.4-2	2.4.47+dfsg-3+deb10u6	—
A vulnerability was found in openldap. This security flaw causes a null pointer dereference in ber_memalloc_x() function.					
CVE-2023-2953	High	7.5	libldap-common	2.4.47+dfsg-3+deb10u6	—
A vulnerability was found in openldap. This security flaw causes a null pointer dereference in ber_memalloc_x() function.					
CVE-2023-3138	High	7.5	libx11-6	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u3
A vulnerability was found in libX11. The security flaw occurs because the functions in src/InitExt.c in libX11 do not check that the values provided for the Request, Event, or Error IDs are within the bounds of the arrays that those functions write to, using those IDs as array					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
indexes. They trust that they were called with values provided by an Xserver adhering to the bounds specified in the X11 protocol, as all X servers provided by X.Org do. As the protocol only specifies a single byte for these values, an out-of-bounds value provided by a malicious server (or a malicious proxy-in-the-middle...					
CVE-2023-3138	High	7.5	libx11-data	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u3
A vulnerability was found in libX11. The security flaw occurs because the functions in src/InitExt.c in libX11 do not check that the values provided for the Request, Event, or Error IDs are within the bounds of the arrays that those functions write to, using those IDs as array indexes. They trust that they were called with values provided by an Xserver adhering to the bounds specified in the X11 protocol, as all X servers provided by X.Org do. As the protocol only specifies a single byte for these values, an out-of-bounds value provided by a malicious server (or a malicious proxy-in-the-middle...					
CVE-2023-44487	High	7.5	libnghttp2-14	1.36.0-2+deb10u1	1.36.0-2+deb10u2
The HTTP/2 protocol allows a denial of service (server resource consumption) because request cancellation can reset many streams quickly, as exploited in the wild in August through October 2023.					
CVE-2023-50387	High	7.5	libsystemd0	241-7~deb10u7	–
Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the "KeyTrap" issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records.					
CVE-2023-50387	High	7.5	libudev1	241-7~deb10u7	–
Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the "KeyTrap" issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records.					
CVE-2023-50868	High	7.5	libsystemd0	241-7~deb10u7	–
The Closest Encloser Proof aspect of the DNS protocol (in RFC 5155 when RFC 9276 guidance is skipped) allows remote attackers to cause a denial of service (CPU consumption for SHA-1 computations) via DNSSEC responses in a random subdomain attack, aka the "NSEC3" issue. The RFC 5155 specification implies that an algorithm must perform thousands of iterations of a hash function in certain situations.					
CVE-2023-50868	High	7.5	libudev1	241-7~deb10u7	–
The Closest Encloser Proof aspect of the DNS protocol (in RFC 5155 when RFC 9276 guidance is skipped) allows remote attackers to cause a denial of service (CPU consumption for SHA-1 computations) via DNSSEC responses in a random subdomain attack, aka the "NSEC3" issue. The RFC 5155 specification implies that an algorithm must perform thousands of iterations of a hash function in certain situations.					
CVE-2023-52355	High	7.5	libtiff5	4.1.0+git191117-2~deb10u2	–
An out-of-memory flaw was found in libtiff that could be triggered by passing a crafted tiff file to the TIFFRasterScanlineSize64() API. This flaw allows a remote attacker to cause a denial of service via a crafted input with a size smaller than 379 KB.					
CVE-2023-52356	High	7.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u9
A segment fault (SEGV) flaw was found in libtiff that could be triggered by passing a crafted tiff file to the TIFFReadRGBATileExt() API. This flaw allows a remote attacker to cause a heap-buffer overflow, leading to a denial of service.					
CVE-2023-52425	High	7.5	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u7
libexpat through 2.5.0 allows a denial of service (resource consumption) because many full reparsings are required in the case of a large token for which multiple buffer fills are needed.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2024-0553	High	7.5	libgnutls30	3.6.7-4+deb10u7	3.6.7-4+deb10u12

A vulnerability was found in GnuTLS. The response times to malformed ciphertexts in RSA-PSK ClientKeyExchange differ from the response times of ciphertexts with correct PKCS#1 v1.5 padding. This issue may allow a remote attacker to perform a timing side-channel attack in the RSA-PSK key exchange, potentially leading to the leakage of sensitive data. CVE-2024-0553 is designated as an incomplete resolution for CVE-2023-5981.

CVE-2024-2398	High	7.5	curl	7.64.0-4+deb10u2	—

When an application tells libcurl it wants to allow HTTP/2 server push, and the amount of received headers for the push surpasses the maximum allowed limit (1000), libcurl aborts the server push. When aborting, libcurl inadvertently does not free all the previously allocated headers and instead leaks the memory. Further, this error condition fails silently and is therefore not easily detected by an application.

CVE-2024-2398	High	7.5	libcurl4	7.64.0-4+deb10u2	—

When an application tells libcurl it wants to allow HTTP/2 server push, and the amount of received headers for the push surpasses the maximum allowed limit (1000), libcurl aborts the server push. When aborting, libcurl inadvertently does not free all the previously allocated headers and instead leaks the memory. Further, this error condition fails silently and is therefore not easily detected by an application.

CVE-2024-25062	High	7.5	libxml2	2.9.4+dfsg1-7+deb10u2	—

An issue was discovered in libxml2 before 2.11.7 and 2.12.x before 2.12.5. When using the XML Reader interface with DTD validation and XInclude expansion enabled, processing crafted XML documents can lead to an xmlValidatePopElement use-after-free.

CVE-2021-3712	High	7.4	libssl1.1	1.1.1d-0+deb10u6	1.1.1d-0+deb10u7

ASN.1 strings are represented internally within OpenSSL as an ASN1_STRING structure which contains a buffer holding the string data and a field holding the buffer length. This contrasts with normal C strings which are repesented as a buffer for the string data which is terminated with a NUL (0) byte. Although not a strict requirement, ASN.1 strings that are parsed using OpenSSL's own "d2i" functions (and other similar parsing functions) as well as any string whose value has been set with the ASN1_STRING_set() function will additionally NUL terminate the byte array in the ASN1_STRING structure....

CVE-2021-3712	High	7.4	openssl	1.1.1d-0+deb10u6	1.1.1d-0+deb10u7

ASN.1 strings are represented internally within OpenSSL as an ASN1_STRING structure which contains a buffer holding the string data and a field holding the buffer length. This contrasts with normal C strings which are repesented as a buffer for the string data which is terminated with a NUL (0) byte. Although not a strict requirement, ASN.1 strings that are parsed using OpenSSL's own "d2i" functions (and other similar parsing functions) as well as any string whose value has been set with the ASN1_STRING_set() function will additionally NUL terminate the byte array in the ASN1_STRING structure....

CVE-2023-0286	High	7.4	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4

There is a type confusion vulnerability relating to X.400 address processing inside an X.509 GeneralName. X.400 addresses were parsed as an ASN1_STRING but the public structure definition for GENERAL_NAME incorrectly specified the type of the x400Address field as ASN1_TYPE. This field is subsequently interpreted by the OpenSSL function GENERAL_NAME_cmp as an ASN1_TYPE rather than an ASN1_STRING.

When CRL checking is enabled (i.e. the application sets the X509_V_FLAG_CRL_CHECK flag), this vulnerability may allow an attacker to pass arbitrary pointers to a memcmp call, enabling them to read mem...

CVE-2023-0286	High	7.4	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4

There is a type confusion vulnerability relating to X.400 address processing inside an X.509 GeneralName. X.400 addresses were parsed as an ASN1_STRING but the public structure definition for GENERAL_NAME incorrectly specified the type of the x400Address field as ASN1_TYPE. This field is subsequently interpreted by the OpenSSL function GENERAL_NAME_cmp as an ASN1_TYPE rather than an ASN1_STRING.

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
When CRL checking is enabled (i.e. the application sets the X509_V_FLAG_CRL_CHECK flag), this vulnerability may allow an attacker to pass arbitrary pointers to a memcmp call, enabling them to read mem...					
CVE-2023-0361	High	7.4	libgnutls30	3.6.7-4+deb10u7	3.6.7-4+deb10u10
A timing side-channel in the handling of RSA ClientKeyExchange messages was discovered in GnuTLS. This side-channel can be sufficient to recover the key encrypted in the RSA ciphertext across a network in a Bleichenbacher style attack. To achieve a successful decryption the attacker would need to send a large amount of specially crafted messages to the vulnerable server. By recovering the secret from the ClientKeyExchange message, the attacker would be able to decrypt the application data exchanged over that connection.					
CVE-2022-1292	High	7.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u2
The c_rehash script does not properly sanitise shell metacharacters to prevent command injection. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbitrary commands with the privileges of the script. Use of the c_rehash script is considered obsolete and should be replaced by the OpenSSL rehash command line tool. Fixed in OpenSSL 3.0.3 (Affected 3.0.0,3.0.1,3.0.2). Fixed in OpenSSL 1.1.1o (Affected 1.1.1-1.1.1n). Fixed in OpenSSL 1.0.2ze (Affected 1.0.2-1.0.2zd).					
CVE-2022-1292	High	7.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u2
The c_rehash script does not properly sanitise shell metacharacters to prevent command injection. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbitrary commands with the privileges of the script. Use of the c_rehash script is considered obsolete and should be replaced by the OpenSSL rehash command line tool. Fixed in OpenSSL 3.0.3 (Affected 3.0.0,3.0.1,3.0.2). Fixed in OpenSSL 1.1.1o (Affected 1.1.1-1.1.1n). Fixed in OpenSSL 1.0.2ze (Affected 1.0.2-1.0.2zd).					
CVE-2022-2068	High	7.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u3
In addition to the c_rehash shell command injection identified in CVE-2022-1292, further circumstances where the c_rehash script does not properly sanitise shell metacharacters to prevent command injection were found by code review. When the CVE-2022-1292 was fixed it was not discovered that there are other places in the script where the file names of certificates being hashed were possibly passed to a command executed through the shell. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbi...					
CVE-2022-2068	High	7.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u3
In addition to the c_rehash shell command injection identified in CVE-2022-1292, further circumstances where the c_rehash script does not properly sanitise shell metacharacters to prevent command injection were found by code review. When the CVE-2022-1292 was fixed it was not discovered that there are other places in the script where the file names of certificates being hashed were possibly passed to a command executed through the shell. This script is distributed by some operating systems in a manner where it is automatically executed. On such operating systems, an attacker could execute arbi...					
CVE-2022-0891	High	7.1	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
A heap buffer overflow in ExtractImageSection function in tiffcrop.c in libtiff library Version 4.3.0 allows attacker to trigger unsafe or out of bounds memory access via crafted TIFF image file which could result into application crash, potential information disclosure or any other context-dependent impact					
CVE-2022-29458	High	7.1	libncursesw6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u3
ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library.					
CVE-2022-29458	High	7.1	libtinfo6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u3
ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-29458	High	7.1	ncurses-base	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u3
ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library.					
CVE-2022-29458	High	7.1	ncurses-bin	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u3
ncurses 6.3 before patch 20220416 has an out-of-bounds read and segmentation violation in convert_strings in tinfo/read_entry.c in the terminfo library.					
CVE-2020-1751	High	7.0	libc-bin	2.28-10	–
An out-of-bounds write vulnerability was found in glibc before 2.31 when handling signal trampolines on PowerPC. Specifically, the backtrace function did not properly check the array bounds when storing the frame address, resulting in a denial of service or potential code execution. The highest threat from this vulnerability is to system availability.					
CVE-2020-1751	High	7.0	libc6	2.28-10	–
An out-of-bounds write vulnerability was found in glibc before 2.31 when handling signal trampolines on PowerPC. Specifically, the backtrace function did not properly check the array bounds when storing the frame address, resulting in a denial of service or potential code execution. The highest threat from this vulnerability is to system availability.					
CVE-2020-1752	High	7.0	libc-bin	2.28-10	2.28-10+deb10u2
A use-after-free vulnerability introduced in glibc upstream version 2.14 was found in the way the tilde expansion was carried out. Directory paths containing an initial tilde followed by a valid username were affected by this issue. A local attacker could exploit this flaw by creating a specially crafted path that, when processed by the glob function, would potentially lead to arbitrary code execution. This was fixed in version 2.32.					
CVE-2020-1752	High	7.0	libc6	2.28-10	2.28-10+deb10u2
A use-after-free vulnerability introduced in glibc upstream version 2.14 was found in the way the tilde expansion was carried out. Directory paths containing an initial tilde followed by a valid username were affected by this issue. A local attacker could exploit this flaw by creating a specially crafted path that, when processed by the glob function, would potentially lead to arbitrary code execution. This was fixed in version 2.32.					
CVE-2016-2781	Medium	6.5	coreutils	8.30-3	–
CVE-2020-19143	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u3
CVE-2020-19189	Medium	6.5	libncursesw6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u4
CVE-2020-19189	Medium	6.5	libtinfo6	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u4
CVE-2020-19189	Medium	6.5	ncurses-base	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u4
CVE-2020-19189	Medium	6.5	ncurses-bin	6.1+20181013-2+deb10u2	6.1+20181013-2+deb10u4
CVE-2021-37750	Medium	6.5	libgssapi-krb5-2	1.17-3+deb10u1	1.17-3+deb10u3
CVE-2021-37750	Medium	6.5	libk5crypto3	1.17-3+deb10u1	1.17-3+deb10u3

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2021-37750	Medium	6.5	libkrb5-3	1.17-3+deb10u1	1.17-3+deb10u3
CVE-2021-37750	Medium	6.5	libkrb5support0	1.17-3+deb10u1	1.17-3+deb10u3
CVE-2021-38115	Medium	6.5	libgd3	2.2.5-5.2	2.2.5-5.2+deb10u1
CVE-2021-40812	Medium	6.5	libgd3	2.2.5-5.2	2.2.5-5.2+deb10u1
CVE-2021-4209	Medium	6.5	libgnutls30	3.6.7-4+deb10u7	3.6.7-4+deb10u9
CVE-2022-0865	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-1210	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	–
CVE-2022-2056	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-2057	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-2058	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-25313	Medium	6.5	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u3
CVE-2022-27776	Medium	6.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-27776	Medium	6.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-29824	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u4
CVE-2022-32206	Medium	6.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-32206	Medium	6.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-34526	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-34903	Medium	6.5	gpgv	2.2.12-1+deb10u1	2.2.12-1+deb10u2
CVE-2022-3597	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-3598	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-3599	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-3626	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-3627	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-40090	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	—
CVE-2023-23916	Medium	6.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u5
CVE-2023-23916	Medium	6.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u5
CVE-2023-2650	Medium	6.5	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-2650	Medium	6.5	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-28484	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u6
CVE-2023-29469	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u2	2.9.4+dfsg1-7+deb10u6
CVE-2023-3316	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-36054	Medium	6.5	libgssapi-krb5-2	1.17-3+deb10u1	1.17-3+deb10u6
CVE-2023-36054	Medium	6.5	libk5crypto3	1.17-3+deb10u1	1.17-3+deb10u6
CVE-2023-36054	Medium	6.5	libkrb5-3	1.17-3+deb10u1	1.17-3+deb10u6
CVE-2023-36054	Medium	6.5	libkrb5support0	1.17-3+deb10u1	1.17-3+deb10u6
CVE-2023-3618	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-39615	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u2	—
CVE-2023-40745	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-41175	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-45322	Medium	6.5	libxml2	2.9.4+dfsg1-7+deb10u2	—

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-46218	Medium	6.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u8
CVE-2023-46218	Medium	6.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u8
CVE-2023-50495	Medium	6.5	libncursesw6	6.1+20181013-2+deb10u2	—
CVE-2023-50495	Medium	6.5	libtinfo6	6.1+20181013-2+deb10u2	—
CVE-2023-50495	Medium	6.5	ncurses-base	6.1+20181013-2+deb10u2	—
CVE-2023-50495	Medium	6.5	ncurses-bin	6.1+20181013-2+deb10u2	—
CVE-2023-6277	Medium	6.5	libtiff5	4.1.0+git191117-2~deb10u2	—
CVE-2019-13627	Medium	6.3	libgcrypt20	1.8.4-5+deb10u1	—
CVE-2016-3709	Medium	6.1	libxml2	2.9.4+dfsg1-7+deb10u2	—
CVE-2022-1355	Medium	6.1	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2016-10228	Medium	5.9	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2016-10228	Medium	5.9	libc6	2.28-10	2.28-10+deb10u2
CVE-2019-25013	Medium	5.9	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2019-25013	Medium	5.9	libc6	2.28-10	2.28-10+deb10u2
CVE-2021-22947	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2021-22947	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2021-4160	Medium	5.9	libssl1.1	1.1.1d-0+deb10u6	1.1.1d-0+deb10u8
CVE-2021-4160	Medium	5.9	openssl	1.1.1d-0+deb10u6	1.1.1d-0+deb10u8
CVE-2022-32208	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-32208	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-4304	Medium	5.9	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-4304	Medium	5.9	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
CVE-2022-43552	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2022-43552	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2023-27535	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-27535	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-27536	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-27536	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-28321	Medium	5.9	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u7
CVE-2023-28321	Medium	5.9	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u7
CVE-2023-4806	Medium	5.9	libc-bin	2.28-10	—
CVE-2023-4806	Medium	5.9	libc6	2.28-10	—
CVE-2023-4813	Medium	5.9	libc-bin	2.28-10	—
CVE-2023-4813	Medium	5.9	libc6	2.28-10	—
CVE-2023-5981	Medium	5.9	libgnutls30	3.6.7-4+deb10u7	3.6.7-4+deb10u11
CVE-2023-7008	Medium	5.9	libsystemd0	241-7~deb10u7	—
CVE-2023-7008	Medium	5.9	libudev1	241-7~deb10u7	—
CVE-2022-27774	Medium	5.7	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2022-27774	Medium	5.7	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2024-4741	Medium	5.6	libssl1.1	1.1.1d-0+deb10u6	—
CVE-2024-4741	Medium	5.6	openssl	1.1.1d-0+deb10u6	—
CVE-2016-9318	Medium	5.5	libxml2	2.9.4+dfsg1-7+deb10u2	—
CVE-2020-10029	Medium	5.5	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2020-10029	Medium	5.5	libc6	2.28-10	2.28-10+deb10u2
CVE-2020-21913	Medium	5.5	libicu63	63.1-6+deb10u1	63.1-6+deb10u2

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-27618	Medium	5.5	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2020-27618	Medium	5.5	libc6	2.28-10	2.28-10+deb10u2
CVE-2020-35538	Medium	5.5	libjpeg62-turbo	1:1.5.2-2+deb10u1	—
CVE-2021-33910	Medium	5.5	libsystemd0	241-7~deb10u7	241-7~deb10u8
CVE-2021-33910	Medium	5.5	libudev1	241-7~deb10u7	241-7~deb10u8
CVE-2021-37600	Medium	5.5	bsdutils	1:2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	fdisk	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	libblkid1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	libfdisk1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	libmount1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	libsmartcols1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	libuuid1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	mount	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-37600	Medium	5.5	util-linux	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2021-3997	Medium	5.5	libsystemd0	241-7~deb10u7	—
CVE-2021-3997	Medium	5.5	libudev1	241-7~deb10u7	—
CVE-2021-46822	Medium	5.5	libjpeg62-turbo	1:1.5.2-2+deb10u1	—
CVE-2022-0561	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-0562	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-0907	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-0908	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-0909	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-0924	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-1354	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-22844	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u4
CVE-2022-2867	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-2868	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-2869	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-3570	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-3821	Medium	5.5	libsystemd0	241-7~deb10u7	241-7~deb10u10
CVE-2022-3821	Medium	5.5	libudev1	241-7~deb10u7	241-7~deb10u10
CVE-2022-4415	Medium	5.5	libsystemd0	241-7~deb10u7	—
CVE-2022-4415	Medium	5.5	libudev1	241-7~deb10u7	—
CVE-2022-4645	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2022-48281	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u6
CVE-2023-0795	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0796	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0797	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0798	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-0799	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0800	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0801	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0802	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0803	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-0804	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-25433	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-25435	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u7
CVE-2023-26965	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-26966	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-27538	Medium	5.5	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-27538	Medium	5.5	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u6
CVE-2023-2908	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u8
CVE-2023-30086	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2023-30774	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u5
CVE-2023-3576	Medium	5.5	libtiff5	4.1.0+git191117-2~deb10u2	4.1.0+git191117-2~deb10u9
CVE-2023-43785	Medium	5.5	libx11-6	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4
CVE-2023-43785	Medium	5.5	libx11-data	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-43786	Medium	5.5	libx11-6	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4
CVE-2023-43786	Medium	5.5	libx11-data	2:1.6.7-1+deb10u2	2:1.6.7-1+deb10u4
CVE-2023-43788	Medium	5.5	libxpm4	1:3.5.12-1	1:3.5.12-1+deb10u2
CVE-2023-43789	Medium	5.5	libxpm4	1:3.5.12-1	1:3.5.12-1+deb10u2
CVE-2023-4641	Medium	5.5	login	1:4.5-1.1	—
CVE-2023-4641	Medium	5.5	passwd	1:4.5-1.1	—
CVE-2024-0727	Medium	5.5	libssl1.1	1.1.1d-0+deb10u6	—
CVE-2024-0727	Medium	5.5	openssl	1.1.1d-0+deb10u6	—
CVE-2024-22365	Medium	5.5	libpam-modules	1.3.1-5	—
CVE-2024-22365	Medium	5.5	libpam-modules-bin	1.3.1-5	—
CVE-2024-22365	Medium	5.5	libpam-runtime	1.3.1-5	—
CVE-2024-22365	Medium	5.5	libpam0g	1.3.1-5	—
CVE-2018-7169	Medium	5.3	login	1:4.5-1.1	—
CVE-2018-7169	Medium	5.3	passwd	1:4.5-1.1	—
CVE-2020-14155	Medium	5.3	libpcre3	2:8.39-12	—
CVE-2022-2097	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
CVE-2022-2097	Medium	5.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u4
CVE-2023-0465	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-0465	Medium	5.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-0466	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-0466	Medium	5.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u5
CVE-2023-3446	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u6
CVE-2023-3446	Medium	5.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u6
CVE-2023-3817	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	1.1.1n-0+deb10u6
CVE-2023-3817	Medium	5.3	openssl	1.1.1d-0+deb10u6	1.1.1n-0+deb10u6
CVE-2023-5678	Medium	5.3	libssl1.1	1.1.1d-0+deb10u6	—

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-5678	Medium	5.3	openssl	1.1.1d-0+deb10u6	—
CVE-2024-28182	Medium	5.3	libnghttp2-14	1.36.0-2+deb10u1	1.36.0-2+deb10u3
CVE-2024-33600	Medium	5.3	libc-bin	2.28-10	2.28-10+deb10u4
CVE-2024-33600	Medium	5.3	libc6	2.28-10	2.28-10+deb10u4
CVE-2024-28085	Medium	4.4	bsdutils	1:2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	fdisk	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	libblkid1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	libfdisk1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	libmount1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	libsmartcols1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	libuuid1	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	mount	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-28085	Medium	4.4	util-linux	2.33.1-0.1	2.33.1-0.1+deb10u1
CVE-2024-33601	Medium	4.0	libc-bin	2.28-10	2.28-10+deb10u4
CVE-2024-33601	Medium	4.0	libc6	2.28-10	2.28-10+deb10u4
CVE-2024-33602	Medium	4.0	libc-bin	2.28-10	2.28-10+deb10u4
CVE-2024-33602	Medium	4.0	libc6	2.28-10	2.28-10+deb10u4
CVE-2021-22924	Low	3.7	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2021-22924	Low	3.7	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2022-35252	Low	3.7	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2022-35252	Low	3.7	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u4
CVE-2023-28322	Low	3.7	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u8
CVE-2023-28322	Low	3.7	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u8

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2023-38546	Low	3.7	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u7
CVE-2023-38546	Low	3.7	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u7
CVE-2024-2511	Low	3.7	libssl1.1	1.1.1d-0+deb10u6	—
CVE-2024-2511	Low	3.7	openssl	1.1.1d-0+deb10u6	—
CVE-2019-19126	Low	3.3	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2019-19126	Low	3.3	libc6	2.28-10	2.28-10+deb10u2
CVE-2021-36084	Low	3.3	libsepol1	2.8-1	—
CVE-2021-36085	Low	3.3	libsepol1	2.8-1	—
CVE-2021-36086	Low	3.3	libsepol1	2.8-1	—
CVE-2021-36087	Low	3.3	libsepol1	2.8-1	—
CVE-2023-29383	Low	3.3	login	1:4.5-1.1	—
CVE-2023-29383	Low	3.3	passwd	1:4.5-1.1	—
CVE-2023-39804	Low	3.3	tar	1.30+dfsg-6	1.30+dfsg-6+deb10u1
CVE-2021-22898	Low	3.1	curl	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2021-22898	Low	3.1	libcurl4	7.64.0-4+deb10u2	7.64.0-4+deb10u3
CVE-2021-27645	Low	2.5	libc-bin	2.28-10	2.28-10+deb10u2
CVE-2021-27645	Low	2.5	libc6	2.28-10	2.28-10+deb10u2
DLA-3112-1	Unrated	—	libbz2-1.0	1.0.6-9.2~deb10u1	1.0.6-9.2~deb10u2
DLA-3134-1	Unrated	—	tzdata	2021a-0+deb10u1	2021a-0+deb10u7
DLA-3161-1	Unrated	—	tzdata	2021a-0+deb10u1	2021a-0+deb10u8
DLA-3366-1	Unrated	—	tzdata	2021a-0+deb10u1	2021a-0+deb10u10
DLA-3412-1	Unrated	—	tzdata	2021a-0+deb10u1	2021a-0+deb10u11
DLA-3482-1	Unrated	—	debian-archive-keyring	2019.1+deb10u1	2019.1+deb10u2
DLA-3684-1	Unrated	—	tzdata	2021a-0+deb10u1	2021a-0+deb10u12
DLA-3788-1	Unrated	—	tzdata	2021a-0+deb10u1	2024a-0+deb10u1

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
DSA-5085-2	Unrated	—	libexpat1	2.2.6-2+deb10u1	2.2.6-2+deb10u4

ghcr.io/christophetd/log4shell-vulnerable-app:latest

Digest	sha256:6f88430688108e512f7405ac3c73d47f5c370780b94182854ea2cddc6bd59929
平台	linux/amd64
作業系統	alpine 3.8.2
大小	—
建立時間	2022-02-24T11:34:04Z
掃描時間	2026-11-07T14:33:40Z
各嚴重等級弱點數	Critical 17 High 85 Medium 171 Low 160 Unrated 0

弱點明細

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2021-44228	Critical	10.0	org.apache.logging.log4j:log4j-core	2.14.1	2.15.0, 2.3.1, 2.12.2
Apache Log4j2 2.0-beta9 through 2.15.0 (excluding security releases 2.12.2, 2.12.3, and 2.3.1) JNDI features used in configuration, log messages, and parameters do not protect against attacker controlled LDAP and other JNDI related endpoints. An attacker who can control log messages or log message parameters can execute arbitrary code loaded from LDAP servers when message lookup substitution is enabled. From log4j 2.15.0, this behavior has been disabled by default. From version 2.16.0 (along with 2.12.2, 2.12.3, and 2.3.1), this functionality has been completely removed. Note that this vulnera...					
CVE-2016-1000027	Critical	9.8	org.springframework:spring-web	5.3.13	6.0.0
Pivotal Spring Framework through 5.3.16 suffers from a potential remote code execution (RCE) issue if used for Java deserialization of untrusted data. Depending on how the library is implemented within a product, this issue may or not occur, and authentication may be required. NOTE: the vendor's position is that untrusted data is not an intended use case. The product's behavior will not be changed because some users rely on deserialization of trusted data.					
CVE-2019-12900	Critical	9.8	libbz2	1.0.6-r6	1.0.6-r7
BZ2_decompress in decompress.c in bzip2 through 1.0.6 has an out-of-bounds write when there are many selectors.					
CVE-2019-14697	Critical	9.8	musl	1.1.19-r10	1.1.19-r11
musl libc through 1.1.23 has an x87 floating-point stack adjustment imbalance, related to the math/i386/ directory. In some cases, use of this library could introduce out-of-bounds writes that are not present in an application's source code.					
CVE-2019-14697	Critical	9.8	musl-utils	1.1.19-r10	1.1.19-r11
musl libc through 1.1.23 has an x87 floating-point stack adjustment imbalance, related to the math/i386/ directory. In some cases, use of this library could introduce out-of-bounds writes that are not present in an application's source code.					
CVE-2019-8457	Critical	9.8	sqlite-libs	3.24.0-r0	3.25.3-r1
SQLite3 from 3.6.0 to and including 3.27.2 is vulnerable to heap out-of-bound read in the rtreenode() function when handling invalid rtree tables.					
CVE-2022-1471	Critical	9.8	org.yaml:snakeyaml	1.29	2.0
SnakeYaml's Constructor() class does not restrict types which can be instantiated during deserialization. Deserializing yaml content provided by an attacker can lead to remote code execution. We recommend using SnakeYaml's SafeConsturctor when parsing untrusted content to restrict deserialization. We recommend upgrading to version 2.0 and beyond.					
CVE-2022-22965	Critical	9.8	org.springframework:spring-beans	5.3.13	5.2.20.RELEASE, 5.3.18
A Spring MVC or Spring WebFlux application running on JDK 9+ may be vulnerable to remote code execution (RCE) via data binding. The specific exploit requires the application to run on Tomcat as a WAR deployment. If the application is deployed as a Spring Boot executable jar, i.e. the default, it is not vulnerable to the exploit. However, the nature of the vulnerability is more general, and there may be other ways to exploit it.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2022-22965	Critical	9.8	org.springframework:spring-webmvc	5.3.13	5.2.20.RELEASE, 5.3.18

A Spring MVC or Spring WebFlux application running on JDK 9+ may be vulnerable to remote code execution (RCE) via data binding. The specific exploit requires the application to run on Tomcat as a WAR deployment. If the application is deployed as a Spring Boot executable jar, i.e. the default, it is not vulnerable to the exploit. However, the nature of the vulnerability is more general, and there may be other ways to exploit it.

CVE-2025-24813	Critical	9.8	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.3, 10.1.35, 9.0.99

Path Equivalence: 'file.Name' (Internal Dot) leading to Remote Code Execution and/or Information disclosure and/or malicious content added to uploaded files via write enabled Default Servlet in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.2, from 10.1.0-M1 through 10.1.34, from 9.0.0.M1 through 9.0.98.
The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions
may also be affected.

If all of the following were true, a malicious user was able to view security sensitive ...

CVE-2026-47884	Critical	9.8	org.springframework:spring-webmvc	5.3.13	7.0.9

Use of XsltView in a Spring MVC application can result in SSRF and RCE attack if the application has an "/**" mapping that results in view rendering, and where the view name is not explicitly specified.
Spring Framework 7.0.0 - 7.0.8
Spring Framework 6.2.0 - 6.2.19
Spring Framework 6.1.0 - 6.1.28
Spring Framework 6.0.0 - 6.0.30
Spring Framework 5.3.0 - 5.3.49
Spring Framework 5.2.25.RELEASE and earlier

CVE-2025-66614	Critical	9.1	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.15, 10.1.50, 9.0.113

Improper Input Validation vulnerability.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.14, from 10.1.0-M1 through 10.1.49, from 9.0.0-M1 through 9.0.112.

The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 through 8.5.100. Older EOL versions are not affected.
Tomcat did not validate that the host name provided via the SNI
extension was the same as the host name provided in the HTTP host header
field. If Tomcat was configured with more than one virtual host and the
TLS configuration for one of those hosts did not require clie...

CVE-2018-3183	Critical	9.0	openjdk8	8.181.13-r0	8.191.12-r0

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...

CVE-2018-3183	Critical	9.0	openjdk8-jre	8.181.13-r0	8.191.12-r0

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...

CVE-2018-3183	Critical	9.0	openjdk8-jre-base	8.181.13-r0	8.191.12-r0

Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...					
CVE-2018-3183	Critical	9.0	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: Scripting). Supported versions that are affected are Java SE: 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. While the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded, JRockit...					
CVE-2021-45046	Critical	9.0	org.apache.logging.log4j:log4j-core	2.14.1	2.16.0, 2.12.2, 2.3.1
It was found that the fix to address CVE-2021-44228 in Apache Log4j 2.15.0 was incomplete in certain non-default configurations. This could allows attackers with control over Thread Context Map (MDC) input data when the logging configuration uses a non-default Pattern Layout with either a Context Lookup (for example, $${ctx:loginId}) or a Thread Context Map pattern (%X, %mdc, or %MDC) to craft malicious input data using a JNDI Lookup pattern resulting in an information leak and remote code execution in some environments and local code execution in all environments. Log4j 2.16.0 (Java 8) and 2....					
CVE-2018-14550	High	8.8	libpng	1.6.34-r1	1.6.37-r0
An issue has been found in third-party PNM decoding associated with libpng 1.6.35. It is a stack-based buffer overflow in the function get_token in pnm2png.c in pnm2png.					
CVE-2025-49124	High	8.4	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.8, 10.1.42, 9.0.106
Untrusted Search Path vulnerability in Apache Tomcat installer for Windows. During installation, the Tomcat installer for Windows used icacls.exe without specifying a full path. This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.7, from 10.1.0 through 10.1.41, from 9.0.23 through 9.0.105. The following versions were EOL at the time the CVE was created but are known to be affected: 8.5.0 through 8.5.100 and 7.0.95 through 7.0.109. Other EOL versions may also be affected. Users are recommended to upgrade to version 11.0.8, 10.1.42 or 9.0.106, which fix the issue.					
CVE-2018-3149	High	8.3	openjdk8	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe...					
CVE-2018-3149	High	8.3	openjdk8-jre	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe...					
CVE-2018-3149	High	8.3	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe...					
CVE-2018-3149	High	8.3	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded, JRockit component of Oracle Java SE (subcomponent: JNDI). Supported versions that are affected are Java SE: 6u201, 7u191, 8u182 and 11; Java SE Embedded: 8u181; JRockit: R28.3.19. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded, JRockit. Successful					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, JRockit, attacks may significantly impact additional products. Succe...					
CVE-2018-3169	High	8.3	openjdk8	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...					
CVE-2018-3169	High	8.3	openjdk8-jre	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...					
CVE-2018-3169	High	8.3	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...					
CVE-2018-3169	High	8.3	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Hotspot). Supported versions that are affected are Java SE: 7u191, 8u182 and 11; Java SE Embedded: 8u181. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...					
CVE-2020-14583	High	8.3	openjdk8	8.181.13-r0	8.272.10-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r...					
CVE-2020-14583	High	8.3	openjdk8-jre	8.181.13-r0	8.272.10-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r...					
CVE-2020-14583	High	8.3	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r...					
CVE-2020-14583	High	8.3	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can r...					
CVE-2020-2803	High	8.3	openjdk8	8.181.13-r0	8.252.09-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2803	High	8.3	openjdk8-jre	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2803	High	8.3	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2803	High	8.3	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2805	High	8.3	openjdk8	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2805	High	8.3	openjdk8-jre	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2805	High	8.3	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2020-2805	High	8.3	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Libraries). Supported versions that are affected are Java SE: 7u251, 8u241, 11.0.6 and 14; Java SE Embedded: 8u241. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can resul...					
CVE-2026-65182	High	8.2	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.25, 10.1.58, 9.0.121
Improper Access Control, Incorrect Authorization vulnerability in Apache Tomcat leads to security constraint bypass if a constraint for a longer path is specified before a more restrictive constraint for a shorter sub-path.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.24, from 10.1.0-M1 through 10.1.57, from 9.0.0.M1 through 9.0.120, from 8.5.0 through 8.5.100, from 7.0.0 through 7.0.109.

Users are recommended to upgrade to version 11.0.25, 10.1.58, 9.0.121, which fixes the issue.

CVE-2018-20346	● High	8.1	sqlite-libs	3.24.0-r0	3.25.3-r0

SQLite before 3.25.3, when the FTS3 extension is enabled, encounters an integer overflow (and resultant buffer overflow) for FTS3 queries that occur after crafted changes to FTS3 shadow tables, allowing remote attackers to execute arbitrary code by leveraging the ability to run arbitrary SQL statements (such as in certain WebSQL use cases), aka Magellan.

CVE-2019-2698	● High	8.1	openjdk8	8.181.13-r0	8.212.04-r0

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

CVE-2019-2698	● High	8.1	openjdk8-jre	8.181.13-r0	8.212.04-r0

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

CVE-2019-2698	● High	8.1	openjdk8-jre-base	8.181.13-r0	8.212.04-r0

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

CVE-2019-2698	● High	8.1	openjdk8-jre-lib	8.181.13-r0	8.212.04-r0

Vulnerability in the Java SE component of Oracle Java SE (subcomponent: 2D). Supported versions that are affected are Java SE: 7u211 and 8u202. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE. Successful attacks of this vulnerability can result in takeover of Java SE. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets (in Java SE 8), that load and run untrusted code (e.g., code that comes from the internet) and rely ...

CVE-2020-2604	● High	8.1	openjdk8	8.181.13-r0	8.242.08-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

CVE-2020-2604	● High	8.1	openjdk8-jre	8.181.13-r0	8.242.08-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

CVE-2020-2604	● High	8.1	openjdk8-jre-base	8.181.13-r0	8.242.08-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-2604	High	8.1	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: Serialization). Supported versions that are affected are Java SE: 7u241, 8u231, 11.0.5 and 13.0.1; Java SE Embedded: 8u231. Difficult to exploit vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in takeover of Java SE, Java SE Embedded. Note: This vulnerability applies to Java deployments, typically in clients running sandboxed Java Web Start applications or sandboxed Java applets...

CVE-2024-22259	High	8.1	org.springframework:spring-web	5.3.13	6.1.5, 6.0.18, 5.3.33

Applications that use UriComponentsBuilder in Spring Framework to parse an externally provided URL (e.g. through a query parameter) AND perform validation checks on the host of the parsed URL may be vulnerable to a open redirect https://cwe.mitre.org/data/definitions/601.html attack or to a SSRF attack if the URL is used after passing validation checks.

This is the same as CVE-2024-22243 https://spring.io/security/cve-2024-22243 , but with different input.

CVE-2024-22262	High	8.1	org.springframework:spring-web	5.3.13	5.3.34, 6.0.19, 6.1.6

Applications that use UriComponentsBuilder to parse an externally provided URL (e.g. through a query parameter) AND perform validation checks on the host of the parsed URL may be vulnerable to a open redirect https://cwe.mitre.org/data/definitions/601.html attack or to a SSRF attack if the URL is used after passing validation checks.

This is the same as CVE-2024-22259 https://spring.io/security/cve-2024-22259 and CVE-2024-22243 https://spring.io/security/cve-2024-22243 , but with different input.

CVE-2024-50379	High	8.1	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.2, 10.1.34, 9.0.98

Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability during JSP compilation in Apache Tomcat permits an RCE on case insensitive file systems when the default servlet is enabled for write (non-default configuration).

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.1, from 10.1.0-M1 through 10.1.33, from 9.0.0.M1 through 9.0.97.

The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.2, 10.1.34 or 9.0.98, which ...

CVE-2024-56337	High	8.1	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.2, 10.1.34, 9.0.98

Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.1, from 10.1.0-M1 through 10.1.33, from 9.0.0.M1 through 9.0.97.
The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.0 though 8.5.100. Other, older, EOL versions
may also be affected.

The mitigation for CVE-2024-50379 was incomplete.

Users running Tomcat on a case insensitive file system with the default servlet write enabled (readonly initialisation
parameter set to the non-default value of false) m...

CVE-2026-54512	High	8.1	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.8, 3.1.4, 2.21.4

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.10.0 until 2.18.8, 2.21.4, and 3.1.4, jackson-databind's PolymorphicTypeValidator (PTV) is the primary safety mechanism guarding polymorphic deserialization. When polymorphic typing is enabled and a type identifier contains generic parameters (i.e. the type ID string contains <), DatabindContext._resolveAndValidateGeneric() validates only the raw container class name (the substring before <) against the configured PTV. If the container type is approved, the method parses t...

CVE-2026-54513	High	8.1	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.8, 2.21.4, 3.1.4

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.10.0 until 2.18.8, 2.21.4, and 3.1.4, BasicPolymorphicTypeValidator.Builder.allowIfSubTypeIsArray() allowlists any array type based only on

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
clazz.isArray(), without validating the array's component (element) type against the configured allowlist. A PTV built with allowIfSubTypeIsArray() plus an explicit concrete-type allowlist therefore still permits EvilType[] even though EvilType is not allowlisted. When Jackson deserializes the elements and no per-element type IDs are p...					
CVE-2019-2201	High	7.8	libjpeg-turbo	1.5.3-r3	1.5.3-r6
In generate_jsimd_ycc_rgb_convert_neon of jsimd_arm64_neon.S, there is a possible out of bounds write due to a missing bounds check. This could lead to remote code execution in an unprivileged process with no additional execution privileges needed. User interaction is needed for exploitation.Product: AndroidVersions: Android-8.0 Android-8.1 Android-9 Android-10Android ID: A-120551338					
CVE-2019-19244	High	7.5	sqlite-libs	3.24.0-r0	3.25.3-r3
sqlite3Select in select.c in SQLite 3.30.1 allows a crash if a sub-select uses both DISTINCT and window functions, and also has certain ORDER BY usage.					
CVE-2019-2602	High	7.5	openjdk8	8.181.13-r0	8.212.04-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t...					
CVE-2019-2602	High	7.5	openjdk8-jre	8.181.13-r0	8.212.04-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t...					
CVE-2019-2602	High	7.5	openjdk8-jre-base	8.181.13-r0	8.212.04-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t...					
CVE-2019-2602	High	7.5	openjdk8-jre-lib	8.181.13-r0	8.212.04-r0
Vulnerability in the Java SE, Java SE Embedded component of Oracle Java SE (subcomponent: Libraries). Supported versions that are affected are Java SE: 7u211, 8u202, 11.0.2 and 12; Java SE Embedded: 8u201. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Java SE, Java SE Embedded. Note: This vulnerability can only be exploited by supplying data to APIs in t...					
CVE-2020-11655	High	7.5	sqlite-libs	3.24.0-r0	3.25.0-r4
SQLite through 3.31.1 allows attackers to cause a denial of service (segmentation fault) via a malformed window-function query because the AggInfo object's initialization is mishandled.					
CVE-2020-36518	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.13.2.1, 2.12.6.1
jackson-databind before 2.13.0 allows a Java StackOverflow exception and denial of service via a large depth of nested objects.					
CVE-2021-46877	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.12.6, 2.13.1
jackson-databind 2.10.x through 2.12.x before 2.12.6 and 2.13.x before 2.13.1 allows attackers to cause a denial of service (2 GB transient heap usage per read) in uncommon situations involving JsonNode JDK serialization.					
CVE-2022-25857	High	7.5	org.yaml:snakeyaml	1.29	1.31
The package org.yaml:snakeyaml from 0 and before 1.31 are vulnerable to Denial of Service (DoS) due missing to nested depth limitation for collections.					
CVE-2022-42003	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.12.7.1, 2.13.4.2

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
In FasterXML jackson-databind before versions 2.13.4.1 and 2.12.17.1, resource exhaustion can occur because of a lack of a check in primitive value deserializers to avoid deep wrapper array nesting, when the UNWRAP_SINGLE_VALUE_ARRAYS feature is enabled.					
CVE-2022-42004	● High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.12.7.1, 2.13.4
In FasterXML jackson-databind before 2.13.4, resource exhaustion can occur because of a lack of a check in BeanDeserializer._deserializeFromArray to prevent use of deeply nested arrays. An application is vulnerable only with certain customized choices for deserialization.					
CVE-2022-42252	● High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	8.5.83, 9.0.68, 10.0.27, 10.1.1
If Apache Tomcat 8.5.0 to 8.5.82, 9.0.0-M1 to 9.0.67, 10.0.0-M1 to 10.0.26 or 10.1.0-M1 to 10.1.0 was configured to ignore invalid HTTP headers via setting rejectIllegalHeader to false (the default for 8.5.x only), Tomcat did not reject a request containing an invalid Content-Length header making a request smuggling attack possible if Tomcat was located behind a reverse proxy that also failed to reject the request with the invalid header.					
CVE-2022-45143	● High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	8.5.84, 9.0.69, 10.1.2
The JsonErrorReportValve in Apache Tomcat 8.5.83, 9.0.40 to 9.0.68 and 10.1.0-M1 to 10.1.1 did not escape the type, message or description values. In some circumstances these are constructed from user provided data and it was therefore possible for users to supply values that invalidated or manipulated the JSON output.					
CVE-2023-20860	● High	7.5	org.springframework:spring-webmvc	5.3.13	6.0.7, 5.3.26
Spring Framework running version 6.0.0 - 6.0.6 or 5.3.0 - 5.3.25 using "**" as a pattern in Spring Security configuration with the mvcRequestMatcher creates a mismatch in pattern matching between Spring Security and Spring MVC, and the potential for a security bypass.					
CVE-2023-20883	● High	7.5	org.springframework.boot:spring-boot-autoconfigure	2.6.1	3.0.7, 2.7.12, 2.6.15, 2.5.15
In Spring Boot versions 3.0.0 - 3.0.6, 2.7.0 - 2.7.11, 2.6.0 - 2.6.14, 2.5.0 - 2.5.14 and older unsupported versions, there is potential for a denial-of-service (DoS) attack if Spring MVC is used together with a reverse proxy cache.					
CVE-2023-24998	● High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	10.1.5, 11.0.0-M5, 8.5.88, 9.0.71
Apache Commons FileUpload before 1.5 does not limit the number of request parts to be processed resulting in the possibility of an attacker triggering a DoS with a malicious upload or series of uploads. Note that, like all of the file upload limits, the new configuration option (FileUploadBase#setFileCountMax) is not enabled by default and must be explicitly configured.					
CVE-2023-44487	● High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.0-M12, 10.1.14, 9.0.81, 8.5.94
The HTTP/2 protocol allows a denial of service (server resource consumption) because request cancellation can reset many streams quickly, as exploited in the wild in August through October 2023.					
CVE-2023-46589	● High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.0-M11, 10.1.16, 9.0.83, 8.5.96
Improper Input Validation vulnerability in Apache Tomcat.Tomcat from 11.0.0-M1 through 11.0.0-M10, from 10.1.0-M1 through 10.1.15, from 9.0.0-M1 through 9.0.82 and from 8.5.0 through 8.5.95 did not correctly parse HTTP trailer headers. A trailer header that exceeded the header size limit could cause Tomcat to treat a single request as multiple requests leading to the possibility of request smuggling when behind a reverse proxy.					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本

Older, EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.0-M11 onwards, 10.1.16 onwards, 9.0.83 onwards or 8.5.96 onwards, which...

CVE-2024-23672	High	7.5	org.apache.tomcat.embed:tomcat-embed-websocket	9.0.55	11.0.0-M17, 10.1.19, 9.0.86, 8.5.99

Denial of Service via incomplete cleanup vulnerability in Apache Tomcat. It was possible for WebSocket clients to keep WebSocket connections open leading to increased resource consumption.This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M16, from 10.1.0-M1 through 10.1.18, from 9.0.0-M1 through 9.0.85, from 8.5.0 through 8.5.98.

Older, EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.0-M17, 10.1.19, 9.0.86 or 8.5.99 which fix the issue.

CVE-2024-24549	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	8.5.99, 9.0.86, 10.1.19, 11.0.0-M17

Denial of Service due to improper input validation vulnerability for HTTP/2 requests in Apache Tomcat. When processing an HTTP/2 request, if the request exceeded any of the configured limits for headers, the associated HTTP/2 stream was not reset until after all of the headers had been processed.This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M16, from 10.1.0-M1 through 10.1.18, from 9.0.0-M1 through 9.0.85, from 8.5.0 through 8.5.98. Other, older, EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.0-M17, 10.1.19, 9.0.86 or 8.5.99 which fix the...

CVE-2024-34750	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.0-M21, 10.1.25, 9.0.90

Improper Handling of Exceptional Conditions, Uncontrolled Resource Consumption vulnerability in Apache Tomcat. When processing an HTTP/2 stream, Tomcat did not handle some cases of excessive HTTP headers correctly. This led to a miscounting of active HTTP/2 streams which in turn led to the use of an incorrect infinite timeout which allowed connections to remain open which should have been closed.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M20, from 10.1.0-M1 through 10.1.24, from 9.0.0-M1 through 9.0.89.

The following versions were EOL at the time the CVE was created but...

CVE-2024-38286	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.0-M21, 10.1.25, 9.0.90

Allocation of Resources Without Limits or Throttling vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.0-M20, from 10.1.0-M1 through 10.1.24, from 9.0.13 through 9.0.89.

The following versions were EOL at the time the CVE was created but are
known to be affected: 8.5.35 through 8.5.100 and 7.0.92 through 7.0.109. Other EOL versions may also be affected.

Users are recommended to upgrade to version 11.0.0-M21, 10.1.25, or 9.0.90, which fixes the issue.

Apache Tomcat, under certain configurations on any platform, allows an attacker to cause an ...

CVE-2024-38816	High	7.5	org.springframework:spring-webmvc	5.3.13	6.1.13

Applications serving static resources through the functional web frameworks WebMvc.fn or WebFlux.fn are vulnerable to path traversal attacks. An attacker can craft malicious HTTP requests and obtain any file on the file system that is also accessible to the process in which the Spring application is running.

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
Specifically, an application is vulnerable when both of the following are true: * the web application uses RouterFunctions to serve static resources * resource handling is explicitly configured with a FileSystemResource location However, malicious requests are blocked and rejecte...					
CVE-2024-38819	High	7.5	org.springframework:spring-webmvc	5.3.13	6.1.14
Applications serving static resources through the functional web frameworks WebMvc.fn or WebFlux.fn are vulnerable to path traversal attacks. An attacker can craft malicious HTTP requests and obtain any file on the file system that is also accessible to the process in which the Spring application is running.					
CVE-2025-41249	High	7.5	org.springframework:spring-core	5.3.13	6.2.11
The Spring Framework annotation detection mechanism may not correctly resolve annotations on methods within type hierarchies with a parameterized super type with unbounded generics. This can be an issue if such annotations are used for authorization decisions. Your application may be affected by this if you are using Spring Security's @EnableMethodSecurity feature. You are not affected by this if you are not using @EnableMethodSecurity or if you do not use security annotations on methods in generic superclasses or generic interfaces. This CVE is published in conjunction with CVE-2025-41248...					
CVE-2025-48989	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.10, 10.1.44, 9.0.108
Improper Resource Shutdown or Release vulnerability in Apache Tomcat made Tomcat vulnerable to the made you reset attack. This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.9, from 10.1.0-M1 through 10.1.43 and from 9.0.0.M1 through 9.0.107. Older, EOL versions may also be affected. Users are recommended to upgrade to one of versions 11.0.10, 10.1.44 or 9.0.108 which fix the issue.					
CVE-2025-52999	High	7.5	com.fasterxml.jackson.core:jackson-core	2.13.0	2.15.0
jackson-core contains core low-level incremental ("streaming") parser and generator abstractions used by Jackson Data Processor. In versions prior to 2.15.0, if a user parses an input file and it has deeply nested data, Jackson could end up throwing a StackoverflowError if the depth is particularly large. jackson-core 2.15.0 contains a configurable limit for how deep Jackson will traverse in an input document, defaulting to an allowable depth of 1000. jackson-core will throw a StreamConstraintsException if the limit is reached. jackson-databind also benefits from this change because it uses ja...					
CVE-2025-55752	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.11, 10.1.45, 9.0.109
Relative Path Traversal vulnerability in Apache Tomcat. The fix for bug 60013 introduced a regression where the rewritten URL was normalized before it was decoded. This introduced the possibility that, for rewrite rules that rewrite query parameters to the URL, an attacker could manipulate the request URI to bypass security constraints including the protection for /WEB-INF/ and /META-INF/. If PUT requests were also enabled then malicious files could be uploaded leading to remote code execution. PUT requests are normally limited to trusted users and it is considered unl...					
CVE-2026-34479	High	7.5	org.apache.logging.log4j:log4j-core	2.14.1	2.25.4
The Log4j1XmlLayout from the Apache Log4j 1-to-Log4j 2 bridge fails to escape characters forbidden by the XML 1.0 standard, producing malformed XML output. Conforming XML parsers are required to reject documents containing such characters with a fatal error, which may cause downstream log processing systems to drop or fail to index affected records. Two groups of users are affected: * Those using Log4j1XmlLayout directly in a Log4j Core 2 configuration file. * Those using the Log4j 1 configuration compatibility layer with org.apache.log4j.xml.XMLLayout specified as the layout class. ...					

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-34480	High	7.5	org.apache.logging.log4j:log4j-core	2.14.1	2.25.4

Apache Log4j Core's XmlLayout https://logging.apache.org/log4j/2.x/manual/layouts.html#XmlLayout , in versions up to and including 2.25.3, fails to sanitize characters forbidden by the XML 1.0 specification https://www.w3.org/TR/xml/#charsets producing invalid XML output whenever a log message or MDC value contains such characters.

The impact depends on the StAX implementation in use:

* JRE built-in StAX: Forbidden characters are silently written to the output, producing malformed XML. Conforming parsers must reject such documents with a fatal error, which may cause downstream log-proc...

CVE-2026-41284	High	7.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22

Allocation of Resources Without Limits or Throttling vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.21, from 10.1.0-M1 through 10.1.54, from 9.0.0.M1 through 9.0.117. Older, unsupported versions may also be affected.

Users are recommended to upgrade to version [FIXED_VERSION], which fixes the issue.

CVE-2026-41848	High	7.5	org.springframework:spring-core	5.3.13	7.0.8, 6.2.19

Applications may be vulnerable to a Regular Expression Denial of Service (ReDoS) attack if an attacker is able to provide a pattern which is then directly or indirectly supplied to one of the following methods in AntPathMatcher: match(String pattern, String path), matchStart(String pattern, String path), extractUriTemplateVariables(String pattern, String path).

Affected versions:
Spring Framework 7.0.0 through 7.0.7; 6.2.0 through 6.2.18; 6.1.0 through 6.1.27; 5.3.0 through 5.3.48.

CVE-2026-41851	High	7.5	org.springframework:spring-expression	5.3.13	7.0.8, 6.2.19

Applications which accept user-supplied Spring Expression Language (SpEL) expressions may be vulnerable to a Denial of Service (DoS) attack if the evaluation of a SpEL expression triggers unbounded cache growth.

Affected versions:
Spring Framework 7.0.0 through 7.0.7; 6.2.0 through 6.2.18; 6.1.0 through 6.1.27; 5.3.0 through 5.3.48.

CVE-2026-50193	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.14.0

jackson-databind contains the general-purpose data-binding functionality and tree-model for Jackson Data Processor. From 2.13.0 until 2.14.0, a potential Denial-of-Service exists when attacker sends deeply nested JSON if (and only if) the service reads deeply nested (1000s of levels) JSON as JsonNode (ObjectMapper.readTree()) and writes out same (or modified) node using JsonNode.toString(). This can consume significant amount of resources with concurrent relatively small requests (1000 nested arrays is 2kB). This vulnerability is fixed in 2.14.0.

CVE-2026-68494	High	7.5	com.fasterxml.jackson.core:jackson-core	2.13.0	2.18.8, 2.21.4

The fix released in jackson-core 2.18.6 and 2.21.1 for CVE-2026-18401 (GHSA-72hv-8253-57qq, number length constraint bypass in the non-blocking parser) is incomplete. This record covers the remaining bypass.

The earlier fix wired validateIntegerLength() into a new _setIntLength() helper and invoked it wherever the integer portion of a number is decided: a terminator byte arrives, a '.' or 'e'/'E' is seen, or input ends inside a fully buffered value. It was not invoked on the attacker-relevant path where the parser runs out of input while still inside the MINOR_NUMBER_INTEGER_DIGITS minor stat...

CVE-2026-89425	High	7.5	com.fasterxml.jackson.core:jackson-core	2.13.0	2.21.7, 2.22.3, 2.18.11

UTF8DataInputJsonParser._reportInvalidToken() in FasterXML jackson-core builds the offending-token text for its error message by appending Java identifier characters to a StringBuilder in a loop that has no upper bound. Unlike the three sibling parser implementations, including UTF8StreamJsonParser, it never consults ErrorReportConfiguration.getMaxErrorTokenLength() (default 256). A malformed token supplied to a parser created through JsonFactory.createParser(DataInput) is therefore accumulated in full. No StreamReadConstraints setting mitigates this: maxDocumentLength cannot be applied to Dat...

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-91776	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.11, 2.21.7, 2.22.3

TypeDeserializerBase._findDeserializer() in FasterXML jackson-databind caches the resolved deserializer under the raw, attacker-supplied type ID. When name-based polymorphism is configured with a fallback, for example @JsonTypeInfo(use = Id.NAME, defaultImpl = ...), every distinct unrecognized type ID resolves to the same fallback deserializer but is retained as its own key in the _deserializers map. That map has no configurable bound and lives for the lifetime of the type deserializer, so an attacker who can repeatedly supply fresh unknown type IDs causes monotonic memory retention across req...

CVE-2026-91777	High	7.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.21.7, 2.18.11, 2.22.3

Forward-reference completion for @JsonIdentityInfo object IDs in FasterXML jackson-databind performs a linear scan of the pending-reference accumulator for every resolved ID. The affected paths are CollectionDeserializer.CollectionReferringAccumulator.resolveForwardReference() and the equivalent implementation in MapDeserializer. When a document first creates N unresolved object-ID references in an identity-enabled collection or map and then defines those same IDs in reverse order, completion performs on the order of N * (N + 1) / 2 identity comparisons, so a shallow document whose size grows ...

CVE-2020-14593	High	7.4	openjdk8	8.181.13-r0	8.272.10-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

CVE-2020-14593	High	7.4	openjdk8-jre	8.181.13-r0	8.272.10-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

CVE-2020-14593	High	7.4	openjdk8-jre-base	8.181.13-r0	8.272.10-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

CVE-2020-14593	High	7.4	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0

Vulnerability in the Java SE, Java SE Embedded product of Oracle Java SE (component: 2D). Supported versions that are affected are Java SE: 7u261, 8u251, 11.0.7 and 14.0.1; Java SE Embedded: 8u251. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Java SE, Java SE Embedded. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Java SE, Java SE Embedded, attacks may significantly impact additional products. Successful attacks of this vulnerability can result in ...

CVE-2025-22235	High	7.3	org.springframework.boot:spring-boot	2.6.1	3.3.11, 3.4.5

EndpointRequest.to() creates a matcher for null/** if the actuator endpoint, for which the EndpointRequest has been created, is disabled or not exposed.

Your application may be affected by this if all the following conditions are met:

* You use Spring Security
* EndpointRequest.to() has been used in a Spring Security chain configuration
* The endpoint which EndpointRequest references is disabled or not exposed via web
* Your application handles requests to /null and this path needs protection

You are not affected if any of the following is true:

* You don't use Spring Secur...

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-41293	High	7.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22

Improper Input Validation vulnerability in Apache Tomcat.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.21, from 10.1.0-M1 through 10.1.54, from 9.0.0.M1 through 9.0.117, from 10.0.0-M1 through 10.0.27.
Older, end of support versions may also be affected.

Users are recommended to upgrade to version [FIXED_VERSION], which fixes the issue.

CVE-2026-55957	High	7.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.5, 10.1.37, 9.0.101

Missing Critical Step in Authentication vulnerability in Apache Tomcat when the JNDIRealm was configured to authenticate binds using GSSAPI allowed attackers to authenticate without provided the correct password.

This issue affects Apache Tomcat: from 11.0.0-M1 through 11.0.4, from 10.1.0-M1 through 10.1.36, from 9.0.0.M1 through 9.0.100, from 8.5.0 through 8.5.100, from 7.0.0 through 7.0.109.

Users are recommended to upgrade to version 11.0.5, 10.1.37 or 9.0.101, which fixes the issue.

CVE-2026-40973	High	7.0	org.springframework.boot:spring-boot	2.6.1	4.0.6, 3.5.14

A local attacker on the same host as the application may be able to take control of the directory used by `ApplicationTemp`. When `server.servlet.session.persistent` is set to `true` and the attack persists across application restarts, this may allow the attacker to read session information and hijack authenticated users or deploy a gadget chain and execute code as the application's user.

Affected: Spring Boot 4.0.0–4.0.5 (fix 4.0.6), 3.5.0–3.5.13 (fix 3.5.14), 3.4.0–3.4.15 (fix 3.4.16), 3.3.0–3.3.18 (fix 3.3.19), 2.7.0–2.7.32 (fix 2.7.33); predictable temp directory / `ApplicationTemp` owner...

CVE-2019-2949	Medium	6.8	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2949	Medium	6.8	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2949	Medium	6.8	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2949	Medium	6.8	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2989	Medium	6.8	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2989	Medium	6.8	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2989	Medium	6.8	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2989	Medium	6.8	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2020-2601	Medium	6.8	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2601	Medium	6.8	openjdk8-jre	8.181.13-r0	8.242.08-r0
CVE-2020-2601	Medium	6.8	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2601	Medium	6.8	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2019-5094	Medium	6.7	libcom_err	1.44.2-r0	1.44.2-r1
CVE-2019-5188	Medium	6.7	libcom_err	1.44.2-r0	1.44.2-r2
CVE-2021-44832	Medium	6.6	org.apache.logging.log4j:log4j-core	2.14.1	2.3.2, 2.12.4, 2.17.1
CVE-2018-11212	Medium	6.5	openjdk8	8.181.13-r0	8.201.08-r0
CVE-2018-11212	Medium	6.5	openjdk8-jre	8.181.13-r0	8.201.08-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2018-11212	Medium	6.5	openjdk8-jre-base	8.181.13-r0	8.201.08-r0
CVE-2018-11212	Medium	6.5	openjdk8-jre-lib	8.181.13-r0	8.201.08-r0
CVE-2018-13785	Medium	6.5	openjdk8	8.181.13-r0	8.191.12-r0
CVE-2018-13785	Medium	6.5	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-13785	Medium	6.5	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-13785	Medium	6.5	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2018-14048	Medium	6.5	libpng	1.6.34-r1	1.6.37-r0
CVE-2018-14498	Medium	6.5	libjpeg-turbo	1.5.3-r3	1.5.3-r5
CVE-2019-16168	Medium	6.5	sqlite-libs	3.24.0-r0	3.25.3-r2
CVE-2022-22950	Medium	6.5	org.springframework:spring-expression	5.3.13	5.3.17, 5.2.20.RELEASE
CVE-2022-38749	Medium	6.5	org.yaml:snakeyaml	1.29	1.31
CVE-2022-38751	Medium	6.5	org.yaml:snakeyaml	1.29	1.31
CVE-2022-38752	Medium	6.5	org.yaml:snakeyaml	1.29	1.32
CVE-2022-41854	Medium	6.5	org.yaml:snakeyaml	1.29	1.32
CVE-2023-20861	Medium	6.5	org.springframework:spring-expression	5.3.13	6.0.7, 5.3.26, 5.2.23.RELEASE
CVE-2023-20863	Medium	6.5	org.springframework:spring-expression	5.3.13	6.0.8, 5.3.27, 5.2.24.RELEASE
CVE-2025-46701	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.105, 10.1.41, 11.0.7
CVE-2025-55668	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.8, 10.1.42, 9.0.106
CVE-2026-22737	Medium	6.5	org.springframework:spring-webmvc	5.3.13	7.0.6, 6.2.17
CVE-2026-34487	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.117, 10.1.54, 11.0.21
CVE-2026-42498	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22
CVE-2026-43512	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22
CVE-2026-53404	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.23, 10.1.56, 9.0.119
CVE-2026-55956	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.23, 10.1.56, 9.0.119

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-59889	Medium	6.5	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.21.5, 2.18.9, 2.22.1
CVE-2026-68525	Medium	6.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.25, 10.1.58, 9.0.121
CVE-2023-41080	Medium	6.1	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	8.5.93, 9.0.80, 10.1.13, 11.0.0-M11
CVE-2026-41844	Medium	6.1	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-41845	Medium	6.1	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-41846	Medium	6.1	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2019-19242	Medium	5.9	sqlite-libs	3.24.0-r0	3.25.3-r3
CVE-2019-2684	Medium	5.9	openjdk8	8.181.13-r0	8.212.04-r0
CVE-2019-2684	Medium	5.9	openjdk8-jre	8.181.13-r0	8.212.04-r0
CVE-2019-2684	Medium	5.9	openjdk8-jre-base	8.181.13-r0	8.212.04-r0
CVE-2019-2684	Medium	5.9	openjdk8-jre-lib	8.181.13-r0	8.212.04-r0
CVE-2019-2958	Medium	5.9	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2958	Medium	5.9	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2958	Medium	5.9	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2958	Medium	5.9	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2021-45105	Medium	5.9	org.apache.logging.log4j:log4j-core	2.14.1	2.12.3, 2.17.0, 2.3.1
CVE-2024-38808	Medium	5.9	org.springframework:spring-expression	5.3.13	5.3.39
CVE-2025-41242	Medium	5.9	org.springframework:spring-webmvc	5.3.13	6.2.10
CVE-2026-22741	Medium	5.9	org.springframework:spring-webmvc	5.3.13	7.0.7, 6.2.18
CVE-2026-34477	Medium	5.9	org.apache.logging.log4j:log4j-core	2.14.1	2.25.4
CVE-2026-41841	Medium	5.9	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-41842	Medium	5.9	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-41843	Medium	5.9	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-41849	Medium	5.9	org.springframework:spring-expression	5.3.13	—
CVE-2026-41850	Medium	5.9	org.springframework:spring-expression	5.3.13	7.0.8, 6.2.19
CVE-2026-49844	Medium	5.9	org.apache.logging.log4j:log4j-api	2.14.1	2.25.5, 2.26.1
CVE-2018-3180	Medium	5.6	openjdk8	8.181.13-r0	8.191.12-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2018-3180	Medium	5.6	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-3180	Medium	5.6	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-3180	Medium	5.6	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2026-83557	Medium	5.6	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.10, 2.21.6, 2.22.2
CVE-2018-1000654	Medium	5.5	libtasn1	4.13-r0	4.14-r0
CVE-2018-16435	Medium	5.5	openjdk8	8.181.13-r0	8.191.12-r0
CVE-2018-16435	Medium	5.5	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-16435	Medium	5.5	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-16435	Medium	5.5	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2022-38750	Medium	5.5	org.yaml:snakeyaml	1.29	1.31
CVE-2026-34483	Medium	5.4	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.116, 10.1.54, 11.0.21
CVE-2026-43515	Medium	5.4	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22
CVE-2018-20217	Medium	5.3	krb5-libs	1.15.3-r0	1.15.4-r0
CVE-2018-3214	Medium	5.3	openjdk8	8.181.13-r0	8.191.12-r0
CVE-2018-3214	Medium	5.3	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-3214	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-3214	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2019-2762	Medium	5.3	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2762	Medium	5.3	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2762	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2762	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-2769	Medium	5.3	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2769	Medium	5.3	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2769	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2769	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-7317	Medium	5.3	libpng	1.6.34-r1	1.6.37-r0
CVE-2019-7317	Medium	5.3	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-7317	Medium	5.3	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-7317	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-7317	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2020-14621	Medium	5.3	openjdk8	8.181.13-r0	8.272.10-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-14621	Medium	5.3	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14621	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14621	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14803	Medium	5.3	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14803	Medium	5.3	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14803	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14803	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-2781	Medium	5.3	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2781	Medium	5.3	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2781	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2781	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2020-2830	Medium	5.3	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2830	Medium	5.3	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2830	Medium	5.3	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2830	Medium	5.3	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2022-22968	Medium	5.3	org.springframework:spring-context	5.3.13	5.3.19, 5.2.21.RELEASE
CVE-2022-22970	Medium	5.3	org.springframework:spring-beans	5.3.13	5.2.22.RELEASE, 5.3.20
CVE-2023-42795	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	10.1.14, 9.0.81, 8.5.94, 11.0.0-M12
CVE-2023-45648	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.0-M12, 10.1.14, 9.0.81, 8.5.94
CVE-2024-38809	Medium	5.3	org.springframework:spring-web	5.3.13	5.3.38, 6.0.23, 6.1.12
CVE-2024-38820	Medium	5.3	org.springframework:spring-context	5.3.13	6.1.14
CVE-2024-38820	Medium	5.3	org.springframework:spring-web	5.3.13	6.1.14
CVE-2024-38828	Medium	5.3	org.springframework:spring-webmvc	5.3.13	5.3.42
CVE-2025-48988	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.8, 10.1.42, 9.0.106
CVE-2025-52434	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.107
CVE-2025-53506	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.107, 10.1.43, 11.0.9
CVE-2025-61795	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.12, 10.1.47, 9.0.110

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-19032	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.10, 2.21.6, 2.22.2
CVE-2026-22745	Medium	5.3	org.springframework:spring-webmvc	5.3.13	7.0.7, 6.2.18
CVE-2026-41852	Medium	5.3	org.springframework:spring-expression	5.3.13	7.0.8, 6.2.19
CVE-2026-41853	Medium	5.3	org.springframework:spring-webmvc	5.3.13	7.0.8, 6.2.19
CVE-2026-43513	Medium	5.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22
CVE-2026-54514	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.8, 2.21.4, 3.1.4
CVE-2026-54515	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.13.0	3.1.4, 2.18.9, 2.21.5, 2.22.1
CVE-2026-77310	Medium	5.3	com.fasterxml.jackson.core:jackson-databind	2.13.0	2.18.9, 2.21.5, 2.22.1
CVE-2019-2745	Medium	5.1	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2745	Medium	5.1	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2745	Medium	5.1	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2745	Medium	5.1	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-2816	Medium	4.8	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2816	Medium	4.8	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2816	Medium	4.8	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2816	Medium	4.8	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-2975	Medium	4.8	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2975	Medium	4.8	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2975	Medium	4.8	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2975	Medium	4.8	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2020-14556	Medium	4.8	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14556	Medium	4.8	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14556	Medium	4.8	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14556	Medium	4.8	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-2593	Medium	4.8	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2593	Medium	4.8	openjdk8-jre	8.181.13-r0	8.242.08-r0
CVE-2020-2593	Medium	4.8	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2593	Medium	4.8	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2020-2800	Medium	4.8	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2800	Medium	4.8	openjdk8-jre	8.181.13-r0	8.252.09-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-2800	Medium	4.8	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2800	Medium	4.8	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2025-68161	Medium	4.8	org.apache.logging.log4j:log4j-core	2.14.1	2.25.3
CVE-2026-65905	Medium	4.8	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.25, 10.1.58, 9.0.121
CVE-2019-2999	Medium	4.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2999	Medium	4.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2999	Medium	4.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2999	Medium	4.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2021-22060	Medium	4.3	org.springframework:spring-core	5.3.13	5.3.14, 5.2.19
CVE-2026-24880	Medium	4.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.116, 10.1.52, 11.0.20
CVE-2026-25854	Medium	4.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.116, 10.1.53, 11.0.20
CVE-2020-14792	Medium	4.2	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14792	Medium	4.2	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14792	Medium	4.2	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14792	Medium	4.2	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2019-2426	Low	3.7	openjdk8	8.181.13-r0	8.201.08-r0
CVE-2019-2426	Low	3.7	openjdk8-jre	8.181.13-r0	8.201.08-r0
CVE-2019-2426	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.201.08-r0
CVE-2019-2426	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.201.08-r0
CVE-2019-2842	Low	3.7	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2842	Low	3.7	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2842	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2842	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-2894	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2894	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2894	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2894	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2962	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2962	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2962	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2962	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2019-2964	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2964	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2964	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2964	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2973	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2973	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2973	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2973	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2978	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2978	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2978	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2978	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2981	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2981	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2981	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2981	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2983	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2983	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2983	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2983	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2987	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2987	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2987	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2987	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2988	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2988	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2988	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2988	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2992	Low	3.7	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2992	Low	3.7	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2992	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2992	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2020-14577	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14577	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14577	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-14577	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14578	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14578	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14578	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14578	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14579	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14579	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14579	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14579	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14581	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14581	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14581	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14581	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14779	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14779	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14779	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14779	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14781	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14781	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14781	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14781	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14782	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14782	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14782	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14782	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14797	Low	3.7	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14797	Low	3.7	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14797	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14797	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-2583	Low	3.7	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2583	Low	3.7	openjdk8-jre	8.181.13-r0	8.242.08-r0
CVE-2020-2583	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2583	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2020-2590	Low	3.7	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2590	Low	3.7	openjdk8-jre	8.181.13-r0	8.242.08-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-2590	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2590	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2020-2654	Low	3.7	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2654	Low	3.7	openjdk8-jre	8.181.13-r0	8.242.08-r0
CVE-2020-2654	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2654	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2020-2659	Low	3.7	openjdk8	8.181.13-r0	8.242.08-r0
CVE-2020-2659	Low	3.7	openjdk8-jre	8.181.13-r0	8.242.08-r0
CVE-2020-2659	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.242.08-r0
CVE-2020-2659	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.242.08-r0
CVE-2020-2754	Low	3.7	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2754	Low	3.7	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2754	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2754	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2020-2755	Low	3.7	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2755	Low	3.7	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2755	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2755	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2020-2756	Low	3.7	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2756	Low	3.7	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2756	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2756	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2020-2757	Low	3.7	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2757	Low	3.7	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2757	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2757	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2020-2773	Low	3.7	openjdk8	8.181.13-r0	8.252.09-r0
CVE-2020-2773	Low	3.7	openjdk8-jre	8.181.13-r0	8.252.09-r0
CVE-2020-2773	Low	3.7	openjdk8-jre-base	8.181.13-r0	8.252.09-r0
CVE-2020-2773	Low	3.7	openjdk8-jre-lib	8.181.13-r0	8.252.09-r0
CVE-2025-49125	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.8, 10.1.42, 9.0.106
CVE-2025-52520	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.9, 10.1.43, 9.0.107

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-43514	Low	3.7	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	9.0.118, 10.1.55, 11.0.22
CVE-2025-55754	Low	3.5	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.11, 10.1.45, 9.0.109
CVE-2018-3136	Low	3.4	openjdk8	8.181.13-r0	8.191.12-r0
CVE-2018-3136	Low	3.4	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-3136	Low	3.4	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-3136	Low	3.4	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2019-2786	Low	3.4	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2786	Low	3.4	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2786	Low	3.4	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2786	Low	3.4	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2024-22243	Low	3.4	org.springframework:spring-web	5.3.13	6.1.4, 6.0.17, 5.3.32
CVE-2018-3139	Low	3.1	openjdk8	8.181.13-r0	8.191.12-r0
CVE-2018-3139	Low	3.1	openjdk8-jre	8.181.13-r0	8.191.12-r0
CVE-2018-3139	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.191.12-r0
CVE-2018-3139	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.191.12-r0
CVE-2019-2422	Low	3.1	openjdk8	8.181.13-r0	8.201.08-r0
CVE-2019-2422	Low	3.1	openjdk8-jre	8.181.13-r0	8.201.08-r0
CVE-2019-2422	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.201.08-r0
CVE-2019-2422	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.201.08-r0
CVE-2019-2766	Low	3.1	openjdk8	8.181.13-r0	8.222.10-r0
CVE-2019-2766	Low	3.1	openjdk8-jre	8.181.13-r0	8.222.10-r0
CVE-2019-2766	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.222.10-r0
CVE-2019-2766	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.222.10-r0
CVE-2019-2933	Low	3.1	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2933	Low	3.1	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2933	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2933	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2019-2945	Low	3.1	openjdk8	8.181.13-r0	8.232.09-r0
CVE-2019-2945	Low	3.1	openjdk8-jre	8.181.13-r0	8.232.09-r0
CVE-2019-2945	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.232.09-r0
CVE-2019-2945	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.232.09-r0
CVE-2020-14796	Low	3.1	openjdk8	8.181.13-r0	8.272.10-r0

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2020-14796	Low	3.1	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14796	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14796	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2020-14798	Low	3.1	openjdk8	8.181.13-r0	8.272.10-r0
CVE-2020-14798	Low	3.1	openjdk8-jre	8.181.13-r0	8.272.10-r0
CVE-2020-14798	Low	3.1	openjdk8-jre-base	8.181.13-r0	8.272.10-r0
CVE-2020-14798	Low	3.1	openjdk8-jre-lib	8.181.13-r0	8.272.10-r0
CVE-2025-22233	Low	3.1	org.springframework:spring-context	5.3.13	6.2.7, 6.1.20
CVE-2026-22735	Low	2.6	org.springframework:spring-webmvc	5.3.13	7.0.6, 6.2.17
CVE-2026-55276	Low	2.3	org.apache.tomcat.embed:tomcat-embed-core	9.0.55	11.0.23, 10.1.56, 9.0.119

alpine:3.22

Digest sha256:bfe7ceb9f09ec0566c48fb93356e45a47a00be5a1dd14fa5b909e7709c66b034
平台 linux/amd64
作業系統 alpine 3.22.8
大小 —
建立時間 2026-11-05T18:01:05Z
掃描時間 2026-11-07T14:32:29Z
各嚴重等級弱點數 Critical 0 High 0 Medium 1 Low 0 Unrated 0

弱點明細

弱點編號	嚴重等級	CVSS	套件	已安裝版本	修補版本
CVE-2026-4738	Medium	—	zlib	1.3.2-r1	1.4-r0
標籤：MEDIUM					

busybox:1.37

Digest sha256:a7dbc319b1438115a207e11930dc4bb3e643dcb3ec0bdd694bb36cd8fad289ec
平台 linux/amd64
作業系統 —
大小 —
建立時間 2024-09-26T21:31:42Z
掃描時間 2026-11-07T14:33:25Z
各嚴重等級弱點數 Critical 0 High 0 Medium 0 Low 0 Unrated 0

弱點明細

未發現弱點。

附錄

判定方法

掃描工具	Trivy (files) · Trivy
弱點資料庫	—
報告工具	judex 0.1.0

嚴重等級判定規則

嚴重等級由本工具依 CVSS v3 分數判定，不採用掃描工具的標籤；若無 v3 分數則改用 v2，仍無則採用掃描工具標籤並加註說明。

Critical	≥ 9.0
High	7.0 – 8.9
Medium	4.0 – 6.9
Low	0.1 – 3.9
Unrated	–

CVSS 分數來源

來源	數量
nvd	687
redhat	129
–	10
bitnami	1
ghsa	1

本報告涵蓋倉庫中存放的映像檔，不代表叢集內實際執行中的工作負載。

掃描失敗或尚未掃描的映像檔

—

超過 30 天未掃描的映像檔

—

限制事項

1. 本工具重新判定嚴重等級，結果可能與掃描工具介面顯示不同。
2. 不同掃描工具採用的資料來源不同，同一弱點的分數可能不同。
3. NeuVector 會為部分舊弱點補上分數，可能影響嚴重等級判定。
4. 弱點涵蓋範圍取決於掃描工具及其資料庫。
5. 掃描範圍為倉庫中的映像檔，不代表實際執行中的工作負載。
6. 各次報告獨立產生，不保留歷次掃描的變更紀錄。

由 judex 0.1.0 產生