

Eindhoven University of Technology
Department of Mathematics and Computing Science

A taxonomy of finite automata
construction algorithms

by

Bruce W. Watson
93/43

ISSN 0926-4515

All rights reserved
editors: prof.dr. J.C.M. Baeten
prof.dr. M. Rem

Computing Science Report 93/43
Eindhoven, January 1995

A taxonomy of finite automata construction algorithms*

Bruce W. Watson

Faculty of Mathematics and Computing Science

Eindhoven University of Technology

P.O. Box 513, 5600 MB Eindhoven

The Netherlands

e-mail: `watson@win.tue.nl`

Tel: +31 40 474319

January 24, 1995

Abstract

This paper presents a taxonomy of finite automata construction algorithms. Each algorithm is classified into one of two families: those based upon the structure of regular expressions, and those based upon the automata-theoretic work of Myhill and Nerode.

Many of the algorithms appearing in the literature are based upon the structure of regular expressions. In this paper, we make this term precise by defining regular expressions as a Σ -term algebra, and automata constructions as various Σ -algebras of automata. Each construction algorithm is then presented as the unique natural homomorphism from the Σ -term algebra of regular expressions to the appropriate Σ -algebra of automata. The concept of duality is introduced and used to derive more practical construction algorithms. In this way, we successfully present (and relate) algorithms given by Thompson, Berry and Sethi, McNaughton and Yamada, Glushkov, and Aho, Sethi, and Ullman. Efficient implementations (including those due to Chang and Paige, and Brüggemann-Klein) are also treated. As a side-effect we derive several new algorithms.

A pair of impractical, but theoretically interesting, construction algorithms were presented by Myhill and Nerode. Some encoding techniques are used to make the algorithms practical — giving Brzozowski's algorithm based upon derivatives. DeRemer's algorithm is derived as an encoding of Brzozowski's algorithm. Two new algorithms, related to DeRemer's, are derived. Lastly, this family of algorithms is related to the first family.

In addition to classifying the algorithms, we identify (and abstract from) the coding tricks and implementation details present in many of the published algorithms. This paper also presents an introduction to finite automata, Σ -algebras, and their properties.

*Third printing.

Contents

1	Introduction	3
2	Finite automata	6
2.1	Properties of finite automata	7
2.2	Transformations on finite automata	10
2.2.1	Algorithms implementing the subset construction	12
3	Σ-algebras and regular expressions	14
3.1	Some basic definitions	14
3.2	Regular expressions as a Σ -term algebra	15
4	Constructions based on regular expression structure	18
4.1	Thompson's construction	18
4.1.1	A top-down version of Thompson's construction	22
4.1.2	Constructing ϵ -lookahead automata	23
4.2	Towards the Berry-Sethi construction	27
4.2.1	Reduced FA's	32
4.2.2	The Berry-Sethi construction	35
4.2.3	The McNaughton-Yamada-Glushkov construction	37
4.3	The dual of the Berry-Sethi construction	39
4.3.1	The Aho-Sethi-Ullman DFA construction	43
4.4	Extending regular expressions	44
4.5	Efficiently computing with RFA's	46
4.5.1	A practical implementation of the RFA operators	46
4.5.2	More efficient RFA operators	49
5	The Myhill-Nerode, Brzozowski and DeRemer constructions	53
5.1	The Myhill-Nerode construction	54
5.2	The minimal equivalence relation R_L	56
5.2.1	Encoding R_L	56
5.3	The Brzozowski construction	58
5.3.1	Computing derivatives of an ERE	62
5.3.2	Extending derivatives	63
5.4	Relating the Brzozowski and Berry-Sethi constructions	63
5.5	Towards DeRemer's construction	65
5.5.1	Making the construction more efficient	69
6	Conclusions	73
A	Some basic definitions	76
B	Proofs of some Σ-algebra operators	79
References		81

List of Figures

1	The family tree of finite automata constructions	4
2	A representative <i>FA</i> of the isomorphism class $Th((a \cup \epsilon)b^*)$	22
3	The <i>LAFA</i> $K((a \cup \epsilon)b^*)$	26
4	A representative <i>LBFA</i> of the isomorphism class $lbfa((a \cup \epsilon)b^*)$	32
5	A representative <i>DFA</i> of the isomorphism class $MYG((a \cup \epsilon)b^*)$	38
6	A representative <i>FA</i> of the isomorphism class $R \circ lbfa \circ R((a \cup \epsilon)b^*)$	40
7	A representative <i>DFA</i> of the isomorphism class $ASU((a \cup \epsilon)b^*)$	43
8	The <i>DFA</i> $MNmin(\{\epsilon, a\}\{b\}^*)$	58
9	The <i>DFA</i> $Brz((a \cup \epsilon)b^*)$	62
10	The <i>DFA</i> $Iconstr((a \cup \epsilon)b^*)$	69
11	The <i>DFA</i> $Iconstr(b^*)$	69
12	The <i>DFA</i> $DeRemer(b^*)$	70
13	The <i>DFA</i> $Oconstr((a \cup \epsilon)b^*)$	71
14	The <i>DFA</i> 's $Brz(ac \cup bc)$ and $Oconstr(ac \cup bc)$	71

1 Introduction

The **construction of finite automata (from regular expressions)** is one of the oldest and most extensively developed areas of computing science. Just as the variety of applications has grown, so has the diversity of solutions. Some of the solutions were devised to deal with an extension of the problem, such as constructing a finite automaton from an extended regular expression¹, while others were devised with efficiency in mind. Such a myriad of objectives in the algorithm design has lead to solutions that are difficult to compare. Frequently, people that study the algorithms (or *constructions* as they are called in this paper) marvel that two seemingly different algorithms construct isomorphic finite automata from the same regular expression. In order to differentiate these algorithms, a taxonomy of construction algorithms would be useful. This report presents such a taxonomy. A related taxonomy of finite automata minimization algorithms appears in [Wats93].

In developing a taxonomy, we have the luxury of rearranging the relationships between the algorithms, possibly introducing relationships that are not present in the history of an algorithm's development. In this paper, for example, we derive DeRemer's construction from Myhill and Nerode's construction. Historically, the theory of LR parsing had a much greater influence on DeRemer's construction.

Section 2 gives definitions of finite automata and some transformations on them. Section 3 introduces **Σ -algebras**, the foundations for the first family of finite automata constructions. Sections 4 and 5 include the two families of finite automata constructions. Appendix A gives the basic definitions required for reading this paper, while Appendix B presents some proofs related to Section 4. The construction relationships are summarized in the “family tree” shown in Figure 1. The main results of the taxonomy are summarized in the conclusions — Section 6.

In this taxonomy, the finite automata constructions are arranged into two families: those constructions that are based upon the structure of regular expressions, and those based upon the automata-theoretic results of Myhill and Nerode.

The first family of constructions is presented in Section 4:

- **Thompson's construction** as presented in [Thom68]. This algorithm constructs a (possibly nondeterministic) finite automaton (possibly with ϵ -transitions). The description in this paper (Construction 4.3) is based upon those given in [AU92, HU79, Wood87, ASU86] as they are usually considered more readable than Thompson's original paper. Additionally, a more practical (top-down) version of Thompson's construction is presented (Construction 4.5).
- The **ϵ -lookahead finite automaton construction**. This algorithm (Construction 4.11) constructs finite automata that are similar to those constructed by Thompson's construction. They may include so-called ϵ -lookahead transitions.
- The **guarded commands program construction**. This algorithm (Construction 4.17) constructs a guarded commands program from a regular expression. The program is an acceptor for the regular language denoted by the regular expression. It is presented in this paper as a refinement (using hard-coded guarded commands) of the ϵ -lookahead construction.
- The **left-biased and right-biased constructions**. These two constructions (Constructions 4.22 and 4.43 respectively) are related by being the mirror images (or *duals*) of one another. They both construct an **ϵ -free** (possibly nondeterministic) finite automaton.
- Berry and Sethi's construction as presented in [BS86, Glus61, MY60]. This construction (Construction 4.32) uses some precomputation of sets to construct the same finite automaton as the left-biased construction. This construction is implicitly given by Glushkov [Glus61] and McNaughton and Yamada [MY60], where it is used as the nondeterministic finite automaton construction underlying a deterministic finite automaton construction. Berry and Sethi [BS86] explicitly present this algorithm, and they relate it to Brzozowski's construction

look ahead
预测未来

¹ An extended regular expression is one that includes either the intersection or complementation operator.




Figure 1: The family trees of finite automata constructions. The constructions fall into two broad categories: those based on the structure of regular expressions (descended from Σ -algebras), and those based on the Myhill-Nerode theorem. Each construction presented in this paper appears as a vertex in this tree, along with the name that it is given in this paper. If the construction is presented explicitly (in this paper), the construction number appears in parentheses (indicating where it appears in this paper). Solid edges denote refinements of the solution (and therefore explicit relationships between constructions). They are labeled with the name of the refinement. Dotted edges denote relationships (between algorithms) that are not elaborated upon in this paper. Some of the dotted edges are labeled with the name of the relationship or refinement. Vertices that are connected by a dashed edge are related by duality (they are the “mirror images” of one another).

[Brzo64]. We also present (in Construction 4.38) a variant of the Berry-Sethi construction that is more easily implemented in practice.

- McNaughton, Yamada and Glushkov's construction as presented in [MY60, Glus61]. This construction (Construction 4.39) produces a deterministic finite automaton.
- The dual of the Berry-Sethi construction. This construction (Construction 4.45) is the “mirror image” of Berry and Sethi’s construction. A variant of this construction was also mentioned in passing by Aho, Sethi, and Ullman [ASU86, Example 3.22, pg. 140]; it appears in this paper as Construction 4.48. In our presentation of this construction, we correct an error appearing in Aho, Sethi, and Ullman’s version (see Construction 4.48 of this paper).
- Aho, Sethi, and Ullman’s construction as presented in [ASU86, Alg. 3.5, Fig. 3.44]. This construction (Construction 4.50) produces a deterministic finite automaton. It is the “mirror image” of the McNaughton-Yamada construction.

The second family of constructions (from regular expressions) are those based upon the automata-theoretic results of Myhill and Nerode [RS59]. They are presented in Section 5:

- Myhill and Nerode’s construction as presented in [RS59]. This construction (Construction 5.11, which is given as part of the proof of the Myhill-Nerode theorem) uses some language theoretical results to construct a deterministic finite automaton. A version of this construction (Construction 5.19) gives the unique (up to isomorphism) minimal finite automaton. It is not a very practical construction (and usually is not even given as a construction), as it relies on the computation of possibly infinite sets. Certain encoding schemes can be used to represent these infinite sets, making the construction practical. Brzozowski’s and DeRemer’s constructions are two such encoding schemes.
- Brzozowski’s construction as presented in [Brzo64]. This construction (Construction 5.34) gives a deterministic finite automaton. We derive it as an encoding of the Myhill-Nerode construction, although Brzozowski’s derivation was entirely independent.
- The item set construction. This construction (Construction 5.69, not appearing in the literature) produces a deterministic finite automaton, and is based upon the concept of “items” which is borrowed from LR parsing [Knut65]. In this paper, we present it as an encoding of the Myhill and Nerode construction.
- DeRemer’s construction as presented in [DeRe74]. This construction (Construction 5.75) produces a deterministic finite automaton. In this paper, it is derived from the item set construction, although DeRemer made use of LR parsing in his derivation.
- An improvement of the item set construction. This construction (Construction 5.82, not appearing in the literature) produces a deterministic finite automaton, and is also based upon the item set construction. Furthermore, it is an improvement of DeRemer’s construction. A variant (Construction 5.85) is also related to the Aho-Sethi-Ullman deterministic finite automaton construction.

```

class FA { StatePool Q;StateSet S,F; TTransRel Transitions; StateRel E;}
class StatePool {int next;}
class StateSet:protected BitVec{ int set_domain();} calss BitVec{ int bits_in_use; int words; unsigned int data;}
struct TransPair {CharRange transition_label; State transition_destination;} // V x Q
class TransImpl { TransPair *date;} calss Trans:protected TransImpl{ }
class TransRel: public StateTo<Trans> {} // P(V x Q) , out-transitions of state p }
template <class T> class StateTo { T *data; } // State p; p--> (data[p]=T)

```

2 Finite automata

In this section we define finite automata, some of their properties, and some transformations on finite automata.

Definition 2.1 (Finite automaton): A finite automaton (an *FA*) is a 6-tuple (Q, V, T, E, S, F) where

- Q is a finite set of states,
- V is an alphabet,
- $T \in \mathcal{P}(Q \times V \times Q)$ is a transition relation,
- $E \in \mathcal{P}(Q \times Q)$ is an ϵ -transition relation
- $S \subseteq Q$ is a set of start states, and
- $F \subseteq Q$ is a set of final states.

T和E用function表示, 例如 :

$T : V \rightarrow \mathcal{P}(Q \times Q)$, $T(a) = \{(p, q) \mid p, q \in Q, a \in V\}$
 $E : Q \rightarrow \mathcal{P}(Q)$, $E(p) = \{q \mid p, q \in Q\}$

NFA与DFA之间的唯一区别在于转移函数返回值的类型 : NFA转移函数是一个状态集合 ; 而DFA的转移函数返回值是一个单个状态。

The definitions of an alphabet and function \mathcal{P} are in Definition A.9 and Convention A.1 respectively. \square

Remark 2.2: We will take some liberty in our interpretation of the **signatures of the transition relations**. For example, we also use the signatures $T \in V \rightarrow \mathcal{P}(Q \times Q)$, $T \in Q \times Q \rightarrow \mathcal{P}(V)$, $T \in Q \times V \rightarrow \mathcal{P}(Q)$, $T \in Q \rightarrow \mathcal{P}(V \times Q)$, and $E \in Q \rightarrow \mathcal{P}(Q)$. In each case, the order of the Q 's from left to right will be preserved; for example, the function $T \in Q \rightarrow \mathcal{P}(V \times Q)$ is defined as $T(p) = \{(a, q) : (p, a, q) \in T\}$. The signature that is used will be clear from the context. See Remark A.3. The definition of \rightarrow appears in Convention A.2. \square f: A→B, f(a) = b 一个a唯一对应一个b

Remark 2.3: Our definition of finite automata differs from the traditional approach in three ways:

- **multiple start** states are permitted;
- the transition relations are presented in a symmetrical way (**without any inherent left-to-right bias**); and
- the **ϵ -transitions (relation E)** are separate from transitions on alphabet symbols (relation T).


\square

Since we only consider finite automata in this paper, we will frequently simply use the term *automata*.


Convention 2.4 (Finite automaton state graphs): When drawing the state graph corresponding to a finite automaton, we adopt the following conventions:

- All states are drawn as circles (vertices).
- Transitions are drawn as labeled (with ϵ or **alphabet symbol** $a \in V$) directed edges between states.
- Start states have an in-transition with no source (the transition does not come from another state).
- Final states are drawn as two concentric circles.

For example, the *FA* below has two states, one is the start state, and other is the final state, with a transition on a :



\square



Automata H and G are language equivalent. However, nondeterministic automaton G models the fact that after event a, the system can execute either event b or event c, but not both.




图 1.2: Isomorphism $M_0 \cong M_1$ if and only if $V_0 = V_1$ and there exists a bijection $g: Q_0 \rightarrow Q_1$

2.1 Properties of finite automata

In this subsection we define some properties of finite automata. To make these definitions more concise, we introduce particular finite automata $M = (Q, V, T, E, S, F)$, $M_0 = (Q_0, V_0, T_0, E_0, S_0, F_0)$, and $M_1 = (Q_1, V_1, T_1, E_1, S_1, F_1)$.

concise
简明的

Definition 2.5 (Size of an FA): Define the size of an FA as $|M| = |Q|$. \square

Definition 2.6 (Isomorphism (\cong) of FA's): We define isomorphism (\cong) as an equivalence relation on FA's. M_0 and M_1 are isomorphic (written $M_0 \cong M_1$) if and only if $V_0 = V_1$ and there exists a bijection $g: Q_0 \rightarrow Q_1$ such that

- $T_1 = \{(g(p), a, g(q)) : (p, a, q) \in T_0\}$,
- $E_1 = \{(g(p), g(q)) : (p, q) \in E_0\}$,
- $S_1 = \{g(s) : s \in S_0\}$, and
- $F_1 = \{g(f) : f \in F_0\}$.

\square

$$g(p) = \{q, (p \in Q_0, q \in Q_1)\}$$

* 函数f称为是一对一 (one-to-one) 或单射函数 (injection)，当且仅当对于f的定义域中的所有a和b有f(a)=f(b)蕴含a=b。一个函数如果是一对一的，就称为是单射的(injective)。

* 一个从A到B的函数f称为映上 (onto) 或满射 (surjection) 函数，当且仅当对每个b在B有元素a在A使得f(a)=b。一个函数f如果是映上的就称为是满射的(surjective)。

* 函数f是一一对应(one-to-one corresponding)或双射(bijection)函数，如果它既是一一对应的又是映上的，这样的函数称为是双射的(bijective)。

Definition 2.7 (Extending the transition relation T): We extend transition relation $T \in V \rightarrow \mathcal{P}(Q \times Q)$ to $T^* \in V^* \rightarrow \mathcal{P}(Q \times Q)$ as follows:

$$T^*(\epsilon) = E^*$$

and (for $a \in V, w \in V^*$) 转移函数参数由a扩展到w, $T(a) = \{(p, q) \mid p, q \text{ in } Q\} ==> T(w)$

$$T^*(aw) = E^* \circ T(a) \circ T^*(w)$$

Operator \circ (composition) is defined in Convention A.6. This definition could also have been presented symmetrically. \square

Remark 2.8: We also sometimes use the signature $T^* \in Q \times Q \rightarrow \mathcal{P}(V^*)$. \square $T(p, q) = \{w \mid w \text{ in } V^*\}$

Remark 2.9: If $E = \emptyset$ then $E^* = \emptyset^* = I_Q$ where I_Q is the identity relation on the states of M . \square 单位关系

Definition 2.10 (The language between states): The language between any two states $q_0, q_1 \in Q$ is $T^*(q_0, q_1)$.

Definition 2.11 (Left and right languages): The left language of a state (in M) is given by function $\overleftarrow{\mathcal{L}}_M: Q \rightarrow \mathcal{P}(V^*)$, where

$$\overleftarrow{\mathcal{L}}_M(q) = (\cup s : s \in S : T^*(s, q))$$


S: start states, F: final states

所有s到q的字符串集合，从q向左看

The right language of a state (in M) is given by function $\overrightarrow{\mathcal{L}}_M: Q \rightarrow \mathcal{P}(V^*)$, where

$$\overrightarrow{\mathcal{L}}_M(q) = (\cup f : f \in F : T^*(q, f))$$

所有q到f的字符串集合，从q向右看




The subscript M is usually dropped when no ambiguity can arise. \square

Definition 2.12 (Language of an FA): The language of a finite automaton (with alphabet V) is given by the function $\mathcal{L}_{FA} \in FA \rightarrow \mathcal{P}(V^*)$ defined as:


$$\mathcal{L}_{FA}(M) = (\cup s, f : s \in S \wedge f \in F : T^*(s, f))$$

\square



Property 2.13 (Language of an FA): From the definitions of left and right languages (of a state), we can also write:

$$\mathcal{L}_F(M) = (\cup f : f \in F : \overleftarrow{\mathcal{L}}(f)) \quad \text{所有从}s\text{到}f\text{的字符串集合，从}f\text{向左看}$$



and

$$\mathcal{L}_F(M) = (\cup s : s \in S : \overrightarrow{\mathcal{L}}(s)) \quad \text{所有}s\text{到}f\text{的字符串集合（同上），从}s\text{向右看}$$

□

Definition 2.14 (Extension of \mathcal{L}_F): Function \mathcal{L}_F is extended to $[FA]_{\cong}$ as $\mathcal{L}_F([M]_{\cong}) = \mathcal{L}_F(M)$. This use of brackets $([], [])$ is defined in Convention A.7. The choice of representative is irrelevant, as isomorphic FA's accept the same language. □ **Convention A.7 (Equivalence classes of an equivalence relation):**

Definition 2.15 (Complete): A Complete finite automaton is one satisfying the following:

$$\text{Complete}(M) \equiv (\forall q, a : q \in Q \wedge a \in V : T(q, a) \neq \emptyset) \quad \text{完全自动机，转移函数为全函数}$$

□

Property 2.16 (Complete): For all Complete FA's (Q, V, T, E, S, F) :

$$(\cup q : q \in Q : \overleftarrow{\mathcal{L}}(q)) = V^* \quad \text{全自动机的在所有状态的转移函数均为全函数。}$$

□

Definition 2.17 (ϵ -free): Automaton M is ϵ -free if and only if $E = \emptyset$. □ **无epsilon转移**

Remark 2.18: Even if M is ϵ -free it is still possible that $\epsilon \in \mathcal{L}_F(M)$: in this case $S \cap F \neq \emptyset$. □ **E = empty epsilon-free；但是，当S和F有交集时，epsilon属于语言中的一个元素。开始状态也是接受状态。**

Definition 2.19 (Reachable states): For M we can define a reachability relation $\text{Reach}(M) \subseteq (Q \times Q)$ defined as

$$T \in \mathbb{P}(Q \times V \times Q), T = \{(p, a, q) | p, q \in Q, a \in V\},$$

$$\text{Reach}(M) = (\bar{\pi}_2(T) \cup E)^* \quad \bar{\pi}_2(T) = \{(p, q) | (p, a, q) \in T\}$$

Functions π and $\bar{\pi}$ are defined in Convention A.4. Similarly the set of start-reachable states is defined to be:

$$S\text{Reachable}(M) = \text{Reach}(M)(S) \quad \text{start} \rightarrow Q \quad \text{从start state可以到达的状态集合}$$

and the set of final-reachable states is defined to be:

$$F\text{Reachable}(M) = (\text{Reach}(M))^R(F) \quad Q \rightarrow \text{final} \quad \text{可以到达final state的状态集合}$$

Reversal of a relation is defined in Definition A.20. The set of useful states is:


$$\text{Reachable}(M) = S\text{Reachable}(M) \cap F\text{Reachable}(M)$$

$$\text{Reach}(M) = \{(1,2), (2,3), (1,4), (4,2), (4,3)\}$$

$$S\text{Reachable}(M) = \{1, 2, 3, 4, 6\} = \{\text{从start可以到达的state}\}$$

$$F\text{Reachable}(M) = \{1, 2, 3, 4\} = \{\text{可以到达final 的state}\}$$

$$\text{Reachable}(M) = \{1, 2, 3, 4\} = \{\text{删除了不可达状态5,6}\}$$





Remark 2.20: For FA $M = (Q, V, T, E, S, F)$, function $S\text{Reachable}$ satisfies the following interesting property:

$$q \in S\text{Reachable}(M) \equiv \overleftarrow{\mathcal{L}}_M(q) \neq \emptyset$$

$F\text{Reachable}$ satisfies a similar property:

$$q \in F\text{Reachable}(M) \equiv \overrightarrow{\mathcal{L}}_M(q) \neq \emptyset$$

□



```
class DTransRel protected StateTo<DTrans>
What are all States reverse reachable from r?
StateSet reverse_closure( const StateSet& r ) const;
```

```
class DFA yirt ual public FAahs
// Can all States reach a final State?
int Usefulf( ) const;
```

Definition 2.21 (Useful automaton): A *Useful* finite automaton is one with only reachable states:

$$\text{Useful}(M) \equiv (Q = \text{Reachable}(M)) \quad \text{所有可以到达的合法状态集合，其中的每个状态都可到达final state.}$$

□

Definition 2.22 (Start-useful automaton): A *Useful_s* finite automaton is one with only start-reachable states:

$$\text{Useful}_s(M) \equiv (Q = S\text{Reachable}(M)) \quad \text{从start state可以到达的状态集合}$$

□

Definition 2.23 (Final-useful automaton): A *Useful_f* finite automaton is one with only final-reachable states

$$\text{Useful}_f(M) \equiv (Q = F\text{Reachable}(M)) \quad \text{可以到达final state的状态集合}$$

□

Remark 2.24: *Useful_s* and *Useful_f* are closely related by *FA reversal* (to be presented in Transformation 2.34). For all $M \in FA$ we have $\text{Useful}_f(M) \equiv \text{Useful}_s(M^R)$. □

Property 2.25 (Deterministic finite automaton): A finite automaton M is deterministic if and only if

- it does not have multiple start states,
- it is ϵ -free, and 无epsilon转移
- transition function $T \in Q \times V \rightarrow \mathcal{P}(Q)$ does not map pairs in $Q \times V$ to multiple states.
 $T(q,a) = \{ p \}$, (q,a) 不能映射至多于一个以上的状态

Formally,

$$\text{Det}(M) \equiv (|S| \leq 1 \wedge \epsilon\text{-free}(E) \wedge (\forall q, a : q \in Q \wedge a \in V : |T(q, a)| \leq 1))$$

□


Definition 2.26 (Deterministic FA's): *DFA* denotes the set of all deterministic finite automata. We call *FA* \ *DFA* the set of *nondeterministic finite automata*. □

Convention 2.27 (Transition function of a DFA): For $(Q, V, T, \emptyset, S, F) \in DFA$ we can consider the transition function to have signature $T \in Q \times V \not\rightarrow Q$. (A definition of $\not\rightarrow$ appears in Convention A.2.) The transition function is total if and only if the *DFA* is *Complete*. □ T: the set all partial functions.

Property 2.28 (Weakly deterministic automaton): Some authors use a definition of a deterministic automaton that is weaker than *Det*; it uses left languages and is defined as follows:

$$\text{Det}'(M) \equiv (\forall q_0, q_1 : q_0 \in Q \wedge q_1 \in Q \wedge q_0 \neq q_1 : \overleftarrow{\mathcal{L}}(q_0) \cap \overleftarrow{\mathcal{L}}(q_1) = \emptyset)$$

□




Remark 2.29: $\text{Det}(M) \Rightarrow \text{Det}'(M)$ is easily proved. We can also demonstrate that there exists an $M \in FA$ such that $\text{Det}'(M) \wedge \neg\text{Det}(M)$:

$$(\{q_0, q_1\}, \{b\}, \{(q_0, b, q_0), (q_0, b, q_1)\}, \emptyset, \emptyset, \emptyset)$$

In this *FA*, $\overleftarrow{\mathcal{L}}(q_0) = \overleftarrow{\mathcal{L}}(q_1) = \emptyset$, but state q_0 has two out-transitions on symbol alphabet b . □

由于没有start状态，因此均为empty。



predicate

谓词，断言

语句 $P(x)$ 是命题函数 P 在 x 的值，一旦给 x 赋一个值，语句 $P(x)$ 就成为命题并具有真值。如 $P(x)$ 表示语句“ $x > 3$ ”。 $P(4)$ 为真， $P(2)$ 为假。 P 称为谓词， $P(x)$ 谓词函数。

Definition 2.30 (Minimality of a DFA): An $M \in DFA$ is minimal as follows:

$$Min(M) \equiv (\forall M' : M' \in DFA \wedge \mathcal{L}_{FA}(M) = \mathcal{L}_{FA}(M') : |M| \leq |M'|)$$

Predicate Min is defined only on DFA 's. Some definitions are simpler if we define a minimal, but still *Complete*, DFA as follows:

$$Min_C(M) \equiv (\forall M' : M' \in DFA \wedge Complete(M') \wedge \mathcal{L}_{FA}(M) = \mathcal{L}_{FA}(M') : |M| \leq |M'|)$$

Predicate Min_C is defined only on *Complete DFA*'s. \square

Property 2.31 (Minimality of a DFA): An M , such that $Min(M)$, is the unique (modulo \cong) minimal DFA , as will be shown in Section 5. There is no similar uniqueness property for nondeterministic finite automata. \square

Property 2.32 (An alternate definition of minimality of a DFA): For the purposes of minimizing a DFA , we use the definition (defined only on DFA 's):

$$\begin{aligned} Minimal(Q, V, T, \emptyset, S, F) &\equiv (\forall q_0, q_1 : q_0 \in Q \wedge q_1 \in Q \wedge q_0 \neq q_1 : \overrightarrow{\mathcal{L}}(q_0) \neq \overrightarrow{\mathcal{L}}(q_1)) \\ &\quad \wedge Useful(Q, V, T, \emptyset, S, F) \end{aligned}$$

q0,q1由语言不相等，就是q0,q1不可合并，即可区分。
因此，最小的DFA是M中的所有q不可合并（可区分）并且所有状态均可达。

We have the property that (for all $M \in DFA$) $Minimal(M) \equiv Min(M)$. It is easy to prove that $Min(M) \Rightarrow Minimal(M)$. The reverse direction follows from the Myhill-Nerode theorem (Theorem 5.7).

A similar definition that relates to Min_C is (also defined only on DFA 's):

$$\begin{aligned} Minimal_C(Q, V, T, \emptyset, S, F) &\equiv (\forall q_0, q_1 : q_0 \in Q \wedge q_1 \in Q \wedge q_0 \neq q_1 : \overrightarrow{\mathcal{L}}(q_0) \neq \overrightarrow{\mathcal{L}}(q_1)) \\ &\quad \wedge Useful_s(Q, V, T, \emptyset, S, F) \end{aligned}$$

因为是全函数，因此仅考虑Useful(s)即可

We have the property that (for all $M \in DFA$ such that $Complete(M)$) $Minimal_C(M) \equiv Min_C(M)$. The contrapositive of $Min_C(M) \Rightarrow Minimal_C(M)$ is easily proved, and the reverse direction also follows from Theorem 5.7. \square


Remark 2.33: In the literature the second conjunct in the definition of predicate $Minimal_C$ is sometimes erroneously omitted. The necessity of the conjunct can be seen by considering the DFA

$$(\{p, q\}, \{a\}, \{(p, a, p), (q, a, q)\}, \emptyset, \emptyset, \{p\})$$

p是final状态，没有start状态

Here $\overleftarrow{\mathcal{L}}(p) = \overleftarrow{\mathcal{L}}(q) = \emptyset$ (which is also the language of the DFA), $\overrightarrow{\mathcal{L}}(p) = \{a\}^*$, and $\overrightarrow{\mathcal{L}}(q) = \emptyset$. Without the second conjunct, this DFA would be considered $Minimal_C$; clearly this is not the case, as the minimal *Complete DFA* accepting \emptyset is $(\emptyset, \{a\}, \emptyset, \emptyset, \emptyset, \emptyset)$. \square

有限自动机的各种变换操作



2.2 Transformations on finite automata

Transformation 2.34 (FA reversal): FA reversal is given by postfix (superscript) function $R \in FA \longrightarrow FA$, defined as:

$$(Q, V, T, E, S, F)^R = (Q, V, T^R, E^R, F, S) \quad \text{对T和E进行R操作，S,F对调}$$

Function R satisfies

$$(\forall M : M \in FA : (\mathcal{L}_{FA}(M))^R = \mathcal{L}_{FA}(M^R)).$$

and preserves ϵ -free and *Useful*. R操作，不会影响无epsilon转移状态和Useful状态集合，他们将保持不变。

Reversal functions are defined in Definition A.19, and preservation is defined in Definition A.18.


\square

Reach(M) = {(1,2),(2,3),(1,4),(4,2),(4,3)}

SReachable(M) = { 1,2,3,4,6 } = {从start可以到达的state}

FReachable(M) = { 1,2,3,4 } = {可以到达final 的state}

Reachable(M) = { 1,2,3,4 } = {删除了不可达状态5,6 }



2.2 Transformations on finite automata

11

Remark 2.35: The property $(\mathcal{L}_{FA}(M^R))^R = \mathcal{L}_{FA}(M)$ means that function \mathcal{L}_{FA} is its own dual, and is therefore symmetrical (see Definitions A.21 and A.22). \square $f(a) = (f(a^R))^R$

Definition 2.36 (Extending reversal to $[FA]_{\cong}$): We extend reversal to $R \in [FA]_{\cong} \rightarrow [FA]_{\cong}$ defined as $([M]_{\cong})^R = [M^R]_{\cong}$. The definition is independent of the choice of representative (of an equivalence class of \cong) since R and isomorphism commute. \square

Transformation 2.37 (Useless state removal): There exists a function $useful \in FA \rightarrow FA$ that removes states that are not reachable. A definition of this function is not given here, as it is not needed. Function $useful$ satisfies

$$(\forall M : M \in FA : Useful(useful(M)) \wedge \mathcal{L}_{FA}(useful(M)) = \mathcal{L}_{FA}(M))$$

and can be defined so as to preserve ϵ -free, Useful, Det, and Min. \square

Transformation 2.38 (Removing start state unreachable states): Transformation $useful_s \in FA \rightarrow FA$ removes those states that are not start-reachable:

$$\begin{aligned} useful_s(Q, V, T, E, S, F) &= \text{let } U = SReachable(Q, V, T, E, S, F) \quad U = \text{从start state可以到达的状态集合} \\ &\quad \text{in } (U, V, T \cap (U \times V \times U), E \cap (U \times U), S \cap U, F \cap U) \\ &\quad \text{end} \end{aligned}$$

Function $useful_s$ satisfies

$$(\forall M : M \in FA : Useful_s(useful_s(M)) \wedge \mathcal{L}_{FA}(useful_s(M)) = \mathcal{L}_{FA}(M))$$

and preserves Complete, ϵ -free, Useful, Det, and (trivially) Min_C and Min. \square

Remark 2.39: A function $useful_f \in FA \rightarrow FA$ could also be defined, removing states that are not final-reachable. Such a function is not needed in this paper. \square 可以到达final state的状态集合

Transformation 2.40 (Completing an FA): Function $complete \in FA \rightarrow FA$ is defined as:

$$\begin{aligned} complete(Q, V, T, E, S, F) &= \text{let } s \text{ be a new (sink) state} \quad \text{sink/dump state 汇集状态, 有文献称为陷阱状态 trap} \\ &\quad \text{in } \begin{aligned} &\text{let } T' = \{(p, a, s) : \neg(\exists q : q \in Q : (p, a, q) \in T)\} \\ &\quad T'' = \text{if } (T' \neq \emptyset) \text{ then } \{s\} \times V \times \{s\} \text{ else } \emptyset \text{ fi} \\ &\quad \text{in } T' \text{非空, 表示至少一个(p,a,q)没定义, 添加(p,a,s)转移函数, 和自环(s x V x s)} \\ &\quad (Q \cup \text{if } (T' \neq \emptyset) \text{ then } \{s\} \text{ else } \emptyset \text{ fi}, V, \\ &\quad T \cup T' \cup T'', E, S, F) \end{aligned} \\ &\quad \text{end} \end{aligned}$$

It satisfies the requirement that:

$$(\forall M : M \in FA : Complete(complete(M)) \wedge \mathcal{L}_{FA}(complete(M)) = \mathcal{L}_{FA}(M))$$

In general, this transformation adds a sink state to the FA. This transformation preserves ϵ -free, (trivially) Complete, Det, and Min_C . \square

Transformation 2.41 (ϵ removal): An ϵ removal transformation $remove_{\epsilon} \in FA \rightarrow FA$ is one that satisfies


$$(\forall M : M \in FA : \epsilon\text{-free}(remove_{\epsilon}(M)) \wedge \mathcal{L}_{FA}(remove_{\epsilon}(M)) = \mathcal{L}_{FA}(M))$$

There are several possible implementations of $remove_{\epsilon}$. One implementation is:

$$\begin{aligned} remove_{\epsilon, sym}(Q, V, T, E, S, F) &= \text{let } T'(a) = E^* \circ T(a) \circ E^* \quad \text{从S state出发的E, 汇集到S} \\ &\quad \text{in } (Q, V, T', \emptyset, E^*(S), (E^*)^R(F)) \quad \text{到达Final state的E, 汇集到F} \\ &\quad \text{end} \end{aligned}$$

This implementation preserves Complete and Useful and is symmetrical. \square

$T = \{(1, \text{epsilon}, 2), (2, a, 3), (3, \text{epsilon}, 4)\}$
 $= \{(1, a, 4)\}$
 $(1, \text{epsilon}, 2)$ 中的1合并到起始状态
 $(3, \text{epsilon}, 4)$ 中的4合并到接受状态



12

Transformation 2.42 (Subset construction): The function *subset* transforms an ϵ -free FA into a DFA (in the let clause $T' \in \mathcal{P}(Q) \times V \rightarrow \mathcal{P}(\mathcal{P}(Q))$)

```

subset(Q, V, T, ∅, S, F) = let T'(U, a) = {(q : q ∈ U : T(q, a))} 
                           F' = {U : U ∈ P(Q) ∧ U ∩ F ≠ ∅}
                           in (P(Q), V, T', ∅, {S}, F')
breadth-first traversal
T(q0, a) = {q1, q2}
全局状态 : U = {q1, q2}, U 属于 P(Q), 初始 = {s}
T(q1, a) = {q3}, T(q2, a) = {q4}, add {q3, q4} to U


```

In addition to the obvious property that (for all $M \in FA$) $\mathcal{L}_{FA}(\text{subset}(M)) = \mathcal{L}_{FA}(M)$, function *subset* satisfies

$$(\forall M : M \in FA \wedge \epsilon\text{-free}(M) : \text{Det}(\text{subset}(M)) \wedge \text{Complete}(\text{subset}(M)))$$

and preserves *Complete*, ϵ -free, *Det*, and *MinC*. It is also known as the “powerset” construction. \square

Property 2.43 (Subset construction): Let $M_0 = (Q_0, V, T_0, \emptyset, S_0, F_0)$ be finite automata. By the subset construction, the state set of M_1 is $\mathcal{P}(Q_0)$. We have the following property:



Definition 2.44 (Optimized subset construction): The function *subsetopt* transforms an ϵ -free FA into a DFA. This function is an optimized version of *subset*.

```

subsetopt(Q, V, T, ∅, S, F) = let T'(U, a) = {(q : q ∈ U : T(q, a))} 
                               Q' = P(Q) \ {∅}          去除幂集中的空集empty
                               F' = {U : U ∈ P(Q) ∧ U ∩ F ≠ ∅}
                               in (Q', V, T' ∩ (Q' × V × Q'), ∅, {S}, F')
                               end

```

In addition to the property that (for all $M \in FA$) $\mathcal{L}_{FA}(\text{subsetopt}(M)) = \mathcal{L}_{FA}(M)$, function *subsetopt* satisfies

$$(\forall M : M \in FA \wedge \epsilon\text{-free}(M) : \text{Det}(\text{subsetopt}(M)))$$

and preserves ϵ -free, *Det*. \square

2.2.1 Algorithms implementing the subset construction NFA to DFA

Since many of the states in a subset-constructed DFA may be unreachable, we consider an algorithm implementing the composition $\text{useful}_s \circ \text{subset}$. $\text{useful}(s) : \{(a,b)\}, \text{subset} : \{(b,c)\} \Rightarrow \{(a,c)\}$

In this algorithm, D (for done) is the set of states (of the DFA being constructed) already considered, and U (for un-done) is the set of states to be considered. The type of S' , D , and U is $\mathcal{P}(\mathcal{P}(Q))$ (in particular, S' is a set of states in the constructed DFA). This algorithm will yield a *Complete DFA*. In the case that the language of the automaton (being subset constructed) is not V^* , then there will be a state $\emptyset \in D$ which is the sink state. The algorithm is implemented in Dijkstra's guarded command language [Dijk76].

sink(dump) state 汇集状态 , trap陷阱状态

Algorithm 2.45:
 $\{(Q, V, T, \emptyset, S, F) \in FA\}$
 $S', T' := \{S\}, \emptyset;$
 $D, U := \emptyset, S';$
do $U \neq \emptyset \rightarrow$
let $u : u \in U;$
 $D, U := D \cup \{u\}, U \setminus \{u\};$ 添加{u} to D

for $a : a \in V$ **do** 所有字母表, breadth-first traversal

 $d := \bigcup_{q \in U} T(q, a)$
 $\{q_1, q_2\} \xrightarrow{a} \{T(q_1, a), T(q_2, a)\}$
 $d := (\cup q : q \in u : T(q, a));$ 按照全函数考虑, 所有V中的字母均在每个状态可发生, 没发生的生成sink(dump)


if $d \notin D \rightarrow U := U \cup \{d\}$ 添加{d} to U

if $d \in D \rightarrow$ skip 如果d是“旧”状态, is for done, 跳出for循环

fi;
 $T' := T' \cup \{(u, a, d)\}$ 添加转移函数

rof
od;
 $F' := \{d : d \in D \wedge d \cap F \neq \emptyset\}$ $F' = D$ 与 F 的交集

 $\{(D, V, T', \emptyset, S', F') = useful_s \circ subset(Q, V, T, \emptyset, S, F)\}$ 从start state可达的状态集与构造出的子集复合生成的DFA

 $\{Complete(D, V, T', \emptyset, S', F')\}$ 必要时, 生成sink(dump) state汇集状态, 成为全自动机


$$subset \circ useful_s = useful_s(subset(Q, V, T, \emptyset, S, F)) = (D, V, T', \emptyset, S', F')$$

An algorithm implementing $useful_s \circ subsetopt$, yielding a (possibly non-*Complete*) DFA with no sink state is:

Algorithm 2.46: 优化NFA to DFA: 不生成sink(dump)状态
 $\{(Q, V, T, \emptyset, S, F) \in FA\}$
 $S', T' := (\text{if } (S \neq \emptyset) \text{ then } \{S\} \text{ else } \emptyset \text{ fi}), \emptyset;$
 $D, U := \emptyset, S';$
do $U \neq \emptyset \rightarrow$
let $u : u \in U;$
 $D, U := D \cup \{u\}, U \setminus \{u\};$
for $a : a \in V \wedge (\exists q : q \in u : T(q, a) \neq \emptyset)$ **do** 仅考虑部分转移函数, 仅考察原自动机存在的转移

 $d := (\cup q : q \in u : T(q, a));$
if $d \notin D \rightarrow U := U \cup \{d\}$
if $d \in D \rightarrow$ skip

fi;
 $T' := T' \cup \{(u, a, d)\}$ 添加转移函数及U (to D)

rof
od;
 $F' := \{d : d \in D \wedge d \cap F \neq \emptyset\}$
 $\{(D, V, T', \emptyset, S', F') = useful_s \circ subsetopt(Q, V, T, \emptyset, S, F)\}$

Remark 2.47: The algorithm given above can be made more efficient by removing the \exists quantification from the **for** guard, and implementing it in an **if-fi** structure within the **for** statement. The algorithm is left in this form since it is used in Construction 4.50 to present the Aho-Sethi-Ullman algorithm. \square

3 Σ -algebras and regular expressions

Many of the known *FA* constructions have definitions that follow the syntactic structure of regular expressions. The best known (and perhaps the easiest to understand) is Thompson's construction [Thom68]. We would like to formalize the notion of "following the syntactic structure." This is done by introducing Σ -algebras in this section. Regular expressions are then defined as a Σ -algebra.

3.1 Some basic definitions

This subsection provides the basic definitions required for Σ -algebras. Most of these definitions are taken, with slight modification, from [EM85].

Sorts : 有序集

Definition 3.1 (Sorts): Given set S (the elements of which are called *sorts*), a set of sets X is called S -sorted if the elements of X correspond one-to-one with S . The element of X corresponding to $s \in S$ is written X_s . \square

Definition 3.2 (Signature Σ): A signature Σ is a pair (S, Γ) where

- S is a finite set, and
- Γ is an $(S^* \times S)$ -sorted set called the operators. epsilon , empty , symbol(a1...an) gama ==> constant
binary: or(union), concat; unary: start(*), plus,question(?)

We write elements of $S^* \times S$ as $<< s_1, \dots, s_k >, s >$. We can make a couple of notational simplifications:

有限集S及其操作 对，对S中若干元素实施 operator后，生成的新元素添加到S中，成为S的新成员。

arity gama参数的数量

arity : 自变量数目

- Given $\gamma \in \Gamma_{<< s_1, \dots, s_k >, s >}$ we write $\gamma : s_1 \times \dots \times s_k \longrightarrow s$. Constant k is known as the arity of operator γ . k=0 , is constant ; k=1 , is unary operator , k = 2 , is binary operator
- For $\gamma \in \Gamma_{<< >, s >}$ we write $\gamma : s$, and call γ a constant; that is, constants are operators of arity zero. 常数操作是无参的

\square

$S^* \times S$ 是无限的
可数集(countable set): **Remark 3.3:** Although the set $S^* \times S$ is infinite (for $S \neq \emptyset$), this does not imply that there are infinitely many operators. There may be $<< s_1, \dots, s_m >, s > \in S^* \times S$ such that $\Gamma_{<< s_1, \dots, s_m >, s >} = \emptyset$; in that case, there is no operator $\gamma : s_1 \times \dots \times s_m \longrightarrow s$. \square

$S^* \times S$ 是无限的，但是操作是有限的

Several of the following definitions are with respect to signature $\Sigma = (S, \Gamma)$.

限定它为S的最小集合 **Definition 3.4 (Term $_\Sigma$):** The S -sorted set Term_Σ is the smallest S -sorted set such that²

- if $\gamma : s_1 \times \dots \times s_k \longrightarrow s$ (for some $k \geq 0$) ($s, s_1, \dots, s_k \in S$) and (for all $1 \leq i \leq k$) $t_i \in \text{Term}_{\Sigma_{s_i}}$ then $\gamma[t_1, \dots, t_k] \in \text{Term}_{\Sigma_s}$. We adopt the convention that $\gamma[]$ is simply written γ .

\square

Definition 3.5 (Σ -algebra): A Σ -algebra is a pair (V, F) such that

V是载体集 : carrier set; F是操作集 operator set

- V is an S -sorted set, and
- F is a set of functions f_γ (with $\gamma \in \Gamma$) such that
 - if $\gamma : s_1 \times \dots \times s_k \longrightarrow s$ then $f_\gamma \in V_{s_1} \times \dots \times V_{s_k} \longrightarrow V_s$. k个元素实施操作后，成为V的新成员

Set V is called the carrier set of the Σ -algebra. Set F is called the operator set of the Σ -algebra.

\square

²Square brackets ([and]) are used syntactically here.

Class RE is the implementation of the carrier set of the Σ -term algebra (an RE is a term in the Σ -term algebra)
 REops op; // {EPSILON, EMPTY, SYMBOL, OR, CONCAT, STAR, PLUS, QUESTION}
 RE *left, *right; CharRange sym;
 template<class T> class Reg :public T{ }; Template class Reg<T> takes a single type parameter T which is used as the carrier set of the Σ -algebra.
 Class Reg<T> derives publicly from T, and so an Reg<T> can be used anywhere that a T can.
 three type parameters (carrier sets): Reg<RE>, Reg<FA>, and Reg<RFA>. Reg is the only template required, since the regular expression Sigma algebra only has one sort : Reg.

3.2 Regular expressions as a Σ -term algebra

15

Definition 3.6 (Σ -term algebra): The Σ -term algebra is the Σ -algebra $(Term_{\Sigma}, F)$ such that

$$F = \{f_{\gamma} : (\gamma : s_1 \times \dots \times s_k \rightarrow s)\}$$

where (for all $f_{\gamma} \in F$) $f_{\gamma} \in Term_{\Sigma_{s_1}} \times \dots \times Term_{\Sigma_{s_k}} \rightarrow Term_{\Sigma_s}$ is defined as $f_{\gamma}(t_1, \dots, t_k) = \gamma[t_1, \dots, t_k]$. \square

Σ -同态: $(V, F) \Leftrightarrow (W, G)$, 载体 (V, W) 和操作 (F, G) 一一对应。

Definition 3.7 (Σ -homomorphism): Given Σ -algebras (V, F) and (W, G) , a Σ -homomorphism $\boxed{=}$ from (V, F) to (W, G) is an S-indexed set of functions h such that

- for all $s \in S$ we have $h_s \in V_s \rightarrow W_s$, and 这里的映射, 表示V和W一一对应的顺序关系
- for all $\gamma : s_1 \times \dots \times s_k \rightarrow s$, $f_{\gamma} \in F$, $g_{\gamma} \in G$, and $e_1 \in V_{s_1}, \dots, e_k \in V_{s_k}$

$$\begin{array}{ccc} (e_1, e_2) & \xrightarrow{h} & (h(e_1), h(e_2)) \\ f \downarrow & & \swarrow L \\ f(e_1, e_2) & \xrightarrow{h} & g(h(e_1), h(e_2)) \end{array}$$

$$h_s(f_{\gamma}(e_1, \dots, e_k)) = g_{\gamma}(h_{s_1}(e_1), \dots, h_{s_k}(e_k))$$

$$\square \quad (h \circ f)(e_1, e_2) = (g \circ h)(e_1, e_2) \Rightarrow h(f(e_1, e_2)) = g(h(e_1), h(e_2))$$

Remark 3.8: In the case that there is only one sort, a Σ -homomorphism is a singleton set and we speak of the homomorphic function. \square 如, RE, FA 均为单元素集合, 单元素集合 Sigma-同态称为同态函数。

Definition 3.9 (Initial Σ -algebra): A Σ -algebra is *initial* if there is a unique Σ -homomorphism from it to all other Σ -algebras. \square

$$\begin{array}{ccc} (e, f) & \xrightarrow{h_{expr}} & (h_{expr}(e), h_{expr}(f)) \\ plus \downarrow & \swarrow L & \downarrow f_{plus} \\ plus[e, f] & \xrightarrow{h_{expr}} & f_{plus}(h_{expr}(e), h_{expr}(f)) \end{array}$$

Proposition 3.10 (Σ -term algebras): Σ -term algebras are initial. \square

Example 3.11 (Σ -algebras): Consider signature $\Sigma = (S, \Gamma)$ where S consists only of sort *expr*, and Γ consists of constant $a : expr$ and operator $plus : expr \times expr \rightarrow expr$. Some examples of terms in the Σ -term algebra are $plus[a, a]$ and $plus[plus[a, plus[a, a]], a]$.

We define another Σ -algebra X with the natural numbers as the carrier set, 0 (the natural number) as the constant, and $f_{plus}(x, y) = (x \max y) + 1$ as the operator.

As an example of a Σ -homomorphism, we define the “expression tree height” function as a homomorphism from the Σ -term algebra to algebra X . With only one sort, we define function h_{expr} as $h_{expr}(a) = 0$ and $h_{expr}(plus[e, f]) = f_{plus}(h_{expr}(e), h_{expr}(f)) = (h_{expr}(e) \max h_{expr}(f)) + 1$. \square

$$(h_{expr} \circ plus)(e, f) = (f_{plus} \circ h_{expr})(e, f) \Rightarrow h_{expr}(plus[e, f]) = f_{plus}(h_{expr}(e), h_{expr}(f))$$

3.2 Regular expressions as a Σ -term algebra

Definition 3.12 (Regular expressions): We define *regular expressions* (over alphabet V) as the Σ -term algebra over signature $\Sigma = (S, O)$ where


- S consists of a single sort *Reg* (for regular expression), and constants : epsilon , empty , symbol 常数看做无参的操作 (operator)
- O is a set of several constants: $\epsilon, \emptyset, a_1, \dots, a_n : Reg$ (where $V = \{a_1, \dots, a_n\}$) and five operators $\cdot : Reg \times Reg \rightarrow Reg$ (the dot operator), $\cup : Reg \times Reg \rightarrow Reg$, $*$: $Reg \rightarrow Reg$, $+ : Reg \rightarrow Reg$, and $? : Reg \rightarrow Reg$.

Signature Σ will be used throughout the remainder of this paper. We make the following notational simplification when writing terms in the Σ -term algebra:

- operators \cdot (the dot) and \cup are written as infix operators; infix 中缀, postfix 后缀
- operator \cdot is usually not written, juxtaposition is used instead; juxtaposition 毗邻
- operators $*$, $+$, and $?$ are written as postfix (superscript) operator. superscript 上标

The following will also be used for conciseness:

- a term in the Σ -term algebra is called a regular expression;



$$(h \circ f)(v) = (g \circ h)(v) \Rightarrow h(f(v)) = g(h(v))$$

//Sigma.h
 template<class T>
 class Reg :public T {
 // T is carrier set: RE, FA, RFA,
 // 各自的操作, 分别在Sig-RE.cpp, Sig-
 // FA.cpp, Sig-RFA.cpp中定义
 void homomorphic_image(const RE& r);
 Reg<T>& Or(const Reg<T>& r);
 Reg<T>& concat(const Reg<T>& r);

- the set $Term_{\Sigma}$ is denoted by RE ; 包括FA和RFA
- the operators have (ascending) precedence: \cup , \cdot , $*$ and $+$ and $?$; ϵ , \emptyset , and $a_1, \dots, a_n \in V$ are constants;
- regular expressions are usually fully parenthesized; parentheses can be omitted where the operator precedence allows.

□

Remark 3.13: The $?$ operator is non-standard. It will be used to denote union with the language containing the empty string ϵ . See Definition 3.17. □ question操作包含epsilon空串 , plus操作不包含空串 star操作包含epsilon空串

Remark 3.14: Some authors write \cup as (infix) $+$ or as $|$. □

Example 3.15 (A regular expression): Given alphabet $V = \{a, b\}$ the regular expression $\cdot[\cup[a, \epsilon], *[b]]$ is usually written as $(a \cup \epsilon)b^*$. This particular regular expression will be used in running examples of **FA construction**. □

Remark 3.16: Some authors leave \emptyset , $?$, or $+$ out of the definition of regular expressions. Strictly speaking, operators ϵ , $+$, and $?$ are not needed in the signature, since they can be constructed from the other operators. There are some *FA* constructions (from *RE*'s) that have running time dependent on the size of the regular expression. In these cases, treating the extra operators fully (instead of as abbreviations) becomes advantageous. □

Definition 3.17 (The Σ -algebra of regular languages): We define a Σ -algebra of regular languages (over alphabet V), with carrier $\mathcal{P}(V^*)$ and constants:

- $\{\epsilon\} \in \mathcal{P}(V^*)$ (the language containing only the empty string);
- $\emptyset \in \mathcal{P}(V^*)$ (the empty language);
- $\{a\} \in \mathcal{P}(V^*)$ (for all $a \in V$).

and operators:

- $\cup \in \mathcal{P}(V^*) \times \mathcal{P}(V^*) \longrightarrow \mathcal{P}(V^*)$ (language union);
- $\cdot \in \mathcal{P}(V^*) \times \mathcal{P}(V^*) \longrightarrow \mathcal{P}(V^*)$ (language concatenation);
- $* \in \mathcal{P}(V^*) \longrightarrow \mathcal{P}(V^*)$ (Kleene closure); 包含epsilon空串
- $+\in \mathcal{P}(V^*) \longrightarrow \mathcal{P}(V^*)$ (+ closure), and 不包含epsilon空串
- $? \in \mathcal{P}(V^*) \longrightarrow \mathcal{P}(V^*)$ (union with $\{\epsilon\}$, see Definition A.14). 包含epsilon空串 $L^? = L \cup \{\epsilon\}$

Each of these operators corresponds (in the obvious way) to the operators of signature Σ . □

Definition 3.18 (Language denoted by an RE): The function \mathcal{L}_{RE} is the (unique) homomorphism from the Σ -term algebra of *RE*'s to the Σ -algebra of regular languages. Function \mathcal{L}_{RE} maps regular expressions to the languages they denote. □

Definition 3.19 (Equivalence (\doteq) of RE's): Two regular expressions, E_0 and E_1 , are said to be equivalent (written $E_0 \doteq E_1$, note the dot above the $=$) if and only if they denote the same language. □

Definition 3.20 (The nullable Σ -algebra): We define the *nullable* Σ -algebra as follows:

- The carrier set is $\{true, false\}$. true表示sigma-代数中含有epsilon , false表示不含

false: 对应 empty和a in V , 这两种操作均不含epsilon , 因此表示为false
true: 对应 epsilon ; star ; question 这三种操作均含有epsilon , 因此表示为true

以下三种操作可以推导出{true,false}中的一种
disjunction (析取 , 或) , E1 union(or) E2 ;

conjunction (合取 , 与) , E1 and E2 , E1 concatenate E2 ;

identify function: E plus , 如果E中含epsilon , 则为true,否则为false。

$a \in V, E_1, E_2 \in RE, \epsilon \in E_1^*, \epsilon \in E_1^?, \epsilon \notin E_1^+$

$\text{nullable}(\epsilon) = \text{true}$

$\text{nullable}(\emptyset) = \text{nullable}(a) = \text{false}$

$\text{nullable}(E_1 \vee E_2) = \text{nullable}(E_1 \cup E_2)$

$\text{nullable}(E_1 \wedge E_2) = \text{nullable}(E_1 \cdot E_2)$

$\text{nullable}(E_1^*) = \text{true}$

$\text{nullable}(E_1^+) = \text{nullable}(E_1 \cdot E_2)$

$\text{nullable}(E_1^?) = \text{true}$

$\text{nullable}(E_1) = \begin{cases} \text{true} & \epsilon \in E_1 \\ \text{false} & \epsilon \notin E_1 \end{cases}$

3.2 Regular expressions as a Σ -term algebra

(析取disjunction,"OR"), (conjunction合取,"AND")

- The constants are: true, false, and false (corresponding respectively to ϵ , \emptyset , and $a : a \in V$). Here the constant false corresponds to \emptyset and to all $a \in V$. The operators are: \vee (disjunction), \wedge (conjunction), the constant function true, the identity function, and (again) the constant function true (corresponding respectively to \cup , \cdot , $*$, $+$, and $?$). The operators corresponding to $*$ and to $?$ are interesting because they map their argument to the constant true.

We denote the (unique) homomorphism from RE to this Σ -algebra as Null. \square

identity
function单位函
数 , 这里指
nullable(E)的
值与E一致

Property 3.21 (The nullable Σ -algebra): The homomorphism Null has the property that for all $E \in RE$

$$\epsilon \in \mathcal{L}_{RE}(E) \equiv \text{Null}(E)$$

Null(E): true : E中含epsilon , 如epsilon,star,question操作 ; 否则 , false.

union , concatenate , plus操作 , 由Definition 3.20可以递归推导NULL(E)

\square

Definition 3.22 (RE reversal): Regular expression reversal is given by the postfix (superscript) isomorphism $R \in RE \longrightarrow RE$

$$\begin{aligned}\epsilon^R &= \epsilon \\ \emptyset^R &= \emptyset \\ a^R &= a \quad (\text{for } a \in V) \\ (E_0 \cup E_1)^R &= (E_0^R) \cup (E_1^R) \\ (E_0 \cdot E_1)^R &= (E_1^R) \cdot (E_0^R) \\ (E^*)^R &= (E^R)^* \\ (E^+)^R &= (E^R)^+ \\ (E^?)^R &= (E^R)?\end{aligned}$$

Function R satisfies the obvious property that

$$(\forall E : E \in RE : (E^R)^R = E \wedge (\mathcal{L}_{RE}(E^R))^R = \mathcal{L}_{RE}(E))$$

\square

Remark 3.23: The property satisfied by regular expression reversal implies that \mathcal{L}_{RE} is an example of a symmetrical function (according to Definition A.22). \square

对称函数互为对偶

$$f(a) = (f(a^R))^R$$

$$\begin{array}{ccc} V & \xrightarrow{h} & h(v) \\ f \downarrow & \swarrow L & \downarrow g \\ f(v) & \xrightarrow{h} & g(h(v)) \end{array}$$

$$(h \circ f)(v) = (g \circ h)(v) \Rightarrow h(f(v)) = g(h(v))$$

18

$$\begin{array}{ccccc} RE & \xrightarrow{f} & FA & & \\ & \searrow L_{RE} & \downarrow L_{FA} & & \\ & & L_{reg} & & \end{array}$$

$$\begin{array}{ccccc} (re_1, re_2) & \xrightarrow{f} & (f(re_1), f(re_2)) & & \\ RE_{opt} \downarrow & & & & \downarrow FA_{opt} \\ RE_{opt}(re_1, re_2) & \xrightarrow{f} & FA_{opt}(f(re_1), f(re_2)) & & \end{array}$$

4 Constructions based on regular expression structure

A finite automaton construction is any function f , such that the following diagram commutes:

$$\begin{array}{ccc} RE & \xrightarrow{f} & FA \\ & \searrow L_{RE} & \downarrow L_{FA} \\ & & L_{reg} \end{array}$$

Reg<RE> : carrier set is RE
Reg<FA> : carrier set is FA

正则表达式的语言与FA的语言相同。

In this section, we will be defining some Σ -algebras with $[FA]_{\cong}$ as the carrier set; the idea behind the above commuting diagram still holds in this case, as all isomorphic FA's accept the same language. The isomorphism class of an FA corresponding to a given regular expression is the image of the regular expression under the (unique) homomorphism from RE to the other Σ -algebras. Such a homomorphism is a FA construction. Thompson's construction is considered first, followed by a derivation of Berry and Sethi's, McNaughton, Yamada and Glushkov's, and Aho, Sethi, and Ullman's constructions. We also consider methods of efficiently implementing some of the constructions, and methods of constructing FA's from extended regular expressions (see Definition 4.53).

4.1 Thompson's construction RE to FA

One Σ -algebra is based upon an RE to FA construction given by Thompson in [Thom68]. The explanations given in textbooks such as [HU79, Wood87, AU92, ASU86] are generally considered more readable than Thompson's original paper. None of those presentations made use of Σ -algebras.

Definition 4.1 (Thompson's Σ -algebra of FA's): The carrier set is $[FA]_{\cong}$. The operator requirement³ is:

- For the binary operators, the representatives of the arguments must have disjoint state sets. For any two equivalence classes (under \cong) we can always choose a representative of each such that they satisfy this requirement.


The correctness of the operators⁴ is not included here, but is discussed in Theorem B.1. Along with each operator we present a graphic representation of the operator. The operators are separated by horizontal lines for clarity. The operators (with subscript Th, for Thompson) are:

$$C_{\epsilon, Th} = \text{let } q_0, q_1 \text{ be new states} \\ \text{in} \\ \quad [(\{q_0, q_1\}, V, \emptyset, \{(q_0, q_1)\}, \{q_0\}, \{q_1\})]_{\cong} \\ \text{end}$$

二元操作的两个参数的状态集无交集。就是它们分属各自的等价类。等价类之间无交集。
A finite automaton (an FA) is a 6-tuple
(Q, V, T, E, S, F)
Q = {q0, q1}, T = ,
E = {q0, q1}, S = {q0}, F = {q1}

因为epsilon属于L(M)。

因此允许从新的start state(q0)到达新的final state(q1)



$$C_{\emptyset, Th} = \text{let } q_0, q_1 \text{ be new states} \\ \text{in} \\ \quad [(\{q_0, q_1\}, V, \emptyset, \emptyset, \{q_0\}, \{q_1\})]_{\cong} \\ \text{end}$$

FA = (Q, V, T, E, S, F)
Q = {q0, q1}, T = E =
S = {q0}, F = {q1}

³ Σ -algebras presented in this section may have a list of items such as this, stating the requirements on the arguments for the correctness of the operators.


⁴For example, the concatenation operator is correct when (for all M_0, M_1 in Thompson's Σ -algebra) $\mathcal{L}_{FA}(C_{\cdot, Th}([M_0]_{\cong}, [M_1]_{\cong})) = \mathcal{L}_{FA}([M_0]_{\cong})\mathcal{L}_{FA}([M_1]_{\cong})$.



$C_{a,Th} = \text{let } q_0, q_1 \text{ be new states}$
 $\text{in } [(q_0, q_1), V, \{(q_0, a, q_1)\}, \emptyset, \{q_0\}, \{q_1\}]] \cong$
 end


$\text{FA} = (Q, V, T, E, S, F)$
 $Q = \{q_0, q_1\}, T = \{(q_0, a, q_1)\}$
 $E =$
 $S = \{q_0\}, F = \{q_1\}$

for all $a \in V$.




$C_{,Th}([M_0] \cong, [M_1] \cong) = \text{let } (Q_0, V, T_0, E_0, S_0, F_0) = M_0$
 $\text{binary operator , Q0和Q1无交集 , disjoint state sets}$
 $\text{in } (Q_1, V, T_1, E_1, S_1, F_1) = M_1$
 $\text{let } E' = E_0 \cup E_1 \cup (F_0 \times S_1)$
 $\text{in } [(Q_0 \cup Q_1, V, T_0 \cup T_1, E', S_0, F_1)] \cong$
 end

括号外编号：
construction 4.5: td(s,a,f)
FA(const RE& e); FA.cpp
括号内编号：
construction 4.3: Sigma-algebra
Reg(const RE& r); Sig-FA.cpp



$C_{\cup,Th}([M_0] \cong, [M_1] \cong) = \text{let } (Q_0, V, T_0, E_0, S_0, F_0) = M_0$
 $(Q_1, V, T_1, E_1, S_1, F_1) = M_1$
 $\text{binary operator , Q0和Q1无交集 , disjoint state sets}$
 $\text{in } q_0, q_1 \text{ be new states}$
 $\text{let } Q' = Q_0 \cup Q_1 \cup \{q_0, q_1\}$
 $E' = E_0 \cup E_1 \cup (\{q_0\} \times (S_0 \cup S_1))$
 $\cup ((F_0 \cup F_1) \times \{q_1\})$
 $\text{in } [(Q', V, T_0 \cup T_1, E', \{q_0\}, \{q_1\})] \cong$
 end



$$C_{*,Th}([M]_{\cong}) = \text{let } (Q, V, T, E, S, F) = M \\ q_0, q_1 \text{ be new states}$$

star : 表示Kleen闭包 , 包含epsilon , M重复0次或多次 in
plus : 不包含epsilon , M至少重复一次
question : 包含epsilon , M重复0次或一次


let $Q' = Q \cup \{q_0, q_1\}$
in $E' = E \cup (\{q_0\} \times S) \cup \underline{(F \times S)} \cup (F \times \{q_1\}) \cup \{(q_0, q_1)\}$
end

{ epsilon } , M重复了0次

$[(Q', V, T, E', \{q_0\}, \{q_1\})]_{\cong}$

一次或多次重复M的自动机。

M重复0次或多次 , 表示Kleene闭包
包含epsilon语言



闭包操作包含epsilon。因此允许从新的start state(q0)到达新的final state(q1)。这条路径直接从q0到q1 , 表示M重复了0次。它与q0->S->F->q1路径是“或”的关系。

$$C_{+,Th}([M]_{\cong}) = \text{let } (Q, V, T, E, S, F) = M \\ \text{in } q_0, q_1 \text{ be new states}$$

M至少重复一次 , 不包含epsilon语言


$\epsilon \in E_1^*, \epsilon \in E_1^?, \epsilon \notin E_1^+$

end

let $Q' = Q \cup \{q_0, q_1\}$
in $E' = E \cup (\{q_0\} \times S) \cup \underline{(F \times S)} \cup (F \times \{q_1\})$
end

$[(Q', V, T, E', \{q_0\}, \{q_1\})]_{\cong}$

一次或多次重复M的自动机。



$$C_{?,Th}([M]_{\cong}) = \text{let } (Q, V, T, E, S, F) = M \\ \text{in } q_0, q_1 \text{ be new states}$$

M执行0次或1次 , 包含epsilon语言

$\epsilon \in E_1^*, \epsilon \in E_1^?, \epsilon \notin E_1^+$

end


let $Q' = Q \cup \{q_0, q_1\}$
in $E' = E \cup (\{q_0\} \times S) \cup \underline{(F \times \{q_1\})} \cup \{(q_0, q_1)\}$
end

$[(Q', V, T, E', \{q_0\}, \{q_1\})]_{\cong}$

{ epsilon } , M执行0次

M执行仅1次与
右边的0次
是“或”的关系

因为question操作包括epsilon。因此允许从新的start state(q0)到达新的final state(q1)。这条路径直接从q0到q1。如果这条路径执行，M就执行了0次，否则M仅执行1次。



$$f(a) = (f(a^R))^R$$

These operators are symmetrical (see Definition A.22 for a definition of symmetrical operators and functions). Furthermore, they do not depend upon the choice of representative of the equivalence classes (under \cong). An automaton in Thompson's Σ -algebra (here we speak of a representative FA, instead of the isomorphism class) has the following properties:

- It has a single start state with no in-transitions.
- It has a single final state with no out-transitions.
- Every state has either a single in-transition on a symbol (in V), or at most two ϵ in-transitions.
- Every state has either a single out-transition on a symbol (in V), or at most two ϵ out-transitions.



These properties are symmetrical because the operators are symmetrical. Hopcroft and Ullman have shown [HU79] that in practice these properties facilitate the quick simulation of M . For the remainder of this paper we will not duplicate properties such as these, but rather state whether the operator is symmetrical. \square

Remark 4.2: In the literature, these operators are usually presented as having arguments and results of type FA instead of $[FA]_{\cong}$. Such a presentation is given in terms of particular representatives, and ignores the nondeterminism in choosing new states. \square

Construction 4.3 (Thompson): Thompson's construction is the (unique) homomorphism Th from RE to Thompson's Σ -algebra of FA's. \square

Example 4.4 (Thompson's construction): We construct a particular representative⁵ of

$$\begin{aligned} Th((a \cup \epsilon)b^*) &= C_{\cdot, Th}(Th(a \cup \epsilon), Th(b^*)) \\ &= C_{\cdot, Th}(C_{\cup, Th}(Th(a), Th(\epsilon)), C_{*, Th}(b)) \\ &= C_{\cdot, Th}(C_{\cup, Th}(C_{a, Th}, C_{\epsilon, Th}), C_{*, Th}(C_{b, Th})) \end{aligned}$$

(The regular expression is taken from Example 3.15.) The representative is shown in Figure 2. \square

In the next two subsections, we consider two algorithms that construct an FA (from a regular expression) based on the top-down syntactic structure of the regular expression. In these two constructions, we use regular expressions as syntactic objects denoting regular languages.

The first construction is a top-down version of Thompson's construction. The second one is also top-down, but constructs a so-called ϵ -lookahead automaton. Such an automaton can be efficiently simulated or it can be converted to an efficient program, accepting the language of the automaton.

⁵Obviously, constructing the entire equivalence class of isomorphic FA's is not possible

括号外编号：

construction 4.5: td(s,a,f)

FA(const RE& e); FA.cpp

括号内编号：

construction 4.3: Sigma-algebra

Reg(const RE& r); Sig-FA.cpp




Figure 2: A representative FA of the isomorphism class $\text{Th}((a \cup \epsilon)b^*)$.

4.1.1 A top-down version of Thompson's construction

The top-down version of Thompson's construction is a practical implementation of homomorphism Th . It is a function of three parameters: a start state s , a regular expression E , and a final state f . It produces an FA, with start state s and final state f , accepting the language $\mathcal{L}_{RE}(E)$.

Construction 4.5 (Top-down Thompson's): We assume a universe of available states U , to define function


FA.cpp
void td(const State s, const RE& e, const State f);
FA(const RE& e);

$$td \in U \times RE \times U \longrightarrow FA$$


The function is defined recursively on the structure of regular expressions:

$$FA = (Q, V, T, E, S, F)$$

$$\begin{aligned} td(s, \epsilon, f) &= (\{s, f\}, V, \emptyset, \{(s, f)\}, \{s\}, \{f\}) & Q = \{s, f\}, T = \emptyset, E = \{(s, f)\}, S = \{s\}, F = \{f\} \\ td(s, \emptyset, f) &= (\{s, f\}, V, \emptyset, \emptyset, \{s\}, \{f\}) & Q = \{s, f\}, T = E = \emptyset, S = \{s\}, F = \{f\} \\ td(s, a, f) &= (\{s, f\}, V, \{(s, a, f)\}, \emptyset, \{s\}, \{f\}) & \text{(for all } a \in V\text{)} \\ Q = \{s, f\}, T = \{(s, a, f)\}, E = \emptyset, S = \{s\}, F = \{f\} \\ td(s, E_0 \cdot E_1, f) &= \text{let } p, q \text{ be new states} & \text{左表达式 } E_0 = E.\text{left_subexpr}; \\ \text{in} & \quad \text{let } (Q_0, V, T_0, E_0, \{s\}, \{p\}) = td(s, E_0, p) & \text{右表达式 } E_1 = E.\text{right_subexpr}; \\ & \quad (Q_1, V, T_1, E_1, \{q\}, \{f\}) = td(q, E_1, f) & \\ \text{in} & \quad (Q_0 \cup Q_1, V, T_0 \cup T_1, E_0 \cup E_1 \cup \{(p, q)\}, \{s\}, \{f\}) & \text{递归调用左右表达式} \\ \text{end} & & \text{后，依据该式，生成新的FA} \\ \text{end} & & \end{aligned}$$



end




end

$td(s, E^*, f) = \text{let } p, q \text{ be new states}$


$$\begin{aligned} \text{in} & \quad \text{let } (Q, V, T, E, \{p\}, \{q\}) = td(p, E, q) \\ \text{in} & \quad (Q \cup \{s, f\}, V, T, E \cup \{(s, p), (q, p), (q, f), (s, f)\}, \{s\}, \{f\}) \\ \text{end} & \end{aligned}$$

$$\varepsilon \in E_1^*, \varepsilon \in E_1^?, \varepsilon \notin E_1^+$$

end



$\varepsilon \in E_1^*, \varepsilon \in E_1^?, \varepsilon \notin E_1^+$



Function td satisfies the property that, for all $E \in RE$:

```


$$Th(E) = \text{let } s, f \text{ be new states} \\
\text{in} \\
[td(s, E, f)] \simeq \text{递归调用td,生成同构的FA} \\
\text{end}$$


```

□

Construction 4.3
各子FA单独构造，为了确保状态集间无交集，必须重新对状态进行编号。

Construction 4.5
(Top-down Th)
使用全局state sets
不会有交集。

The advantage of function td over homomorphism Th (Construction 4.3) is one of implementation. In Thompson's construction, the subparts of the final FA are constructed in isolation; when two subparts are combined some states may have to be renamed to ensure that the subparts have disjoint state sets. In the top-down construction, more global knowledge is available concerning the final FA and this type of problem is avoided. (In practice, function td would make use of a global variable: the set of remaining available states.)

We do not prove the correctness of construction td in this paper.

4.1.2 Constructing ϵ -lookahead automata

epsilon预测自动机

In this subsection, we extend the top-down Thompson construction (function td) to construct ϵ -lookahead finite automata (*LAFA*). In an *LAFA*, every ϵ -transition is qualified by a symbol of V (known as the lookahead symbol). When simulating an *LAFA*, an ϵ -transition can be taken if the next symbol of the input string matches the lookahead symbol of the ϵ -transition. Naturally, for any given state, it is desirable that there only be one ϵ -transition from the state on any given symbol. The following definitions formalize this.

Definition 4.6 (ϵ -lookahead automata): An ϵ -lookahead finite automaton (*LAFA*) is a 6-tuple (Q, V, T, E, S, F) which is a normal FA with one exception:

- ϵ -transition relation is now $E \in \mathcal{P}(Q \times V \times Q)$ instead of $E \in \mathcal{P}(Q \times Q)$.

□

(1) ϵ -lookahead
使用一个特殊的
symbol表示epsilon转移
(2) normal ϵ -transition
正常的epsilon转移
又称作not care的转移

Definition 2.1 (Finite automaton): A finite automaton is a 5-tuple (Q, V, T, S, F) where

- Q is a finite set of states,
- V is an alphabet,
- $T \in \mathcal{P}(Q \times V \times Q)$ is a transition relation,
- $S \subseteq Q$ is an ϵ -transition relation
- $S \subseteq Q$ is a set of start states, and
- $F \subseteq Q$ is a set of final states.

Remark 4.7: A more commonly presented definition of *LAFA*'s involves both ϵ -lookahead and normal ϵ -transitions (also called *don't-care transitions*). Since we have combined the two, we implement normal ϵ -transitions as lookahead transitions, where the lookahead set is V (the entire alphabet). □

lookahead transition
合并(1),(2), 其中
lookahead set 属于V

Remark 4.8: Naturally, we extend such functions as $\overleftarrow{\mathcal{L}}$, $\overrightarrow{\mathcal{L}}$, and \mathcal{L}_{FA} to use the definition of a *LAFA*. As a result, the language accepted by an *LAFA* is in accordance with the intuitive interpretation of an *LAFA*. □

(RE.h,Deriv.cpp), Function First returns a CRSet denoting the characters which can occur as the first character of a word in the language denoted by the regular expression.

Remark 4.9: In order to present the following definition, we require the definition of function $\text{First} \in RE \rightarrow \mathcal{P}(V)$. Function First is defined in Definition 4.60. Informally, $\text{First}(E)$ is the set of all alphabet symbols that can occur as the first symbol of a word in $\mathcal{L}_{RE}(E)$. \square

计算 (预测) E的第一个symbol是First(E)和L的并集，L表示，如果epsilon属于L(E)，则用L表示连接字符。

Definition 4.10 (Lookahead function): In order to make the definition of the LAFA construction readable, we introduce function $\text{look} \in RE \times \mathcal{P}(V) \rightarrow \mathcal{P}(V)$, defined as:

把L看做属于V的特殊symbol，代表epsilon，就是把epsilon当做V处理。

$\text{look}(E, L) = \text{First}(E) \cup \text{if } (\text{Null}(E)) \text{ then } L \text{ else } \emptyset \text{ fi}$

$\text{Null}(E): \text{true : } E \text{中含epsilon, 如epsilon, star, question操作;}$
 否则, false.

$\text{union, concatenate, plus操作, 由Definition 3.20可以递归推导NULL(E).}$

Property 3.21(The nullable sigma-algebra): $\epsilon \in \mathcal{L}_{RE}(E) \equiv \text{Null}(E)$


We now define an LAFA construction, based on the top-down version of Thompson's construction.


Construction 4.11 (ϵ -lookahead finite automaton): We define function K which takes four parameters: a start state s , a regular expression, final state f , and a lookahead set $L \in \mathcal{P}(V)$. As with the top-down version of Thompson's construction, we assume a universe of states U . Function $K \in U \times RE \times U \times \mathcal{P}(V) \rightarrow \text{LAFA}$ is defined recursively on the structure of regular expressions.

First(epsilon) = empty, Null(epsilon) = true, look(E,L)=First(epsilon) L = L

$$\begin{aligned} K(s, \epsilon, f, L) &= (\{s, f\}, V, \emptyset, \{s\} \times L \times \{f\}, \{s\}, \{f\}) && L \text{是连接s,f的symbol, LAFA的E: P(Q x V x Q)} \\ K(s, \emptyset, f, L) &= (\{s, f\}, V, \emptyset, \emptyset, \{s\}, \{f\}) && L = \text{empty} \\ K(s, a, f, L) &= (\{s, f\}, V, \{(s, a, f)\}, \emptyset, \{s\}, \{f\}) && L = \text{empty} \quad (\text{for all } a \in V) \end{aligned}$$

left=E0, right=E1





Remark 4.12: Since we make use of a single symbol of lookahead, we assume that the input string always has an end-marker $\$$ concatenated on its right. We assume that $\$ \in V$ and that $\$$ does not appear elsewhere in the regular expression. This means that, for $E \in RE$:

```
let   s, f be new states
in
       $K(s, E, f, \{\$\})$       $看做特殊的V, 表示L (epsilon)
end
```

is a LAFA accepting $\mathcal{L}_{RE}(E)$. □

Definition 4.13 (Deterministic LAFA's): A LAFA is deterministic if and only if it has at most one start state and no state has more than one out-transition (either an ϵ -lookahead or a normal transition) on any given alphabet symbol. □ 每个state的out-transition要么是\$,要么是正常的字母V

We present some determinism conditions that ensure that Construction 4.11 produces deterministic LAFA's.

Definition 4.14 (Determinism conditions): In order for function K to produce a deterministic LAFA we impose the following requirements for particular cases of K :


- For $K(s, E_0 \cup E_1, f, L)$ we require that $\text{look}(E_0, L) \cap \text{look}(E_1, L) = \emptyset$.
- For $K(s, E^*, f, L)$, $K(s, E^+, f, L)$, and $K(s, E^?, f, L)$ we require that $\text{First}(E) \cap L = \emptyset$.

□

Remark 4.15: The lookahead transitions in LAFA's make them are more efficient to simulate than an equivalent FA constructed with Thompson's construction. Simulation of a deterministic LAFA is as efficient as the simulation of a DFA. □

Example 4.16 (LAFA): Given new states s, f , we construct the deterministic LAFA $K(s, (a \cup \epsilon)b^*, f, \{\$\})$. The ϵ -lookahead transitions are labeled with both ϵ and the lookahead symbols. The state graph is given in Figure 3. □

括号外编号:
construction 4.5: td(s,a,f)
FA(const RE& e); FA.cpp
括号内编号:
construction 4.3: Sigma-algebra
Reg(const RE& r); Sig-FA.cpp



STRUCTURE




Figure 3: The LAFA $K((a \cup \epsilon)b^*)$.

Construction 4.17 (Creating a program from a LAFA): A deterministic LAFA can also be converted into a program which is a hard-coded simulation of the LAFA. We now describe a mapping $N : RE \times \mathcal{P}(V) \rightarrow GCL$, where GCL denotes the set of all **guarded commands** programs [Dijk76]. This construction is based upon the LAFA construction. The created programs are correct when the determinism conditions of Definition 4.14 hold. In the generated program, we assume that variable $w \in V^*$ is the input string (with an end-marker $\$$ concatenated on its right), and that $hd(w)$ refers to the first symbol of w and $tl(w)$ refers to the remainder of w . We annotate the program fragments (in the definition of N) with the state names (in braces) in the corresponding definition of Construction 4.11. (The semantics of the guarded commands specify that if none of the guards in an **if-else** statement are true, the statement is equivalent to **abort**.)

$N(\epsilon, L)$	=	$\{s\}$	
		if $hd(w) \in L \rightarrow \text{skip}$	$hd(w) = \text{First}(w)$
		fi	
		$\{f\}$	
$N(\emptyset, L)$	=	$\{s\} \text{ abort}\{f\}$	
$N(a, L)$	=	$\{s\}$	(for all $a \in V$)
		if $hd(w) = a \rightarrow w := tl(w)$	下一次迭代处理其余字符
		fi	
		$\{f\}$	
$N(E_0 \cdot E_1, L)$	=	$\{s\} N(E_0, \text{look}(E_1, L))\{p\};$	
		$\{q\} N(E_1, L)\{f\}$	
$N(E_0 \cup E_1, L)$	=	$\{s\}$	
else	→	if $hd(w) \in \text{look}(E_0, L) \rightarrow \{p\} N(E_0, L)\{q\}$	
		$hd(w) \in \text{look}(E_1, L) \rightarrow \{r\} N(E_1, L)\{t\}$	
		fi	
		$\{f\}$	
$N(E^*, L)$	=	$\{s\}$	
		do $hd(w) \in \text{First}(E) \rightarrow \{p\} N(E, \text{First}(E) \cup L)\{q\}$	多次或0次
		od	
		$\{f\}$	
$N(E^+, L)$	=	$\{s\}$	
		repeat $\{p\} N(E, \text{First}(E) \cup L)\{q\}$	至少执行一次
		until $hd(w) \notin \text{First}(E)$	
		$\{f\}$	
$N(E^?, L)$	=	$\{s\}$	
		if $hd(w) \in \text{First}(E) \rightarrow \{p\} N(E, L)\{q\}$	一次或0次
		$hd(w) \in L \rightarrow \text{skip}$	
		fi	
		$\{f\}$	

As with Construction 4.11 we concatenate an end-marker $\$$ on the right of the input string w . The entire program of the acceptor (for $E \in RE$) is:

```

{ $w \in V^*\{\$\}$ }
 $N(E, \{\$\});$ 
if  $w = \$ \rightarrow$  skip
fi
{ $w \in \mathcal{L}_{RE}(E)$ }

```

Termination of the program is equivalent to $w \in \mathcal{L}_{RE}(E)$. \square

Example 4.18 (Programs from LAFAs): We construct the program corresponding to $(a \cup \epsilon)b^*$.

```

{ $w \in V^*\{\$\}$ }
ab* if  $hd(w) \in \{a\} \rightarrow$ 
      if  $hd(w) = a \rightarrow w := tl(w)$ 
      fi
b* ||  $hd(w) \in \{b, \$\} \rightarrow$ 
      if  $hd(w) \in \{b, \$\} \rightarrow$  skip
      fi
      fi;
do  $hd(w) \in \{b\} \rightarrow$ 
    if  $hd(w) = b \rightarrow w := tl(w)$ 
    fi
od
if  $w = \$ \rightarrow$  skip
fi
{ $w \in \{a, \epsilon\}\{b\}^*$ }

```




Figure 3: The LAFa $K((a \cup \epsilon)b^*)$.

\square

4.2 Towards the Berry-Sethi construction

We now consider Σ -algebras of ϵ -free FA's. One such Σ -algebra can be given with symmetrical operators.

Definition 4.19 (Symmetrical ϵ -free Σ -algebra operators): The carrier set is $[FA]_{\cong}$. The operator requirement is (as with Thompson's Σ -algebra):

- For the binary operators, the representatives of the arguments must have disjoint state sets.

The symmetrical ϵ -free preserving operators of the Σ -algebra are defined using Thompson's Σ -algebra operators and symmetrical function $remove_{\epsilon, sym}$ (which is extended to $[FA]_{\cong} \rightarrow [FA]_{\cong}$):

$$\begin{aligned}
C_{\epsilon, sym} &= remove_{\epsilon, sym} \circ C_{\epsilon, Th} \\
C_{\emptyset, sym} &= remove_{\epsilon, sym} \circ C_{\emptyset, Th} \\
C_{a, sym} &= remove_{\epsilon, sym} \circ C_{a, Th} && (\text{for all } a \in V) \\
C_{\cdot, sym} &= remove_{\epsilon, sym} \circ C_{\cdot, Th} \\
C_{\cup, sym} &= remove_{\epsilon, sym} \circ C_{\cup, Th} \\
C_{*, sym} &= remove_{\epsilon, sym} \circ C_{*, Th} \\
C_{+, sym} &= remove_{\epsilon, sym} \circ C_{+, Th} \\
C_{?, sym} &= remove_{\epsilon, sym} \circ C_{?, Th}
\end{aligned}$$

These operators are symmetrical since they are compositions of symmetrical operators (see Proposition A.23). An FA in this Σ -algebra has the property that it is ϵ -free. \square

$$f(a) = (f(a^R))^R$$

cumbersome , clumsy: 笨重的 , 麻烦的

These operators are cumbersome to present fully. Furthermore, they are not particularly useful in practice. For this reason, we now consider asymmetrically defined ϵ -free preserving operators.

The first asymmetrical ϵ -free preserving Σ -algebra operators that we consider are the left-biased ones. The image of a RE in this Σ -algebra is easier to compute than its image in the Σ -algebra given in Definition 4.19).

Definition 4.20 (Σ -algebra of left-biased ϵ -free operators): The carrier set is $[FA]_{\cong}$. The operator requirements are:

LBFA := (Q,V,T,empty,{s},F); class LBFA{StatePoll Q,State s, StateSet F,Trans


Qmap_inverse,StateRel follow}

- For binary operators, the representatives of the arguments must have disjoint state sets.
- The following is required of the representatives of each argument:
 - it is ϵ -free, 免 (无) epsilon转移, E = empty
 - it has a single start state, and 仅有单个start
 - the single start state has no in-transitions.

A proof of the correctness of these operators is outlined in Theorem B.2. As in Thompson's Σ -algebra, each operator is presented here with a graphic representation of the operator⁶. Parts of the operator definitions are intentionally clumsy or verbose. This is done to facilitate the derivation of a Σ -algebra of reduced FA's (in Definition 4.29). The operators are:


$C_{\epsilon,LBFA} = \text{let } q_0 \text{ be a new state}$
 in $[(\{q_0\}, V, \emptyset, \emptyset, \{q_0\}, \{q_0\})]_{\cong}$
 end

State s has no in-transitions; only T(s) (the out-transitions from the start state) and s in F are needed.




注意，这里与Thompson's Sigma-algebra of FA's不同的是没有生成epsilon表示的E关系

$C_{\emptyset,LBFA} = \text{let } q_0 \text{ be a new state}$
 in $[(\{q_0\}, V, \emptyset, \emptyset, \{q_0\}, \emptyset)]_{\cong}$
 end



$C_{a,LBFA} = \text{let } q_0, q_1 \text{ be new states}$
 in $[(\{q_0, q_1\}, V, \{(q_0, a, q_1)\}, \emptyset, \{q_0\}, \{q_1\})]_{\cong}$
 end

for all $a \in V$.



唯一生成新的转移函数的操作。

⁶The graphic representations of the operators depict only the simplest cases of each operator. Thick arrowed lines are intended to depict multiple transitions, while dotted arrowed lines are transitions that are removed from the constructed FA. In the case of the non-constant operators, the start states (of the arguments) is struck out indicating that it is removed.

$C_{\cdot, LBFA}([M_0]_{\cong}, [M_1]_{\cong}) = \text{let } (Q_0, V, T_0, \emptyset, \{s_0\}, F_0) = M_0$

the start states of the arguments to the operators are always removed, with only the out-transitions from the argument's start state being used. the if-fi structures within the final states definition are of the same structure in each operator.

$(Q_1, V, T_1, \emptyset, \{s_1\}, F_1) = M_1$

$N_0 = \epsilon \in \mathcal{L}_{FA}(M_0)$

$N_1 = \epsilon \in \mathcal{L}_{FA}(M_1)$

$N = \epsilon \in (\mathcal{L}_{FA}(M_0) \cup \mathcal{L}_{FA}(M_1))$

q_0 be a new state

$\epsilon \in L_{FA}(M) \equiv s \in F$

start $\rightarrow q_0$

in

let $Q' = Q_0 \setminus \{s_0\} \cup Q_1 \setminus \{s_1\} \cup \{q_0\}$ 总是剔除 s_0, s_1

$T' = T_0 \cup T_1 \cup (F_0 \times T_1(s_1))$

$\cup (\{q_0\} \times (T_0(s_0)))$

$\cup \text{if } (N_0) \text{ then } T_1(s_1) \text{ else } \emptyset \text{ fi})$

$F' = F_1 \cup \text{if } (N_1) \text{ then } F_0 \text{ else } \emptyset \text{ fi}$

$\cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi}$

in

$[(Q', V, T' \cap (Q' \times V \times Q')), \emptyset, \{q_0\}, F' \cap Q')]_{\cong}$

end

transitions that are removed from the constructed FA

$C_{\cup, LBFA}([M_0]_{\cong}, [M_1]_{\cong}) = \text{let } (Q_0, V, T_0, \emptyset, \{s_0\}, F_0) = M_0$

$(Q_1, V, T_1, \emptyset, \{s_1\}, F_1) = M_1$

$N = \epsilon \in (\mathcal{L}_{FA}(M_0) \cup \mathcal{L}_{FA}(M_1))$

q_0 be a new state

in

let $Q' = Q_0 \setminus \{s_0\} \cup Q_1 \setminus \{s_1\} \cup \{q_0\}$ 总是剔除 s_0, s_1

$T' = T_0 \cup T_1 \cup (\{q_0\} \times (T_0(s_0) \cup T_1(s_1)))$


$F' = F_0 \cup F_1 \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi}$

in

$[(Q', V, T' \cap (Q' \times V \times Q')), \emptyset, \{q_0\}, F' \cap Q')]_{\cong}$


end

end




$C_{*,LBFA}([M]_{\cong}) = \text{let } (Q, V, T, \emptyset, \{s\}, F) = M$
 $N = \epsilon \in \mathcal{L}_{FA}(M)^*$ (see Remark 4.21)
 q_0 be a new state
in
 let $Q' = Q \setminus \{s\} \cup \{q_0\}$ 总是剔除 s $T \in P(Q \times V \times Q), T = \{(s, a, q)\}$
 $T(s) \in Q \rightarrow P(V \times Q), T(s) = \{(a, q) : (s, a, q) \in T\}$
 $T' = T \cup (F \cup \{q_0\}) \times T(s)$
 $F' = F \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi}$ star, if(N) 总是成立的
in
 $[(Q', V, T' \cap (Q' \times V \times Q'),$
 $\emptyset, \{q_0\}, F' \cap Q')]_{\cong}$
end
end

epsilon属于N ,
q0属于final set




$C_{+,LBFA}([M]_{\cong}) = \text{let } (Q, V, T, \emptyset, \{s\}, F) = M$
 $N = \epsilon \in \mathcal{L}_{FA}(M)^+$
 q_0 be a new state
in
 let $Q' = Q \setminus \{s\} \cup \{q_0\}$
 $T' = T \cup (F \cup \{q_0\}) \times T(s)$
 $F' = F \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi}$
in
 $[(Q', V, T' \cap (Q' \times V \times Q'),$
 $\emptyset, \{q_0\}, F' \cap Q')]_{\cong}$
end
end

epsilon不属于N ,
q0不属于final set



$C_{?, LBFA}([M]_{\cong}) = \text{let } (Q, V, T, \emptyset, \{s\}, F) = M$
 $N = \epsilon \in \mathcal{L}_{FA}(M) ?$ (see Remark 4.21)
 q_0 be a new state
 in
 $\text{let } Q' = Q \setminus \{s\} \cup \{q_0\}$
 $T' = T \cup (\{q_0\} \times T(s))$ ←与star,plus不同
 $F' = F \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi}$
 in
 $[(Q', V, T' \cap (Q' \times V \times Q')),$
 $\emptyset, \{q_0\}, F' \cap Q')]_{\cong}$
 end
 end

epsilon属于N ,
 q_0 属于final set



$\epsilon \in \mathcal{L}_{FA}(M) \equiv s \in F$
 start → s

The choice of representatives in these operators is irrelevant. For construction purposes, we note that $\epsilon \in \mathcal{L}_{FA}(M) \equiv s \in F$.

Let $LBFA$ (where $LBFA \subset FA$) denote the set of all finite automata that are images⁷ in this Σ -algebra of some $E \in RE$. (That is, $LBFA$ is the smallest set that contains the $LBFA$ constants and is closed under the $LBFA$ operators.) An $LBFA$ has the following properties:

- It is ϵ -free.
- It has a single start state.
- The single start state has no in-transitions.
- All in-transitions to a state are on the same symbol (in V). This can be seen by considering the constants $C_{a,LBFA}$ (for all $a \in V$), which are the only operators introducing new transitions on an alphabet symbol. 只有该操作在a(属于V)产生新的transition , $(q0, a, q1)$.

Only the constants are symmetrical. □

Remark 4.21: Parts of the operator definitions of Definition 4.20 are intentionally clumsy; they are presented this way to facilitate the derivation of a Σ -algebra of reduced FA's (Definition 4.29). □

Construction 4.22 (Left-biased finite automata): Define construction $lbfa \in RE \rightarrow [LBFA]_{\cong}$ to be the unique homomorphism from RE 's to $[LBFA]_{\cong}$. □

Example 4.23 (Σ -algebra of $LBFA$'s): We construct a representative of the isomorphism class $lbfa((a \cup \epsilon)b^*)$ (the regular expression is from Example 3.15). The representative is shown in Figure 4. □

$LBFA$ 的Sigma操作
 有许多冗余操作 ,
 总是要删除start
 state,保留它的
 out-transitions.
 if-fi中在各个operator
 中有相同的结构。
 encoding操作是一种
 廉价的构造LBFA的方法


Computing within the Σ -algebra of $LBFA$'s is inefficient. Each operator defined above does much redundant work. For example, the start states of the arguments to the operators are always removed, with only the out-transitions from the argument's start state being used. Additionally, the if-fi structures within the final states definition are of the same structure in each operator. We wish to introduce an encoding of $LBFA$'s that will allow us to find cheap constructions that are equivalent to $lbfa$. We now describe such an encoding.

A method of encoding an $LBFA$ $(Q, V, T, \emptyset, \{s\}, F)$ is:



The images are really elements of $[LBFA]_{\cong}$. We consider a particular representative of the image.

$T \in \mathbb{P}(Q \times V \times Q)$, $T = \{(p, a, q) \mid (p, a, q) \in T\}$
 $\pi_2(T) = \{a \mid (p, a, q) \in T\}$, $\bar{\pi}_2(T) = \{(p, q) \mid (p, a, q) \in T\}$
 $T \in Q \rightarrow \mathbb{P}(V \times Q)$, $T(p) = \{(a, q) \mid (p, a, q) \in T\}$
 $\pi_2(T(p)) = \{q \mid (p, a, q) \in T\}$, $\bar{\pi}_2(T(p)) = \{a \mid (p, a, q) \in T\}$
 $Q_{map} : Q \times V \times T(p) = \{(a, q) \mid (p, a, q) \in T\}$
 $Q_{map}(q) = \{a\}$
 $Q_{map} : Q \times V \times T \in \mathbb{P}(Q \times V \times Q)$
 $\pi_1(T) = \{p \mid (p, a, q) \in T\}$, $\bar{\pi}_1(T) = \{(a, q) \mid (p, a, q) \in T\}$
 $Q_{map} = (\bar{\pi}_1(T))^R = \{(a, q) \mid (p, a, q) \in T\}^R = \{(q, a) \mid (p, a, q) \in T\}$

STRUCTURES BASED ON REGULAR EXPRESSION STRUCTURE



LBFA: $Q = [0,3]$, $s = 2$, $F = \{0, 1, 2\}$
 $Q_{map_inverse} = \{'a' \rightarrow 0, 'b' \rightarrow 1\}$
 $follow = 0 \rightarrow \{1\}, 1 \rightarrow \{1\}, 2 \rightarrow \{0, 1\}$




RFA : $Q = [0,2]$, first = {0, 1}, last = {0, 1}
 $Q_{map_inverse} = \{'a' \rightarrow 0, 'b' \rightarrow 1\}$
 $follow = 0 \rightarrow \{1\}, 1 \rightarrow \{1\}$ Nullable = true

Figure 4: A representative LBFA of the isomorphism class $lbfa((a \cup \epsilon)b^*)$. epsilon 属于 LBFA
A method of encoding an LBFA ($Q, V, T, \text{empty}, \{s\}, F$) is:

- The ϵ -transitions are not needed (since LBFA's are ϵ -free).
- State s has no in-transitions; only $T(s)$ (the out-transitions from the start state) and $s \in F$ are needed.
- All in-transitions to a state are on the same symbol (in V). Therefore, a state-to-symbol map can be used, and the symbol components of T and $T(s)$ can be removed.

In the following subsection, we introduce reduced FA's as an encoding of LBFA's.



4.2.1 Reduced FA's 简化的FA，规约的FA

Definition 4.24 (RFA): A reduced FA (RFA) is a 7-tuple $(Q, V, follow, first, last, null, Qmap)$ where 由follow和Qmap表示原来的 $T : Q \times V \rightarrow Q$

- Q is a finite set of states,
- V is a alphabet,
- $follow \in \mathcal{P}(Q \times Q)$ is a follow relation (replacing the transition relation),
- $first \subseteq Q$ is a set of initial states (replacing $T(s)$ in an LBFA), $first = \{\text{start状态的out of transitions}\}$
- $last \subseteq Q$ is a set of final states,
- $null \in \{true, false\}$ is a Boolean value (encoding $s \in F$ in an LBFA), and
- $Qmap \in \mathcal{P}(Q \times V)$ maps each state to exactly one symbol (it is also viewed as $Qmap \in Q \rightarrow V$, and its inverse as $Qmap^{-1} \in V \rightarrow \mathcal{P}(Q)$). $Qmap(q) = \{a \mid (p, a, q) \in T\}$ 表示 (q, v) 的一一对应关系。物理含义是进入 q 状态的唯一字母 a

$\epsilon \in L_{FA}(M) \equiv s \in F$
start $\rightarrow s$

□ Trans用struct TransPair 表示: $T(a) = \{q \mid (p, a, q) \in T\}$

RFA.h和LBFA.h: Trans Qmap_inverse, class RFA 中表示其逆: $Qmap^{-1} : V \rightarrow \mathbb{P}(Q)$, 部分函数 $Qmap^{-1}(a) = \{q \mid (p, a, q) \in T\}$

Definition 4.25 (Isomorphism of RFA's): We extend isomorphism (\cong) to RFA's. □


Definition 4.26 (Reversal of RFA's): Reversal of RFA's is given by postfix (superscript) function $R \in RFA \rightarrow RFA$ defined as:

$$(Q, V, follow, first, last, null, Qmap)^R = (Q, V, follow^R, last, first, null, Qmap)$$

□

Definition 4.27 (Extending reversal to $[RFA]_\cong$): We extend reversal to $[RFA]_\cong \rightarrow [RFA]_\cong$ as $([M]_\cong)^R = [M^R]_\cong$. □

We can now give isomorphisms between $[LBFA]_\cong$ and $[RFA]_\cong$. These isomorphisms will be used to present a Σ -algebra of RFA's.



(a) $Q \rightarrow V$ 一一对应关系 (b) $V \rightarrow \mathbb{P}(Q)$ 一对多的关系 (c) 物理含义, 进入状态的字母是唯一的。

$Qmap(q_1) = \{v_1\}, Qmap^{-1}(v_1) = \{q_1\}, (q_3, v_1, q_1) \in T$
 $Qmap(q_2) = \{v_2\}, Qmap^{-1}(v_2) = \{q_2\}, (q_3, v_2, q_2) \in T, (q_4, v_2, q_2) \in T$

Reversal取反操作：
first和last对调

follow取反, Qmap不变(仅表示Q到V的一一对应关系, 因此不变)


Specially construct from an RFA(see Definition 4.28). RFA \rightarrow LBFA
 $//LBFA\ lbfa = LBFA(rfa); // 在 LBFA.h, LBFA.cpp 定义 LBFA(const RFA& r)$
 $// 等效, 由 LBFA 中的 LBFA& decode(const RFA& r) 函数完成$
 $// LBFA\ lbfa; lbfa = lbfa.decode(rfa);$

4.2 Towards the Berry-Sethi construction

同构

Definition 4.28 (An isomorphism between $[LBFA]_{\cong}$ and $[RFA]_{\cong}$): We define isomorphism
 $encode \in [LBFA]_{\cong} \longrightarrow [RFA]_{\cong}$ 这里, LBFA := (Q,V,T,empty,{s},F); RFA := {Q,V,follow,first,last,null,Qmap}

$encode([(Q, V, T, \emptyset, \{s\}, F)]_{\cong}) = \text{let } Q' = Q \setminus \{s\}$
 把{s}从Q中删除, 生成RFA
 in
 $[(Q', V, \bar{\pi}_2(T) \cap (Q' \times Q'), \pi_2(T(s)),$
 $F \cap Q', s \in F, (\bar{\pi}_1(T))^R)]_{\cong}$
 end



and its inverse $decode \in [RFA]_{\cong} \longrightarrow [LBFA]_{\cong}$ as

$decode([M]_{\cong}) = \text{let } (Q, V, follow, first, last, null, Qmap) = M$
 恢复 encode 中删除的{s}, 生成 LBFA
 in

$Qmap(q1) = \{a \mid a \in v\}$

let $T = \{(q_0, Qmap(q_1), q_1) : (q_0, q_1) \in follow\}$ $\{(q0, a, q1)\}$
 $T' = \{(s, Qmap(q), q) : q \in first\}$ $s \rightarrow first$
 $F = last \cup \text{if } (null) \text{ then } \{s\} \text{ else } \emptyset \text{ fi}$ if (null) : 如果 epsilon 属于 LBFA, true
 in
 $[(Q \cup \{s\}, V, T \cup T', \emptyset, \{s\}, F)]_{\cong}$
 end


end

isomorphism
 函数同构, FA同构
 $f(a) = (f_a(a^R))^R'$

Given function $encode$ and $decode$, we would like to obtain a Σ -algebra with $[RFA]_{\cong}$ as carrier (and a corresponding unique homomorphism $rfa \in RE \longrightarrow [RFA]_{\cong}$) such that the following diagram commutes:

rfa: RE-->[RFA];
 Sigma.h,Sig-RE.cpp,Sig-RFA.cpp
 Reg<RE>,Reg<RFA>
 执行对应操作, 实现
 $RE \rightarrow [RFA]$
 $decode: RFA \rightarrow LBFA$
 $encode: LBFA \rightarrow RFA$

lbfa : RE-->[LBFA] 过多冗余操作,
 代码就不实现了。



We can now define a Σ -algebra of RFA 's; it will be cheaper to compute the RFA image of a regular expression and map the RFA to an $LBFA$, than to compute the $LBFA$ directly. The operators of the Σ -algebra of RFA 's are defined using the $LBFA$ operators and the isomorphisms $encode$ and $decode$.

Definition 4.29 (Σ -algebra of RFA 's): The carrier is $[RFA]_{\cong}$. Given the operator requirement in the Σ -algebra of $LBFA$'s, the operator requirement in this Σ -algebra is:

- For binary operators, the argument representatives must have disjoint state sets.

The operators of the Σ -algebra of RFA 's are defined in terms of the operators of $LBFA$'s:

$$\begin{aligned}
 C_{\epsilon,RFA} &= encode(C_{\epsilon,LBFA}) \\
 C_{\emptyset,RFA} &= encode(C_{\emptyset,LBFA}) \\
 C_{a,RFA} &= encode(C_{a,LBFA}) \quad (\text{for all } a \in V) \\
 C_{\cdot,RFA}([M_0]_{\cong}, [M_1]_{\cong}) &= encode \circ C_{\cdot,LBFA}(decode([M_0]_{\cong}), decode([M_1]_{\cong})) \\
 C_{\cup,RFA}([M_0]_{\cong}, [M_1]_{\cong}) &= encode \circ C_{\cup,LBFA}(decode([M_0]_{\cong}), decode([M_1]_{\cong})) \\
 C_{*,RFA}([M]_{\cong}) &= encode \circ C_{*,LBFA}(decode([M]_{\cong})) \\
 C_{+,RFA}([M]_{\cong}) &= encode \circ C_{+,LBFA}(decode([M]_{\cong})) \\
 C_{?,RFA}([M]_{\cong}) &= encode \circ C_{?,LBFA}(decode([M]_{\cong}))
 \end{aligned}$$

decode: RFA \rightarrow LBFA

Definition 4.29

// RFA rfa1 = Reg<RFA>(re); // 在 Sigma.h 中定义 Reg(const RE& r), sigma-operator 在 Sig-RFA.cpp 中定义
// RFA rfa1 = rfa_sigma(re); // 等效, 在 Constrs.h 封装, RFA rfa_sigma(const RE& r)

RFA := (Q, V, follow, first, last, null, Qmap), 原来的开始状态的out-transitions成为first

In full: RE \rightarrow RFA: Sigma operator:

$$C_{\epsilon, RFA} = [(\emptyset, V, \emptyset, \emptyset, \emptyset, true, \emptyset)] \cong \text{null = true, 表示LBFA包含有epsilon, encoding时, s属于F}$$

这两种操作的有效信息, 仅用null的值就可表示

$$C_{\emptyset, RFA} = [(\emptyset, V, \emptyset, \emptyset, \emptyset, false, \emptyset)] \cong \text{null = false, 表示LBFA不包含有epsilon, encoding时, s不属于F}$$

这两种操作不会产生新的状态

对应的LBFA




For all $a \in V$:

$$C_{a, RFA} = \text{let } q_0 \text{ be a new state}$$

// There is a symbol here, so give it a State
一个symbol, 产生一个状态,
只有该操作产生一个新的状态。


$$\text{in } [(\{q_0\}, V, \emptyset, \{q_0\}, \{q_0\}, false, \{(q_0, a)\})] \cong$$



对应的LBFA

删除LBFA的开始状态q0, q1改名为新的q0, 成为first,
 $Q=\{q_0\}$, follow=empty, first=last={q0}, null=false
Qmap={(q0,a)}, 物理含义: q0的输入字母是
a, $a \rightarrow q_0$, q_0 是a的image, 就是Qmap的逆。

$$C_{*, RFA}([M_0] \cong, [M_1] \cong) = \text{let } (Q_0, V, follow_0, first_0, last_0, null_0, Qmap_0) = M_0 \\ (Q_1, V, follow_1, first_1, last_1, null_1, Qmap_1) = M_1$$




LBFA的q0被删除
(下同)

$$\text{in } \begin{aligned} &\text{let } first' = first_0 \cup \text{if } (null_0) \text{ then } first_1 \text{ else } \emptyset \text{ fi} \\ &last' = last_1 \cup \text{if } (null_1) \text{ then } last_0 \text{ else } \emptyset \text{ fi} \\ &\text{in } [(Q_0 \cup Q_1, V, follow_0 \cup follow_1 \cup (last_0 \times first_1), \\ &first', last', null_0 \wedge null_1, Qmap_0 \cup Qmap_1)] \cong \end{aligned}$$

end


$$C_{\cup, RFA}([M_0] \cong, [M_1] \cong) = \text{let } (Q_0, V, follow_0, first_0, last_0, null_0, Qmap_0) = M_0 \\ (Q_1, V, follow_1, first_1, last_1, null_1, Qmap_1) = M_1$$



$$\text{in } [(Q_0 \cup Q_1, V, follow_0 \cup follow_1, first_0 \cup first_1, \\ last_0 \cup last_1, null_0 \vee null_1, Qmap_0 \cup Qmap_1)] \cong$$

end


$$C_{*, RFA}([M] \cong) = \text{let } (Q, V, follow, first, last, null, Qmap) = M$$



$$\text{in } [(Q, V, follow \cup (last \times first), first, last, true, Qmap)] \cong$$

star操作含有epsilon, null=true


$$C_{+, RFA}([M] \cong) = \text{let } (Q, V, follow, first, last, null, Qmap) = M$$



$$\text{in } [(Q, V, follow \cup (last \times first), first, last, null, Qmap)] \cong$$

plus操作的null取值, 取决于E中是否含有
epsilon

$$C_{?, RFA}([M] \cong) = \text{let } (Q, V, follow, first, last, null, Qmap) = M$$



$$\text{in } [(Q, V, follow, first, last, true, Qmap)] \cong$$

question操作含有epsilon, null=true

An $M \in RFA$ (the image of some $E \in RE$) in this Σ -algebra has the following interesting property:

RFA中的状态数等于, V中的symbol数(一定相同)。

- The number of states in M equals the number of (not necessarily distinct) symbols (of V) occurring in E . This follows from the fact that the operators $C_{a, RFA}$ (for all $a \in V$) are the only RFA operators that introduce new states. This property will be used in Section 4.5 to derive a practical implementation of the RFA operators.

因为只有常数a操作, 才产生一个新的状态。
not necessarily distinct

We can also note the following about the operators:

- The operators do not depend on the choice of representatives of the equivalence classes.

Definition 4.30 RE --> RFA

```
// RFA rfa1(re); // 在RFA.h , RFA.cpp定义和实现RFA(const RE& e)
// RFA rfa1 = rfa(re); // 等效 , 在Constrs.h中封装 , RFA rfa(const RE& r)
```

4.2 Towards the Berry-Sethi construction

35

- An important fact is that the operators of this Σ -algebra are symmetrical. That is, each operator is its own dual.

□

a top down version of Sigma homomorphism rfa. RFA.h,RFA.cpp; RFA(const RE& e);

Definition 4.30 (Homomorphism from RE to $[RFA]_{\cong}$): We define $rfa \in RE \rightarrow [RFA]_{\cong}$ to be the unique homomorphism from RE's to $[RFA]_{\cong}$. □

Property 4.31 (Homomorphism rfa): Since the operators of the Σ -algebra of RFA's are symmetrical (symmetrical functions are defined in Definition A.22), so is rfa . That is, $rfa \circ R(E) = R \circ rfa(E)$. □


$$f(a) = (f(a^R))^R$$

R(E) : 对E取反

In Section 4.5 practical implementations of the Σ -algebra of RFA's (in particular, of homomorphism rfa) are discussed.

4.2.2 The Berry-Sethi construction

Given the Σ -algebra of RFA's, we have the desired property that (for $E \in RE$):



lbfa(E) = decode o rfa(E) decode: RFA --> LBFA

We now present Berry and Sethi's FA construction.

Construction 4.32 (Berry-Sethi): Construction $BS \in RE \rightarrow [FA]_{\cong}$ is defined as:

$$BS(E) = decode \circ rfa(E) \quad lbfa(E) = BS(E)$$

An automaton constructed using this function has the same properties as one constructed with function $lbfa$, namely:

- It is ϵ -free.
- It has a single start state.
- The single start state has no in-transitions.
- All in-transitions to a state are on the same symbol (of V).



In practice, function BS is cheaper to compute than $lbfa$. □ 实践中 , rfa(E): RE-->RFA, decode : RFA-->LBFA
较之lbfa(E)是一种廉价的实现方式(RE-->LBFA)。

Remark 4.33: The history of this algorithm is somewhat complicated. The following account is given by Brüggemann-Klein [B-K93b]. Glushkov and McNaughton and Yamada simultaneously (and independently) discovered the same DFA construction [Glus61, MY60]. These papers use the same underlying ϵ -free FA construction to which they apply the subset construction⁸. Unfortunately, neither of them present the ϵ -free FA construction (without the subset construction) explicitly. The underlying ϵ -free FA construction was presented in some depth (with correctness arguments) by Berry and Sethi in [BS86, Alg. 4.4]. In their paper, Berry and Sethi also relate the construction to the Brzozowski construction (Brzozowski's construction appears as Construction 5.34 in this paper).


account
描述 , 账户

In this paper, we adopt the convention that the ϵ -free FA construction (without subset construction) is named after Berry and Sethi, while the construction with the subset construction is named after McNaughton, Yamada, and Glushkov. □

Example 4.34 (Berry-Sethi): A representative of the equivalence class $BS((a \cup \epsilon)b^*)$ is shown in Figure 4 appearing on page 32. This is the same FA as in Example 4.23. (This follows from the fact that the Berry-Sethi construction and the LBFA Σ -algebra are commuting ways of arriving at the same FA isomorphism class). □

⁸The underlying construction may actually produce a nondeterministic finite automata.

BS(E)
LBFA: Q = [0,3], s = 2, F = { 0 1 2 }
Qmap_inverse = { 'a'->0 'b'->1 }
follow = 0->{ 1 },1->{ 1 }, 2->{ 0 1 }



RFA : Q = [0,2], first = { 0 1 }, last = { 0 1 }
Qmap_inverse = { 'a'->0 'b'->1 }
follow = 0->{ 1 },1->{ 1 } Nullable = true

It is possible to find a composition of functions that commutes with $lbfa$ (and therefore $decode \circ rfa$) and is cheaper to compute in practice. We first give some required definitions.

Definition 4.35 (Non-isomorphic mapping from $[RFA]_{\cong}$ to $[FA]_{\cong}$): Function $convert \in [RFA]_{\cong} \rightarrow [FA]_{\cong}$ is defined as:

$L = \{a, aab, baa\}$

$V^{-1}L = \{\epsilon, aa, ab\}, V \in \{a, b\}$

RFA: $\{s\} \times \{\text{first}\}$
在Qmap,follow中存储

$convert([M]_{\cong}) = \begin{array}{l} \text{let } (Q, V, follow, first, last, null, Qmap) = M \\ \text{in} \\ \quad \text{let } T = \{(q_0, Qmap(q_1), q_1) : (q_0, q_1) \in follow\} \\ \quad \text{in } [(Q, V, T, \emptyset, first, last)]_{\cong} \\ \quad \text{end} \end{array}$

convert类似于decode(P35),
不同之处是convert获得的start
仅取自原来RFA的first,
没有保留start到first的转移函数信息。
简单的丢掉start状态。

尤其是转为LBFA时，仅取first中的一个作为LBFA要求的唯一start.

An important property of this function is that:

$$(\forall E : E \in RE : \mathcal{L}_{FA} \circ convert \circ rfa(E) = V^{-1} \mathcal{L}_{RE}(E))$$

This follows from the fact that $convert$ simply discards the transitions that would be out of the start state. Function $convert$ does not add any new states, unlike function $decode$ which adds a new start state. \square

这里：
FA := (Q, V, T, empty, first, last);
class LBFA{
StatePoll Q, State s, StateSet F, Trans
Qmap_inverse, StateRel follow};因此虽然
取RFA的最小编号为LBFA的start，但是原来的
转移函数信息，仍然保留在
Qmap_inverse.follow中。

LBFA & LBFA::convert(const
RFA& r)取RFA的first中编号最
小的状态为LBFA的单个
{start}，就是原start的out-
transition中的一个状态。

L(E)中由V的所有后缀组成的字符串。
即：删除第一个字符后的字符串集合。

Definition 4.36 (Adding a begin-marker): Define function $marker_b \in RE \rightarrow RE$ as:

$$marker_b(E) = \$ \cdot E$$

Where $\$$ is an alphabet symbol, called a begin-marker. (In the literature, it is usually assumed — for no particular reason — that symbol $\$$ does not occur in regular expression E .) This function satisfies the obvious property that:


$$(\forall E : E \in RE : \mathcal{L}_{RE}(marker_b(E)) = \{\$\} \mathcal{L}_{RE}(E))$$

\square

Given functions $marker_b$, rfa , $convert$, and the following important property, we can construct an efficient alternative to homomorphism $lbfa$.

Property 4.37 (Functions $marker_b$, rfa , and $convert$): Because of the properties of $convert$ and $marker_b$, we can show that:

$$\begin{aligned} & convert \circ rfa \circ marker_b(E) \\ = & \{ \text{Definition of } marker_b \} \\ & convert \circ rfa(\$ \cdot E) \\ = & \{ \text{Definitions of } rfa, C_{\cdot, RFA} \} \\ & convert \circ C_{\cdot, RFA}(rfa(\$), rfa(E)) \\ = & \{ \text{Definitions of } rfa, C_{\$, RFA} \} \\ & convert \circ C_{\cdot, RFA}(C_{\$, RFA}, rfa(E)) \\ = & \{ \text{Definitions of } convert, C_{\cdot, RFA}, C_{\$, RFA}, rfa, \text{ and } decode \} \\ & decode \circ rfa(E) \\ = & \{ \text{Commutativity} \} \\ & lbfa(E) \end{aligned}$$



homomorphism: $rfa: RE \rightarrow RFA$

$C_{\cdot, RFA}(rfa(\$), rfa(E)) = C_{\cdot, RFA}(C_{\$, RFA}, rfa(E)) = L_{RE}(\$E) = \{\$\} L_{RE}(E)$
convert 简单剔除 E 的第一个字符。 $L_{FA} \circ convert \circ rfa(E) = V^{-1} L_{RE}(E)$

$convert(C_{\cdot, RFA}(C_{\$, RFA}, rfa(E))) = rfa(E)$

\square

RE

\xrightarrow{rfa}

RFA

$\downarrow L_{FA}$

L_{reg}

\square

RE

\xrightarrow{rfa}

(\\$E)

$\downarrow rfa$

\square

S · E

\xrightarrow{rfa}

$rfa(\$) \cdot rfa(E)$

The composite $convert \circ rfa \circ marker_b$ is an alternative (and in practice, cheaper) implementation of $lbfa$. \square

The fact that $\text{convert} \circ \text{rfa} \circ \text{marker}_b$ is a construction is depicted in the following commuting diagram:

$$\begin{array}{ccc}
 RE & \xrightarrow{\text{lbfa}} & [LBFA]_{\cong} \\
 \downarrow \text{marker}_b & & \uparrow \text{convert} \\
 RE & \xrightarrow{\text{rfa}} & [RFA]_{\cong}
 \end{array}$$

Construction 4.38 (A variation on the Berry-Sethi construction): Instead of constructing an FA using the functions lbfa or BS , it is cheaper in practice to use the composite function

$$\text{convert} \circ \text{rfa} \circ \text{marker}_b(E)$$

□

4.2.3 The McNaughton-Yamada-Glushkov construction

Since the Berry-Sethi construction produces an ϵ -free (possibly nondeterministic) FA, we now consider making the resulting FA deterministic.

$$\text{lbfa}(E) = \text{decode} \circ \text{rfa}(E)$$

Construction 4.39 (McNaughton-Yamada-Glushkov): (We assume that the composite function $\text{useful}_s \circ \text{subset}$ is extended to $[FA]_{\cong} \rightarrow [DFA]_{\cong}$.) The McNaughton-Yamada-Glushkov DFA construction is $MYG \in RE \rightarrow [DFA]_{\cong}$, defined as:


$$\begin{aligned}
 MYG(E) = \text{useful}_s \circ \text{subset} \circ \text{decode} \circ \text{rfa}(E) & \quad RE \xrightarrow{\text{rfa}} [RFA]_{\cong} \xrightarrow{\text{decode}} [NFA]_{\cong} \\
 & \quad [DFA]_{\cong} \xleftarrow{\text{useful}_s} P(Q) \xrightarrow{\text{subset}} [DFA]_{\cong}
 \end{aligned}$$

A DFA produced by MYG is *Complete* (by a property of $\text{useful}_s \circ \text{subset}$). A practical implementation is given in Algorithm 4.42 (given below), which implements $\text{useful}_s \circ \text{subset} \circ \text{decode}$. Homomorphism rfa can be implemented using the techniques described in Section 4.5. This algorithm is the same⁹ as that given by McNaughton and Yamada [MY60, Construction method on pg. 44]. □

Example 4.40 (McNaughton-Yamada-Glushkov): In the case of $(a \cup \epsilon)b^* \in RE$, the Berry-Sethi construction produces a deterministic FA. Function MYG produces a similar DFA, with a sink state added to make it *Complete*. The state graph of a representative DFA of isomorphism class $MYG((a \cup \epsilon)b^*)$ is shown in Figure 5. □

Remark 4.41: The variation on the Berry-Sethi construction (Construction 4.38) can be used for a practical implementation of the McNaughton-Yamada-Glushkov construction. This would yield a construction not appearing in the literature. □


⁹The only difference is that the unrolled first iteration step is not presented explicitly in McNaughton and Yamada's paragraph describing their algorithm.




BS(E)
LBFA: Q = [0,3), s = 2, F = { 0 1 2 }
Qmap_inverse = { 'a'->0 'b'->1 }
follow = 0->{ 1 }, 1->{ 1 }, 2->{ 0 1 }

38

4 CONSTRUCTIONS BASED ON REGULAR EXPRESSION STRUCTURE



RFA : Q = [0,2], first = { 0 1 }, last = { 0 1 }
Qmap_inverse = { 'a'->0 'b'->1 }
follow = 0->{ 1 }, 1->{ 1 } Nullable = true



DFA
Q = [0,3)
S = { 0 }, F = { 0 1 2 }
Transitions = 0->{ 'a'->1 'b'->2 },
1->{ 'b'->2 }, 2->{ 'b'->2 }




Figure 5: A representative DFA of the isomorphism class $MYG((a \cup \epsilon)b^*)$.

Composite function $useful_s \circ subset \circ decode$ can be implemented using Algorithm 2.45 (which implements $useful_s \circ subset$). Here, the first iteration is unrolled to accommodate the definition of function $decode$, and some obvious improvements have not yet been made).

be unrolled to 展开
accommodate 使适应

decode:
添加一个开始状态


```

{(Q,V,follow,first,last,null,Qmap) ∈ RFA}
let S = {{s}} : s is a new state, s ∉ Q;
T := ∅;
D,U := ∅,S;
let u : u ∈ U; u={s}
D,U := D ∪ {u},U \ {u};
for a : a ∈ V do
    d := (U(p : p ∈ U) {q : q ∈ first ∧ Qmap(q) = a});    d := ∪{q | q ∈ first ∧ Qmap(q) = a}
    if d ∉ D → U := U ∪ {d}                                {s} →a {d}
    || d ∈ D → skip
    fi;
    T := T ∪ {(u,a,d)}
rof; 以上，建立开始状态{s}与{first}的转移函数T={(s,v,f) | v属于V , f属于{first}}
do U ≠ ∅ →
    let u : u ∈ U;
    D,U := D ∪ {u},U \ {u};
    for a : a ∈ V do
        d := (U(p : p ∈ U : {q : (p,q) ∈ follow ∧ Qmap(q) = a});    d := ∪p ∈ U{q | (p,q) ∈ follow ∧ Qmap(q) = a}
        if d ∉ D → U := U ∪ {d}                                u = {p1,p2}, d = {q1,q2},
        || d ∈ D → skip                                         follow(p1) = q1, follow(p2) = q2, Qmap(q1) = Qmap(q2) = a
        fi;                                                 {p1,p2} →a {q1,q2}
        T := T ∪ {(u,a,d)}
    rof
od;
F := {d : d ∈ D ∧ d ∩ last ≠ ∅} ∪ if (null) then S else ∅ fi  if (epsilon属于L(FA),则开始状态{s}属于接受状态)
{[(D,V,T,∅,S,F)]≈ = usefuls ∘ subset ∘
decode([(Q,V,follow,first,last,null,Qmap)]≈)
{Complete(D,V,T,∅,S,F)}}

```

$RE \rightarrow [DFA]_{\approx}$

$MYG(E) = useful_s \circ subset \circ decode \circ rfa(E)$



Some simplification gives the algorithm:

Algorithm 4.42 (McNaughton-Yamada-Glushkov):

```

 $\{(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map}) \in RFA\}$ 
let  $S = \{\{s\}\} : s$  is a new state,  $s \notin Q$ ; s为DFA的start state
 $T := \emptyset;$ 
 $D, U := S, \emptyset;$ 
for  $a : a \in V$  do
     $d := \{q : q \in \text{first} \wedge Q\text{map}(q) = a\}$   $d := \bigcup \{q | q \in \text{first} \wedge Q\text{map}(q) = a\}$ 
     $U := U \cup \{d\};$   $\{s\} \xrightarrow{a} \{d\}$ 
     $T := T \cup \{\{s\}, a, d\}$ 
rof; 以上，建立开始状态{s}与{first}的转移函数T={({s,v,f} | v属于V , f属于{first})}
do  $U \neq \emptyset \longrightarrow$ 
    let  $u : u \in U;$ 
     $D, U := D \cup \{u\}, U \setminus \{u\};$ 
    for  $a : a \in V$  do
         $d := (\cup p : p \in u : \{q : (p, q) \in \text{follow} \wedge Q\text{map}(q) = a\});$   $d := \bigcup_{p \in u} \{q | (p, q) \in \text{follow} \wedge Q\text{map}(q) = a\}$ 
        if  $d \notin D \longrightarrow U := U \cup \{d\}$   $u = \{p_1, p_2\}, d = \{q_1, q_2\},$ 
        if  $d \in D \longrightarrow \text{skip}$   $\text{follow}(p_1) = q_1, \text{follow}(p_2) = q_2, Q\text{map}(q_1) = Q\text{map}(q_2) = a$ 
        fi;  $\{p_1, p_2\} \xrightarrow{a} \{q_1, q_2\}$ 
         $T := T \cup \{(u, a, d)\}$ 
    rof
od;
 $F := \{d : d \in D \wedge d \cap \text{last} \neq \emptyset\} \cup \text{if } (\text{null}) \text{ then } S \text{ else } \emptyset \text{ fi}$  if (epsilon属于L(FA),则开始状态{s}属于接受状态)
 $\{[(D, V, T, \emptyset, S, F)] \cong = \text{useful}_s \circ \text{subset} \circ$ 
 $\text{decode}([(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map})] \cong )\}$ 
 $\{\text{Complete}(D, V, T, \emptyset, S, F)\}$ 

```

This algorithm is used in the McNaughton-Yamada construction [MY60].

4.3 The dual of the Berry-Sethi construction

The following commuting diagram gives a property of regular expressions and regular languages that will prove to be useful:

P37. Property 4.31(Homomorphism rfa)

$$rfa \circ R(E) = R \circ rfa(E)$$

$$\begin{array}{ccc} E & \xrightarrow{rfa} & RFA \\ R \downarrow & \searrow & \downarrow R \\ \circ & \xrightarrow{rfa} & \circ \end{array}$$

$$\begin{array}{ccc} RE & \xrightarrow{\mathcal{L}_{RE}} & \mathcal{L}_{\text{reg}} \\ R \downarrow & & \uparrow R \\ RE & \xrightarrow{\mathcal{L}_{RE}} & \mathcal{L}_{\text{reg}} \end{array}$$

$$\text{Dual construction: } R \circ f \circ R$$

$$RE \xrightarrow{R} RE \xrightarrow{f} FA \xrightarrow{R} FA$$

$$f : FA \text{ construction}$$

$$\begin{array}{ccc} RE & \xrightarrow{f} & FA \\ & \searrow & \downarrow L_{FA} \\ & & L_{\text{reg}} \end{array}$$

In this diagram, the two reversal operators are different: one is reversal of RE 's, while the other is reversal of languages.

Given the definition of an FA construction f and the above diagram, we have the property that the dual of a construction is again a construction. That is, $R \circ f \circ R$ is also a construction. Such a dual construction is less efficient than f (since it involves two reversal functions), and we explore ways to efficiently implement the dual constructions.

Construction 4.43 (Right-biased): We can use $R \circ lbf \circ R$ as a construction. For any given $E \in RE$, a representative of $R \circ lbf \circ R(E)$ has the following properties (the properties are based upon those of the left-biased Σ -algebra):




Figure 6: A representative FA of the isomorphism class $R \circ lbfa \circ R((a \cup \epsilon)b^*)$.


$R \circ convert \circ R \circ rfa \circ marker_e((a \cup \epsilon)b^*)$

- It is ϵ -free.
- It has a single final state. 原来lbfa的唯一start变成final
- The single final state has no out-transitions.
- All out-transitions from a state are on the same symbol (in V).

□

Example 4.44 (Right-biased construction): We construct a representative FA of the isomorphism class $R \circ lbfa \circ R((a \cup \epsilon)b^*)$. The representative is shown in Figure 6. □

To consider the dual of the Berry-Sethi construction, we combine the commuting diagrams of duals of a construction (above) and construction $decode \circ rfa$, giving:



The source is the upper-left vertex, and the sink is the upper FA vertex.

The construction $R \circ decode \circ rfa \circ R$ (in this diagram) is still inefficient, requiring two redundant reversal operations. We can make it more efficient, by finding functions that form new paths in the commuting diagram.

From the definitions of the Σ -algebra of RFA 's (Definition 4.29) and homomorphism rfa (Definition 4.30) we know that the RFA operators are symmetrical, and so is rfa . In other words $rfa \circ R(E) = R \circ rfa(E)$. This allows us to add two new edges to the above commuting diagram; the resulting diagram is:

$(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map})^R = (Q, V, \text{follow}^R, \text{last}, \text{first}, \text{null}, Q\text{map})$

Function R satisfies


$(\forall M : M \in FA : (\mathcal{L}_{FA}(M))^R = \mathcal{L}_{FA}(M^R)).$

4.3 The dual of the Berry-Sethi construction

P37. Property 4.31(Homomorphism rfa)

$rfa \circ R(E) = R \circ rfa(E)$

$$\begin{array}{ccc} E & \xrightarrow{rfa} & RFA \\ \downarrow R & \searrow rfa & \downarrow \\ \circ & \xrightarrow{rfa} & \circ \end{array}$$



Construction 4.45 (The dual of Berry-Sethi): The construction is:

$R \circ decode \circ R \circ rfa(E)$

Construction 4.32 (Berry-Sethi): Construction $BS \in RE \rightarrow [FA]_≈$ is defined as:

$BS(E) = decode \circ rfa(E) \quad lba(E) = BS(E)$


This construction is the dual of the Berry-Sethi construction (Construction 4.32). \square We give $R \circ decode \circ R$ in full:

```

 $R \circ decode \circ R([M]_≈) = \text{let } (Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map}) = M$ 
 $f \text{ be a new state } \text{唯一 final state}$ 
 $\text{in}$ 
 $\quad \text{let } T = \{(q_0, Q\text{map}(q_0), q_1) : (q_0, q_1) \in \text{follow}\}$ 
 $\quad T' = \{(q, Q\text{map}(q), f) : q \in \text{last}\}$ 
 $\quad S = \text{first} \cup \text{if } (\text{null}) \text{ then } \{f\} \text{ else } \emptyset \text{ fi}$ 
 $\quad \text{in } [(Q \cup \{f\}, V, T \cup T', \emptyset, S, \{f\})]_≈$ 
 $\quad \text{end}$ 
 $\text{end}$ 

```

The FA resulting from this construction is the same as given in Example 4.44

We can also consider improving the dual of the variation on the Berry-Sethi construction (Construction 4.38). We combine the commuting diagram showing the dual of a construction, with construction $convert \circ rfa \circ marker_b$, giving:Again, the source is the upper-left RE vertex, while the sink is the upper-right FA vertex.Consider the composite function $R \circ convert \circ rfa \circ marker_b \circ R$. We begin with the two rightmost functions:

$$\begin{aligned}
 & marker_b \circ R(E) \\
 &= \{ \text{Writing } R \text{ as postfix and superscript} \} \\
 & marker_b(E^R) \\
 &= \{ \text{Definition of } marker_b \text{ (Definition 4.36)} \} \\
 & \$ \cdot (E^R) \\
 &= \{ \text{Function } R \circ R \text{ is the identity (see Definition A.19)} \} \quad R \circ R \text{ is the identity } \Rightarrow R \circ R(A) = A \\
 & R \circ R(\$ \cdot (E^R)) \\
 &= \{ \text{Definition of } R \text{ on } \cdot \text{ regular expressions} \} \quad (E_0 \cdot E_1)^R = (E_1^R) \cdot (E_0^R)
 \end{aligned}$$

$$\begin{aligned}
 & R((E^R)^R \cdot (\$)^R) \\
 = & \quad \{ \text{Definition of } R \text{ and } R \circ R \} \\
 & R(E \cdot \$)
 \end{aligned}$$

To make this definition more concise, we define an end-marker function.

Definition 4.46 (Adding an end-marker): Define function $\text{marker}_e \in RE \rightarrow RE$ as:

$$\text{marker}_e(E) = E \cdot \$$$


where $\$$ is assumed to be a symbol in the alphabet. \square

Property 4.47 (marker_e): Function marker_e is the dual of function marker_b (Definition 4.36):


$$\text{marker}_b \circ R(E) = R \circ \text{marker}_e(E)$$

\square

With the above property, we can transform the above commuting diagram, by adding two new edges:



The composite $R \circ \text{convert} \circ rfa \circ R \circ \text{marker}_e$ is no more efficient even with the use of marker_e . Fortunately, since rfa is symmetrical, we can replace $rfa \circ R$ by $R \circ rfa$, giving:



The composite function $R \circ \text{convert} \circ R$ is particularly easy to present, using the definitions of R and convert (Definition 4.35):

$$\begin{aligned}
 R \circ \text{convert} \circ R([R]_{\cong}) = & \quad \text{let } (Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Qmap) = R \\
 & \quad \text{in} \\
 & \quad \quad \text{let } T = \{(q_0, Qmap(q_0), q_1) : (q_0, q_1) \in \text{follow}\} \\
 & \quad \quad \text{in } [(Q, V, T, \emptyset, \text{first}, \text{last})]_{\cong} \\
 & \quad \quad \text{end} \\
 & \quad \text{end}
 \end{aligned}$$

This leads to the following construction.




Figure 7: A representative *DFA* of the isomorphism class $ASU((a \cup \epsilon)b^*)$.

Construction 4.48 (The dual of the variation on the Berry-Sethi construction): The construction is:

$$R \circ \text{convert} \circ R \circ \text{rfa} \circ \text{marker}_e(E)$$

This construction is also presented very informally by Aho, Sethi, and Ullman [ASU86, Example 3.22, pg. 140]. There appears to be an error in item two of the three steps describing the construction in [ASU86]. Instead of

2. label each directed edge (i, j) by the symbol at position j , and

the step should read

2. label each directed edge (i, j) by the symbol at position i , and

□

Example 4.49 (The dual of the variation on the Berry-Sethi construction): A representative *FA* of the isomorphism class $R \circ \text{convert} \circ R \circ \text{rfa} \circ \text{marker}_e((a \cup \epsilon)b^*)$ is shown in Figure 6 on page 40. This is the same *FA* as in Example 4.44. □

4.3.1 The Aho-Sethi-Ullman *DFA* construction

In order to obtain a (possibly non-*Complete*) *DFA* we use the composite function $\text{useful}_s \circ \text{subsetopt}$ (given in Definition 2.44), extended to $[\text{FA}]_{\cong} \longrightarrow [\text{DFA}]_{\cong}$.

We can immediately give the Aho-Sethi-Ullman *DFA* construction using this composite function.

Construction 4.50 (Aho-Sethi-Ullman): The construction is $ASU \in RE \longrightarrow [\text{DFA}]_{\cong}$ defined as:

$$ASU(E) = \text{useful}_s \circ \text{subsetopt} \circ R \circ \text{convert} \circ R \circ \text{rfa} \circ \text{marker}_e(E)$$

Algorithm 4.52 (given below) is an imperative program implementing

$$\text{useful}_s \circ \text{subsetopt} \circ R \circ \text{convert} \circ R$$

Homomorphism *rfa* can be implemented using the techniques described in Section 4.5, and function *marker_e* is trivial to implement. The Aho-Sethi-Ullman algorithm is given in [ASU86, Alg. 3.5, Fig. 3.44]. □

Example 4.51 (Aho-Sethi-Ullman): We give a representative *DFA* of the isomorphism class $ASU((a \cup \epsilon)b^*)$. The state graph is shown in Figure 7. □

We compose $\text{useful}_s \circ \text{subsetopt}$ (as implemented by Algorithm 2.46) with $R \circ \text{convert} \circ R$. The resulting algorithm is simplified in a similar way to the McNaughton-Yamada-Glushkov algorithm (Algorithm 4.42).

Algorithm 4.52 (Aho-Sethi-Ullman): $\text{useful}_s \circ \text{subsetopt} \circ R \circ \text{convert} \circ R$

```

 $\{(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map}) \in \text{RFA}\}$ 
 $S, T := (\text{if } (\text{first} \neq \emptyset) \text{ then } \{\text{first}\} \text{ else } \emptyset \text{ fi}), \emptyset;$ 
 $D, U := \emptyset, S;$ 
 $\text{do } U \neq \emptyset \rightarrow$ 
     $\quad \text{let } u : u \in U;$ 
     $\quad D, U := D \cup \{u\}, U \setminus \{u\};$ 
     $\quad \text{for } a : a \in V \wedge (\exists q : q \in u : Q\text{map}(q) = a \wedge \text{follow}(q) \neq \emptyset) \text{ do}$ 
         $\quad \quad d := (\cup q : q \in u \wedge Q\text{map}(q) = a : \text{follow}(q));$ 
         $\quad \quad \text{if } d \notin D \rightarrow U := U \cup \{d\}$ 
         $\quad \quad \parallel d \in D \rightarrow \text{skip}$ 
         $\quad \quad \text{fi};$ 
         $\quad \quad T := T \cup \{(u, a, d)\}$ 
     $\quad \text{rof}$ 
 $\text{od};$ 
 $F := \{d : d \in D \wedge d \cap \text{last} \neq \emptyset\}$ 
 $\{[(D, V, T, \emptyset, S, F)]_{\cong} = \text{useful}_s \circ \text{subsetopt} \circ$ 
 $R \circ \text{convert} \circ R([(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map})]_{\cong})\}$ 

```

4.4 Extending regular expressions

For some regular languages, the regular expressions denoting the language can be considerably more succinct when operators such as intersection (\cap) and complement (\neg) are available in *RE*'s. Without formally adding them to the signature Σ , we briefly consider how to implement operator \cap in the left-biased Σ -algebra of *FA*'s.

Definition 4.53 (Extended regular expressions and their languages): The set of extended regular expressions (over alphabet V), *ERE*, and the languages they denote, are exactly as *RE*, with the addition of the operators $\cap \in \text{ERE} \times \text{ERE} \rightarrow \text{ERE}$ (an infix operator) and $\neg \in \text{ERE} \rightarrow \text{ERE}$ (a prefix operator). Operator \cap has the same precedence as \cup , while \neg has higher precedence than $*$. The language of an *ERE* is defined using the function $\mathcal{L}_{\text{ERE}} \in \text{ERE} \rightarrow \mathcal{L}_{\text{reg}}$ which is as function \mathcal{L}_{RE} , with the extensions

$$\begin{aligned}\mathcal{L}_{\text{ERE}}(E_0 \cap E_1) &= \mathcal{L}_{\text{ERE}}(E_0) \cap \mathcal{L}_{\text{ERE}}(E_1) \\ \mathcal{L}_{\text{ERE}}(\neg E_0) &= V^* \setminus \mathcal{L}_{\text{ERE}}(E_0)\end{aligned}$$

□

Remark 4.54: The Σ -algebra definition of regular expressions are not used in this section as the algebraic structure is not needed. □

Definition 4.55 (Intersection of LBFA's): In defining intersection, we assume that the two arguments have been constructed in the Σ -algebra of *LBFA*. In particular, we require that for each state, all in-transitions are on the same symbol. Assuming the argument representatives

have disjoint state sets, one possible implementation of the operator is¹⁰:

```

 $C_{\cap, LBFA}([M_0]_{\cong}, [M_1]_{\cong}) = \text{let } (Q_0, V, T_0, \emptyset, \{s_0\}, F_0) = M_0$ 
 $(Q_1, V, T_1, \emptyset, \{s_1\}, F_1) = M_1$ 
 $q_0 \text{ be a new state}$ 
 $N = \epsilon \in (\mathcal{L}_{FA}(M_0) \cap \mathcal{L}_{FA}(M_1))$ 
in
 $\text{let } Q' = \{q_0\} \cup (\cup b : b \in V : \pi_2(T_0(b)) \times \pi_2(T_1(b)))$ 
 $T'(a) = \{q_0\} \times (T_0(s_0, a) \times T_1(s_1, a))$ 
 $\cup \{(p, q), (p', q') : (p, p') \in T_0(a) \wedge p \neq s_0$ 
 $\wedge (q, q') \in T_1(a) \wedge q \neq s_1$ 
 $\wedge (\exists b : b \in V : p \in \pi_2(T_0(b)) \wedge q \in \pi_2(T_1(b)))\}$ 
in
 $[(Q', V, T', \emptyset, \{q_0\}, (F_0 \times F_1) \cap Q' \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi})]_{\cong}$ 
end
end

```

The expression

$$Q' = \{q_0\} \cup (\cup b : b \in V : \pi_2(T_0(b)) \times \pi_2(T_1(b)))$$

in the **let** clause deserves some explanation. A state in the constructed *LBFA* is either the new state q_0 , or a pair of states (p, q) where p and q ($p \neq s_0, q \neq s_1$) are from M_0 and M_1 respectively. If p and q do not have an in-transition on the same symbol, the state (p, q) will be start-unreachable in the constructed *LBFA*. For this reason, it is omitted. The definition of the transition relation is similar. The constructed *LBFA* is sometimes called the *cross-product* *LBFA*. Although the operator removes most start-unreachable states, some may still remain. \square

We can now present an intersection operator for *RFA*'s.

Definition 4.56 (Intersection of *RFA*'s): We define intersection of *RFA*'s as:

$$C_{\cap, RFA}([M_0]_{\cong}, [M_1]_{\cong}) = \text{encode} \circ C_{\cap, LBFA}(\text{decode}([M_0]_{\cong}), \text{decode}([M_1]_{\cong}))$$


In full:

```

 $C_{\cap, RFA}([M_0]_{\cong}, [M_1]_{\cong}) = \text{let } (Q_0, V, follow_0, first_0, last_0, null_0, Qmap_0) = M_0$ 
 $(Q_1, V, follow_1, first_1, last_1, null_1, Qmap_1) = M_1$ 
in
 $\text{let } Q' = (\cup b : b \in V : Qmap_0^{-1}(b) \times Qmap_1^{-1}(b))$ 
 $follow' = \{((p, q), (p', q')) : (p, p') \in follow_0$ 
 $\wedge (q, q') \in follow_1$ 
 $\wedge Qmap_0(p) = Qmap_1(q)$ 
 $\wedge Qmap_0(p') = Qmap_1(q')\}$ 
 $first' = \{(p, q) : p \in first_0 \wedge q \in first_1$ 
 $\wedge Qmap_0(p) = Qmap_1(q)\}$ 
 $Qmap'^{-1}(a) = Qmap_0^{-1}(a) \times Qmap_1^{-1}(a)$ 
in
 $[(Q', V, follow', first', (last_0 \times last_1) \cap Q',$ 
 $null_0 \wedge null_1, Qmap')]_{\cong}$ 
end
end

```

Note that this operator is symmetrical. \square



¹⁰The definition presented here is intentionally clumsy, making it easier to present intersection of *RFA*'s

In their original paper [MY60, Section IV], McNaughton and Yamada attempt to define intersection. Unfortunately, their informal presentation is difficult to understand. Subsequent presentations of the *RFA* operators have all omitted intersection. For example, Berry and Sethi note (in [BS86, Remark 3.1]):

“The approach . . . does not extend to regular expressions with intersection and complementation operators.”

We can construct an *RFA* operator for any regular operator (an operator on languages that preserves the regularity property) for which we can construct an *LBFA* operator. Examples of such operators are intersection, symmetrical difference, complement, asymmetrical difference, and prefix closure.

4.5 Efficiently computing with *RFA*'s

In this section, we consider some practical methods for constructing *RFA*'s. The first subsection considers a practical implementation of the (Σ -algebra of) *RFA* operators, while the second subsection introduces some improvements (due to Chang, Paige, and Brüggemann-Klein) to the *RFA* operators.

A reduced *FA* (*RFA*) is a 7-tuple $(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map})$

4.5.1 A practical implementation of the *RFA* operators

In an *RFA*, the states are mapped to their corresponding symbol (of V) by the seventh component (usually called *Qmap*) of the *RFA*. This seventh component would be redundant if the states and symbols were in a one-to-one correspondence. Furthermore, the symbols could then be used as the states. In this subsection, we explore this encoding method, and the requirements on the *RE*'s for this method to work. We will also be defining a new, restricted, mapping $rfa' \in RE \dashrightarrow RFA$. We will be able to use this mapping for regular expressions in which each alphabet symbol occurs no more than once.

We first define an important auxiliary function.

Definition 4.57 (Occurrences of symbols in *RE*'s): We define function $Occ \in RE \longrightarrow \mathcal{P}(V)$ such that $Occ(E)$ is the set of symbols (of V) occurring in E . We can also define *Occ* recursively as follows:

Occ(E): 在 E 中出现的符号集合

$$\begin{aligned} Occ(\epsilon) &= \emptyset \\ Occ(\emptyset) &= \emptyset \\ Occ(a) &= \{a\} \quad (\text{for } a \in V) \\ Occ(E \cdot F) &= Occ(E) \cup Occ(F) \\ Occ(E \cup F) &= Occ(E) \cup Occ(F) \\ Occ(E^*) &= Occ(E) \\ Occ(E^+) &= Occ(E) \\ Occ(E^?) &= Occ(E) \end{aligned}$$



[RRE \(for restricted regular expressions\)](#)

Definition 4.58 (RRE): We define $RRE \subset RE$ as the smallest set satisfying:

- $\epsilon \in RRE$,
- $\emptyset \in RRE$,
- $a \in RRE$ (for $a \in V$),
- if $E, F \in RRE$, and $Occ(E) \cap Occ(F) = \emptyset$ then $E \cdot F \in RRE$ and $E \cup F \in RRE$, and
- if $E \in RRE$ then $E^* \in RRE$, $E^+ \in RRE$, and $E^? \in RRE$.

$$\begin{aligned}
First((a \cup \epsilon)b^*) &= (\text{Defn. } First(E \cdot F), \epsilon \in (a \cup \epsilon), Null(E) = \text{true}) \\
&= (\Rightarrow First(E) \cup First(F)) \\
&= First(a \cup \epsilon) \cup First(b^*) \\
&= (\text{Defn. } First(E \cup F) = First(E) \cup First(F), First(E^*) = First(E)) \\
&= (First(a) \cup First(\epsilon)) \cup First(b) \\
&= \{a \cup \emptyset\} \cup \{b\} = \{a, b\}
\end{aligned}$$

$$\begin{aligned}
Last((a \cup \epsilon)b^*) &= (\text{Defn. } Last(E \cdot F), \epsilon \in (a \cup \epsilon), Null(E) = \text{true}) \\
&= (\Rightarrow Last(E) \cup Last(F)) \\
&= Last(a \cup \epsilon) \cup Last(b^*) \\
&= (\text{Defn. } Last(E \cup F) = Last(E) \cup Last(F), Last(E^*) = Last(E)) \\
&= (Last(a) \cup Last(\epsilon)) \cup Last(b) \\
&= \{a \cup \emptyset\} \cup \{b\} = \{a, b\}
\end{aligned} \tag{47}$$

Intuitively, **RRE** (for restricted regular expressions) denotes the set of all $E \in RE$ such that each symbol (of V) occurs no more than once in E . \square

Example 4.59 (RRE): A RRE is $(a \cup \epsilon)b^*$. \square

In order to give our alternative **RE** to **RFA** mapping, $rfa' \in RRE \rightarrow RFA$, we first define some more auxiliary functions. The definitions of these functions also follow directly from the **RFA** operators.

Definition 4.60 (First): We define $First \in RE \rightarrow \mathcal{P}(V)$ recursively (recall from Example 3.20 that $Null(E) \equiv (\epsilon \in \mathcal{L}_{RE}(E))$):

Definition 3.20
Property 3.21

Null(E): true : E 中含 epsilon , 如 epsilon, star, question 操作 ; 否则 , false. union , concatenate , plus 操作 由 Definition 3.20 可以 递归推导 NULL(E).	$First(\epsilon) = \emptyset$ $First(\emptyset) = \emptyset$ $First(a) = \{a\}$ (for $a \in V$) $First(E \cdot F) = First(E) \cup \text{if } (Null(E)) \text{ then } First(F) \text{ else } \emptyset \text{ fi}$ $First(E \cup F) = First(E) \cup First(F)$ $First(E^*) = First(E)$ $First(E^+) = First(E)$ $First(E^?) = First(E)$	Property 3.21 (The nullable sigma-algebra) (RE.h, Deriv.cpp) Function First returns a CRSet denoting the characters which can occur as the first character of a word in the language denoted by the regular expression.
--	--	---

This definition follows directly from the **first tuple** element of the **RFA** operator definitions. \square

Remark 4.61: It is useful to have an intuitive understanding of function **First**. $First(E)$ is the set of all symbols that can occur as the first symbol of a string in $\mathcal{L}_{RE}(E)$. \square

Definition 4.62 (Last): Function **Last** is defined to be the dual of **First**. \square


Remark 4.63: $Last(E)$ is the set of all symbols that can occur as the last symbol of a string in $\mathcal{L}_{RE}(E)$. \square

Definition 4.64 (Follow): We define $Follow \in RE \rightarrow \mathcal{P}(V \times V)$ recursively:

$Follow(\epsilon) = \emptyset$ $Follow(\emptyset) = \emptyset$ $Follow(a) = \emptyset$ (for $a \in V$) $Follow(E \cdot F) = Follow(E) \cup Follow(F) \cup (Last(E) \times First(F))$ $Follow(E \cup F) = Follow(E) \cup Follow(F)$ $Follow(E^*) = Follow(E) \cup (Last(E) \times First(E))$ $Follow(E^+) = Follow(E) \cup (Last(E) \times First(E))$ $Follow(E^?) = Follow(E)$
--

This definition follows directly from the **follow tuple** element of the **RFA** operator definitions. \square

Remark 4.65: For $a, b \in V$, $(a, b) \in Follow(E)$ is equivalent to ab being a substring of some string in $\mathcal{L}_{RE}(E)$. \square



Example 4.66 (First, Last, Null, Follow): We use the regular expression $(a \cup \epsilon)b^*$ (from Example 3.15):

$$\begin{aligned}
First((a \cup \epsilon)b^*) &= \{a, b\} \\
Last((a \cup \epsilon)b^*) &= \{a, b\} \\
Null((a \cup \epsilon)b^*) &= \text{true} \\
Follow((a \cup \epsilon)b^*) &= \{(a, b), (b, b)\}
\end{aligned}$$

\square

$$\begin{aligned}
Null((a \cup \epsilon)b^*) &= (\text{Defn. } Null(E \cdot F) = Null(E \wedge F), \epsilon \in L_{RE} \equiv Null(E)) \\
&= Null(a \cup \epsilon) \wedge Null(b^*) \\
&= (\text{Defn. } Null(E \cup F) = Null(E \vee F), Null(E^*) = \text{true}) \\
&= (Null(a) \vee Null(\epsilon)) \wedge \text{true} \\
&= \text{true} \wedge \text{true} = \text{true}
\end{aligned}$$

We now have the auxiliary functions required for the definition of rfa' .

$$Last(a \cup \epsilon) = Last(a) \cup Last(\epsilon) = \{a\} \cup \emptyset = \{a\}$$

$$Follow((a \cup \epsilon)b^*) = Follow(a \cup \epsilon) \cup Follow(b^*) \cup (Last(a \cup \epsilon) \times First(b^*))$$

$$First(b^*) = First(b) = \{b\}$$

$$= \emptyset \cup \{(b, b)\} \cup \{(\{a\} \times \{b\})\}$$

$$Follow(a \cup \epsilon) = Follow(a) \cup Follow(\epsilon) = \emptyset \cup \emptyset = \emptyset$$

$$= \{(b, b)\} \cup \{(a, b)\}$$

$$Follow(b^*) = Follow(b) \cup (Last(b) \times First(b)) = \emptyset \cup \{(b, b)\} = \{(b, b)\}$$

$$= \{(a, b), (b, b)\}$$

Definition 4.67 (Function $rfa' \in RRE \rightarrow RFA$): The definition of rfa' is straightforward:

$$rfa'(E) = (Occ(E), V, Follow(E), First(E), Last(E), Null(E), I_V)$$

where I_V is the identity function on alphabet symbols. \square

Example 4.68 (rfa'): Using the results of the above example, we have:

$$rfa'((a \cup \epsilon)b^*) = (\{a, b\}, \{a, b\}, \{(a, b), (b, b)\}, \{a, b\}, \{a, b\}, \text{true}, \{(a, a), (b, b)\})$$

\square

Property 4.69 (rfa'): Given $E \in RRE$ then $rfa'(E) = [rfa'(E)]_{\cong}$. \square

Function rfa' is convenient, as all of the auxiliary functions can easily be computed bottom-up on the structure of E .

Construction 4.70 (An encoding of BS): The method of constructing an RFA (using rfa') leads to a particularly concise definition of BS . For example, we define $BSenc \in RRE \rightarrow FA$:

$BSenc(E) = \begin{array}{l} \text{let } s \text{ be a new state } \text{添加唯一一个开始状态} \\ \text{in} \\ \quad \text{let } T = \{(a, b, b) : (a, b) \in Follow(E)\} \\ \quad T' = \{(s, a, a) : a \in First(E)\} \\ \quad F = Last(E) \cup \text{if } (Null(E)) \text{ then } \{s\} \text{ else } \emptyset \text{ fi} \\ \quad \text{in} \\ \quad \quad (Occ(E) \cup \{s\}, V, T \cup T', \emptyset, \{s\}, F) \\ \quad \text{end} \\ \text{end} \end{array}$	
--	--

\square

Remark 4.71: Compare the definition of $BSenc$ to the definition of $decode$ (Definition 4.28). \square

Property 4.72 (Construction $BSenc$): For $E \in RRE$:

$$[BSenc(E)]_{\cong} = BS(E)$$

\square

Remark 4.73: By inspection, we see that (for $E \in RRE$) the FA $BSenc(E)$ (equivalently $BS(E)$) is deterministic. This implies that:

$$MYG(E) = \text{complete} \circ BS(E)$$

\square

Remark 4.74: In Section 5.4 we will show that Brzozowski's construction (with an appropriate encoding) produces a DFA (from an $E \in RRE$) that is isomorphic to the one produced by $BSenc$ (and therefore BS). \square

Similarly, the Aho-Sethi-Ullman algorithm becomes quite concise (from Algorithm 4.52):

```

 $\{E \in RRE\}$ 
 $E' := \text{marker}_e(E);$ 
 $S, T := (\text{if } (\text{First}(E') \neq \emptyset) \text{ then } \{\text{First}(E')\} \text{ else } \emptyset \text{ fi}), \emptyset;$ 
 $D, U := \emptyset, S;$ 
 $\text{do } U \neq \emptyset \longrightarrow$ 
     $\text{let } u : u \in U;$ 
     $D, U := D \cup \{u\}, U \setminus \{u\};$ 
     $\text{for } a : a \in u \wedge \text{Follow}(E')(a) \neq \emptyset \text{ do}$ 
         $d := (\text{Follow}(E'))(a);$ 
         $\text{if } d \notin D \longrightarrow U := U \cup \{d\}$ 
         $\parallel d \in D \longrightarrow \text{skip}$ 
         $\text{fi;}$ 
         $T := T \cup \{(u, a, d)\}$ 
     $\text{rof}$ 
 $\text{od;}$ 
 $F := \{d : d \in D \wedge \$ \in d\}$ 
 $\{\mathcal{L}_{FA}(D, V, T, \emptyset, S, F) = \mathcal{L}_{RE}(E)\}$ 

```

This algorithm is very similar to the one given in [ASU86].

The only problem remaining is how to deal with an $E \in RE$ when $E \notin RRE$. The method usually used is to “mark” the symbols of E (perhaps with an integer subscript), making each symbol unique. For example, $(a^+ \cup ab) \notin RRE$ but after marking we get $(a_1^+ \cup a_2 b_3) \in RRE$. Once the corresponding FA is constructed from the marked regular expression, the marks are removed (the FA is “unmarked”) and the FA accepts $\mathcal{L}_{RE}(E)$. There are a few different styles of marking. For example, consider $a^+ \cup ab$: McNaughton-Yamada mark this as $a_1^+ \cup a_2 b_1$, Berry-Sethi use $a_1^+ \cup a_2 b_3$, and Aho-Sethi-Ullman use $1^+ \cup 23$.

The only disadvantage to the use of marking to encode RFA computation is that marking is unable to deal with some of the other regular operators, such as intersection, and complementation. For all $E, F \in RRE$ we have the property that $\mathcal{L}_{RE}(E \cap F) = \mathcal{L}_{RE}(E) \cap \mathcal{L}_{RE}(F) = \emptyset$. For example, given¹¹ $aa \cap a^*$ (with language $\mathcal{L}_{RE}(aa \cap a^*) = \mathcal{L}_{RE}(aa) \cap \mathcal{L}_{RE}(a^*) = \{aa\}$). After marking we get $a_1 a_2 \cap a_3^*$ after marking (with $\mathcal{L}_{RE}(a_1 a_2 \cap a_3^*) = \emptyset$). In Section 4.4 we saw how these operators can be readily implemented with RFA's (without the encoding scheme of this section).

The approach presented in this subsection is essentially due to McNaughton and Yamada [MY60], Glushkov [Glus61], and Berry and Sethi [BS86]. The presentations in [B-K93a, Section 2], [BS86], [tEvG93], and [ASU86, Fig. 3.40, pp. 134–141] are particularly clear. Those interested in a rigorous treatment of this approach to RFA's can refer to the paper of ten Eikelder and van Geldrop [tEvG93].

4.5.2 More efficient RFA operators

The definition of the RFA operators may still result in inefficient implementation. In particular, Brüggemann-Klein and Chang and Paige found that the implementation of the (\cup) in the RFA operators may require more than constant time [B-K93a, Chan92, CP92]. In most cases the arguments (of \cup) are disjoint; the only possible exception is the union $\text{follow} \cup (\text{last} \times \text{first})$, appearing in the $C_{*,RFA}$ and $C_{+,RFA}$ operators. Two solutions to this problem will be presented here.

Convention 4.75 (Constant time union): We use the symbol \uplus to denote union where the arguments to \uplus are assumed to be disjoint. \square

¹¹ Here we assume, for the moment, that \mathcal{L}_{RE} can deal with the intersection operator.

The first solution was proposed by Chang and Paige [Chan92, CP92].

Definition 4.76 (Chang-Paige RFA): We add an eighth component W to each RFA

$$(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map}, W)$$

such that

$$W = (\text{last} \times \text{first}) \setminus \text{follow}$$

These modified RFA's will be called Chang-Paige RFA's, and are denoted by RFA' . \square

We only give the new operators, instead of the Σ -algebra. The operators follow directly from the above definition.


Construction 4.77 (Operators of the Σ -algebra of Chang-Paige RFA's): As usual, the operator requirement is:


- For binary operators, the representatives have disjoint state sets.

$$C_{\epsilon, \text{RFA}'} = [(\emptyset, V, \emptyset, \emptyset, \emptyset, \text{true}, \emptyset, \emptyset)]_{\cong}$$

$$C_{\emptyset, \text{RFA}'} = [(\emptyset, V, \emptyset, \emptyset, \emptyset, \text{false}, \emptyset, \emptyset)]_{\cong}$$

$$C_{a \in V, \text{RFA}'} = \begin{array}{l} \text{let } q_0 \text{ be a new state} \\ \text{in } \\ \text{end} \end{array} [(\{q_0\}, V, \emptyset, \{q_0\}, \{q_0\}, \text{false}, \{(q_0, a)\}, \{(q_0, q_0)\})]_{\cong}$$



$$C_{\cdot, \text{RFA}'}([M_0]_{\cong}, [M_1]_{\cong}) = \begin{array}{l} \text{let } (Q_0, V, \text{follow}_0, \text{first}_0, \text{last}_0, \text{null}_0, Q\text{map}_0, W_0) = M_0 \\ (Q_1, V, \text{follow}_1, \text{first}_1, \text{last}_1, \text{null}_1, Q\text{map}_1, W_1) = M_1 \\ \text{in} \\ \text{let } \text{first}' = \text{first}_0 \uplus \text{if } (\text{null}_0) \text{ then } \text{first}_1 \text{ else } \emptyset \text{ fi} \\ \text{last}' = \text{last}_1 \uplus \text{if } (\text{null}_1) \text{ then } \text{last}_0 \text{ else } \emptyset \text{ fi} \\ W' = \text{if } (\text{null}_1) \text{ then } W_0 \text{ else } \emptyset \text{ fi} \\ W'' = \text{if } (\text{null}_0) \text{ then } W_1 \text{ else } \emptyset \text{ fi} \\ \text{in} \\ [(Q_0 \uplus Q_1, V, \text{follow}_0 \uplus \text{follow}_1 \uplus (\text{last}_0 \times \text{first}_1), \\ \text{first}', \text{last}', \text{null}_0 \wedge \text{null}_1, Q\text{map}_0 \uplus Q\text{map}_1, \\ (\text{last}_1 \times \text{first}_0) \uplus W' \uplus W'')]_{\cong} \\ \text{end} \\ \text{end} \end{array}$$


$$C_{\cup, \text{RFA}'}([M_0]_{\cong}, [M_1]_{\cong}) = \begin{array}{l} \text{let } (Q_0, V, \text{follow}_0, \text{first}_0, \text{last}_0, \text{null}_0, Q\text{map}_0, W_0) = M_0 \\ (Q_1, V, \text{follow}_1, \text{first}_1, \text{last}_1, \text{null}_1, Q\text{map}_1, W_1) = M_1 \\ \text{in} \\ \text{let } [(Q_0 \uplus Q_1, V, \text{follow}_0 \uplus \text{follow}_1, \text{first}_0 \uplus \text{first}_1, \\ \text{last}_0 \uplus \text{last}_1, \text{null}_0 \vee \text{null}_1, Q\text{map}_0 \uplus Q\text{map}_1, \\ (\text{last}_0 \times \text{first}_1) \uplus (\text{last}_1 \times \text{first}_0) \uplus W_0 \uplus W_1)]_{\cong} \\ \text{end} \end{array}$$


$$C_{*, \text{RFA}'}([M]_{\cong}) = \begin{array}{l} \text{let } (Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Q\text{map}, W) = M \\ \text{in} \\ \text{end} \end{array} [(Q, V, \text{follow} \uplus W, \text{first}, \text{last}, \text{true}, Q\text{map}, \emptyset)]_{\cong}$$




$C_{+,RFA'}([M]_\cong) = \text{let } (Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Qmap, W) = M \text{ in } [(Q, V, \text{follow} \uplus W, \text{first}, \text{last}, \text{null}, Qmap, \emptyset)]_\cong \text{ end}$



$C_{?,RFA'}([M]_\cong) = \text{let } (Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Qmap, W) = M \text{ in } [(Q, V, \text{follow}, \text{first}, \text{last}, \text{true}, Qmap, W)]_\cong \text{ end}$

These operators are symmetrical. The correctness of these operators is shown in Theorem B.3. \square

Chang and Paige make additional running-time savings by computing the components of a *RFA'* only as needed in the operators $C_{*,RFA'}$ and $C_{+,RFA'}$. The running-time and space savings, along with implementation details are given in [Chan92, CP92].

The second solution also involves adding an eighth tuple element to *RFA*'s, giving *RFA''*.

Definition 4.78 (*RFA''*): We add an eighth component *W* to each *RFA*

$$(Q, V, \text{follow}, \text{first}, \text{last}, \text{null}, Qmap, W)$$

such that

$$W = \text{follow} \setminus (\text{last} \times \text{first})$$

These modified *RFA*'s are denoted by *RFA''*. \square


As before, the new operators follow directly from the above definition.

Construction 4.79 (Operators of the Σ -algebra of *RFA''*): As usual, the requirement for binary operators is that the representatives of the arguments are chosen such that they have disjoint state sets.

$$\begin{aligned} C_{\epsilon,RFA''} &= [(\emptyset, V, \emptyset, \emptyset, \emptyset, \text{true}, \emptyset, \emptyset)]_\cong \\ C_{\emptyset,RFA''} &= [(\emptyset, V, \emptyset, \emptyset, \emptyset, \text{false}, \emptyset, \emptyset)]_\cong \end{aligned}$$

$C_{a \in V,RFA''} = \text{let } q_0 \text{ be a new state} \text{ in } [(\{q_0\}, V, \emptyset, \{q_0\}, \{q_0\}, \text{false}, \{(q_0, a)\}, \emptyset)]_\cong \text{ end}$

$C_{.,RFA''}([M_0]_\cong, [M_1]_\cong) = \text{let } (Q_0, V, \text{follow}_0, \text{first}_0, \text{last}_0, \text{null}_0, Qmap_0, W_0) = M_0 \text{ in } (Q_1, V, \text{follow}_1, \text{first}_1, \text{last}_1, \text{null}_1, Qmap_1, W_1) = M_1$




$\text{let } \begin{aligned} \text{first}' &= \text{first}_0 \uplus \text{if } (\text{null}_0) \text{ then first}_1 \text{ else } \emptyset \text{ fi} \\ \text{last}' &= \text{last}_1 \uplus \text{if } (\text{null}_1) \text{ then last}_0 \text{ else } \emptyset \text{ fi} \\ W' &= \text{if } (\text{null}_1) \text{ then } W_0 \text{ else follow}_0 \text{ fi} \\ W'' &= \text{if } (\text{null}_0) \text{ then } W_1 \text{ else follow}_1 \text{ fi} \\ W''' &= \text{if } (\text{null}_0 \wedge \text{null}_1) \text{ then } \emptyset \text{ else } (\text{last}_0 \times \text{first}_1) \text{ fi} \end{aligned} \text{ in } [(Q_0 \uplus Q_1, V, \text{follow}_0 \uplus \text{follow}_1 \uplus (\text{last}_0 \times \text{first}_1), \text{first}', \text{last}', \text{null}_0 \wedge \text{null}_1, Qmap_0 \uplus Qmap_1, W' \uplus W'' \uplus W''')]_\cong \text{ end}$

$$\begin{aligned}
C_{\cup, RFA''}([M_0]_{\cong}, [M_1]_{\cong}) &= \text{let } (Q_0, V, follow_0, first_0, last_0, null_0, Qmap_0, W_0) = M_0 \\
&\quad (Q_1, V, follow_1, first_1, last_1, null_1, Qmap_1, W_1) = M_1 \\
&\quad \text{in} \\
&\quad \quad [(Q_0 \uplus Q_1, V, follow_0 \uplus follow_1, first_0 \uplus first_1, \\
&\quad \quad \quad last_0 \uplus last_1, null_0 \vee null_1, Qmap_0 \uplus Qmap_1, \\
&\quad \quad \quad W_0 \uplus W_1)]_{\cong} \\
&\quad \text{end} \\
C_{*, RFA''}([M]_{\cong}) &= \text{let } (Q, V, follow, first, last, null, Qmap, W) = M \\
&\quad \text{in} \\
&\quad \quad [(Q, V, W \uplus (last \times first), first, last, true, Qmap, W)]_{\cong} \\
&\quad \text{end} \\
C_{+, RFA''}([M]_{\cong}) &= \text{let } (Q, V, follow, first, last, null, Qmap, W) = M \\
&\quad \text{in} \\
&\quad \quad [(Q, V, W \uplus (last \times first), first, last, null, Qmap, W)]_{\cong} \\
&\quad \text{end} \\
C_{?, RFA''}([M]_{\cong}) &= \text{let } (Q, V, follow, first, last, null, Qmap, W) = M \\
&\quad \text{in} \\
&\quad \quad [(Q, V, follow, first, last, true, Qmap, W)]_{\cong} \\
&\quad \text{end}
\end{aligned}$$









These operators are symmetrical. Their correctness is shown in Theorem B.4. \square

Definition 4.80 (Mapping $[RFA']_{\cong}$ and $[RFA'']_{\cong}$ to $[RFA]_{\cong}$): The mapping is $\bar{\pi}_8$. \square

Remark 4.81: Although this construction does not appear in the literature, a related one does: Brüggemann-Klein describes a transformation on regular expressions which closely parallels the RFA'' operators. A regular expression E is first transformed into a *star normal-form* expression, denoted by E^* ; the RFA image of E^* has similar properties to the RFA'' image of E . The details of the star normal-form transformations (and the running time improvements resulting from them) are described in [B-K93a]. \square

5 The Myhill-Nerode, Brzozowski and DeRemer constructions


In this section, we explore a *DFA* construction method — due to Myhill and Nerode — from which we derive Brzozowski's construction. First, we make some observations about determinism in finite automata.

Recall a property of *weakly deterministic automata* — [Property 2.28](#). Given that the set of left languages (of the states) in a *DFA* are disjoint, we will be exploring methods of computing a set of left languages to construct an automaton. $\text{Det}'(M) \equiv (\forall q_0, q_1 : q_0 \in Q \wedge q_1 \in Q \wedge q_0 \neq q_1 : \overleftarrow{\mathcal{L}}(q_0) \cap \overleftarrow{\mathcal{L}}(q_1) = \emptyset)$

Definition 5.1 (Left languages of a DFA): Define the left languages of a *DFA* as:

$$\overleftarrow{\mathcal{L}}(Q, V, T, E, S, F) = \{\overleftarrow{\mathcal{L}}(q) : q \in Q\}$$

□



Since the elements of this set are pairwise disjoint (by [Property 2.28](#)), we can also view it as the (finite) set of equivalence classes of some equivalence relation on V^* . There are two potential problems with this:

- In the case that an $M \in \text{DFA}$ is not *Complete* then $\overleftarrow{\mathcal{L}}(M)$ is a partial partition of V^* . (This follows from [Property 2.16](#).) To make the definitions in this section easier to present, we restrict ourselves to *Complete DFA*'s. $(\cup q : q \in Q : \overleftarrow{\mathcal{L}}(q)) = V^*$
- It may be that \emptyset is a left language of some state — corresponding to a start-unreachable state. In this section, we will not be interested in *DFA*'s with start-unreachable states.

Since $\mathcal{L}_{FA}(Q, V, T, E, S, F) = (\cup f : f \in F : \overleftarrow{\mathcal{L}}(f))$ (see [Definition 2.12](#)) we also note that the language of an automaton M is the union of some of the equivalence classes in $\overleftarrow{\mathcal{L}}(M)$.

Definition 5.2 (Right invariance of an equivalence relation): An equivalence relation E on V^* is right-invariant if and only if

$$(\forall u, a : u \in V^* \wedge a \in V : (\exists v : v \in V^* : [u]_E \cdot \{a\} \subseteq [v]_E))$$

□

右不变的等价关系

Property 5.3 (Right invariance of an equivalence relation): Sometimes right invariance of equivalence relation E on V^* is given as

$$(\forall u, z : u \in V^* \wedge z \in V^* : (\exists v : v \in V^* : [u]_E \cdot \{z\} \subseteq [v]_E)) \quad \text{u,v在同一个等价关系中。# (id) 一致}$$


This is equivalent to the definition given above (by induction on the length of $z \in V^*$). □

We can now formulate an important property of $\overleftarrow{\mathcal{L}}(M)$, the partition of V^* .

Property 5.4 (Right invariance of a partition of V^*): Partition $\overleftarrow{\mathcal{L}}(Q, V, T, E, S, F)$ is right-invariant if and only if


$$(\forall p, a : p \in Q \wedge a \in V : (\exists q : q \in Q : \overleftarrow{\mathcal{L}}(p) \cdot \{a\} \subseteq \overleftarrow{\mathcal{L}}(q)))$$

□



Remark 5.5: It should be clear that for all $M \in \text{DFA}$ such that $\text{Complete}(M)$, $\overleftarrow{\mathcal{L}}(M)$ is right-invariant; this follows since for all states p , (and transition relation $T \in Q \times V \rightarrow Q$, since $M \in \text{DFA}$) (and $a \in V$):

$$\overleftarrow{\mathcal{L}}(p) \cdot \{a\} \subseteq \overleftarrow{\mathcal{L}}(T(p, a))$$



□

Remark 5.6: Had we been considering non-*Complete DFA*'s, we would not have a partition on V^* ; right invariance could still be defined (for partial partition $\overleftarrow{\mathcal{L}}(Q, V, T, E, S, F)$) as:

$$(\forall p, a : p \in Q \wedge a \in V \wedge T^*(p, a) \neq \emptyset : (\exists q : q \in Q : \overleftarrow{\mathcal{L}}(p) \cdot \{a\} \subseteq \overleftarrow{\mathcal{L}}(q)))$$

We will not be using this definition. We give it to point out that the techniques of this section are also usable in constructing non-*Complete DFA*'s (as Brzozowski demonstrated in [Brzo64]). \square

5.1 The Myhill-Nerode construction

Before considering how to construct finite automata, we first present the Myhill-Nerode theorem. A good text book introduction to the theorem is [HU79].

Theorem 5.7 (Myhill-Nerode): The Myhill-Nerode theorem states that the following statements are equivalent [Myhi57, Nero58, RS59, HU79]:

1. L is a regular language.
2. L is the union of some of the equivalence classes of a right-invariant equivalence relation (on V^*) of finite index.
3. Let R_L be the right-invariant equivalence relation defined by

$$(x, y) \in R_L \equiv (\forall z : z \in V^* : (xz \in L) \equiv (yz \in L))$$

Relation R_L is of finite index. 有限指数(等价类的个数)

Proof:

A following proof is given in [HU79, Theorem 3.9].

(1) \Rightarrow (2): Assume L is accepted by $M \in DFA$ such that $Complete(M)$. Let E be the equivalence relation corresponding to $\overleftarrow{\mathcal{L}}(M)$. $\#E$ is finite, and $L = (\cup f : f \in F : \overleftarrow{\mathcal{L}}(f))$. (See Definition A.8 for the definition of $\#$.) #E称为E的指数，就是等价类的个数。

(2) \Rightarrow (3): We show that for an equivalence relation E satisfying (2) that $E \subseteq R_L$. (Here \subseteq denotes equivalence relation refinement, see Definition A.10.) We start the derivation using the right invariance property of E (Property 5.4, written slightly differently):

$$\begin{aligned} & (\forall u : u \in V^* : (\forall w : w \in V^* : (\exists v : v \in V^* : ([u]_E \cdot \{w\}) \subseteq [v]_E))) \\ \Rightarrow & \{ \text{Assumption that } E \text{ satisfies (2), for all } v \in V^* : ([v]_E \subseteq L) \vee ([v]_E \cap L = \emptyset) \} \\ & (\forall u : u \in V^* : (\forall w : w \in V^* : (([u]_E \cdot \{w\}) \subseteq L) \vee (([u]_E \cdot \{w\}) \cap L = \emptyset))) \\ \Rightarrow & \{ \text{Definition of } R_L \} \\ & (\forall u : u \in V^* : (\exists v : v \in V^* : [u]_E \subseteq [v]_{R_L})) \\ \equiv & \{ \text{Definition of refinement } (\sqsubseteq) — \text{Definition A.11} \} \\ & [V^*]_E \sqsubseteq [V^*]_{R_L} \\ \equiv & \{ \text{Definition of refinement } (\subseteq) — \text{Definition A.10} \} \\ & E \subseteq R_L \quad E \text{是RL的加细} \\ \Rightarrow & \{ \text{Property of refinement} — \text{Property A.12} \} \\ & \#E \geq \#R_L \quad E \text{的指数更大，就是划分更细} \end{aligned}$$

It follows that since $\#E$ is finite, so is $\#R_L$.


(3) \Rightarrow (1): We can construct the following *Complete DFA* (from R_L) accepting L :

```
let    $T([w]_{R_L}, a) = \{[wa]_{R_L}\}$   

       $F = \{[w]_{R_L} : w \in L\}$   

in    $([V^*]_{R_L}, V, T, \emptyset, \{[\epsilon]_{R_L}\}, F)$   

end
```



$[V^*]_{R_L} = V^*/R_L$ 表示右不变的等价关系，每个等价关系对应一个状态。
 $[\epsilon]_{R_L}$ 表示 ϵ 所在的等价类对应的状态，就是开始状态

It follows that L is a regular language.

□

Property 5.8 (Index of equivalence relation E): Given $L \in \mathcal{L}_{\text{reg}}$, $M \in \text{DFA}$ accepting L , and E (satisfying statement 2 and constructed as in the proof of (1) \Rightarrow (2) of the Myhill-Nerode theorem) then $\#E \leq |M|$ (since $\#E = \#\overleftarrow{\mathcal{L}}(M)$ by definition of E and Det'). □ 等价关系个数小于等于M的状态数

Property 5.9 (Uniqueness and minimality of equivalence relation R_L): Of all equivalence relations satisfying statement 2 of the Myhill-Nerode theorem, R_L is the unique minimal one. This follows from the fact that all others are refinements of R_L (see the proof of (2) \Rightarrow (3)). □

The theorem does not say much about how to find equivalence relations satisfying statement 2, other than providing a definition of the unique minimal one, R_L .

We can formalize statement 2 of the Myhill-Nerode theorem:

Definition 5.10 (Predicate MN): For regular language L and equivalence relation E (on V^*) $MN(L, E)$ is equivalent to

- $\#E$ is finite,
- $L = (\cup v : v \in L : [v]_E)$, and
- E is right-invariant. E 是右不变的等价关系

□

Note that $MN(L, R_L)$.

The DFA construction given in the (3) \Rightarrow (1) proof can be used with other right-invariant equivalence relations.


Construction 5.11 (Myhill-Nerode): Given a language L and right-invariant equivalence relation E such that $MN(L, E)$ we can construct an automaton accepting L using the function

```
MNconstr( $L, E$ ) = let    $T([w]_E, a) = \{[wa]_E\}$   

                     $F = \{[w]_E : w \in L\}$   

in    $([V^*]_E, V, T, \emptyset, \{[\epsilon]_E\}, F)$   

end
```



$[V^*]_E = V^*/R_E$ 表示右不变的等价关系，每个等价关系对应一个状态。
 $[\epsilon]_E$ 表示 ϵ 所在的等价类对应的状态，就是开始状态

This construction has the following properties:

- The definition is independent of the choice of representatives of the equivalence classes of E .
- By inspection we can see that the FA constructed by $MNconstr$ is a *Complete DFA*.
- For any state $U \in [V^*]_E$ we have $\overleftarrow{\mathcal{L}}(U) = U$.
- All states in the constructed automaton are start-reachable.
- The number of states is $\#E$. 状态数与等价类的个数相同
- The construction satisfies the property

$$(\forall L, E : MN(L, E) : \mathcal{L}_{FA}(MNconstr(L, E)) = L)$$

□

5.2 The minimal equivalence relation R_L

The only relation (corresponding to $L \in \mathcal{L}_{\text{reg}}$) that Myhill and Nerode actually defined was R_L . This relation is particularly important, being the unique one of minimal index.

唯一最小的DFA

Theorem 5.12 (Unique minimal DFA): Given $L \in \mathcal{L}_{\text{reg}}$, $M = \text{MNconstr}(L, R_L)$ is the unique minimal Complete DFA accepting L ; that is, $\text{Min}_C(M)$.

Proof:

Assume there exists $M' \in \text{DFA}$ such that $\text{Complete}(M')$, $\mathcal{L}_{\text{FA}}(M') = L$ and $|M'| \leq |M|$. From the proof of (2) \Rightarrow (3) (and Property 5.8), $\#R_L \leq \# \overleftarrow{\mathcal{L}}(M')$. In summary, $\#R_L \leq \# \overleftarrow{\mathcal{L}}(M') \leq |M'| \leq |M| = \#R_L$, and so (by Property A.12) $|M'| = |M|$, $E = R_L$ and $M' \cong M$. \square

Property 5.13 (Reformulating R_L): We can rewrite the definition of R_L using derivatives (see Definition A.15) as follows:

$$\begin{aligned} & (x, y) \in R_L \\ \equiv & \{ \text{Property of derivatives and definition of } R_L \} \\ & (\forall z : z \in V^* : (z \in x^{-1}L) \equiv (z \in y^{-1}L)) \quad z \text{是 } x(y) \text{ 的后缀字符串} \\ \equiv & \{ \text{Definition of } = \text{ on languages} \} \\ & x^{-1}L = y^{-1}L \quad x, y \text{ 具有相同的后缀} \end{aligned}$$

\square

We could combine this definition of R_L with MNconstr to get a minimal DFA construction. Such a function would have a clumsy definition, and therefore we explore some encoding tricks.

5.2.1 Encoding R_L

An encoding trick is hinted at by Property 5.13: every equivalence class $[w]_{R_L}$ of R_L can be characterized by the language $w^{-1}L$. w 的等价类可以由 w 的后缀刻画。

Definition 5.14 (Derivative set of a language): We define the set of derivatives of language L as

$$\text{deriv}(L) = \{v^{-1}L : v \in V^*\}$$

\square

We have the following theorem relating to deriv

Theorem 5.15 (Finiteness of derivatives): If $L \in \mathcal{L}_{\text{reg}}$ then $|\text{deriv}(L)|$ is finite.

Proof:


$\#R_L$ is finite (from the Myhill-Nerode theorem), and since $|\text{deriv}(L)| = \#R_L$, $|\text{deriv}(L)|$ is also finite. \square


This theorem has also been given by Brzozowski [Brzo64]. His proof is, however, somewhat more complicated, and is by induction on the structure of language L .

Definition 5.16 (Encoding an equivalence class): We define a derivative encoding function (for a given $L \in \mathcal{L}_{\text{reg}}$) $\text{encderiv}_L : [V^*]_{R_L} \rightarrow \text{deriv}(L)$ as

$$\text{encderiv}_L([w]_{R_L}) = w^{-1}L$$

This function has inverse $\text{encderiv}_L^{-1}(v^{-1}L) = [v]_{R_L}$. Both of these functions are independent of the choice of representative of equivalence class of R_L . \square





5.2 The minimal equivalence relation R_L

57

Remark 5.17: In Construction 5.11 (with R_L as the equivalence class parameter) the equivalence classes of R_L are the left languages of the states of a DFA constructed from R_L . The function encderiv_L maps these left languages (equivalence classes) to their corresponding right languages (the derivatives). The right language ($\text{encderiv}_L(U)$) of a particular equivalence class $U \in [V^*]_{R_L}$ is called the *continuation* of U (in language L) by Berry and Sethi [BS86]. \square

Property 5.18 (Derivatives and function encderiv_L): Note that (for $a \in V$, $w \in V^*$):

- $\text{encderiv}_L([\epsilon]_{R_L}) = \epsilon^{-1}L = L$,
- $\text{encderiv}_L([wa]_{R_L}) = (wa)^{-1}L = a^{-1}(w^{-1}L)$.

These properties follow from Property A.16, and the definition of encderiv_L . \square

Noting the form of function $MNconstr$, we use the encoding (function encderiv_L) to obtain construction $MNmin \in \mathcal{L}_{\text{reg}} \rightarrow \text{DFA}$.

Construction 5.19 ($MNmin$): Combining $MNconstr$ (Construction 5.11) with encderiv_L (and its inverse) gives construction $MNmin \in \mathcal{L}_{\text{reg}} \rightarrow \text{DFA}$:

$$\begin{aligned} MNmin(L) &= \text{let } T(w^{-1}L, a) = \{a^{-1}(w^{-1}L)\} \\ &\quad F = \{w^{-1}L : \epsilon \in w^{-1}L\} \\ &\quad \text{in } (deriv(L), V, T, \emptyset, \{L\}, F) \\ &\quad \text{end} \end{aligned}$$

Since $MNmin$ is defined using $MNconstr$, the properties are similar:

- By inspection we can see that the FA constructed by $MNmin$ is a *Complete DFA*.
- For any state $U \in deriv(L)$ we have $\vec{\mathcal{L}}(U) = U$.
- All states in the constructed automaton are start-reachable.
- The only state that is not final-reachable is \emptyset . The state \emptyset exists in automaton $MNmin(L)$ if and only if $L \neq V^*$. It follows that we can remove the sink state \emptyset , to obtain a (possibly) non-*Complete DFA* with only useful states.
- The constructed DFA is the unique (up to isomorphism) minimal *Complete DFA* accepting L (since R_L is implicit in the definition).
- The construction satisfies the property


$$(\forall L : L \in \mathcal{L}_{\text{reg}} : \mathcal{L}_{\text{FA}}(MNmin(L)) = L)$$

\square

Example 5.20 ($MNmin$ construction): We construct the minimal *Complete DFA* corresponding to the regular language $\{\epsilon, a\}\{b\}^*$, denoted by regular expression $(a \cup \epsilon)b^*$ (the regular expression from Example 3.15).

After some calculation (using Property A.17):

$$\begin{aligned} a^{-1}(\{\epsilon, a\}\{b\}^*) &= (a^{-1}\{\epsilon, a\})\{b\}^* \cup a^{-1}\{b\}^* \\ &= \{\epsilon\}\{b\}^* \cup (a^{-1}\{b\})\{b\}^* \\ &= \{b\}^* \\ b^{-1}(\{\epsilon, a\}\{b\}^*) &= (b^{-1}\{\epsilon, a\})\{b\}^* \cup b^{-1}\{b\}^* & a^{-1}\emptyset &= \emptyset \\ &= \emptyset\{b\}^* \cup (b^{-1}\{b\})\{b\}^* & a^{-1}\{\epsilon\} &= \emptyset \\ &= \{b\}^* & a^{-1}\{b\} &= \text{if } (a = b) \text{ then } \{\epsilon\} \text{ else } \emptyset \text{ fi} \\ & & a^{-1}(L_0L_1) &= (a^{-1}L_0)L_1 \cup \text{if } (\epsilon \in L_0) \text{ then } a^{-1}L_1 \text{ else } \emptyset \text{ fi} \\ & & a^{-1}(L_0 \cup L_1) &= (a^{-1}L_0) \cup (a^{-1}L_1) \\ & & a^{-1}(L^*) &= (a^{-1}L)L^* \\ & & a^{-1}(L^+) &= (a^{-1}L)L^* \\ & & a^{-1}(L^?) &= a^{-1}L \\ & & a^{-1}(L_0 \cap L_1) &= (a^{-1}L_0) \cap (a^{-1}L_1) \\ & & a^{-1}(\neg L) &= \neg(a^{-1}L) \end{aligned}$$

Figure 8: The DFA $MNmin(\{\epsilon, a\}\{b\}^*)$.

$$\begin{aligned}
 a^{-1}(\{b\}^*) &= (a^{-1}\{b\})\{b\}^* \\
 &= \emptyset\{b\}^* \\
 &= \emptyset \\
 b^{-1}(\{b\}^*) &= (b^{-1}\{b\})\{b\}^* \\
 &= \{b\}^* \\
 a^{-1}\emptyset &= \emptyset \\
 b^{-1}\emptyset &= \emptyset
 \end{aligned}$$

we determine that the three derivatives are: $L = \{\epsilon, a\}\{b\}^*$, $L_1 = \{b\}^*$, and \emptyset . The state graph is shown in Figure 8. \square

5.3 The Brzozowski construction

We now concentrate on constructing *DFA*'s from extended regular expressions, as opposed to constructing them from regular languages. In Property A.17, a method is given for computing a derivative of a regular language (based upon the structure of the language). Being able to compute derivatives in this way also provides us with a definition of derivatives of extended regular expressions (*ERE*'s). Extended regular expressions were defined in Definition 4.53.

Remark 5.21: The Σ -algebra definition of regular expressions is not used in this section as the algebraic structure is not needed. Regular expressions are used only as syntactic objects, denoting regular languages. \square

Remark 5.22: The remaining constructions in this section do not necessarily depend on extended regular expressions (normal regular expressions can also be used). They are introduced because some regular languages have more succinct descriptions as *ERE*'s than as *RE*'s. \square

Definition 5.23 (Derivatives of *ERE*'s): Assuming $a \in V$ and $E, E_0, E_1 \in ERE$

$$\begin{aligned}
 a^{-1}\emptyset &= \emptyset \\
 a^{-1}\epsilon &= \emptyset \\
 a^{-1}b &= \text{if } (a = b) \text{ then } \epsilon \text{ else } \emptyset \text{ fi} && (\text{for all } b \in V) \\
 a^{-1}(E_0 E_1) &= (a^{-1}E_0)E_1 \cup \text{if } (\epsilon \in L_{ERE}(E_0)) \text{ then } a^{-1}E_1 \text{ else } \emptyset \text{ fi} \\
 a^{-1}(E_0 \cup E_1) &= (a^{-1}E_0) \cup (a^{-1}E_1)
 \end{aligned}$$

$$\begin{aligned}
a^{-1}(E^*) &= (a^{-1}E)E^* \\
a^{-1}(E^+) &= (a^{-1}E)E^* \\
a^{-1}(E^?) &= a^{-1}E \\
a^{-1}(E_0 \cap E_1) &= (a^{-1}E_0) \cap (a^{-1}E_1) \\
a^{-1}(\neg E) &= \neg(a^{-1}E)
\end{aligned}$$

□

Property 5.24 (Derivatives of ERE's): By inspecting the definition of derivatives of ERE's, we can verify that (for $a \in V, E \in ERE$) $a^{-1}\mathcal{L}_{ERE}(E) = \mathcal{L}_{ERE}(a^{-1}E)$. □

Remark 5.25: Given equivalence relation \doteq (equivalence of regular expressions, extended to ERE), an $E \in ERE$ will have a finite number of derivatives. More formally, $|\{[w^{-1}E]_\doteq : w \in V^*\}|$ is finite. Brzozowski gave the same result by induction on the structure of a ERE in [Brzo64, Theorem 4.3a]. □

Definition 5.26 (Similarity (\sim) of regular expressions): Similarity (written \sim) is an equivalence relation on ERE's. Two ERE's are similar if and only if they are identical or one can be transformed into the other using the following rules:

1. $E_0 \cup E_1 = E_1 \cup E_0$ (commutativity of \cup),
2. $E_0 \cup (E_1 \cup E_2) = (E_0 \cup E_1) \cup E_2$ (associativity of \cup), and
3. $E \cup E = E$ (idempotence of \cup).

□

Property 5.27 (Similarity): $\sim \subseteq \doteq$; that is, \sim is a refinement of \doteq . □

Definition 5.28 (The derivatives of an ERE): Function $deriv_{ERE} \in ERE \longrightarrow \mathcal{P}([ERE]_\sim)$ is defined as

$$deriv_{ERE}(E) = \{[v^{-1}E : v \in V^*]\}_\sim = \{[v^{-1}E]_\sim : v \in V^*\}$$

□

Before proving that $deriv_{ERE}(E)$ is finite (for all $E \in ERE$), we need the following proposition.

Proposition 5.29 (Similarity equivalence class of a union ERE): Assume a finite set $H \subseteq ERE$ and a fully parenthesized regular expression

$$J = (\cdots (((h_1 \cup h_2) \cup h_3) \cup h_4) \cdots \cup h_k)$$

where (for $1 \leq i \leq k$) $h_i \in H$; each h_i is called a *term* of J . Using \sim we can always find a similar (and, of course, equivalent) regular expression K , where K is the union of at most $|H|$ terms of J . This is because the rules defining \sim can be used to reassociate and commute the terms of J (to place identical terms adjacent to one another), while the idempotence rule of \sim can be used to remove identical terms. □

Proposition 5.30 (Similarity): Given a finite set $H \subseteq ERE$, the set of all non-similar ERE's that are unions of terms $h_i \in H$ is finite. □

Theorem 5.31 (Finiteness of derivatives under similarity): For all $E \in ERE$, $|deriv_{ERE}(E)|$ is finite.

Proof:

This proof is similar to the one given in Brzozowski's original paper [Brzo64, Theorem 5.2]. The proof is by induction on the number of operators in $E \in ERE$.

Basis: The theorem is true for each of the constants: $\text{deriv}_{\text{ERE}}(\epsilon) = \{[\epsilon]_{\sim}, [\emptyset]_{\sim}\}$, $\text{deriv}_{\text{ERE}}(\emptyset) = \{[\emptyset]_{\sim}\}$, and $\text{deriv}_{\text{ERE}}(a) = \{[a]_{\sim}, [\epsilon]_{\sim}, [\emptyset]_{\sim}\}$ (for $a \in V$).

Induction hypothesis: Assume that $|\text{deriv}_{\text{ERE}}(E)|$ is finite for all $E \in \text{ERE}$ where E has fewer than k operators.

Induction step: Assume $E \in \text{ERE}$ has k operators. We use case analysis to deal with the possible forms of E :

$E = E_0 \cup E_1$: It is possible to show that

$$\{[w^{-1}(E_0 \cup E_1)]_{\sim} : w \in V^*\} = \{[w^{-1}E_0 \cup w^{-1}E_1]_{\sim} : w \in V^*\}$$

By the induction hypothesis, $|\text{deriv}_{\text{ERE}}(E_0)|$ and $|\text{deriv}_{\text{ERE}}(E_1)|$ are finite, and so is $|\text{deriv}_{\text{ERE}}(E)|$.

$E = E_0 \cap E_1$ or $E = E_0^*$ or $E = \neg E_0$: An argument similar to that for \cup applies to these cases.

$E = E_0 \cdot E_1$: In order to analyze $|\text{deriv}_{\text{ERE}}(E_0 \cdot E_1)|$, we consider a particular $w^{-1}(E_0 \cdot E_1)$ (for $w \in V^*$). Let $w = a_1 \cdots a_n$ where each $a_i \in V$. Writing out $w^{-1}(E_0 \cdot E_1)$ we get

$$\begin{aligned} & w^{-1}(E_0 \cdot E_1) \\ &= (a_2 \cdots a_n)^{-1}((a_1^{-1}E_0)E_1 \cup \text{if } (\epsilon \in \mathcal{L}_{\text{ERE}}(E_0)) \text{ then } a_1^{-1}E_1 \text{ else } \emptyset \text{ fi}) \end{aligned}$$

If we had been able to continue this rewriting, we would see that $[w^{-1}(E_0 \cdot E_1)]_{\sim}$ is equal to

$$[(w^{-1}E_0) \cdot E_1 \cup (\cup u, v : uv = w : \text{if } (\epsilon \in \mathcal{L}_{\text{ERE}}(u^{-1}E_0)) \text{ then } v^{-1}E_1 \text{ else } \emptyset \text{ fi})]_{\sim}$$

That is, $w^{-1}(E_0 \cdot E_1)$ is the union of a set of terms, one of which is $(w^{-1}E_0) \cdot E_1$, and the remaining ones are either a derivative of E_1 , or $\emptyset \in \text{ERE}$. By the induction hypothesis (the set of derivatives of E_1 is finite) the set of possible terms is finite. It follows from Propositions 5.29 and 5.30 that $|\text{deriv}_{\text{ERE}}(E)|$ is finite.

$E = E_0^*$ or $E = E_0^+$: As in the $E_0 \cdot E_1$ case, we could write out $w^{-1}(E_0^*)$ for a particular $w \in V^*$. If we do this, we see that it is the union of terms, each of which is a derivative of E_0 concatenated with E_0^* . The set of possible terms is finite — by the induction hypothesis. Again, it follows from Propositions 5.29 and 5.30 that $|\text{deriv}_{\text{ERE}}(E)|$ is finite.

□

Remark 5.32: Unfortunately, using similarity (in computing derivatives) may yield more derivatives than recognizing equivalence (\doteq) of derivatives (as shown in Example 5.37). The rules defining similarity can be augmented with others to decrease the redundancy of the derivatives (and therefore the size of the constructed DFA). Any equivalence relation G such that $\sim \subseteq G \subseteq \doteq$ is usable for this. Examples of additional rules are (for $E_0, E_1, E_2 \in \text{ERE}$):

1. $E_0 \cdot \emptyset = \emptyset$ (\emptyset is the zero of concatenation),
2. $E_0 \cup \emptyset = E_0$ (\emptyset is the unit of \cup),
3. $E_0 \cdot \epsilon = E_0$ (ϵ is the unit of concatenation),
4. $\emptyset^* = \epsilon$ (a property of $*$),
5. $E_0 \cdot (E_1 \cup E_2) = E_0 \cdot E_1 \cup E_0 \cdot E_2$ (\cdot distributes over \cup),
6. $E_0 \cap \emptyset = \emptyset$ (\emptyset is the zero of \cap),
7. $E_0 \cap E_1 = E_1 \cap E_0$ (commutativity of \cap),

8. $E_0 \cap (E_1 \cap E_2) = (E_0 \cap E_1) \cap E_2$ (associativity of \cap).
9. $E \cap E = E$ (idempotence of \cap).

□

There is a property of similarity that will be needed to present the Brzozowski construction.

Definition 5.33 (Derivative of a similarity equivalence class): For $E \in ERE$ and $a \in V$ we have $a^{-1}[E]_{\sim} = [a^{-1}E]_{\sim}$. This definition does not depend on the choice of representative of the equivalence class (under \sim). □

The Brzozowski construction is an encoding of $MNmin$ to use ERE 's and equivalence classes of \sim .

Construction 5.34 (Brzozowski): Function $Brz \in ERE \rightarrow DFA$ is defined as:

```

 $Brz(E) = \text{let } T([v^{-1}E]_{\sim}, a) = \{a^{-1}[v^{-1}E]_{\sim}\}$ 
           $F = \{[w^{-1}E]_{\sim} : \epsilon \in \mathcal{L}_{ERE}(w^{-1}E)\}$ 
           $\text{in } (deriv_{ERE}(E), V, T, \emptyset, \{[E]_{\sim}\}, F)$ 
           $\text{end}$ 
```

The properties of Brz correspond to those of $MNmin$:

- The construction is independent of the representatives of equivalence classes.
- By inspection we can see that Brz constructs *Complete DFA*'s.
- For any state $E' \in deriv_{ERE}(E)$ we have $\overrightarrow{\mathcal{L}}(E') = \mathcal{L}_{ERE}(E')$.
- All states in the constructed automaton are start-reachable.
- There may be a state that is not final-reachable; this sink state will exist if and only if $\mathcal{L}_{ERE}(E) \neq V^*$. The sink state corresponds to the derivative $\emptyset \in ERE$.
- The construction satisfies the property

$$(\forall E : E \in ERE : \mathcal{L}_{FA}(Brz(E)) = \mathcal{L}_{ERE}(E))$$


□

Remark 5.35: Any equivalence relation G (on ERE 's) such that $\sim \subseteq G \subseteq \dot{=}$ can be used in place of \sim in Brzozowski's construction. □

Remark 5.36: In Brzozowski's original paper [Brzo64], the sink state (corresponding to derivative $\emptyset \in ERE$) was always omitted from the constructed *DFA*, producing a possibly non-*Complete DFA*. □

Example 5.37 (Brzozowski's construction): We construct a *Complete DFA* corresponding to regular expression $(a \cup \epsilon)b^*$ (the regular expression from Example 3.15). The derivatives are:

$$\begin{aligned}
 a^{-1}((a \cup \epsilon)b^*) &= (a^{-1}(a \cup \epsilon))b^* \cup a^{-1}(b^*) \\
 &= (a^{-1}a \cup a^{-1}\epsilon)b^* \cup (a^{-1}b)b^* \\
 &= (\epsilon \cup \emptyset)b^* \cup \emptyset b^* \\
 b^{-1}((a \cup \epsilon)b^*) &= (b^{-1}(a \cup \epsilon))b^* \cup b^{-1}(b^*) \\
 &= (b^{-1}a \cup b^{-1}\epsilon)b^* \cup (b^{-1}b)b^* \\
 &= (\emptyset \cup \emptyset)b^* \cup \epsilon b^*
 \end{aligned}$$

Figure 9: The DFA $\text{Brz}((a \cup \epsilon)b^*)$.

$$\begin{aligned}
&\sim \emptyset b^* \cup \epsilon b^* \\
a^{-1}((\epsilon \cup \emptyset)b^* \cup \emptyset b^*) &= a^{-1}((\epsilon \cup \emptyset)b^*) \cup a^{-1}(\emptyset b^*) \\
&= ((a^{-1}(\epsilon \cup \emptyset))b^* \cup a^{-1}(b^*)) \cup (a^{-1}\emptyset)b^* \\
&= (((a^{-1}\epsilon \cup a^{-1}\emptyset)b^*) \cup (a^{-1}b)b^*) \cup \emptyset b^* \\
&= ((\emptyset \cup \emptyset)b^* \cup (\emptyset)b^*) \cup \emptyset b^* \\
&\sim \emptyset b^* \\
b^{-1}((\epsilon \cup \emptyset)b^* \cup \emptyset b^*) &= b^{-1}((\epsilon \cup \emptyset)b^*) \cup b^{-1}(\emptyset b^*) \\
&= ((b^{-1}(\epsilon \cup \emptyset))b^* \cup (b^{-1}b)b^*) \cup (b^{-1}\emptyset)b^* \\
&= ((b^{-1}\epsilon \cup b^{-1}\emptyset)b^* \cup (\epsilon)b^*) \cup \emptyset b^* \\
&= ((\emptyset \cup \emptyset)b^* \cup \epsilon b^*) \cup \emptyset b^* \\
&\sim \emptyset b^* \cup \epsilon b^* \\
a^{-1}(\emptyset b^* \cup \epsilon b^*) &= a^{-1}(\emptyset b^*) \cup a^{-1}(\epsilon b^*) \\
&= (a^{-1}\emptyset)b^* \cup ((a^{-1}\epsilon)b^* \cup (a^{-1}b)b^*) \\
&\sim \emptyset b^* \\
b^{-1}(\emptyset b^* \cup \epsilon b^*) &= b^{-1}(\emptyset b^*) \cup b^{-1}(\epsilon b^*) \\
&= (b^{-1}\emptyset)b^* \cup ((b^{-1}\epsilon)b^* \cup (b^{-1}b)b^*) \\
&\sim \emptyset b^* \cup \epsilon b^* \\
a^{-1}(\emptyset b^*) &= (a^{-1}\emptyset)b^* \\
&= \emptyset b^* \\
b^{-1}(\emptyset b^*) &= (b^{-1}\emptyset)b^* \\
&= \emptyset b^*
\end{aligned}$$

The four derivatives (under \sim) are: $d_0 = (a \cup \epsilon)b^*$, $d_1 = (\epsilon \cup \emptyset)b^* \cup \emptyset b^*$, $d_2 = \emptyset b^* \cup \epsilon b^*$, and $d_3 = \emptyset b^*$. The state graph is shown in Figure 9. Had we been able to recognize equivalence of ERE's, we would have had a smaller DFA since $(\epsilon \cup \emptyset)b^* \cup \emptyset b^* \doteq \emptyset b^* \cup \epsilon b^*$, and we could have identified states d_1 and d_2 . \square

5.3.1 Computing derivatives of an ERE

Brzozowski also shows [Brzo64] if $E \in \text{ERE}$ has n derivatives (including E , under any equivalence relation G such that $\sim \subseteq G \subseteq \doteq$) then they are all of the form $v^{-1}E$ where $|v| < n$ [Brzo64, Theorem 4.3b]. Also part of this theorem is if all derivatives (of E) with respect to strings of length not greater than n have been found, and no new ones are found with respect to strings of length $n+1$, then no new ones will be found with respect to strings of length greater than n . This useful property of derivatives (in fact a slightly stronger property) can be stated as follows:

Theorem 5.38 (Finding derivatives): For all $r \geq 0$

$$\begin{aligned} & \{[w^{-1}E]_\sim : w \in V^* \wedge |w| = r\} \subseteq \{[w^{-1}E]_\sim : w \in V^* \wedge |w| < r\} \\ \Rightarrow & \{[w^{-1}E]_\sim : w \in V^* \wedge |w| \geq r\} \subseteq \{[w^{-1}E]_\sim : w \in V^* \wedge |w| < r\} \end{aligned}$$

□

This gives the following algorithm (in the guarded commands of [Dijk76]) which computes the derivatives of a regular expression E ($D \subseteq [ERE]_\sim$ and $next \subseteq [ERE]_\sim$):

Algorithm 5.39:

```

{ $E \in ERE$ }
 $D, next, k := \emptyset, \{[E]_\sim\}, 0;$ 
{invariant:  $D = \{[w^{-1}E]_\sim : w \in V^* \wedge |w| < k\} \wedge next = \{[w^{-1}E]_\sim : w \in V^* \wedge |w| = k\}$ }
do  $next \not\subseteq D$  —
   $D, next, k := D \cup next, \{a^{-1}F : a \in V \wedge F \in next\}, k + 1$ 
od { $D = deriv_{ERE}(E)$ }
```

5.3.2 Extending derivatives

It is sometimes useful to extend derivatives to deal with additional operators: prefix closure and certain functions on languages. We now briefly give the definition of derivatives of regular languages (and thus regular expressions) with these operators.

The prefix closure of a language is defined as:

$$\text{pref}(L) = \{u : u^{-1}L \neq \emptyset\}$$

and the derivative of a prefix closed language is:

$$a^{-1}(\text{pref}(L)) = \text{pref}(a^{-1}L)$$

For certain functions $f \in \mathcal{L}_{\text{reg}} \times \mathcal{L}_{\text{reg}} \rightarrow \mathcal{L}_{\text{reg}}$, derivatives are defined as:

$$a^{-1}(f(L_0, L_1)) = f(a^{-1}L_0, a^{-1}L_1)$$

Some examples of such functions are \cap , \cup , asymmetrical difference, and symmetrical difference. For more on this see [Brzo64].

5.4 Relating the Brzozowski and Berry-Sethi constructions

It turns out that for RRE 's (recall from Definition 4.58 that an $E \in RRE$ is an RE such that each symbol of V occurs at most once in E), the Brzozowski construction (with sink state removal — as in Brzozowski's original paper — and a suitable encoding) and the Berry-Sethi construction produce isomorphic DFA 's. In this section, we consider only RRE 's. Berry and Sethi first presented this result in [BS86].

We will be using the following version of Brzozowski's construction (for $E \in RRE$), which does not introduce a sink state (the sink state is equivalent (\doteq) to $\emptyset \in RRE$ — its language under \mathcal{L}_{RE} is \emptyset).

Construction 5.40 (Brzozowski — without sink state): Given $E \in RE$, the following constructs a DFA accepting $\mathcal{L}_{RE}(E)$:

```

let    $Q = \{[w^{-1}E]_\sim : w \in V^* \wedge \mathcal{L}_{RE}(w^{-1}E) \neq \emptyset\}$ 
       $T([v^{-1}E]_\sim, a) = \text{if } (\mathcal{L}_{RE}(a^{-1}(v^{-1}E)) \neq \emptyset) \text{ then } \{a^{-1}[v^{-1}E]_\sim\} \text{ else } \emptyset \text{ fi}$ 
       $F = \{[w^{-1}E]_\sim : \text{Null}(w^{-1}E)\}$ 
in     $(Q, V, T, \emptyset, \{[E]_\sim\}, F)$ 
end
```

In the `let` clause, the transition function has signature $T \in Q \times V \rightarrow \mathcal{P}(Q)$. Recall from Definition 3.20 that $\text{Null}(E) \equiv \epsilon \in \mathcal{L}_{RE}(E)$. \square

For any $E \in RRE$, the only way that $\mathcal{L}_{RE}(b^{-1}((wa)^{-1}E)) \neq \emptyset$ is if $\mathcal{L}_{RE}((wa)^{-1}E) \neq \emptyset$ and a b can follow a wa in some string in $\mathcal{L}_{RE}(E)$.

In order to make the above construction practical, we explore the possibility of characterizing all of the derivatives of an $E \in RE$ (except for the derivative E itself) by the symbols occurring in E .

Definition 5.41 (Unambiguous regular expressions): An $E \in RE$ is said to be *unambiguous* if and only if, for all $a \in \text{Occ}(E)$ (function Occ is defined in Definition 4.57), the following set is a singleton set:

$$\{[(wa)^{-1}E]_\sim : w \in V^* \wedge \mathcal{L}_{RE}((wa)^{-1}E) \neq \emptyset\}$$

In other words, all derivatives of E by wa (for $w \in V^*$ and $a \in V$) are either equivalent to $\emptyset \in RRE$, or are similar to one another. \square

Remark 5.42: If an $E \in RE$ is unambiguous, its derivatives are either E or \emptyset , or can be characterized by an element of $\text{Occ}(E)$. \square

Remark 5.43: The regular expression $(a \cup a)$ is unambiguous, but is not an *RRE*. \square

Remark 5.44: Unambiguous regular expressions are also defined by Champarnaud [Cham93], although he characterizes them quite differently, and he does not make use of derivatives. Champarnaud calls such regular expressions *local*. \square

Theorem 5.45 (Characterizing derivatives of *RRE*'s): For any $E \in RRE$, E is unambiguous. This theorem is also given by Berry and Sethi [BS86, Theorem 3.4].

Proof:

We proceed by induction on the number of operators in $E \in RRE$.

Basis: The theorem is trivially true for the *RRE* base cases ϵ and \emptyset since $\text{Occ}(\epsilon) = \text{Occ}(\emptyset) = \emptyset$. It is also trivially true for the *RRE* $a \in V$.

Induction hypothesis: Assume that the theorem is true for any $E \in RRE$ with fewer than k operators.

Induction step: We now consider $E \in RRE$ with k operators. We now examine the possible structure of E (assuming $a \in \text{Occ}(E)$).

$E = E_0 \cup E_1$: Given $w \in V^*$ such that $\mathcal{L}_{RE}((wa)^{-1}E) \neq \emptyset$

$$(wa)^{-1}(E_0 \cup E_1) = ((wa)^{-1}E_0) \cup ((wa)^{-1}E_1)$$

Since $E \in RRE$, then either $a \in \text{Occ}(E_0)$ or $a \in \text{Occ}(E_1)$ (but not both). It follows that $(wa)^{-1}(E_0 \cup E_1)$ is similar to $(wa)^{-1}E_0 \cup \emptyset$ or similar to $(wa)^{-1}E_1 \cup \emptyset$ (but not both). The theorem then follows from the induction hypothesis.

$E = E_0 \cdot E_1$: From Theorem 5.31 we know that (for $w \in V^*, a \in V$) $[(wa)^{-1}(E_0 \cdot E_1)]_\sim$ is equal to:

$$[((wa)^{-1}E_0)E_1 \cup (\cup u, v : uva = wa : \text{if } (\epsilon \in \mathcal{L}_{ERE}(u^{-1}E_0)) \text{ then } (va)^{-1}E_1 \text{ else } \emptyset \text{ fi}])_\sim$$

Since $E \in RRE$, then either $a \in \text{Occ}(E_0)$ or $a \in \text{Occ}(E_1)$ (but not both). It follows, by an argument similar to the $E = E_0 \cup E_1$ case (above), that the theorem holds from the induction hypothesis.

$E = E_0^*, E = E_0^+$ or $E = E_0^?$: The argument for these cases proceeds similarly to the $E = E_0 \cdot E_1$ case. For more on this type of argument see Theorem 5.31.

□

Remark 5.46: The above theorem implies that each derivative of $E \in RRE$ (under similarity) is either \emptyset (which we ignore since it corresponds to the sink state) or E , or it can be characterized by an $a \in Occ(E)$. □

Definition 5.47 (Encoding the derivatives of an RRE): Given the theorem above, $E \in RRE$, we can now give a partial encoding function enc_E (corresponding to the $E \in RRE$) from the derivatives of E to $Occ(E)$ such that (for $w \in V^*, a \in V$) $enc_E((wa)^{-1}E) = a$ when $\mathcal{L}_{RE}((wa)^{-1}E) \neq \emptyset$, and enc_E is undefined otherwise. Note that this function is not defined on E . □

The following property makes use of the definitions of *Null*, *Occ*, *First*, *Last*, and *Follow* (Definitions 3.20, 4.57, 4.60–4.64 respectively).

Property 5.48 (Functions Follow, First, and Last): The following properties will be used:

- $(a, b) \in Follow(E) \equiv (\exists w : w \in V^* : \mathcal{L}_{RE}(b^{-1}((wa)^{-1}E)) \neq \emptyset)$.
- $a \in First(E) \equiv \mathcal{L}_{RE}(a^{-1}E) \neq \emptyset$.
- $a \in Last(E) \equiv \mathcal{L}_{RE}(Ea^{-1}) \neq \emptyset \equiv (\exists w : w \in V^* : \epsilon \in \mathcal{L}_{RE}((wa)^{-1}E))$.

Derivatives on the right are mentioned in Definition A.15. □

We can rewrite our sink stateless version of Brzozowski's construction, using the above properties, to obtain the construction now following.

Construction 5.49 (Encoding Brzozowski for RRE's): We can now give our encoded version (using *Occ*, *First*, *Last*, *Null*, and *Follow*) of Construction 5.40, as $Brzenc \in RRE \rightarrow DFA$:

```

 $Brzenc(E) = \text{let } s \text{ be a new state (characterizing } E \in RRE)$ 
 $\quad \text{in}$ 
 $\quad \quad \text{let } T = \{(a, b, b) : (a, b) \in Follow(E)\}$ 
 $\quad \quad T' = \{(s, a, a) : a \in First(E)\}$ 
 $\quad \quad F = Last(E) \cup \text{if } (Null(E)) \text{ then } \{s\} \text{ else } \emptyset \text{ fi}$ 
 $\quad \quad \text{in}$ 
 $\quad \quad \quad (Occ(E) \cup \{s\}, V, T \cup T', \emptyset, \{s\}, F)$ 
 $\quad \quad \text{end}$ 
 $\quad \text{end}$ 
```

□

Remark 5.50: Using the set *Occ*(E) as the set of states can yield a *DFA* with start-unreachable states. For example, in the *DFA* $Brzenc(\emptyset \cdot a)$, we have start-unreachable state a . □

Remark 5.51: By inspection we see that, for all $E \in RRE$, $Brzenc(E) \cong BSenc(E)$ (Construction 4.70). It follows from Remark 4.73, that for $E \in RRE$, $[Brz(E)]_{\cong} = MYG(E)$. □

Remark 5.52: Finally, we note that the construction *Brzenc* produces a correct *DFA* for any $E \in RE$ such that E is unambiguous. That is, $E \in RRE$ is not required. This property is not noted in the literature. This follows from Definition 5.41 and the definition of *Brzenc*. □

5.5 Towards DeRemer's construction

In this subsection, we consider several more constructions based upon the *MNconstr* and *MNmin* constructions (Constructions 5.11 and 5.19). The idea is to characterize the derivatives of a regular expression by so-called dotted regular expressions. We only consider constructing a *DFA* from an *RE*, as opposed to an *ERE*. Since some of the proofs are tedious to present, we give this construction in an informal manner.

We begin by introducing *dotted regular expressions*, which are essentially regular expressions with a dot (\bullet) appearing in each of them.

Remark 5.53: We will be characterizing derivatives, not equivalence classes (as is required for *MNconstr*). Using dotted *RE*'s, it is considerably easier to characterize the derivatives than the equivalence classes. \square

The dot should not be confused with the concatenation dot, the star normal-form dot of Brüggemann-Klein (presented in Section 4.5), or the bullet used in typesetting lists.

Definition 5.54 (Dotted regular expressions, their languages, and *undot*): We recursively define dotted regular expressions (*DRE*'s), function $\mathcal{R} \in DRE \rightarrow \mathcal{P}(V^*)$, and function $undot \in DRE \rightarrow RE$. Function \mathcal{R} maps *DRE*'s to the (regular) language to the right of the dot, and function *undot* removes the dot in a *DRE*.

1. If $E \in RE$ then
 - (a) $\bullet E \in DRE$, $\mathcal{R}(\bullet E) = \mathcal{L}_{RE}(E)$, and $undot(\bullet E) = E$;
 - (b) $E\bullet \in DRE$, $\mathcal{R}(E\bullet) = \{\epsilon\}$, and $undot(E\bullet) = E$.
2. If $E \in RE$ and $D \in DRE$ then
 - (a) $E \cup D \in DRE$, $D \cup E \in DRE$, $\mathcal{R}(E \cup D) = \mathcal{R}(D \cup E) = \mathcal{R}(D)$, $undot(E \cup D) = E \cup undot(D)$, and $undot(D \cup E) = undot(D) \cup E$;
 - (b) $E \cdot D \in DRE$, $D \cdot E \in DRE$, $\mathcal{R}(E \cdot D) = \mathcal{R}(D)$, $\mathcal{R}(D \cdot E) = \mathcal{R}(D) \cdot \mathcal{L}_{RE}(E)$, $undot(E \cdot D) = E \cdot undot(D)$, and $undot(D \cdot E) = undot(D) \cdot E$;
 - (c) $D^* \in DRE$, $\mathcal{R}(D^*) = \mathcal{R}(D) \cdot \mathcal{L}_{RE}(undot(D))^*$, and $undot(D^*) = undot(D)^*$;
 - (d) $D^+ \in DRE$, $\mathcal{R}(D^+) = \mathcal{R}(D) \cdot \mathcal{L}_{RE}(undot(D))^*$, and $undot(D^+) = undot(D)^+$;
 - (e) $D^? \in DRE$, $\mathcal{R}(D^?) = \mathcal{R}(D)$, and $undot(D^?) = undot(D)^?$.
3. Nothing else is a *DRE*.

A dotted regular expression is also known as an *item*, from LR parsing [Knut65]; we will frequently use this name. \square

We also require a function mapping a regular expression to all of its dottings.

Definition 5.55 (Function *dots*): We define function $dots \in RE \rightarrow \mathcal{P}(DRE)$ as follows:

$$dots(E) = \{D : D \in DRE \wedge undot(D) = E\}$$

\square

Remark 5.56: For a given $E \in RE$, we will be using sets of items (elements of $\mathcal{P}(dots(E))$) to characterize the derivatives of $\mathcal{L}_{RE}(E)$ when constructing a DFA accepting $\mathcal{L}_{RE}(E)$. \square

Property 5.57 (*dots*): For all $E \in RE$, $|dots(E)|$ is finite, and so is $|\mathcal{P}(dots(E))|$. \square

We define an item set, and its language as follows:

Definition 5.58 (Item sets and their languages): An *item set* J is a subset of *DRE* such that:

$$(\exists E : E \in RE : J \subseteq dots(E))$$

IS denotes the set of all item sets. Essentially, an *IS* is a set of items, all of which are dottings of the same regular expression. We also extend *undot* to *IS*. \square

Definition 5.59 (Language of an *IS*): The language of a $J \in IS$ is given by function $\mathcal{L}_{IS} \in IS \rightarrow \mathcal{P}(V^*)$ defined as:

$$\mathcal{L}_{IS}(J) = (\cup I : I \in J : \mathcal{R}(I))$$

\square

Remark 5.60: We will use item sets to characterize the derivatives of an RE. \square

We now define derivatives of item sets.

Definition 5.61 (Derivative of an item set): Given $J \in IS$ and $a \in V$ we define $a^{-1}J$ to be the following set:

1. If $I \in J$ has a subexpression $\bullet a$ then I' is in $a^{-1}J$, where I' is the same as I with the subexpression $\bullet a$ replaced by $a\bullet$.
2. Nothing else is in $a^{-1}J$.

\square

We can now define a special type of function, which we call a *closure function*.

Definition 5.62 (Closure functions): Any function $\mathcal{E} : IS \rightarrow IS$ can be used as a closure function, provided that

$$(\forall J : J \in IS : \mathcal{L}_{IS}(\mathcal{E}(J)) = \mathcal{L}_{IS}(J) \wedge \mathcal{E} \circ \mathcal{E}(J) = \mathcal{E}(J))$$

and

$$(\forall E, J : E \in RE \wedge J \subseteq dots(E) : \epsilon \in \mathcal{L}_{IS}(J) \equiv (E\bullet) \in \mathcal{E}(J))$$

and

$$(\forall J, a : J \in IS \wedge a \in V : \mathcal{L}_{IS}(a^{-1}\mathcal{E}(J)) = a^{-1}\mathcal{L}_{IS}(J))$$

\square

We are now in a position to define our first closure function, and an auxiliary relation.

Definition 5.63 (Dot closure relation \mathcal{D}): We define a binary relation \mathcal{D} on DRE. \mathcal{D} is the smallest relation such that:

1. If $E, F \in RE$, then (here we use infix notation for relation \mathcal{D}):

$\bullet\epsilon$	\mathcal{D}	$\epsilon\bullet$
$\bullet(E \cdot F)$	\mathcal{D}	$(\bullet E) \cdot F$
$(E\bullet) \cdot F$	\mathcal{D}	$E \cdot (\bullet F)$
$E \cdot (F\bullet)$	\mathcal{D}	$(E \cdot F)\bullet$
$\bullet(E \cup F)$	\mathcal{D}	$(\bullet E) \cup F$
$\bullet(E \cup F)$	\mathcal{D}	$E \cup (\bullet F)$
$(E\bullet) \cup F$	\mathcal{D}	$(E \cup F)\bullet$
$E \cup (F\bullet)$	\mathcal{D}	$(E \cup F)\bullet$
$\bullet(E^*)$	\mathcal{D}	$(\bullet E)^*$
$\bullet(E^*)$	\mathcal{D}	$(E^*)\bullet$
$(E\bullet)^*$	\mathcal{D}	$(\bullet E)^*$
$(E\bullet)^*$	\mathcal{D}	$(E^*)\bullet$
$\bullet(E^+)$	\mathcal{D}	$(\bullet E)^+$
$(E\bullet)^+$	\mathcal{D}	$(\bullet E)^+$
$(E\bullet)^+$	\mathcal{D}	$(E^+)\bullet$
$\bullet(E^?)$	\mathcal{D}	$(\bullet E)^?$
$\bullet(E^?)$	\mathcal{D}	$(E^?)\bullet$
$(E\bullet)^?$	\mathcal{D}	$(E^?)\bullet$

2. If $E \in RE$ and $D_0, D_1 \in DRE$ such that $(D_0, D_1) \in \mathcal{D}$, then:

- (a) $(E \cup D_0, E \cup D_1) \in \mathcal{D}$, $(D_0 \cup E, D_1 \cup E) \in \mathcal{D}$, $(E \cdot D_0, E \cdot D_1) \in \mathcal{D}$, and $(D_0 \cdot E, D_1 \cdot E) \in \mathcal{D}$.

(b) $(D_0^*, D_1^*) \in \mathcal{D}$, $(D_0^+, D_1^+) \in \mathcal{D}$, and $(D_0^?, D_1^?) \in \mathcal{D}$.

□

Definition 5.64 (Closure function \mathcal{C}): We define function $\mathcal{C} \in IS \rightarrow IS$ as:

$$\mathcal{C}(J) = \mathcal{D}^*(J)$$

Function \mathcal{C} satisfies the Definition 5.62, making it a closure function. □

Remark 5.65: The closure function \mathcal{C} presented here is an extension (to deal with our definition of regular expressions) of the one usually given for LR parsing. □

Example 5.66 (Function \mathcal{C}): $\mathcal{C}(\{\bullet((a \cup \epsilon)b^*)\})$ is computed to be $\{\bullet((a \cup \epsilon)b^*), (\bullet(a \cup \epsilon))b^*, (\bullet a \cup \epsilon)b^*, (a \cup \bullet \epsilon)b^*, (a \cup \epsilon \bullet)b^*, ((a \cup \epsilon)\bullet)b^*, (a \cup \epsilon)(\bullet(b^*)), (a \cup \epsilon)(\bullet b)^*, (a \cup \epsilon)(b^*\bullet), ((a \cup \epsilon)b^*)\bullet\}$. □

In order to construct a DFA for an RE, we require a set of item sets which characterize the set of derivatives of a the regular expression. The following definition gives the necessary conditions.

Definition 5.67 (Derivative item set): Given $E \in RE$, the set $D \subseteq \mathcal{P}(\text{dots}(E))$ (that is, $D \subseteq IS$ and for each $J \in D$, $E = \text{undot}(J)$) characterizes (under some closure function \mathcal{E}) the derivatives of E if and only if:

$$\{w^{-1}\mathcal{L}_{RE}(E) : w \in V^*\} = \{\mathcal{L}_{IS}(J) : J \in D\}$$

and

$$(\forall J : J \in D : J = \mathcal{E}(J))$$

and

$$(\forall J, a : J \in D \wedge a \in V : \mathcal{E}(a^{-1}J) \in D)$$

We write this property $DIS(E, D, \mathcal{E})$. The set D is called a *derivative item set* for E . □

We are now in a position to modify Algorithm 5.39 to compute such a derivative item set (under some closure function \mathcal{E}), instead of a set of derivatives. In the following algorithm, $D, next \subseteq IS$.

Algorithm 5.68:

```

{ $E \in RE$ }
 $D, next := \emptyset, \{\mathcal{E}(\{\bullet E\})\};$ 
 $\text{do } next \not\subseteq D \rightarrow$ 
     $D, next := D \cup next, \{\mathcal{E}(a^{-1}I) : a \in V \wedge I \in next\}$ 
 $\text{od}$ 
{ $DIS(E, D, \mathcal{E})$ }
```

This algorithm terminates since $|\mathcal{P}(\text{dots}(E))|$ is finite (Property 5.57). With the set D computed above, we can now construct a DFA accepting $\mathcal{L}_{RE}(E)$.

Construction 5.69 (Item set construction): Function $Iconstr \in RE \times \mathcal{P}(IS) \rightarrow DFA$ takes a regular expression (E) and a derivative item set (D) for the RE (such that $DIS(E, D, \mathcal{C})$), and constructs a DFA:



```

 $Iconstr(E, D) = \text{let } T(J, a) = \{\mathcal{C}(a^{-1}J)\}$ 
 $S = \{\mathcal{C}(\{\bullet E\})\}$ 
 $F = \{J : J \in D \wedge E \bullet \in J\}$ 
 $\text{in } (D, V, T, \emptyset, S, F)$ 
 $\text{end}$ 
```

A DFA constructed with $Iconstr$ has the following property:

$$(\forall E, D : DIS(E, D, \mathcal{C}) : \mathcal{L}_{FA}(Iconstr(E, D)) = \mathcal{L}_{RE}(E))$$

The DFA is also *Complete*. □

Figure 10: The DFA $I\text{constr}((a \cup \epsilon)b^*)$.Figure 11: The DFA $I\text{constr}(b^*)$.

Example 5.70 ($I\text{constr}$): We construct the DFA corresponding to $(a \cup \epsilon)b^*$. The derivative item set is (the individual item sets have been compressed, as a notational convenience, and each item set is given a label):

$$\{I_0 = \bullet(\bullet(a \cup \epsilon)\bullet)(\bullet(b)^*\bullet), I_1 = ((a \cup \epsilon)\bullet)(\bullet(b)^*\bullet), I_2 = ((a \cup \epsilon))((b^*)^*\bullet), I_3 = \emptyset\}$$

The DFA is shown in Figure 10 \square

5.5.1 Making the construction more efficient

Because of the definition of \mathcal{C} , function $I\text{constr}$ sometimes constructs a DFA which is larger than necessary, as shown in the following example.

Example 5.71 (A DFA that is not minimal): We use $I\text{constr}$ to construct a DFA for $b^* \in RE$. The two item sets are $D = \{\{(b^*)^*, (b^*)\bullet\}, \{(b^*)^*, (\bullet b)^*\}\}$. The DFA is shown in Figure 11. The problem is that the two item sets should have been recognized as denoting equivalent derivatives since:


$$\mathcal{L}_{IS}(\{(b^*)^*, (b^*)\bullet\}) = \mathcal{L}_{IS}(\{(b^*)^*, (\bullet b)^*\})$$

They only differ in the items $\bullet(b^*)$ and $(b^*)^*$. \square

The problem is that for some $J \in IS$, there is much redundant information in $\mathcal{C}(J)$. In particular, there may be a $J' \subset J$ such that $\mathcal{L}_{IS}(J') = \mathcal{L}_{IS}(J)$. We can introduce a function \mathcal{X} such that $\mathcal{X} \circ \mathcal{C}$ is a closure function. That is, \mathcal{X} is used as a filter.

Definition 5.72 (Item set optimization function \mathcal{X}): Given $J \in IS$ such that $J = \mathcal{C}(J)$, $\mathcal{X}(J)$ is the same as J , with the following removed: any item containing a subexpression of the form $\bullet(E \cup F)$, $\bullet(E^*)$, or $(E\bullet)^*$. \square

Property 5.73 (Function $\mathcal{X} \circ \mathcal{C}$): Function $\mathcal{X} \circ \mathcal{C}$ satisfies Definition 5.62, and is a closure function. \square

Figure 12: The DFA $\text{DeRemer}(b^*)$.

Remark 5.74: The reason that such items are removed is that the definition of \mathcal{C} ensures that they are redundant; other items will have been added to the item set to ensure that these ones are not needed. For example, in the case of $\bullet(E \cup F)$ function \mathcal{C} will ensure that $\bullet E \cup F$ and $E \cup \bullet F$ are added to the item set. In this case $\mathcal{R}(\bullet(E \cup F)) = \mathcal{R}(\bullet E \cup F) \cup \mathcal{R}(E \cup \bullet F)$. \square

Using composite function $\mathcal{X} \circ \mathcal{C}$, we can now present a revised version of the above construction.

Construction 5.75 (DeRemer's construction): DeRemer's construction is function DeRemer , which is exactly as $I\text{constr}$, except that the composite function $\mathcal{X} \circ \mathcal{C}$ is used as the closure function wherever \mathcal{C} was used in $I\text{constr}$. This construction is due to DeRemer [DeRe74], where he attributes the idea behind the definition of \mathcal{X} to Earley [Earl70]. \square

Remark 5.76: DeRemer presented this construction in a slightly different context: he extended an LR parser to deal with grammar production rules with regular expression as right hand sides [DeRe74]. Remark 5.78 points out a slight problem with the original presentation by DeRemer. \square

Example 5.77 (DeRemer): We use DeRemer to construct a DFA for $b^* \in RE$. The only item set is $\{(\bullet b)^*, (b^*)\bullet\}$ and the DFA is shown in Figure 12. With alphabet $V = \{b\}$, this is the minimal Complete DFA accepting $\mathcal{L}_{RE}(b^*)$. \square

Remark 5.78: DeRemer and Earley specify that both the closure (function \mathcal{C}) and the optimization (function \mathcal{X}) operations are to be performed simultaneously. Unfortunately, when ϵ is permitted as an RE (as we have done) it is possible that the process never terminates. For example, consider the closure (with optimization) of $\{\bullet(a \cup \epsilon)^*\}$, in the style of DeRemer and Earley. After the first step we have $\{\bullet(a \cup \epsilon)^*, (\bullet(a \cup \epsilon))^*\}$. After an optimization step, and a few more steps we have $\{(\bullet a \cup \epsilon)^*, ((a \cup \epsilon)\bullet)^*\}$, after which we add $(\bullet(a \cup \epsilon))^*$ which we had originally removed. The rewriting process begins again. In this paper, we avoid this problem by defining the closure and optimization steps separately. \square

We can devise an even more effective optimization function than \mathcal{X} .

Definition 5.79 (Function \mathcal{Y}): Given $J \in IS$ corresponding to $E \in RE$ such that $J = \mathcal{C}(J)$, $\mathcal{Y}(J)$ is a subset of J , keeping only the following items:



1. Any item containing a subexpression of the form $\bullet a$ (for some regular expression $a \in V$).
2. The item $E\bullet$ (if present in J).

\square

Property 5.80 (Function $\mathcal{Y} \circ \mathcal{C}$): Composite function $\mathcal{Y} \circ \mathcal{C}$ satisfies Definition 5.62, and is a closure function. \square

Remark 5.81: The function \mathcal{Y} makes the computation of derivatives (of a $J \in IS$ such that $J = \mathcal{C}(J)$) particularly easy, as the items in $\mathcal{Y}(J)$ are precisely those required in the computation of derivatives and for determining if $\epsilon \in \mathcal{L}_{IS}(J)$. \square

Construction 5.82 (Improved item sets): Our optimized construction, called $O\text{constr}$, is as $I\text{constr}$, except that the composite function $\mathcal{Y} \circ \mathcal{C}$ is used wherever \mathcal{C} was used in $I\text{constr}$. This construction does not appear in the literature. \square

Figure 13: The DFA $O\text{constr}((a \cup \epsilon)b^*)$.Figure 14: The DFA's $Brz(ac \cup bc)$ and $O\text{constr}(ac \cup bc)$.

Example 5.83 ($O\text{constr}$): Using $O\text{constr}$, we construct a DFA for $(a \cup \epsilon)b^*$. The derivative item sets are (each item set is given a label for use in the state graph): $\{I_0 = \{(\bullet a \cup \epsilon)b^*, (a \cup \epsilon)(\bullet b)^*\}, I_1 = \{(a \cup \epsilon)(\bullet b)^*, (a \cup \epsilon)b^*\bullet\}, I_2 = \emptyset\}$. The DFA is shown in Figure 13. This is the minimal Complete DFA for the given regular expression. \square

As seen in the above example, function $O\text{constr}$ constructs a smaller DFA than Brz did in Example 5.37. The two constructions seem difficult to compare, as the following example shows:

Example 5.84 (Comparing Brz to $O\text{constr}$): We use Brz and $O\text{constr}$ to construct DFA's for $ac \cup bc$. The derivatives (under extended similarity — see Remark 5.32, each given a label) are: $\{d_0 = ac \cup bc, d_1 = c, d_2 = \epsilon, d_3 = \emptyset\}$. The derivative item sets (using $\mathcal{Y} \circ \mathcal{C}$, each given a label) are: $\{I_0 = \{\bullet ac \cup bc, ac \cup \bullet bc\}, I_1 = \{a \bullet c \cup bc\}, I_2 = \{ac \cup b \bullet c\}, I_3 = \{(ac \cup bc)\bullet\}, I_4 = \emptyset\}$. The results are shown in Figure 14. Construction $O\text{constr}$ is unable to recognize that states I_1 and I_2 are equivalent. (An equivalence relation on IS — much like \sim on ERE's — could be defined in order to identify such equivalent states.) \square

We can make a more practical implementation by concatenating an end-marker $\$$ onto $E \in RE$ (using function $marker_e$ — see Definition 4.46). The second rule defining \mathcal{Y} (Definition 5.79) is then no longer required.

Construction 5.85 (*Oconstr* with end-marker): Using the end-marker, the body of the *Oconstr* construction becomes (assuming that $DIS(E\$, D, \mathcal{Y} \circ \mathcal{C})$):

```

let    $T(J, a) = \{\mathcal{Y} \circ \mathcal{C}(a^{-1}J)\}$ 
       $S = \{\mathcal{Y} \circ \mathcal{C}(\{\bullet E\})\}$ 
       $F = \{J : J \in D \wedge \$^{-1}J \neq \emptyset\}$ 
in     $(D, V, T, \emptyset, S, F)$ 
end

```

□

Remark 5.86: The Aho-Sethi-Ullman construction (Construction 4.50) can be viewed as a heavily encoded variation on the *Oconstr* construction. Each item in an item set of D is of the form $\dots \bullet a \dots$ (for $a \in V$) and corresponds to the basis *RFA*'s that are used in the construction of the *RFA* for E . The subset construction (with start-unreachable state removal) of the Aho-Sethi-Ullman algorithm (Algorithm 4.52) is folded into the algorithm computing the derivative item set (using composite function $\mathcal{Y} \circ \mathcal{C}$) and the definition of a derivative of an item set. Compare the *DFA* produced in Example 4.51 to that produced in Example 5.83; the only difference is the sink state in the latter example. □

6 Conclusions

The conclusions of this paper fall into two groups, depending on the section to which they relate: constructions based upon the structure of regular expressions (Section 4), or constructions based upon the Myhill-Nerode theorem (Section 5).

The conclusions about constructions based on regular expression structure are:

- Finite automaton constructions are frequently said to be “based upon the structure of regular expressions.” The Σ -algebra framework (given in Sections 3 and 4) was useful in formalizing this notion. The Σ -algebras were particularly useful in the following ways:
 - They placed Thompson’s, the left-biased, the right-biased, and the reduced finite automata (*RFA*) constructions in a common framework.
 - They highlighted the fact that the type of object produced by the Thompson’s, the left-biased and the right-biased constructions is actually the isomorphism class of a finite automaton, as opposed to a finite automaton.
- The concept of *duality* (that one construction can be the mirror image of another) played a central part in finding common parts in constructions. Duality was made more obvious through the use of Σ -algebras. The following constructions were found to be related by duality:
 - The Berry-Sethi nondeterministic finite automaton construction (also known in the literature as the McNaughton-Yamada or the Glushkov nondeterministic finite automata construction) and the dual of the Berry-Sethi construction (a variant of which is also known as the Aho-Sethi-Ullman nondeterministic finite automata construction [ASU86, Example 3.22, pg. 140]).
 - The McNaughton-Yamada-Glushkov deterministic finite automaton (*DFA*) construction and the Aho-Sethi-Ullman *DFA* construction¹².
- The use of end-markers (concatenated to either the left or the right of a regular expression) was found to be a simple coding trick, which may be useful in practice. End markers do not play a central role in any of the constructions, although they have previously been portrayed as important.
- The concept of marking a regular expression (each alphabet symbol occurring in the regular expression is given a unique mark, making all of the symbols unique — see Section 4.5) is an encoding trick. Marking is not central to the correctness of any of the constructions, although it is a useful technique in the practical implementation of some of the constructions.
- Marking was found to cause problems in some of the constructions. In particular, intersection, complementation, and language difference cannot be dealt with using marking¹³. In the Σ -algebra framework, intersection, complementation, and language difference can easily be implemented for the Berry-Sethi, McNaughton-Yamada-Glushkov, and Aho-Sethi-Ullman constructions — constructions that are all traditionally defined using marking.
- Two interpretations of marking appear in the literature. In the first one, being “at a mark” (Aho, Sethi, and Ullman use the phrase “at a position” [ASU86]) means to be in the state resulting from making a transition on the alphabet symbol associated with the particular mark¹⁴. The second interpretation equates being “at a mark” with being in the state which

¹²Here we assume that the sink state (if it exists) is removed from a *DFA* produced by the McNaughton-Yamada-Glushkov construction.

¹³Actually, McNaughton and Yamada [MY60] attempted to define intersection and complementation. Their informal descriptions are difficult to understand, and more recent papers use marking and have abandoned trying to define intersection or complementation. See Section 4.4.

¹⁴This is the interpretation taken by Glushkov, McNaughton and Yamada, and Berry and Sethi [Glus61, MY60, BS86].

has an out-transition on the alphabet symbol associated with the particular mark (that is, the marked symbol is valid as the next input symbol)¹⁵. The two interpretations are duals of one another, and arise naturally from the duality of the left-biased and right-biased constructions. For example, the interpretations give rise to the duality between McNaughton, Yamada and Glushkov's DFA and Aho, Sethi, and Ullman's DFA constructions.

- The improvements to the Berry-Sethi construction¹⁶ due to Brüggemann-Klein [B-K93a] and Chang and Paige [Chan92, CP92] have been difficult to compare. This has been largely due to the fact that Chang and Paige's improvements are to the finite automaton construction itself, while Brüggemann-Klein's improvements involve transforming the regular expression. In Section 4.5, we presented an improvement to the construction (not found in the literature) that mirrors Brüggemann-Klein's improvements (not on regular expressions, but on finite automata), and is easy to compare to Chang and Paige's construction.
- Some relationships between the constructions were found that were not made obvious by the Σ -algebra derivations:
 - For restricted regular expressions (where each alphabet symbol occurs at most once — as in marked regular expressions) the Berry-Sethi construction produces a deterministic FA. As a consequence, the Berry-Sethi construction and the McNaughton-Yamada-Glushkov DFA construction produce isomorphic finite automata (with the exception of the sink state present in a McNaughton-Yamada-Glushkov DFA).
 - The Berry-Sethi construction (and therefore the McNaughton-Yamada-Glushkov DFA construction) and the Brzozowski construction (under an appropriate encoding) produce isomorphic finite automata for restricted regular expressions. This result was originally presented by Berry and Sethi [BS86].

The conclusions about the Myhill-Nerode, Brzozowski, and DeRemer constructions (Section 5) are:

- Deriving the second major family of constructions from the Myhill-Nerode theorem proved useful in a number of ways:
 - The use of equivalence classes makes the correctness argument for the Myhill-Nerode construction particularly clear.
 - The unique minimal DFA (for a particular language) can be easily constructed using a particular equivalence class as the parameter to the Myhill-Nerode construction.
 - Derivatives (of a language) are a useful encoding of the equivalence classes of Myhill and Nerode's unique minimal-index equivalence relation R_L .
 - The definition of derivatives provides an efficient method to compute finite sets which encode the infinite sets that are used in the Myhill-Nerode construction.
- The Brzozowski construction can be viewed as an ingenious encoding of the Myhill-Nerode minimal DFA construction.
- Brzozowski's original paper provided a proof (a similar one is given in this paper) that his construction also works when only similarity of regular expressions is recognized. Similarity is defined in his paper using four rules, and is defined in this paper using only three rules. The missing fourth rule (that ϵ is the unit of concatenation) is not required in the definition of similarity for the correctness of our presentation of Brzozowski's construction.

¹⁵This is the interpretation taken by Aho, Sethi, and Ullman [ASU86].

¹⁶Which is therefore an improvement to the McNaughton-Yamada-Glushkov and the Aho-Sethi-Ullman nondeterministic finite automaton constructions.

- We defined the equivalence and the similarity of regular expressions as equivalence relations on regular expressions. We also demonstrated that any such equivalence relation E can be used in Brzozowski's construction, provided that E is a refinement of equivalence and similarity is a refinement of E .
- For restricted regular expressions, Brzozowski's construction (with an encoding), the Berry-Sethi construction, and the McNaughton-Yamada-Glushkov construction produce isomorphic DFA 's.
- The use of dotted regular expressions (also known as *items*, from LR parsing) is a useful, if obscure, encoding of the derivatives of a regular expression. We obtained the following results on the use of dotted regular expressions:
 - Computing the set of all dotted regular expressions (from a given regular expression) can be defined very simply. The derivatives of dotted regular expressions, and the construction of a DFA can be defined simply. This construction does not appear in the literature.
 - The straightforward definition of dotted regular expressions is unable to deal with intersection and complementation. This is for the same reason that marking constructions are unable to deal with intersection and complementation.
 - DeRemer specified a DFA construction that appears to be very easy to implement. It is an optimization over the straightforward dotted regular expression construction, and the constructed DFA is always smaller.
 - The original specification of item closure, due to DeRemer and Earley, is incomplete. They attempted to define closure and optimization as a single step. This can lead to non-termination, as we have demonstrated. The problem can be easily solved by defining closure and optimization steps separately.
 - We show that additional optimizations, added to DeRemer's construction, can reduce the size of the produced DFA . This construction is not given in the literature. Furthermore, the optimizations are arguably easier to understand than those of DeRemer, and likely easier to implement.
 - It is possible to show that this improved construction is related to the Aho-Sethi-Ullman DFA construction.

定义：令A和B为非空集合。从A到B的函数f是对元素的一种指派，对A的每个元素恰好指派B的一个元素。如果B中元素b是唯一由函数f指派给A中元素a的，则我们就写成 $f(a)=b$ 。如果f是从A到B的函数，就写成 $f: A \rightarrow B$ 。函数有时也称为映射(mapping)或者变换(transformation)。

定义：如果f是从A到B的函数，我们说A是的定义域(domain)，而B是f的陪域(codomain)。如果 $f(a)=b$ ，b是a的像(image)，而a是b的原像(preimage)。f的值域(range)或像是A中元素的所有像的集合。如果f是从A到B的函数，我们说f把A映射(map)到B。

定义：一个从集合A到集合B的部分函数(partial function)f是给A的一个子集(称为f的定义域(domain of function))中的每个元素a指派唯一的一个B中的元素b。集合A和B分别称为f的域和陪域。我们说f对于A中但不在f的定义域中的元素无定义(undefined)。当f的定义域等于A时，就说f是权函数(total function)。

A Some basic definitions

Convention A.1 (Powerset): For any set A we use $\mathcal{P}(A)$ to denote the set of all subsets of A . $\mathcal{P}(A)$ is called the *powerset* of A ; it is sometimes written 2^A . \square

Convention A.2 (Sets of functions): For sets A and B , $A \rightarrow B$ denotes the set of **all total** functions from A to B , while $A \not\rightarrow B$ denotes the set of all **partial functions** from A to B . \square

Remark A.3: For sets A, B and relation $C \subseteq A \times B$ we can interpret C as a function $C \in A \rightarrow \mathcal{P}(B)$. \square

Convention A.4 (Tuple projection): For an n -tuple $t = (x_1, x_2, \dots, x_n)$ we use the notation $\pi_i(t)$ ($1 \leq i \leq n$) to denote tuple element x_i ; we use the notation $\bar{\pi}_i(t)$ ($1 \leq i \leq n$) to denote the $(n - 1)$ -tuple $(x_1, \dots, x_{i-1}, x_{i+1}, \dots, x_n)$. Both π and $\bar{\pi}$ extend naturally to sets of tuples. \square

Convention A.5 (Tuple arguments to functions): For functions (or **predicates**) taking a single tuple as an argument, we usually drop one set of parentheses in a function application. \square



Convention A.6 (Relation composition): Given sets A, B, C (not necessarily different) and two relations, $E \subseteq A \times B$ and $F \subseteq B \times C$, we define relation composition (infix operator \circ) as:

$$E \circ F = \{(a, c) : (\exists b : b \in B : (a, b) \in E \wedge (b, c) \in F)\}$$

\square

infix: 中缀, 中间插入
prefix: 前缀
postfix: 后缀

Convention A.7 (Equivalence classes of an equivalence relation): For any equivalence relation E on set A we denote the set of equivalence classes of E by $[A]_E$; that is

$$[A]_E = \{[a]_E : a \in A\}$$

定义在集合A上的关系叫做等价关系，如果它是自反的、对称的和传递的。
设E是定义在集合A上的等价关系。与A中的一个元素a有关系的所有元素的集合
叫做a的等价类

Set $[A]_E$ is also called the **partition of A induced by E**. \square

Definition A.8 (Index of an equivalence class): For equivalence relation E on set A , define $\#E = |[A]_E|$. $\#E$ is called the *index* of E . \square #E称为E的指数，就是等价类的个数。

Definition A.9 (Alphabet): An *alphabet* is a non-empty set of finite size. \square

Definition A.10 (Refinement of an equivalence relation): For equivalence relations E and E' (on set A), E is a *refinement* of E' if and only if $E \subseteq E'$. \square E是E'的加细，即E的划分更细。

Definition A.11 (Refinement (\sqsubseteq) relation on partitions): For equivalence relations E and E' (on set A), $[A]_E$ is said to be a refinement of $[A]_{E'}$ (written $[A]_E \sqsubseteq [A]_{E'}$) if and only if $E \subseteq E'$. An equivalent statement is that $[A]_E \sqsubseteq [A]_{E'}$ if and only if every equivalence class (of A) under E is entirely contained in some equivalence class (of A) under E' . \square

Property A.12 (Equivalence relations): Given two equivalence relations E, F , we have the following property:

$$(E \subseteq F) \wedge (\#E = \#F) \Rightarrow (E = F)$$

\square

Definition A.13 (Regular languages): $\mathcal{L}_{\text{reg}V}$ denotes the set of all regular languages over alphabet V . That is, $\mathcal{L}_{\text{reg}V} \subseteq \mathcal{P}(V^*)$ is the smallest set containing V that is **closed** under \cup (language union), \cdot (a dot, language concatenation), and $*$ (Kleene closure). The subscript V is dropped when no ambiguity arises. \square

Definition A.14 (Operator ? on languages): We define $?$ as a postfix (superscript) operator on languages as $L? = L \cup \{e\}$. \square

$$V^* = V^0 \cup V^1 \cup V^2 \cup \dots \quad V^0 = \{ \text{epsilon} \}$$

$$L^* = L^0 \cup L^1 \cup L^2 \cup \dots = L \quad L^0 = \{ \text{epsilon} \}$$

predicate
谓词，断言
语句 $P(x)$ 是命题
函数 P 在 x 的值，一旦给 x 赋一个值，语句 $P(x)$ 就成为命题并具有真值。如 $P(x)$ 表示语句“ $x > 3$ ”。 $P(4)$ 为真， $P(2)$ 为假。 P 称为谓词， $P(x)$ 谓词函数。

(1) 如果 L 是一个语言, a 是一个符号, 则 L/a (称作 L 和 a 的商) 是所有满足如下条件的串 w 的集合: wa 属于 L 。例如, 如果 $L = \{a, aab, baa\}$, 则 $L/a = \{\epsilon, ba\}$, 证明: 如果 L 是正则的, 那么 L/a 也是。提示: 从 L 的 DFA 出发, 考虑接受状态的集合。

(2) 如果 L 是一个语言, a 是一个符号, 则 $a \setminus L$ 是所有满足如下条件的串 w 的集合: aw 属于 L 。例如, 如果 $L = \{a, aab, baa\}$, 则 $a \setminus L = \{\epsilon, ab\}$, 证明: 如果 L 是正则的, 那么 $a \setminus L$ 也是。提示: 记得正则语言在反转运算下是封闭的, 又由(1)知, 正则语言的商运算下是封闭的。

Definition A.15 (Left derivatives): Given language $A \subseteq V^*$ and $w \in V^*$ we define the *left derivative* of A with respect to w as:



$$w^{-1}A = \{x \in V^* : wx \in A\} \quad \text{A关于w的左导数, 就是A中: \{w的后缀组成的字符串集合\}。}$$

Sometimes derivatives are written as $D_w A$ or as $\frac{dA}{dw}$. Right derivatives are analogously defined. Derivatives can also be extended to $B^{-1}A$ where B is also a language. \square

Property A.16 (Left derivatives): The following two properties follow from Definition A.15 (assuming L is a language):

- $w \in L \equiv \epsilon \in w^{-1}L$, and
- $(wa)^{-1}L = a^{-1}(w^{-1}L)$.

\square



Property A.17 (Derivatives of regular languages): Assuming $a \in V$ and $L, L_0, L_1 \in \mathcal{L}_{\text{reg}}$, derivatives have the following properties (given with respect to the structure of regular languages):

$$\begin{aligned} a^{-1}\emptyset &= \emptyset \\ a^{-1}\{\epsilon\} &= \emptyset \\ a^{-1}\{b\} &= \text{if } (a = b) \text{ then } \{\epsilon\} \text{ else } \emptyset \text{ fi} \\ a^{-1}(L_0 L_1) &= (a^{-1}L_0)L_1 \cup \text{if } (\epsilon \in L_0) \text{ then } a^{-1}L_1 \text{ else } \emptyset \text{ fi} \\ a^{-1}(L_0 \cup L_1) &= (a^{-1}L_0) \cup (a^{-1}L_1) \\ a^{-1}(L^*) &= (a^{-1}L)L^* \\ a^{-1}(L^+) &= (a^{-1}L)L^* \\ a^{-1}(L^?) &= a^{-1}L \\ a^{-1}(L_0 \cap L_1) &= (a^{-1}L_0) \cap (a^{-1}L_1) \\ a^{-1}(\neg L) &= \neg(a^{-1}L) \end{aligned}$$

The definition related to Kleene closure is shown as follows: [Kleene闭包](#)

$$\begin{aligned} &a^{-1}(L^*) \\ &= \{\text{Definition of } *\} \\ &= a^{-1}((L \setminus \{\epsilon\})L^* \cup \{\epsilon\}) \\ &= \{\text{Definition of } a^{-1}(L_0 \cup L_1)\} \\ &= a^{-1}((L \setminus \{\epsilon\})L^*) \cup a^{-1}\{\epsilon\} \\ &= \{\text{Definition of derivative of concatenation and } \{\epsilon\}\} \\ &\quad (a^{-1}(L \setminus \{\epsilon\}))L^* \\ &= \{\text{Definition of derivative of } \{\epsilon\}\} \\ &\quad (a^{-1}L)L^* \end{aligned}$$

The definition related to complementation \neg is as follows:

$$\begin{aligned} &a^{-1}(\neg L) \\ &= \{\text{Definition of derivative}\} \\ &\quad \{x : ax \in \neg L\} \\ &= \{\text{Definition of } \neg \text{ operator}\} \\ &\quad \neg\{x : ax \in L\} \\ &= \{\text{Definition of } a^{-1}L\} \\ &\quad \neg(a^{-1}L) \end{aligned}$$

Example 1 $A = \{a, aab, baa\}, a^{-1}A = D_a A = \frac{dA}{da} = \{\epsilon, ab, \emptyset\} = \{\epsilon, ab\}$

Example 2 $L = \{ba, baa, baab, ca\}, w = \{ba\}$,

$$w^{-1}L = \{\epsilon, a, ab, \emptyset\} = \{\epsilon, a, ab\}$$

$$(wa)^{-1}L = (baa)^{-1}L = \{\emptyset, \epsilon, b, \emptyset\} = \{\epsilon, b\}$$

$$a^{-1}(w^{-1}L) = a^{-1}\{\epsilon, a, ab\} = \{\emptyset, \epsilon, b\} = \{\epsilon, b\}$$

$$w \in L \equiv \epsilon \in w^{-1}L, \text{ and } (wa)^{-1}L = a^{-1}(w^{-1}L)$$

□

Definition A.18 (Preserving a predicate): A (partial) function $f \in B^n \rightarrow B$ (for fixed $n \geq 0$) is said to *preserve* predicate (or property) P (on B) if and only if

$$(\forall B' : B' \in B^n \cap (\text{domain}(f)) \wedge (\forall k : 1 \leq k \leq n : P(\pi_k(B')))) : P(f(B'))$$

project(B')删除一些关系，谓词 P 关于 B 还成立，因为 f 定义的部分函数。

The set $\text{domain}(f)$ refers to those elements of B^n on which f is defined. □

Intuitively, a function f preserves a property P if, when every argument of f satisfies P , the result of f applied to the arguments also satisfies P .

Definition A.19 (Reversal operator): A reversal operator R (usually written postfix and superscript) for a set A is a function $R \in A \rightarrow A$ such that $R \circ R$ (equivalently R^2) is the identity function on A . We sometimes write the reversal operator as a standard (prefix notation) function.

$R \circ R$ is the identity $\Rightarrow R \circ R(A) = A$

Definition A.20 (Tuple and relation reversal): For an n -tuple (x_1, x_2, \dots, x_n) define reversal as (postfix and superscript) function R :

$$(x_1, x_2, \dots, x_n)^R = (x_n, \dots, x_2, x_1)$$

Given a set A of tuples, we define $A^R = \{x^R : x \in A\}$. □

Definition A.21 (Dual of a function): We assume two sets A and B whose reversal operators are R and R' respectively. Two functions, $f \in A \rightarrow B$ and $f_d \in A \rightarrow B$ are one another's *dual* if and only if

$$f(a) = (f_d(a^R))^{R'} \quad \text{两个函数互为对偶，就是对称的(A.22)}.$$

In some cases we relax the equality to *isomorphism* (when isomorphism is defined on B). □


Definition A.22 (Symmetrical function): A *symmetrical* function is one that is its own dual.


□ 对称函数互为对偶 $f(a) = (f(a^R))^R$

Proposition A.23 (Symmetrical functions): The composition of two symmetrical functions is again symmetrical. □

$$f_d \circ R(a) = R' \circ f(a) \Rightarrow f_d(R(a)) = R'(f(a)) \Rightarrow$$

$$f_d(a^R) = (f(a))^{R'} \Rightarrow f(a) = (f_d(a^R))^{R'}$$



$$\begin{aligned}
C_{\cup,Th}([M_0]_{\cong}, [M_1]_{\cong}) &= \text{let } (Q_0, V, T_0, E_0, S_0, F_0) = M_0 \\
&\quad (Q_1, V, T_1, E_1, S_1, F_1) = M_1 \\
&\quad q_0, q_1 \text{ be new states} \\
&\text{in} \\
&\quad \text{let } Q' = Q_0 \cup Q_1 \cup \{q_0, q_1\} \\
&\quad E' = E_0 \cup E_1 \cup (\{q_0\} \times (S_0 \cup S_1)) \\
&\quad \cup ((F_0 \cup F_1) \times \{q_1\}) \\
&\text{in} \\
&\quad [(Q', V, T_0 \cup T_1, E', \{q_0\}, \{q_1\})]_{\cong} \\
&\text{end} \\
&\text{end}
\end{aligned}$$


B Proofs of some Σ -algebra operators

In this section, we sketch proofs of the correctness of the operators of Thompson's Σ -algebra (Definition 4.1), the left-biased Σ -algebra operators (Definition 4.20), the Chang-Paige RFA' operators (Construction 4.77), and the RFA'' operators (Construction 4.79).

Theorem B.1 (Correctness of Thompson's Σ -algebra of FA 's): Recall the operator definitions of Definition 4.1. We only present a correctness proof for the operator $C_{\cup,Th}$. In the following derivation we assume the context of the innermost let clause of the operator definition.


$$\begin{aligned}
&\mathcal{L}_{FA}(C_{\cup,Th}([M_0]_{\cong}, [M_1]_{\cong})) \\
&= \{\text{Definition of } \mathcal{L}_{FA}\} \quad \mathcal{L}_{FA} \in FA \rightarrow \mathcal{P}(V^*) \quad \mathcal{L}_{FA}(M) = (\cup s, f : s \in S \wedge f \in F : T^*(s, f)) \quad \text{p9 Definition 2.12 (Language of an FA)} \\
&\quad (T_0 \cup T_1)^*(q_0, q_1) \\
&= \{\text{Definition of } E'\} \\
&\quad (\cup s, f : s \in S_0 \wedge f \in F_0 : T_0^*(s, f)) \cup (\cup s, f : s \in S_1 \wedge f \in F_1 : T_1^*(s, f)) \\
&= \{\text{Definitions of } \mathcal{L}_{FA}([M_0]_{\cong}), \mathcal{L}_{FA}([M_1]_{\cong})\} \quad \text{p10. Definition 2.14 (Extension of L)isomorphic FA's accept the same language.} \\
&\quad \mathcal{L}_{FA}([M_0]_{\cong}) \cup \mathcal{L}_{FA}([M_1]_{\cong})
\end{aligned}$$

□

Theorem B.2 (Correctness of the $LBFA$ operators): Recall the operator definitions of Definition 4.20. We present a correctness proof of the operator $C_{\cup,LBFA}$. In the following derivation we assume the context of the innermost let clause of the operator definition.

$$\begin{aligned}
&\mathcal{L}_{FA}(C_{\cup,LBFA}([M_0]_{\cong}, [M_1]_{\cong})) \\
&= \{\text{Definitions of } \mathcal{L}_{FA} \text{ and } F'\} \\
&\quad (\cup f : f \in F_0 \cap Q' : T'^*(q_0, f)) \cup (\cup f : f \in F_1 \cap Q' : T'^*(q_0, f)) \\
&\quad \cup \text{if } (N) \text{ then } T'^*(q_0, q_0) \text{ else } \emptyset \text{ fi} \\
&= \{\text{Definitions of } \mathcal{L}_{FA}([M_0]_{\cong}), \mathcal{L}_{FA}([M_1]_{\cong}), N, T'\} \\
&\quad \mathcal{L}_{FA}([M_0]_{\cong}) \cup \mathcal{L}_{FA}([M_1]_{\cong}) \cup \text{if } (\epsilon \in (\mathcal{L}_{FA}(M_0) \cup \mathcal{L}_{FA}(M_1))) \text{ then } \{\epsilon\} \text{ else } \emptyset \text{ fi} \\
&= \{\text{Definition of } \mathcal{L}_{FA}([M_0]_{\cong}) \cup \mathcal{L}_{FA}([M_1]_{\cong})\} \\
&\quad \mathcal{L}_{FA}([M_0]_{\cong}) \cup \mathcal{L}_{FA}([M_1]_{\cong})
\end{aligned}$$

$$\begin{aligned}
C_{\cup,LBFA}([M_0]_{\cong}, [M_1]_{\cong}) &= \text{let } (Q_0, V, T_0, \emptyset, \{s_0\}, F_0) \cong M_0 \\
&\quad (Q_1, V, T_1, \emptyset, \{s_1\}, F_1) \cong M_1 \\
&\quad N = \epsilon \in (\mathcal{L}_{FA}(M_0) \cup \mathcal{L}_{FA}(M_1)) \\
&\quad q_0 \text{ be a new state} \\
&\quad \text{let } Q' = Q_0 \setminus \{s_0\} \cup Q_1 \setminus \{s_1\} \cup \{q_0\} \\
&\quad T' = T_0 \cup T_1 \cup (\{q_0\} \times (T_0(s_0) \cup T_1(s_1))) \\
&\quad F' = F_0 \cup F_1 \cup \text{if } (N) \text{ then } \{q_0\} \text{ else } \emptyset \text{ fi} \\
&\quad \text{in} \\
&\quad [(Q', V, T' \cap (Q' \times V \times Q'), \\
&\quad \emptyset, \{q_0\}, F' \cap Q')]_{\cong} \\
&\quad \text{end}
\end{aligned}$$



Theorem B.3 (Correctness of the Chang-Paige RFA' operators): Recall Definition 4.76 and Construction 4.77. We only present the derivation of the eighth component (usually called W) for operators $C_{\cdot,RFA'}$ and $C_{\cup,RFA'}$ (the others are easy to prove). We assume the context of the innermost let clause for both operators.

$$\begin{aligned}
C_{\cdot,RFA'}: &\quad last' \times first' \setminus (follow_0 \uplus follow_1 \uplus last_0 \times first_1) \\
&= \{\text{Definitions of } first' \text{ and } last'\} \\
&\quad (last_1 \uplus \text{if } (null_1) \text{ then } last_0 \text{ else } \emptyset \text{ fi}) \times (first_0 \uplus \text{if } (null_0) \text{ then } first_1 \text{ else } \emptyset \text{ fi}) \\
&\quad \setminus (follow_0 \uplus follow_1 \uplus last_0 \times first_1) \\
&= \{\text{Rewriting}\} \\
&\quad (last_1 \times first_0 \uplus \text{if } (null_0) \text{ then } last_1 \times first_1 \text{ else } \emptyset \text{ fi} \\
&\quad \uplus \text{if } (null_1) \text{ then } last_0 \times first_0 \text{ else } \emptyset \text{ fi} \\
&\quad \uplus \text{if } (null_0 \wedge null_1) \text{ then } last_0 \times first_1 \text{ else } \emptyset \text{ fi} \\
&\quad \setminus (follow_0 \uplus follow_1 \uplus last_0 \times first_1)) \\
&= \{\text{Assumption that } Q_0 \cap Q_1 = \emptyset\} \\
&\quad last_1 \times first_0 \uplus \text{if } (null_0) \text{ then } last_1 \times first_1 \setminus follow_1 \text{ else } \emptyset \text{ fi}
\end{aligned}$$

$$\begin{aligned}
& \sqcup \text{if } (\text{null}_1) \text{ then } \text{last}_0 \times \text{first}_0 \setminus \text{follow}_0 \text{ else } \emptyset \text{ fi} \\
= & \quad \{ \text{Definitions of } W_0 \text{ and } W_1 \} \\
& \text{last}_1 \times \text{first}_0 \sqcup \text{if } (\text{null}_0) \text{ then } W_1 \text{ else } \emptyset \text{ fi} \sqcup \text{if } (\text{null}_1) \text{ then } W_0 \text{ else } \emptyset \text{ fi} \\
= & \quad \{ \text{Definitions of } W' \text{ and } W'' \} \\
& \text{last}_1 \times \text{first}_0 \sqcup W' \sqcup W'' \\
C_{\cup,RFA'}: & \quad (\text{last}_0 \sqcup \text{last}_1) \times (\text{first}_0 \sqcup \text{first}_1) \setminus (\text{follow}_0 \sqcup \text{follow}_1) \\
= & \quad \{ \text{Rewriting} \} \\
& (\text{last}_0 \times \text{first}_0 \sqcup \text{last}_0 \times \text{first}_1 \sqcup \text{last}_1 \times \text{first}_0 \sqcup \text{last}_1 \times \text{first}_1) \setminus (\text{follow}_0 \sqcup \text{follow}_1) \\
= & \quad \{ \text{Assumption that } Q_0 \cap Q_1 = \emptyset \} \\
& (\text{last}_0 \times \text{first}_0 \setminus \text{follow}_0) \sqcup \text{last}_0 \times \text{first}_1 \sqcup \text{last}_1 \times \text{first}_0 \sqcup (\text{last}_1 \times \text{first}_1 \setminus \text{follow}_1) \\
= & \quad \{ \text{Definitions of } W_0 \text{ and } W_1 \} \\
& \text{last}_0 \times \text{first}_1 \sqcup \text{last}_1 \times \text{first}_0 \sqcup W_0 \sqcup W_1
\end{aligned}$$

□

Theorem B.4 (Correctness of the RFA'' operators): Recall Definition 4.78 and Construction 4.79. We only present the derivation of the eighth component (usually called W) for operators $C_{\cdot,RFA''}$ and $C_{\cup,RFA''}$ (the others are easy to prove). We assume the context of the innermost **let** clause for both operators.

$$\begin{aligned}
C_{\cdot,RFA''}: & \quad (\text{follow}_0 \sqcup \text{follow}_1 \sqcup (\text{last}_0 \times \text{first}_1)) \setminus (\text{last}' \times \text{first}') \\
= & \quad \{ \text{Definitions of } \text{first}' \text{ and } \text{last}' \} \\
& (\text{follow}_0 \sqcup \text{follow}_1 \sqcup (\text{last}_0 \times \text{first}_1)) \setminus ((\text{last}_1 \sqcup \text{if } (\text{null}_1) \text{ then } \text{last}_0 \text{ else } \emptyset \text{ fi} \\
& \quad \times (\text{first}_0 \sqcup \text{if } (\text{null}_0) \text{ then } \text{first}_1 \text{ else } \emptyset \text{ fi})) \\
= & \quad \{ \text{Rewriting} \} \\
& (\text{follow}_0 \sqcup \text{follow}_1 \sqcup (\text{last}_0 \times \text{first}_1)) \setminus (\text{last}_1 \times \text{first}_0 \\
& \quad \sqcup \text{if } (\text{null}_0) \text{ then } \text{last}_1 \times \text{first}_1 \text{ else } \emptyset \text{ fi} \\
& \quad \sqcup \text{if } (\text{null}_1) \text{ then } \text{last}_0 \times \text{first}_0 \text{ else } \emptyset \text{ fi} \\
& \quad \sqcup \text{if } (\text{null}_0 \wedge \text{null}_1) \text{ then } \text{last}_0 \times \text{first}_1 \text{ else } \emptyset \text{ fi}) \\
= & \quad \{ \text{Assumption that } Q_0 \cap Q_1 = \emptyset \} \\
& \text{if } (\text{null}_0) \text{ then } \text{follow}_1 \setminus \text{last}_1 \times \text{first}_1 \text{ else } \text{follow}_1 \text{ fi} \\
& \quad \sqcup \text{if } (\text{null}_1) \text{ then } \text{follow}_0 \setminus \text{last}_0 \times \text{first}_0 \text{ else } \text{follow}_0 \text{ fi} \\
& \quad \sqcup \text{if } (\text{null}_0 \wedge \text{null}_1) \text{ then } \text{last}_0 \times \text{first}_1 \setminus \text{last}_0 \times \text{first}_1 \text{ else } \text{last}_0 \times \text{first}_1 \text{ fi} \\
= & \quad \{ \text{Definitions of } W_0 \text{ and } W_1; \text{ rewriting} \} \\
& \text{if } (\text{null}_0) \text{ then } W_1 \text{ else } \text{follow}_1 \text{ fi} \sqcup \text{if } (\text{null}_1) \text{ then } W_0 \text{ else } \text{follow}_0 \text{ fi} \\
& \quad \sqcup \text{if } (\text{null}_0 \wedge \text{null}_1) \text{ then } \emptyset \text{ else } \text{last}_0 \times \text{first}_1 \text{ fi} \\
= & \quad \{ \text{Definitions of } W', W'', \text{ and } W''' \} \\
& W' \sqcup W'' \sqcup W'''
\\
C_{\cup,RFA''}: & \quad (\text{follow}_0 \sqcup \text{follow}_1) \setminus ((\text{last}_0 \sqcup \text{last}_1) \times (\text{first}_0 \sqcup \text{first}_1)) \\
= & \quad \{ \text{Rewriting} \} \\
& (\text{follow}_0 \sqcup \text{follow}_1) \setminus (\text{last}_0 \times \text{first}_0 \sqcup \text{last}_0 \times \text{first}_1 \sqcup \text{last}_1 \times \text{first}_0 \sqcup \text{last}_1 \times \text{first}_1) \\
= & \quad \{ \text{Assumption that } Q_0 \cap Q_1 = \emptyset \} \\
& \text{follow}_0 \setminus (\text{last}_0 \times \text{first}_0) \sqcup \text{follow}_1 \setminus (\text{last}_1 \times \text{first}_1) \\
= & \quad \{ \text{Definitions of } W_0 \text{ and } W_1 \} \\
& W_0 \sqcup W_1
\end{aligned}$$

□

References

- [ASU86] AHO, A.V., R. SETHI, AND J.D. ULLMAN. *Compilers: Principles, Techniques, and Tools*, Addison-Wesley Publishing Co., Reading, M.A., 1988.
- [AU92] AHO, A.V. AND J.D. ULLMAN. *Foundations of Computer Science*, Computer Science Press, New York, N.Y. 1992.
- [BL77] BACKHOUSE, R.C. AND R.K. LUTZ. “Factor graphs, failure functions and bi-trees,” in *Fourth Colloquium on Automata, Languages and Programming*, (G. Goos and J. Hartmanis, eds.), pp. 61–75, Lecture Notes in Computer Science 52, Springer-Verlag, Berlin, 1977.
- [BS86] BERRY, G. AND R. SETHI. “From regular expressions to deterministic automata,” *Theoretical Computer Science*, 48: 117–126, 1986.
- [B-K93a] BRÜGGERMANN-KLEIN, A. “Regular expressions into finite automata,” to appear in *Theoretical Computer Science*.
- [B-K93b] BRÜGGERMANN-KLEIN, A. *Private communication*, July 1993.
- [Brzo64] BRZOZOWSKI, J.A. “Derivatives of regular expressions,” *J. ACM* 11(4): 481–494, 1964.
- [Cham93] CHAMPARNAUD, J.M. “From a regular expression to an automaton,” Technical report, IBP, LITP, Université Paris 7, Paris, France, Working document 23 September 1993.
- [Chan92] CHANG, C.-H. “From regular expressions to DFAs using compressed NFAs,” PhD thesis, Computer Science Department, Courant Institute of Mathematical Sciences, New York University, N.Y., Oct. 1992.
- [CP92] CHANG, C.-H. AND R. PAIGE. “From regular expressions to DFAs using compressed NFAs,” Computer Science Department, Courant Institute of Mathematical Sciences, New York University, N.Y., 1992.
- [DeRe74] DEREMER, F.L. “Lexical analysis,” in *Compiler Construction: an Advanced Course*, (F.L. Bauer and J. Eickel, eds.), pp. 109–120, Lecture Notes in Computer Science 21, Springer-Verlag, Berlin, 1974.
- [Dijk76] DIJKSTRA, E.W. *A discipline of programming*, Prentice-Hall Inc., N.J., 1976.
- [Earl70] EARLEY, J. “An efficient context-free parsing algorithm,” *C. ACM* 13(2): 94–102, Feb. 1970.
- [EM85] EHRIG, E. AND B. MAHR. *Fundamentals of Algebraic Specification 1: Equations and Initial Semantics*, Springer, Berlin, 1985.
- [tEvG93] TEN EIKEELDER, H.M.M. AND H.P.J. VAN GELDROP. “On the correctness of some algorithms to generate finite automata for regular expressions,” Computing Science Note 93/32, Eindhoven University of Technology, The Netherlands, 1993.
- [Glus61] GLUSHKOV, V.M. “The abstract theory of automata,” *Russian Mathematical Surveys* 16: 1–53, 1961.
- [GJ90] GRUNE, D. AND C.J.H. JACOBS. *Parsing Techniques: A Practical Guide*, Ellis Horwood Ltd., West Sussex, England, 1990.
- [HU79] HOPCROFT, J.E. AND J.D. ULLMAN. *Introduction to Automata Theory, Languages, and Computation*, Addison-Wesley Publishing Co., Reading, M.A., 1979.

- [Knut65] KNUTH, D.E. "On the translation of languages from left to right," *Inform. Control* 8: 607–639, 1965.
- [MY60] MCNAUGHTON, R. AND H. YAMADA. "Regular expressions and state graphs for automata," *IEEE Trans. on Electronic Computers* 9(1): 39–47, 1960.
- [Myhi57] MYHILL, J. "Finite automata and the representation of events," WADD TR-57-624, pp. 112–137, Wright Patterson AFB, Ohio, 1957.
- [Nero58] NERODE, A. "Linear automaton transformations," *Proc. AMS* 9: 541–544, 1958.
- [RS59] RABIN, M.O AND D. SCOTT. "Finite automata and their decision problems," *IBM J. Res.* 3(2): 115–125, 1959.
- [SS-S88] SIPPU, S. AND E. SOISALON-SOININEN. *Parsing Theory: Languages and Parsing*, Vol. 1, Springer-Verlag, Berlin, 1988.
- [Thom68] THOMPSON, K. "Regular expression search algorithms," *C. ACM* 11(6): 419–422, 1968.
- [Wats93] WATSON, B.W. "A taxonomy of finite automata minimization algorithms," *Computing Science Note* 93/44, Eindhoven University of Technology, The Netherlands, 1993.
- [Wood87] WOOD, D. *Theory of Computation*, Harper & Row, Publishers, New York, N.Y., 1987.

Index

- \circ , *see* composition
- \doteq , *see* regular expressions, equivalence of
- \rightarrow , *see* function, total
- $\not\rightarrow$, *see* function, partial
- \cong , *see* isomorphism
- π , *see* tuple, projection
- $\bar{\pi}$, *see* tuple, projection
- \sim , *see* regular expressions, similarity of
- Aho, Sethi, and Ullman's construction, *see* finite automata, construction, Aho, Sethi, and Ullman's
- algebras, *see* Σ -algebras
- algorithms
 - subset construction, 12
- alphabet, 6, 15, 16
- ASU, *see* finite automata, construction, Aho, Sethi, and Ullman's
- automata, *see* finite automata
- Berry and Sethi's construction, *see* finite automata, construction, Berry and Sethi's
- bias
 - left-to-right, 6
- Brüggemann-Klein's construction, *see* finite automata, construction, Brüggemann-Klein
- Brz, *see* finite automata, construction, Brzozowski
- Brzenc, *see* finite automata, construction, Brzozowski (encoded)
- Brzozowski's construction, *see* finite automata, construction, Brzozowski
- BS, *see* finite automata, construction, Berry and Sethi's
- BSenc, *see* finite automata, construction, Berry and Sethi's (encoded)
- \mathcal{C} , *see* item set, closure of carrier set, 14, 16
- Chang and Paige's construction, *see* finite automata, construction, Chang-Paige closure
 - Kleene, 16
 - of an item set, 67–72
- Complete, *see* finite automata, complete
- complete, *see* finite automata, transformations on, complete
- composition, 7, 11–13, 27, 33, 35–45, 48, 67, 69–72, 76, 78
- constants, 14, 17
- construction, *see* finite automata, construction
- Aho-Sethi-Ullman, 13
- powerset, *see* finite automata, subset construction
- subset, *see* finite automata, subset construction
- convert, 36, 37, 41–44
- \mathcal{D} , *see* item set, relation on
- decode, 33, 35–41, 45, 48
- DeRemer, *see* finite automata, construction, DeRemer
- DeRemer's construction, *see* finite automata, construction, DeRemer
- deriv, 56, 57
- derivative
 - left, 36, 56–65, 67, 68, 72, 77
- derivative item set, 68, 72
- deriv_{ERE}, 59–61
- Det, *see* finite automata, deterministic
- deterministic finite automata, *see* finite automata, deterministic
- Det', *see* finite automata, deterministic, weak
- DFA, *see* finite automata, deterministic
- Dijkstra, E.W., 12
- DIS, *see* derivative item set
- dots, 66–68
- dotted regular expressions, 66, 67
- DRE, *see* dotted regular expressions
- dual, 11
- \mathcal{E} , *see* item set, closure of edge
 - labeled directed, 6
- Ehrig, E., 14
- encderiv, 56, 57
- enc_E, 65
- encode, 33, 45
- ϵ -free, *see* finite automata, ϵ -free
- ϵ -lookahead finite automata, 23–27
- ϵ -transition
 - relation, 6
 - removal of, *see* finite automata (transf. on), ϵ removal
- equivalence
 - of regular expressions, *see* regular expressions, equivalence of
- equivalence relation, *see* relation, equivalence
- ERE, *see* regular expressions, extended
- expression tree height, 15

- extended regular expressions, *see* regular expressions, extended language of, 44, 58–61, 64
- FA*, *see* finite automata
- false*, 16, 17, 32, 34, 50, 51
- final states, *see* states, final
- final-reachable states, *see* states, final-reachable
- finite automata, 6–14, 16, 18, 21–23, 25, 27, 28, 31, 32, 35–37, 39–44, 48, 49, 55, 57, 74, 79
- complete, 8–13, 37–39, 43, 53–57, 61, 68, 70, 71
- construction
- Aho, Sethi, and Ullman’s, 43
 - Berry and Sethi’s, 35, 37, 48
 - Berry and Sethi’s (encoded), 48, 65
 - Brüggemann-Klein, 52
 - Brzozowski, 61, 62, 65, 71
 - Brzozowski (encoded), 65
 - Chang-Paige, 50
 - DeRemer, 70
 - guarded commands, 26, 27
 - item set, 68–70
 - lookahead automata, 24–26
 - McNaughton, Yamada, and Glushkov’s, 37, 38, 48, 65
 - Myhill and Nerode’s, 55–57, 65, 66
 - Myhill and Nerode’s minimal, 57, 58, 61, 65
 - optimized item set, 70–72
 - Thompson, 18, 21–23
 - Thompson top-down, 22, 23
- definition of, 6
- deterministic, 9–13, 25, 35, 37, 38, 43, 48, 53–58, 60–63, 65, 66, 68–75
- definition of, 9
 - minimality of, 10–12, 56
 - weak, 9, 55
- ϵ -free, 3, 8–12, 27, 28, 31, 32, 35, 37, 40
- isomorphism of, 7, 8, 11
- language of, 7, 8, 10–12, 18, 23, 29–31, 36, 40–42, 45, 49, 53, 55–57, 61, 68, 79
- extension, 8
- property of, 8
- left-biased, 28–33, 35, 37, 44–46, 79
- powerset construction, *see* finite automata, subset construction
- properties of, 7–10
- reduced, *see* reduced finite automata
- reverse of, 9, 10
- extension of, 11
- size of, 7
- subset construction, 12, 13, 37–39
- implementation of, 12
 - optimized, 12, 13, 43, 44
- transformations on, 10–13
- complete, 11, 48
 - ϵ -transition removal, 11, 27
 - final-unreach. removal, 11–13, 37–39, 43, 44
 - start-unreach. removal, 11
 - useless state removal, 11
- useful, 9–11
- final, 9
 - start, 9–11
- First*, 24–26, 47–49, 65
- first*, 32–34, 36, 38, 39, 41, 42, 44, 45, 47, 49–52, 79, 80
- Follow*, 47–49, 65
- follow*, 32–34, 36, 38, 39, 41, 42, 44, 45, 47, 49–52, 79, 80
- FReachable*, *see* states, final-reachable
- function
- partial, 9, 32, 46, 68, 76, 78
 - total, 6, 7, 9–12, 14–17, 22, 24, 26, 27, 31–33, 35–37, 42–44, 46–48, 53, 56, 57, 59, 61, 63–68, 76, 78
- GCL*, *see* guarded command language
- guarded command language, 12, 26
- Iconstr*, *see* finite automata, construction, item set
- identity relation, *see* relation, identity
- initial Σ -algebra, *see* Sigma-algebra, initial
- IS*, *see* item sets
- isomorphism, 7, 8, 10, 11, 17–21, 23, 27–45, 48, 50–52, 56, 65, 79
- classes, 8, 11, 18–21, 23, 27–45, 48, 50–52, 65, 79
- of finite automata, *see* finite automata, isomorphism of
- item, *see* dotted regular expression
- language of, 66, 70
- item set
- closure of, 67–72
 - optimization of, 4, 69–72
- construction, *see* finite automata, construction, item set
- DeRemer’s, *see* finite automata, construction, DeRemer’s
- improved, *see* finite automata, construction, item set (high quality)
- derivative, *see* derivative item set
- language of, 66–70
- relation on, 67, 68

- item sets, 66–71
- K*, *see* finite automata, construction, lookahead automata
- LAFA*, *see* ϵ -lookahead finite automata language
- of an item, 66, 70
 - of extended regular expressions, 44, 58–61, 64
 - of finite automata, 7, 8, 10–12, 18, 23, 29–31, 36, 40–42, 45, 49, 53, 55–57, 61, 68, 79
 - extension of, 8
 - of item sets, 66–70
 - of regular expressions, 16–18, 22, 24, 25, 27, 36, 39, 44, 47, 49, 63–66, 68, 70
 - regular, 18, 39–42, 44, 55–57, 63, 76, 77
 - Σ -algebra of, 16
- Last*, 47, 48, 65
- last*, 32–34, 36, 38, 39, 41, 42, 44, 45, 49–52, 79, 80
- LBFA*, *see* finite automata, left-biased
- lbfa*, 31–33, 35–37, 39, 40
- left derivative, 36, 56–65, 67, 68, 72, 77
- left-biased finite automata, *see* finite automata, left-biased
- \mathcal{L}_{ERE} , *see* extended regular expressions, language denoted by
- \mathcal{L}_{FA} , *see* finite automata, language of
- \mathcal{L}_{IS} , *see* item set, language of
- look*, 24–26
- lookahead finite automata, *see* ϵ -lookahead finite automata
- \mathcal{L}_{RE} , *see* regular expressions, language denoted by
- \mathcal{L}_{reg} , *see* language, regular
- \mathcal{L}_{RFA} , *see* reduced finite automata, language of
- Mahr, B., 14
- convert_b*, 36, 37, 41, 42
- convert_e*, 42, 43, 49, 71
- max**, 15
- McNaughton, Yamada and Glushkov's construction, *see* finite automata, construction, McNaughton, Yamada and Glushkov's
- merge*, *see* finite automata, transformations on, merge
- Min*, *see* finite automata, deterministic, minimality of
- Min_C*, *see* finite automata, deterministic, minimality of
- Minimal*, *see* finite automata, deterministic, minimality of
- Minimal_C*, *see* finite automata, deterministic, minimality of
- MN*, 55
- MNconstr*, *see* finite automata, construction, Myhill and Nerode's
- MNmin*, *see* finite automata, construction, Myhill and Nerode's minimal
- MYG*, *see* finite automata, construction, McNaughton, Yamada, and Glushkov's
- Myhill and Nerode's construction, *see* finite automata, construction, Myhill and Nerode's
- minimal, *see* finite automata, construction, Myhill and Nerode's minimal
- Myhill-Nerode theorem, 10
- N*, *see* finite automata, construction, guarded commands
- nondeterministic finite automata, *see* finite automata, nondeterministic
- Null*, 17, 24, 47, 48, 63–65
- null*, 32–34, 36, 38, 39, 41, 42, 44, 45, 50–52, 79, 80
- Occ*, 46, 48, 64, 65
- Oconstr*, *see* finite automata, construction, optimized item set
- operator set, 14
- operators, 14, 15
- arity of, 14
 - constant, *see* constants
- optimization
- of closure of an item set, 4, 69–72
- \mathcal{P} , *see* powerset
- powerset, 6, 7, 9, 12, 16, 23, 24, 26, 32, 46, 47, 59, 64, 66, 68, 76
- powerset construction, *see* finite automata, subset construction
- preservation, 10
- projection, 8, 33, 45, 52, 76, 78
- properties
- of finite automata, 7–10
- Qmap*, 32–34, 36, 38, 39, 41, 42, 44–46, 50–52
- \mathcal{R} , *see* item, language of
- RBFA*, *see* finite automata, right-biased
- RE*, *see* regular expressions
- Reach*, *see* states, reachability relation on
- reachability relation
- on states, *see* states, reachability relation on

- Reachable*, *see* states, reachable
 reachable states, *see* state, reachability relation on
 reduced finite automata, 4, 32–42, 44–52, 72, 73, 79, 80
Reg, 15
 regular expressions, 15–18, 21–26, 28, 31, 33–37, 39–44, 46, 47, 49, 58, 63–71
 constants, 15
 definition of, 15
 dotted, *see* dotted regular expressions
 equivalence of, 16, 59–63
 extended, 44, 58–63, 65, 71
 language denoted by, 44, 58–61, 64
 language denoted by, 16–18, 22, 24, 25, 27, 36, 39, 44, 47, 49, 63–66, 68, 70
 operators, 15
 abbreviations, 16
 restricted, 46–49, 63–65
 reverse of, 17
 similarity, 59–61, 63, 64
 similarity of, 59–64, 71
 regular languages, *see* language, regular relation
 ϵ -transition, *see* ϵ -transition relation
 equivalence, 7
 identity, 7
 reachability, of states, *see* states, reachability relation on transition, *see* transition, relation
 remove_ϵ , *see* finite automata (transf. on), ϵ removal
 $\text{remove}_{\epsilon,\text{sym}}$, *see* finite automata (transf. on), ϵ removal
 restricted regular expressions, *see* regular expressions, restricted reversal
 of finite automata, *see* finite automata, reverse of
 of regular expressions, *see* regular expressions, reverse of
RFA, *see* reduced finite automata
rfa, 33, 35–37, 40–43, 46–48
 right-biased finite automata, *see* finite automata, right-biased
RRE, *see* regular expressions, restricted
 Σ -algebras, 14
 basic definitions, 14–15
 definition of, 14
 example of, 15
 initial, 15
 Σ -homomorphism, 15, 16
 example of, 15
Null, 17
 Σ -term algebra, 15
 signature, 14, 15
 sink state, *see* states, sink
 size of finite automata, *see* finite automata, size of sort, 14
SReachable, *see* states, start-reachable
 start states, *see* states, start
 start-reachable states, *see* states, start-reachable state graphs, 6
 states, 6
 final, 6
 final-reachable, 8, 9
 final-unreachable, removal, *see* finite automata (transf. on), final-unreachable removal
 language between, 7
 left language of, 7, 8
 right language of, 7, 8
 sink, 11–13
 start, 6, 9
 start-reachable, 8, 9, 11
 start-unreachable, removal, *see* finite automata (transf. on), start-unreachable removal
 useless, removal, *see* finite automata, transformations on, useless state removal subset, *see* finite automata, subset construction
 subset construction, *see* finite automata, subset construction implementation of, 12
subsetopt, *see* finite automata, subset construction, optimized symmetrical, *see* dual function, 11, 17 transformation, 11
td, *see* finite automata, construction, Thompson top-down
Term $_\Sigma$, 14
Th, *see* finite automata, construction, Thompson
 Thompson's construction, *see* finite automata, construction, Thompson top-down
 top-down, *see* finite automata, construction, Thompson transformations on finite automata, 10–13 transition function, 9 relation, 6 extension of, 7

true, 16, 17, 32, 34, 47, 48, 50–52
tuple, 6
 projection, 8, 33, 45, 52, 76, 78

undot, 66, 68

Useful, *see* finite automata, useful

useful, *see* finite automata, transformations
 on, useless state removal

useful states, *see* states, useful

Useful_f, *see* finite automata, useful, final

useful_f, *see* finite automata (transf. on), final-
 unreach. removal

Useful_s, *see* finite automata, useful, start

useful_s, *see* finite automata (transf. on), start-
 unreach. removal

vertices, 6

\mathcal{X} , *see* item set, optimization of closure of

\mathcal{Y} , *see* item set, optimization of closure of

In this series appeared:

- | | | |
|-------|---|---|
| 91/01 | D. Alstein | Dynamic Reconfiguration in Distributed Hard Real-Time Systems, p. 14. |
| 91/02 | R.P. Nederpelt
H.C.M. de Swart | Implication. A survey of the different logical analyses "if...,then...", p. 26. |
| 91/03 | J.P. Katoen
L.A.M. Schoenmakers | Parallel Programs for the Recognition of <i>P</i> -invariant Segments, p. 16. |
| 91/04 | E. v.d. Sluis
A.F. v.d. Stappen | Performance Analysis of VLSI Programs, p. 31. |
| 91/05 | D. de Reus | An Implementation Model for GOOD, p. 18. |
| 91/06 | K.M. van Hee | SPECIFICATIEMETHODEN, een overzicht, p. 20. |
| 91/07 | E.Poll | CPO-models for second order lambda calculus with recursive types and subtyping, p. 49. |
| 91/08 | H. Schepers | Terminology and Paradigms for Fault Tolerance, p. 25. |
| 91/09 | W.M.P.v.d.Aalst | Interval Timed Petri Nets and their analysis, p.53. |
| 91/10 | R.C.Backhouse
P.J. de Bruin
P. Hoogendijk
G. Malcolm
E. Voermans
J. v.d. Woude | POLYNOMIAL RELATORS, p. 52. |
| 91/11 | R.C. Backhouse
P.J. de Bruin
G.Malcolm
E.Voermans
J. van der Woude | Relational Catamorphism, p. 31. |
| 91/12 | E. van der Sluis | A parallel local search algorithm for the travelling salesman problem, p. 12. |
| 91/13 | F. Rietman | A note on Extensionality, p. 21. |
| 91/14 | P. Lemmens | The PDB Hypermedia Package. Why and how it was built, p. 63. |
| 91/15 | A.T.M. Aerts
K.M. van Hee | Eldorado: Architecture of a Functional Database Management System, p. 19. |
| 91/16 | A.J.J.M. Marcelis | An example of proving attribute grammars correct:
the representation of arithmetical expressions by DAGs, p. 25. |

91/17	A.T.M. Aerts P.M.E. de Bra K.M. van Hee	Transforming Functional Database Schemes to Relational Representations, p. 21.
91/18	Rik van Geldrop	Transformational Query Solving, p. 35.
91/19	Erik Poll	Some categorical properties for a model for second order lambda calculus with subtyping, p. 21.
91/20	A.E. Eiben R.V. Schuwer	Knowledge Base Systems, a Formal Model, p. 21.
91/21	J. Coenen W.-P. de Roever J.Zwiers	Assertional Data Reification Proofs: Survey and Perspective, p. 18.
91/22	G. Wolf	Schedule Management: an Object Oriented Approach, p. 26.
91/23	K.M. van Hee L.J. Somers M. Voorhoeve	Z and high level Petri nets, p. 16.
91/24	A.T.M. Aerts D. de Reus	Formal semantics for BRM with examples, p. 25.
91/25	P. Zhou J. Hooman R. Kuiper	A compositional proof system for real-time systems based on explicit clock temporal logic: soundness and completeness, p. 52.
91/26	P. de Bra G.J. Houben J. Paredaens	The GOOD based hypertext reference model, p. 12.
91/27	F. de Boer C. Palamidessi	Embedding as a tool for language comparison: On the CSP hierarchy, p. 17.
91/28	F. de Boer	A compositional proof system for dynamic process creation, p. 24.
91/29	H. Ten Eikelder R. van Geldrop	Correctness of Acceptor Schemes for Regular Languages, p. 31.
91/30	J.C.M. Baeten F.W. Vaandrager	An Algebra for Process Creation, p. 29.
91/31	H. ten Eikelder	Some algorithms to decide the equivalence of recursive types, p. 26.
91/32	P. Struik	Techniques for designing efficient parallel programs, p. 14.
91/33	W. v.d. Aalst	The modelling and analysis of queueing systems with QNM-ExSpect, p. 23.
91/34	J. Coenen	Specifying fault tolerant programs in deontic logic, p. 15.

92/21	F.Kamareddine	Non well-foundedness and type freeness can unify the interpretation of functional application, p. 16.
92/22	R. Nederpelt F.Kamareddine	A useful lambda notation, p. 17.
92/23	F.Kamareddine E.Klein	Nominalization, Predication and Type Containment, p. 40.
92/24	M.Codish D.Dams Eyal Yardeni	Bottum-up Abstract Interpretation of Logic Programs, p. 33.
92/25	E.Poll	A Programming Logic for F ω , p. 15.
92/26	T.H.W.Beelen W.J.J.Stut P.A.C.Verkoulen	A modelling method using MOVIE and SimCon/ExSpect, p. 15.
92/27	B. Watson G. Zwaan	A taxonomy of keyword pattern matching algorithms, p. 50.
93/01	R. van Geldrop	Deriving the Aho-Corasick algorithms: a case study into the synergy of programming methods, p. 36.
93/02	T. Verhoeff	A continuous version of the Prisoner's Dilemma, p. 17
93/03	T. Verhoeff	Quicksort for linked lists, p. 8.
93/04	E.H.L. Aarts J.H.M. Korst P.J. Zwietering	Deterministic and randomized local search, p. 78.
93/05	J.C.M. Baeten C. Verhoef	A congruence theorem for structured operational semantics with predicates, p. 18.
93/06	J.P. Veltkamp	On the unavoidability of metastable behaviour, p. 29
93/07	P.D. Moerland	Exercises in Multiprogramming, p. 97
93/08	J. Verhoosel	A Formal Deterministic Scheduling Model for Hard Real-Time Executions in DEDOS, p. 32.
93/09	K.M. van Hee	Systems Engineering: a Formal Approach Part I: System Concepts, p. 72.
93/10	K.M. van Hee	Systems Engineering: a Formal Approach Part II: Frameworks, p. 44.
93/11	K.M. van Hee	Systems Engineering: a Formal Approach Part III: Modeling Methods, p. 101.
93/12	K.M. van Hee	Systems Engineering: a Formal Approach Part IV: Analysis Methods, p. 63.
93/13	K.M. van Hee	Systems Engineering: a Formal Approach Part V: Specification Language, p. 89.

93/14	J.C.M. Baeten J.A. Bergstra	On Sequential Composition, Action Prefixes and Process Prefix, p. 21.
93/15	J.C.M. Baeten J.A. Bergstra R.N. Bol	A Real-Time Process Logic, p. 31.
93/16	H. Schepers J. Hooman	A Trace-Based Compositional Proof Theory for Fault Tolerant Distributed Systems, p. 27
93/17	D. Alstein P. van der Stok	Hard Real-Time Reliable Multicast in the DEDOS system, p. 19.
93/18	C. Verhoef	A congruence theorem for structured operational semantics with predicates and negative premises, p. 22.
93/19	G.-J. Houben	The Design of an Online Help Facility for ExSpect, p.21.
93/20	F.S. de Boer	A Process Algebra of Concurrent Constraint Programming, p. 15.
93/21	M. Codish D. Dams G. Filé M. Bruynooghe	Freeness Analysis for Logic Programs - And Correctness?, p. 24.
93/22	E. Poll	A Typechecker for Bijective Pure Type Systems, p. 28.
93/23	E. de Kogel	Relational Algebra and Equational Proofs, p. 23.
93/24	E. Poll and Paula Severi	Pure Type Systems with Definitions, p. 38.
93/25	H. Schepers and R. Gerth	A Compositional Proof Theory for Fault Tolerant Real-Time Distributed Systems, p. 31.
93/26	W.M.P. van der Aalst	Multi-dimensional Petri nets, p. 25.
93/27	T. Kloks and D. Kratsch	Finding all minimal separators of a graph, p. 11.
93/28	F. Kamareddine and R. Nederpelt	A Semantics for a fine λ -calculus with de Bruijn indices, p. 49.
93/29	R. Post and P. De Bra	GOLD, a Graph Oriented Language for Databases, p. 42.
93/30	J. Deogun T. Kloks D. Kratsch H. Müller	On Vertex Ranking for Permutation and Other Graphs, p. 11.
93/31	W. Körver	Derivation of delay insensitive and speed independent CMOS circuits, using directed commands and production rule sets, p. 40.
93/32	H. ten Eikelder and H. van Geldrop	On the Correctness of some Algorithms to generate Finite Automata for Regular Expressions, p. 17.
93/33	L. Loyens and J. Moonen	ILIAS, a sequential language for parallel matrix computations, p. 20.

93/34	J.C.M. Baeten and J.A. Bergstra	Real Time Process Algebra with Infinitesimals, p.39.
93/35	W. Ferrer and P. Severi	Abstract Reduction and Topology, p. 28.
93/36	J.C.M. Baeten and J.A. Bergstra	Non Interleaving Process Algebra, p. 17.
93/37	J. Brunekreef J-P. Katoen R. Koymans S. Mauw	Design and Analysis of Dynamic Leader Election Protocols in Broadcast Networks, p. 73.
93/38	C. Verhoef	A general conservative extension theorem in process algebra, p. 17.
93/39	W.P.M. Nijtjen E.H.L. Aarts D.A.A. van Erp Taalman Kip K.M. van Hee	Job Shop Scheduling by Constraint Satisfaction, p. 22.
93/40	P.D.V. van der Stok M.M.M.P.J. Claessen D. Alstein	A Hierarchical Membership Protocol for Synchronous Distributed Systems, p. 43.
93/41	A. Bijlsma	Temporal operators viewed as predicate transformers, p. 11.
93/42	P.M.P. Rambags	Automatic Verification of Regular Protocols in P/T Nets, p. 23.