

Homework #1

CS 4710: Artificial Intelligence (Fall'21)

Due Friday 09/10 10:00 pm

Introduction: Welcome to the first official homework for CS4710! As you are hopefully already aware, this PDF comprises the written component of the first problem set. In addition to solving the problems found below, you will also need to complete the coding part of the assignment. Finally, we'd like to remind you that while you are allowed a partner for the coding part of the assignment, you are **NOT** allowed a partner for this and all future written components. All written work should be yours and yours alone. This being said, in addition to being able to ask questions at office hours, you are allowed to discuss questions with fellow classmates, provided 1) you note the people with whom you collaborated, and 2) you **DO NOT** copy any answers. Please write up the solutions to all problems independently.

Collaborators:

Problem 1: Which of the following are true and which are false? Explain your answers.

- (a) Depth-first search always expands at least as many nodes as A* search with an admissible heuristic.
- (b) $h(n) = 0$ is an admissible heuristic for the 15-Puzzle (https://en.wikipedia.org/wiki/15_puzzle).
- (c) A* is of no use in robotics because percepts, states, and actions are continuous.
- (d) Breadth-first search is complete even if zero step costs are allowed.
- (e) Assume that a rook can move on a chessboard any number of squares in a straight line, vertically or horizontally, but cannot jump over other pieces. Manhattan distance is an admissible heuristic for the problem of moving the rook from square A to square B in the smallest number of moves.

Solution 1:

Problem 2: Describe a state space graph in which iterative deepening search performs much worse than depth-first search (for example, $O(n^2)$ vs. $O(n)$).

Solution 2:

Problem 3: For each of the following statements, prove it is true or briefly explain why it is not true:

- (a) Breadth-first search is a special case of uniform-cost search.
- (b) Depth-first search is a special case of best-first search.

Note: best-first search is a class of uninformed tree search algorithms whose fringe is a priority queue based on certain some evaluation function of your choice.

- (c) Uniform-cost search is a special case of A* search.

Solution 3:

Problem 4: Prove that if a heuristic is consistent, it must be admissible.
Construct an admissible heuristic that is not consistent.

Solution 4: