

1 history

2 bandwidth

3 archive weights

4 proposal


5 one draw

6 weight

(a) textbook ABC-PMC, schematic: one update per generation shown: generation $t \rightarrow t+1$, after 135 simulations




$P_t: (\theta_i, \rho_i, \omega_i^{(t)})$
gen. $< t$ discarded




$\epsilon_{t+1} = \text{quantile}_\alpha \{\rho_i\}_{i \leq N}$
hard: keep $\rho < \epsilon_{t+1}$




$\Sigma_t = 2 \widehat{\text{Cov}}_{\omega^{(t)}}(\{\theta_i\})$
weights carried over



$q_t = \sum_{i \leq N} \omega_i^{(t)} K_{\Sigma_t}(\cdot - \theta_i)$



$\theta^* \sim q_t$, simulate,
keep if $\rho^* < \epsilon_{t+1}$;
one at a time, until N kept




$\omega^{(t+1)} \propto \pi/q_t$
after acceptance


P_{t+1} : the N kept, weighted; the rejected are discarded

barrier: q_{t+1} needs the complete P_{t+1}


(b) generation-free (ours): one update per arrival shown: the update after 84 evaluations, $w^* = 1$, no bandwidth stored




$\mathcal{H}_n$: all n so far
($\theta_i, \rho_i, \epsilon_i, w_i$)




$A_n = \text{Top}_k(\rho)$
 ϵ_n non-increasing, smooth K_{ϵ_n}




$\bar{W}_j \propto w_j K_{\epsilon_n}(\rho_j)$
 $\Sigma_n = s \widehat{\text{Cov}}_{\bar{W}}(A_n)$



$q_n = \sum_{j \in A_n} \bar{W}_j K_{\Sigma_n}(\cdot - \theta_j)$



$\theta^* = \theta_J + L_n z$, $J \sim \bar{W}$
one candidate



$w^* = \pi/\bar{q}_n^{\text{on}}$ at θ^*

θ^* to a free worker; ρ^* arrives later, among other workers' results: append $(\theta^*, \rho^*, \epsilon_n, w^*)$