

# Extended Formulations for Quadratic Mixed Integer Programming

Juan Pablo Vielma

Sloan School of Business,  
Massachusetts Institute of Technology

IP for Lunch,  
IBM T. J. Watson Research Center,  
Yorktown Heights, NY. December, 2014.

Supported by NSF grants CMMI-1233441 and CMMI-1351619


# Nonlinear MIP B&B Algorithms

$$\max \quad \sum_{i=1}^n c_i x_i$$

s.t.

$$g_i(x) \leq 0, \quad i \in I, \quad x \in \mathbb{Z}^n$$

$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms


- NLP (QCP) Based B&B

$$\max \quad \sum_{i=1}^n c_i x_i$$

s.t.

$$g_i(x) \leq 0, \quad i \in I, \quad x \in \mathbb{Z}^n$$

$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms


- NLP (QCP) Based B&B

$$\max \quad \sum_{i=1}^n c_i x_i$$

s.t.

$$g_i(x) \leq 0, \quad i \in I, \quad x \in \mathbb{Z}^n$$

$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms


- NLP (QCP) Based B&B

$$\max \quad \sum_{i=1}^n c_i x_i$$

s.t.

$$g_i(x) \leq 0, \quad i \in I, \quad x \in \mathbb{Z}^n$$

$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms


- NLP (QCP) Based B&B

$$\max \quad \sum_{i=1}^n c_i x_i$$

s.t.

$$g_i(x) \leq 0, \quad i \in I, \quad x \in \mathbb{Z}^n$$


$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.

$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$




# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.

$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \end{aligned}$$

$$x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2}$$



# Nonlinear MIP B&B Algorithms


- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B

- Few cuts = high speed.
- Possible slow convergence.

- Lifted LP B&B

- Extended or Lifted relaxation.
- Static relaxation
  - Mimic NLP B&B.
- Dynamic relaxation
  - Standard LP B&B


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Nonlinear MIP B&B Algorithms

- NLP (QCP) Based B&B
- (Dynamic) LP Based B&B
  - Few cuts = high speed.
  - Possible slow convergence.
- Lifted LP B&B
  - Extended or Lifted relaxation.
  - Static relaxation
    - Mimic NLP B&B.
  - Dynamic relaxation
    - Standard LP B&B


$$\begin{aligned} \max \quad & \sum_{i=1}^n c_i x_i \\ \text{s.t.} \quad & Ax + Dz \leq b, \\ & g_i(x) \leq 0, i \in I, \quad x \in \mathbb{Z}^n \\ & x \in \mathbb{Z}^{n_1} \times \mathbb{R}^{n_2} \end{aligned}$$



# Static Lifted LP for Conic Quadratic MIP

---


- Approximation of Second Order Cone of dimension  $n$  by Ben-Tal and Nemirovski (Glineur).
- $O(n \log(1/\varepsilon))$  variables and constraints for quality  $\varepsilon$ .
  - Exponential increment in # of constraints through projection.
- Problem:
  - Fixed a-priori quality: no dynamic improvement (e.g.  $\varepsilon = 0.01$  best for some portfolio optimization problems)



# Correct Quality = Significant Improvement

---

- Results from V., Ahmed and Nemhauser '08.




# Dynamic Lifted LP for Separable Problems

---

- Motivating example from Hijazi et al. '14

$$F^n := \left\{ x \in \mathbb{R}^n : \sum_{i=1}^n \left( x_i - \frac{1}{2} \right)^2 \leq \frac{n-1}{4} \right\}$$

Showing  $F^n \cap \mathbb{Z}^n = \emptyset$  requires  $2^n$  cuts.



# Dynamic Lifted LP for Separable Problems


- Motivating example from Hijazi et al. '14

$$F^n := \left\{ x \in \mathbb{R}^n : \sum_{i=1}^n \left( x_i - \frac{1}{2} \right)^2 \leq \frac{n-1}{4} \right\}$$

Extended formulation of  $F^n$ :

$$\left( x_i - \frac{1}{2} \right)^2 \leq z_i \quad \forall i \in [n]$$

$$\sum_{i=1}^n z_i \leq \frac{n-1}{4}$$



# Dynamic Lifted LP for Separable Problems


- Motivating example from Hijazi et al. '14

$$F^n := \left\{ x \in \mathbb{R}^n : \sum_{i=1}^n \left( x_i - \frac{1}{2} \right)^2 \leq \frac{n-1}{4} \right\}$$

Extended formulation of  $F^n$ :

$$\left( x_i - \frac{1}{2} \right)^2 \leq z_i \quad \forall i \in [n]$$

$$\sum_{i=1}^n z_i \leq \frac{n-1}{4}$$



# Dynamic Lifted LP for Separable Problems

- Motivating example from Hijazi et al. '14

$$F^n := \left\{ x \in \mathbb{R}^n : \sum_{i=1}^n \left( x_i - \frac{1}{2} \right)^2 \leq \frac{n-1}{4} \right\}$$


Extended formulation of  $F^n$ :

$$\left( x_i - \frac{1}{2} \right)^2 \leq z_i \quad \forall i \in [n]$$

$$\sum_{i=1}^n z_i \leq \frac{n-1}{4}$$

$B^n \cap \mathbb{Z}^n = \emptyset$  with only  $2n$  cuts

on extended formulation.



# Significant Improvement For Many Problems

---

- Tawarmalani and Sahinidis '05:

$f_j : \mathbb{R} \rightarrow \mathbb{R}$  convex differentiable

Lifted Relaxation of  $F := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sum_{j=1}^n f_j(y_j) \leq y_0 \right\}$ :

$$f_j(\gamma) + f'_j(\gamma)(y_j - \gamma) \leq w_j \quad \forall \gamma \in \Gamma_j, \quad j \in [n]$$

$$\sum_{j=1}^n w_j \leq y_0$$

# Significant Improvement For Many Problems

---

- Tawarmalani and Sahinidis '05:

$f_j : \mathbb{R} \rightarrow \mathbb{R}$  convex differentiable

Lifted Relaxation of  $F := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sum_{j=1}^n f_j(y_j) \leq y_0 \right\}$ :

$$f_j(\gamma) + f'_j(\gamma)(y_j - \gamma) \leq w_j \quad \forall \gamma \in \Gamma_j, \quad j \in [n]$$

$$\sum_{j=1}^n w_j \leq y_0$$

Projection to  $(y_0, y)$  = up to  $\prod_{j=1}^n |\Gamma_j|$  constraints

# Significant Improvement For Many Problems

---

- Tawarmalani and Sahinidis '05:

$f_j : \mathbb{R} \rightarrow \mathbb{R}$  convex differentiable

Lifted Relaxation of  $F := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sum_{j=1}^n f_j(y_j) \leq y_0 \right\}$ :

$$f_j(\gamma) + f'_j(\gamma)(y_j - \gamma) \leq w_j \quad \forall \gamma \in \Gamma_j, \quad j \in [n]$$

$$\sum_{j=1}^n w_j \leq y_0$$

Projection to  $(y_0, y)$  = up to  $\prod_{j=1}^n |\Gamma_j|$  constraints

- Polynomial (degree  $n$ ) increment in # of constraints through projection

# Separable Approach for Conic Quadratic?

---

- “Separable Sets” include many quadratics:
  - Euclidean Ball

$$B^n := \left\{ y \in \mathbb{R}^n : \sum_{j=1}^n y_j^2 \leq 1 \right\}$$

- Paraboloids

$$Q^n := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sum_{j=1}^n y_j^2 \leq y_0 \right\}$$

- Does not include Lorentz/SOCP cone:

$$L^n := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sqrt{\sum_{j=1}^n y_j^2} \leq y_0 \right\}$$

# Separable to Conic: Homogenize


---

- From Euclid to Lorentz

$$B^n := \left\{ y \in \mathbb{R}^n : \sum_{j=1}^n y_j^2 \leq 1 \right\}$$

$$L^n := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sqrt{\sum_{j=1}^n y_j^2} \leq y_0 \right\}$$

$$L^n = \text{cone}(\{1\} \times B^n)$$



# Separable to Conic: Homogenize

---


- From Euclid to Lorentz

$$B^n := \left\{ y \in \mathbb{R}^n : \sum_{j=1}^n y_j^2 \leq 1 \right\}$$

$$L^n := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sqrt{\sum_{j=1}^n y_j^2} \leq y_0 \right\}$$

$$L^n = \text{cone}(\{1\} \times B^n)$$

$$B^n \subseteq P$$



# Separable to Conic: Homogenize


---

- From Euclid to Lorentz

$$B^n := \left\{ y \in \mathbb{R}^n : \sum_{j=1}^n y_j^2 \leq 1 \right\}$$

$$L^n := \left\{ (y_0, y) \in \mathbb{R}^{n+1} : \sqrt{\sum_{j=1}^n y_j^2} \leq y_0 \right\}$$

$$L^n = \text{cone}(\{1\} \times B^n)$$



$$B^n \subseteq P \Rightarrow L^n \subseteq \text{cone}(\{1\} \times P)$$

# Lifted Relaxation for Separable Conic Sets

---

$f_j : \mathbb{R} \rightarrow \mathbb{R}$  convex, differentiable and 1-coercive

$$C := \left\{ y \in \mathbb{R}^n : \sum_{j=1}^n f_j(y_j) \leq 1 \right\}$$

Lifted Relaxation of cone  $(\{1\} \times C)$ :

$$(f(\gamma) - \gamma f'(\gamma)) y_0 + f'(\gamma) y \leq w_j \quad \forall \gamma \in \Gamma_j, j \in [n]$$

$$\sum_{j=1}^n w_j \leq y_0$$

$$0 \leq y_0$$

# Lifted Reformulation for Conic Quadratic Sets

---

- Lifted Reformulation of  $L^n := \{(y_0, y) \in \mathbb{R}^{n+1} : \|y\|_2 \leq y_0\}$ :

$$y_i^2 \leq z_i \cdot y_0 \quad \forall i \in [n]$$

$$\sum_{i=1}^n z_i \leq y_0$$

# Lifted Reformulation for Conic Quadratic Sets

---

- Lifted Reformulation of  $L^n := \{(y_0, y) \in \mathbb{R}^{n+1} : \|y\|_2 \leq y_0\}$ :

$$\sum_{i=1}^n z_i \leq y_0$$

$y_i^2 \leq z_i \cdot y_0 \quad \forall i \in [n]$

↑  
Rotated SOCP cone


# Lifted Reformulation for Conic Quadratic Sets

---

- Lifted Reformulation of  $L^n := \{(y_0, y) \in \mathbb{R}^{n+1} : \|y\|_2 \leq y_0\}$ :

$$\sum_{i=1}^n z_i \leq y_0$$
$$y_i^2 \leq z_i \cdot y_0 \quad \forall i \in [n]$$

Rotated SOCP cone



- Lifted polyhedral relaxation automatic from standard polyhedral approximation of (rotated) SOCP cone:
  - Dynamic Lifted LP-based algorithm:
    1. Replace every SOCP cone with lifted formulation
    2. Solve with standard LP-based algorithm

# Computational Experiments 1: Solvers

---

# Computational Experiments 1: Solvers

---

- NLP-based Branch-and-Bound:
  - **CPLEXCP** : MIQCPSTRAT = 1
  - **GurobiCP** : MIQCPMethod = 0

# Computational Experiments 1: Solvers

---

- NLP-based Branch-and-Bound:
  - **CPLEXCP** : MIQCPSTRAT = 1
  - **GurobiCP** : MIQCPMethod = 0
- Traditional LP-based Branch-and-Bound:
  - **CPLEXLP** : MIQCPSTRAT = 2
  - **GurobiLP** : MIQCPMethod = 1

# Computational Experiments 1: Solvers

---

- NLP-based Branch-and-Bound:
  - **CPLEXCP** : MIQCPSTRAT = 1
  - **GurobiCP** : MIQCPMethod = 0
- Traditional LP-based Branch-and-Bound:
  - **CPLEXLP** : MIQCPSTRAT = 2
  - **GurobiLP** : MIQCPMethod = 1
- Dynamic Lifted LP-based Branch-and-Bound:
  - **CPLEXSepLP** : CPLEXLP on lifted reformulation
  - **GurobiSepLP**: GurobiLP on lifted reformulation

# Computational Experiments 1: Solvers

---

- NLP-based Branch-and-Bound:
  - **CPLEXCP** : MIQCPSTRAT = 1
  - **GurobiCP** : MIQCPMethod = 0
- Traditional LP-based Branch-and-Bound:
  - **CPLEXLP** : MIQCPSTRAT = 2
  - **GurobiLP** : MIQCPMethod = 1
- Dynamic Lifted LP-based Branch-and-Bound:
  - **CPLEXSepLP** : CPLEXLP on lifted reformulation
  - **GurobiSepLP**: GurobiLP on lifted reformulation
- CPLEX v 12.6 and Gurobi v 5.6.3

# Computational Experiments 1: Solvers

---

- NLP-based Branch-and-Bound:
  - **CPLEXCP** : MIQCPSTRAT = 1
  - **GurobiCP** : MIQCPMethod = 0
- Traditional LP-based Branch-and-Bound:
  - **CPLEXLP** : MIQCPSTRAT = 2
  - **GurobiLP** : MIQCPMethod = 1
- Dynamic Lifted LP-based Branch-and-Bound:
  - **CPLEXSepLP** : CPLEXLP on lifted reformulation
  - **GurobiSepLP**: GurobiLP on lifted reformulation
- CPLEX v 12.6 and Gurobi v 5.6.3
- Time limit of 3,600 s on i7-3770 3.40GHz

# Computational Experiments 1: Instances

---

- Portfolio optimization problems:

Classical:

$$\max \quad \bar{a}x$$

s.t.

$$\left\| Q^{1/2}x \right\|_2 \leq \sigma$$


$$\sum_{j=1}^n x_j = 1, \quad x \in \mathbb{R}_+^n$$

$$x_j \leq z_j \quad \forall j \in [n]$$


$$\sum_{j=1}^n z_j \leq K, \quad z \in \{0, 1\}^n$$

- $\bar{a}$  expected returns.
- $Q^{1/2}$  square root of covariance matrix.
- $K$  maximum number of assets.
- $\sigma$  maximum risk.

# Results for CPLEX: 100 instances per n



# Results for Gurobi: 100 instances per n



## Computational Experiments 2: More Solvers

---

- Static Lifted LP-based Branch-and-Bound:
  - **LiftedLP**: from V., Ahmed and Nemhauser '08
  - Fixed approximation by Ben-Tal and Nemirovski (Glineur)
  - No refinement: integer nodes = solve NLP and process
  - Heuristic: Correct integral solutions (fix integers, solve NLP)
  - CPLEX Branch, heuristic and incumbent callbacks in JuMP

## Computational Experiments 2: More Solvers

---

- Static Lifted LP-based Branch-and-Bound:
  - **LiftedLP**: from V., Ahmed and Nemhauser '08
  - Fixed approximation by Ben-Tal and Nemirovski (Glineur)
  - No refinement: integer nodes = solve NLP and process
  - Heuristic: Correct integral solutions (fix integers, solve NLP)
  - CPLEX Branch, heuristic and incumbent callbacks in JuMP
- Static/Dynamic Lifted LP-based Branch-and-Bound:
  - **CPLEXSepLazy / GurobiSepLazy** : LiftedLP + Refinement through Separable extended formulation
  - Solver independent implementation in JuMP


## Computational Experiments 2: More Solvers

---

- Static Lifted LP-based Branch-and-Bound:
  - **LiftedLP**: from V., Ahmed and Nemhauser '08
  - Fixed approximation by Ben-Tal and Nemirovski (Glineur)
  - No refinement: integer nodes = solve NLP and process
  - Heuristic: Correct integral solutions (fix integers, solve NLP)
  - CPLEX Branch, heuristic and incumbent callbacks in JuMP
- Static/Dynamic Lifted LP-based Branch-and-Bound:
  - **CPLEXSepLazy / GurobiSepLazy** : LiftedLP + Refinement through Separable extended formulation
  - Solver independent implementation in JuMP
- ~ 400 lines of JuMP code in about a week

# JuMP : Julia for Mathematical Programming

---



- Developed by ORC students: Iain Dunning, Joey Huchette and Miles Lubin.
- “As easy as AMPL and faster than C++” (JPV 2014).
- Linear/Quadratic MIP and general nonlinear
  - Cbc/Clp, CPLEX, ECOS, GLPK, Gurobi, Ipopt, KNITRO, MOSEK, and Nlopt.
- Automatic differentiation, solver independent MIP callbacks, etc.
- <https://github.com/JuliaOpt/JuMP.jl>

# Computational Experiments 2 : More Instances

---

- Portfolio optimization problems:

Classical:

$$\begin{aligned} \max \quad & \bar{a}x \\ s.t. \quad & \|Q^{1/2}x\|_2 \leq \sigma \\ & \sum_{j=1}^n x_j = 1, \quad x \in \mathbb{R}_+^n \\ & x_j \leq z_j \quad \forall j \in [n] \\ & \sum_{j=1}^n z_j \leq K, \quad z \in \{0, 1\}^n \end{aligned}$$

- $\bar{a}$  expected returns.
- $Q^{1/2}$  square root of covariance matrix.
- $K$  maximum number of assets.
- $\sigma$  maximum risk.

## Computational Experiments 2 : More Instances

---

- Portfolio optimization problems:

Shortfall:

$$\max \quad \bar{a}x$$

s.t.

$$\Phi^{-1}(\eta_i) \left\| Q^{1/2}y \right\|_2 \leq \bar{a}y - W_i^{low} \quad i \in \{1, 2\}$$

$$\sum_{j=1}^n x_j = 1, \quad x \in \mathbb{R}_+^n$$

$$x_j \leq z_j \quad \forall j \in [n]$$

$$\sum_{j=1}^n z_j \leq K, \quad z \in \{0, 1\}^n$$

- $\bar{a}$  expected returns.
- $Q^{1/2}$  square root of covariance matrix.
- $K$  maximum number of assets.
- $\approx \mathbb{P}(\bar{a}x \geq W_i^{low}) \geq \eta_i$

# Computational Experiments 2 : More Instances

---

- Portfolio optimization problems:

Robust:

$$\max \quad \bar{a}x - \alpha \left\| R^{1/2}y \right\|_2$$

s.t.

$$\left\| Q^{1/2}x \right\|_2 \leq \sigma$$


$$\sum_{j=1}^n x_j = 1, \quad x \in \mathbb{R}_+^n$$

$$x_j \leq z_j \quad \forall j \in [n]$$


$$\sum_{j=1}^n z_j \leq K, \quad z \in \{0, 1\}^n$$

- $\bar{a}$  expected returns.
- $Q^{1/2}$  square root of covariance matrix.
- $K$  maximum number of assets.
- $\sigma$  maximum risk.
- Robust objective.


# Performance Profile for n “=” 20-60, 100 and 200




# Performance Profile for n “=” 20-60, 100 and 200




# Performance Profile for n “=” 20-60, 100 and 200



# Performance Profile for n “=” 20-60, 100 and 200



# Performance Profile for n “=” 20-60, 100 and 200



# Summary

---

# Summary

---

- Extended Formulations can help in
  - LP-based B&B: Both in theory and practice.

# Summary

---

- Extended Formulations can help in
  - LP-based B&B: Both in theory and practice.
- Most ideas can be extended beyond quadratic
  - p-order cones almost directly
  - General nonlinear through perspective functions

# Summary

---

- Extended Formulations can help in
  - LP-based B&B: Both in theory and practice.
- Most ideas can be extended beyond quadratic
  - p-order cones almost directly
  - General nonlinear through perspective functions
- You should definitely try:

