Por fin tenemos reference.



Contents

1 Algorithm Descriptions **2**
1.1 Data Structures . . . 2
1.2 Graphs . . . 2
1.3 Math . . . 3
1.4 Strings . . . 3
1.5 Flow . . . 3

2 Data structures **3**
2.1 Segment tree . . . 3
2.2 Segment tree - Lazy propagation . . . 3
2.3 Segment tree - Persistence . . . 4
2.4 Segment tree - 2D . . . 4
2.5 Sparse table (static RMQ) . . . 5
2.6 Fenwick tree . . . 5
2.7 Wavelet tree . . . 5
2.8 STL extended set . . . 6
2.9 STL rope . . . 6
2.10 Treap (as BST) . . . 6
2.11 Treap (implicit key) . . . 7
2.12 Treap (with node father) . . . 7
2.13 Link-Cut tree . . . 8
2.14 Convex hull trick (static) . . . 9
2.15 Convex hull trick (dynamic) . . . 9
2.16 Li-Chao tree . . . 9
2.17 Gain-cost-set . . . 10
2.18 Disjoint intervals . . . 10

3 Graphs **11**
3.1 Topological sort . . . 11
3.2 Kruskal (+ Union-Find) . . . 11
3.3 Dijkstra . . . 11
3.4 Bellman-Ford . . . 11
3.5 Floyd-Warshall . . . 12
3.6 Strongly connected components (+ 2-SAT) . . . 12
3.7 Articulation - Bridges - Biconnected . . . 12
3.8 Chu-Liu (minimum spanning arborescence) . . . 13
3.9 LCA - Binary Lifting . . . 13
3.10 Heavy-Light decomposition . . . 14
3.11 Centroid decomposition . . . 14
3.12 Parallel DFS . . . 14
3.13 Eulerian path . . . 15
3.14 Dynamic connectivity . . . 15
3.15 Dominator tree . . . 16
3.16 Edmond's blossom (matching in general graphs) . . . 17

4 Math **17**
4.1 Identities . . . 17
4.2 Theorems . . . 18
4.3 Integer floor division . . . 18
4.4 Sieve of Eratosthenes . . . 18
4.5 Generate divisors . . . 18
4.6 Pollard's rho . . . 18
4.7 Simpson's rule . . . 19
4.8 Polynomials . . . 19
4.9 Bairstow . . . 20
4.10 Fast Fourier Transform . . . 21
4.11 FFT operations . . . 22
4.12 Fast Hadamard Transform . . . 24
4.13 Karatsuba . . . 25
4.14 Diophantine . . . 25
4.15 Modular inverse . . . 25
4.16 Chinese remainder theorem . . . 25
4.17 Mobius . . . 26
4.18 Matrix exponentiation . . . 26
4.19 Matrix reduce and determinant . . . 26
4.20 Simplex . . . 26
4.21 Discrete log . . . 27
4.22 Berlekamp Massey . . . 27
4.23 Linear Rec . . . 28
4.24 Tonelli Shanks . . . 28
4.25 Prime count . . . 28

5 Geometry **29**

5.1 Point . . . 29
5.2 Line . . . 29
5.3 Circle . . . 30
5.4 Polygon . . . 31
5.5 Plane . . . 32
5.6 Radial order of points . . . 32
5.7 Convex hull . . . 33
5.8 Dual from planar graph . . . 33
5.9 Halfplane intersection . . . 33
5.10 KD tree . . . 34
5.11 Minkowski sum . . . 34
5.12 Delaunay triangulation . . . 34

6 Strings **36**
6.1 KMP . . . 36
6.2 Z function . . . 36
6.3 Manacher . . . 36
6.4 Aho-Corasick . . . 37
6.5 Suffix automaton . . . 37
6.6 Palindromic Tree . . . 37
6.7 Suffix array (shorter but slower) . . . 38
6.8 Suffix array . . . 38
6.9 LCP (Longest Common Prefix) . . . 38
6.10 Suffix Tree (Ukkonen's algorithm) . . . 39
6.11 Hashing . . . 39
6.12 Hashing with ll (using __int128) . . . 39

7 Flow **40**
7.1 Matching (slower) . . . 40
7.2 Matching (Hopcroft-Karp) . . . 40
7.3 Hungarian . . . 40
7.4 Dinic . . . 41
7.5 Min cost max flow . . . 41

8 Other **42**
8.1 Mo's algorithm . . . 42
8.2 Divide and conquer DP optimization . . . 42
8.3 Dates . . . 43
8.4 C++ stuff . . . 43
8.5 Interactive problem tester template . . . 44
8.6 Max number of divisors up to 10^n . . . 44
8.7 Template . . . 44

1 Algorithm Descriptions

1.1 Data Structures

- **Segment Tree**: Range queries and updates in $O(\log n)$. Lazy propagation for range updates.
- **Sparse Table**: Static Range Minimum Query (RMQ) in $O(1)$ with $O(n \log n)$ preprocessing.
- **Fenwick Tree**: Prefix sums and point updates in $O(\log n)$. Very low constant factor.
- **Treap**: Randomized binary search tree. Supports split/merge and implicit keys for sequence operations.
- **Link-Cut Tree**: Maintains a forest of trees under edge addition/deletion and path queries in $O(\log n)$.
- **Convex Hull Trick**: Maintains a set of lines to find min / max value at x in $O(\log n)$ or $O(1)$.
- **Li-Chao Tree**: Insert line/segments and query min / max at a point in $O(\log n)$.

1.2 Graphs

- **Tarjan / SCC**: Finds strongly connected components in directed graphs in $O(V+E)$.
- **Articulation Points/Bridges**: Finds vertices/edges whose removal increases connected components.
- **HLD**: Decomposes a tree into paths to perform range queries on paths in $O(\log^2 n)$.
- **Centroid Decomposition**: Divide and conquer on trees based on centroids for path-related problems.
- **Dominator Tree**: For a flowgraph, u dominates v if every path from start to v goes through u.
- **Blossom Algorithm**: Finds a maximum matching in general (non-bipartite) graphs in $O(V^2E)$.

1.3 Math

- **Pollard's Rho**: Integer factorization in $O(n^{1/4})$.
- **FFT / NTT**: Polynomial multiplication in $O(n \log n)$.
- **Berlekamp-Massey**: Finds the shortest linear recurrence for a given sequence.
- **Simplex**: Solves linear programming problems (optimization under constraints).
- **Chinese Remainder Theorem**: Solves systems of congruences with coprime moduli.

1.4 Strings

- **Aho-Corasick**: Multiple pattern matching using a trie-based automaton in $O(\sum |pattern|)$.
- **Suffix Automaton**: DFA that recognizes all substrings of a string in $O(n)$.
- **Palindromic Tree**: Maintains all unique palindromic substrings in $O(n)$.
- **Suffix Array**: Lexicographically sorted list of all suffixes of a string.

1.5 Flow

- **Dinic**: Maximum flow in $O(V^2E)$, much faster in unit networks or bipartite matching.
- **MCMF**: Minimum cost maximum flow using SPFA or Dijkstra with potentials.
- **Hungarian**: Solves the assignment problem (perfect matching in bipartite graphs) in $O(n^3)$.

2 Data structures

2.1 Segment tree

```cpp
#define oper min
#define NEUT INF
struct STree { // segment tree for min over integers
  vector<int> st;int n;
  STree(int n): st(4*n+5,NEUT), n(n) {}
  void init(int k, int s, int e, int *a){
    if(s+1==e){st[k]=a[s];return;}
    int m=(s+e)/2;
    init(2*k,s,m,a);init(2*k+1,m,e,a);
    st[k]=oper(st[2*k],st[2*k+1]);
  }
  void upd(int k, int s, int e, int p, int v){
    if(s+1==e){st[k]=v;return;}
    int m=(s+e)/2;
    if(p<m)upd(2*k,s,m,p,v);
    else upd(2*k+1,m,e,p,v);
    st[k]=oper(st[2*k],st[2*k+1]);
  }
  int query(int k, int s, int e, int a, int b){
    if(s>=b||e<=a)return NEUT;
    if(s>=a&&e<=b)return st[k];
    int m=(s+e)/2;
    return oper(query(2*k,s,m,a,b),query(2*k+1,m,e,a,b));
  }
  void init(int *a){init(1,0,n,a);}
  void upd(int p, int v){upd(1,0,n,p,v);}
  int query(int a, int b){return query(1,0,n,a,b);}
}; // usage: STree rmq(n);rmq.init(x);rmq.upd(i,v);rmq.query(s,e);
```

2.2 Segment tree - Lazy propagation

```cpp
struct STree { // example: range sum with range addition
  vector<int> st,lazy;int n;
  STree(int n): st(4*n+5,0), lazy(4*n+5,0), n(n) {}
  void init(int k, int s, int e, int *a){
    lazy[k]=0;  // lazy neutral element
    if(s+1==e){st[k]=a[s];return;}
    int m=(s+e)/2;
    init(2*k,s,m,a);init(2*k+1,m,e,a);
```

```
    st[k]=st[2*k]+st[2*k+1]; // operation
  }
  void push(int k, int s, int e){
    if(!lazy[k])return; // if neutral, nothing to do
    st[k]+=(e-s)*lazy[k]; // update st according to lazy
    if(s+1<e){ // propagate to children
      lazy[2*k]+=lazy[k];
      lazy[2*k+1]+=lazy[k];
    }
    lazy[k]=0; // clear node lazy
  }
  void upd(int k, int s, int e, int a, int b, int v){
    push(k,s,e);
    if(s>=b||e<=a)return;
    if(s>=a&&e<=b){
      lazy[k]+=v; // accumulate lazy
      push(k,s,e);return;
    }
    int m=(s+e)/2;
    upd(2*k,s,m,a,b,v);upd(2*k+1,m,e,a,b,v);
    st[k]=st[2*k]+st[2*k+1]; // operation
  }
  int query(int k, int s, int e, int a, int b){
    if(s>=b||e<=a)return 0; // operation neutral
    push(k,s,e);
    if(s>=a&&e<=b)return st[k];
    int m=(s+e)/2;
    return query(2*k,s,m,a,b)+query(2*k+1,m,e,a,b); // operation
  }
  void init(int *a){init(1,0,n,a);}
  void upd(int a, int b, int v){upd(1,0,n,a,b,v);}
  int query(int a, int b){return query(1,0,n,a,b);}
}; // usage: STree rmq(n);rmq.init(x);rmq.upd(s,e,v);rmq.query(s,e);
```

2.3 Segment tree - Persistence

```
#define oper(a,b) min(a,b)
#define NEUT INF
struct STree { // persistent segment tree for min over integers
  vector<int> st, L, R; int n,sz,rt;
  STree(int n): st(1,NEUT),L(1,0),R(1,0),n(n),rt(0),sz(1){}
  int new_node(int v, int l=0, int r=0){
    int ks=((int)(st).size());
    st.push_back(v);L.push_back(l);R.push_back(r);
    return ks;
  }
  int init(int s, int e, int *a){ // not necessary in most cases
    if(s+1==e)return new_node(a[s]);
    int m=(s+e)/2,l=init(s,m,a),r=init(m,e,a);
    return new_node(oper(st[l],st[r]),l,r);
  }
  int upd(int k, int s, int e, int p, int v){
    int ks=new_node(st[k],L[k],R[k]);
    if(s+1==e){st[ks]=v;return ks;}
    int m=(s+e)/2,ps;
    if(p<m)ps=upd(L[ks],s,m,p,v),L[ks]=ps;
    else ps=upd(R[ks],m,e,p,v),R[ks]=ps;
    st[ks]=oper(st[L[ks]],st[R[ks]]);
    return ks;
  }
  int query(int k, int s, int e, int a, int b){
    if(e<=a||b<=s)return NEUT;
    if(a<=s&&e<=b)return st[k];
    int m=(s+e)/2;
    return oper(query(L[k],s,m,a,b),query(R[k],m,e,a,b));
  }
  int init(int *a){return init(0,n,a);}
  int upd(int k, int p, int v){return rt=upd(k,0,n,p,v);}
  int upd(int p, int v){return upd(rt,p,v);} // update on last root
  int query(int k,int a, int b){return query(k,0,n,a,b);};
}; // usage: STree rmq(n);root=rmq.init(x);new_root=rmq.upd(root,i,v);
    rmq.query(root,s,e);
```

2.4 Segment tree - 2D

```
int n,m;
int a[MAXN][MAXN],st[2*MAXN][2*MAXN];
void build(){
  for (int i = 0, _n = n; i < _n; ++i)for (int j = 0, _n = m; j < _n; ++
      j)st[i+n][j+m]=a[i][j];
  for (int i = 0, _n = n; i < _n; ++i)for(int j=m-1;j;--j)
    st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
  for(int i=n-1;i;--i)for (int j = 0, _n = 2*m; j < _n; ++j)
    st[i][j]=op(st[i<<1][j],st[i<<1|1][j]);
}
void upd(int x, int y, int v){
```

```
  st[x+n][y+m]=v;
  for(int j=y+m;j>1;j>>=1)st[x+n][j>>1]=op(st[x+n][j],st[x+n][j^1]);
  for(int i=x+n;i>1;i>>=1)for(int j=y+m;j;j>>=1)
    st[i>>1][j]=op(st[i][j],st[i^1][j]);
}
int query(int x0, int x1, int y0, int y1){
  int r=NEUT;
  for(int i0=x0+n,i1=x1+n;i0<i1;i0>>=1,i1>>=1){
    int t[4],q=0;
    if(i0&1)t[q++]=i0++;
    if(i1&1)t[q++]=--i1;
    for (int k = 0, _n = q; k < _n; ++k)for(int j0=y0+m,j1=y1+m;j0<j1;j0
        >>=1,j1>>=1){
      if(j0&1)r=op(r,st[t[k]][j0++]);
      if(j1&1)r=op(r,st[t[k]][--j1]);
    }
  }
  return r;
}
```

2.5 Sparse table (static RMQ)

```
#define oper min
int st[K][1<<K];int n;  // K such that 2^K>n
void st_init(int *a){
  for (int i = 0, _n = n; i < _n; ++i)st[0][i]=a[i];
  for (int k = 1, _n = K; k < _n; ++k)for (int i = 0, _n = n-(1<<k; i <
      _n; ++i)+1)
    st[k][i]=oper(st[k-1][i],st[k-1][i+(1<<(k-1))]);
}
int st_query(int s, int e){
  int k=31-__builtin_clz(e-s);
  return oper(st[k][s],st[k][e-(1<<k)]);
}
```

2.6 Fenwick tree

```
int ft[MAXN+1]; // for more dimensions, make ft multi-dimensional
void upd(int i0, int v){ // add v to i0th element (0-based)
  // add extra fors for more dimensions
  for(int i=i0+1;i<=MAXN;i+=i&-i)ft[i]+=v;
}
int get(int i0){ // get sum of range [0,i0)
  int r=0;
  // add extra fors for more dimensions
  for(int i=i0;i;i-=i&-i)r+=ft[i];
  return r;
}
int get_sum(int i0, int i1){ // get sum of range [i0,i1) (0-based)
  return get(i1)-get(i0);
}
```

2.7 Wavelet tree

```
struct WT {
  vector<int> wt[1<<20];int n;
  void init(int k, int s, int e){
    if(s+1==e)return;
    wt[k].clear();wt[k].push_back(0);
    int m=(s+e)/2;
    init(2*k,s,m);init(2*k+1,m,e);
  }
  void add(int k, int s, int e, int v){
    if(s+1==e)return;
    int m=(s+e)/2;
    if(v<m)wt[k].push_back(wt[k].back()),add(2*k,s,m,v);
    else wt[k].push_back(wt[k].back()+1),add(2*k+1,m,e,v);
  }
  int query0(int k, int s, int e, int a, int b, int i){
    if(s+1==e)return s;
    int m=(s+e)/2;
    int q=(b-a)-(wt[k][b]-wt[k][a]);
    if(i<q)return query0(2*k,s,m,a-wt[k][a],b-wt[k][b],i);
    else return query0(2*k+1,m,e,wt[k][a],wt[k][b],i-q);
  }
  void upd(int k, int s, int e, int i){
    if(s+1==e)return;
    int m=(s+e)/2;
    int v0=wt[k][i+1]-wt[k][i],v1=wt[k][i+2]-wt[k][i+1];
    if(!v0&&!v1)upd(2*k,s,m,i-wt[k][i]);
    else if(v0&&v1)upd(2*k+1,m,e,wt[k][i]);
    else if(v0)wt[k][i+1]--;
    else wt[k][i+1]++;
  }
  void init(int _n){n=_n;init(1,0,n);} // (values in range [0,n))
  void add(int v){add(1,0,n,v);}
  int query0(int a, int b, int i){ // ith element in range [a,b)
```

```
    return query0(1,0,n,a,b,i);    // (if it was sorted)
  }
  void upd(int i){ // swap positions i,i+1
    upd(1,0,n,i);
  }
};
```

2.8 STL extended set

```
#include<ext/pb_ds/assoc_container.hpp>
#include<ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
typedef tree<int,null_type,less<int>,rb_tree_tag,
    tree_order_statistics_node_update> ordered_set;
// find_by_order(i) -> iterator to ith element
// order_of_key(k) -> position (int) of lower_bound of k
```

2.9 STL rope

```
#include <ext/rope>
using namespace __gnu_cxx;
rope<int> s;
// Sequence with O(log(n)) random access, insert, erase at any position
// s.push_back(x);
// s.insert(i,r) // insert rope r at position i
// s.erase(i,k) // erase subsequence [i,i+k)
// s.substr(i,k) // return new rope corresponding to subsequence [i,i+k)
// s[i] // access ith element (cannot modify)
// s.mutable_reference_at(i) // acces ith element (allows modification)
// s.begin() and s.end() are const iterators (use mutable_begin(),
    mutable_end() to allow modification)
```

2.10 Treap (as BST)

```
typedef struct item *pitem;
struct item {
  int pr,key,cnt;
  pitem l,r;
  item(int key):key(key),pr(rand()),cnt(1),l(0),r(0) {}
};
int cnt(pitem t){return t?t->cnt:0;}
void upd_cnt(pitem t){if(t)t->cnt=cnt(t->l)+cnt(t->r)+1;}
void split(pitem t, int key, pitem& l, pitem& r){ // l: < key, r: >= key
  if(!t)l=r=0;
  else if(key<t->key)split(t->l,key,l,t->l),r=t;
  else split(t->r,key,t->r,r),l=t;
  upd_cnt(t);
}
void insert(pitem& t, pitem it){
  if(!t)t=it;
  else if(it->pr>t->pr)split(t,it->key,it->l,it->r),t=it;
  else insert(it->key<t->key?t->l:t->r,it);
  upd_cnt(t);
}
void merge(pitem& t, pitem l, pitem r){
  if(!l||!r)t=l?l:r;
  else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
  else merge(r->l,l,r->l),t=r;
  upd_cnt(t);
}
void erase(pitem& t, int key){
  if(t->key==key)merge(t,t->l,t->r);
  else erase(key<t->key?t->l:t->r,key);
  upd_cnt(t);
}
void unite(pitem &t, pitem l, pitem r){
  if(!l||!r){t=l?l:r;return;}
  if(l->pr<r->pr)swap(l,r);
  pitem p1,p2;split(r,l->key,p1,p2);
  unite(l->l,l->l,p1);unite(l->r,l->r,p2);
  t=l;upd_cnt(t);
}
pitem kth(pitem t, int k){
  if(!t)return 0;
  if(k==cnt(t->l))return t;
  return k<cnt(t->l)?kth(t->l,k):kth(t->r,k-cnt(t->l)-1);
}
pair<int,int> lb(pitem t, int key){ // position and value of lower_bound
  if(!t)return {0,1<<30}; // (special value)
  if(key>t->key){
    auto w=lb(t->r,key);w.first+=cnt(t->l)+1;return w;
  }
  auto w=lb(t->l,key);
  if(w.first==cnt(t->l))w.second=t->key;
  return w;
}
```

2.11 Treap (implicit key)

```
// example that supports range reverse and addition updates, and range sum query
// (commented parts are specific to this  problem)
typedef struct item *pitem;
struct item {
  int pr,cnt,val;
//  int sum; // (paramters for range query)
//  bool rev;int add; // (parameters for lazy prop)
  pitem l,r;
  item(int val): pr(rand()),cnt(1),val(val),l(0),r(0)/*,sum(val),rev(0),add(0)*/ {}
};
void push(pitem it){
  if(it){
    /*if(it->rev){
      swap(it->l,it->r);
      if(it->l)it->l->rev^=true;
      if(it->r)it->r->rev^=true;
      it->rev=false;
    }
    it->val+=it->add;it->sum+=it->cnt*it->add;
    if(it->l)it->l->add+=it->add;
    if(it->r)it->r->add+=it->add;
    it->add=0;*/
  }
}
int cnt(pitem t){return t?t->cnt:0;}
// int sum(pitem t){return t?push(t),t->sum:0;}
void upd_cnt(pitem t){
  if(t){
    t->cnt=cnt(t->l)+cnt(t->r)+1;
    // t->sum=t->val+sum(t->l)+sum(t->r);
  }
}
void merge(pitem& t, pitem l, pitem r){
  push(l);push(r);
  if(!l||!r)t=l?l:r;
  else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
  else merge(r->l,l,r->l),t=r;
  upd_cnt(t);
}
void split(pitem t, pitem& l, pitem& r, int sz){ // sz:desired size of l
  if(!t){l=r=0;return;}
  push(t);
  if(sz<=cnt(t->l))split(t->l,l,t->l,sz),r=t;
  else split(t->r,t->r,r,sz-1-cnt(t->l)),l=t;
  upd_cnt(t);
}
void output(pitem t){ // useful for debugging
  if(!t)return;
  push(t);
  output(t->l);printf(" %d",t->val);output(t->r);
}
// use merge and split for range updates and queries
```

2.12 Treap (with node father)

```
// node father is useful to keep track of the chain of each node
// alternative: splay tree
// IMPORTANT: add pointer f in struct item
void merge(pitem& t, pitem l, pitem r){
  push(l);push(r);
  if(!l||!r)t=l?l:r;
  else if(l->pr>r->pr)merge(l->r,l->r,r),l->r->f=t=l;
  else merge(r->l,l,r->l),r->l->f=t=r;
  upd_cnt(t);
}
void split(pitem t, pitem& l, pitem& r, int sz){
  if(!t){l=r=0;return;}
  push(t);
  if(sz<=cnt(t->l)){
    split(t->l,l,t->l,sz);r=t;
    if(l)l->f=0;
    if(t->l)t->l->f=t;
  }
  else {
    split(t->r,t->r,r,sz-1-cnt(t->l));l=t;
    if(r)r->f=0;
    if(t->r)t->r->f=t;
  }
  upd_cnt(t);
}
void push_all(pitem t){
  if(t->f)push_all(t->f);
```

```
  push(t);
}
pitem root(pitem t, int& pos){ // get root and position for node t
  push_all(t);
  pos=cnt(t->l);
  while(t->f){
    pitem f=t->f;
    if(t==f->r)pos+=cnt(f->l)+1;
    t=f;
  }
  return t;
}
```

2.13 Link-Cut tree

```
typedef struct item *pitem;
struct item {
  int pr;bool rev;
  pitem l,r,f,d;
  item():pr(rand()),l(0),r(0),f(0),d(0),rev(0){}
};
void push(pitem t){
  if(t&&t->rev){
    swap(t->l,t->r);
    if(t->l)t->l->rev^=1;
    if(t->r)t->r->rev^=1;
    t->rev=0;
  }
}
void merge(pitem& t, pitem l, pitem r){
  push(l);push(r);
  if(!l||!r)t=l?l:r;
  else if(l->pr>r->pr)merge(l->r,l->r,r),l->r->f=t=l;
  else merge(r->l,l,r->l),r->l->f=t=r;
}
void push_all(pitem t){
  if(t->f)push_all(t->f);
  push(t);
}
void split(pitem t, pitem& l, pitem& r){
  push_all(t);
  l=t->l;r=t->r;t->l=t->r=0;
  while(t->f){
    pitem f=t->f;t->f=0;
    if(t==f->l){
      if(r)r->f=f;
      f->l=r;r=f;
    }
    else {
      if(l)l->f=f;
      f->r=l;l=f;
    }
    t=f;
  }
  if(l)l->f=0;
  if(r)r->f=0;
}
pitem path(pitem p){return p->f?path(p->f):p;}
pitem tail(pitem p){push(p);return p->r?tail(p->r):p;}
pitem expose(pitem p){
  pitem q,r,t;
  split(p,q,r);
  if(q)tail(q)->d=p;
  merge(p,p,r);
  while(t=tail(p),t->d){
    pitem d=t->d;t->d=0;
    split(d,q,r);
    if(q)tail(q)->d=d;
    merge(p,p,d);merge(p,p,r);
  }
  return p;
}
pitem root(pitem v){return tail(expose(v));}
void evert(pitem v){expose(v)->rev^=1;v->d=0;}
void link(pitem v, pitem w){ // make v son of w
  evert(v);
  pitem p=path(v);
  merge(p,p,expose(w));
}
void cut(pitem v){ // cut v from its father
  pitem p,q;
  expose(v);split(v,p,q);v->d=0;
}
void cut(pitem v, pitem w){evert(w);cut(v);}
```

2.14 Convex hull trick (static)

```
typedef ll tc;
struct Line{tc m,h;};
struct CHT { // for minimum (for maximum just change the sign of lines)
  vector<Line> c;
  int pos=0;
  tc in(Line a, Line b){
    tc x=b.h-a.h,y=a.m-b.m;
    return x/y+(x%y?!((x>0)^(y>0)):0); // ==ceil(x/y)
  }
  void add(tc m, tc h){ // m's should be non increasing
    Line l=(Line){m,h};
    if(c.size()&&m==c.back().m){
      l.h=min(h,c.back().h);c.pop_back();if(pos)pos--;
    }
    while(c.size()>1&&in(c.back(),l)<=in(c[c.size()-2],c.back())){
      c.pop_back();if(pos)pos--;
    }
    c.push_back(l);
  }
  inline bool fbin(tc x, int m){return in(c[m],c[m+1])>x;}
  tc eval(tc x){
    // O(log n) query:
    int s=0,e=c.size();
    while(e-s>1){int m=(s+e)/2;
      if(fbin(x,m-1))e=m;
      else s=m;
    }
    return c[s].m*x+c[s].h;
    // O(1) query (for ordered x's):
    while(pos>0&&fbin(x,pos-1))pos--;
    while(pos<c.size()-1&&!fbin(x,pos))pos++;
    return c[pos].m*x+c[pos].h;
  }
};
```

2.15 Convex hull trick (dynamic)

```
typedef ll tc;
const tc is_query=-(1LL<<62); // special value for query
struct Line {
  tc m,b;
  mutable multiset<Line>::iterator it,end;
  const Line* succ(multiset<Line>::iterator it) const {
    return (++it==end? NULL : &*it);}
  bool operator<(const Line& rhs) const {
    if(rhs.b!=is_query)return m<rhs.m;
    const Line *s=succ(it);
    if(!s)return 0;
    return b-s->b<(s->m-m)*rhs.m;
  }
};
struct HullDynamic : public multiset<Line> { // for maximum
  bool bad(iterator y){
    iterator z=next(y);
    if(y==begin()){
      if(z==end())return false;
      return y->m==z->m&&y->b<=z->b;
    }
    iterator x=prev(y);
    if(z==end())return y->m==x->m&&y->b<=x->b;
    return (x->b-y->b)*(z->m-y->m)>=(y->b-z->b)*(y->m-x->m);
  }
  iterator next(iterator y){return ++y;}
  iterator prev(iterator y){return --y;}
  void add(tc m, tc b){
    iterator y=insert((Line){m,b});
    y->it=y;y->end=end();
    if(bad(y)){erase(y);return;}
    while(next(y)!=end()&&bad(next(y)))erase(next(y));
    while(y!=begin()&&bad(prev(y)))erase(prev(y));
  }
  tc eval(tc x){
    Line l=*lower_bound((Line){x,is_query});
    return l.m*x+l.b;
  }
};
```

2.16 Li-Chao tree

```
// LiChaoTree lct(sz) -> allows queries for all x in range [0,sz)
// lct.add(L)         -> add line L to range [0,sz) in O(log(sz))
// lct.add(L,st,en)   -> add line L to range [st,en) in O(log^2(sz))
// lct.query(x)       -> query maximum L(x) across all current lines in
    O(log(sz))
```

```cpp

typedef long long T;
T INF=1e18;

struct Line{
  T a, b;
  Line():a(0),b(-INF){}
  Line(T a, T b):a(a),b(b){}
  T get(T x){return a*x+b;}
};

struct LiChaoTree{
  struct Node{
    Line line;
    Node *lc,*rc=0;
  }*root;
  int sz;
  LiChaoTree(int sz): root(new Node()), sz(sz){}

  void addRec(Node* &n, int tl, int tr, Line x){
    if(!n) n=new Node();
    if(n->line.get(tl)<x.get(tl)) swap(n->line,x);
    if(n->line.get(tr-1)>=x.get(tr-1)||tl+1==tr) return;
    int mid=(tl+tr)/2;
    if(n->line.get(mid)>x.get(mid)){
      addRec(n->rc,mid,tr,x);
    }
    else{
      swap(n->line,x);
      addRec(n->lc,tl,mid,x);
    }
  }

  void add(Node* &n, int tl, int tr, int l, int r, Line x){
    if(tr<=l||r<=tl) return;
    if(!n) n=new Node();
    if(l<=tl&&tr<=r) return addRec(n,tl,tr,x);
    int mid=(tl+tr)/2;
    add(n->lc,tl,mid,l,r,x);
    add(n->rc,mid,tr,l,r,x);
  }

  T query(Node* &n, int tl, int tr, int x){
    if(!n) return -INF;
    if(tl+1==tr) return n->line.get(x);
    T res=n->line.get(x);
    int mid=(tl+tr)/2;
    if(x<mid) res=max(res, query(n->lc,tl,mid,x));
    else res=max(res, query(n->rc,mid,tr,x));
    return res;
  }

  void add(Line x){add(root,0,sz,0,sz,x);}
  void add(Line x, int l, int r){add(root,0,sz,l,r,x);}
  T query(int x){return query(root,0,sz,x);}
};
```

2.17 Gain-cost-set

```cpp
// stores pairs (benefit,cost) (erases non-optimal pairs)
struct GCS {
  set<pair<int,int> > s;
  void add(int g, int c){
    pair<int,int> x={g,c};
    auto p=s.lower_bound(x);
    if(p!=s.end()&&p->second<=x.second)return;
    if(p!=s.begin()){ // erase pairs with less benefit
      --p;            // and more cost
      while(p->second>=x.second){
        if(p==s.begin()){s.erase(p);break;}
        s.erase(p--);
      }
    }
    s.insert(x);
  }
  int get(int gain){ // min cost for some benefit
    auto p=s.lower_bound((pair<int,int>){gain,-INF});
    int r=p==s.end()?INF:p->second;
    return r;
  }
};
```

2.18 Disjoint intervals

```cpp
// stores disjoint intervals as [first, second)
struct disjoint_intervals {
  set<pair<int,int> > s;
```

```
  void insert(pair<int,int> v){
    if(v.first>=v.second) return;
    auto at=s.lower_bound(v);auto it=at;
    if(at!=s.begin()&&(--at)->second>=v.first)v.first=at->first,--it;
    for(;it!=s.end()&&it->first<=v.second;s.erase(it++))
      v.second=max(v.second,it->second);
    segs.insert(v);
  }
};
```

3 Graphs

3.1 Topological sort

```
vector<int> g[MAXN];int n;
vector<int> tsort(){  // lexicographically smallest topological sort
  vector<int> r;priority_queue<int> q;
  vector<int> d(2*n,0);
  for (int i = 0, _n = n; i < _n; ++i)for (int j = 0, _n = g[i].size(; j
       < _n; ++j))d[g[i][j]]++;
  for (int i = 0, _n = n; i < _n; ++i)if(!d[i])q.push(-i);
  while(!q.empty()){
    int x=-q.top();q.pop();r.push_back(x);
    for (int i = 0, _n = g[x].size(; i < _n; ++i)){
      d[g[x][i]]--;
      if(!d[g[x][i]])q.push(-g[x][i]);
    }
  }
  return r;  // if not DAG it will have less than n elements
}
```

3.2 Kruskal (+ Union-Find)

```
int uf[MAXN];
void uf_init(){memset(uf,-1,sizeof(uf));}
int uf_find(int x){return uf[x]<0?x:uf[x]=uf_find(uf[x]);}
bool uf_join(int x, int y){
  x=uf_find(x);y=uf_find(y);
  if(x==y)return false;
  if(uf[x]>uf[y])swap(x,y);
  uf[x]+=uf[y];uf[y]=x;
  return true;
}
vector<pair<ll,pair<int,int> > > es; // edges (cost,(u,v))
ll kruskal(){  // assumes graph is connected
  sort(es.begin(),es.end());uf_init();
  ll r=0;
  for (int i = 0, _n = es.size(; i < _n; ++i)){
    int x=es[i].second.first,y=es[i].second.second;
    if(uf_join(x,y))r+=es[i].first; // (x,y,c) belongs to mst
  }
  return r; // total cost
}
```

3.3 Dijkstra

```
vector<pair<int,int> > g[MAXN];  // u->[(v,cost)]
ll dist[MAXN];
void dijkstra(int x){
  memset(dist,-1,sizeof(dist));
  priority_queue<pair<ll,int> > q;
  dist[x]=0;q.push({0,x});
  while(!q.empty()){
    x=q.top().second;ll c=-q.top().first;q.pop();
    if(dist[x]!=c)continue;
    for (int i = 0, _n = g[x].size(; i < _n; ++i)){
      int y=g[x][i].first; ll c=g[x][i].second;
      if(dist[y]<0||dist[x]+c<dist[y])
        dist[y]=dist[x]+c,q.push({-dist[y],y});
    }
  }
}
```

3.4 Bellman-Ford

```
int n;
vector<pair<int,int> > g[MAXN]; // u->[(v,cost)]
ll dist[MAXN];
void bford(int src){ // O(nm)
  fill(dist,dist+n,INF);dist[src]=0;
  for (int _ = 0, _n = n; _ < _n; ++_)for (int x = 0, _n = n; x < _n; ++
      x)if(dist[x]!=INF)for(auto t:g[x]){
    dist[t.first]=min(dist[t.first],dist[x]+t.second);
  }
  for (int x = 0, _n = n; x < _n; ++x)if(dist[x]!=INF)for(auto t:g[x]){
    if(dist[t.first]>dist[x]+t.second){
      // neg cycle: all nodes reachable from t.first have -INF distance
```

```
      // to reconstruct neg cycle: save "prev" of each node, go up from t.first until repeating a node. this node and all nodes between the two occurences form a neg cycle
    }
  }
}
```

3.5 Floyd-Warshall

```
// g[i][j]: weight of edge (i, j) or INF if there's no edge
// g[i][i]=0
ll g[MAXN][MAXN];int n;
void floyd(){ // O(n^3) . Replaces g with min distances
  for (int k = 0, _n = n; k < _n; ++k)for (int i = 0, _n = n; i < _n; ++i)if(g[i][k]<INF)for (int j = 0, _n = n; j < _n; ++j)if(g[k][j]<INF)
    g[i][j]=min(g[i][j],g[i][k]+g[k][j]);
}
bool inNegCycle(int v){return g[v][v]<0;}
bool hasNegCycle(int a, int b){ // true iff there's neg cycle in between
  for (int i = 0, _n = n; i < _n; ++i)if(g[a][i]<INF&&g[i][b]<INF&&g[i][i]<0)return true;
  return false;
}
```

3.6 Strongly connected components (+ 2-SAT)

```
// MAXN: max number of nodes or 2 * max number of variables (2SAT)
bool truth[MAXN]; // truth[cmp[i]]=value of variable i (2SAT)
int nvar;int neg(int x){return MAXN-1-x;} // (2SAT)
vector<int> g[MAXN];
int n,lw[MAXN],idx[MAXN],qidx,cmp[MAXN],qcmp;
stack<int> st;
void tjn(int u){
  lw[u]=idx[u]=++qidx;
  st.push(u);cmp[u]=-2;
  for(int v:g[u]){
    if(!idx[v]||cmp[v]==-2){
      if(!idx[v]) tjn(v);
      lw[u]=min(lw[u],lw[v]);
    }
  }
  if(lw[u]==idx[u]){
    int x,l=-1;
    do{x=st.top();st.pop();cmp[x]=qcmp;if(min(x,neg(x))<nvar)l=x;}
    while(x!=u);
    if(l!=-1)truth[qcmp]=(cmp[neg(l)]<0); // (2SAT)
    qcmp++;
  }
}
void scc(){
  memset(idx,0,sizeof(idx));qidx=0;
  memset(cmp,-1,sizeof(cmp));qcmp=0;
  for (int i = 0, _n = n; i < _n; ++i)if(!idx[i])tjn(i);
}
// Only for 2SAT:
void addor(int a, int b){g[neg(a)].push_back(b);g[neg(b)].push_back(a);}
bool satisf(int _nvar){
  nvar=_nvar;n=MAXN;scc();
  for (int i = 0, _n = nvar; i < _n; ++i)if(cmp[i]==cmp[neg(i)])return false;
  return true;
}
```

3.7 Articulation - Bridges - Biconnected

```
vector<int> g[MAXN];int n;
struct edge {int u,v,comp;bool bridge;};
vector<edge> e;
void add_edge(int u, int v){
  g[u].push_back(e.size());g[v].push_back(e.size());
  e.push_back((edge){u,v,-1,false});
}
int D[MAXN],B[MAXN],T;
int nbc;  // number of biconnected components
int art[MAXN];  // articulation point iff !=0
stack<int> st;  // only for biconnected
void dfs(int u,int pe){
  B[u]=D[u]=T++;
  for(int ne:g[u])if(ne!=pe){
    int v=e[ne].u^e[ne].v^u;
    if(D[v]<0){
      st.push(ne);dfs(v,ne);
      if(B[v]>D[u])e[ne].bridge = true; // bridge
      if(B[v]>=D[u]){
        art[u]++; // articulation
        int last; // start biconnected
```

```
        do {
          last=st.top();st.pop();
          e[last].comp=nbc;
        } while(last!=ne);
        nbc++;    // end biconnected
      }
      B[u]=min(B[u],B[v]);
    }
    else if(D[v]<D[u])st.push(ne),B[u]=min(B[u],D[v]);
  }
}
void doit(){
  memset(D,-1,sizeof(D));memset(art,0,sizeof(art));
  nbc=T=0;
  for (int i = 0, _n = n; i < _n; ++i)if(D[i]<0)dfs(i,-1),art[i]--;
}
```

3.8 Chu-Liu (minimum spanning arborescence)

```
//O(n*m) minimum spanning tree in directed graph
//returns -1 if not possible
//included i-th edge if take[i]!=0
typedef int tw; tw INF=1ll<<30;
struct edge{int u,v,id;tw len;};
struct ChuLiu{
  int n; vector<edge> e;
  vector<int> inc,dec,take,pre,num,id,vis;
  vector<tw> inw;
  void add_edge(int x, int y, tw w){
    inc.push_back(0); dec.push_back(0); take.push_back(0);
    e.push_back({x,y,((int)(e).size()),w});
  }
  ChuLiu(int n):n(n),pre(n),num(n),id(n),vis(n),inw(n){}
  tw doit(int root){
    auto e2=e;
    tw ans=0; int eg=((int)(e).size())-1,pos=((int)(e).size())-1;
    while(1){
      for (int i = 0, _n = n; i < _n; ++i) inw[i]=INF,id[i]=vis[i]=-1;
      for(auto ed:e2) if(ed.len<inw[ed.v]){
        inw[ed.v]=ed.len; pre[ed.v]=ed.u;
        num[ed.v]=ed.id;
      }
      inw[root]=0;
      for (int i = 0, _n = n; i < _n; ++i) if(inw[i]==INF) return -1;
      int tot=-1;
      for (int i = 0, _n = n; i < _n; ++i){
        ans+=inw[i];
        if(i!=root)take[num[i]]++;
        int j=i;
        while(vis[j]!=i&&j!=root&&id[j]<0)vis[j]=i,j=pre[j];
        if(j!=root&&id[j]<0){
          id[j]=++tot;
          for(int k=pre[j];k!=j;k=pre[k]) id[k]=tot;
        }
      }
      if(tot<0)break;
      for (int i = 0, _n = n; i < _n; ++i) if(id[i]<0)id[i]=++tot;
      n=tot+1; int j=0;
      for (int i = 0, _n = ((int)(e2; i < _n; ++i).size())){
        int v=e2[i].v;
        e2[j].v=id[e2[i].v];
        e2[j].u=id[e2[i].u];
        if(e2[j].v!=e2[j].u){
          e2[j].len=e2[i].len-inw[v];
          inc.push_back(e2[i].id);
          dec.push_back(num[v]);
          take.push_back(0);
          e2[j++].id=++pos;
        }
      }
      e2.resize(j);
      root=id[root];
    }
    while(pos>eg){
      if(take[pos]>0) take[inc[pos]]++, take[dec[pos]]--;
      pos--;
    }
    return ans;
  }
};
```

3.9 LCA - Binary Lifting

```
vector<int> g[1<<K];int n;  // K such that 2^K>=n
int F[K][1<<K],D[1<<K];
void lca_dfs(int x){
```

```
  for (int i = 0, _n = g[x].size(; i < _n; ++i)){
    int y=g[x][i];if(y==F[0][x])continue;
    F[0][y]=x;D[y]=D[x]+1;lca_dfs(y);
  }
}
void lca_init(){
  D[0]=0;F[0][0]=-1;
  lca_dfs(0);
  for (int k = 1, _n = K; k < _n; ++k)for (int x = 0, _n = n; x < _n; ++
      x)
    if(F[k-1][x]<0)F[k][x]=-1;
    else F[k][x]=F[k-1][F[k-1][x]];
}
int lca(int x, int y){
  if(D[x]<D[y])swap(x,y);
  for(int k=K-1;k>=0;--k)if(D[x]-(1<<k)>=D[y])x=F[k][x];
  if(x==y)return x;
  for(int k=K-1;k>=0;--k)if(F[k][x]!=F[k][y])x=F[k][x],y=F[k][y];
  return F[0][x];
}
```

3.10 Heavy-Light decomposition

```
1  vector<int> g[MAXN];
2  int wg[MAXN],dad[MAXN],dep[MAXN]; // weight,father,depth
3  void dfs1(int x){
4    wg[x]=1;
5    for(int y:g[x])if(y!=dad[x]){
6      dad[y]=x;dep[y]=dep[x]+1;dfs1(y);
7      wg[x]+=wg[y];
8    }
9  }
10 int curpos,pos[MAXN],head[MAXN];
11 void hld(int x, int c){
12   if(c<0)c=x;
13   pos[x]=curpos++;head[x]=c;
14   int mx=-1;
15   for(int y:g[x])if(y!=dad[x]&&(mx<0||wg[mx]<wg[y]))mx=y;
16   if(mx>=0)hld(mx,c);
17   for(int y:g[x])if(y!=mx&&y!=dad[x])hld(y,-1);
18 }
19 void hld_init(){dad[0]=-1;dep[0]=0;dfs1(0);curpos=0;hld(0,-1);}
20 int query(int x, int y, STree& rmq){
21   int r=NEUT;
22   while(head[x]!=head[y]){
23     if(dep[head[x]]>dep[head[y]])swap(x,y);
24     r=oper(r,rmq.query(pos[head[y]],pos[y]+1));
25     y=dad[head[y]];
26   }
27   if(dep[x]>dep[y])swap(x,y); // now x is lca
28   r=oper(r,rmq.query(pos[x],pos[y]+1));
29   return r;
30 }
31 // for updating: rmq.upd(pos[x],v);
32 // queries on edges: - assign values of edges to "child" node
33 //                   - change pos[x] to pos[x]+1 in query (line 28)
```

3.11 Centroid decomposition

```
vector<int> g[MAXN];int n;
bool tk[MAXN];
int fat[MAXN]; // father in centroid decomposition
int szt[MAXN]; // size of subtree
int calcsz(int x, int f){
  szt[x]=1;
  for(auto y:g[x])if(y!=f&&!tk[y])szt[x]+=calcsz(y,x);
  return szt[x];
}
void cdfs(int x=0, int f=-1, int sz=-1){ // O(nlogn)
  if(sz<0)sz=calcsz(x,-1);
  for(auto y:g[x])if(!tk[y]&&szt[y]*2>=sz){
    szt[x]=0;cdfs(y,f,sz);return;
  }
  tk[x]=true;fat[x]=f;
  for(auto y:g[x])if(!tk[y])cdfs(y,x);
}
void centroid(){memset(tk,false,sizeof(tk));cdfs();}
```

3.12 Parallel DFS

```
struct Tree {
  int n,z[2];
  vector<vector<int>> g;
  vector<int> ex,ey,p,w,f,v[2];
  Tree(int n):g(n),w(n),f(n){}
  void add_edge(int x, int y){
```

```
    p.push_back(g[x].size());g[x].push_back(ex.size());ex.push_back(x);
        ey.push_back(y);
    p.push_back(g[y].size());g[y].push_back(ex.size());ex.push_back(y);
        ey.push_back(x);
  }
  bool go(int k){ // returns true if it finds new node
    int& x=z[k];
    while(x>=0&&
      (w[x]==g[x].size()||w[x]==g[x].size()-1&&(g[x].back()^1)==f[x]))
      x=f[x]>=0?ex[f[x]]:-1;
    if(x<0)return false;
    if((g[x][w[x]]^1)==f[x])w[x]++;
    int e=g[x][w[x]],y=ey[e];
    f[y]=e;w[x]++;w[y]=0;x=y;
    v[k].push_back(x);
    return true;
  }
  vector<int> erase_edge(int e){
    e*=2; // erases eth edge, returns smaller component
    int x=ex[e],y=ey[e];
    p[g[x].back()]=p[e];
    g[x][p[e]]=g[x].back();g[x].pop_back();
    p[g[y].back()]=p[e^1];
    g[y][p[e^1]]=g[y].back();g[y].pop_back();
    f[x]=f[y]=-1;
    w[x]=w[y]=0;
    z[0]=x;z[1]=y;
    v[0]={x};v[1]={y};
    bool d0=true,d1=true;
    while(d0&&d1)d0=go(0),d1=go(1);
    if(d1)return v[0];
    return v[1];
  }
};
```

3.13 Eulerian path

```
// Directed version (uncomment commented code for undirected)
struct edge {
  int y;
//  list<edge>::iterator rev;
  edge(int y):y(y){}
};
list<edge> g[MAXN];
void add_edge(int a, int b){
  g[a].push_front(edge(b));//auto ia=g[a].begin();
//  g[b].push_front(edge(a));auto ib=g[b].begin();
//  ia->rev=ib;ib->rev=ia;
}
vector<int> p;
void go(int x){
  while(g[x].size()){
    int y=g[x].front().y;
    //g[y].erase(g[x].front().rev);
    g[x].pop_front();
    go(y);
  }
  p.push_back(x);
}
vector<int> get_path(int x){ // get a path that begins in x
// check that a path exists from x before calling to get_path!
  p.clear();go(x);reverse(p.begin(),p.end());
  return p;
}
```

3.14 Dynamic connectivity

```
struct UnionFind {
  int n,comp;
  vector<int> uf,si,c;
  UnionFind(int n=0):n(n),comp(n),uf(n),si(n,1){
    for (int i = 0, _n = n; i < _n; ++i)uf[i]=i;}
  int find(int x){return x==uf[x]?x:find(uf[x]);}
  bool join(int x, int y){
    if((x=find(x))==(y=find(y)))return false;
    if(si[x]<si[y])swap(x,y);
    si[x]+=si[y];uf[y]=x;comp--;c.push_back(y);
    return true;
  }
  int snap(){return c.size();}
  void rollback(int snap){
    while(c.size()>snap){
      int x=c.back();c.pop_back();
      si[uf[x]]-=si[x];uf[x]=x;comp++;
    }
  }
```

```
};
enum {ADD,DEL,QUERY};
struct Query {int type,x,y;};
struct DynCon {
  vector<Query> q;
  UnionFind dsu;
  vector<int> mt;
  map<pair<int,int>,int> last;
  DynCon(int n):dsu(n){}
  void add(int x, int y){
    if(x>y)swap(x,y);
    q.push_back((Query){ADD,x,y});mt.push_back(-1);last[{x,y}]=q.size()
        -1;
  }
  void remove(int x, int y){
    if(x>y)swap(x,y);
    q.push_back((Query){DEL,x,y});
    int pr=last[{x,y}];mt[pr]=q.size()-1;mt.push_back(pr);
  }
  void query(){q.push_back((Query){QUERY,-1,-1});mt.push_back(-1);}
  void process(){ // answers all queries in order
    if(!q.size())return;
    for (int i = 0, _n = q.size(; i < _n; ++i))if(q[i].type==ADD&&mt[i
        ]<0)mt[i]=q.size();
    go(0,q.size());
  }
  void go(int s, int e){
    if(s+1==e){
      if(q[s].type==QUERY) // answer query using DSU
        printf("%d\n",dsu.comp);
      return;
    }
    int k=dsu.snap(),m=(s+e)/2;
    for(int i=e-1;i>=m;--i)if(mt[i]>=0&&mt[i]<s)dsu.join(q[i].x,q[i].y);
    go(s,m);dsu.rollback(k);
    for(int i=m-1;i>=s;--i)if(mt[i]>=e)dsu.join(q[i].x,q[i].y);
    go(m,e);dsu.rollback(k);
  }
};
```

3.15 Dominator tree

```
//idom[i]=parent of i in dominator tree with root=rt, or -1 if not
    exists
int n,rnk[MAXN],pre[MAXN],anc[MAXN],idom[MAXN],semi[MAXN],low[MAXN];
vector<int> g[MAXN],rev[MAXN],dom[MAXN],ord;
void dfspre(int pos){
  rnk[pos]=((int)(ord).size()); ord.push_back(pos);
  for(auto x:g[pos]){
    rev[x].push_back(pos);
    if(rnk[x]==n) pre[x]=pos,dfspre(x);
  }
}
int eval(int v){
  if(anc[v]<n&&anc[anc[v]]<n){
    int x=eval(anc[v]);
    if(rnk[semi[low[v]]]>rnk[semi[x]]) low[v]=x;
    anc[v]=anc[anc[v]];
  }
  return low[v];
}
void dominators(int rt){
  for (int i = 0, _n = n; i < _n; ++i){
    dom[i].clear(); rev[i].clear();
    rnk[i]=pre[i]=anc[i]=idom[i]=n;
    semi[i]=low[i]=i;
  }
  ord.clear(); dfspre(rt);
  for(int i=((int)(ord).size())-1;i;i--){
    int w=ord[i];
    for(int v:rev[w]){
      int u=eval(v);
      if(rnk[semi[w]]>rnk[semi[u]])semi[w]=semi[u];
    }
    dom[semi[w]].push_back(w); anc[w]=pre[w];
    for(int v:dom[pre[w]]){
      int u=eval(v);
      idom[v]=(rnk[pre[w]]>rnk[semi[u]]?u:pre[w]);
    }
    dom[pre[w]].clear();
  }
  for(int w:ord) if(w!=rt&&idom[w]!=semi[w]) idom[w]=idom[idom[w]];
  for (int i = 0, _n = n; i < _n; ++i) if(idom[i]==n)idom[i]=-1;
}
```

3.16 Edmond's blossom (matching in general graphs)

```
vector<int> g[MAXN];
int n,m,mt[MAXN],qh,qt,q[MAXN],ft[MAXN],bs[MAXN];
bool inq[MAXN],inb[MAXN],inp[MAXN];
int lca(int root, int x, int y){
  memset(inp,0,sizeof(inp));
  while(1){
    inp[x=bs[x]]=true;
    if(x==root)break;
    x=ft[mt[x]];
  }
  while(1){
    if(inp[y=bs[y]])return y;
    else y=ft[mt[y]];
  }
}
void mark(int z, int x){
  while(bs[x]!=z){
    int y=mt[x];
    inb[bs[x]]=inb[bs[y]]=true;
    x=ft[y];
    if(bs[x]!=z)ft[x]=y;
  }
}
void contr(int s, int x, int y){
  int z=lca(s,x,y);
  memset(inb,0,sizeof(inb));
  mark(z,x);mark(z,y);
  if(bs[x]!=z)ft[x]=y;
  if(bs[y]!=z)ft[y]=x;
  for (int x = 0, _n = n; x < _n; ++x)if(inb[bs[x]]){
    bs[x]=z;
    if(!inq[x])inq[q[++qt]=x]=true;
  }
}
int findp(int s){
  memset(inq,0,sizeof(inq));
  memset(ft,-1,sizeof(ft));
  for (int i = 0, _n = n; i < _n; ++i)bs[i]=i;
  inq[q[qh=qt=0]=s]=true;
  while(qh<=qt){
    int x=q[qh++];
    for(int y:g[x])if(bs[x]!=bs[y]&&mt[x]!=y){
      if(y==s||mt[y]>=0&&ft[mt[y]]>=0)contr(s,x,y);
      else if(ft[y]<0){
        ft[y]=x;
        if(mt[y]<0)return y;
        else if(!inq[mt[y]])inq[q[++qt]=mt[y]]=true;
      }
    }
  }
  return -1;
}
int aug(int s, int t){
  int x=t,y,z;
  while(x>=0){
    y=ft[x];
    z=mt[y];
    mt[y]=x;mt[x]=y;
    x=z;
  }
  return t>=0;
}
int edmonds(){ // O(n^2 m)
  int r=0;
  memset(mt,-1,sizeof(mt));
  for (int x = 0, _n = n; x < _n; ++x)if(mt[x]<0)r+=aug(x,findp(x));
  return r;
}
```

4 Math

4.1 Identities

$$C_n = \frac{2(2n-1)}{n+1} C_{n-1}$$
$$C_n = \frac{1}{n+1}\binom{2n}{n}$$
$$C_n \sim \frac{4^n}{n^{3/2}\sqrt{\pi}}$$
$$\sigma(n) = O(\log(\log(n))) \text{ (number of divisors of } n)$$
$$F_{2n+1} = F_n^2 + F_{n+1}^2$$
$$F_{2n} = F_{n+1}^2 - F_{n-1}^2$$
$$\sum_{i=1}^{n} F_i = F_{n+2} - 1$$
$$F_{n+i}F_{n+j} - F_nF_{n+i+j} = (-1)^n F_i F_j$$

(Möbius Inv. Formula) Let $g(n) = \sum_{d|n} f(d)$, then $f(n) = \sum d \mid n g(d)\mu\left(\frac{n}{d}\right)$.

4.2 Theorems

```
(Tutte) A graph, G = (V, E), has a perfect matching if and only if for every subset U of V, the subgraph induced by V - U has at most |U| connected components with an odd number of vertices.
Petersens Theorem. Every cubic, bridgeless graph contains a perfect matching.
(Dilworth) In any finite partially ordered set, the maximum number of elements in any antichain equals the minimum number of chains in any partition of the set into chains
Pick: A=I+B/2-1  (area of polygon, points inside, points on border)
```

4.3 Integer floor division

```
void floordiv(ll x, ll y, ll& q, ll& r) { // (for negative x)
  q=x/y;r=x%y;
  if((r!=0)&&((r<0)!=(y<0)))q--,r+=y;
}
```

4.4 Sieve of Eratosthenes

```
int cr[MAXN]; // -1 if prime, some not trivial divisor if not
void init_sieve(){
  memset(cr,-1,sizeof(cr));
  for (int i = 2, _n = MAXN; i < _n; ++i)if(cr[i]<0)for(ll j=1LL*i*i;j<MAXN;j+=i)cr[j]=i;
}
map<int,int> fact(int n){  // must call init_cribe before
  map<int,int> r;
  while(cr[n]>=0)r[cr[n]]++,n/=cr[n];
  if(n>1)r[n]++;
  return r;
}
```

4.5 Generate divisors

```
void div_rec(vector<ll>& r, vector<pair<ll,int> >& f, int k, ll c){
  if(k==f.size()){r.push_back(c);return;}
  for (int i = 0, _n = f[k].second+1; i < _n; ++i)div_rec(r,f,k+1,c),c*=f[k].first;
}
vector<ll> divisors(vector<pair<ll,int> > f){
  vector<ll> r; // returns divisors given factorization
  div_rec(r,f,0,1);
  return r;
}
```

4.6 Pollard's rho

```
ll gcd(ll a, ll b){return a?gcd(b%a,a):b;}
ll mulmod(ll a, ll b, ll m) {
  ll r=a*b-(ll)((long double)a*b/m+.5)*m;
  return r<0?r+m:r;
}
ll expmod(ll b, ll e, ll m){
  if(!e)return 1;
  ll q=expmod(b,e/2,m);q=mulmod(q,q,m);
  return e&1?mulmod(b,q,m):q;
}
bool is_prime_prob(ll n, int a){
  if(n==a)return true;
  ll s=0,d=n-1;
  while(d%2==0)s++,d/=2;
  ll x=expmod(a,d,n);
  if((x==1)||(x+1==n))return true;
  for (int _ = 0, _n = s-1; _ < _n; ++_){
    x=mulmod(x,x,n);
    if(x==1)return false;
    if(x+1==n)return true;
  }
  return false;
}
bool rabin(ll n){ // true iff n is prime
  if(n==1)return false;
  int ar[]={2,3,5,7,11,13,17,19,23};
  for (int i = 0, _n = 9; i < _n; ++i)if(!is_prime_prob(n,ar[i]))return false;
  return true;
}
ll rho(ll n){
  if(!(n&1))return 2;
  ll x=2,y=2,d=1;
  ll c=rand()%n+1;
  while(d==1){
    x=(mulmod(x,x,n)+c)%n;
    y=(mulmod(y,y,n)+c)%n;
    y=(mulmod(y,y,n)+c)%n;
```

```
    if(x>=y)d=gcd(x-y,n);
    else d=gcd(y-x,n);
  }
  return d==n?rho(n):d;
}
void fact(ll n, map<ll,int>& f){ //O (lg n)^3
  if(n==1)return;
  if(rabin(n)){f[n]++;return;}
  ll q=rho(n);fact(q,f);fact(n/q,f);
}
// optimized version: replace rho and fact with the following:
const int MAXP=1e6+1; // sieve size
int sv[MAXP]; // sieve
ll add(ll a, ll b, ll m){return (a+=b)<m?a:a-m;}
ll rho(ll n){
  static ll s[MAXP];
  while(1){
    ll x=rand()%n,y=x,c=rand()%n;
    ll *px=s,*py=s,v=0,p=1;
    while(1){
      *py++=y=add(mulmod(y,y,n),c,n);
      *py++=y=add(mulmod(y,y,n),c,n);
      if((x=*px++)==y)break;
      ll t=p;
      p=mulmod(p,abs(y-x),n);
      if(!p)return gcd(t,n);
      if(++v==26){
        if((p=gcd(p,n))>1&&p<n)return p;
        v=0;
      }
    }
    if(v&&(p=gcd(p,n))>1&&p<n)return p;
  }
}
void init_sv(){
  for (int i = 2, _n = MAXP; i < _n; ++i)if(!sv[i])for(ll j=i;j<MAXP;j+=
      i)sv[j]=i;
}
void fact(ll n, map<ll,int>& f){ // call init_sv first!!!
  for(auto&& p:f){
    while(n%p.first==0){
      p.second++;
      n/=p.first;
    }
  }
  if(n<MAXP)while(n>1)f[sv[n]]++,n/=sv[n];
  else if(rabin(n))f[n]++;
  else {ll q=rho(n);fact(q,f);fact(n/q,f);}
}
```

4.7 Simpson's rule

```
double integrate(double f(double), double a, double b, int n=10000){
  double r=0,h=(b-a)/n,fa=f(a),fb;
  for (int i = 0, _n = n; i < _n; ++i){fb=f(a+h*(i+1));r+=fa+4*f(a+h*(i
      +0.5))+fb;fa=fb;}
  return r*h/6.;
}
```

4.8 Polynomials

```
typedef int tp; // type of polynomial
template<class T=tp>
struct poly {  // poly<> : 1 variable, poly<poly<>>: 2 variables, etc.
  vector<T> c;
  T& operator[](int k){return c[k];}
  poly(vector<T>& c):c(c){}
  poly(initializer_list<T> c):c(c){}
  poly(int k):c(k){}
  poly(){}
  poly operator+(poly<T> o){
    int m=c.size(),n=o.c.size();
    poly res(max(m,n));
    for (int i = 0, _n = m; i < _n; ++i)res[i]=res[i]+c[i];
    for (int i = 0, _n = n; i < _n; ++i)res[i]=res[i]+o.c[i];
    return res;
  }
  poly operator*(tp k){
    poly res(c.size());
    for (int i = 0, _n = c.size(; i < _n; ++i))res[i]=c[i]*k;
    return res;
  }
  poly operator*(poly o){
    int m=c.size(),n=o.c.size();
    poly res(m+n-1);
    for (int i = 0, _n = m; i < _n; ++i)for (int j = 0, _n = n; j < _n;
        ++j)res[i+j]=res[i+j]+c[i]*o.c[j];
```

```
    return res;
  }
  poly operator-(poly<T> o){return *this+(o*-1);}
  T operator()(tp v){
    T sum(0);
    for(int i=c.size()-1;i>=0;--i)sum=sum*v+c[i];
    return sum;
  }
};
// example: p(x,y)=2*x^2+3*x*y-y+4
// poly<poly<>> p={{4,-1},{0,3},{2}}
// printf("%d\n",p(2)(3)) // 27 (p(2,3))
set<tp> roots(poly<> p){ // only for integer polynomials
  set<tp> r;
  while(!p.c.empty()&&!p.c.back())p.c.pop_back();
  if(!p(0))r.insert(0);
  if(p.c.empty())return r;
  tp a0=0,an=abs(p[p.c.size()-1]);
  for(int k=0;!a0;a0=abs(p[k++]));
  vector<tp> ps,qs;
  for (int i = 1, _n = sqrt(a0; i < _n; ++i)+1)if(a0%i==0)ps.push_back(i
      ),ps.push_back(a0/i);
  for (int i = 1, _n = sqrt(an; i < _n; ++i)+1)if(an%i==0)qs.push_back(i
      ),qs.push_back(an/i);
  for(auto pt:ps)for(auto qt:qs)if(pt%qt==0){
    tp x=pt/qt;
    if(!p(x))r.insert(x);
    if(!p(-x))r.insert(-x);
  }
  return r;
}
pair<poly<>,tp> ruffini(poly<> p, tp r){ // returns pair (result,rem)
  int n=p.c.size()-1;
  vector<tp> b(n);
  b[n-1]=p[n];
  for(int k=n-2;k>=0;--k)b[k]=p[k+1]+r*b[k+1];
  return {poly<>(b),p[0]+r*b[0]};
}
// only for double polynomials
pair<poly<>,poly<> > polydiv(poly<> p, poly<> q){ // returns pair (
    result,rem)
  int n=p.c.size()-q.c.size()+1;
  vector<tp> b(n);
  for(int k=n-1;k>=0;--k){
    b[k]=p.c.back()/q.c.back();
    for (int i = 0, _n = q.c.size(; i < _n; ++i))p[i+k]-=b[k]*q[i];
    p.c.pop_back();
  }
  while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
  return {poly<>(b),p};
}
// only for double polynomials
poly<> interpolate(vector<tp> x, vector<tp> y){ //TODO TEST
  poly<> q={1},S={0};
  for(tp a:x)q=poly<>({-a,1})*q;
  for (int i = 0, _n = x.size(; i < _n; ++i)){
    poly<> Li=ruffini(q,x[i]).first;
    Li=Li*(1.0/Li(x[i])); // change for int polynomials
    S=S+Li*y[i];
  }
  return S;
}
```

4.9 Bairstow

```
double pget(poly<>& p, int k){return k<p.c.size()?p[k]:0;}
poly<> bairstow(poly<> p){ // returns polynomial of degree 2 that
  int n=p.c.size()-1;    // divides p
  assert(n>=3&&abs(p.c.back())>EPS);
  double u=p[n-1]/p[n],v=p[n-2]/p[n];
  for (int _ = 0, _n = ITER; _ < _n; ++_){
    auto w=polydiv(p,{v,u,1});
    poly<> q=w.first,r0=w.second;
    poly<> r1=polydiv(q,{v,u,1}).second;
    double c=pget(r0,1),d=pget(r0,0),g=pget(r1,1),h=pget(r1,0);
    double det=1/(v*g*g+h*(h-u*g)),uu=u;
    u-=det*(-h*c+g*d);v-=det*(-g*v*c+(g*uu-h)*d);

  }
  return {v,u,1};
}
void addr(vector<double>& r, poly<>& p){
  assert(p.c.size()<=3);
  if(p.c.size()<=1)return;
  if(p.c.size()==2)r.push_back(-p[0]/p[1]);
  if(p.c.size()==3){
```

```
    double a=p[2],b=p[1],c=p[0];
    double d=b*b-4*a*c;
    if(d<-0.1)return; // huge epsilon because of bad precision
    d=d>0?sqrt(d):0;r.push_back((-b-d)/2/a);r.push_back((-b+d)/2/a);
  }
}
vector<double> roots(poly<> p){
  while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
  for (int i = 0, _n = p.c.size(; i < _n; ++i))p[i]/=p.c.back();
  vector<double> r;int n;
  while((n=p.c.size()-1)>=3){
    poly<> q=bairstow(p);addr(r,q);
    p=polydiv(p,q).first;
    while(p.c.size()>n-1)p.c.pop_back();
  }
  addr(r,p);
  return r;
}
```

4.10 Fast Fourier Transform

```
// MAXN must be power of 2 !!
// MOD-1 needs to be a multiple of MAXN !!
// big mod and primitive root for NTT:
typedef ll tf;
typedef vector<tf> poly;
const tf MOD=2305843009255636993,RT=5;
// FFT
struct CD {
  double r,i;
  CD(double r=0, double i=0):r(r),i(i){}
  double real()const{return r;}
  void operator/=(const int c){r/=c, i/=c;}
};
CD operator*(const CD& a, const CD& b){
  return CD(a.r*b.r-a.i*b.i,a.r*b.i+a.i*b.r);}
CD operator+(const CD& a, const CD& b){return CD(a.r+b.r,a.i+b.i);}
CD operator-(const CD& a, const CD& b){return CD(a.r-b.r,a.i-b.i);}
const double pi=acos(-1.0);
// NTT
/*
struct CD {
  tf x;
  CD(tf x):x(x){}
  CD(){}
};
CD operator*(const CD& a, const CD& b){return CD(mulmod(a.x,b.x));}
CD operator+(const CD& a, const CD& b){return CD(addmod(a.x,b.x));}
CD operator-(const CD& a, const CD& b){return CD(submod(a.x,b.x));}
vector<tf> rts(MAXN+9,-1);
CD root(int n, bool inv){
  tf r=rts[n]<0?rts[n]=pm(RT,(MOD-1)/n):rts[n];
  return CD(inv?pm(r,MOD-2):r);
}
*/
CD cp1[MAXN+9],cp2[MAXN+9];
int R[MAXN+9];
void dft(CD* a, int n, bool inv){
  for (int i = 0, _n = n; i < _n; ++i)if(R[i]<i)swap(a[R[i]],a[i]);
  for(int m=2;m<=n;m*=2){
    double z=2*pi/m*(inv?-1:1); // FFT
    CD wi=CD(cos(z),sin(z)); // FFT
    // CD wi=root(m,inv); // NTT
    for(int j=0;j<n;j+=m){
      CD w(1);
      for(int k=j,k2=j+m/2;k2<j+m;k++,k2++){
        CD u=a[k];CD v=a[k2]*w;a[k]=u+v;a[k2]=u-v;w=w*wi;
      }
    }
  }
  if(inv)for (int i = 0, _n = n; i < _n; ++i)a[i]/=n; // FFT
  //if(inv){ // NTT
  //  CD z(pm(n,MOD-2)); // pm: modular exponentiation
  //  for (int i = 0, _n = n; i < _n; ++i)a[i]=a[i]*z;
  //}
}
poly multiply(poly& p1, poly& p2){
  int n=p1.size()+p2.size()+1;
  int m=1,cnt=0;
  while(m<=n)m+=m,cnt++;
  for (int i = 0, _n = m; i < _n; ++i){R[i]=0;for (int j = 0, _n = cnt;
      j < _n; ++j)R[i]=(R[i]<<1)|((i>>j)&1);}
  for (int i = 0, _n = m; i < _n; ++i)cp1[i]=0,cp2[i]=0;
  for (int i = 0, _n = p1.size(; i < _n; ++i))cp1[i]=p1[i];
  for (int i = 0, _n = p2.size(; i < _n; ++i))cp2[i]=p2[i];
  dft(cp1,m,false);dft(cp2,m,false);
```

```
  for (int i = 0, _n = m; i < _n; ++i)cp1[i]=cp1[i]*cp2[i];
  dft(cp1,m,true);
  poly res;
  n-=2;
  for (int i = 0, _n = n; i < _n; ++i)res.push_back((tf)floor(cp1[i].real()+0.5)); // FFT
  //for (int i = 0, _n = n; i < _n; ++i)res.push_back(cp1[i].x); // NTT
  return res;
}
```

4.11 FFT operations

```
// Polynomial division: O(n*log(n))
// Multi-point polynomial evaluation for arbitrarily large points: O(n*log^2(n))
// Multi-point polynomial evaluation for all points in [0, MOD): O((n+MOD)*log(n+MOD))
// Polynomial interpolation: O(n*log^2(n))
// Inverse: O(n*log(n))
// Log: O(n*log(n))
// Exp: O(n*log(n))

//Works with NTT. For FFT, just replace addmod,submod,mulmod,inv
poly add(poly &a, poly &b){
  int n=((int)(a).size()),m=((int)(b).size());
  poly ans(max(n,m));
  fore(i,0,max(n,m)) ans[i]=addmod(i<((int)(a).size())?a[i]:0, i<((int)(b).size())?b[i]:0);
  while(((int)(ans).size())>1&&!ans.back())ans.pop_back();
  return ans;
}

// derivative of p
poly derivate(poly &p){
  poly ans(max(1, ((int)(p).size())-1));
  for (int i = 1, _n = ((int)(p; i < _n; ++i).size())) ans[i-1]=mulmod(p[i],i);
  return ans;
}

// integral of p
poly integrate(poly &p){
  poly ans(((int)(p).size())+1);
  for (int i = 0, _n = ((int)(p; i < _n; ++i).size())) ans[i+1]=mulmod(p[i], inv(i+1));
  return ans;
}

// p % (x^n)
poly takemod(poly &p, int n){
  poly res=p;
  res.resize(min(((int)(res).size()),n));
  while(((int)(res).size())>1&&res.back()==0) res.pop_back();
  return res;
}

// first d terms of 1/p
poly invert(poly &p, int d){
  assert(p[0]);
  poly res={inv(p[0])};
  int sz=1;
  while(sz<d){
    sz*=2;
    poly pre(p.begin(), p.begin()+min(((int)(p).size()),sz));
    poly cur=multiply(res,pre);
    for (int i = 0, _n = ((int)(cur; i < _n; ++i).size())) cur[i]=submod(0,cur[i]);
    cur[0]=addmod(cur[0],2);
    res=multiply(res,cur);
    res=takemod(res,sz);
  }
  res.resize(d);
  return res;
}

// first d terms of log(p)
poly log(poly &p, int d){
  assert(p[0]==1);
  poly cur=takemod(p,d);
  poly a=invert(cur,d), b=derivate(cur);
  auto res=multiply(a,b);
  res=takemod(res,d-1);
  res=integrate(res);
  return res;
}
```

```
// first d terms of exp(p)
poly exp(poly &p, int d){
  assert(!p[0]);
  poly res={1};
  int sz=1;
  while(sz<d){
    sz*=2;
    poly lg=log(res, sz), cur(sz);
    for (int i = 0, _n = sz; i < _n; ++i) cur[i]=submod(i<((int)(p).size
        ())?p[i]:0, i<((int)(lg).size())?lg[i]:0);
    cur[0]=addmod(cur[0],1);
    res=multiply(res,cur);
    res=takemod(res, sz);
  }

  res.resize(d);
  return res;
}

pair<poly,poly> divslow(poly &a, poly &b){
  poly q,r=a;
  while(((int)(r).size())>=((int)(b).size())){
    q.push_back(mulmod(r.back(),inv(b.back())));
    if(q.back()) for (int i = 0, _n = ((int)(b; i < _n; ++i).size())){
      r[((int)(r).size())-i-1]=submod(r[((int)(r).size())-i-1],mulmod(q.
          back(),b[((int)(b).size())-i-1]));
    }
    r.pop_back();
  }
  reverse(ALL(q));
  return {q,r};
}

pair<poly,poly> divide(poly &a, poly &b){ //returns {quotient,remainder}
  int m=((int)(a).size()),n=((int)(b).size()),MAGIC=750;
  if(m<n) return {{0},a};
  if(min(m-n,n)<MAGIC)return divslow(a,b);
  poly ap=a; reverse(ALL(ap));
  poly bp=b; reverse(ALL(bp));
  bp=invert(bp,m-n+1);
  poly q=multiply(ap,bp);
  q.resize(((int)(q).size())+m-n-((int)(q).size())+1,0);
  reverse(ALL(q));
  poly bq=multiply(b,q);
  for (int i = 0, _n = ((int)(bq; i < _n; ++i).size())) bq[i]=submod(0,
      bq[i]);
  poly r=add(a,bq);
  return {q,r};
}

vector<poly> tree;

void filltree(vector<tf> &x){
  int k=((int)(x).size());
  tree.resize(2*k);
  for (int i = k, _n = 2*k; i < _n; ++i) tree[i]={submod(0,x[i-k]),1};
  for(int i=k-1;i;i--) tree[i]=multiply(tree[2*i],tree[2*i+1]);
}

// Multi-point polynomial evaluation for arbitrarily large points
vector<tf> evaluate(poly &a, vector<tf> &x){
  filltree(x);
  int k=((int)(x).size());
  vector<poly> ans(2*k);
  ans[1]=divide(a,tree[1]).second;
  for (int i = 2, _n = 2*k; i < _n; ++i) ans[i]=divide(ans[i>>1],tree[i
      ]).second;
  vector<tf> r; for (int i = 0, _n = k; i < _n; ++i) r.push_back(ans[i+k
      ][0]);
  return r;
}

// Given any number g, perform multi-point polynomial evaluation
// for all points of the form g^i, for each i in [0, k)
// in O((n+k) * log(n+k))
vector<int> chirpTransform(poly& p, int g, int k) {
  int inv_g=inv(g), n=((int)(p).size())-1, sz=min(k,MOD-1), gk=1;
  poly ap(n+1), bp(n+sz);

  for (int i = 0, _n = n+sz; i < _n; ++i){
    ll exp=1ll*i*(i-1)/2%(MOD-1);
    if(i<=n) ap[n-i]=mulmod(p[i],fpow(inv_g, exp));
    bp[i]=fpow(g, exp);
  }

  poly cp=multiply(ap, bp);
```

```
  vector<int> ans(k);

  for (int i = 0, _n = sz; i < _n; ++i){
    ll exp=1ll*i*(i-1)/2%(MOD-1);
    int val=0;
    if(n+i<((int)(cp).size())) val=cp[n+i];
    val=mulmod(val, fpow(inv_g,exp));
    ans[i]=val;
    gk=mulmod(gk,g);
  }
  for (int i = sz, _n = k; i < _n; ++i) ans[i]=ans[i-MOD+1];
  return ans;
}

int get_primitive_root(int p) {
  if(p==2)return 1;
  int phi=p-1, n=phi;
  vector<int> fact;
  for(int i=2;i*i<=n;i++) if(n%i==0){
    fact.push_back(i);
    while(n%i==0) n/=i;
  }
  if(n>1) fact.push_back(n);

  for (int res = 2, _n = p+1; res < _n; ++res){
    int ok=1;
    for(int f:fact){
      if(fpow(res,phi/f)==1){
        ok=false;
        break;
      }
    }
    if(ok)return res;
  }
  return -1;
}

// Multi-point polynomial evaluation for all points in [0, MOD)
// MOD needs to be a prime number
vector<int> evaluate_all_points(poly& p) {
  int g=get_primitive_root(MOD), gk=1;
  assert(g!=-1);

  vector<int> ch=chirpTransform(p,g,MOD-1), ans(MOD, p[0]);

  for (int i = 0, _n = MOD-1; i < _n; ++i){
    ans[gk]=ch[i];
    gk=mulmod(gk,g);
  }
  return ans;
}

poly interpolate(vector<tf> &x, vector<tf> &y){
  filltree(x);
  poly p=derivate(tree[1]);
  int k=((int)(y).size());
  vector<tf> d=evaluate(p,x);
  vector<poly> intree(2*k);
  for (int i = k, _n = 2*k; i < _n; ++i) intree[i]={mulmod(y[i-k],inv(d[
      i-k]))};
  for(int i=k-1;i;i--){
    poly p1=multiply(tree[2*i],intree[2*i+1]);
    poly p2=multiply(tree[2*i+1],intree[2*i]);
    intree[i]=add(p1,p2);
  }
  return intree[1];
}
```

4.12 Fast Hadamard Transform

```
ll c1[MAXN+9],c2[MAXN+9];  // MAXN must be power of 2 !!
void fht(ll* p, int n, bool inv){
  for(int l=1;2*l<=n;l*=2)for(int i=0;i<n;i+=2*l)for (int j = 0, _n = l;
      j < _n; ++j){
    ll u=p[i+j],v=p[i+l+j];
    if(!inv)p[i+j]=u+v,p[i+l+j]=u-v; // XOR
    else p[i+j]=(u+v)/2,p[i+l+j]=(u-v)/2;
    //if(!inv)p[i+j]=v,p[i+l+j]=u+v; // AND
    //else p[i+j]=-u+v,p[i+l+j]=u;
    //if(!inv)p[i+j]=u+v,p[i+l+j]=u; // OR
    //else p[i+j]=v,p[i+l+j]=u-v;
  }
}
// like polynomial multiplication, but XORing exponents
// instead of adding them (also ANDing, ORing)
vector<ll> multiply(vector<ll>& p1, vector<ll>& p2){
```

```
  int n=1<<(32-__builtin_clz(max(((int)(p1).size()),((int)(p2).size()))
      -1));
  for (int i = 0, _n = n; i < _n; ++i)c1[i]=0,c2[i]=0;
  for (int i = 0, _n = ((int)(p1; i < _n; ++i).size()))c1[i]=p1[i];
  for (int i = 0, _n = ((int)(p2; i < _n; ++i).size()))c2[i]=p2[i];
  fht(c1,n,false);fht(c2,n,false);
  for (int i = 0, _n = n; i < _n; ++i)c1[i]*=c2[i];
  fht(c1,n,true);
  return vector<ll>(c1,c1+n);
}
```

4.13 Karatsuba

```
typedef ll tp;
#define add(n,s,d,k) for (int i = 0, _n = n; i < _n; ++i)(d)[i]+=(s)[i]*
    k
tp* ini(int n){tp *r=new tp[n];fill(r,r+n,0);return r;}
void karatsura(int n, tp* p, tp* q, tp* r){
  if(n<=0)return;
  if(n<35)for (int i = 0, _n = n; i < _n; ++i)for (int j = 0, _n = n; j
      < _n; ++j)r[i+j]+=p[i]*q[j];
  else {
    int nac=n/2,nbd=n-n/2;
    tp *a=p,*b=p+nac,*c=q,*d=q+nac;
    tp *ab=ini(nbd+1),*cd=ini(nbd+1),*ac=ini(nac*2),*bd=ini(nbd*2);
    add(nac,a,ab,1);add(nbd,b,ab,1);
    add(nac,c,cd,1);add(nbd,d,cd,1);
    karatsura(nac,a,c,ac);karatsura(nbd,b,d,bd);
    add(nac*2,ac,r+nac,-1);add(nbd*2,bd,r+nac,-1);
    add(nac*2,ac,r,1);add(nbd*2,bd,r+nac*2,1);
    karatsura(nbd+1,ab,cd,r+nac);
    free(ab);free(cd);free(ac);free(bd);
  }
}
vector<tp> multiply(vector<tp> p0, vector<tp> p1){
  int n=max(p0.size(),p1.size());
  tp *p=ini(n),*q=ini(n),*r=ini(2*n);
  for (int i = 0, _n = p0.size(; i < _n; ++i))p[i]=p0[i];
  for (int i = 0, _n = p1.size(; i < _n; ++i))q[i]=p1[i];
  karatsura(n,p,q,r);
  vector<tp> rr(r,r+p0.size()+p1.size()-1);
  free(p);free(q);free(r);
  return rr;
}
```

4.14 Diophantine

```
pair<ll,ll> extendedEuclid (ll a, ll b){ //a * x + b * y = gcd(a,b)
  ll x,y;
  if (b==0) return {1,0};
  auto p=extendedEuclid(b,a%b);
  x=p.second;
  y=p.first-(a/b)*x;
  if(a*x+b*y==-gcd(a,b)) x=-x, y=-y;
  return {x,y};
}
pair<pair<ll,ll>,pair<ll,ll> > diophantine(ll a,ll b, ll r) {
  //a*x+b*y=r where r is multiple of gcd(a,b);
  ll d=gcd(a,b);
  a/=d; b/=d; r/=d;
  auto p = extendedEuclid(a,b);
  p.first*=r; p.second*=r;
  assert(a*p.first+b*p.second==r);
  return {p,{-b,a}}; // solutions: p+t*ans.second
}
```

4.15 Modular inverse

```
ll inv(ll a, ll mod) { //inverse of a modulo mod
  assert(gcd(a,mod)==1);
  pl sol = extendedEuclid(a,mod);
  return ((sol.first%mod)+mod)%mod;
}
```

4.16 Chinese remainder theorem

```
#define mod(a,m) (((a)%m+m)%m)
pair<ll,ll> sol(tuple<ll,ll,ll> c){ //requires inv, diophantine
    ll a=get<0>(c), x1=get<1>(c), m=get<2>(c), d=gcd(a,m);
    if(d==1) return {mod(x1*inv(a,m),m), m};
    else return x1%d ? ii({-1LL,-1LL}) : sol(make_tuple(a/d,x1/d,m/d));
}
pair<ll,ll> crt(vector< tuple<ll,ll,ll> > cond) { // returns: (sol, lcm)
  ll x1=0,m1=1,x2,m2;
  for(auto t:cond){
    tie(x2,m2)=sol(t);
    if(m2<0||(x1-x2)%gcd(m1,m2))return {-1,-1};
```

```
    if(m1==m2)continue;
    ll k=diophantine(m2,-m1,x1-x2).first.second,l=m1*(m2/gcd(m1,m2));
    x1=mod((__int128)m1*k+x1,l);m1=l;
  }
  return sol(make_tuple(1,x1,m1));
} //cond[i]={ai,bi,mi} ai*xi=bi (mi); assumes lcm fits in ll
```

4.17 Mobius

```
short mu[MAXN] = {0,1};
void mobius(){
  for (int i = 1, _n = MAXN; i < _n; ++i)if(mu[i])for(int j=i+i;j<MAXN;j
      +=i)mu[j]-=mu[i];
}
```

4.18 Matrix exponentiation

```
typedef vector<vector<ll> > Matrix;
Matrix ones(int n) {
  Matrix r(n,vector<ll>(n));
  for (int i = 0, _n = n; i < _n; ++i)r[i][i]=1;
  return r;
}
Matrix operator*(Matrix &a, Matrix &b) {
  int n=((int)(a).size()),m=((int)(b[0]).size()),z=((int)(a[0]).size());
  Matrix r(n,vector<ll>(m));
  for (int i = 0, _n = n; i < _n; ++i)for (int j = 0, _n = m; j < _n; ++
      j)for (int k = 0, _n = z; k < _n; ++k)
    r[i][j]+=a[i][k]*b[k][j],r[i][j]%=mod;
  return r;
}
Matrix be(Matrix b, ll e) {
  Matrix r=ones(((int)(b).size()));
  while(e){if(e&1LL)r=r*b;b=b*b;e/=2;}
  return r;
}
```

4.19 Matrix reduce and determinant

```
double reduce(vector<vector<double> >& x){ // returns determinant
  int n=x.size(),m=x[0].size();
  int i=0,j=0;double r=1.;
  while(i<n&&j<m){
    int l=i;
    for (int k = i+1, _n = n; k < _n; ++k)if(abs(x[k][j])>abs(x[l][j]))l
        =k;
    if(abs(x[l][j])<EPS){j++;r=0.;continue;}
    if(l!=i){r=-r;swap(x[i],x[l]);}
    r*=x[i][j];
    for(int k=m-1;k>=j;k--)x[i][k]/=x[i][j];
    for (int k = 0, _n = n; k < _n; ++k){
      if(k==i)continue;
      for(int l=m-1;l>=j;l--)x[k][l]-=x[k][j]*x[i][l];
    }
    i++;j++;
  }
  return r;
}
```

4.20 Simplex

```
vector<int> X,Y;
vector<vector<double> > A;
vector<double> b,c;
double z;
int n,m;
void pivot(int x,int y){
  swap(X[y],Y[x]);
  b[x]/=A[x][y];
  for (int i = 0, _n = m; i < _n; ++i)if(i!=y)A[x][i]/=A[x][y];
  A[x][y]=1/A[x][y];
  for (int i = 0, _n = n; i < _n; ++i)if(i!=x&&abs(A[i][y])>EPS){
    b[i]-=A[i][y]*b[x];
    for (int j = 0, _n = m; j < _n; ++j)if(j!=y)A[i][j]-=A[i][y]*A[x][j
        ];
    A[i][y]=-A[i][y]*A[x][y];
  }
  z+=c[y]*b[x];
  for (int i = 0, _n = m; i < _n; ++i)if(i!=y)c[i]-=c[y]*A[x][i];
  c[y]=-c[y]*A[x][y];
}
pair<double,vector<double> > simplex( // maximize c^T x s.t. Ax<=b, x>=0
    vector<vector<double> > _A, vector<double> _b, vector<double> _c){
  // returns pair (maximum value, solution vector)
  A=_A;b=_b;c=_c;
  n=b.size();m=c.size();z=0.;
  X=vector<int>(m);Y=vector<int>(n);
```

```
  for (int i = 0, _n = m; i < _n; ++i)X[i]=i;
  for (int i = 0, _n = n; i < _n; ++i)Y[i]=i+m;
  while(1){
    int x=-1,y=-1;
    double mn=-EPS;
    for (int i = 0, _n = n; i < _n; ++i)if(b[i]<mn)mn=b[i],x=i;
    if(x<0)break;
    for (int i = 0, _n = m; i < _n; ++i)if(A[x][i]<-EPS){y=i;break;}
    assert(y>=0); // no solution to Ax<=b
    pivot(x,y);
  }
  while(1){
    double mx=EPS;
    int x=-1,y=-1;
    for (int i = 0, _n = m; i < _n; ++i)if(c[i]>mx)mx=c[i],y=i;
    if(y<0)break;
    double mn=1e200;
    for (int i = 0, _n = n; i < _n; ++i)if(A[i][y]>EPS&&b[i]/A[i][y]<mn)
        mn=b[i]/A[i][y],x=i;
    assert(x>=0); // c^T x is unbounded
    pivot(x,y);
  }
  vector<double> r(m);
  for (int i = 0, _n = n; i < _n; ++i)if(Y[i]<m)r[Y[i]]=b[i];
  return {z,r};
}
```

4.21 Discrete log

```
//returns x such that a^x = b (mod m) or -1 if inexistent
ll discrete_log(ll a,ll b,ll m) {
    a%=m, b%=m;
    if(b == 1) return 0;
    int cnt=0;
    ll tmp=1;
    for(int g=__gcd(a,m);g!=1;g=__gcd(a,m)) {
        if(b%g) return -1;
        m/=g, b/=g;
        tmp = tmp*a/g%m;
        ++cnt;
        if(b == tmp) return cnt;
    }
    map<ll,int> w;
    int s = ceil(sqrt(m));
    ll base = b;
    for (int i = 0, _n = s; i < _n; ++i) {
        w[base] = i;
        base=base*a%m;
    }
    base=fastpow(a,s,m);
    ll key=tmp;
    for (int i = 1, _n = s+2; i < _n; ++i) {
        key=base*key%m;
        if(w.count(key)) return i*s-w[key]+cnt;
    }
    return -1;
}
```

4.22 Berlekamp Massey

```
typedef vector<int> vi;
vi BM(vi x){
  vi ls,cur;int lf,ld;
  for (int i = 0, _n = ((int)(x; i < _n; ++i).size())){
    ll t=0;
    for (int j = 0, _n = ((int)(cur; j < _n; ++j).size()))t=(t+x[i-j
        -1]*(ll)cur[j])%MOD;
    if((t-x[i])%MOD==0)continue;
    if(!((int)(cur).size())){cur.resize(i+1);lf=i;ld=(t-x[i])%MOD;
        continue;}
    ll k=-(x[i]-t)*fast_pow(ld,MOD-2)%MOD;
    vi c(i-lf-1);c.push_back(k);
    for (int j = 0, _n = ((int)(ls; j < _n; ++j).size()))c.push_back(-ls
        [j]*k%MOD);
    if(((int)(c).size())<((int)(cur).size()))c.resize(((int)(cur).size()
        ));
    for (int j = 0, _n = ((int)(cur; j < _n; ++j).size()))c[j]=(c[j]+cur
        [j])%MOD;
    if(i-lf+((int)(ls).size())>=((int)(cur).size()))ls=cur,lf=i,ld=(t-x[
        i])%MOD;
    cur=c;
  }
  for (int i = 0, _n = ((int)(cur; i < _n; ++i).size()))cur[i]=(cur[i]%
      MOD+MOD)%MOD;
  return cur;
}
```

4.23 Linear Rec

```
//init O(n^2log) query(n^2 logk)
//input: terms: first n term; trans: transition function; MOD; LOG=mxlog of k
//output calc(k): kth term mod MOD
//example: {1,1} {2,1} an=2*a_(n-1)+a_(n-2); calc(3)=3 calc(10007)=71480733
struct LinearRec{
  typedef vector<int> vi;
  int n; vi terms, trans; vector<vi> bin;
  vi add(vi &a, vi &b){
    vi res(n*2+1);
    for (int i = 0, _n = n+1; i < _n; ++i)for (int j = 0, _n = n+1; j < _n; ++j)res[i+j]=(res[i+j]*1LL+(ll)a[i]*b[j])%MOD;
    for(int i=2*n; i>n; --i){
      for (int j = 0, _n = n; j < _n; ++j)res[i-1-j]=(res[i-1-j]*1LL+(ll)res[i]*trans[j])%MOD;
      res[i]=0;
    }
    res.erase(res.begin()+n+1,res.end());
    return res;
  }
  LinearRec(vi &terms, vi &trans):terms(terms),trans(trans){
    n=((int)(trans).size());vi a(n+1);a[1]=1;
    bin.push_back(a);
    for (int i = 1, _n = LOG; i < _n; ++i)bin.push_back(add(bin[i-1],bin[i-1]));
  }
  int calc(int k){
    vi a(n+1);a[0]=1;
    for (int i = 0, _n = LOG; i < _n; ++i)if((k>>i)&1)a=add(a,bin[i]);
    int ret=0;
    for (int i = 0, _n = n; i < _n; ++i)ret=((ll)ret+(ll)a[i+1]*terms[i])%MOD;
    return ret;
  }
};
```

4.24 Tonelli Shanks

```
ll legendre(ll a, ll p){
  if(a%p==0)return 0; if(p==2)return 1;
  return fpow(a,(p-1)/2,p);
}
ll tonelli_shanks(ll n, ll p){  // sqrt(n) mod p (p must be a prime)
  assert(legendre(n,p)==1); if(p==2)return 1;
  ll s=__builtin_ctzll(p-1), q=(p-1LL)>>s, z=rnd(1,p-1);
  if(s==1)return fpow(n,(p+1)/4LL,p);
  while(legendre(z,p)!=p-1)z=rnd(1,p-1);
  ll c=fpow(z,q,p), r=fpow(n,(q+1)/2,p), t=fpow(n,q,p), m=s;
  while(t!=1){
    ll i=1, ts=(t*t)%p;
    while(ts!=1)i++,ts=(ts*ts)%p;
    ll b=c;
    for (int _ = 0, _n = m-i-1; _ < _n; ++_)b=(b*b)%p;
    r=r*b%p;c=b*b%p;t=t*c%p;m=i;
  }
  return r;
}
```

4.25 Prime count

```
// Count number of primes in [1,n]
// O(n^(2/3)) time
// O(sqrt(n)) memory
ll prime_count(ll n) {
    if (n <= 1) return 0;
    int v = sqrtl(n), s = (v+1)>>1, pc=0;
    vector<int> smalls(s), roughs(s), skip(v+1);
    vector<ll> larges(s);
    for (int i = 0, _n = s; i < _n; ++i){
        smalls[i]=i;
        roughs[i]=2*i+1;
        larges[i]=(n/roughs[i]-1)>>1;
    }
    for(int p=3;p<=v;p+=2) if(!skip[p]){
        int q=p*p;
        if(1ll*q*q>n) break;
        skip[p]=1;
        for(int i=q;i<=v;i+=2*p) skip[i]=1;
        int ns=0;
        for (int k = 0, _n = s; k < _n; ++k){
            int i=roughs[k];
            if(skip[i]) continue;
            ll d=1ll*i*p;
```

```
            larges[ns]=larges[k]-(d<=v?larges[smalls[d>>1]-pc]:smalls[(n/d-1)>>1])+pc;
            roughs[ns++]=i;
        }
        s=ns;
        for(int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2){
            int c=smalls[j>>1]-pc;
            for(int e=(j*p)>>1;i>=e;i--) smalls[i]-=c;
        }
        pc++;
    }
    larges[0]+=1ll*(s+2*(pc-1))*(s-1)>>1;
    for (int k = 1, _n = s; k < _n; ++k) larges[0]-=larges[k];
    for (int l = 1, _n = s; l < _n; ++l){
        int q=roughs[l];
        ll m=n/q, t=0;
        int e=smalls[(m/q-1)>>1]-pc;
        if(e<l+1)break;
        for (int k = l+1, _n = e+1; k < _n; ++k) t+=smalls[(m/roughs[k]-1)>>1];
        larges[0]+=t-1ll*(e-l)*(pc+l-1);
    }
    return larges[0]+1;
}
```

5 Geometry

5.1 Point

```
struct pt {  // for 3D add z coordinate
  double x,y;
  pt(double x, double y):x(x),y(y){}
  pt(){}
  double norm2(){return *this**this;}
  double norm(){return sqrt(norm2());}
  bool operator==(pt p){return abs(x-p.x)<=EPS&&abs(y-p.y)<=EPS;}
  pt operator+(pt p){return pt(x+p.x,y+p.y);}
  pt operator-(pt p){return pt(x-p.x,y-p.y);}
  pt operator*(double t){return pt(x*t,y*t);}
  pt operator/(double t){return pt(x/t,y/t);}
  double operator*(pt p){return x*p.x+y*p.y;}
//  pt operator^(pt p){ // only for 3D
//    return pt(y*p.z-z*p.y,z*p.x-x*p.z,x*p.y-y*p.x);}
  double angle(pt p){ // redefine acos for values out of range
    return acos(*this*p/(norm()*p.norm()));}
  pt unit(){return *this/norm();}
  double operator%(pt p){return x*p.y-y*p.x;}
  // 2D from now on
  bool operator<(pt p)const{ // for convex hull
    return x<p.x-EPS||(abs(x-p.x)<=EPS&&y<p.y-EPS);}
  bool left(pt p, pt q){ // is it to the left of directed line pq?
    return (q-p)%(*this-p)>EPS;}
  pt rot(pt r){return pt(*this%r,*this*r);}
  pt rot(double a){return rot(pt(sin(a),cos(a)));}
};
pt ccw90(1,0);
pt cw90(-1,0);
```

5.2 Line

```
int sgn2(double x){return x<0?-1:1;}
struct ln {
  pt p,pq;
  ln(pt p, pt q):p(p),pq(q-p){}
  ln(){}
  bool has(pt r){return dist(r)<=EPS;}
  bool seghas(pt r){return has(r)&&(r-p)*(r-(p+pq))<=EPS;}
//  bool operator /(ln l){return (pq.unit()^l.pq.unit()).norm()<=EPS;} // 3D
  bool operator/(ln l){return abs(pq.unit()%l.pq.unit())<=EPS;} // 2D
  bool operator==(ln l){return *this/l&&has(l.p);}
  pt operator^(ln l){ // intersection
    if(*this/l)return pt(DINF,DINF);
    pt r=l.p+l.pq*((p-l.p)%pq/(l.pq%pq));
//    if(!has(r)){return pt(NAN,NAN,NAN);} // check only for 3D
    return r;
  }
  double angle(ln l){return pq.angle(l.pq);}
  int side(pt r){return has(r)?0:sgn2(pq%(r-p));} // 2D
  pt proj(pt r){return p+pq*((r-p)*pq/pq.norm2());}
  pt ref(pt r){return proj(r)*2-r;}
  double dist(pt r){return (r-proj(r)).norm();}
//  double dist(ln l){ // only 3D
//    if(*this/l)return dist(l.p);
//    return abs((l.p-p)*(pq^l.pq))/(pq^l.pq).norm();
//  }
```

```
  ln rot(auto a){return ln(p,p+pq.rot(a));} // 2D
};
ln bisector(ln l, ln m){ // angle bisector
  pt p=l^m;
  return ln(p,p+l.pq.unit()+m.pq.unit());
}
ln bisector(pt p, pt q){ // segment bisector (2D)
  return ln((p+q)*.5,p).rot(ccw90);
}
```

5.3 Circle

```
struct circle {
  pt o;double r;
  circle(pt o, double r):o(o),r(r){}
  circle(pt x, pt y, pt z){o=bisector(x,y)^bisector(x,z);r=(o-x).norm()
      ;}
  bool has(pt p){return (o-p).norm()<=r+EPS;}
  vector<pt> operator^(circle c){ // ccw
    vector<pt> s;
    double d=(o-c.o).norm();
    if(d>r+c.r+EPS||d+min(r,c.r)+EPS<max(r,c.r))return s;
    double x=(d*d-c.r*c.r+r*r)/(2*d);
    double y=sqrt(r*r-x*x);
    pt v=(c.o-o)/d;
    s.push_back(o+v*x-v.rot(ccw90)*y);
    if(y>EPS)s.push_back(o+v*x+v.rot(ccw90)*y);
    return s;
  }
  vector<pt> operator^(ln l){
    vector<pt> s;
    pt p=l.proj(o);
    double d=(p-o).norm();
    if(d-EPS>r)return s;
    if(abs(d-r)<=EPS){s.push_back(p);return s;}
    d=sqrt(r*r-d*d);
    s.push_back(p+l.pq.unit()*d);
    s.push_back(p-l.pq.unit()*d);
    return s;
  }
  vector<pt> tang(pt p){
    double d=sqrt((p-o).norm2()-r*r);
    return *this^circle(p,d);
  }
  bool in(circle c){ // non strict
    double d=(o-c.o).norm();
    return d+r<=c.r+EPS;
  }
  double intertriangle(pt a, pt b){ // area of intersection with oab
    if(abs((o-a)%(o-b))<=EPS)return 0.;
    vector<pt> q={a},w=*this^ln(a,b);
    if(w.size()==2)for(auto p:w)if((a-p)*(b-p)<-EPS)q.push_back(p);
    q.push_back(b);
    if(q.size()==4&&(q[0]-q[1])*(q[2]-q[1])>EPS)swap(q[1],q[2]);
    double s=0;
    for (int i = 0, _n = q.size(; i < _n; ++i)-1){
      if(!has(q[i])||!has(q[i+1]))s+=r*r*(q[i]-o).angle(q[i+1]-o)/2;
      else s+=abs((q[i]-o)%(q[i+1]-o)/2);
    }
    return s;
  }
};
vector<double> intercircles(vector<circle> c){
  vector<double> r(((int)(c).size())+1); // r[k]: area covered by at
      least k circles
  for (int i = 0, _n = ((int)(c; i < _n; ++i).size())){          // O(n
      ^2 log n) (high constant)
    int k=1;Cmp s(c[i].o);
    vector<pair<pt,int> > p={
      {c[i].o+pt(1,0)*c[i].r,0},
      {c[i].o-pt(1,0)*c[i].r,0}};
    for (int j = 0, _n = ((int)(c; j < _n; ++j).size()))if(j!=i){
      bool b0=c[i].in(c[j]),b1=c[j].in(c[i]);
      if(b0&&(!b1||i<j))k++;
      else if(!b0&&!b1){
        auto v=c[i]^c[j];
        if(((int)(v).size())==2){
          p.push_back({v[0],1});p.push_back({v[1],-1});
          if(s(v[1],v[0]))k++;
        }
      }
    }
    sort(p.begin(),p.end(),
      [&](pair<pt,int> a, pair<pt,int> b){return s(a.first,b.first);});
    for (int j = 0, _n = ((int)(p; j < _n; ++j).size())){
      pt p0=p[j?j-1:((int)(p).size())-1].first,p1=p[j].first;
```

```
      double a=(p0-c[i].o).angle(p1-c[i].o);
      r[k]+=(p0.x-p1.x)*(p0.y+p1.y)/2+c[i].r*c[i].r*(a-sin(a))/2;
      k+=p[j].second;
    }
  }
  return r;
}
```

5.4 Polygon

```
int sgn(double x){return x<-EPS?-1:x>EPS;}
struct pol {
  int n;vector<pt> p;
  pol(){}
  pol(vector<pt> _p){p=_p;n=p.size();}
  double area(){
    double r=0.;
    for (int i = 0, _n = n; i < _n; ++i)r+=p[i]%p[(i+1)%n];
    return abs(r)/2; // negative if CW, positive if CCW
  }
  pt centroid(){ // (barycenter)
    pt r(0,0);double t=0;
    for (int i = 0, _n = n; i < _n; ++i){
      r=r+(p[i]+p[(i+1)%n])*(p[i]%p[(i+1)%n]);
      t+=p[i]%p[(i+1)%n];
    }
    return r/t/3;
  }
  bool has(pt q){ // O(n)
    for (int i = 0, _n = n; i < _n; ++i)if(ln(p[i],p[(i+1)%n]).seghas(q)
        )return true;
    int cnt=0;
    for (int i = 0, _n = n; i < _n; ++i){
      int j=(i+1)%n;
      int k=sgn((q-p[j])%(p[i]-p[j]));
      int u=sgn(p[i].y-q.y),v=sgn(p[j].y-q.y);
      if(k>0&&u<0&&v>=0)cnt++;
      if(k<0&&v<0&&u>=0)cnt--;
    }
    return cnt!=0;
  }
  void normalize(){ // (call before haslog, remove collinear first)
    if(p[2].left(p[0],p[1]))reverse(p.begin(),p.end());
    int pi=min_element(p.begin(),p.end())-p.begin();
    vector<pt> s(n);
    for (int i = 0, _n = n; i < _n; ++i)s[i]=p[(pi+i)%n];
    p.swap(s);
  }
  bool haslog(pt q){ // O(log(n)) only CONVEX. Call normalize first
    if(q.left(p[0],p[1])||q.left(p.back(),p[0]))return false;
    int a=1,b=p.size()-1;  // returns true if point on boundary
    while(b-a>1){          // (change sign of EPS in left
      int c=(a+b)/2;       //  to return false in such case)
      if(!q.left(p[0],p[c]))a=c;
      else b=c;
    }
    return !q.left(p[a],p[a+1]);
  }
  pt farthest(pt v){ // O(log(n)) only CONVEX
    if(n<10){
      int k=0;
      for (int i = 1, _n = n; i < _n; ++i)if(v*(p[i]-p[k])>EPS)k=i;
      return p[k];
    }
    if(n==((int)(p).size()))p.push_back(p[0]);
    pt a=p[1]-p[0];
    int s=0,e=n,ua=v*a>EPS;
    if(!ua&&v*(p[n-1]-p[0])<=EPS)return p[0];
    while(1){
      int m=(s+e)/2;pt c=p[m+1]-p[m];
      int uc=v*c>EPS;
      if(!uc&&v*(p[m-1]-p[m])<=EPS)return p[m];
      if(ua&&(!uc||v*(p[s]-p[m])>EPS))e=m;
      else if(ua||uc||v*(p[s]-p[m])>=-EPS)s=m,a=c,ua=uc;
      else e=m;
      assert(e>s+1);
    }
  }
  pol cut(ln l){   // cut CONVEX polygon by line l
    vector<pt> q;  // returns part at left of l.pq
    for (int i = 0, _n = n; i < _n; ++i){
      int d0=sgn(l.pq%(p[i]-l.p)),d1=sgn(l.pq%(p[(i+1)%n]-l.p));
      if(d0>=0)q.push_back(p[i]);
      ln m(p[i],p[(i+1)%n]);
      if(d0*d1<0&&!(l/m))q.push_back(l^m);
    }
```

```
    return pol(q);
  }
  double intercircle(circle c){ // area of intersection with circle
    double r=0.;
    for (int i = 0, _n = n; i < _n; ++i){
      int j=(i+1)%n;double w=c.intertriangle(p[i],p[j]);
      if((p[j]-c.o)%(p[i]-c.o)>0)r+=w;
      else r-=w;
    }
    return abs(r);
  }
  double callipers(){ // square distance of most distant points
    double r=0;     // prereq: convex, ccw, NO COLLINEAR POINTS
    for(int i=0,j=n<2?0:1;i<j;++i){
      for(;;j=(j+1)%n){
        r=max(r,(p[i]-p[j]).norm2());
        if((p[(i+1)%n]-p[i])%(p[(j+1)%n]-p[j])<=EPS)break;
      }
    }
    return r;
  }
};
// Dynamic convex hull trick
vector<pol> w;
void add(pt q){ // add(q), O(log^2(n))
  vector<pt> p={q};
  while(!w.empty()&&((int)(w.back().size()).p)<2*((int)(p).size())){
    for(pt v:w.back().p)p.push_back(v);
    w.pop_back();
  }
  w.push_back(pol(chull(p)));
}
ll query(pt v){ // max(q*v:q in w), O(log^2(n))
  ll r=-INF;
  for(auto& p:w)r=max(r,p.farthest(v)*v);
  return r;
}
```

5.5 Plane

```
struct plane {
  pt a,n; // n: normal unit vector
  plane(pt a, pt b, pt c):a(a),n(((b-a)^(c-a)).unit()){}
  plane(){}
  bool has(pt p){return abs((p-a)*n)<=EPS;}
  double angle(plane w){return acos(n*w.n);}
  double dist(pt p){return abs((p-a)*n);}
  pt proj(pt p){inter(ln(p,p+n),p);return p;}
  bool inter(ln l, pt& r){
    double x=n*(l.p+l.pq-a),y=n*(l.p-a);
    if(abs(x-y)<=EPS)return false;
    r=(l.p*x-(l.p+l.pq)*y)/(x-y);
    return true;
  }
  bool inter(plane w, ln& r){
    pt nn=n^w.n;pt v=n^nn;double d=w.n*v;
    if(abs(d)<=EPS)return false;
    pt p=a+v*(w.n*(w.a-a)/d);
    r=ln(p,p+nn);
    return true;
  }
};
```

5.6 Radial order of points

```
struct Cmp { // IMPORTANT: add const in pt operator -
  pt r;
  Cmp(pt r):r(r){}
  int cuad(const pt &a)const {
    if(a.x>0&&a.y>=0)return 0;
    if(a.x<=0&&a.y>0)return 1;
    if(a.x<0&&a.y<=0)return 2;
    if(a.x>=0&&a.y<0)return 3;
    assert(a.x==0&&a.y==0);
    return -1;
  }
  bool cmp(const pt& p1, const pt& p2)const {
    int c1=cuad(p1),c2=cuad(p2);
    if(c1==c2)return p1.y*p2.x<p1.x*p2.y;
    return c1<c2;
  }
  bool operator()(const pt& p1, const pt& p2)const {
    return cmp(p1-r,p2-r);
  }
};
```

5.7 Convex hull

```
// CCW order
// Includes collinear points (change sign of EPS in left to exclude)
vector<pt> chull(vector<pt> p){
  vector<pt> r;
  sort(p.begin(),p.end()); // first x, then y
  p.erase(unique(ALL(p)), p.end());
  for (int i = 0, _n = p.size(; i < _n; ++i)){ // lower hull
    while(r.size()>=2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
    r.push_back(p[i]);
  }
  r.pop_back();
  int k=r.size(),pr=k-1;
  for(int i=p.size()-1;i>=0;--i){ // upper hull
    while(r.size()>=k+2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
    while(pr>=0&&p[i]<r[pr]) pr--;
    if(pr<0||!(p[i]==r[pr])) r.push_back(p[i]);
  }
  return r;
}
```

5.8 Dual from planar graph

```
vector<int> g[MAXN];int n; // input graph (must be connected)
vector<int> gd[MAXN];int nd; // output graph
vector<int> nodes[MAXN]; // nodes delimiting region (in CW order)
map<pair<int,int>,int> ps,es;
void get_dual(vector<pt> p){ // p: points corresponding to nodes
  ps.clear();es.clear();
  for (int x = 0, _n = n; x < _n; ++x){
    Cmp pc(p[x]); // (radial order of points)
    auto comp=[&](int a, int b){return pc(p[a],p[b]);};
    sort(g[x].begin(),g[x].end(),comp);
    for (int i = 0, _n = g[x].size(; i < _n; ++i))ps[{x,g[x][i]}]=i;
  }
  nd=0;
  for (int xx = 0, _n = n; xx < _n; ++xx)for(auto yy:g[xx])if(!es.count
      ({xx,yy})){
    int x=xx,y=yy;gd[nd].clear();nodes[nd].clear();
    while(!es.count({x,y})){
      es[{x,y}]=nd;nodes[nd].push_back(y);
      int z=g[y][(ps[{y,x}]+1)%g[y].size()];x=y;y=z;
    }
    nd++;
  }
  for(auto p:es){
    pair<int,int> q={p.first.second,p.first.first};
    assert(es.count(q));
    if(es[q]!=p.second)gd[p.second].push_back(es[q]);
  }
  for (int i = 0, _n = nd; i < _n; ++i){
    sort(gd[i].begin(),gd[i].end());
    gd[i].erase(unique(gd[i].begin(),gd[i].end()),gd[i].end());
  }
}
```

5.9 Halfplane intersection

```
// polygon intersecting left side of halfplanes
struct halfplane:public ln{
  double angle;
  halfplane(){}
  halfplane(pt a,pt b){p=a; pq=b-a; angle=atan2(pq.y,pq.x);}
  bool operator<(halfplane b)const{return angle<b.angle;}
  bool out(pt q){return pq%(q-p)<-EPS;}
};
vector<pt> intersect(vector<halfplane> b){
  vector<pt>bx={{DINF,DINF},{-DINF,DINF},{-DINF,-DINF},{DINF,-DINF}};
  for (int i = 0, _n = 4; i < _n; ++i) b.push_back(halfplane(bx[i],bx[(i
      +1)%4]));
  sort(ALL(b));
  int n=((int)(b).size()),q=1,h=0;
  vector<halfplane> c(((int)(b).size())+10);
  for (int i = 0, _n = n; i < _n; ++i){
    while(q<h&&b[i].out(c[h]^c[h-1])) h--;
    while(q<h&&b[i].out(c[q]^c[q+1])) q++;
    c[++h]=b[i];
    if(q<h&&abs(c[h].pq%c[h-1].pq)<EPS){
      if(c[h].pq*c[h-1].pq<=0) return {};
      h--;
      if(b[i].out(c[h].p)) c[h]=b[i];
    }
  }
  while(q<h-1&&c[q].out(c[h]^c[h-1]))h--;
  while(q<h-1&&c[h].out(c[q]^c[q+1]))q++;
```

```
  if(h-q<=1)return {};
  c[h+1]=c[q];
  vector<pt> s;
  for (int i = q, _n = h+1; i < _n; ++i) s.push_back(c[i]^c[i+1]);
  return s;
}
```

5.10 KD tree

```
// given a set of points, answer queries of nearest point in O(log(n))
bool onx(pt a, pt b){return a.x<b.x;}
bool ony(pt a, pt b){return a.y<b.y;}
struct Node {
  pt pp;
  ll x0=INF, x1=-INF, y0=INF, y1=-INF;
  Node *first=0, *second=0;
  ll distance(pt p){
    ll x=min(max(x0,p.x),x1);
    ll y=min(max(y0,p.y),y1);
    return (pt(x,y)-p).norm2();
  }
  Node(vector<pt>&& vp):pp(vp[0]){
    for(pt p:vp){
      x0=min(x0,p.x); x1=max(x1,p.x);
      y0=min(y0,p.y); y1=max(y1,p.y);
    }
    if(((int)(vp).size())>1){
      sort(ALL(vp),x1-x0>=y1-y0?onx:ony);
      int m=((int)(vp).size())/2;
      first=new Node({vp.begin(),vp.begin()+m});
      second=new Node({vp.begin()+m,vp.end()});
    }
  }
};
struct KDTree {
  Node* root;
  KDTree(const vector<pt>& vp):root(new Node({ALL(vp)})) {}
  pair<ll,pt> search(pt p, Node *node){
    if(!node->first){
      //avoid query point as answer
      //if(p==node->pp) {INF,pt()};
      return {(p-node->pp).norm2(),node->pp};
    }
    Node *f=node->first, *s=node->second;
    ll bf=f->distance(p), bs=s->distance(p);
    if(bf>bs)swap(bf,bs),swap(f,s);
    auto best=search(p,f);
    if(bs<best.first) best=min(best,search(p,s));
    return best;
  }
  pair<ll,pt> nearest(pt p){return search(p,root);}
};
```

5.11 Minkowski sum

```
// Compute Minkowski sum of two CONVEX polygons (remove collinear first)
// Returns answer in CCW order
void reorder(vector<pt> &p){
  if(!p[2].left(p[0],p[1])) reverse(ALL(p));
  int pos=0;
  for (int i = 1, _n = ((int)(p; i < _n; ++i).size())) if(pt(p[i].y,p[i
      ].x) < pt(p[pos].y,p[pos].x)) pos=i;
  rotate(p.begin(), p.begin()+pos, p.end());
}
vector<pt> minkowski_sum(vector<pt> p, vector<pt> q){
  if(min(((int)(p).size()),((int)(q).size()))<3){
    vector<pt> v;
    for(pt pp:p) for(pt qq:q) v.push_back(pp+qq);
    return chull(v);
  }
  reorder(p); reorder(q);
  for (int i = 0, _n = 2; i < _n; ++i) p.push_back(p[i]), q.push_back(q[
      i]);
  vector<pt> r;
  int i=0,j=0;
  while(i+2<((int)(p).size())||j+2<((int)(q).size())){
    r.push_back(p[i]+q[j]);
    auto cross=(p[i+1]-p[i])%(q[j+1]-q[j]);
    i+=cross>=-EPS;
    j+=cross<=EPS;
  }
  return r;
}
```

5.12 Delaunay triangulation

```
// Returns planar graph representing Delaunay's triangulation.
```

```
2  // Edges for each vertex are in ccw order.
3  // It can work with doubles, but also integers (replace long double in line 51)
4  typedef struct QuadEdge* Q;
5  struct QuadEdge {
6    int id,used;
7    pt o;
8    Q rot,nxt;
9    QuadEdge(int id=-1, pt o=pt(INF,INF)):id(id),used(0),o(o),rot(0),nxt(0){}
10   Q rev(){return rot->rot;}
11   Q next(){return nxt;}
12   Q prev(){return rot->next()->rot;}
13   pt dest(){return rev()->o;}
14 };
15
16 Q edge(pt a, pt b, int ida, int idb){
17   Q e1=new QuadEdge(ida,a);
18   Q e2=new QuadEdge(idb,b);
19   Q e3=new QuadEdge;
20   Q e4=new QuadEdge;
21   tie(e1->rot,e2->rot,e3->rot,e4->rot)={e3,e4,e2,e1};
22   tie(e1->nxt,e2->nxt,e3->nxt,e4->nxt)={e1,e2,e4,e3};
23   return e1;
24 }
25
26 void splice(Q a, Q b){
27   swap(a->nxt->rot->nxt,b->nxt->rot->nxt);
28   swap(a->nxt,b->nxt);
29 }
30
31 void del_edge(Q& e, Q ne){
32   splice(e,e->prev()); splice(e->rev(),e->rev()->prev());
33   delete e->rev()->rot; delete e->rev();
34   delete e->rot; delete e;
35   e=ne;
36 }
37
38 Q conn(Q a, Q b){
39   Q e=edge(a->dest(),b->o,a->rev()->id,b->id);
40   splice(e,a->rev()->prev());
41   splice(e->rev(),b);
42   return e;
43 }
44
45 auto area(pt p, pt q, pt r){return (q-p)%(r-q);}
46
47 // is p in circunference formed by (a,b,c)?
48 bool in_c(pt a, pt b, pt c, pt p){
49   // Warning: this number is O(max_coord^4).
50   // Consider using int128 or using an alternative method for this function
51   long double p2=p*p,A=a*a-p2,B=b*b-p2,C=c*c-p2;
52   return area(p,a,b)*C+area(p,b,c)*A+area(p,c,a)*B>EPS;
53 }
54
55 pair<Q,Q> build_tr(vector<pt>& p, int l, int r){
56   if(r-l+1<=3){
57     Q a=edge(p[l],p[l+1],l,l+1),b=edge(p[l+1],p[r],l+1,r);
58     if(r-l+1==2) return {a,a->rev()};
59     splice(a->rev(),b);
60     auto ar=area(p[l],p[l+1],p[r]);
61     Q c=abs(ar)>EPS?conn(b,a):0;
62     if(ar>=-EPS) return {a,b->rev()};
63     return {c->rev(),c};
64   }
65   int m=(l+r)/2;
66   auto [la,ra]=build_tr(p,l,m);
67   auto [lb,rb]=build_tr(p,m+1,r);
68   while(1){
69     if(ra->dest().left(lb->o,ra->o)) ra=ra->rev()->prev();
70     else if(lb->dest().left(lb->o,ra->o)) lb=lb->rev()->next();
71     else break;
72   }
73   Q b=conn(lb->rev(),ra);
74   auto valid=[&](Q e){return b->o.left(e->dest(),b->dest());};
75   if(ra->o==la->o) la=b->rev();
76   if(lb->o==rb->o) rb=b;
77   while(1){
78     Q L=b->rev()->next();
79     if(valid(L)) while(in_c(b->dest(),b->o,L->dest(),L->next()->dest())) del_edge(L,L->next());
80     Q R=b->prev();
81     if(valid(R)) while(in_c(b->dest(),b->o,R->dest(),R->prev()->dest())) del_edge(R,R->prev());
82     if(!valid(L)&&!valid(R)) break;
```

```
    if(!valid(L)||(valid(R)&&in_c(L->dest(),L->o,R->o,R->dest()))) b=conn(R,b->rev());
    else b=conn(b->rev(),L->rev());
  }
  return {la,rb};
}

vector<vector<int>> delaunay(vector<pt> v){
  int n=((int)(v).size()); auto tmp=v;
  vector<int> id(n); iota(ALL(id),0);
  sort(ALL(id),[&](int l, int r){return v[l]<v[r];});
  for (int i = 0, _n = n; i < _n; ++i) v[i]=tmp[id[i]];
  assert(unique(ALL(v))==v.end());
  vector<vector<int>> g(n);
  int col=1;
  for (int i = 2, _n = n; i < _n; ++i) col&=abs(area(v[i],v[i-1],v[i-2]))<=EPS;
  if(col){
    for (int i = 1, _n = n; i < _n; ++i) g[id[i-1]].push_back(id[i]),g[id[i]].push_back(id[i-1]);
  }
  else{
    Q e=build_tr(v,0,n-1).first;
    vector<Q> edg={e};
    for(int i=0;i<((int)(edg).size());e=edg[i++]){
      for(Q at=e;!at->used;at=at->next()){
        at->used=1;
        g[id[at->id]].push_back(id[at->rev()->id]);
        edg.push_back(at->rev());
      }
    }
  }
  return g;
}
```

6 Strings

6.1 KMP

```
vector<int> kmppre(string& t){ // r[i]: longest border of t[0,i)
  vector<int> r(t.size()+1);r[0]=-1;
  int j=-1;
  for (int i = 0, _n = t.size(; i < _n; ++i)){
    while(j>=0&&t[i]!=t[j])j=r[j];
    r[i+1]=++j;
  }
  return r;
}
void kmp(string& s, string& t){ // find t in s
  int j=0;vector<int> b=kmppre(t);
  for (int i = 0, _n = s.size(; i < _n; ++i)){
    while(j>=0&&s[i]!=t[j])j=b[j];
    if(++j==t.size())printf("Match at %d\n",i-j+1),j=b[j];
  }
}
```

6.2 Z function

```
vector<int> z_function(string& s){
  int l=0,r=0,n=s.size();
  vector<int> z(s.size(),0); // z[i] = max k: s[0,k) == s[i,i+k)
  for (int i = 1, _n = n; i < _n; ++i){
    if(i<=r)z[i]=min(r-i+1,z[i-l]);
    while(i+z[i]<n&&s[z[i]]==s[i+z[i]])z[i]++;
    if(i+z[i]-1>r)l=i,r=i+z[i]-1;
  }
  return z;
}
```

6.3 Manacher

```
int d1[MAXN];//d1[i] = max odd palindrome centered on i
int d2[MAXN];//d2[i] = max even palindrome centered on i
//s  aabbaacaabbaa
//d1 1111117111111
//d2 0103010010301
void manacher(string& s){
  int l=0,r=-1,n=s.size();
  for (int i = 0, _n = n; i < _n; ++i){
    int k=i>r?1:min(d1[l+r-i],r-i);
    while(i+k<n&&i-k>=0&&s[i+k]==s[i-k])k++;
    d1[i]=k--;
    if(i+k>r)l=i-k,r=i+k;
  }
  l=0;r=-1;
  for (int i = 0, _n = n; i < _n; ++i){
    int k=i>r?0:min(d2[l+r-i+1],r-i+1);k++;
```

```
    while(i+k<=n&&i-k>=0&&s[i+k-1]==s[i-k])k++;
    d2[i]=--k;
    if(i+k-1>r)l=i-k,r=i+k-1;
  }
}
```

6.4 Aho-Corasick

```
struct vertex {
  map<char,int> next,go;
  int p,link;
  char pch;
  vector<int> leaf;
  vertex(int p=-1, char pch=-1):p(p),pch(pch),link(-1){}
};
vector<vertex> t;
void aho_init(){ //do not forget!!
  t.clear();t.push_back(vertex());
}
void add_string(string s, int id){
  int v=0;
  for(char c:s){
    if(!t[v].next.count(c)){
      t[v].next[c]=t.size();
      t.push_back(vertex(v,c));
    }
    v=t[v].next[c];
  }
  t[v].leaf.push_back(id);
}
int go(int v, char c);
int get_link(int v){
  if(t[v].link<0)
    if(!v||!t[v].p)t[v].link=0;
    else t[v].link=go(get_link(t[v].p),t[v].pch);
  return t[v].link;
}
int go(int v, char c){
  if(!t[v].go.count(c))
    if(t[v].next.count(c))t[v].go[c]=t[v].next[c];
    else t[v].go[c]=v==0?0:go(get_link(v),c);
  return t[v].go[c];
}
```

6.5 Suffix automaton

```
struct state {int len,link;map<char,int> next;}; //clear next!!
state st[100005];
int sz,last;
void sa_init(){
  last=st[0].len=0;sz=1;
  st[0].link=-1;
}
void sa_extend(char c){
  int k=sz++,p;
  st[k].len=st[last].len+1;
  for(p=last;p!=-1&&!st[p].next.count(c);p=st[p].link)st[p].next[c]=k;
  if(p==-1)st[k].link=0;
  else {
    int q=st[p].next[c];
    if(st[p].len+1==st[q].len)st[k].link=q;
    else {
      int w=sz++;
      st[w].len=st[p].len+1;
      st[w].next=st[q].next;st[w].link=st[q].link;
      for(;p!=-1&&st[p].next[c]==q;p=st[p].link)st[p].next[c]=w;
      st[q].link=st[k].link=w;
    }
  }
  last=k;
}
//  input: abcbcbc
//  i,link,len,next
//  0 -1 0 (a,1) (b,5) (c,7)
//  1 0 1 (b,2)
//  2 5 2 (c,3)
//  3 7 3 (b,4)
//  4 9 4 (c,6)
//  5 0 1 (c,7)
//  6 11 5 (b,8)
//  7 0 2 (b,9)
//  8 9 6 (c,10)
//  9 5 3 (c,11)
//  10 11 7
//  11 7 4 (b,8)
```

6.6 Palindromic Tree

```
struct palindromic_tree{
    static const int SIGMA=26;
    struct Node{
        int len, link, to[SIGMA];
        ll cnt;
        Node(int len, int link=0, ll cnt=1):len(len),link(link),cnt(cnt)
            {
            memset(to,0,sizeof(to));
        }
    };
    vector<Node> ns;
    int last;
    palindromic_tree():last(0){ns.push_back(Node(-1));ns.push_back(Node
        (0));}
    void add(int i, string &s){
        int p=last, c=s[i]-'a';
        while(s[i-ns[p].len-1]!=s[i])p=ns[p].link;
        if(ns[p].to[c]){
            last=ns[p].to[c];
            ns[last].cnt++;
        }else{
            int q=ns[p].link;
            while(s[i-ns[q].len-1]!=s[i])q=ns[q].link;
            q=max(1,ns[q].to[c]);
            last=ns[p].to[c]=((int)(ns).size());
            ns.push_back(Node(ns[p].len+2,q,1));
        }
    }
};
```

6.7 Suffix array (shorter but slower)

```
pair<int, int> sf[MAXN];
bool sacomp(int lhs, int rhs) {return sf[lhs]<sf[rhs];}
vector<int> constructSA(string& s){ // O(n log^2(n))
  int n=s.size();                   // (sometimes fast enough)
  vector<int> sa(n),r(n);
  for (int i = 0, _n = n; i < _n; ++i)r[i]=s[i];
  for(int m=1;m<n;m*=2){
    for (int i = 0, _n = n; i < _n; ++i)sa[i]=i,sf[i]={r[i],i+m<n?r[i+m
        ]:-1};
    stable_sort(sa.begin(),sa.end(),sacomp);
    r[sa[0]]=0;
    for (int i = 1, _n = n; i < _n; ++i)r[sa[i]]=sf[sa[i]]!=sf[sa[i-1]]?
        i:r[sa[i-1]];
  }
  return sa;
}
```

6.8 Suffix array

```
#define RB(x) (x<n?r[x]:0)
void csort(vector<int>& sa, vector<int>& r, int k){
  int n=sa.size();
  vector<int> f(max(255,n),0),t(n);
  for (int i = 0, _n = n; i < _n; ++i)f[RB(i+k)]++;
  int sum=0;
  fore(i,0,max(255,n))f[i]=(sum+=f[i])-f[i];
  for (int i = 0, _n = n; i < _n; ++i)t[f[RB(sa[i]+k)]++]=sa[i];
  sa=t;
}
vector<int> constructSA(string& s){ // O(n logn)
  int n=s.size(),rank;
  vector<int> sa(n),r(n),t(n);
  for (int i = 0, _n = n; i < _n; ++i)sa[i]=i,r[i]=s[i];
  for(int k=1;k<n;k*=2){
    csort(sa,r,k);csort(sa,r,0);
    t[sa[0]]=rank=0;
    for (int i = 1, _n = n; i < _n; ++i){
      if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!=RB(sa[i-1]+k))rank++;
      t[sa[i]]=rank;
    }
    r=t;
    if(r[sa[n-1]]==n-1)break;
  }
  return sa;
}
```

6.9 LCP (Longest Common Prefix)

```
vector<int> computeLCP(string& s, vector<int>& sa){
  int n=s.size(),L=0;
  vector<int> lcp(n),plcp(n),phi(n);
  phi[sa[0]]=-1;
  for (int i = 1, _n = n; i < _n; ++i)phi[sa[i]]=sa[i-1];
  for (int i = 0, _n = n; i < _n; ++i){
    if(phi[i]<0){plcp[i]=0;continue;}
```

```
    while(s[i+L]==s[phi[i]+L])L++;
    plcp[i]=L;
    L=max(L-1,0);
  }
  for (int i = 0, _n = n; i < _n; ++i)lcp[i]=plcp[sa[i]];
  return lcp; // lcp[i]=LCP(sa[i-1],sa[i])
}
```

6.10 Suffix Tree (Ukkonen's algorithm)

```
struct SuffixTree {
  char s[MAXN];
  map<int,int> to[MAXN];
  int len[MAXN]={INF},fpos[MAXN],link[MAXN];
  int node,pos,sz=1,n=0;
  int make_node(int p, int l){
    fpos[sz]=p;len[sz]=l;return sz++;}
  void go_edge(){
    while(pos>len[to[node][s[n-pos]]]){
      node=to[node][s[n-pos]];
      pos-=len[node];
    }
  }
  void add(int c){
    s[n++]=c;pos++;
    int last=0;
    while(pos>0){
      go_edge();
      int edge=s[n-pos];
      int& v=to[node][edge];
      int t=s[fpos[v]+pos-1];
      if(v==0){
        v=make_node(n-pos,INF);
        link[last]=node;last=0;
      }
      else if(t==c){link[last]=node;return;}
      else {
        int u=make_node(fpos[v],pos-1);
        to[u][c]=make_node(n-1,INF);
        to[u][t]=v;
        fpos[v]+=pos-1;len[v]-=pos-1;
        v=u;link[last]=u;last=u;
      }
      if(node==0)pos--;
      else node=link[node];
    }
  }
};
```

6.11 Hashing

```
struct Hash {
  int P=1777771,MOD[2],PI[2];
  vector<int> h[2],pi[2];
  Hash(string& s){
    MOD[0]=999727999;MOD[1]=1070777777;
    PI[0]=325255434;PI[1]=10018302;
    for (int k = 0, _n = 2; k < _n; ++k)h[k].resize(s.size()+1),pi[k].
        resize(s.size()+1);
    for (int k = 0, _n = 2; k < _n; ++k){
      h[k][0]=0;pi[k][0]=1;
      ll p=1;
      for (int i = 1, _n = s.size(; i < _n; ++i)+1){
        h[k][i]=(h[k][i-1]+p*s[i-1])%MOD[k];
        pi[k][i]=(1LL*pi[k][i-1]*PI[k])%MOD[k];
        p=(p*P)%MOD[k];
      }
    }
  }
  ll get(int s, int e){
    ll h0=(h[0][e]-h[0][s]+MOD[0])%MOD[0];
    h0=(1LL*h0*pi[0][s])%MOD[0];
    ll h1=(h[1][e]-h[1][s]+MOD[1])%MOD[1];
    h1=(1LL*h1*pi[1][s])%MOD[1];
    return (h0<<32)|h1;
  }
};
```

6.12 Hashing with ll (using __int128)

```
#define bint __int128
struct Hash {
  bint MOD=212345678987654321LL,P=1777771,PI=106955741089659571LL;
  vector<bint> h,pi;
  Hash(string& s){
    assert((P*PI)%MOD==1);
    h.resize(s.size()+1);pi.resize(s.size()+1);
```

```
    h[0]=0;pi[0]=1;
    bint p=1;
    for (int i = 1, _n = s.size(; i < _n; ++i)+1){
      h[i]=(h[i-1]+p*s[i-1])%MOD;
      pi[i]=(pi[i-1]*PI)%MOD;
      p=(p*P)%MOD;
    }
  }
  ll get(int s, int e){
    return (((h[e]-h[s]+MOD)%MOD)*pi[s])%MOD;
  }
};
```

7 Flow

7.1 Matching (slower)

```
vector<int> g[MAXN]; // [0,n)->[0,m)
int n,m;
int mat[MAXM];bool vis[MAXN];
int match(int x){
  if(vis[x])return 0;
  vis[x]=true;
  for(int y:g[x])if(mat[y]<0||match(mat[y])){mat[y]=x;return 1;}
  return 0;
}
vector<pair<int,int> > max_matching(){
  vector<pair<int,int> > r;
  memset(mat,-1,sizeof(mat));
  for (int i = 0, _n = n; i < _n; ++i)memset(vis,false,sizeof(vis)),
      match(i);
  for (int i = 0, _n = m; i < _n; ++i)if(mat[i]>=0)r.push_back({mat[i],i
      });
  return r;
}
```

7.2 Matching (Hopcroft-Karp)

```
vector<int> g[MAXN]; // [0,n)->[0,m)
int n,m;
int mt[MAXN],mt2[MAXN],ds[MAXN];
bool bfs(){
  queue<int> q;
  memset(ds,-1,sizeof(ds));
  for (int i = 0, _n = n; i < _n; ++i)if(mt2[i]<0)ds[i]=0,q.push(i);
  bool r=false;
  while(!q.empty()){
    int x=q.front();q.pop();
    for(int y:g[x]){
      if(mt[y]>=0&&ds[mt[y]]<0)ds[mt[y]]=ds[x]+1,q.push(mt[y]);
      else if(mt[y]<0)r=true;
    }
  }
  return r;
}
bool dfs(int x){
  for(int y:g[x])if(mt[y]<0||ds[mt[y]]==ds[x]+1&&dfs(mt[y])){
    mt[y]=x;mt2[x]=y;
    return true;
  }
  ds[x]=1<<30;
  return false;
}
int mm(){
  int r=0;
  memset(mt,-1,sizeof(mt));memset(mt2,-1,sizeof(mt2));
  while(bfs()){
    for (int i = 0, _n = n; i < _n; ++i)if(mt2[i]<0)r+=dfs(i);
  }
  return r;
}
```

7.3 Hungarian

```
typedef long double td; typedef vector<int> vi; typedef vector<td> vd;
const td INF=1e100;//for maximum set INF to 0, and negate costs
bool zero(td x){return fabs(x)<1e-9;}//change to x==0, for ints/ll
struct Hungarian{
    int n; vector<vd> cs; vi L, R;
    Hungarian(int N, int M):n(max(N,M)),cs(n,vd(n)),L(n),R(n){
        for (int x = 0, _n = N; x < _n; ++x)for (int y = 0, _n = M; y <
            _n; ++y)cs[x][y]=INF;
    }
    void set(int x,int y,td c){cs[x][y]=c;}
  td assign() {
    int mat = 0; vd ds(n), u(n), v(n); vi dad(n), sn(n);
```

```
    for (int i = 0, _n = n; i < _n; ++i)u[i]=*min_element(ALL(cs[i]));
    for (int j = 0, _n = n; j < _n; ++j){v[j]=cs[0][j]-u[0];for (int i = 1, _n = n; i < _n; ++i)v[j]=min(v[j],cs[i][j]-u[i]);}
    L=R=vi(n, -1);
    for (int i = 0, _n = n; i < _n; ++i)for (int j = 0, _n = n; j < _n; ++j)
      if(R[j]==-1&&zero(cs[i][j]-u[i]-v[j])){L[i]=j;R[j]=i;mat++;break;}
    for(;mat<n;mat++){
        int s=0, j=0, i;
        while(L[s] != -1)s++;
        fill(ALL(dad),-1);fill(ALL(sn),0);
        for (int k = 0, _n = n; k < _n; ++k)ds[k]=cs[s][k]-u[s]-v[k];
        for(;;){
            j = -1;
            for (int k = 0, _n = n; k < _n; ++k)if(!sn[k]&&(j==-1||ds[k]<ds[j]))j=k;
            sn[j] = 1; i = R[j];
            if(i == -1) break;
            for (int k = 0, _n = n; k < _n; ++k)if(!sn[k]){
                auto new_ds=ds[j]+cs[i][k]-u[i]-v[k];
                if(ds[k] > new_ds){ds[k]=new_ds;dad[k]=j;}
            }
        }
        for (int k = 0, _n = n; k < _n; ++k)if(k!=j&&sn[k]){auto w=ds[k]-ds[j];v[k]+=w,u[R[k]]-=w;}
        u[s] += ds[j];
        while(dad[j]>=0){int d = dad[j];R[j]=R[d];L[R[j]]=j;j=d;}
        R[j]=s;L[s]=j;
    }
    td value=0;for (int i = 0, _n = n; i < _n; ++i)value+=cs[i][L[i]];
    return value;
  }
};
```

7.4 Dinic

```
// Min cut: nodes with dist>=0 vs nodes with dist<0
// Matching MVC: left nodes with dist<0 + right nodes with dist>0
struct Dinic{
  int nodes,src,dst;
  vector<int> dist,q,work;
  struct edge {int to,rev;ll f,cap;};
  vector<vector<edge>> g;
  Dinic(int x):nodes(x),g(x),dist(x),q(x),work(x){}
  void add_edge(int s, int t, ll cap){
    g[s].push_back((edge){t,((int)(g[t]).size()),0,cap});
    g[t].push_back((edge){s,((int)(g[s]).size())-1,0,0});
  }
  bool dinic_bfs(){
    fill(ALL(dist),-1);dist[src]=0;
    int qt=0;q[qt++]=src;
    for(int qh=0;qh<qt;qh++){
      int u=q[qh];
      for (int i = 0, _n = ((int)(g[u]; i < _n; ++i).size())){
        edge &e=g[u][i];int v=g[u][i].to;
        if(dist[v]<0&&e.f<e.cap)dist[v]=dist[u]+1,q[qt++]=v;
      }
    }
    return dist[dst]>=0;
  }
  ll dinic_dfs(int u, ll f){
    if(u==dst)return f;
    for(int &i=work[u];i<((int)(g[u]).size());i++){
      edge &e=g[u][i];
      if(e.cap<=e.f)continue;
      int v=e.to;
      if(dist[v]==dist[u]+1){
        ll df=dinic_dfs(v,min(f,e.cap-e.f));
        if(df>0){e.f+=df;g[v][e.rev].f-=df;return df;}
      }
    }
    return 0;
  }
  ll max_flow(int _src, int _dst){
    src=_src;dst=_dst;
    ll result=0;
    while(dinic_bfs()){
      fill(ALL(work),0);
      while(ll delta=dinic_dfs(src,INF))result+=delta;
    }
    return result;
  }
};
```

7.5 Min cost max flow

```cpp
typedef ll tf;
typedef ll tc;
const tf INFFLOW=1e9;
const tc INFCOST=1e9;
struct MCF{
  int n;
  vector<tc> prio, pot; vector<tf> curflow; vector<int> prevedge, prevnode;
  priority_queue<pair<tc, int>, vector<pair<tc, int>>, greater<pair<tc, int>>> q;
  struct edge{int to, rev; tf f, cap; tc cost;};
  vector<vector<edge>> g;
  MCF(int n):n(n),prio(n),curflow(n),prevedge(n),prevnode(n),pot(n),g(n){}
  void add_edge(int s, int t, tf cap, tc cost) {
    g[s].push_back((edge){t,((int)(g[t]).size()),0,cap,cost});
    g[t].push_back((edge){s,((int)(g[s]).size())-1,0,0,-cost});
  }
  pair<tf,tc> get_flow(int s, int t) {
    tf flow=0; tc flowcost=0;
    while(1){
      q.push({0, s});
      fill(ALL(prio),INFCOST);
      prio[s]=0; curflow[s]=INFFLOW;
      while(!q.empty()) {
        auto cur=q.top();
        tc d=cur.first;
        int u=cur.second;
        q.pop();
        if(d!=prio[u]) continue;
        for(int i=0; i<((int)(g[u]).size()); ++i) {
          edge &e=g[u][i];
          int v=e.to;
          if(e.cap<=e.f) continue;
          tc nprio=prio[u]+e.cost+pot[u]-pot[v];
          if(prio[v]>nprio) {
            prio[v]=nprio;
            q.push({nprio, v});
            prevnode[v]=u; prevedge[v]=i;
            curflow[v]=min(curflow[u], e.cap-e.f);
          }
        }
      }
      if(prio[t]==INFCOST) break;
      for (int i = 0, _n = n; i < _n; ++i) pot[i]+=prio[i];
      tf df=min(curflow[t], INFFLOW-flow);
      flow+=df;
      for(int v=t; v!=s; v=prevnode[v]) {
        edge &e=g[prevnode[v]][prevedge[v]];
        e.f+=df; g[v][e.rev].f-=df;
        flowcost+=df*e.cost;
      }
    }
    return {flow,flowcost};
  }
};
```

8 Other

8.1 Mo's algorithm

```cpp
int n,sq,nq; // array size, sqrt(array size), #queries
struct qu{int l,r,id;};
qu qs[MAXN];
ll ans[MAXN]; // ans[i] = answer to ith query
bool qcomp(const qu &a, const qu &b){
    if(a.l/sq!=b.l/sq) return a.l<b.l;
    return (a.l/sq)&1?a.r<b.r:a.r>b.r;
}
void mos(){
    for (int i = 0, _n = nq; i < _n; ++i)qs[i].id=i;
    sq=sqrt(n)+.5;
    sort(qs,qs+nq,qcomp);
    int l=0,r=0;
    init();
    for (int i = 0, _n = nq; i < _n; ++i){
        qu q=qs[i];
        while(l>q.l)add(--l);
        while(r<q.r)add(r++);
        while(l<q.l)remove(l++);
        while(r>q.r)remove(--r);
        ans[q.id]=get_ans();
    }
}
```

8.2 Divide and conquer DP optimization

```cpp
// O(knlogn). For 2D dps, when the position of optimal choice is non-decreasing as the second variable increases
int k,n,f[MAXN],f2[MAXN];
void doit(int s, int e, int s0, int e0, int i){
  // [s,e): range of calculation, [s0,e0): range of optimal choice
  if(s==e)return;
  int m=(s+e)/2,r=INF,rp;
  fore(j,s0,min(e0,m)){
    int r0=something(i,j); // "something" usually depends on f
    if(r0<r)r=r0,rp=j; // position of optimal choice
  }
  f2[m]=r;
  doit(s,m,s0,rp+1,i);doit(m+1,e,rp,e0,i);
}
int doall(){
  init_base_cases();
  for (int i = 1, _n = k; i < _n; ++i)doit(1,n+1,0,n,i),memcpy(f,f2,sizeof(f));
  return f[n];
}
```

8.3 Dates

```cpp
int dateToInt(int y, int m, int d){
  return 1461*(y+4800+(m-14)/12)/4+367*(m-2-(m-14)/12*12)/12-3*((y+4900+(m-14)/12)/100)/4+d-32075;
}
void intToDate(int jd, int& y, int& m, int& d){
  int x,n,i,j;x=jd+68569;
  n=4*x/146097;x-=(146097*n+3)/4;
  i=(4000*(x+1))/1461001;x-=1461*i/4-31;
  j=80*x/2447;d=x-2447*j/80;
  x=j/11;m=j+2-12*x;y=100*(n-49)+i+x;
}
int DayOfWeek(int d, int m, int y){ //starting on Sunday
  static int ttt[]={0, 3, 2, 5, 0, 3, 5, 1, 4, 6, 2, 4};
  y-=m<3;
  return (y+y/4-y/100+y/400+ttt[m-1]+d)%7;
}
```

8.4 C++ stuff

```cpp
// --- 1. PRECISION Y CONSTANTES ---
// Valor infinito para double. Mas seguro que usar 1e18 o similares.
const double DINF = numeric_limits<double>::infinity();

// Epsilon: margen de error para comparar flotantes.
// Ajustar segun el problema (usualmente entre 1e-7 y 1e-9).
const double EPS = 1e-9;

// Comparador personalizado para usar double como llave en set o map.
// Evita que 0.3000000000001 y 0.3 sean tratados como distintos.
struct DoubleComparator {
    bool operator()(const double& a, const double& b) const {
        // Se considera que a < b solo si a es menor que b por al menos EPS.
        return a + EPS < b;
    }
};

// Uso: set<double, DoubleComparator> mi_set;

// --- 2. TRUCOS DE BITMASKS ---

void bitmask_tricks(int m) {
    // Iterar sobre todos los subconjuntos de la mascara 'm' (Orden decreciente)
    // Ejemplo: si m = 1010 (10), iterara por 1010, 1000, 0010.
    for (int s = m; s > 0; s = (s - 1) & m) {
        // s es un subconjunto no vacio de m
    }

    // Iterar sobre todos los subconjuntos de 'm' (Orden creciente)
    // Esta sintaxis es muy compacta; 's = (s - m) & m' hace la magia.
    for (int s = 0; s = (s - m) & m; ) {
        // s es un subconjunto no vacio de m
    }
}

// --- 3. BUILT-INS DE GCC (Super rapidos) ---

void built_ins(unsigned int x, unsigned long long xll) {
    // Cuenta cuantos bits estan encendidos (en 1).
    int unos = __builtin_popcount(x);

    // Cuenta ceros al final (derecha).
    // Util para saber la potencia de 2 mas grande que divide a x.
```

```cpp
    // OJO: __builtin_ctz(0) es INDEFINIDO.
    if (x != 0) {
        int ceros_derecha = __builtin_ctz(x);
    }

    // Cuenta ceros al inicio (izquierda).
    // Util para saber cuantos bits se necesitan para representar el numero.
    // OJO: __builtin_clz(0) es INDEFINIDO.
    if (x != 0) {
        int ceros_izquierda = __builtin_clz(x);
    }

    // Versiones para long long (64 bits): solo agrega el sufijo 'll'
    int unos_ll = __builtin_popcountll(xll);
}

// --- 4. LEAST SIGNIFICANT BIT (LSB) ---

int get_lsb(int x) {
    // Aisla el bit encendido mas a la derecha.
    // Ejemplo: x = 12 (1100), -x en binario es (0100), x & -x = 4 (0100).
    return x & (-x);
}
```

8.5 Interactive problem tester template

```python
#Easier method with bash commands:
#mkfifo fifo
#(./solution < fifo) | (./interactor > fifo)

# tester for cf 101021A (guess a number, queries: is it >=k?)
import random
import subprocess as sp
seed = random.randint(0, sys.maxint);random.seed(seed)
n=random.randint(1,1000000)
try:
  p=sp.Popen(['./a.out'],stdin=sp.PIPE,stdout=sp.PIPE)
  it=0
  s=p.stdout.readline()
  while it<25 and s and s[0]!='!':
    k=int(s)
    assert k>=1 and k<=1000000
    if n>=k: p.stdin.write('>=\n')
    else: p.stdin.write('<\n')
    s=p.stdout.readline()
    it+=1
  assert s and s[0]=='!'
  k=int(s.split()[1])
  assert k==n
except:
  print 'failed with seed %s' % seed
  raise
```

8.6 Max number of divisors up to 10^n

```
(0,1) (1,4) (2,12) (3,32) (4,64) (5,128) (6,240) (7,448) (8,768)
    (9,1344) (10,2304) (11,4032) (12,6720) (13,10752) (14,17280)
    (15,26880) (16,41472) (17,64512) (18,103680)
```

8.7 Template

```cpp
#include <bits/stdc++.h>

using namespace std;
typedef long long ll;

int main(){
  return 0;
}
```