



List of SQL Commands

Glossary of commonly used SQL commands.

Update: Cheat Sheets BETA is here!

- Learn SQL: [Manipulation](#)
- Learn SQL: [Queries](#)
- Learn SQL: [Aggregate Functions](#)
- Learn SQL: [Multiple Tables](#)

Background

SQL, **S**tructured **Q**uery **L**anguage, is a programming language designed to manage data stored in relational databases. SQL operates through simple, declarative statements. This keeps data accurate and secure, and it helps maintain the integrity of

Here's an appendix of commonly used commands.

Commands

ALTER TABLE

```
ALTER TABLE table_name  
ADD column_name datatype;
```

ALTER TABLE lets you add columns to a table in a database.

AND

```
SELECT column_name(s)  
FROM table_name  
WHERE column_1 = value_1  
      AND column_2 = value_2;
```

AND is an operator that combines two conditions. Both conditions must be true for the row to be included in the result set.

AS

```
SELECT column_name AS 'Alias'  
FROM table_name;
```

AVG()

```
SELECT AVG(column_name)
FROM table_name;
```

`AVG()` is an aggregate function that returns the average value for a numeric column.

BETWEEN

```
SELECT column_name(s)
FROM table_name
WHERE column_name BETWEEN value_1 AND value_2;
```

The `BETWEEN` operator is used to filter the result set within a certain range. The values can be numbers, text or dates.

CASE

```
SELECT column_name,
CASE
    WHEN condition THEN 'Result_1'
    WHEN condition THEN 'Result_2'
    ELSE 'Result_3'
END
FROM table_name;
```

`CASE` statements are used to create different outputs (usually in the `SELECT`

COUNT()

```
SELECT COUNT(column_name)
FROM table_name;
```

`COUNT()` is a function that takes the name of a column as an argument and counts the number of rows where the column is not `NULL`.

CREATE TABLE

```
CREATE TABLE table_name (
    column_1 datatype,
    column_2 datatype,
    column_3 datatype
);
```

`CREATE TABLE` creates a new table in the database. It allows you to specify the name of the table and the name of each column in the table.

DELETE

```
DELETE FROM table_name
WHERE some_column = some_value;
```

`DELETE` statements are used to remove rows from a table.

```
SELECT column_name, COUNT(*)  
FROM table_name  
GROUP BY column_name;
```

GROUP BY is a clause in SQL that is only used with aggregate functions. It is used in collaboration with the **SELECT** statement to arrange identical data into groups.

HAVING

```
SELECT column_name, COUNT(*)  
FROM table_name  
GROUP BY column_name  
HAVING COUNT(*) > value;
```

HAVING was added to SQL because the **WHERE** keyword could not be used with aggregate functions.

INNER JOIN

```
SELECT column_name(s)  
FROM table_1  
JOIN table_2  
ON table_1.column_name = table_2.column_name;
```

An inner join will combine rows from different tables if the *join condition* is true.

INSERT

```
INSERT INTO table_name (column_1, column_2, column_3)
VALUES (value_1, 'value_2', value_3);
```

`INSERT` statements are used to add a new row to a table.

IS NULL / IS NOT NULL

```
SELECT column_name(s)
FROM table_name
WHERE column_name IS NULL;
```

`IS NULL` and `IS NOT NULL` are operators used with the `WHERE` clause to test for empty values.

LIKE

```
SELECT column_name(s)
FROM table_name
WHERE column_name LIKE pattern;
```

`LIKE` is a special operator used with the `WHERE` clause to search for a specific pattern in a column.

LIMIT

```
SELECT column_name(s)
```

LIMIT is a clause that lets you specify the maximum number of rows the result set will have.

MAX()

```
SELECT MAX(column_name)
FROM table_name;
```

MAX() is a function that takes the name of a column as an argument and returns the largest value in that column.

MIN()

```
SELECT MIN(column_name)
FROM table_name;
```

MIN() is a function that takes the name of a column as an argument and returns the smallest value in that column.

OR

```
SELECT column_name
FROM table_name
WHERE column_name = value_1
      OR column_name = value_2;
```

OR is an operator that filters the result set to only include rows where either condition is true.

ORDER BY

```
SELECT column_name  
FROM table_name  
ORDER BY column_name ASC | DESC;
```

ORDER BY is a clause that indicates you want to sort the result set by a particular column either alphabetically or numerically.

OUTER JOIN

```
SELECT column_name(s)  
FROM table_1  
LEFT JOIN table_2  
ON table_1.column_name = table_2.column_name;
```

An outer join will combine rows from different tables even if the join condition is not met. Every row in the *left* table is returned in the result set, and if the join condition is not met, then **NULL** values are used to fill in the columns from the *right* table.

ROUND()

```
SELECT ROUND(column_name, integer)
```


`ROUND()` is a function that takes a column name and an integer as arguments. It rounds the values in the column to the number of decimal places specified by the integer.

SELECT

```
SELECT column_name  
FROM table_name;
```

`SELECT` statements are used to fetch data from a database. Every query will begin with `SELECT`.

SELECT DISTINCT

```
SELECT DISTINCT column_name  
FROM table_name;
```

`SELECT DISTINCT` specifies that the statement is going to be a query that returns unique values in the specified column(s).

SUM

```
SELECT SUM(column_name)  
FROM table_name;
```

UPDATE

```
UPDATE table_name  
SET some_column = some_value  
WHERE some_column = some_value;
```

UPDATE statements allow you to edit rows in a table.

WHERE

```
SELECT column_name(s)  
FROM table_name  
WHERE column_name operator value;
```

WHERE is a clause that indicates you want to filter the result set to include only rows where the following *condition* is true.

WITH

```
WITH temporary_name AS (  
    SELECT *  
    FROM table_name)  
SELECT *  
FROM temporary_name  
WHERE column_name operator value;
```

WITH clause lets you store the result of a query in a temporary table using an alias.

The `WITH` clause is also known as common table expression (CTE) and subquery factoring.