

A modern conference room with large windows and a blue tint. The room features a long table, several chairs, and a laptop on the table. The windows offer a view of a cityscape.

# Integers

# Integers

text ≠ numbers



numeric data types

integer

fixed-point

floating-point



**integers**

whole numbers with no decimal point

e.g. 5; 15; -200; 1,000

**INTEGER**

**INT**

# Integers

<u>numeric data type</u>	<u>size</u> (bytes)	<u>minimum value</u> (signed/unsigned)	<u>maximum value</u> (signed/unsigned)
TINYINT	1	-128	127
		0	255
SMALLINT	2	-32,768	32,767
		0	65,535
MEDIUMINT	3	-8,388,608	8,388,607
		0	16,777,215
INT	4	-2,147,483,648	2,147,483,647
		0	4,294,967,295
BIGINT	8	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
		0	18,446,744,073,709,551,615

# Integers

signed ≠ unsigned



if the encompassed range includes  
both positive and negative values

# Integers

<u>numeric data type</u>	<u>size</u> (bytes)	<u>minimum value</u> (signed/unsigned)	<u>maximum value</u> (signed/unsigned)
TINYINT	1	-128	127
		0	255
SMALLINT	2	-32,768	32,767
		0	65,535
MEDIUMINT	3	-8,388,608	8,388,607
		0	16,777,215
INT	4	-2,147,483,648	2,147,483,647
		0	4,294,967,295
BIGINT	8	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
		0	18,446,744,073,709,551,615

# Integers

signed ≠ unsigned



if the encompassed range includes  
both positive and negative values



if integers are allowed to be only  
positive

# Integers

<u>numeric data type</u>	<u>size</u> (bytes)	<u>minimum value</u> (signed/unsigned)	<u>maximum value</u> (signed/unsigned)
TINYINT	1	-128	127
		0	255
SMALLINT	2	-32,768	32,767
		0	65,535
MEDIUMINT	3	-8,388,608	8,388,607
		0	16,777,215
INT	4	-2,147,483,648	2,147,483,647
		0	4,294,967,295
BIGINT	8	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
		0	18,446,744,073,709,551,615

# Integers

- integer data types are 'signed' by default



# Integers

<u>numeric data type</u>	<u>size</u> (bytes)	<u>minimum value</u> (signed/unsigned)	<u>maximum value</u> (signed/unsigned)
TINYINT	1	-128	127
		0	256
SMALLINT	2	-32,768	32,767
		0	65,535
MEDIUMINT	3	-8,388,608	8,388,607
		0	16,777,215
INT	4	-2,147,483,648	2,147,483,647
		0	4,294,967,295
BIGINT	8	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
		0	18,446,744,073,709,551,615

# Integers

- integer data types are 'signed' by default
- if you want to use a range containing only positive, 'unsigned' values, you would have to specify this in your query

# Integers

<u>numeric data type</u>	<u>size</u> (bytes)	<u>minimum value</u> (signed/unsigned)	<u>maximum value</u> (signed/unsigned)
TINYINT	1	-128	127
		0	256
SMALLINT	2	-32,768	32,767
		0	65,535
MEDIUMINT	3	-8,388,608	8,388,607
		0	16,777,215
INT	4	-2,147,483,648	2,147,483,647
		0	4,294,967,295
BIGINT	8	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
		0	18,446,744,073,709,551,615

# Integers

- Why not just use **BIGINT** all the time?

# Integers

- Why not just use **BIGINT** all the time?
- e.g. if you are sure that, in a certain column, you won't need an integer smaller than 0 or greater than 100, **TINYINT** would do the job perfectly and you would not need more storage space per data point

# Integers

- Why not just use **BIGINT** all the time?
- e.g. if you are sure that, in a certain column, you won't need an integer smaller than 0 or greater than 100, **TINYINT** would do the job perfectly and you would not need more storage space per data point
- a smaller integer type may increase the processing speed