


#### <u>queries</u>

one of their main features is to manipulate data within a database



#### queries

one of their main features is to manipulate data within a database

e.g.



SELECT \* FROM customers;

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

#### **SQL** Objects:

- SQL table

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

#### SQL Objects:

- SQL table
- views
- stored procedures
- functions

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

1) set a default database

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

1) set a default database

```
</>>SQL
```

```
USE sales;
SELECT * FROM customers;
```

Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied

- 1) set a default database
- 2) call a table from a certain database

- Whenever you would like to refer to an *SQL object* in your queries, you must <u>specify the database</u> to which it is applied
  - 1) set a default database
  - 2) call a table from a certain database



database\_object . sql\_object



database\_object . sql\_object

. - "dot operator"
signals the existence of a connection between the two object types

```
database_object . sql_object

SQL SELECT * FROM sales.customers;
```

. - "dot operator"
signals the existence of a connection between the two object types

