Machine Learning: Practice Midterm

Name: _____

1. Evaluating classifiers (20 points)

A charity trains African giant pouched rats ("HeroRATs") to detect tuberculosis (TB) via their impressive sense of smell. To make sure the rats are effective, each rat is tested on 1000 samples of sputum. Suppose a laboratory test shows that 100 of them come from patients with TB. The rat pauses at 80% of the TB samples and at 10% of the others. Treat "has TB" as the positive class.

1.1 [4 points] Write down the confusion matrix.

1.2 [2 points] What are precision and recall for this rat?


1.3 [2 points] Do we care more about improving precision or recall for this problem, and why?

The rat handler also records how long the rat pauses at each sample before moving on. Here are 10 samples, 5 from TB patients and 5 without TB:

sample	A	B	C	D	E	F	G	H	I	J
pause (seconds)	2.6	0.6	4.6	2.0	1.3	3.7	4.2	1.0	3.0	2.4
TB?	yes	no	yes	no	yes	no	yes	no	yes	no

We say a rat flags a sample as TB if it pauses for over t seconds.

1.4 [10 points] Draw the ROC curve.



1.5 [2 points] Compute the AUC.

2. Support vector machines (20 points)

2.1 [10 points] A soft-margin SVM returned $\boldsymbol{w} = (4, 3)$, $b = -12$.

point	A	B	C	D	E
x_1	3	1	2.5	1	3
x_2	1	2	1	2.5	0.5
label	+	−	+	−	−

(a) Compute $f(\boldsymbol{x})$ and the predicted class of each point.

(b) What is the width of the margin?

(c) Compute each point's distance to the decision boundary.

(d) Which points are support vectors? Which point is on the margin, which is inside it, and which is misclassified?

2.2 [6 points] Write down the objective function for the soft-margin SVM and explain why this is what we want to optimize.

2.3 [2 points] Suppose our soft-margin SVM obtains 95% training accuracy but 60% validation accuracy. What does this suggest about our hyperparameter C?

2.4 [2 points] What are support vectors? Is every training datapoint that falls inside the margin a support vector?