Machine Learning: Midterm

Solutions

1. Evaluating classifiers (20 points)

A course runs an AI-text detector on all 400 essays submitted for an assignment. An honor-code review later established that 60 of the essays were written with AI. The detector flagged 50 essays, and 45 of the flagged essays were written with AI. Treat "written with AI" as the positive class.

1.1 [4 points] Write down the confusion matrix.

Solution: 60 AI-written essays and 340 human-written essays.

	flagged	not flagged
written with AI	TP = 45	FN = 15
human-written	FP = 5	TN = 335

1.2 [2 points] What are precision and recall for this detector?

Solution: Precision = $45/50 = 0.90$. Recall = $45/60 = 0.75$.

1.3 [2 points] Do we care more about improving precision or recall for this problem, and why?

Solution: Precision. A false positive accuses an innocent student of cheating; a missed AI essay (false negative) is a smaller harm. A flag should almost always be right before anyone acts on it.

The detector also gives each essay a score between 0 and 1; a higher score means "more likely written with AI". Here are 8 essays, 4 written with AI and 4 by students:


essay	1	2	3	4	5	6	7	8
score	0.95	0.85	0.70	0.60	0.50	0.40	0.30	0.10
written with AI?	yes	yes	no	yes	no	yes	no	no

We say the detector flags an essay as AI-written if its score is over t.

1.4 [10 points] Draw the ROC curve.

Solution: As t passes each essay, from the highest score down, an AI essay moves the point up by $1/4 = 0.25$ and a human essay moves it right by 0.25. Starting at $(0, 0)$, the points are

$$(0, 0.25),\ (0, 0.5),\ (0.25, 0.5),\ (0.25, 0.75),\ (0.5, 0.75),\ (0.5, 1),\ (0.75, 1),\ (1, 1).$$



1.5 [2 points] Compute the AUC.

Solution: The area under the staircase, in columns of width 0.25 with heights $0.5, 0.75, 1, 1$: $\text{AUC} = 0.25 \times (0.5 + 0.75 + 1 + 1) = 0.8125 \approx 0.81$.

2. Support vector machines (20 points)

2.1 [10 points] A soft-margin SVM returned $\boldsymbol{w} = (6, 8)$, $b = -20$.

point	A	B	C	D	E
x_1	3	1	1.5	1.25	3
x_2	1	1	1.5	1.5	0.5
label	+	−	+	−	−

(a) Compute $f(\boldsymbol{x})$ and the predicted class of each point.

(b) What is the width of the margin?

(c) Compute each point's distance to the decision boundary.

(d) Which points are support vectors? Which point is on the margin, which is inside it, and which is misclassified?

Solution: $f(\boldsymbol{x}) = 6x_1 + 8x_2 - 20$ and $\|\boldsymbol{w}\| = \sqrt{6^2 + 8^2} = 10$.

point	A	B	C	D	E
$f(\boldsymbol{x})$	6	−6	1	−0.5	2
predicted class	+	−	+	−	+
distance $\lvert f(\boldsymbol{x})\rvert/\|\boldsymbol{w}\|$	0.6	0.6	0.1	0.05	0.2
$y\, f(\boldsymbol{x})$	6	6	1	0.5	−2

(b) Margin width $= 2/\|\boldsymbol{w}\| = 2/10 = 0.2$.

(d) The support vectors are the points with $y\, f(\boldsymbol{x}) \le 1$: C, D and E. C is on the margin ($y\, f = 1$), D is inside the margin but correctly classified ($y\, f = 0.5$), and E is misclassified (label −, predicted +).

2.2 [6 points] Write down the optimization problem for the hard-margin SVM and explain why this is what we want to optimize.

Solution:

$$\min_{\boldsymbol{w}, b} \ \tfrac{1}{2}\|\boldsymbol{w}\|^2 \quad \text{subject to} \quad y_i(\boldsymbol{w} \cdot \boldsymbol{x}_i + b) \geq 1 \ \text{ for every } i.$$

The margin is $2/\|\boldsymbol{w}\|$, so minimizing $\frac{1}{2}\|\boldsymbol{w}\|^2$ maximizes the margin. The constraints require every training point to be on its correct side of the boundary and outside the margin. Among all lines that separate the data, this picks the one that leaves the most room on both sides.

2.3 [2 points] Two soft-margin SVMs are trained on the same data, one with $C = 0.01$ and one with $C = 100$. Which one has the wider margin, and which one is more likely to overfit?

Solution: $C = 0.01$ has the wider margin: slack is cheap, so the SVM allows many points inside the margin. $C = 100$ is more likely to overfit: violations are expensive, so the margin narrows to fit individual training points.

2.4 [2 points] You remove a training point that is not a support vector and retrain the SVM. What changes? Why?

Solution: Nothing. The solution depends only on the support vectors; a point outside the margin does not affect $\boldsymbol{w}$ or b.