

Documentación Soccer API:

Authentication:

Default user:

```
"id": "123",  
"name": "juane",  
"username": "juancode9",  
"password": "1234"
```

For login use the route : api/auth/login and the credentials as a json

```
{  
  "username": "juancode9",  
  "password": "1234"  
}
```

It responds the token that you can copy for use as authorization as bearer token for the required routes.

For the exercise the routes queries that needs the token just are:

```
/api/futbolist/country/  
/api/futbolist/team/  
/api/futbolist/delete
```

Routes and queries:

api/auth/login

Recibes body params as json

GET:

```
/api/team/ = responds with the list of teams  
/api/futbolist/ = responds with the list of soccer players
```

Post and update:

/api/futbolist = Recibes the body with json for a new futbol player ex:

```
{  
  "name": "neymar",  
  
  "team_id": "psg",
```

```
"squad_number": 11,
```

```
"position": "attack",
```

```
"nationality": "brasil"
```

```
}
```

/api/team= Recibes the body with json for a new futol team

Ex>:

```
{
```

```
"name": "millonarios",
```

```
"league": "aguila",
```

```
"country": "colombia"
```

```
}
```

Delete :

/api/futbolist/delete

```
{id: 21mi13m}
```

Recibes de id from the body request for delete the player

Queries:

Players by country(nationality) = requires token by login

api/futbolist/country/:nationality

Ex <http://localhost:3000/api/Futbolist/country/brasil>

Players by team = requires auth by token

api/futbolist/team/:team\_id

Ex : [api/futbolist/team/barcelona](http://localhost:3000/api/futbolist/team/barcelona)

Players by position:

api/futbolist/position/:position

EX: api/futbolist/position/attack