

# CPSC 540: Machine Learning

## Message Passing, Directed Acyclic Graphical Models

Mark Schmidt

University of British Columbia

Winter 2017

# Admin

- **Assignment 3:**
  - 1 late day to hand in today, 2 for Monday.
- **Assignment 4:**
  - Due March 20.
- For **graduate students planning to graduate in May:**
  - Send me a private message on Piazza ASAP.

## Last Time: Monte Carlo Methods

- If we want to approximate expectations of random functions,

$$\mathbb{E}[g(X)] = \underbrace{\sum_{x \in \mathcal{X}} g(x)p(x)}_{\text{discrete } x} \quad \text{or} \quad \mathbb{E}[g(X)] = \underbrace{\int_{x \in \mathcal{X}} g(x)p(x)dx}_{\text{continuous } x},$$

the Monte Carlo estimate is

$$\mathbb{E}[g(X)] \approx \frac{1}{n} \sum_{i=1}^n g(x^i),$$

## Last Time: Monte Carlo Methods

- If we want to approximate expectations of random functions,

$$\mathbb{E}[g(X)] = \underbrace{\sum_{x \in \mathcal{X}} g(x)p(x)}_{\text{discrete } x} \quad \text{or} \quad \underbrace{\int_{x \in \mathcal{X}} g(x)p(x)dx}_{\text{continuous } x},$$

the Monte Carlo estimate is

$$\mathbb{E}[g(X)] \approx \frac{1}{n} \sum_{i=1}^n g(x^i),$$


where the  $x^i$  are independent samples from  $p(x)$ .

- We can use this to approximate marginals,

$$p(x_j = c) = \frac{1}{n} \sum_{i=1}^n \mathcal{I}_{x_j^i = c}.$$

## Last Time: Inverse Transform Sampling Method

- The **cumulative distribution function** (CDF)  $F$  is  $p(X \leq x)$ .
  - $F(x)$  is between 0 and 1 and gives proportion of times  $X$  is below  $x$ .




[https://en.wikipedia.org/wiki/Cumulative\\_distribution\\_function](https://en.wikipedia.org/wiki/Cumulative_distribution_function)

- The **inverse CDF** (or **quantile function**)  $F^{-1}$  is its inverse:
  - Given a number  $u$  between 0 and 1, gives  $x$  such that  $p(X \leq x) = u$ .

## Last Time: Inverse Transform Sampling Method

- The **cumulative distribution function** (CDF)  $F$  is  $p(X \leq x)$ .
  - $F(x)$  is between 0 and 1 and gives proportion of times  $X$  is below  $x$ .



[https://en.wikipedia.org/wiki/Cumulative\\_distribution\\_function](https://en.wikipedia.org/wiki/Cumulative_distribution_function)

- The **inverse CDF** (or **quantile function**)  $F^{-1}$  is its inverse:
  - Given a number  $u$  between 0 and 1, gives  $x$  such that  $p(X \leq x) = u$ .
- **Inverse transform** method for exact sampling in 1D:
  - 1 Sample  $u \sim \mathcal{U}(0, 1)$ .
  - 2 Compute  $x = F^{-1}(u)$ .

## Last Time: Markov Chains

- We can use **Markov chains** for density estimation,

$$p(x) = \underbrace{p(x_1)}_{\text{initial prob.}} \prod_{j=2}^d \underbrace{p(x_j | x_{j-1})}_{\text{transition prob.}},$$

which model **dependency between adjacent features**.

## Last Time: Markov Chains

- We can use **Markov chains** for density estimation,

$$p(x) = \underbrace{p(x_1)}_{\text{initial prob.}} \prod_{j=2}^d \underbrace{p(x_j | x_{j-1})}_{\text{transition prob.}},$$

which model **dependency between adjacent features**.

- **Homogeneous** chains use same transition probability for all  $j$  (**parameter tying**).
  - Gives more data to estimate transitions, allows examples of different sizes.
- **Inhomogeneous** chains allow different transitions at different times.



## Last Time: Markov Chains

- We can use **Markov chains** for density estimation,

$$p(x) = \underbrace{p(x_1)}_{\text{initial prob.}} \prod_{j=2}^d \underbrace{p(x_j | x_{j-1})}_{\text{transition prob.}},$$

which model **dependency between adjacent features**.

- **Homogeneous** chains use same transition probability for all  $j$  (**parameter tying**).
  - Gives more data to estimate transitions, allows examples of different sizes.
- **Inhomogeneous** chains allow different transitions at different times.
- **Ancestral sampling** from a Markov chain:
  - Sample  $x_1$ , then  $x_2$  given  $x_1$ , then  $x_3$  given  $x_2$ , and so on.

## Last Time: Chapman-Kolmogorov Equations

- We can compute **marginals** like  $p(x_j = c)$  recursively in a Markov chain,

$$p(x_j) = \sum_{x_{j-1}} p(x_j | x_{j-1}) p(x_{j-1}),$$

## Last Time: Chapman-Kolmogorov Equations

- We can compute **marginals** like  $p(x_j = c)$  recursively in a Markov chain,

$$p(x_j) = \sum_{x_{j-1}} p(x_j | x_{j-1}) p(x_{j-1}),$$

$$p(x_j) = \int_{x_{j-1}} p(x_j | x_{j-1}) p(x_{j-1}) = \int_{x_{j-1}} p(x_j, x_{j-1}),$$

which are called the **Chapman-Kolmogorov equations**.

- Yields closed-form solutions for marginals in discrete or Gaussian Markov chains.

# Outline

- 1 Message Passing
- 2 Directed Acyclic Graphical Models
- 3 D-Separation

## Decoding: Maximizing Joint Probability

- The **decoding** problem in density models is finding **most probable**  $x$ :

$$\operatorname{argmax}_x p(x).$$

- For example, for binary  $x$  we might have  $[1 \ 0 \ 0 \ 1]$ .

## Decoding: Maximizing Joint Probability

- The **decoding** problem in density models is finding **most probable**  $x$ :

$$\operatorname{argmax}_x p(x).$$

- For example, for binary  $x$  we might have  $[1 \ 0 \ 0 \ 1]$ .
- For independent models this is easy:
  - The log-likelihood is separable so we can optimize each  $x_j$  independently.

## Decoding: Maximizing Joint Probability

- The **decoding** problem in density models is finding **most probable**  $x$ :

$$\operatorname{argmax}_x p(x).$$

- For example, for binary  $x$  we might have  $[1 \ 0 \ 0 \ 1]$ .

- For independent models this is easy:

- The log-likelihood is separable so we can optimize each  $x_j$  independently.
- For example, with three variables we have

$$\max_{x_1, x_2, x_3, x_4} \{p(x_1)p(x_2)p(x_3)p(x_4)\} = \left(\max_{x_1} p(x_1)\right) \left(\max_{x_2} p(x_2)\right) \left(\max_{x_3} p(x_3)\right) \left(\max_{x_4} p(x_4)\right).$$

- Can we also maximize the marginals to decode a Markov chain?

## Decoding vs. Maximizing Marginals

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$



## Decoding vs. Maximizing Marginals

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and the transition probabilities are such that

$$x_2 = \begin{cases} \text{“alive”} & \text{If } x_1 = \text{“land”} \\ \text{“dead”} & \text{otherwise} \end{cases}$$

## Decoding vs. Maximizing Marginals

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and the transition probabilities are such that

$$x_2 = \begin{cases} \text{“alive”} & \text{If } x_1 = \text{“land”} \\ \text{“dead”} & \text{otherwise} \end{cases}$$

- The **decoding** is given by ( “land”, “alive” ), which has probability 0.4.

## Decoding vs. Maximizing Marginals

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and the transition probabilities are such that

$$x_2 = \begin{cases} \text{“alive”} & \text{If } x_1 = \text{“land”} \\ \text{“dead”} & \text{otherwise} \end{cases}$$

- The **decoding** is given by ( “land”, “alive” ), which has probability 0.4.
- The marginals for the different values of  $x_2$  are given by

$$p(x_2 = \text{“alive”}) = 0.4, \quad p(x_2 = \text{“dead”}) = 0.6,$$

so maximizing the marginals gives ( “land”, “dead” ) which has probability 0.

## Distributing Max across Product

- Note that decoding **can't be done forward in time** as in CK equations.
  - Even if  $p(x_0 = 2) = 0.99$ , the most likely sequence could have  $x_0 = 1$ .
  - We need to **optimize over all  $k^d$  length- $d$  paths**.

## Distributing Max across Product

- Note that decoding **can't be done forward in time** as in CK equations.
  - Even if  $p(x_0 = 2) = 0.99$ , the most likely sequence could have  $x_0 = 1$ .
  - We need to **optimize over all  $k^d$  length- $d$  paths**.
- Fortunately, the **Markov property** makes the max simplify:

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_1, x_2, x_3, x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1)$$

## Distributing Max across Product

- Note that decoding **can't be done forward in time** as in CK equations.
  - Even if  $p(x_0 = 2) = 0.99$ , the most likely sequence could have  $x_0 = 1$ .
  - We need to **optimize over all  $k^d$  length- $d$  paths**.
- Fortunately, the **Markov property** makes the max simplify:

$$\begin{aligned}\max_{x_1, x_2, x_3, x_4} p(x) &= \max_{x_1, x_2, x_3, x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} \max_{x_2} \max_{x_1} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1)\end{aligned}$$

## Distributing Max across Product

- Note that decoding **can't be done forward in time** as in CK equations.
  - Even if  $p(x_0 = 2) = 0.99$ , the most likely sequence could have  $x_0 = 1$ .
  - We need to **optimize over all  $k^d$  length- $d$  paths**.
- Fortunately, the **Markov property** makes the max simplify:

$$\begin{aligned}\max_{x_1, x_2, x_3, x_4} p(x) &= \max_{x_1, x_2, x_3, x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} \max_{x_2} \max_{x_1} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} \max_{x_2} p(x_4|x_3)p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1)\end{aligned}$$

where we're using that  $\max_i \alpha a_i = \alpha \max_i a_i$  for non-negative  $\alpha$ .

## Distributing Max across Product

- Note that decoding **can't be done forward in time** as in CK equations.
  - Even if  $p(x_0 = 2) = 0.99$ , the most likely sequence could have  $x_0 = 1$ .
  - We need to **optimize over all  $k^d$  length- $d$  paths**.
- Fortunately, the **Markov property** makes the max simplify:

$$\begin{aligned}\max_{x_1, x_2, x_3, x_4} p(x) &= \max_{x_1, x_2, x_3, x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} \max_{x_2} \max_{x_1} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} \max_{x_2} p(x_4|x_3)p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1) \\ &= \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1),\end{aligned}$$

where we're using that  $\max_i \alpha a_i = \alpha \max_i a_i$  for non-negative  $\alpha$ .



## Decoding with Memoization

- The Markov property writes decoding as a sequence of max problems:

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1),$$

but note that we can't just "solve"  $\max_{x_1}$  once because it depends on  $x_2$ .

## Decoding with Memoization

- The Markov property writes decoding as a sequence of max problems:

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1),$$

but note that we **can't just "solve"  $\max_{x_1}$  once because it depends on  $x_2$ .**

- Instead, we'll **memoize** solution  $M_2(x_2) = \max_{x_1} p(x_2|x_1)p(x_1)$  for all  $x_2$ ,

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) M_2(x_2).$$

## Decoding with Memoization

- The Markov property writes decoding as a sequence of max problems:

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1),$$

but note that we **can't just "solve"  $\max_{x_1}$  once because it depends on  $x_2$ .**

- Instead, we'll **memoize** solution  $M_2(x_2) = \max_{x_1} p(x_2|x_1)p(x_1)$  for all  $x_2$ ,

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) M_2(x_2).$$

- Now we memoize solution  $M_3(x_3) = \max_{x_2} p(x_3|x_2) M_2(x_2)$  for all  $x_3$ ,

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) M_3(x_3).$$

## Decoding with Memoization

- The Markov property writes decoding as a sequence of max problems:

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) \max_{x_1} p(x_2|x_1)p(x_1),$$

but note that we **can't just "solve"  $\max_{x_1}$  once because it depends on  $x_2$ .**

- Instead, we'll **memoize** solution  $M_2(x_2) = \max_{x_1} p(x_2|x_1)p(x_1)$  for all  $x_2$ ,

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) \max_{x_2} p(x_3|x_2) M_2(x_2).$$

- Now we memoize solution  $M_3(x_3) = \max_{x_2} p(x_3|x_2) M_2(x_2)$  for all  $x_3$ ,

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} \max_{x_3} p(x_4|x_3) M_3(x_3).$$

- And defining  $M_4(x_4) = \max_{x_3} p(x_4|x_3) M_3(x_3)$  the maximum value is given by

$$\max_{x_1, x_2, x_3, x_4} p(x) = \max_{x_4} M_4(x_4).$$

## Decoding Example

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and  $x_2 = \text{“alive”}$  if we land and is “dead” otherwise.

## Decoding Example

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and  $x_2 = \text{“alive”}$  if we land and is “dead” otherwise.

- We have  $M_1(x_1) = p(x_1)$  so we get

$$M_1(\text{“land”}) = 0.4, \quad M_1(\text{“crash”}) = 0.3, \quad M_1(\text{“explode”}) = 0.3.$$

## Decoding Example

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and  $x_2 = \text{“alive”}$  if we land and is “dead” otherwise.

- We have  $M_1(x_1) = p(x_1)$  so we get

$$M_1(\text{“land”}) = 0.4, \quad M_1(\text{“crash”}) = 0.3, \quad M_1(\text{“explode”}) = 0.3.$$

- We have  $M_2(x_2) = \max_{x_1} p(x_2|x_1)M_1(x_1)$  so we get

$$M_2(\text{“alive”}) = 0.4, \quad M_2(\text{“dead”}) = 0.3.$$

## Decoding Example

- Consider the “plane of doom” 2-variable Markov chain:
  - Initial probabilities are given by

$$p(x_1 = \text{“land”}) = 0.4, \quad p(x_1 = \text{“crash”}) = 0.3, \quad p(x_1 = \text{“explode”}) = 0.3,$$

and  $x_2 = \text{“alive”}$  if we land and is “dead” otherwise.

- We have  $M_1(x_1) = p(x_1)$  so we get

$$M_1(\text{“land”}) = 0.4, \quad M_1(\text{“crash”}) = 0.3, \quad M_1(\text{“explode”}) = 0.3.$$

- We have  $M_2(x_2) = \max_{x_1} p(x_2|x_1)M_1(x_1)$  so we get

$$M_2(\text{“alive”}) = 0.4, \quad M_2(\text{“dead”}) = 0.3.$$

- This means the optimal decoding has probability 0.4 and ends with “alive”.
  - We now need need to **backtrack** to find the state that lead to “alive”, giving “land”.



## Vitebi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.

# Vitebi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.
- The **Viterbi decoding** algorithm (special case of **dynamic programming**):
  - 1 Set  $M_1(x_1) = p(x_1)$  for all  $x_1$ .

# Viterbi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.
- The **Viterbi decoding** algorithm (special case of **dynamic programming**):
  - 1 Set  $M_1(x_1) = p(x_1)$  for all  $x_1$ .
  - 2 Compute  $M_2(x_2)$  for all  $x_2$ , and store the  $x_1$  leading to each  $x_2$  in  $D_2(x_2)$ .

# Viterbi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.
- The **Viterbi decoding** algorithm (special case of **dynamic programming**):
  - 1 Set  $M_1(x_1) = p(x_1)$  for all  $x_1$ .
  - 2 Compute  $M_2(x_2)$  for all  $x_2$ , and store the  $x_1$  leading to each  $x_2$  in  $D_2(x_2)$ .
  - 3 Compute  $M_3(x_3)$  for all  $x_3$ , and store the  $x_2$  leading to each  $x_3$  in  $D_3(x_3)$ .
  - 4 ...

# Viterbi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.
- The **Viterbi decoding** algorithm (special case of **dynamic programming**):
  - 1 Set  $M_1(x_1) = p(x_1)$  for all  $x_1$ .
  - 2 Compute  $M_2(x_2)$  for all  $x_2$ , and store the  $x_1$  leading to each  $x_2$  in  $D_2(x_2)$ .
  - 3 Compute  $M_3(x_3)$  for all  $x_3$ , and store the  $x_2$  leading to each  $x_3$  in  $D_3(x_3)$ .
  - 4 ...
  - 5 Maximize  $M_d(x_d)$  to find  $x_d$  in decoding, **backtrack** with  $D_j$ 's to find decoding.

## Viterbi Decoding

- What is  $M_j(x_j)$  in words?
  - “Probability of most likely length- $j$  sequence ending in  $x_j$  (ignoring future)”.
- The **Viterbi decoding** algorithm (special case of **dynamic programming**):
  - 1 Set  $M_1(x_1) = p(x_1)$  for all  $x_1$ .
  - 2 Compute  $M_2(x_2)$  for all  $x_2$ , and store the  $x_1$  leading to each  $x_2$  in  $D_2(x_2)$ .
  - 3 Compute  $M_3(x_3)$  for all  $x_3$ , and store the  $x_2$  leading to each  $x_3$  in  $D_3(x_3)$ .
  - 4 ...
  - 5 Maximize  $M_d(x_d)$  to find  $x_d$  in decoding, **backtrack** with  $D_j$ 's to find decoding.
- Computing all  $M_j(x_j)$  given all  $M_{j-1}(x_{j-1})$  costs  $O(k^2)$ .
  - Total cost is only  $O(dk^2)$  to search over all  $k^d$  paths.

# Conditional Probabilities

- We often want to compute **conditional probabilities** in Markov chains.
  - We can ask “what lead to  $x_{10} = 4$ ?” with queries like  $p(x_1|x_{10})$ .
  - We can ask “where does  $x_{10} = 4$  lead?” with queries like  $p(x_d|x_{10})$ .

## Conditional Probabilities

- We often want to compute **conditional probabilities** in Markov chains.
  - We can ask “what lead to  $x_{10} = 4$ ?” with queries like  $p(x_1|x_{10})$ .
  - We can ask “where does  $x_{10} = 4$  lead?” with queries like  $p(x_d|x_{10})$ .
- **Monte Carlo approach** to estimating  $p(x_j|x_{j'})$ :
  - 1 Generate a large number of samples from the Markov chain,  $x^i \sim p(x_1, x_2, \dots, x_d)$ .
  - 2 Use Monte Carlo estimates of  $p(x_j, x_{j'} = c)$  and  $p(x_{j'} = c)$  to give

$$p(x_j|x_{j'} = c) = \frac{p(x_j, x_{j'} = c)}{p(x_{j'} = c)}.$$



# Conditional Probabilities

- We often want to compute **conditional probabilities** in Markov chains.
  - We can ask “what lead to  $x_{10} = 4$ ?” with queries like  $p(x_1|x_{10})$ .
  - We can ask “where does  $x_{10} = 4$  lead?” with queries like  $p(x_d|x_{10})$ .
- **Monte Carlo approach** to estimating  $p(x_j|x_{j'})$ :
  - 1 Generate a large number of samples from the Markov chain,  $x^i \sim p(x_1, x_2, \dots, x_d)$ .
  - 2 Use Monte Carlo estimates of  $p(x_j, x_{j'} = c)$  and  $p(x_{j'} = c)$  to give

$$p(x_j|x_{j'} = c) = \frac{p(x_j, x_{j'} = c)}{p(x_{j'} = c)}.$$

- This is a special case of **rejection sampling** (we'll see general case later).
  - Unfortunately, if  $x_{j'} = c$  is rare then **most samples are “rejected”** (ignored).

## Conditional Probabilities

- For Gaussian/discrete Markov chains, we can do better than rejection sampling.
  - ① We can generate **exact samples** from conditional distribution (bonus slide).
    - Rejection sampling is not needed, relies on “backwards sampling” in time.

## Conditional Probabilities

- For Gaussian/discrete Markov chains, we can do better than rejection sampling.
  - ① We can generate **exact samples** from conditional distribution (bonus slide).
    - Rejection sampling is not needed, relies on “backwards sampling” in time.
  - ② We can find **conditional decoding**  $\max_{x|x_{j'}=c} p(x)$ :
    - Run Viterbi decoding with  $M_{j'}(c) = 1$  and  $M_{j'}(c') = 0$  for  $c \neq c'$ .

## Conditional Probabilities

- For Gaussian/discrete Markov chains, we can do better than rejection sampling.
  - ① We can generate **exact samples** from conditional distribution (bonus slide).
    - Rejection sampling is not needed, relies on “backwards sampling” in time.
  - ② We can find **conditional decoding**  $\max_{x|x_{j'}=c} p(x)$ :
    - Run Viterbi decoding with  $M_{j'}(c) = 1$  and  $M_{j'}(c') = 0$  for  $c \neq c'$ .
  - ③ We can find **univariate conditionals**,  $p(x_j|x_{j'})$ .

## Conditional Probabilities

- For Gaussian/discrete Markov chains, we can do better than rejection sampling.
  - ① We can generate **exact samples** from conditional distribution (bonus slide).
    - Rejection sampling is not needed, relies on “backwards sampling” in time.
  - ② We can find **conditional decoding**  $\max_{x|x_{j'}=c} p(x)$ :
    - Run Viterbi decoding with  $M_{j'}(c) = 1$  and  $M_{j'}(c') = 0$  for  $c \neq c'$ .
  - ③ We can find **univariate conditionals**,  $p(x_j|x_{j'})$ .
- Example of computing  $p(x_1 = c|x_3 = 1)$  in a length-4 discrete Markov chain:

$$\begin{aligned} p(x_1 = c|x_3 = 1) &\propto p(x_1 = c, x_3 = 1) \\ &= \sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4), \end{aligned}$$

## Conditional Probabilities

- For Gaussian/discrete Markov chains, we can do better than rejection sampling.
  - ① We can generate **exact samples** from conditional distribution (bonus slide).
    - Rejection sampling is not needed, relies on “backwards sampling” in time.
  - ② We can find **conditional decoding**  $\max_x p(x|x_{j'}=c)$ :
    - Run Viterbi decoding with  $M_{j'}(c) = 1$  and  $M_{j'}(c') = 0$  for  $c \neq c'$ .
  - ③ We can find **univariate conditionals**,  $p(x_j|x_{j'})$ .
- Example of computing  $p(x_1 = c|x_3 = 1)$  in a length-4 discrete Markov chain:

$$\begin{aligned} p(x_1 = c|x_3 = 1) &\propto p(x_1 = c, x_3 = 1) \\ &= \sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4), \end{aligned}$$

where the normalizing constant is  $p(x_3 = 1)$ .

- This is a **sum over**  $k^{d-2}$  possible assignments to other variables.

## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) = \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1)$$

## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} p(x_4|x_3)p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1) p(x_1)\end{aligned}$$



## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} p(x_4|x_3)p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)M_1(x_1)\end{aligned}$$

where  $M_j(x_j)$  now sums over paths ending in  $x_j$  instead of maximizing.

## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} p(x_4|x_3)p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)M_1(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2)M_2(x_2)\end{aligned}$$

where  $M_j(x_j)$  now sums over paths ending in  $x_j$  instead of maximizing.

## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} p(x_4|x_3)p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)M_1(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2)M_2(x_2) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3)M_3(x_3)\end{aligned}$$

where  $M_j(x_j)$  now sums over paths ending in  $x_j$  instead of maximizing.

## Distributing Sum across Product

- Fortunately, the **Markov property** makes the sums simplify as before:

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} \sum_{x_1=c} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} \sum_{x_2} p(x_4|x_3)p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)p(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2) \sum_{x_1=c} p(x_2|x_1)M_1(x_1) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3) \sum_{x_2} p(x_3|x_2)M_2(x_2) \\ &= \sum_{x_4} \sum_{x_3=1} p(x_4|x_3)M_3(x_3) \\ &= \sum_{x_4} M_4(x_4),\end{aligned}$$

where  $M_j(x_j)$  now sums over paths ending in  $x_j$  instead of maximizing.

## Message-Passing Algorithms

- We've just discussed several algorithms with **similar structure**:
  - CK equations for computing univariate marginals in discrete Markov chains.
  - Recursive marginal updates for Gaussian Markov chains (Assignment 4).
  - Viterbi decoding algorithm for discrete Markov chains.
  - Conditional inference in discrete Markov chains.

# Message-Passing Algorithms

- We've just discussed several algorithms with **similar structure**:
  - CK equations for computing univariate marginals in discrete Markov chains.
  - Recursive marginal updates for Gaussian Markov chains (Assignment 4).
  - Viterbi decoding algorithm for discrete Markov chains.
  - Conditional inference in discrete Markov chains.
- These are all special cases of **message-passing** algorithms:
  - 1 Define  $M_j$  summarizing all relevant information about the past at time  $j$ .

## Message-Passing Algorithms

- We've just discussed several algorithms with **similar structure**:
  - CK equations for computing univariate marginals in discrete Markov chains.
  - Recursive marginal updates for Gaussian Markov chains (Assignment 4).
  - Viterbi decoding algorithm for discrete Markov chains.
  - Conditional inference in discrete Markov chains.
- These are all special cases of **message-passing** algorithms:
  - 1 Define  $M_j$  summarizing all relevant information about the past at time  $j$ .
  - 2 Use Markov property to write  $M_j$  recursively in terms of  $M_{j-1}$ .
  - 3 Solve task by computing  $M_1, M_2, \dots, M_d$ .

## Message-Passing Algorithms

- We've just discussed several algorithms with **similar structure**:
  - CK equations for computing univariate marginals in discrete Markov chains.
  - Recursive marginal updates for Gaussian Markov chains (Assignment 4).
  - Viterbi decoding algorithm for discrete Markov chains.
  - Conditional inference in discrete Markov chains.
- These are all special cases of **message-passing** algorithms:
  - 1 Define  $M_j$  **summarizing all relevant information about the past** at time  $j$ .
  - 2 Use Markov property to write  $M_j$  **recursively in terms of  $M_{j-1}$** .
  - 3 Solve task by computing  $M_1, M_2, \dots, M_d$ .
- In some cases we'll also need **backwards message**  $V_j$  ("cost to go"):
  - $V_j$  **summarizes all relevant information about the future** at time  $j$ .



## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) = \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1)$$

## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3)\end{aligned}$$

## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\begin{aligned}\sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\ &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \\ &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \underbrace{V_4(x_4)}_{=1}\end{aligned}$$

## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\begin{aligned}
 \sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \underbrace{V_4(x_4)}_{=1} \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) V_3(x_3)
 \end{aligned}$$

## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\begin{aligned}
 \sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \underbrace{V_4(x_4)}_{=1} \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) V_3(x_3) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) V_2(x_2)
 \end{aligned}$$

## Conditionals via Backwards Messages

- Performing our conditional calculation using backwards messages.

$$\begin{aligned}
 \sum_{x_4} \sum_{x_2} p(x_1 = c, x_2, x_3 = 1, x_4) &= \sum_{x_1=c} \sum_{x_2} \sum_{x_3=1} \sum_{x_4} p(x_4|x_3)p(x_3|x_2)p(x_2|x_1)p(x_1) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) \sum_{x_4} p(x_4|x_3) \underbrace{V_4(x_4)}_{=1} \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) \sum_{x_3=1} p(x_3|x_2) V_3(x_3) \\
 &= \sum_{x_1=c} p(x_1) \sum_{x_2} p(x_2|x_1) V_2(x_2) \\
 &= \sum_{x_1=c} p(x_1) V_1(x_1).
 \end{aligned}$$

## Forward-Backward Algorithm

- Generic forward and backward messages for discrete marginals have the form

$$M_j(x_j) = \sum_{x_{j-1}} p(x_j|x_{j-1})M_{j-1}(x_{j-1}), \quad V_j(x_j) = \sum_{x_{j+1}} p(x_{j+1}|x_j)V_j(x_{j+1}).$$

## Forward-Backward Algorithm

- Generic forward and backward messages for discrete marginals have the form

$$M_j(x_j) = \sum_{x_{j-1}} p(x_j|x_{j-1})M_{j-1}(x_{j-1}), \quad V_j(x_j) = \sum_{x_{j+1}} p(x_{j+1}|x_j)V_j(x_{j+1}).$$

- We can compute  $p(x_j = c|x_{j'} = c')$  using only forward messages:
  - Set  $M_j(c) = 1$  and  $M_{j'}(c') = 1$ .
- Why we would need backward messages?



## Forward-Backward Algorithm

- We can compute  $p(x_j = c | x_{j'} = c')$  for all  $j$  in  $O(nk^2)$  with both messages.

## Forward-Backward Algorithm

- We can compute  $p(x_j = c | x_{j'} = c')$  for all  $j$  in  $O(nk^2)$  with both messages.
- Compute all message normally with  $M_{j'}(c') = 1$  and  $V_{j'}(c') = 1$ .  
(Other  $M_{j'}$  and  $V_{j'}$  are set to 0)

## Forward-Backward Algorithm

- We can compute  $p(x_j = c | x_{j'} = c')$  for **all  $j$  in  $O(nk^2)$**  with both messages.
- Compute all message normally with  $M_{j'}(c') = 1$  and  $V_{j'}(c') = 1$ .  
(Other  $M_{j'}$  and  $V_{j'}$  are set to 0)
- We then have that
  - $M_j(x_j)$  sums up all the paths that **end** in state  $x_j$  (with  $x_{j'} = c'$ ).
  - $V_j(x_j)$  sums up all the paths that **start** in state  $x_j$  (with  $x_{j'} = c'$ ).
  - We can combine these values to get

$$p(x_j | x_{j'}) \propto M_j(x_j) V_j(x_j),$$

- Special case of the **forward-backward algorithm**.

# Outline

- 1 Message Passing
- 2 Directed Acyclic Graphical Models
- 3 D-Separation

## Higher-Order Markov Models

- Markov models use a density of the form

$$p(x) = p(x_1)p(x_2|x_1)p(x_3|x_2)p(x_4|x_3) \cdots p(x_d|x_{d-1}).$$

- They support efficient computation but Markov assumption is strong.

## Higher-Order Markov Models

- Markov models use a density of the form

$$p(x) = p(x_1)p(x_2|x_1)p(x_3|x_2)p(x_4|x_3) \cdots p(x_d|x_{d-1}).$$

- They support efficient computation but Markov assumption is strong.
- A more flexible model would be a second-order Markov model,

$$p(x) = p(x_1)p(x_2|x_1)p(x_3|x_2, x_1)p(x_4|x_3, x_2) \cdots p(x_d|x_{d-1}, x_{d-2}),$$

or even a higher-order models.

## Higher-Order Markov Models

- Markov models use a density of the form

$$p(x) = p(x_1)p(x_2|x_1)p(x_3|x_2)p(x_4|x_3) \cdots p(x_d|x_{d-1}).$$

- They support efficient computation but Markov assumption is strong.
- A more flexible model would be a second-order Markov model,

$$p(x) = p(x_1)p(x_2|x_1)p(x_3|x_2, x_1)p(x_4|x_3, x_2) \cdots p(x_d|x_{d-1}, x_{d-2}),$$

or even a higher-order models.

- Directed acyclic graphical (DAG) models generalize Markov models:
  - They allow dependence on any subset of previous features.

## DAG Models

- DAG models use product rule,  $p(a, b, c) = p(b, c|a)p(a)$ , to write

$$p(x_1, x_2, \dots, x_d) = p(x_1)p(x_2, x_3, \dots, x_d|x_1)$$



## DAG Models

- DAG models use product rule,  $p(a, b, c) = p(b, c|a)p(a)$ , to write

$$\begin{aligned} p(x_1, x_2, \dots, x_d) &= p(x_1)p(x_2, x_3, \dots, x_d|x_1) \\ &= p(x_1)p(x_2|x_1)p(x_3, x_4, \dots, x_d|x_1, x_2) \end{aligned}$$

## DAG Models

- **DAG** models use product rule,  $p(a, b, c) = p(b, c|a)p(a)$ , to write

$$\begin{aligned} p(x_1, x_2, \dots, x_d) &= p(x_1)p(x_2, x_3, \dots, x_d|x_1) \\ &= p(x_1)p(x_2|x_1)p(x_3, x_4, \dots, x_d|x_1, x_2) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_2, x_1)p(x_4, x_5, \dots, x_d|x_1, x_2, x_3), \end{aligned}$$

## DAG Models

- **DAG** models use product rule,  $p(a, b, c) = p(b, c|a)p(a)$ , to write

$$\begin{aligned} p(x_1, x_2, \dots, x_d) &= p(x_1)p(x_2, x_3, \dots, x_d|x_1) \\ &= p(x_1)p(x_2|x_1)p(x_3, x_4, \dots, x_d|x_1, x_2) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_2, x_1)p(x_4, x_5, \dots, x_d|x_1, x_2, x_3), \end{aligned}$$

and so on until we get

$$p(x_1, x_2, \dots, x_d) = \prod_{j=1}^d p(x_j|x_{1:j-1}).$$

- This **factorization** holds for any distribution.

## DAG Models

- DAG models use product rule,  $p(a, b, c) = p(b, c|a)p(a)$ , to write

$$\begin{aligned} p(x_1, x_2, \dots, x_d) &= p(x_1)p(x_2, x_3, \dots, x_d|x_1) \\ &= p(x_1)p(x_2|x_1)p(x_3, x_4, \dots, x_d|x_1, x_2) \\ &= p(x_1)p(x_2|x_1)p(x_3|x_2, x_1)p(x_4, x_5, \dots, x_d|x_1, x_2, x_3), \end{aligned}$$

and so on until we get

$$p(x_1, x_2, \dots, x_d) = \prod_{j=1}^d p(x_j|x_{1:j-1}).$$

- This factorization holds for any distribution.
- But it has too many parameters:
  - For binary  $x_i$ , we need  $2^d$  parameters for  $p(x_j|x_1, x_2, \dots, x_{j-1})$  alone.

## DAG Models

- To reduce number of parameters, in DAG models we use

$$p(x_1, x_2, \dots, x_d) = \prod_{j=1}^d p(x_j | x_{\text{pa}(j)}),$$

where  $\text{pa}(j)$  are the “parents” of node  $j$ .

- If we have  $k$  parents we only need  $2^{k+1}$  parameters.
- For Markov chains the only “parent” of  $j$  is  $(j - 1)$ .

## DAG Models

- To reduce number of parameters, in DAG models we use

$$p(x_1, x_2, \dots, x_d) = \prod_{j=1}^d p(x_j | x_{\text{pa}(j)}),$$

where  $\text{pa}(j)$  are the “parents” of node  $j$ .


- If we have  $k$  parents we only need  $2^{k+1}$  parameters.
  - For Markov chains the only “parent” of  $j$  is  $(j - 1)$ .
- This corresponds to a set of conditional independence assumptions,

$$p(x_j | x_{1:j-1}) = p(x_j | x_{\text{pa}(j)}),$$

that we’re independent of previous non-parents given the parents.

# MNIST Digits with Markov Chains


- Recall trying to model digits using an **inhomogeneous Markov chain**:



Only models dependence on pixel above, not on 2 pixels above **nor across columns**.

# MNIST Digits with DAG Model (Sparse Parents)

- Samples from a DAG model with 8 parents per feature:



Parents of  $(i, j)$  are 8 other pixels in the neighbourhood  $(i - 2 : i, j - 2 : j)$ :

$\{(i-2, j-2), (i-1, j-2), (i, j-2), (i-2, j-1), (i-1, j-1), (i, j-1), (i-2, j), (i-1, j)\}$ .



## From Probability Factorizations to Graphs

- DAG models are also known as “Bayesian networks” and “belief networks”.
- “Graphical” name comes from visualizing features/parents as a graph:
  - We have a node for each variable  $j$ .

# From Probability Factorizations to Graphs

- DAG models are also known as “Bayesian networks” and “belief networks”.
- “Graphical” name comes from visualizing features/parents as a graph:
  - We have a node for each variable  $j$ .
  - We place an edge into  $j$  from each of its parents.

## From Probability Factorizations to Graphs

- DAG models are also known as “**Bayesian networks**” and “**belief networks**”.
- “**Graphical**” name comes from visualizing features/parents as a graph:
  - We have a node for each variable  $j$ .
  - We place an **edge into  $j$  from each of its parents**.
- The graph for Markov chains is:



## From Probability Factorizations to Graphs

- DAG models are also known as “**Bayesian networks**” and “**belief networks**”.
- “**Graphical**” name comes from visualizing features/parents as a graph:
  - We have a node for each variable  $j$ .
  - We place an **edge into  $j$  from each of its parents**.
- The graph for Markov chains is:



- This graph is not just a visualization tool:
  - Can be used to **test arbitrary conditional independences** (“d-separation”).
  - Graph structure **tells us whether message passing is efficient** (“treewidth”).

# Graph Structure Examples

With **product of independent** we have

$$p(x) = \prod_{j=1}^d p(x_j),$$

so  $\text{pa}(j) = \emptyset$  and the graph is:



## Graph Structure Examples

With **Markov chain** we have

$$p(x) = p(x_1) \prod_{j=2}^d p(x_j | x_{j-1}),$$

so  $\text{pa}(j) = \{j - 1\}$  and the graph is:




## Graph Structure Examples

With **second-order Markov chain** we have

$$p(x) = p(x_1)p(x_2|x_1) \prod_{j=3}^d p(x_j|x_{j-1}, x_{j-2}),$$

so  $\text{pa}(j) = \{j-1, j-2\}$  and the graph is:




## Graph Structure Examples

With **general distribution** we have

$$p(x) = \prod_{j=1}^d p(x_j | x_{1:j-1}).$$

so  $\text{pa}(j) = \{j-1, j-2, \dots, 1\}$  and the graph is:






## Graph Structure Examples

In **naive Bayes** we add an extra variable  $y$  and use

$$p(y, x) = p(y) \prod_{j=1}^d p(x_j|y),$$

which has  $\text{pa}(y) = \emptyset$  and  $\text{pa}(x_j) = y$  giving




## Graph Structure Examples

With **mixture of independent** models we have

$$p(z, x) = p(z) \prod_{j=1}^d p(x_j | z).$$

which has  $\text{pa}(z) = \emptyset$  and  $\text{pa}(x_j) = z$  giving



## Graph Structure Examples

Instead of factorizing by variables  $j$ , could factor into blocks  $b$ :

$$p(x) = \prod_b p(x_b | x_{\text{pa}(b)}),$$

and have the nodes be blocks.

## Graph Structure Examples


Instead of factorizing by variables  $j$ , could **factor into blocks**  $b$ :

$$p(x) = \prod_b p(x_b | x_{\text{pa}(b)}),$$

and have the nodes be blocks. With **mixture of Gaussian** we have

$$p(z, x) = p(z)p(x|z).$$

The corresponding graph structure is:



## Graph Structure Examples


Instead of factorizing by variables  $j$ , could **factor into blocks**  $b$ :

$$p(x) = \prod_b p(x_b | x_{\text{pa}(b)}),$$

and have the nodes be blocks. With **Gaussian generative classifier** we have

$$p(y, x) = p(y)p(x|y).$$

The corresponding graph structure is:




# Graph Structure Examples

With **probabilistic PCA** we have

$$p(z, x) = p(x|z) \prod_{c=1}^k p(z_c).$$


The corresponding graph structure is:



## Graph Structure Examples

Sometimes it's easier to present a model using the graph.


Later in the course we'll see [hidden Markov models](#) which have the structure



## Graph Structure Examples

Sometimes it's easier to present a model using the graph.

Later in the course we'll see [hidden Markov models](#) which have the structure



You should already be able to get an idea of what this model does:

- We have hidden variables  $z_j$  that follow a Markov chain.
- Each feature  $x_j$  depends on corresponding feature  $z_j$ .




## Graph Structure Examples

We can consider less-structured examples,


$$p(S, V, R, W, G, D) = p(S)p(V)p(R|V)p(W|S, R)p(G|V)p(D|G).$$

The corresponding graph structure is:



## Graph Structure Examples

We can consider **phylogeny** (family trees):



# Outline

- 1 Message Passing
- 2 Directed Acyclic Graphical Models
- 3 D-Separation

## Review of Independence

- Let  $A$  and  $B$  be random variables taking values  $a \in \mathcal{A}$  and  $b \in \mathcal{B}$ .
- We say that  $A$  and  $B$  are **independent** if we have

$$p(a, b) = p(a)p(b),$$

for all  $a$  and  $b$ .

- This is **true iff**  $p(a, b) = f(a)g(b)$  for some functions  $f$  and  $g$ .

## Review of Independence

- To denote independence of  $x_i$  and  $x_j$  we use the notation

$$x_i \perp x_j.$$

- For independent  $a$  and  $b$  we have

$$p(a|b) = \frac{p(a, b)}{p(b)} = \frac{p(a)p(b)}{p(b)} = p(a).$$

## Review of Independence

- To denote independence of  $x_i$  and  $x_j$  we use the notation

$$x_i \perp x_j.$$

- For independent  $a$  and  $b$  we have

$$p(a|b) = \frac{p(a, b)}{p(b)} = \frac{p(a)p(b)}{p(b)} = p(a).$$

- This gives us a more intuitive definition:  $A$  and  $B$  are independent if

$$p(a|b) = p(a)$$

for all  $a$  and  $b$ .

- In words: knowing  $b$  tells us nothing about  $a$  (and vice versa).

## Independence in “Independent Bernoulli” Model

- In a product of Bernoullis model we have

$$p(x) = \prod_{j=1}^n p(x_j).$$

From marginalization rule we have

$$p(x_i, x_j) = \sum_{x_{-ij}} p(x),$$

where  $x_{-ij}$  is “all variables except  $i$  and  $j$ ”.

## Independence in “Independent Bernoulli” Model

- In a product of Bernoullis model we have

$$p(x) = \prod_{j=1}^n p(x_j).$$

From marginalization rule we have

$$p(x_i, x_j) = \sum_{x_{-ij}} p(x),$$

where  $x_{-ij}$  is “all variables except  $i$  and  $j$ ”.

- Using the definition of  $p(x)$  above we get

$$p(x_i, x_j) = \sum_{x_{-ij}} \prod_{j'=1}^d p(x_{j'})$$



## Independence in “Independent Bernoulli” Model

- In a product of Bernoullis model we have

$$p(x) = \prod_{j=1}^n p(x_j).$$

From marginalization rule we have

$$p(x_i, x_j) = \sum_{x_{-ij}} p(x),$$

where  $x_{-ij}$  is “all variables except  $i$  and  $j$ ”.

- Using the definition of  $p(x)$  above we get

$$p(x_i, x_j) = \sum_{x_{-ij}} \prod_{j'=1}^d p(x_{j'}) = p(x_i)p(x_j) \underbrace{\sum_{x_{-ij}} \prod_{j' \neq i, j' \neq j} p(x_{j'})}_{=1}$$

## Independence in “Independent Bernoulli” Model

- In a product of Bernoullis model we have

$$p(x) = \prod_{j=1}^n p(x_j).$$

From marginalization rule we have

$$p(x_i, x_j) = \sum_{x_{-ij}} p(x),$$

where  $x_{-ij}$  is “all variables except  $i$  and  $j$ ”.

- Using the definition of  $p(x)$  above we get

$$p(x_i, x_j) = \sum_{x_{-ij}} \prod_{j'=1}^d p(x_{j'}) = p(x_i)p(x_j) \underbrace{\sum_{x_{-ij}} \prod_{j' \neq i, j' \neq j} p(x_{j'})}_{=1} = p(x_i)p(x_j).$$

because the sum is over a joint probability distribution.

## Independence in Product of Bernoullis Model

- In a product of Bernoullis model we have

$$p(x) = \prod_{j=1}^n p(x_j),$$

which we showed implies

$$p(x_i, x_j) = p(x_i)p(x_j),$$

so we have  $x_i \perp x_j$  for all  $i$  and  $j$ .

- In mixture of Bernoullis we have  $x_i \not\perp x_j$ :
  - Knowing  $x_j$  tells you something about  $x_i$ .
  - But there are conditional independences in mixture of Bernoulli...

# Conditional Independence

- We say that  $A$  is **conditionally independent** of  $B$  **given**  $C$  if

$$p(a, b|c) = p(a|c)p(b|c),$$

for all  $a$ ,  $b$ , and  $c$ .

- Equivalently, we have

$$p(a|b, c) = p(a|c).$$

# Conditional Independence

- We say that  $A$  is **conditionally independent** of  $B$  **given**  $C$  if

$$p(a, b|c) = p(a|c)p(b|c),$$

for all  $a$ ,  $b$ , and  $c$ .

- Equivalently, we have

$$p(a|b, c) = p(a|c).$$

- “If you know  $C$ , then *also* knowing  $B$  would tell you nothing about  $A$ ”.

- We often write this as

$$A \perp B \mid C.$$

## Conditional Indpendence in Mixture of Bernoulli

- In a mixture of Bernoulli model

$$p(x) = \sum_{c=1}^k p(z = c) \prod_{j=1}^d p(x_j | z = c),$$

we have that  $x_i \perp x_j \mid z$  (“conditional independence given the cluster”)

## Conditional Independence in Mixture of Bernoulli

- In a mixture of Bernoulli model

$$p(x) = \sum_{c=1}^k p(z = c) \prod_{j=1}^d p(x_j | z = c),$$

we have that  $x_i \perp x_j \mid z$  (“conditional independence given the cluster”)

- In particular, the same tedious notation-heavy cancellation gives that

$$p(x_i, x_j | z) = p(x_i | z) p(x_j | z).$$

- But we can also show [conditional] independencies using the graph...

## D-Separation: From Graphs to Conditional Independence

- In DAGs we make the conditional independence assumption that

$$p(x_j | x_{j-1}, x_{j-2}, \dots, x_1) = p(x_j | x_{\text{pa}(j)}).$$

- But these conditional independence assumptions **imply other assumptions**.



## D-Separation: From Graphs to Conditional Independence

- In DAGs we make the conditional independence assumption that

$$p(x_j | x_{j-1}, x_{j-2}, \dots, x_1) = p(x_j | x_{\text{pa}(j)}).$$

- But these conditional independence assumptions **imply other assumptions**.
  - For example, in Markov chains we assume

$$p(x_j | x_{j-1}, x_{j-2}, \dots, x_1) = p(x_j | x_{j-1}),$$

but this implies that

$$p(x_j | x_{j-2}, x_{j-3}, \dots, x_1) = p(x_j | x_{j-2}),$$

## D-Separation: From Graphs to Conditional Independence

- In DAGs we make the conditional independence assumption that

$$p(x_j | x_{j-1}, x_{j-2}, \dots, x_1) = p(x_j | x_{\text{pa}(j)}).$$

- But these conditional independence assumptions **imply other assumptions**.
  - For example, in Markov chains we assume

$$p(x_j | x_{j-1}, x_{j-2}, \dots, x_1) = p(x_j | x_{j-1}),$$

but this implies that

$$p(x_j | x_{j-2}, x_{j-3}, \dots, x_1) = p(x_j | x_{j-2}),$$

and it implies that

$$p(x_j | x_{j+1}, x_{j+2}, \dots, x_d) = p(x_j | x_{j+1}).$$

## D-Separation: From Graphs to Conditional Independence

- All implied conditional independences can be read from the graph.
  - Variables  $A$  and  $B$  are conditionally independent given  $C$  if:
    - “All paths from any variable in  $A$  to any  $B$  are blocked by d-separation by  $C$ ”.

## D-Separation: From Graphs to Conditional Independence

- All implied conditional independences can be read from the graph.
  - Variables  $A$  and  $B$  are conditionally independent given  $C$  if:
    - “All paths from any variable in  $A$  to any  $B$  are blocked by d-separation by  $C$ ”.
- E.g., consider three  $\{X, Y, Z\}$  variables and the following graph structure:



- We use **black or shaded** nodes to denote observed values (we condition on  $Z$ ).
- D-separation will tell us that  $X \perp Y|Z$  on the left but  $X \not\perp Y|Z$  on the right.

## D-Separation: From Graphs to Conditional Independence

- The rules of d-separation are intuitive in a simple model of **gene inheritance**:
  - Each person has single number, which we'll call a "gene".
  - If you have no parents, your gene is random.
  - If you have parents, your **gene is a linear combination of your parents** plus noise.

## D-Separation: From Graphs to Conditional Indpendence

- The rules of d-separation are intuitive in a simple model of **gene inheritance**:
  - Each person has single number, which we'll call a "gene".
  - If you have no parents, your gene is random.
  - If you have parents, your **gene is a linear combination of your parents** plus noise.
- Genes of people are **independent** if knowing one says nothing about the other:
  - Knowing your mom's gene tells you something about your gene (same up to noise).
  - Knowing your friend's gene tells doesn't say anything about your gene.

# D-Separation: From Graphs to Conditional Indpendence

- The rules of d-separation are intuitive in a simple model of **gene inheritance**:
  - Each person has single number, which we'll call a "gene".
  - If you have no parents, your gene is random.
  - If you have parents, your **gene is a linear combination of your parents** plus noise.
- Genes of people are **independent** if knowing one says nothing about the other:
  - Knowing your mom's gene tells you something about your gene (same up to noise).
  - Knowing your friend's gene tells doesn't say anything about your gene.
- Genes of people can be **conditionally independent** given a third person:
  - Knowing your grandma's gene tells you something about your gene.
  - If you know you mom's gene, then grandma's gene isn't useful.
    - You are conditionally independent of grandma given mom.

## D-Separation Case 0 (No Paths and Direct Links)

Are genes in person  $x$  independent of the genes in person  $y$ ?



## D-Separation Case 0 (No Paths and Direct Links)

Are genes in person  $x$  independent of the genes in person  $y$ ?

- No path:  $x$  and  $y$  are **not related** (independent),



We have  $x \perp y$ : there are no paths to be blocked.

## D-Separation Case 0 (No Paths and Direct Links)

Are genes in person  $x$  independent of the genes in person  $y$ ?

- No path:  $x$  and  $y$  are **not related** (independent),



We have  $x \perp y$ : there are no paths to be blocked.

- Direct link:  $x$  is the **parent** of  $y$ ,



We have  $x \not\perp y$ : knowing  $x$  tells you about  $y$  (direct paths aren't blockable).


## D-Separation Case 0 (No Paths and Direct Links)

Neither case changes if we have a third **independent** person  $z$ :

## D-Separation Case 0 (No Paths and Direct Links)


Neither case changes if we have a third **independent** person  $z$ :

- No path: If  $x$  and  $y$  are independent,



We have  $x \perp y$ : adding  $z$  doesn't make a path.

- Direct link:  $x$  is the **parent** of  $y$ ,




We have  $x \not\perp y$ : adding  $z$  doesn't block path.

## D-Separation Case 1: Chain

- Case 1:  $x$  is the grandmother of  $y$ .


## D-Separation Case 1: Chain

- Case 1:  $x$  is the **grandmother** of  $y$ .
  - If  $z$  is the mother we have:



## D-Separation Case 1: Chain


- Case 1:  $x$  is the **grandmother** of  $y$ .
  - If  $z$  is the mother we have:



We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$  because of  $z$


## D-Separation Case 1: Chain

- Case 1:  $x$  is the **grandmother** of  $y$ .
  - If  $z$  is the mother we have:



We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$  because of  $z$


- But if  $z$  is *observed*:






## D-Separation Case 1: Chain

- Case 1:  $x$  is the **grandmother** of  $y$ .
  - If  $z$  is the mother we have:



We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$  because of  $z$

- But if  $z$  is *observed*:




In this case  $x \perp y \mid z$ : knowing  $z$  “breaks” dependence between  $x$  and  $y$ .

## D-Separation Case 1: Chain

- Consider weird case where parents  $z_1$  and  $z_2$  share mother  $x$ :

## D-Separation Case 1: Chain


- Consider weird case where parents  $z_1$  and  $z_2$  share mother  $x$ :
  - If  $z_1$  and  $z_2$  are observed we have:



We have  $x \perp y \mid z_1, z_2$ : knowing both parents breaks dependency.


## D-Separation Case 1: Chain

- Consider weird case where parents  $z_1$  and  $z_2$  share mother  $x$ :
  - If  $z_1$  and  $z_2$  are observed we have:



We have  $x \perp y \mid z_1, z_2$ : knowing both parents breaks dependency.


- But if only  $z_1$  is *observed*:



We have  $x \not\perp y \mid z_1$ : dependence still “flows” through  $z_2$ .


## D-Separation Case 2: Common Parent

- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z$  is a common unobserved parent:



## D-Separation Case 2: Common Parent


- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z$  is a common unobserved parent:



We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$ .


## D-Separation Case 2: Common Parent

- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z$  is a common unobserved parent:




We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$ .

- But if  $z$  is *observed*:




## D-Separation Case 2: Common Parent

- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z$  is a common unobserved parent:



We have  $x \not\perp y$ : knowing  $x$  would give information about  $y$ .

- But if  $z$  is *observed*:




In this case  $x \perp y \mid z$ : knowing  $z$  “breaks” dependence between  $x$  and  $y$ .




## D-Separation Case 2: Common Parent

- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z_1$  and  $z_2$  are common observed parents:



## D-Separation Case 2: Common Parent


- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z_1$  and  $z_2$  are common observed parents:



We have  $x \perp y \mid z_1, z_2$ : knowing  $z_1$  and  $z_2$  breaks dependence between  $x$  and  $y$ .


## D-Separation Case 2: Common Parent

- Case 2:  $x$  and  $y$  are **siblings**.
  - If  $z_1$  and  $z_2$  are common observed parents:



We have  $x \perp y \mid z_1, z_2$ : knowing  $z_1$  and  $z_2$  breaks dependence between  $x$  and  $y$ .

- But if we only observe  $z_2$ :




Then we have  $x \not\perp y \mid z_2$ : dependence still “flows” through  $z_1$ .

## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z$ :


## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z$ :
  - If we observe  $z$  then we have:



## D-Separation Case 3: Common Child


- Case 3:  $x$  and  $y$  share a **child**  $z$ :
  - If we observe  $z$  then we have:



We have  $x \not\perp y \mid z$ : if we know  $z$ , then knowing  $x$  gives us information about  $y$ .


## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z$ :
  - If we observe  $z$  then we have:




We have  $x \not\perp y \mid z$ : if we know  $z$ , then knowing  $x$  gives us information about  $y$ .

- But if  $z$  is not observed:




## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z$ :
  - If we observe  $z$  then we have:



We have  $x \not\perp y \mid z$ : if we know  $z$ , then knowing  $x$  gives us information about  $y$ .

- But if  $z$  is not observed:




We have  $x \perp y$ : if you don't observe  $z$  then  $x$  and  $y$  are independent.

- Different from Case 1 and Case 2: **not observing the child blocks path.**




## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z_1$ :
  - If there exists an unobserved grandchild  $z_2$ :



## D-Separation Case 3: Common Child


- Case 3:  $x$  and  $y$  share a **child**  $z_1$ :
  - If there exists an unobserved grandchild  $z_2$ :



We have  $x \perp y$ : the path is still blocked by not knowing  $z_1$  or  $z_2$ .


## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z_1$ :
  - If there exists an unobserved grandchild  $z_2$ :




We have  $x \perp y$ : the path is still blocked by not knowing  $z_1$  or  $z_2$ .

- But if  $z_2$  is observed:




## D-Separation Case 3: Common Child

- Case 3:  $x$  and  $y$  share a **child**  $z_1$ :
  - If there exists an unobserved grandchild  $z_2$ :



We have  $x \perp y$ : the path is still blocked by not knowing  $z_1$  or  $z_2$ .

- But if  $z_2$  is observed:



We have  $x \not\perp y \mid z_2$ : grandchild creates dependence even with unobserved parent.


- Case 3 needs to consider **descendants** of child.

## D-Separation

- We say that  $A$  and  $B$  are **d-separated** if  
for *all paths*  $P$  from  $A$  to  $B$ , *at least one* of the following holds:

## D-Separation

- We say that  $A$  and  $B$  are **d-separated** if  
for *all paths*  $P$  from  $A$  to  $B$ , *at least one* of the following holds:
  - ①  $P$  includes a “chain” with an observed middle node:



## D-Separation

- We say that  $A$  and  $B$  are **d-separated** if for *all paths*  $P$  from  $A$  to  $B$ , *at least one* of the following holds:

- 1  $P$  includes a “chain” with an observed middle node:



- 2  $P$  includes a “fork” with an observed parent node:



## D-Separation

- We say that  $A$  and  $B$  are **d-separated** if for *all paths*  $P$  from  $A$  to  $B$ , *at least one* of the following holds:


- 1  $P$  includes a “chain” with an observed middle node:



- 2  $P$  includes a “fork” with an observed parent node:



- 3  $P$  includes a “v-structure” or “collider”:



where child  $C$  and all its descendants are unobserved.



# Summary

- **Decoding** is task of finding most probable  $x$ .
- **Message-passing** allow efficient calculations with Markov chains.

# Summary

- **Decoding** is task of finding most probable  $x$ .
- **Message-passing** allow efficient calculations with Markov chains.
- **DAG models** factorize joint distribution into product of conditionals.
  - Assume conditionals depend on small number “parents”.
  - Joint distribution of models we’ve discussed can be written as DAG models.

# Summary

- **Decoding** is task of finding most probable  $x$ .
- **Message-passing** allow efficient calculations with Markov chains.
- **DAG models** factorize joint distribution into product of conditionals.
  - Assume conditionals depend on small number “parents”.
  - Joint distribution of models we’ve discussed can be written as DAG models.
- **Conditional independence** of  $A$  and  $B$  given  $C$ :
  - Knowing  $B$  tells us nothing about  $A$  if we already know  $C$ .

## Summary

- **Decoding** is task of finding most probable  $x$ .
- **Message-passing** allow efficient calculations with Markov chains.
- **DAG models** factorize joint distribution into product of conditionals.
  - Assume conditionals depend on small number “parents”.
  - Joint distribution of models we’ve discussed can be written as DAG models.
- **Conditional independence** of  $A$  and  $B$  given  $C$ :
  - Knowing  $B$  tells us nothing about  $A$  if we already know  $C$ .
- **D-separation** allows us to test conditional independences based on graph.
- Next time: undirected graphical models and how we use graphical models.

## Bonus Slide: Conditional Samples from Gaussian/Discrete Markov Chain

Generating exact conditional samples from Gaussian/discrete Markov chains:

- 1 If we're only conditioning on first  $j$  states,  $x_{1:j}$ , just fix these values and start ancestral sampling from time  $(j + 1)$ .
- 2 If we have the marginals  $p(x_j)$ , we can get the “backwards” transition probabilities using Bayes rule,

$$p(x_j|x_{j+1}) = \frac{p(x_{j+1}|x_j)p(x_j)}{p_{j+1}},$$

which lets us run ancestral sampling in reverse: sample  $x_d$  from  $p(x_d)$ , then  $x_{d-1}$  from  $p(x_{d-1}|x_d)$ , and so on.

- 3 If we're only conditioning on last  $j$  states  $x_{d-j:d}$ , run CK equations to get marginals and then start ancestral sampling “backwards” starting from  $(d - j - 1)$  to sample the earlier states.

## Bonus Slide: Conditional Samples from Gaussian/Discrete Markov Chain

- ④ If we're conditioning on contiguous states in the middle,  $x_{j:j'}$ , run ancestral sampling forward starting from position  $(j' + 1)$  and backwards starting from position  $(j - 1)$ .
- ⑤ If you condition on non-contiguous positions  $j$  and  $j'$  with  $j < j'$ , need to do (i) forward sampling starting from  $(j' + 1)$ , (ii) backward sampling starting from  $(j - 1)$ , and (iii) CK equations on the sequence  $(j : j')$  to get marginals conditioned on value of  $j$  then backwards sampling back to  $j$  starting from  $(j' - 1)$ .

The above are all special cases of conditioning in an undirected graphical model (UGM), followed by applying the “forward-filter backward-sampling” algorithm on each of the resulting chain-structured UGMs.