

Random Magma knowledge

This is a compilation of some useful **Magma** tricks that I have learned through the years. Thank you to all the wonderful people who have shared their knowledge with me: [Eran Assaf](#), [Edgar Costa](#), [Sachi Hashimoto](#), [Avi Kulkarni](#), [Sam Schiavone](#), [Pim Spelier](#), [Drew Sutherland](#), and [John Voight](#).

- Useful links: [Documentation](#) and [general examples](#).
- You can write the first letter of a function and tab complete twice to get a list of possible functions.
- To kill a process, use `control + c`. To kill **Magma**, do this twice.
- To ignore `>`, use `SetIgnorePrompt(true);`. This is very helpful when you are copying code from the terminal.
- `$1` denotes the last printed result (you can also call `$2` and `$3`).
- The rational numbers are not a number field in **Magma**. You can instead call `RationalsAsNumberField();`. Careful: linear algebra is slower here.
- When you are debugging functions, you can `SetDebugOnError(true);`. This will give you access to the "inside" of your function, up to where **Magma** got stuck. You print things by `p whateverYouWant`. Use `q` to quit back to the **Magma** terminal. You can see all the functions that were used in your computation using `bt` (shows you the "frames"). Go to a specific frame by writing `f theNumberYouWant`. Warning: do not use `;`.
- In your home directory you can create a `file.Magmarc`, if does not exist, to have certain commands to run on start. To find the file, you can go to your home directory and press `Command + Shift + .` (period).
- Use `control + e` to get to the last character of a line in the terminal. Use `control + a` for the first one. Do `control + k` to delete the line. You can also find other combinations [here](#).
- Do `%p` to print all the Magma session.
- You can search only for signatures without inheritance:
`ListSignatures(ModFrmHilElt : Isa := false);`. Moreover, you can also just look for functions where your type is an argument or a return values (very useful when you try to find a function producing the type that another function needs...):
`ListSignatures(ModFrmHilElt : Search := "ReturnValues", Isa := false);`.
- **Magma** complains about types. Elements need to be coerced to have the type you want. For example, to coerce an integer or type `Rational` to type `Integer`: `Integers()!r`.

- The function `Discriminant(K)` returns the discriminant of the polynomial used to define, not the discriminant of K . Use `Discriminant(RingOfIntegers(K))` to get the discriminant of K .
- Use for verbose: `vprintf VerboseLevel : "whatever you want to print";`
- To iterate over a list, you can use `& + (operation)`. For example, to add all the prime numbers ≤ 20 , do:

```
&+[p : p in [1..20] | IsPrime(p)];
```

- To run a magma Jupyter kernel, go to [this GitHub repository](#), and then you can run `sage -n jupyter`.
- To print in a format that is readable by Magma: `Sprint(whateverYouWant, "Magma");`.
- To coerce a list into the same set: `[Integers() | 4/1, 5/1]`.

Do you have more random knowledge? Please email it to me and I will add it to this list!