
AI Agent Studio. 26A.
Agent Team to retrieve data from Bi-Publisher report.
Type: Supervisor.
SUPPLIER_BIP_AGENT
Tools(2)
Topics(0)
Link
Business Object
Credentials
Monitoring and Evaluation
Supplier is "Lee Supplies"
AA_TEAM_SUPP_SUP
Custom Agent Team
Have questions about building better AI agents?
Get expert guidance on designing, optimizing, and scaling high-performance AI agents.
SUPPLIER_BIP_AGENT
Tools(2)
BIP_Report_Tool
Supplier_Tool
Topics(0)
AA_TEAM_SUPP_SUP
I found supplier "Lee Supplies" (Supplier ID: 300000047414503). Below is the requested "po data" presented as an HTML table
PONUMBER
PONUMBER
PROMISEDDELIVERYDATE
ORDERED QUANTITY
RECEIVEDDELIVERYDATE
RECEIVED QUANTITY

AI Agent Studio. 26A.

Agent Team to retrieve data from Bi-Publisher report.

Type: Supervisor.

Introduction/Goal.

Release 26A is latest at the time of this writing.

Disclaimer 1: based partially on Oracle provided artifacts.

Planned steps:

1. The user will provide a supplier name.
2. we will use a REST to find the supplier id.
3. Then we will run BI-Report to get custom data, using the supplier id as a filter.
4. We will show the result of the report using HTML table with colored cells and headers.

Components (basic diagram).

Agent Team (type supervisor).

Agent

Tool 1. REST Business object.

Tool 2. REST. BI-Report.

Preparatory steps.

In Saas you will need a BI-Report in this folder (report provided):



With a Data Model query like this (adapt to your needs).

Disclaimer 2: it is not the goal of the exercise to get this query perfect, it is just for learning purposes.

```
SELECT
        a.po_header_id "POHeaderId"           ,
        b.po_line_id "POLineId"               ,
        c.PROMISED_DATE "PromisedDeliveryDate",
        b.QUANTITY "OrderedQuantity"          ,
        NEED_BY_DATE"ReceivedDeliveryDate" ,
               nvl(QUANTITY_RECEIVED,0) "ReceivedQuantity"
FROM
        po_headers_all        a,
               po_lines_all          b,
        PO_LINE_LOCATIONS_ALL c
WHERE
        a.vendor_id    = :p_vendor_id
AND     a.po_header_id = b.po_header_id
AND     b.po_line_id   = c.po_line_id
and rownum <= 10
order by a.creation_date desc
```

Tool 1.

Tool Name: BIP_Report_Tool.

Type: External REST Tool.

Overview.



Detail.



Authorization.

Require human approval

Enable if you want human approval before running the tool.

Authorization Functions

Authorization

Instance URL
https://dabpqy.ds-fa.oraclepdemos.com

Authentication
Basic

Description
demo

Authentication details

User Name
casey.brown

Password

Required

Function.

Require human approval

Enable if you want human approval before running the tool.

Authorization Functions

Add

Name	Operation Type
BIP_Function	POST

INTERESTING!

Edit Endpoint

Name
BIP_Function

Operation Type
HTTP POST

Resource Path
/xmlpserver/services/ExternalReportWSSService

Description
Supplier item report Information BIP tool

Body Template

```
<soap:Envelope
 xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
 xmlns:pub="http://xmlns.oracle.com/oxp/service/PublicReportService">
 <soap:Header/>
 <soap:Body>
  <pub:runReport>
   <pub:reportRequest>
    <pub:attributeFormat>csv</pub:attributeFormat>
    <pub:byPassCache>true</pub:byPassCache>
    <pub:parameterNameValues>
     <pub:item>
      <pub:name>P_VENDOR_ID</pub:name>
      <pub:values>
       <pub:item>{SupplierId}</pub:item>
      </pub:values>
```

We have learned we can run SOAP web services to run reports.

Body template (SOAP payload).

```
<soap:Envelope
  xmlns:soap="http://www.w3.org/2003/05/soap-envelope"
  xmlns:pub="http://xmlns.oracle.com/oxp/service/PublicReportService">
  <soap:Header/>
  <soap:Body>
    <pub:runReport>
      <pub:reportRequest>
        <pub:attributeFormat>csv</pub:attributeFormat>
        <pub:byPassCache>true</pub:byPassCache>
        <pub:parameterNameValues>
          <pub:item>
            <pub:name>P_VENDOR_ID</pub:name>
            <pub:values>
              <pub:item>{SupplierId}</pub:item>
            </pub:values>
          </pub:item>
        </pub:parameterNameValues>
        <pub:reportAbsolutePath>/Custom/BIP-
Report/Supplier_Data_Report.xdo</pub:reportAbsolutePath>
        <pub:sizeOfDataChunkDownload>-1</pub:sizeOfDataChunkDownload>
      </pub:reportRequest>
    </pub:runReport>
  </soap:Body>
</soap:Envelope>
```

Parameters.



Headers.



Tool 2.

Tool Name: Supplier_Tool.

Type: Business Object Tool

Overview.





Business Object linked: Supplier_BO

Edit businessobject - Supplier_BO

Have questions about building better AI agents?
Get expert guidance on designing, optimizing, and scaling high-performance AI agents.

Family: SCM	Product: Other
Name: Supplier_BO	Code: ORA_SCM_OTHER_SUPPLIERBO
Resource Type: Monolith resource	Resource Path: /fscmRestApi/resources/11.13.18.05/
Oracle Data Source Application	Description: Returns the SupplierId for the given Supplier

Scenario.

Edit scenario - Supplier_BO

Name: Get_SupplierId	Description: Returns the SupplierId
Operation Type: HTTP GET	Resource Path: /fscmRestApi/resources/11.13.18.05/suppliers?q=Supplier='{Supplier}'

Use native authentication Header

Parameter.

Parameters and Business Object Fields

Add Parameter | Add Field | Add Field from Specification

Name	Data Type	Description	Is Parameter
Supplier	string	Supplier	true

Custom Agent.

Name: SUPPLIER_BIP_AGENT

Steps to create.



Then include our 2 tools.



Add button.



Second tool.



Resulting in a new Agent.



Details in Agent.

Original setup	Our changes
Maximum Interactions 20 **Description** Agent for getting the Supplier details from the supplier's name. **Agent Persona and Role** Gets the supplier details **Prompt** You are a Procurement Assistant Agent. Your role is to retrieve POHeaderId and POLineId from the mentioned Tools. --- TOOLS AVAILABLE: 1. Supplier_Tool - Resolves the Supplier ID (supplierId) for a given supplier name. - Input: Supplier Name (provided by the user) - Output: supplierId 2. BIP_Report_Tool - This tool Fetches all POHeaderId, POLineId, PromisedDeliveryDate, OrderedQuantity, ReceivedDeliveryDate and ReceivedQuantity details for a given Supplier ID (supplierId) return by the Supplier_Tool. - Type: External REST Call - Input Parameter: P_VENDOR_ID = <supplierId> - Output: PO Header and PO Line details --- EXECUTION SEQUENCE: Step 1 — Resolve Supplier ID - Extract the supplier name from the user input. - Call Supplier_Tool with the supplier name. - Retrieve the supplierId from the response. - If no supplierId is returned, stop and inform the user: "No supplier found with the name '<supplier name>'. Please verify and try again." Step 2 — Fetch PO Details - Pass the supplierId retrieved in Step 1 to PO_BIP_REST as P_VENDOR_ID. - Retrieve all POHeaderId, POLineId, PromisedDeliveryDate, OrderedQuantity, ReceivedDeliveryDate and ReceivedQuantity details. --- PROCESSING BIP REPORT RESPONSE: - The tool returns a SOAP response containing <ns2:reportBytes> - The reportBytes value is base64-encoded CSV data - You MUST decode the base64 string and parse it as CSV - Display the decoded data as a structured table - Never show the raw base64 string to the user - Never ask the user if they want it decoded — always decode automatically - Remove the VENDOR_ID data from the output.	In prompt. In LLM. 

DECODING STEPS: 1. Extract the value inside <ns2:reportBytes>...</ns2:reportBytes> 2. Base64 decode it to get CSV text 3. Parse the CSV rows and columns 4. Display as a formatted table with proper headers --- RULES: Always follow this execution order: Supplier_Tool ↓ BIP_Report_Tool Never call PO_BIP_REST without a valid supplierId. Never call Schedule_Tool without POHeaderId and POLineId. Never guess or assume supplier IDs or PO data. Never generate sample or placeholder data. Always decode reportBytes automatically. Never display raw base64 values to the user.	

<u>Note.</u>

To be able to modify data in the agent we have to remove Agent from Agent Team.

When assigned to agent team, it seems to become read-only, as shown.



Agent Team.

Name: AA_TEAM_SUPP_SUP.

Steps to create.



Add button.



Result on the main Agent Teams page.



Testing.

Text for test:

Supplier is "Lee Supplies".

AA_TEAM_SUPP_SUP

I found supplier "Lee Supplies" (Supplier ID: 300000047414503). Below is the requested "po data" presented as an HTML table

POHEADERID	POLINEID	PROMISEDDELIVERYDATE	ORDERED QUANTITY	RECEIVEDDELIVERYDATE	RECEIVED QUANTITY
3000000308279841	3000000308279842	2025-07-12T00:00:00.000+00:00	200	2025-07-12T00:00:00.000+00:00	0
3000000305920820	3000000305920821	2025-05-31T00:00:00.000+00:00	1	2025-05-31T00:00:00.000+00:00	0
3000000299286857	3000000299286858	2025-03-02T00:00:00.000+00:00	2	2025-03-02T00:00:00.000+00:00	0
3000000296213606	3000000296213607	2025-01-10T00:00:00.000+00:00	10	2025-01-10T00:00:00.000+00:00	0
3000000296208759	3000000296208763	2025-01-17T00:00:00.000+00:00	1	2025-01-17T00:00:00.000+00:00	0
3000000296208759	3000000296208760	2025-01-17T00:00:00.000+00:00	1	2025-01-17T00:00:00.000+00:00	0
3000000296208759	3000000296208766	2025-01-15T00:00:00.000+00:00	1	2025-01-15T00:00:00.000+00:00	0
300000009200310 8	300000009200310 9	2014-09-19T00:00:00.000+00:00	1		0
3000000005260385	3000000005260385	2014-02-06T00:00:00.000	2		2

Above test shows data limited to 10 records in data model.

Now we remove the limit.

```
        po_lines_all        b,
    PO_LINE_LOCATIONS_ALL c
WHERE
    a.vendor_id    = :p_vendor_id
AND     a.po_header_id = b.po_header_id
AND     b.po_line_id   = c.po_line_id
and rownum <= 10
order by a.creation_date desc
```

Generate Explain Plan | OK | Cancel

-- and rownum <= 10

And test again, and we get.



It seems we will have to limit the number of records.

We will apply a 25 records limit and test.



Feel free to investigate how to overcome the issue, in REST API we have the offset feature, but in BI-reports we would need to think out of the box to solve.

Conclusion.

We can retrieve custom data from BI-Publisher, sending parameters and preparing parameters in a previous step with Business Object to get the id's needed for the report.

Technical

Code example	Comments
BIP-Report.catalog	BI-publisher Report+Data Model used in demo
v2_AATEAMSUPPSUP.json	Agent team available to import in 26B+ instances.