Session 5 · Activity: choose a rollout for IberBank

MLOps: Machine Learning Operations · Session 5 · Saturday 17 October 2026
Breakout activity. Read the case before your room opens.

Overview

When	Minutes 58–86 of the live session (brief · 15 min in breakout rooms · 10 min debrief)
Groups	Rooms of 4–5 students (your group-project team)
Output per room	One slide or one whiteboard (the rollout card), presented by a spokesperson in 2 minutes
Task	Choose how version 2 of a bank's card-fraud model reaches customers

The chat poll ("A model that passed all automated tests can be released to 100% of customers at once") is run during the session and continued as Theme A of Forum 3.

The case: IberBank card-fraud model, version 2 (facts only)

IberBank's card-fraud model (Session 3) has a new version. The engineering team says it is ready. The question is how it reaches customers.

1. **Version 1** has been in production since March: about 40 million transactions a month, answering in under 150 ms, across three channels (point of sale, e-commerce, ATM). It blocks about 0.4% of transactions; roughly one in three blocks turns out to be a false positive (a legitimate purchase).
2. **Version 2** passed validation last week. On the evaluation set it catches 9% more fraud at the same false-positive rate, and the fairness check by region passed. It uses two new "velocity" features from the streaming system (spend and count in the last hour).
3. **Constraint 1 · zero downtime.** Card payments run 24/7. A minute without scoring means every transaction in that minute is either blocked or waved through; both cost money and reputation.
4. **Constraint 2 · the regulator.** After the March incident (Session 3), the regulator requires proof on real traffic that version 2 is at least as safe as version 1 *before any customer is affected by it*.
5. **Constraint 3 · budget.** Infrastructure allows a second production copy of the model for at most four weeks.
6. **Constraint 4 · operations.** The fraud operations team checks by hand the transactions the model sends to its review queue: about 300 a day, its full capacity. Above that, reviews are skipped. Chargebacks (the ground truth for fraud) arrive up to 60 days after the transaction.

Your task: the rollout card

Question	Your answer
Plan. Which strategies, in which order, with what traffic slices and for how long?	
Why not the others? One line per strategy you rejected.	
A/B decision rule. Metric · threshold · how much traffic before deciding.	
Rollback trigger. Which number, watched by whom (or what), makes you stop, and what "stop" means.	
Who signs each step.	
Bonus. One automated test you would add to the CI pipeline for this model (code, data or model layer).	

Vocabulary you can use

- Strategies: basic · blue-green · shadow · canary · A/B test, and the scorecard (zero downtime, extra cost, customer risk, what you learn, rollback).
- The three ingredients of an A/B test: a metric · a threshold · enough traffic.
- The test pyramid: code tests · data tests · model tests.
- Personas: Product owner · ML engineer · IT / DevOps · Risk & Compliance · fraud operations team.