



Regular Grammars

Computation and Discrete Structures III

Juan Marcos Caicedo Mejía – jmcaicedo@icesi.edu.co

Department of Computing and Intelligent Systems
Barberi Faculty of Engineering, Design and Applied Sciences
ICESI University

Material adapted from Professor Oscar Bedoya

2026

1. Regular Grammars

1. Regular Grammars

Type	Languages	Machine Type	Grammar Rules
0	Recursively enumerable	Turing machine	Unrestricted
1	Context-sensitive	Linear bounded automaton	$\alpha \rightarrow \beta, \quad \alpha \leq \beta $
2	Context-free	Pushdown automaton	$A \rightarrow \gamma$
3	Regular	Finite automaton	$A \rightarrow aB$ $A \rightarrow a$

$$S \rightarrow aA \mid bB$$

$$A \rightarrow aA \mid a$$

$$B \rightarrow bB \mid b$$

- S , A and B are non-terminals, indicating they must be replaced according to the productions
- a and b are terminals belonging to an alphabet Σ

$$S \rightarrow aA \mid bB$$

$$A \rightarrow aA \mid a$$

$$B \rightarrow bB \mid b$$

Grammars generate strings

$$S \rightarrow aA \mid bB$$

$$A \rightarrow aA \mid a$$

$$B \rightarrow bB \mid b$$

Grammars generate strings

$$S \rightarrow aA \rightarrow aaA \rightarrow aaa$$

The string *aaa* is generated by the grammar

$$S \rightarrow aA \mid bB$$
$$A \rightarrow aA \mid a$$
$$B \rightarrow bB \mid b$$
$$S \rightarrow aA \rightarrow aa$$
$$S \rightarrow aA \rightarrow aaA \rightarrow aaaA \rightarrow aaaa$$
$$S \rightarrow bB \rightarrow bb$$

$$S \rightarrow aA \mid bB$$

$$A \rightarrow aA \mid a$$

$$B \rightarrow bB \mid b$$

Can the string ab be generated by the grammar?

$$S \rightarrow aAb \mid bBa$$

$$A \rightarrow aAb \mid \epsilon$$

$$B \rightarrow bBa \mid \epsilon$$

Indicate which of the following strings can be generated by the grammar:

- ab
- $aabb$
- $baaa$
- abb
- $bbba$

$$S \rightarrow abS \mid \epsilon$$

Indicate which of the following strings can be generated by the grammar:

- ϵ
- *abab*
- *aaab*
- *abb*

$$S \rightarrow aE$$

$$E \rightarrow A \mid B$$

$$A \rightarrow aA \mid b$$

$$B \rightarrow aB \mid b$$

The string *aaab* can be generated as:

$$S \rightarrow aE \rightarrow aA \rightarrow aaA \rightarrow aaaA \rightarrow aaab$$

The notation $S \xrightarrow{*} w$ indicates that string *w* **can be generated** from *S* in 0 or more steps

Consider the regular language $a(a^* \cup b^*)b$. One way to express the strings accepted by the language is through the productions

Consider the regular language $a(a^* \cup b^*)b$. One way to express the strings accepted by the language is through the productions

$$S \rightarrow aE$$

$$E \rightarrow A \mid B$$

$$A \rightarrow aA \mid b$$

$$B \rightarrow aB \mid b$$

A **regular grammar** is defined as a set of 4 elements, $G = (\Sigma, N, S, P)$ where:

- Σ is the alphabet
- N are the non-terminals
- S is the start symbol
- P is the collection of substitution rules or productions

$$S \rightarrow aE$$

$$E \rightarrow A \mid B$$

$$A \rightarrow aA \mid b$$

$$B \rightarrow aB \mid b$$

A **regular grammar** is defined as a set of 4 elements, $G = (\Sigma, N, S, P)$ where:

- Σ is the alphabet
- N are the non-terminals
- S is the start symbol
- P is the collection of substitution rules or productions of the form $A \rightarrow w$, where $A \in N$ and $w \in (\Sigma \cup N)^*$ that satisfies:
 1. w contains at most one non-terminal
 2. If w contains a non-terminal, it is the rightmost symbol in w

The following grammars are not regular:

$$S \rightarrow AB$$

$$A \rightarrow aA \mid a$$

$$B \rightarrow bB \mid b$$

$$S \rightarrow aAb$$

$$A \rightarrow cA \mid c$$

$$aSb \rightarrow aA$$

$$bAa \rightarrow b \mid c$$

Consider the following regular grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow bA$$

$$A \rightarrow aaA \mid b$$

Consider the following regular grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow bA$$

$$A \rightarrow aaA \mid b$$

bb, baab, baaaab, baaaaaab, ...

Consider the following regular grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow bA$$

$$A \rightarrow aaA \mid b$$

The language accepted by the grammar, $L(G)$, contains strings of the form $b(aa)^*b$

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S\}$
- S is the start symbol
- $P :$

$$S \rightarrow aS \mid b$$

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S\}$
- S is the start symbol
- $P :$

$$S \rightarrow aS \mid b$$

The language accepted by the grammar, $L(G)$, contains strings of the form a^*b

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, B\}$
- S is the start symbol
- $P :$

$$S \rightarrow aS \mid B$$

$$B \rightarrow bB \mid \epsilon$$

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, B\}$
- S is the start symbol
- $P :$

$$S \rightarrow aS \mid B$$

$$B \rightarrow bB \mid \epsilon$$

The language accepted by the grammar, $L(G)$, contains strings of the form a^*b^*

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow abS \mid A$$

$$A \rightarrow a \mid b$$

Indicate the regular expression associated with the following grammar:

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow abS \mid A$$

$$A \rightarrow a \mid b$$

The language accepted by the grammar, $L(G)$, contains strings of the form $(ab)^*(a \cup b)$

Design a regular grammar that recognizes $(ab)^+$

Design a regular grammar that recognizes $(ab)^+$

- $\Sigma = \{a, b\}$
- $N = \{S\}$
- S is the start symbol
- $P :$

$$S \rightarrow abS \mid ab$$

Design a regular grammar that recognizes the language given by $(a \cup b)a^*(a \cup b)$

Design a regular grammar that recognizes the language given by $(a \cup b)a^*(a \cup b)$

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow aA \mid bA$$

$$A \rightarrow aA \mid a \mid b$$

Design a regular grammar that recognizes the language given by $(a \cup b)^* a (a \cup b)^*$

Design a regular grammar that recognizes the language given by $(a \cup b)^* a (a \cup b)^*$

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow aS \mid bS \mid aA$$

$$A \rightarrow aA \mid bA \mid \epsilon$$

Design a regular grammar that recognizes the language given by $(ab)^+(a \cup b)^*$

Design a regular grammar that recognizes the language given by $(ab)^+(a \cup b)^*$

- $\Sigma = \{a, b\}$
- $N = \{S, A\}$
- S is the start symbol
- $P :$

$$S \rightarrow abS \mid abA$$

$$A \rightarrow aA \mid bA \mid \epsilon$$

Design a regular grammar that recognizes the language given by $a^*b^*c^*$

Design a regular grammar that recognizes the language given by $a^*b^*c^*$

- $\Sigma = \{a, b, c\}$
- $N = \{S, B, C\}$
- S is the start symbol
- $P :$


$$S \rightarrow aS \mid bB \mid cC \mid \epsilon$$

$$B \rightarrow bB \mid cC \mid \epsilon$$

$$C \rightarrow cC \mid \epsilon$$

Theorem

Given an automaton M , there exists a grammar G such that $L(M) = L(G)$



$S \rightarrow aS \mid bA$
 $A \rightarrow aS \mid bB$
 $B \rightarrow aB \mid bB \mid \epsilon$

Theorem


Given an automaton M , there exists a grammar G such that $L(M) = L(G)$

The productions are obtained by taking the automaton states as non-terminals and alphabet symbols as terminals

Theorem


Given an automaton M , there exists a grammar G such that $L(M) = L(G)$


The productions are obtained by taking the automaton states as non-terminals and alphabet symbols as terminals



Theorem

Given an automaton M , there exists a grammar G such that $L(M) = L(G)$





The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_0 \mid bq_1$$

$$q_1 \rightarrow aq_0 \mid bq_2$$

$$q_2 \rightarrow aq_2 \mid bq_2 \mid \varepsilon$$




$$S \rightarrow aS \mid bA$$


$$A \rightarrow aS \mid bB$$

$$B \rightarrow aB \mid bB \mid \varepsilon$$

Automaton that recognizes $(a \cup b)^*$




Automaton that recognizes $(a \cup b)^*$




The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_0 \mid bq_0 \mid \varepsilon \quad \Rightarrow \quad S \rightarrow aS \mid bS \mid \varepsilon$$

Automaton that recognizes $(a \cup b)^+$



Automaton that recognizes $(a \cup b)^+$



The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_1 \mid bq_1$$


$$q_1 \rightarrow aq_1 \mid bq_1 \mid \varepsilon$$




$$S \rightarrow aA \mid bA$$

$$A \rightarrow aA \mid bA \mid \varepsilon$$

Show the regular grammar for the following automaton that recognizes $(ab \cup ba)^*$



Show the regular grammar for the following automaton that recognizes $(ab \cup ba)^*$



The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_1 | bq_2 | \epsilon$$

$$q_1 \rightarrow bq_0 | aq_3$$

$$q_2 \rightarrow aq_0 | bq_3$$

$$q_3 \rightarrow aq_3 | bq_3$$




$$S \rightarrow aA | bB | \epsilon$$

$$A \rightarrow bS | aC$$

$$B \rightarrow aS | bC$$

$$C \rightarrow aC | bC$$

Show the regular grammar for the following automaton that recognizes $(ab \cup ba)^*$



The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_1 | bq_2 | \varepsilon$$

$$q_1 \rightarrow bq_0 | aq_3$$

$$q_2 \rightarrow aq_0 | bq_3$$

$$q_3 \rightarrow aq_3 | bq_3$$



$$S \rightarrow aA | bB | \varepsilon$$


$$A \rightarrow bS | aC$$

$$B \rightarrow aS | bC$$

$$C \rightarrow aC | bC$$

Evaluate the string aab

Show the regular grammar for the following automaton that recognizes $(ab \cup ba)^*$



The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_1 | bq_2 | \varepsilon$$

$$q_1 \rightarrow bq_0 | aq_3$$

$$q_2 \rightarrow aq_0 | bq_3$$

$$q_3 \rightarrow aq_3 | bq_3$$



$$S \rightarrow aA | bB | \varepsilon$$


$$A \rightarrow bS | aC$$

$$B \rightarrow aS | bC$$


$$C \rightarrow aC | bC$$

The string aab is not generated by the grammar

Show the regular grammar for the following automaton that recognizes a^+b^+



Show the regular grammar for the following automaton that recognizes a^+b^+



The automaton M induces the regular grammar:

$$q_0 \rightarrow aq_1 | bq_3$$

$$q_1 \rightarrow aq_1 | bq_2$$

$$q_2 \rightarrow bq_2 | \varepsilon | aq_3$$

$$q_3 \rightarrow aq_3 | bq_3$$



$$S \rightarrow aA | bC$$

$$A \rightarrow aA | bB$$

$$B \rightarrow bB | \varepsilon | aC$$

$$C \rightarrow aC | bC$$

Theorem

Given a regular grammar G , there exists an automaton M such that $L(M) = L(G)$

Theorem

Given a regular grammar G , there exists an automaton M such that $L(M) = L(G)$

The automaton construction uses the productions, considering non-terminals as states and terminals as transitions

Theorem

Given a regular grammar G , there exists an automaton M such that $L(M) = L(G)$

The automaton construction uses the productions, considering non-terminals as states and terminals as transitions

$$S \rightarrow aS \mid bA$$

$$A \rightarrow aB \mid bB \mid \epsilon$$

$$B \rightarrow aB \mid bB$$

Design the automaton for the following grammar:

$$S \rightarrow aS \mid bA$$

$$A \rightarrow aB \mid bB \mid \epsilon$$


$$B \rightarrow aB \mid bB$$

Design the automaton for the following grammar:

$$S \rightarrow aS \mid bA$$

$$A \rightarrow aB \mid bB \mid \epsilon$$

$$B \rightarrow aB \mid bB$$



Design the automaton for the following grammar:

$$S \rightarrow aB \mid bA \mid \epsilon$$

$$A \rightarrow abaS$$


$$B \rightarrow babS$$

Design the automaton for the following grammar:

$$S \rightarrow aB \mid bA \mid \epsilon$$

$$A \rightarrow abaS$$

$$B \rightarrow babS$$



Design the automaton for the following grammar:

$$S \rightarrow aA \mid \epsilon$$

$$A \rightarrow abA \mid baB \mid \epsilon$$

$$B \rightarrow aB \mid bA$$



Kozen, D. C. (2007)

Automata and computability

Springer Science & Business Media.