ALL SHORE INDUSTRIES, INC.

SPECIFICATION FOR
LIQUID CRYSTAL DISPLAY MODULE

MODEL #: ASI-A-24012B-/A

(1)	NUMBER OF DOTS	----------	240W X 128H DOTS
(2)	MODULE SIZE	----------	144.0W X 104.0H X 17.0 D (MAX) mm
(3)	EFFECTIVE AREA	----------	114.0W X 64.0H mm
(4)	ACTIVE AREA	----------	107.97W X 57.57H mm
(5)	DOT SIZE	----------	0.42W X 0.42H mm
(6)	DOT PITCH	----------	0.45W X 0.45H mm
(7)	LCD TYPE	----------	STN
(6)	DRIVING METHOD	----------	1 / 128 DUTY MULTIPLEX DRIVE
(7)	VIEWING DIRECTION	----------	6 O ' CLOCK
(8)	BACK - LIGHT	----------	LED COLOR: YELLOW-GREEN
(9)	CONTROLLER	----------	HD61830 or LC7981

All Shore Industries, Inc. One Edgewater Plaza, Staten Island, NY 10305

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

R E C O R D S O F R E V I S I O N

DOC . FIRST ISSUE
DEC.12,1994

D A T E	REVISED DRAWING NO.	S U M M A R Y

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

TABLE OF CONTENTS

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

1. GENERAL SPECIFICATIONS

1 . 1 GENERAL SPECIFICATIONS

PLEASE REFER TO :

CUSTOMER ACCEPTANCE STANDARD SPECIFICATIONS :

AS - 002A

1 . 2 APPLICATION NOTES FOR CONTROLLER / DRIVER :HD61830 OR LC7981

PLEASE REFER TO :

CUSTOMER ACCEPTANCE STANDARD SPECIFICATIONS :

AS-110

1 . 3 THIS INDIVIDUAL SPECIFICATIONS IS PRIOR TO GENERAL SPECIFICATIONS .

2 . MECHANICAL SPECIFICATIONS

(1)	NUMBER OF DOTS	----------	240W X 128H DOTS
(2)	MODULE SIZE	----------	144.0W X 104.0H X 17.0 D (MAX) mm
(3)	EFFECTIVE AREA	----------	114.0W X 64.0H mm
(4)	ACTIVE AREA	----------	107.97W X 57.57H mm
(5)	DOT SIZE	----------	0.42W X 0.42H mm
(6)	DOT PITCH	----------	0.45W X 0.45H mm
(7)	LCD TYPE	----------	STN
(6)	DRIVING METHOD	----------	1 / 128 DUTY MULTIPLEX DRIVE
(7)	VIEWING DIRECTION	----------	6 O ' CLOCK
(8)	BACK - LIGHT	----------	LED COLOR: YELLOW-GREEN
(9)	CONTROLLER	----------	HD61830 or LC7981

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

3 . ABSOLUTE MAXIMUM RATINGS

3 . 1 ELECTRICAL ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN .	MAX .	UNIT	COMMENT
POWER SUPPLY FOR LOGIC	VDD--VSS	0	7.0	V	
POWER SUPPLY FOR LCD DRIVE	VDD-VEE	0	35	V	
INPUT VOLTAGE	VI	VSS	VDD	V	
STATIC ELECTRICITY	————	—	100	V	NOTE (1)
LED POWER VOLTAGE	VLED	—	8	V	
LED FORWARD CURRENT	IF	—	2250	mA	

NOTE (1) : TEST METHOD AND CONDITIONS : AFTER CHARGING UP 200 PF CAPACITOR BY STATED VOLTAGE, THE CAPACITOR IS CONNECTED WITH INTERFACE PINS OF THE MODULE .

3 . 2 ENVIRONMENTAL ABSOLUTE MAXIMUM RATINGS .

I T E M		OPERATING		STORAGE		COMMENT
		MIN .	MAX .	MIN .	MAX .	
AMBIENT TEMPERATURE	N.T.	0°C	50°C	-20 °C	60 °C	NOTE (2), (3)
	W.T.	-20°C	70°C	-30 °C	80 °C	
HUMIDITY		--	85% RH	--	85% RH	WITHOUT CONDENSATION
VIBRATION		--	2.45 m /s^2 (0.25G)	--	1 1 . 76 m /s^2 (1.2G)	10~100 HZ XYZ DIRECTIONS 1 HR. EACH
SHOCK		--	2 9 . 4 m /s^2 (3G)	--	490.0 m /s^2 (50G)	XYZ DIRECTIONS
CORROSIVE GAS		NOT ACCEPTABLE		NOT ACCEPTABLE		

NOTE(2) : Ta AT –20 ° C (-30° FOR W.T.) : 48HR MAX.
60 ° C (80° FOR W.T.) : 168HR MAX.

NOTE (3) : BACKGROUND COLOR CHANGES SLIGHTLY DEPENDING ON AMBIENT TEMPERATURE THIS PHENOMENON IS REVERSIBLE.

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

4 . ELECTRICAL CHARACTERISTICS

Ta = 25°C VDD = 5.0 +\- 0.25 V

PARAMETER	SYMBOL		CONDITION	MIN .	TYP .	MAX .	UNIT
POWER SUPPLY VOLTAGE FOR LOGIC	VDD-VSS		———	4.75	5.0	5.25	V
POWER SUPPLY VOLTAGE FOR LCD DRIVE	VEE-VSS		———	-15.5	-16.0	-16.5	V
INPUT VOLTAGE NOTE (1)	VIH		H LEVEL	2.2	——	——	V
	VIL		L LEVEL	——	——	0.8	V
OUTPUT VOLTAGE NOTE (2)	VOH		H LEVEL	2.4	——	VCC	V
	VOL		L LEVEL	0	——	0.4	V
POWER SUPPLY CURRENT FOR LOGIC	IDD	N.T.	VDD-VSS = 5.0 V VDD-VO = 18.2 V	——	12. 0	——	mA
		W.T.	VDD-VSS = 5.0 V VDD-VO = 16.3 V				
POWER SUPPLY CURRENT FOR DRIVE	IEE	N.T.	VDD-VSS = 5.0 V VDD-VO = 18.2 V	——	5. 0	——	mA
		W.T.	VDD-VSS = 5.0 V VDD-VO = 16.3 V				
RECOMMENDED LCD DRIVING VOLTAGE NOTE (3)	VDD–VO ϕ = 10° θ* = 0°	N.T.	Ta = 0 °C	——	19.0	——	V
			Ta = 25 °C	——	18.2	——	
			Ta = 50 °C	——	15.9	——	
		W.T.	Ta = -20 °C	——	19.5	——	
			Ta = 25 °C	——	16.3	——	
			Ta = 70 °C	——	14.7	——	
CLOCK OSCILLATION FREQUENCY	FOSC		———	——	2	——	MHZ
LED FORWARD VOLTAGE	VF		IF = 900mA	——	4.2	4.6	V
LED FORWARD CURRENT	IF		———	——	900	——	mA
LED REVERSE CURRENT	IR		VR = 8V	——	——	220	λA

θ = 180° WHEN VIEWING DIRECTION IS 12 O'CLOCK

NOTE (1) : APPLIED TO TERMINALS E, CS, R/W, RS, DB0~DB7, RES

NOTE (2) : APPLIED TO TERMINALS DB0~DB7

NOTE (3) : RECOMMENDED LCD DRIVING VOLTAGE: MAY FLUCTUATE ABOUT +/- 1.0v BY EACH MODULE.

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

5. INTERFACE TIMING CHARACTERISTICS

ITEM		SYMBOL	MIN	TYP	MAX	MAX
ENABLE CYCLE TIME		tCYC	1.0	——	——	uS
ENABLE PULSE WIDTH	H LEVEL	tWEH	0.45	——	——	uS
	L LEVEL	tWEL	0.45	——	——	uS
ENABLE RISE TIME		tEr	——	——	25	nS
ENABLE FALL TIME		tEf	——	——	25	nS
SETUP TIME		tAS	140	——	——	nS
DATA SETUP TIME		tDSW	225	——	——	nS
DATA DELAY TIME		tDDR	——	——	225	nS
DATA HOLD TIME		tDHW	10	——	——	nS
ADDRESS HOLD TIME		tAH	10	——	——	nS
DATA HOLD TIME		tDH	20	——	——	nS



ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

6 . OPTICAL CHARACTERISTICS .

Ta = 25°C VDD = 5.0 V VDD-VO=**

I T E M		SYMBOL	CONDITION		MIN .	TYP .	MAX .	UNIT	NOTE
VIEWING AREA	STN	$\phi 2 - \phi 1$	$K \geq 1.4$		40	———	———	Deg .	1
	FSTN				50	———	———	Deg.	1
CONTRAST RATIO	STN	K	$\phi = 10°$ $\theta^* = 0°$		———	5	———	———	1
	FSTN				5	———	———	———	1
RESPONSE TIME	N.T.	Tr (rise)	$\phi = 10°$ $\eta^* = 0°$	Ta=25°C	———	200	———	ms	1
		Tf (fall)		Ta=25°C	———	250	———		
	W.T.	Tr (rise)	$\phi = 10°$ $\eta^* = 0°$	Ta=-20°C	———	2150	———		
				Ta=25°C	———	190	———		
				Ta=70°C	———	85	———		
		Tf (fall)		Ta=-20°C	———	10700	———		
				Ta=25°C	———	330	———		
				Ta=70°C	———	50	———		
THE BRIGHTNESS OF BACKLIGHTING SOURCE		L	IF = 900 mA		———	30	———	cd/m^2	2
					———	180	———		3
PEAK EMISSION WAVELENGTH		λP	IF = 220 mA		———	570	———	nm	1

*θ = 180° WHEN VIEWING DIRECTION IS 12 O'CLOCK

** N.T. = 18.2V
W.T. = 16.3V

NOTE (1) SEE CUSTOMER ACCEPTANCE STANDARD SPECIFICATION FOR DEFINITION OF..
OPTICAL CHARACTERISTICS
AS-002A

NOTE (2) POLARIZER MODE: TRANSFLECTIVE

NOTE (3) POLARIZER MODE: TRANSMISSIVE

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

7 . OUTLINE DIMENSION



ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

8. BLOCK DIAGRAM



ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

9 . DETAIL DRAWING OF DOT MATRIX



10 . INTERFACE SIGNALS

PIN NO.	SYMBOL	LEVEL	FUNCTION
1	VSS	_____	GROUND
2	VDD	_____	POWER SUPPLY FOR LOGIC CIRCUIT
3	VO	_____	OPERATING VOLTAGE FOR LCD DRIVING
4	RS	H/L	H : INSTRUCTION REGISTER L : DATA REGISTER
5	R/W	H/L	H : DATA INPUT (LCD MODULE →MPU) L : DATA WRITE (LCD MODULE ←MPU)
6	E	H,H→L	ENABLE SIGNAL
7 – 14	DBO - DB7	H/L	DATA BUS LINE
15	CS	H	CHIP SELECTION
16	RST	L	RESET
17	VEE	_____	POWER SUPPLY FOR LCD DRIVING
18-20	N.C	_____	_____
21	A	_____	POWER SUPPLY FOR LED BACKLIGHT (A)
22	K	_____	POWER SUPPLY FOR LED BACKLIGHT (K)

ALL SHORE INDUSTRIES

MODEL NO : ASI-A-24012B-/A

11 . POWER SUPPLY

11 . 1 POWER SUPPLY FOR LCM



VDD-V0 : LCD DRIVING VOLTAGE
VR : 20K Ω

11 . 2 POWER SUPPLY FOR LED BACKLIGHT



RECOMMENDED RESISTOR RL = 1 Ω,1WATT(CONTROLLER BY USER)

11 . 3 TIMING OF POWER SUPPLY AND INTERFACE SIGNAL