

Final RTR-01 Config Script

```
enable
configure terminal

hostname RTR-01

service password-encryption
username admin privilege 15 secret <PASSWORD REDACTED>
crypto key generate rsa modulus 2048
ip ssh version 2
ip ssh time-out 60
ip ssh authentication-retries 3

interface FastEthernet0/0
description ISP-Facing
ip address <ISP-assigned-IP> <ISP-assigned-mask>
ip nat outside
ip access-group ACL_WAN_IN in
no shutdown

interface FastEthernet0/1
description Inside-Facing
ip address 203.0.113.2 255.255.255.252
ip nat inside
no shutdown

ip route 0.0.0.0 0.0.0.0 <ISP-gateway-IP>
ip route 10.50.10.0 255.255.255.0 203.0.113.1
ip route 10.50.20.0 255.255.255.0 203.0.113.1
ip route 10.50.30.0 255.255.255.0 203.0.113.1
ip route 10.50.40.0 255.255.255.192 203.0.113.1
ip route 10.50.50.0 255.255.255.192 203.0.113.1

ip route 203.0.113.10 255.255.255.255 203.0.113.1
ip route 203.0.113.20 255.255.255.255 203.0.113.1
```

```
ip access-list standard NAT_TRAFFIC
```

```
permit 10.50.10.0 0.0.0.255
```

```
permit 10.50.20.0 0.0.0.255
```

```
permit 10.50.30.0 0.0.0.255
```

```
permit 10.50.40.0 0.0.0.63
```

```
permit 10.50.50.0 0.0.0.63
```

```
ip nat inside source list NAT_TRAFFIC interface GigabitEthernet0/0/0 overload
```

```
ip nat inside source static 10.50.40.10 203.0.113.20
```

```
ip access-list extended ACL_WAN_IN
```

```
permit tcp any host 203.0.113.20 eq 443
```

```
permit icmp any any echo-reply
```

```
permit udp any any eq 443
```

```
deny ip any any log
```

```
banner motd ^
```

```
AUTHORIZED ACCESS ONLY. All activity is monitored and logged.
```

```
Unauthorized access is prohibited and will be prosecuted.
```

```
^
```

```
line con 0
```

```
login local
```

```
exec-timeout 10 0
```

```
line vty 0 4
```

```
login local
```

```
transport input ssh
```

```
exec-timeout 10 0
```

```
line vty 5 15
```

```
login local
```

```
transport input ssh
```

```
exec-timeout 10 0
```

```
write memory
```