

Final SW-IT Config Script

enable

configure terminal

hostname SW-IT

service password-encryption

username admin secret <PASSWORD REDACTED>

interface FastEthernet0/1

description Domain-Controller

switchport mode access

switchport access vlan 20

spanning-tree portfast

spanning-tree bpduguard enable

switchport nonegotiate

switchport port-security

switchport port-security maximum 1

switchport port-security violation shutdown

switchport port-security mac-address sticky

no shutdown

interface range FastEthernet0/2-7

description IT-Devices

switchport mode access

switchport access vlan 20

spanning-tree portfast

spanning-tree bpduguard enable

switchport nonegotiate

switchport port-security

switchport port-security maximum 1

switchport port-security violation shutdown

switchport port-security mac-address sticky

no shutdown

```
interface range FastEthernet0/8-23
description UNUSED-PARKED
switchport mode access
switchport access vlan 999
shutdown
```

```
interface range GigabitEthernet0/1-2
description UNUSED-PARKED
switchport mode access
switchport access vlan 999
shutdown
```

```
interface FastEthernet0/24
description Uplink-to-Core
switchport mode trunk
switchport trunk allowed vlan 20
switchport nonegotiate
no shutdown
```

```
interface Vlan1
no ip address
shutdown
```

```
interface Vlan20
description IT
ip address 10.50.10.2 255.255.255.0
no shutdown
```

```
interface Vlan999
description UNUSED-PARKED
no ip address
shutdown
```

```
ip default-gateway 10.50.20.1
```

```
banner motd ^
AUTHORIZED ACCESS ONLY. All activity is monitored and logged.
```

Unauthorized access is prohibited and will be prosecuted.

^

```
line vty 0 4
```

```
login local
```

```
transport input ssh
```

```
exec-timeout 10 0
```

```
line vty 5 15
```

```
login local
```

```
transport input ssh
```

```
exec-timeout 10 0
```

```
write memory
```