

Final SW-OT Config Script

enable

configure terminal

hostname SW-OT

service password-encryption

username admin secret <PASSWORD REDACTED>

interface range FastEthernet0/1-6

description OT-Devices

switchport mode access

switchport access vlan 10

spanning-tree portfast

spanning-tree bpduguard enable

switchport nonegotiate

switchport port-security

switchport port-security maximum 1

switchport port-security violation shutdown

switchport port-security mac-address sticky

no shutdown

interface range FastEthernet0/7-23

description UNUSED-PARKED

switchport mode access

switchport access vlan 999

shutdown

interface range GigabitEthernet0/1-2

description UNUSED-PARKED

switchport mode access

switchport access vlan 999

shutdown

interface FastEthernet0/24

description Uplink-to-Core

```
switchport mode trunk
switchport trunk allowed vlan 10
switchport nonegotiate
no shutdown
```

```
interface Vlan1
no ip address
shutdown
```

```
interface Vlan10
description OT
ip address 10.50.10.2 255.255.255.0
no shutdown
```

```
interface Vlan999
description UNUSED-PARKED
no ip address
shutdown
```

```
ip default-gateway 10.50.10.1
```

```
banner motd ^
AUTHORIZED ACCESS ONLY. All activity is monitored and logged.
Unauthorized access is prohibited and will be prosecuted.
^
```

```
line vty 0 4
login local
transport input ssh
exec-timeout 10 0
line vty 5 15
login local
transport input ssh
exec-timeout 10 0
```

```
write memory
```