

UU Motor Technology Co., Limited

www.uumotor.com

编号: KK2107190001

型号: KK16

rated voltage : 48.0(V) rated current : 13.0(A) rated power: 500.0 (W)

测试员: Administrator

特征说明: No Feature!

测试日期: 2021年07月19日

索引	time (s)	torque(N.m)	speed(r/min)	Pout (W)	Voltage(V)	current (A)	Pin (W)	eff (%)
Torque : Max	100.9	80.34	65	546.87	47.38	28.628	1356.44	40.3
Speed : Max	0.0	0.59	249	15.38	48.18	1.295	62.42	24.6
output power : Max	66.3	53.85	169	953.05	47.40	28.640	1357.54	70.2
Voltage : Max	0.0	0.59	249	15.38	48.18	1.295	62.42	24.6
Current : Max	68.4	55.48	161	935.42	47.39	28.898	1369.52	68.3
input power : Max	68.4	55.48	161	935.42	47.39	28.898	1369.52	68.3
efficiency : Max	22.7	14.00	225	329.88	47.97	8.164	391.65	84.2
1	0.0	0.59	249	15.38	48.18	1.295	62.42	24.6
2	1.6	0.76	249	19.82	48.17	1.379	66.44	29.8
3	2.5	0.93	249	24.25	48.17	1.462	70.42	34.4
4	3.5	1.14	248	29.61	48.16	1.579	76.06	38.9
5	4.6	1.47	248	38.18	48.16	1.724	83.03	46.0
6	5.6	1.81	247	46.82	48.15	1.893	91.18	51.3
7	6.5	2.20	246	56.68	48.15	2.088	100.54	56.4
8	7.5	2.64	245	67.73	48.14	2.313	111.35	60.8
9	8.5	3.12	244	79.72	48.13	2.553	122.91	64.9
10	9.6	3.62	243	92.12	48.12	2.823	135.87	67.8
11	10.6	4.20	242	106.44	48.11	3.112	149.74	71.1
12	11.6	4.84	241	122.15	48.10	3.436	165.28	73.9
13	12.7	5.55	240	139.49	48.09	3.868	186.02	75.0
14	13.7	6.26	238	156.02	48.08	4.246	204.15	76.4
15	14.8	7.05	237	174.98	48.07	4.653	223.68	78.2
16	15.8	7.85	235	193.19	48.05	5.080	244.14	79.1
17	16.7	8.73	234	213.93	48.04	5.512	264.82	80.8
18	17.7	9.55	232	232.02	48.03	5.942	285.41	81.3
19	18.8	10.39	231	251.34	48.02	6.360	305.43	82.3
20	19.8	11.20	229	268.59	48.01	6.770	325.06	82.6
21	20.7	12.04	228	287.48	47.99	7.197	345.43	83.2
22	21.7	13.03	226	308.39	47.98	7.670	368.06	83.8
23	22.7	14.00	225	329.88	47.97	8.164	391.65	84.2
24	23.8	14.96	223	349.36	47.95	8.658	415.19	84.1
25	24.8	15.86	221	367.06	47.94	9.124	437.45	83.9
26	25.8	16.80	220	387.06	47.93	9.588	459.54	84.2
27	26.9	17.67	219	405.25	47.91	10.110	484.42	83.7
28	27.9	18.53	217	421.09	47.90	10.557	505.70	83.3
29	29.0	19.51	215	439.28	47.88	11.033	528.30	83.1
30	30.0	20.54	214	460.32	47.87	11.512	551.15	83.5
31	30.9	21.44	213	478.24	47.86	11.990	573.86	83.3
32	31.9	22.35	211	493.86	47.84	12.432	594.88	83.0
33	32.9	23.29	210	512.19	47.83	12.914	617.73	82.9
34	34.0	24.31	208	529.53	47.82	13.401	640.84	82.6
35	34.9	25.25	207	547.36	47.80	13.894	664.23	82.4
36	35.9	26.14	206	563.92	47.79	14.325	684.63	82.4
37	36.9	27.09	204	578.74	47.78	14.800	707.20	81.8
38	38.0	28.01	203	595.46	47.76	15.247	728.31	81.8
39	39.0	28.89	202	611.14	47.75	15.690	749.25	81.6
40	40.0	29.75	201	626.22	47.74	16.140	770.60	81.3

UU Motor Technology Co., Limited

www.uumotor.com

编号: KK2107190001

型号: KK16

rated voltage: 48.0(V) rated current: 13.0(A) rated power: 500.0 (W)

测试员: Administrator

特征说明: No Feature!

测试日期: 2021年07月19日

索引	time (s)	Torque (N.m)	speed (r/min)	Pout (W)	Voltage (V)	Current (A)	Pin (W)	eff (%)
41	41.1	30.56	199	636.87	47.73	16.645	794.49	80.2
42	42.1	31.45	198	652.12	47.71	17.077	814.89	80.0
43	43.1	32.47	197	669.87	47.70	17.548	837.12	80.0
44	44.2	33.38	195	681.65	47.69	18.024	859.63	79.3
45	45.1	34.31	195	700.64	47.68	18.504	882.33	79.4
46	46.1	35.24	193	712.25	47.66	18.944	902.99	78.9
47	47.1	36.12	192	726.26	47.65	19.396	924.29	78.6
48	48.2	36.99	191	739.88	47.64	19.851	945.78	78.2
49	49.2	37.96	190	755.30	47.63	20.313	967.53	78.1
50	50.1	38.84	189	768.75	47.61	20.785	989.71	77.7
51	51.1	39.76	188	782.79	47.60	21.232	1010.78	77.4
52	52.2	40.68	186	792.38	47.59	21.699	1032.65	76.7
53	53.2	41.81	185	810.02	47.57	22.239	1058.00	76.6
54	54.2	42.90	184	826.64	47.56	22.821	1085.37	76.2
55	55.3	43.77	182	834.24	47.54	23.393	1112.20	75.0
56	56.3	44.77	181	848.61	47.52	23.888	1135.35	74.7
57	57.3	45.72	180	861.83	47.51	24.397	1159.20	74.3
58	58.4	46.66	179	874.66	47.50	24.882	1181.97	74.0
59	59.3	47.56	178	886.55	47.49	25.369	1204.85	73.6
60	60.3	48.49	177	898.81	47.47	25.841	1226.84	73.3
61	61.3	49.33	176	909.21	47.46	26.323	1249.34	72.8
62	62.4	50.17	175	919.44	47.45	26.746	1269.11	72.4
63	63.4	51.10	173	925.78	47.43	27.232	1291.77	71.7
64	64.3	52.01	172	936.82	47.42	27.701	1313.69	71.3
65	65.3	52.90	171	947.31	47.41	28.219	1337.87	70.8
66	66.3	53.85	169	953.05	47.40	28.640	1357.54	70.2
67	67.4	54.69	164	939.28	47.39	28.821	1365.96	68.8
68	68.4	55.48	161	935.42	47.39	28.898	1369.52	68.3
69	69.4	56.28	156	919.43	47.39	28.767	1363.50	67.4
70	70.5	57.16	152	909.87	47.40	28.606	1355.95	67.1
71	71.5	58.08	148	900.18	47.40	28.597	1355.52	66.4
72	72.6	58.96	144	889.12	47.40	28.606	1355.91	65.6
73	73.5	59.82	141	883.30	47.39	28.617	1356.35	65.1
74	74.5	60.69	137	870.72	47.39	28.608	1355.99	64.2
75	75.5	61.57	133	857.56	47.39	28.620	1356.55	63.2
76	76.5	62.47	129	843.92	47.39	28.637	1357.25	62.2
77	77.6	63.31	126	835.38	47.39	28.627	1356.69	61.6
78	78.5	64.20	122	820.23	47.39	28.655	1357.98	60.4
79	79.5	65.05	119	810.66	47.39	28.655	1357.99	59.7
80	80.5	65.94	116	801.03	47.39	28.661	1358.25	59.0
81	81.6	66.72	113	789.54	47.39	28.649	1357.70	58.2
82	82.6	67.58	110	778.49	47.39	28.659	1358.15	57.3
83	83.6	68.46	107	767.12	47.39	28.659	1358.17	56.5
84	84.7	69.42	104	756.07	47.39	28.645	1357.51	55.7
85	85.7	70.27	101	743.25	47.39	28.637	1357.10	54.8
86	86.8	71.15	97	722.75	47.39	28.661	1358.26	53.2
87	87.8	72.06	94	709.36	47.39	28.652	1357.84	52.2

UU Motor Technology Co., Limited

www.uumotor.com

编号: KK2107190001

型号: KK16 rated voltage: 48.0(V) rated current: 13.0(A) rated power: 500.0 (W) 测试员: Administrator
特征说明: No Feature! 测试日期: 2021年07月19日

索引	time (s)	Torque (N.m)	speed(r/min)	Pout (W)	Voltage (v)	Current (A)	Pin (W)	eff (%)
88	88.7	72.52	92	698.70	47.39	28.641	1357.33	51.5
89	89.7	72.93	91	695.01	47.39	28.650	1357.73	51.2
90	90.7	73.39	89	684.02	47.39	28.664	1358.42	50.4
91	91.8	74.02	87	674.39	47.39	28.636	1357.05	49.7
92	92.7	74.64	85	664.40	47.39	28.649	1357.67	48.9
93	93.7	75.52	82	648.51	47.39	28.641	1357.29	47.8
94	94.7	75.81	80	635.12	47.38	28.663	1358.28	46.8
95	95.8	76.75	78	626.92	47.39	28.658	1358.09	46.2
96	96.8	77.36	76	615.70	47.38	28.654	1357.74	45.3
97	97.8	78.05	73	596.68	47.38	28.664	1358.29	43.9
98	98.9	78.77	70	577.43	47.38	28.623	1356.30	42.6
99	99.9	79.65	68	567.20	47.38	28.627	1356.48	41.8
100	100.9	80.34	65	546.87	47.38	28.628	1356.44	40.3