









FREIGHT HANDLING WITH OUTSTANDING RELIABILITY

The CHAMP 70, TREPEL's 7 ton cargo high loader range, combines highest availability with extremely low operation and maintenance costs, making this versatile Pallet and Container high loader a real CHAMP. Fast lifting speed as well as accurate freight transfer under all climatic conditions are true operational advantages. The design of the CHAMP 70 offers maximum safety for operating personnel, aircraft and loader. These performances bring freight handling to higher level.

Performance	CHAMP 70S	CHAMP 70W	CHAMP 70U
Dimensions LxWxH	9.20 x 3.60 x 3.10 m	9.20 x 4.30 x 3.10 m	9.20 x 4.30 x 3.20 m
Capacity	7.000 kg	7.000 kg	7.000 kg
Lifting height front platform	1.800 to 3.700 mm	1.800 to 3.700 mm	1.900 to 5.600 mm
Lifting height main platform	485 to 3.700 mm	485 to 3.700 mm	485 to 3.700 mm
Loading width (between guide rails)	2.520 mm	3.300 mm	3.300 mm
Driving speed	15 km/h	15 km/h	15 km/h
Gradability	5 %	5 %	5 %
Turning radius	8.500 mm	8.500 mm	8.500 mm

Design

Engine Deutz 4-cylinder diesel type TD 2011 (COM 3, EPA-TIER 3)

Transmission / axles Open circuit hydrostatic drive system on front axle

Steering Hydraulic power steering

Braking system Dual-circuit hydraulic multiple disc brake,

additional spring-loaded emergency parking brake

Stabilisers 6 hydraulically operated stabilisers

Conveying system Zinc-plated steel rollers for longitudinal transfer,

transversal drive units on front platform,

hydraulically adjustable guide rails on front platform

Hydraulic system Central hydraulic valve block, valves fitted with control light

Electric system 24 V, relay controlled

Options

Side loading and rotation on rear of main platform (standard on 70W and 70U), electrically powered hydraulic emergency system to lower platforms and lift stabilisers, dynamic brake system etc.

Please consult the technical specification for further information.



TREPEL AIRPORT EQUIPMENT GMBH

Hagenauer Straße 42 D-65203 Wiesbaden / Germany http://www.trepel.com phone: +49(0)611-880 88-0 fax: +49(0)611-880 88-11 e-mail: airport@trepel.com





